

---

# **flopy Documentation**

***Release 3.3.5***

**Mark Bakker, Vincent Post, Joseph D. Hughes, Christian D. Lange**

**Mar 09, 2022**



# CONTENTS

<b>1</b>	<b>What is FloPy</b>	<b>3</b>
<b>2</b>	<b>FloPy Installation</b>	<b>5</b>
2.1	conda Installation . . . . .	5
2.2	pip Installation . . . . .	5
<b>3</b>	<b>FloPy Resources</b>	<b>7</b>
<b>4</b>	<b>FloPy Development Team</b>	<b>9</b>
<b>5</b>	<b>How to Cite</b>	<b>11</b>
<b>6</b>	<b>Tutorial</b>	<b>13</b>
6.1	Tutorials . . . . .	13
6.2	Jupyter Notebooks . . . . .	108
<b>7</b>	<b>Code Description</b>	<b>109</b>
7.1	Flopy Code . . . . .	109
<b>8</b>	<b>Indices and tables</b>	<b>719</b>
	<b>Python Module Index</b>	<b>721</b>
	<b>Index</b>	<b>725</b>



## **Documentation for version 3.3.5**

Return to the Github [FloPy](#) website where the code resides.

Contents:



## WHAT IS FLOPY

The FloPy package consists of a set of Python scripts to run MODFLOW, MT3D, SEAWAT and other MODFLOW-related groundwater programs. FloPy enables you to run all these programs with Python scripts. The FloPy project started in 2009 and has grown to a fairly complete set of scripts with a growing user base. FloPy3 was released in December 2014 with a few great enhancements that make FloPy3 backwards incompatible. The first significant change is that FloPy3 uses zero-based indexing everywhere, which means that all layers, rows, columns, and stress periods start numbering at zero. This change was made for consistency as all array-indexing was already zero-based (as are all arrays in Python). This may take a little getting-used-to, but hopefully will avoid confusion in the future. A second significant enhancement concerns the ability to specify time-varying boundary conditions that are specified with a sequence of layer-row-column-values, like the WEL and GHB packages. A variety of flexible and readable ways have been implemented to specify these boundary conditions.

Recently, FloPy has been further enhanced to include full support for MODFLOW 6. The majority of recent development has focused on FloPy functionality for MODFLOW 6, helper functions to use GIS shapefiles and raster files to create MODFLOW datasets, and common plotting and export functionality.

FloPy is an open-source project and any assistance is welcomed. Please email the development team if you want to contribute.

Return to the Github [FloPy](#) website.





## FLOPY INSTALLATION

FloPy can be installed using conda (from the conda-forge channel) or pip.

### 2.1 conda Installation

```
conda install -c conda-forge flopy
```

### 2.2 pip Installation

To install FloPy type:

```
pip install flopy
```

To install the bleeding edge version of FloPy from the git repository type:

```
pip install git+https://github.com/modflowpy/flopy.git
```



## FLOPY RESOURCES

Version history

Supported packages

Model checking capabilities



## FLOPY DEVELOPMENT TEAM

FloPy is developed by a team of MODFLOW users that have switched over to using Python for model development and post-processing. Members of the team currently include:

- Mark Bakker
- Vincent Post
- Joseph D. Hughes
- Christian D. Langevin
- Jeremy T. White
- Andrew T. Leaf
- Scott R. Paulinski
- Jason C. Bellino
- Eric D. Morway
- Michael W. Toews
- Joshua D. Larsen
- Michael N. Fienen
- Jon Jeffrey Starn
- David Brakenhoff
- and others



## HOW TO CITE

- Groundwater Paper
- Software Citation





## TUTORIAL

Contents:

### 6.1 Tutorials

#### 6.1.1 MODFLOW 6 Tutorials

Contents:

##### MODFLOW 6 Tutorial 1: Unconfined Steady-State Flow Model

This tutorial demonstrates use of FloPy to develop a simple MODFLOW 6 model.

##### Getting Started

```
[1]: import os
```

```
[2]: import matplotlib.pyplot as plt  
import numpy as np
```

```
[3]: import flopy
```

We are creating a square model with a specified head equal to  $h1$  along the edge of the model in layer 1. A well is located in the center of the upper-left quadrant in layer 10. First, set the name of the model and the parameters of the model: the number of layers  $N_{lay}$ , the number of rows and columns  $N$ , lengths of the sides of the model  $L$ , aquifer thickness  $H$ , hydraulic conductivity  $k$ , and the well pumping rate  $q$ .

```
[4]: name = "tutorial01_mf6"  
h1 = 100  
Nlay = 10  
N = 101  
L = 400.0  
H = 50.0  
k = 1.0  
q = -1000.0
```

## Create the FloPy Model Objects

One big difference between MODFLOW 6 and previous MODFLOW versions is that MODFLOW 6 is based on the concept of a simulation. A simulation consists of the following:

- Temporal discretization (TDIS)
- One or more models
- Zero or more exchanges (instructions for how models are coupled)
- Solutions

For this simple example, the simulation consists of the temporal discretization (TDIS) package, a groundwater flow (GWF) model, and an iterative model solution (IMS), which controls how the GWF model is solved.

## Create the FloPy simulation object

```
[5]: sim = flopy.mf6.MFSimulation(  
    sim_name=name, exe_name="mf6", version="mf6", sim_ws="."  
)
```

## Create the FloPy TDIS object

```
[6]: tdis = flopy.mf6.ModflowTdis(  
    sim, pname="tdis", time_units="DAYS", nper=1, perioddata=[(1.0, 1, 1.0)]  
)
```

## Create the FloPy IMS Package object

```
[7]: ims = flopy.mf6.ModflowIms(  
    sim,  
    pname="ims",  
    complexity="SIMPLE",  
    linear_acceleration="BICGSTAB",  
)
```

Create the FloPy groundwater flow (gwf) model object

```
[8]: model_name_file = f"{name}.nam"  
gwf = flopy.mf6.ModflowGwf(  
    sim,  
    modelname=name,  
    model_name_file=model_name_file,  
    save_flows=True,  
    newtonoptions="NEWTON UNDER_RELAXATION",  
)
```

Now that the overall simulation is set up, we can focus on building the groundwater flow model. The groundwater flow model will be built by adding packages to it that describe the model characteristics.

### Create the discretization (DIS) Package

Define the discretization of the model. All layers are given equal thickness. The `bot` array is build from `H` and the `Nlay` values to indicate top and bottom of each layer, and `delrow` and `delcol` are computed from model size `L` and number of cells `N`. Once these are all computed, the Discretization file is built.

```
[9]: bot = np.linspace(-H / Nlay, -H, Nlay)
delrow = delcol = L / (N - 1)
dis = flopy.mf6.ModflowGwfdisc(
    gwf,
    nlay=Nlay,
    nrow=N,
    ncol=N,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)
```

### Create the initial conditions (IC) Package

```
[10]: start = h1 * np.ones((Nlay, N, N))
ic = flopy.mf6.ModflowGwfic(gwf, pname="ic", strt=start)
```

### Create the node property flow (NPF) Package

```
[11]: npf = flopy.mf6.ModflowGwfnpf(
    gwf,
    icelltype=1,
    k=k,
)
```

### Create the constant head (CHD) Package

List information is created a bit differently for MODFLOW 6 than for other MODFLOW versions. The `cellid` (layer, row, column, for a regular grid) can be entered as a tuple as the first entry. Remember that these must be zero-based indices!

```
[12]: chd_rec = []
layer = 0
for row_col in range(0, N):
    chd_rec.append(((layer, row_col, 0), h1))
    chd_rec.append(((layer, row_col, N - 1), h1))
    if row_col != 0 and row_col != N - 1:
        chd_rec.append(((layer, 0, row_col), h1))
        chd_rec.append(((layer, N - 1, row_col), h1))
chd = flopy.mf6.ModflowGwfchd(
    gwf,
```

(continues on next page)

(continued from previous page)

```

    stress_period_data=chd_rec,
)

```

The CHD Package stored the constant heads in a structured array, also called a `numpy.recarray`. We can get a pointer to the recarray for the first stress period (`iper = 0`) as follows.

```

[13]: iper = 0
      ra = chd.stress_period_data.get_data(key=iper)
      ra
[13]: rec.array([(0, 0, 0), 100.), ((0, 0, 100), 100.), ((0, 1, 0), 100.),
                ((0, 1, 100), 100.), ((0, 0, 1), 100.), ((0, 100, 1), 100.),
                ((0, 2, 0), 100.), ((0, 2, 100), 100.), ((0, 0, 2), 100.),
                ((0, 100, 2), 100.), ((0, 3, 0), 100.), ((0, 3, 100), 100.),
                ((0, 0, 3), 100.), ((0, 100, 3), 100.), ((0, 4, 0), 100.),
                ((0, 4, 100), 100.), ((0, 0, 4), 100.), ((0, 100, 4), 100.),
                ((0, 5, 0), 100.), ((0, 5, 100), 100.), ((0, 0, 5), 100.),
                ((0, 100, 5), 100.), ((0, 6, 0), 100.), ((0, 6, 100), 100.),
                ((0, 0, 6), 100.), ((0, 100, 6), 100.), ((0, 7, 0), 100.),
                ((0, 7, 100), 100.), ((0, 0, 7), 100.), ((0, 100, 7), 100.),
                ((0, 8, 0), 100.), ((0, 8, 100), 100.), ((0, 0, 8), 100.),
                ((0, 100, 8), 100.), ((0, 9, 0), 100.), ((0, 9, 100), 100.),
                ((0, 0, 9), 100.), ((0, 100, 9), 100.), ((0, 10, 0), 100.),
                ((0, 10, 100), 100.), ((0, 0, 10), 100.), ((0, 100, 10), 100.),
                ((0, 11, 0), 100.), ((0, 11, 100), 100.), ((0, 0, 11), 100.),
                ((0, 100, 11), 100.), ((0, 12, 0), 100.), ((0, 12, 100), 100.),
                ((0, 0, 12), 100.), ((0, 100, 12), 100.), ((0, 13, 0), 100.),
                ((0, 13, 100), 100.), ((0, 0, 13), 100.), ((0, 100, 13), 100.),
                ((0, 14, 0), 100.), ((0, 14, 100), 100.), ((0, 0, 14), 100.),
                ((0, 100, 14), 100.), ((0, 15, 0), 100.), ((0, 15, 100), 100.),
                ((0, 0, 15), 100.), ((0, 100, 15), 100.), ((0, 16, 0), 100.),
                ((0, 16, 100), 100.), ((0, 0, 16), 100.), ((0, 100, 16), 100.),
                ((0, 17, 0), 100.), ((0, 17, 100), 100.), ((0, 0, 17), 100.),
                ((0, 100, 17), 100.), ((0, 18, 0), 100.), ((0, 18, 100), 100.),
                ((0, 0, 18), 100.), ((0, 100, 18), 100.), ((0, 19, 0), 100.),
                ((0, 19, 100), 100.), ((0, 0, 19), 100.), ((0, 100, 19), 100.),
                ((0, 20, 0), 100.), ((0, 20, 100), 100.), ((0, 0, 20), 100.),
                ((0, 100, 20), 100.), ((0, 21, 0), 100.), ((0, 21, 100), 100.),
                ((0, 0, 21), 100.), ((0, 100, 21), 100.), ((0, 22, 0), 100.),
                ((0, 22, 100), 100.), ((0, 0, 22), 100.), ((0, 100, 22), 100.),
                ((0, 23, 0), 100.), ((0, 23, 100), 100.), ((0, 0, 23), 100.),
                ((0, 100, 23), 100.), ((0, 24, 0), 100.), ((0, 24, 100), 100.),
                ((0, 0, 24), 100.), ((0, 100, 24), 100.), ((0, 25, 0), 100.),
                ((0, 25, 100), 100.), ((0, 0, 25), 100.), ((0, 100, 25), 100.),
                ((0, 26, 0), 100.), ((0, 26, 100), 100.), ((0, 0, 26), 100.),
                ((0, 100, 26), 100.), ((0, 27, 0), 100.), ((0, 27, 100), 100.),
                ((0, 0, 27), 100.), ((0, 100, 27), 100.), ((0, 28, 0), 100.),
                ((0, 28, 100), 100.), ((0, 0, 28), 100.), ((0, 100, 28), 100.),
                ((0, 29, 0), 100.), ((0, 29, 100), 100.), ((0, 0, 29), 100.),
                ((0, 100, 29), 100.), ((0, 30, 0), 100.), ((0, 30, 100), 100.),
                ((0, 0, 30), 100.), ((0, 100, 30), 100.), ((0, 31, 0), 100.),
                ((0, 31, 100), 100.), ((0, 0, 31), 100.), ((0, 100, 31), 100.),
                ((0, 32, 0), 100.), ((0, 32, 100), 100.), ((0, 0, 32), 100.),

```

(continues on next page)

(continued from previous page)

```

((0, 100, 32), 100.), ((0, 33, 0), 100.), ((0, 33, 100), 100.),
((0, 0, 33), 100.), ((0, 100, 33), 100.), ((0, 34, 0), 100.),
((0, 34, 100), 100.), ((0, 0, 34), 100.), ((0, 100, 34), 100.),
((0, 35, 0), 100.), ((0, 35, 100), 100.), ((0, 0, 35), 100.),
((0, 100, 35), 100.), ((0, 36, 0), 100.), ((0, 36, 100), 100.),
((0, 0, 36), 100.), ((0, 100, 36), 100.), ((0, 37, 0), 100.),
((0, 37, 100), 100.), ((0, 0, 37), 100.), ((0, 100, 37), 100.),
((0, 38, 0), 100.), ((0, 38, 100), 100.), ((0, 0, 38), 100.),
((0, 100, 38), 100.), ((0, 39, 0), 100.), ((0, 39, 100), 100.),
((0, 0, 39), 100.), ((0, 100, 39), 100.), ((0, 40, 0), 100.),
((0, 40, 100), 100.), ((0, 0, 40), 100.), ((0, 100, 40), 100.),
((0, 41, 0), 100.), ((0, 41, 100), 100.), ((0, 0, 41), 100.),
((0, 100, 41), 100.), ((0, 42, 0), 100.), ((0, 42, 100), 100.),
((0, 0, 42), 100.), ((0, 100, 42), 100.), ((0, 43, 0), 100.),
((0, 43, 100), 100.), ((0, 0, 43), 100.), ((0, 100, 43), 100.),
((0, 44, 0), 100.), ((0, 44, 100), 100.), ((0, 0, 44), 100.),
((0, 100, 44), 100.), ((0, 45, 0), 100.), ((0, 45, 100), 100.),
((0, 0, 45), 100.), ((0, 100, 45), 100.), ((0, 46, 0), 100.),
((0, 46, 100), 100.), ((0, 0, 46), 100.), ((0, 100, 46), 100.),
((0, 47, 0), 100.), ((0, 47, 100), 100.), ((0, 0, 47), 100.),
((0, 100, 47), 100.), ((0, 48, 0), 100.), ((0, 48, 100), 100.),
((0, 0, 48), 100.), ((0, 100, 48), 100.), ((0, 49, 0), 100.),
((0, 49, 100), 100.), ((0, 0, 49), 100.), ((0, 100, 49), 100.),
((0, 50, 0), 100.), ((0, 50, 100), 100.), ((0, 0, 50), 100.),
((0, 100, 50), 100.), ((0, 51, 0), 100.), ((0, 51, 100), 100.),
((0, 0, 51), 100.), ((0, 100, 51), 100.), ((0, 52, 0), 100.),
((0, 52, 100), 100.), ((0, 0, 52), 100.), ((0, 100, 52), 100.),
((0, 53, 0), 100.), ((0, 53, 100), 100.), ((0, 0, 53), 100.),
((0, 100, 53), 100.), ((0, 54, 0), 100.), ((0, 54, 100), 100.),
((0, 0, 54), 100.), ((0, 100, 54), 100.), ((0, 55, 0), 100.),
((0, 55, 100), 100.), ((0, 0, 55), 100.), ((0, 100, 55), 100.),
((0, 56, 0), 100.), ((0, 56, 100), 100.), ((0, 0, 56), 100.),
((0, 100, 56), 100.), ((0, 57, 0), 100.), ((0, 57, 100), 100.),
((0, 0, 57), 100.), ((0, 100, 57), 100.), ((0, 58, 0), 100.),
((0, 58, 100), 100.), ((0, 0, 58), 100.), ((0, 100, 58), 100.),
((0, 59, 0), 100.), ((0, 59, 100), 100.), ((0, 0, 59), 100.),
((0, 100, 59), 100.), ((0, 60, 0), 100.), ((0, 60, 100), 100.),
((0, 0, 60), 100.), ((0, 100, 60), 100.), ((0, 61, 0), 100.),
((0, 61, 100), 100.), ((0, 0, 61), 100.), ((0, 100, 61), 100.),
((0, 62, 0), 100.), ((0, 62, 100), 100.), ((0, 0, 62), 100.),
((0, 100, 62), 100.), ((0, 63, 0), 100.), ((0, 63, 100), 100.),
((0, 0, 63), 100.), ((0, 100, 63), 100.), ((0, 64, 0), 100.),
((0, 64, 100), 100.), ((0, 0, 64), 100.), ((0, 100, 64), 100.),
((0, 65, 0), 100.), ((0, 65, 100), 100.), ((0, 0, 65), 100.),
((0, 100, 65), 100.), ((0, 66, 0), 100.), ((0, 66, 100), 100.),
((0, 0, 66), 100.), ((0, 100, 66), 100.), ((0, 67, 0), 100.),
((0, 67, 100), 100.), ((0, 0, 67), 100.), ((0, 100, 67), 100.),
((0, 68, 0), 100.), ((0, 68, 100), 100.), ((0, 0, 68), 100.),
((0, 100, 68), 100.), ((0, 69, 0), 100.), ((0, 69, 100), 100.),
((0, 0, 69), 100.), ((0, 100, 69), 100.), ((0, 70, 0), 100.),
((0, 70, 100), 100.), ((0, 0, 70), 100.), ((0, 100, 70), 100.),
((0, 71, 0), 100.), ((0, 71, 100), 100.), ((0, 0, 71), 100.),

```

(continues on next page)

(continued from previous page)

```

((0, 100, 71), 100.), ((0, 72, 0), 100.), ((0, 72, 100), 100.),
((0, 0, 72), 100.), ((0, 100, 72), 100.), ((0, 73, 0), 100.),
((0, 73, 100), 100.), ((0, 0, 73), 100.), ((0, 100, 73), 100.),
((0, 74, 0), 100.), ((0, 74, 100), 100.), ((0, 0, 74), 100.),
((0, 100, 74), 100.), ((0, 75, 0), 100.), ((0, 75, 100), 100.),
((0, 0, 75), 100.), ((0, 100, 75), 100.), ((0, 76, 0), 100.),
((0, 76, 100), 100.), ((0, 0, 76), 100.), ((0, 100, 76), 100.),
((0, 77, 0), 100.), ((0, 77, 100), 100.), ((0, 0, 77), 100.),
((0, 100, 77), 100.), ((0, 78, 0), 100.), ((0, 78, 100), 100.),
((0, 0, 78), 100.), ((0, 100, 78), 100.), ((0, 79, 0), 100.),
((0, 79, 100), 100.), ((0, 0, 79), 100.), ((0, 100, 79), 100.),
((0, 80, 0), 100.), ((0, 80, 100), 100.), ((0, 0, 80), 100.),
((0, 100, 80), 100.), ((0, 81, 0), 100.), ((0, 81, 100), 100.),
((0, 0, 81), 100.), ((0, 100, 81), 100.), ((0, 82, 0), 100.),
((0, 82, 100), 100.), ((0, 0, 82), 100.), ((0, 100, 82), 100.),
((0, 83, 0), 100.), ((0, 83, 100), 100.), ((0, 0, 83), 100.),
((0, 100, 83), 100.), ((0, 84, 0), 100.), ((0, 84, 100), 100.),
((0, 0, 84), 100.), ((0, 100, 84), 100.), ((0, 85, 0), 100.),
((0, 85, 100), 100.), ((0, 0, 85), 100.), ((0, 100, 85), 100.),
((0, 86, 0), 100.), ((0, 86, 100), 100.), ((0, 0, 86), 100.),
((0, 100, 86), 100.), ((0, 87, 0), 100.), ((0, 87, 100), 100.),
((0, 0, 87), 100.), ((0, 100, 87), 100.), ((0, 88, 0), 100.),
((0, 88, 100), 100.), ((0, 0, 88), 100.), ((0, 100, 88), 100.),
((0, 89, 0), 100.), ((0, 89, 100), 100.), ((0, 0, 89), 100.),
((0, 100, 89), 100.), ((0, 90, 0), 100.), ((0, 90, 100), 100.),
((0, 0, 90), 100.), ((0, 100, 90), 100.), ((0, 91, 0), 100.),
((0, 91, 100), 100.), ((0, 0, 91), 100.), ((0, 100, 91), 100.),
((0, 92, 0), 100.), ((0, 92, 100), 100.), ((0, 0, 92), 100.),
((0, 100, 92), 100.), ((0, 93, 0), 100.), ((0, 93, 100), 100.),
((0, 0, 93), 100.), ((0, 100, 93), 100.), ((0, 94, 0), 100.),
((0, 94, 100), 100.), ((0, 0, 94), 100.), ((0, 100, 94), 100.),
((0, 95, 0), 100.), ((0, 95, 100), 100.), ((0, 0, 95), 100.),
((0, 100, 95), 100.), ((0, 96, 0), 100.), ((0, 96, 100), 100.),
((0, 0, 96), 100.), ((0, 100, 96), 100.), ((0, 97, 0), 100.),
((0, 97, 100), 100.), ((0, 0, 97), 100.), ((0, 100, 97), 100.),
((0, 98, 0), 100.), ((0, 98, 100), 100.), ((0, 0, 98), 100.),
((0, 100, 98), 100.), ((0, 99, 0), 100.), ((0, 99, 100), 100.),
((0, 0, 99), 100.), ((0, 100, 99), 100.), ((0, 100, 0), 100.),
((0, 100, 100), 100.)],
dtype=[('cellid', 'O'), ('head', '<f8')])

```

## Create the well (WEL) Package

Add a well in model layer 10.

```

[14]: wel_rec = [(Nlay - 1, int(N / 4), int(N / 4), q)]
wel = flopy.mf6.ModflowGwfwel(
    gwf,
    stress_period_data=wel_rec,
)

```

## Create the output control (OC) Package

Save heads and budget output to binary files and print heads to the model listing file at the end of the stress period.

```
[15]: headfile = f"{name}.hds"
      head_filerecord = [headfile]
      budgetfile = f"{name}.cbb"
      budget_filerecord = [budgetfile]
      saverecord = [("HEAD", "ALL"), ("BUDGET", "ALL")]
      printrecord = [("HEAD", "LAST")]
      oc = flopy.mf6.ModflowGwfoc(
          gwf,
          saverecord=saverecord,
          head_filerecord=head_filerecord,
          budget_filerecord=budget_filerecord,
          printrecord=printrecord,
      )
```

## Create the MODFLOW 6 Input Files and Run the Model

Once all the flop objects are created, it is very easy to create all of the input files and run the model.

### Write the datasets

```
[16]: sim.write_simulation()

writing simulation...
  writing simulation name file...
  writing simulation tdis package...
  writing ims package ims...
  writing model tutorial01_mf6...
    writing model name file...
    writing package dis...
    writing package ic...
    writing package npf...
    writing package chd_0...
  INFORMATION: maxbound in ('gwf6', 'chd', 'dimensions') changed to 400 based on size of
  ↳ stress_period_data
    writing package wel_0...
  INFORMATION: maxbound in ('gwf6', 'wel', 'dimensions') changed to 1 based on size of
  ↳ stress_period_data
    writing package oc...
```

## Run the Simulation

We can also run the simulation from python, but only if the MODFLOW 6 executable is available. The executable can be made available by putting the executable in a folder that is listed in the system path variable. Another option is to just put a copy of the executable in the simulation folder, though this should generally be avoided. A final option is to provide a full path to the executable when the simulation is constructed. This would be done by specifying `exe_name` with the full path.

```
[17]: success, buff = sim.run_simulation()
      if not success:
          raise Exception("MODFLOW 6 did not terminate normally.")
```

```
FloPy is using the following executable to run the model: /home/runner/.local/bin/mf6
                                MODFLOW 6
                                U.S. GEOLOGICAL SURVEY MODULAR HYDROLOGIC MODEL
                                VERSION 6.3.0 03/04/2022
```

```
MODFLOW 6 compiled Mar 07 2022 10:55:23 with Intel(R) Fortran Intel(R) 64
Compiler Classic for applications running on Intel(R) 64, Version 2021.5.0
Build 20211109_000000
```

This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use. Also refer to the USGS Water Resources Software User Rights Notice for complete use, copyright, and distribution information.

```
Run start date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09  2:42:38
```

```
Writing simulation list file: mfsim.lst
Using Simulation name file: mfsim.nam
```

```
Solving:  Stress period:      1      Time step:      1
```

```
Run end date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09  2:42:40
Elapsed run time:  1.878 Seconds
```

```
Normal termination of simulation.
```



## Post-Process Head Results

First, a link to the heads file is created with using the `.output.head()` method on the groundwater flow model. The link and the `get_data` method are used with the step number and period number for which we want to retrieve data. A three-dimensional array is returned of size `nlay`, `nrow`, `ncol`. Matplotlib contouring functions are used to make contours of the layers or a cross-section.


Read the binary head file and plot the results. We can use the Flopy `.output.head()` method on the groundwater flow model object (`gwf`). Also set a few variables that will be used for plotting.

```
[18]: h = gwf.output.head().get_data(kstpkper=(0, 0))
      x = y = np.linspace(0, L, N)
      y = y[::-1]
      vmin, vmax = 90.0, 100.0
      contour_intervals = np.arange(90, 100.1, 1.0)
```

## Plot a Map of Layer 1

```
[19]: fig = plt.figure(figsize=(6, 6))
      ax = fig.add_subplot(1, 1, 1, aspect="equal")
      c = ax.contour(x, y, h[0], contour_intervals, colors="black")
      plt.clabel(c, fmt="%2.1f")
```


```
[19]: <a list of 6 text.Text objects>
```



### Plot a Map of Layer 10

```
[20]: x = y = np.linspace(0, L, N)
      y = y[::-1]
      fig = plt.figure(figsize=(6, 6))
      ax = fig.add_subplot(1, 1, 1, aspect="equal")
      c = ax.contour(x, y, h[-1], contour_intervals, colors="black")
      plt.clabel(c, fmt="%1.1f")
```


```
[20]: <a list of 11 text.Text objects>
```



### Plot a Cross-section along row 25

```
[21]: z = np.linspace(-H / Nlay / 2, -H + H / Nlay / 2, Nlay)
      fig = plt.figure(figsize=(9, 3))
      ax = fig.add_subplot(1, 1, 1, aspect="auto")
      c = ax.contour(x, z, h[:, int(N / 4), :], contour_intervals, colors="black")
      plt.clabel(c, fmt="%1.1f")
```


```
[21]: <a list of 15 text.Text objects>
```



### Use the FloPy PlotMapView() capabilities for MODFLOW 6

#### Plot a Map of heads in Layers 1 and 10


```
[22]: fig, axes = plt.subplots(2, 1, figsize=(6, 12), constrained_layout=True)
# first subplot
ax = axes[0]
ax.set_title("Model Layer 1")
modelmap = flopy.plot.PlotMapView(model=gwf, ax=ax)
pa = modelmap.plot_array(h, vmin=vmin, vmax=vmax)
quadmesh = modelmap.plot_bc("CHD")
linecollection = modelmap.plot_grid(lw=0.5, color="0.5")
contours = modelmap.contour_array(
    h,
    levels=contour_intervals,
    colors="black",
)
ax.clabel(contours, fmt="%2.1f")
cb = plt.colorbar(pa, shrink=0.5, ax=ax)
# second subplot
ax = axes[1]
ax.set_title(f"Model Layer {Nlay}")
modelmap = flopy.plot.PlotMapView(model=gwf, ax=ax, layer=Nlay - 1)
linecollection = modelmap.plot_grid(lw=0.5, color="0.5")
pa = modelmap.plot_array(h, vmin=vmin, vmax=vmax)
quadmesh = modelmap.plot_bc("CHD")
contours = modelmap.contour_array(
    h,
    levels=contour_intervals,
    colors="black",
)
ax.clabel(contours, fmt="%2.1f")
cb = plt.colorbar(pa, shrink=0.5, ax=ax)
```



## Use the FloPy PlotCrossSection() capabilities for MODFLOW 6

### Plot a cross-section of heads along row 25

```
[23]: fig, ax = plt.subplots(1, 1, figsize=(9, 3), constrained_layout=True)
# first subplot
ax.set_title("Row 25")
modelmap = flopy.plot.PlotCrossSection(
    model=gwf,
    ax=ax,
    line={"row": int(N / 4)},
)
pa = modelmap.plot_array(h, vmin=vmin, vmax=vmax)
quadmesh = modelmap.plot_bc("CHD")
linecollection = modelmap.plot_grid(lw=0.5, color="0.5")
contours = modelmap.contour_array(
    h,
    levels=contour_intervals,
    colors="black",
)
ax.clabel(contours, fmt="%2.1f")
cb = plt.colorbar(pa, shrink=0.5, ax=ax)
```



### Determine the Flow Residual

The FLOW-JA-FACE cell-by-cell budget data can be processed to determine the flow residual for each cell in a MODFLOW 6 model. The diagonal position for each row in the FLOW-JA-FACE cell-by-cell budget data contains the flow residual for each cell and can be extracted using the `flopy.mf6.utils.get_residuals()` function.

First extract the FLOW-JA-FACE array from the cell-by-cell budget file

```
[24]: flowja = gwf.oc.output.budget().get_data(text="FLOW-JA-FACE", kstpker=(0, 0))[
    0
]
```


Next extract the flow residual. The MODFLOW 6 binary grid file is passed into the function because it contains the `ia` array that defines the location of the diagonal position in the FLOW-JA-FACE array.

```
[25]: grb_file = f"{name}.dis.grb"
      residual = flopy.mf6.utils.get_residuals(flowja, grb_file=grb_file)
```

### Plot a Map of the flow error in Layer 10

```
[26]: fig, ax = plt.subplots(1, 1, figsize=(6, 6), constrained_layout=True)
      ax.set_title("Model Layer 10")
      modelmap = flopy.plot.PlotMapView(model=gwf, ax=ax, layer=Nlay - 1)
      pa = modelmap.plot_array(residual)
      quadmesh = modelmap.plot_bc("CHD")
      linecollection = modelmap.plot_grid(lw=0.5, color="0.5")
      contours = modelmap.contour_array(
          h,
          levels=contour_intervals,
          colors="black",
      )
      ax.clabel(contours, fmt="%2.1f")
      plt.colorbar(pa, shrink=0.5)
```

```
[26]: <matplotlib.colorbar.Colorbar at 0x7fa5a8635e20>
```



## 6.1.2 MODFLOW 6 FloPy Use Tutorials

Contents:

### MODFLOW 6: Accessing Simulation Settings, Models, and Packages

This tutorial shows how to view, access, and change the underlying package variables for MODFLOW 6 objects in FloPy. Interaction with a FloPy MODFLOW 6 model is different from other models, such as MODFLOW-2005, MT3D, and SEAWAT, for example.

The MODFLOW 6 simulation structure is arranged in the following generalized way:

```
SIMULATION --> PACKAGE --> Data

SIMULATION --> MODEL --> PACKAGE (--> PACKAGE) --> Data
```

This tutorial focuses on accessing simulation-wide FloPy settings and how to create and access models and packages. Tutorial 3, 4, and 5 offer a more in depth look at observation, time series, and time array series packages, and tutorial 6, 7, 8, and 9 offer a more in depth look at the data.

### Create Simple Demonstration Model

This tutorial uses a simple demonstration simulation with one GWF Model. The model has 3 layers, 4 rows, and 5 columns. The model is set up to use multiple model layers in order to demonstrate some of the layered functionality in FloPy.

```
[1]: # package import
import flopy

[2]: # set up simulation and basic packages
name = "tutorial02_mf6"
sim = flopy.mf6.MFSimulation(sim_name=name, sim_ws=".")
flopy.mf6.ModflowTdis(
    sim, nper=10, perioddata=[[365.0, 1, 1.0] for _ in range(10)]
)
flopy.mf6.ModflowIms(sim)
gwf = flopy.mf6.ModflowGwf(sim, modelname=name, save_flows=True)
flopy.mf6.ModflowGwfdis(gwf, nlay=3, nrow=4, ncol=5)
flopy.mf6.ModflowGwfic(gwf)
flopy.mf6.ModflowGwfnpf(gwf, save_specific_discharge=True)
flopy.mf6.ModflowGwfchd(
    gwf, stress_period_data=[[(0, 0, 0), 1.0], [(2, 3, 4), 0.0]]
)
budget_file = f"{name}.bud"
head_file = f"{name}.hds"
flopy.mf6.ModflowGwfoc(
    gwf,
    budget_filerecord=budget_file,
    head_filerecord=head_file,
    saverecord=[("HEAD", "ALL"), ("BUDGET", "ALL")],
)
print("Done creating simulation.")
```

```
Done creating simulation.
```

## Accessing Simulation-Level Settings

FloPy has a number of settings that can be set for the entire simulation. These include how much information FloPy writes to the console, how to format the MODFLOW package files, and whether to verify MODFLOW data.

The verbosity level, which determines how much FloPy writes to command line output. The options are 1 for quiet, 2 for normal, and 3 for verbose. Below we set the verbosity level to verbose.

```
[3]: sim.simulation_data.verbosity_level = 3
```

We can also set the number of spaces to indent data when writing package files by setting the indent string.

```
[4]: sim.simulation_data.indent_string = "    "
```

Next we set the precision and number of characters written for floating point variables.

```
[5]: sim.float_precision = 8
     sim.float_characters = 15
```

Lastly, we disable verify\_data and auto\_set\_sizes for faster performance. With these options disabled FloPy will not do any checking or autocorrecting of your data.

```
[6]: sim.verify_data = False
     sim.auto_set_sizes = False
```

## Accessing Models and Packages

At this point a simulation is available in memory. In this particular case the simulation was created directly using Python code; however, the simulation might also have been loaded from existing model files using the FloPy.mf6.MFSimulation.load() function.

Once a MODFLOW 6 simulation is available in memory, the contents of the simulation object can be listed using a simple print command.

```
[7]: print(sim)

sim_name = tutorial02_mf6
sim_path = /home/runner/work/flopy/flopy/.docs/.working/.
exe_name = mf6.exe

#####
Package mfsim.nam
#####

package_name = mfsim.nam
filename = mfsim.nam
package_type = nam
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

(continues on next page)



(continued from previous page)

```
#####
Package tutorial02_mf6.tdis
#####

package_name = tutorial02_mf6.tdis
filename = tutorial02_mf6.tdis
package_type = tdis
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

```
#####
Package ims_-1
#####

package_name = ims_-1
filename = tutorial02_mf6.ims
package_type = ims
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

```
@@@@@@@@@@@@@@@@@@@@
Model tutorial02_mf6
@@@@@@@@@@@@@@@@@@@@

name = tutorial02_mf6
model_type = gw6
version = mf6
model_relative_path = .
```

```
#####
Package dis
#####

package_name = dis
filename = tutorial02_mf6.dis
package_type = dis
model_or_simulation_package = model
model_name = tutorial02_mf6
```

```
#####
Package ic
#####

package_name = ic
filename = tutorial02_mf6.ic
package_type = ic
model_or_simulation_package = model
model_name = tutorial02_mf6
```

(continues on next page)

(continued from previous page)

```
#####
Package npf
#####

package_name = npf
filename = tutorial02_mf6.npf
package_type = npf
model_or_simulation_package = model
model_name = tutorial02_mf6

#####
Package chd_0
#####

package_name = chd_0
filename = tutorial02_mf6.chd
package_type = chd
model_or_simulation_package = model
model_name = tutorial02_mf6

#####
Package oc
#####

package_name = oc
filename = tutorial02_mf6.oc
package_type = oc
model_or_simulation_package = model
model_name = tutorial02_mf6
```

Simulation-level packages, models, and model packages can be shown by printing the simulation object. In this case, you should see the all of the contents of simulation and some information about each FloPy object that is part of simulation.

To get the TDIS package and print the contents, we can do the following

```
[8]: tdis = sim.tdis
      print(tdis)

package_name = tutorial02_mf6.tdis
filename = tutorial02_mf6.tdis
package_type = tdis
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

(continues on next page)

(continued from previous page)

Block dimensions

-----

```
nper
{internal}
(10)
```

Block perioddata

-----

```
perioddata
{internal}
([(365., 1, 1.) (365., 1, 1.) (365., 1, 1.) (365., 1, 1.) (365., 1, 1.)
  (365., 1, 1.) (365., 1, 1.) (365., 1, 1.) (365., 1, 1.) (365., 1, 1.)])
```

To get the Iterative Model Solution (IMS) object, we use the following syntax

```
[9]: ims = sim.get_package("ims_-1")
print(ims)

package_name = ims_-1
filename = tutorial02_mf6.ims
package_type = ims
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

Or because there is only one IMS object for this simulation, we can access it as

```
[10]: ims = sim.get_package("ims")
print(ims)

package_name = ims_-1
filename = tutorial02_mf6.ims
package_type = ims
model_or_simulation_package = simulation
simulation_name = tutorial02_mf6
```

When printing the sim object, there is also a simulation package called nam. This package contains the information that is written to the mfsim.nam file, which is the primary file that MODFLOW 6 reads when it first starts. The nam package is automatically updated for you by FloPy and does not require modification.

```
[11]: nam = sim.get_package("nam")
print(nam)

package_name = mfsim.nam
filename = mfsim.nam
package_type = nam
model_or_simulation_package = simulation
```

(continues on next page)

(continued from previous page)

```
simulation_name = tutorial02_mf6

Block timing
-----
tdis6
{internal}
(tutorial02_mf6.tdis)

Block models
-----
models
{internal}
([('gwf6', 'tutorial02_mf6.nam', 'tutorial02_mf6')])

Block solutiongroup
-----
solutiongroup
{internal}
([('ims6', 'tutorial02_mf6.ims', 'tutorial02_mf6')])
```

To see the models that are contained within the simulation, we can get a list of their names as follows

```
[12]: print(sim.model_names)
dict_keys(['tutorial02_mf6'])
```

`sim.model_names` returns the keys of an ordered dictionary, which isn't very useful to us, but we can convert that to a list and then go through that list and print information about each model in the simulation. In this case there is only one model, but had there been more models, we would see them listed here

```
[13]: model_names = list(sim.model_names)
      for mname in model_names:
          print(mname)
tutorial02_mf6
```

If we want to get a model from a simulation, then we use the `get_model()` method of the `sim` object. Here we go through all the models in the simulation and print the model name and the model type.

```
[14]: model_names = list(sim.model_names)
      for mname in model_names:
          m = sim.get_model(mname)
          print(m.name, m.model_type)
tutorial02_mf6 gwf6
```

For this simple case here with only one GWF model, we can very easily get the FloPy representation of the GWF model as

```
[15]: gwf = sim.get_model("tutorial02_mf6")
```

Now that we have the GWF object, we can print it, and see what's it contains.

```
[16]: print(gwf)

name = tutorial02_mf6
model_type = gwf6
version = mf6
model_relative_path = .

#####
Package dis
#####

package_name = dis
filename = tutorial02_mf6.dis
package_type = dis
model_or_simulation_package = model
model_name = tutorial02_mf6

#####
Package ic
#####

package_name = ic
filename = tutorial02_mf6.ic
package_type = ic
model_or_simulation_package = model
model_name = tutorial02_mf6

#####
Package npf
#####

package_name = npf
filename = tutorial02_mf6.npf
package_type = npf
model_or_simulation_package = model
model_name = tutorial02_mf6

#####
Package chd_0
#####

package_name = chd_0
filename = tutorial02_mf6.chd
package_type = chd
model_or_simulation_package = model
model_name = tutorial02_mf6
```

(continues on next page)

(continued from previous page)

```
#####
Package oc
#####

package_name = oc
filename = tutorial02_mf6.oc
package_type = oc
model_or_simulation_package = model
model_name = tutorial02_mf6
```

What we see here is the information that we saw when we printed the sim object.

One of the most common operations on a model is to see what packages are in it and then get packages of interest. A list of packages in a model can be obtained as

```
[17]: package_list = gwf.get_package_list()
      print(package_list)

['DIS', 'IC', 'NPF', 'CHD_0', 'OC']
```

As you might expect we can access each package in this list with `gwf.get_package()`. Thus, the following syntax can be used to obtain and print the contents of the DIS Package

```
[18]: dis = gwf.get_package("dis")
      print(dis)

package_name = dis
filename = tutorial02_mf6.dis
package_type = dis
model_or_simulation_package = model
model_name = tutorial02_mf6

Block dimensions
-----
nlay
{internal}
(3)

nrow
{internal}
(4)

ncol
{internal}
(5)

Block griddata
-----
```

(continues on next page)

(continued from previous page)

```
delr
{constant 1.0}

delc
{constant 1.0}

top
{constant 1.0}

botm
{constant 0.0}
```

The Python type for this dis package is simply

```
[19]: print(type(dis))

<class 'flopY.mf6.modflow.mfgwfdis.ModflowGwfdis'>
```

## MODFLOW 6: Observation packages

### Introduction to Observations

Observations can be set for any package through the `package.obs` object, and each `package.obs` object has several attributes that can be set:

Attribute	Type	Description
<code>package.obs.filename</code>	str	Name of observations file to create. The default is <code>packagename + '.obs'</code> .
<code>package.obs.continuous</code>	dict	A dictionary that has file names as keys and a list of observations as the dictionary values.
<code>package.obs.digits</code>	int	Number of digits to write the observation values. Default is 10.
<code>package.obs.print_input</code>	bool	Flag indicating whether or not observations are written to listing file.

The following code sets up a simulation used in the observation examples.

```
[1]: # package import
import os

[2]: import numpy as np

[3]: import flopY

[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)
```

```
[5]: # create the flopY simulation and tdis objects
sim = flopY.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)
tdis_rc = [(1.0, 1, 1.0), (10.0, 5, 1.0), (10.0, 5, 1.0), (10.0, 1, 1.0)]
tdis_package = flopY.mf6.modflow.mftdis.ModflowTdis(
    sim, time_units="DAYS", nper=4, perioddata=tdis_rc
)
# create the flopY groundwater flow (gwf) model object
model_nam_file = f"{name}.nam"
gwf = flopY.mf6.ModflowGwf(sim, modelname=name, model_nam_file=model_nam_file)
# create the flopY iterative model solver (ims) package object
ims = flopY.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
# create the discretization package
bot = np.linspace(-3.0, -50.0 / 3.0, 3)
delrow = delcol = 4.0
dis = flopY.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
    nogrb=True,
    nlay=3,
    nrow=101,
    ncol=101,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)
# create the initial condition (ic) and node property flow (npf) packages
ic_package = flopY.mf6.modflow.mfgwfic.ModflowGwfic(gwf, strt=50.0)
npf_package = flopY.mf6.modflow.mfgwfnpf.ModflowGwfnpf(
    gwf,
    save_flows=True,
    icelltype=[1, 0, 0],
    k=[5.0, 0.1, 4.0],
    k33=[0.5, 0.005, 0.1],
)
```

### Observation Example 1

One method to build the observation package is to pass a dictionary with the observations containing “observations” parameters of the parent package.

This example uses the observation package in a GHB package. First the stress period data for a ghb package is built.

```
[6]: # build ghb stress period data
ghb_spd = {}
ghb_period = []
for layer, cond in zip(range(1, 3), [15.0, 1500.0]):
    for row in range(0, 15):
        ghb_period.append(((layer, row, 9), 1.0, cond, "Estuary-L2"))
ghb_spd[0] = ghb_period
```



The next step is to build the observation data in a dictionary. The dictionary key is the filename of the observation output file and optionally a “binary” keyword to make the file binary. When the optional “binary” keyword is used the dictionary key is a tuple, otherwise it is a string. The dictionary value is a list of tuples containing the contents of the observation package’s continuous block, with each tuple containing one line of information.

```
[7]: # build obs data
ghb_obs = {
    ("ghb_obs.csv", "binary"): [
        ("ghb-2-6-10", "GHB", (1, 5, 9)),
        ("ghb-3-6-10", "GHB", (2, 5, 9)),
    ],
    "ghb_flows.csv": [
        ("Estuary2", "GHB", "Estuary-L2"),
        ("Estuary3", "GHB", "Estuary-L3"),
    ],
}
```

The ghb package is now constructed with observations by setting the observations parameter to ghb\_obs on construction of the ghb package.

```
[8]: # build ghb package passing obs dictionary to package constructor
ghb = flopy.mf6.modflow.mfgwfghb.ModflowGwfghb(
    gwf,
    print_input=True,
    print_flows=True,
    save_flows=True,
    boundnames=True,
    observations=ghb_obs,
    pname="ghb",
    maxbound=30,
    stress_period_data=ghb_spd,
)
```

Observation information such as the print\_input option can then be set using the package’s obs parameter.

```
[9]: ghb.obs.print_input = True
```

```
[10]: # clean up for next example
gwf.remove_package("ghb")
```

## Observation Example 2

Alternatively, an obs package can be built by initializing obs through ghb.obs.initialize.

First, a GHB package is built without defining observations.

```
[11]: # build ghb package
ghb = flopy.mf6.modflow.mfgwfghb.ModflowGwfghb(
    gwf,
    print_input=True,
    print_flows=True,
    save_flows=True,
    boundnames=True,
```

(continues on next page)

(continued from previous page)

```
maxbound=30,  
stress_period_data=ghb_spd,  
pname="ghb",  
)
```

Then the ghb observations are defined in a dictionary similar to example 1.

```
[12]: # build obs data  
ghb_obs = {  
    ("ghb_obs.csv", "binary"): [  
        ("ghb-2-6-10", "GHB", (1, 5, 9)),  
        ("ghb-3-6-10", "GHB", (2, 5, 9)),  
    ],  
    "ghb_flows.csv": [  
        ("Estuary2", "GHB", "Estuary-L2"),  
        ("Estuary3", "GHB", "Estuary-L3"),  
    ],  
}
```

The observations can then be added to the ghb package using the obs attribute's initialize method. The observation package's file name, digits, and print\_input options, along with the continuous block data are set in the initialize method.

```
[13]: # initialize obs package  
ghb.obs.initialize(  
    filename="child_pkgs_test.ghb.obs",  
    digits=9,  
    print_input=True,  
    continuous=ghb_obs,  
)
```

## MODFLOW 6: Time Series Packages

### Introduction to Time Series

Time series can be set for any package through the `package.ts` object, and each `package.ts` object has several attributes that can be set:

Attribute	Type	Description
package.ts.filename	str	Name of time series file to create. The default is packagename + “.ts”.
package.ts.timeseries	recarray	Array containing the time series information
package.ts.time_series_names	str or list	List of names of the time series data columns. Default is to use names from timeseries.dtype.names[1:].
package.ts.interpolation_method	str	Interpolation method. Must be only one time series record. If there are multiple time series records, then the methods attribute must be used.
package.ts.interpolation_method_record	float	Scale factor to multiply the time series data column. Can only be used if there is one time series data column.
package.ts.sfac_record_single	float	Scale factor to multiply the time series data column. Can only be used if there is one time series data column.
package.ts.sfac_record	list (of floats)	Scale factors to multiply the time series data columns.

The following code sets up a simulation used in the time series examples.

```
[1]: # package import
import os
```

```
[2]: import numpy as np
```

```
[3]: import flop
```

```
[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)
```

```
[5]: # create the flop simulation and tdis objects
sim = flop.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)
tdis_rc = [(1.0, 1, 1.0), (10.0, 5, 1.0), (10.0, 5, 1.0), (10.0, 1, 1.0)]
tdis_package = flop.mf6.modflow.mftdis.ModflowTdis(
    sim, time_units="DAYS", nper=4, perioddata=tdis_rc
)
# create the Flop groundwater flow (gwf) model object
model_name_file = f"{name}.nam"
gwf = flop.mf6.ModflowGwf(sim, modelname=name, model_name_file=model_name_file)
# create the flop iterative model solver (ims) package object
ims = flop.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
# create the discretization package
bot = np.linspace(-3.0, -50.0 / 3.0, 3)
delrow = delcol = 4.0
dis = flop.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
```

(continues on next page)

(continued from previous page)

```

    pname="dis",
    nogrb=True,
    nlay=3,
    nrow=101,
    ncol=101,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)
# create the initial condition (ic) and node property flow (npf) packages
ic_package = flopy.mf6.modflow.mfgwfic.ModflowGwfic(gwf, strt=50.0)
npf_package = flopy.mf6.modflow.mfgwfnpf.ModflowGwfnpf(
    gwf,
    save_flows=True,
    icelltype=[1, 0, 0],
    k=[5.0, 0.1, 4.0],
    k33=[0.5, 0.005, 0.1],
)

```

## Time Series Example 1

One way to construct a time series is to pass the time series data to the parent package constructor.

This example uses time series data in a GHB package. First the GHB `stress_period_data` is built.

```

[6]: # build ghb stress period data
ghb_spd_ts = {}
ghb_period = []
for layer, cond in zip(range(1, 3), [15.0, 1500.0]):
    for row in range(0, 15):
        ghb_period.append((layer, row, 9), "tides", cond, "Estuary-L2"))
ghb_spd_ts[0] = ghb_period

```

Next the time series data is built. The time series data is constructed as a list of tuples, with each tuple containing a time and the value (or values) at that time.

```

[7]: # build ts data
ts_data = []
for n in range(0, 365):
    time = float(n / 11.73)
    val = float(n / 60.0)
    ts_data.append((time, val))

```

The GHB package is then constructed, passing the time series data into the `timeseries` parameter.

```

[8]: # build ghb package
ghb = flopy.mf6.modflow.mfgwfghb.ModflowGwfghb(
    gwf,
    print_input=True,
    print_flows=True,
    save_flows=True,

```

(continues on next page)

(continued from previous page)

```

    boundnames=True,
    timeseries=ts_data,
    pname="ghb",
    maxbound=30,
    stress_period_data=ghb_spd_ts,
)

```

```

WARNING: Unable to resolve dimension of ('ts', 'timeseries', 'timeseries', 'ts_array')
↳ based on shape "time_series_names".
WARNING: Unable to resolve dimension of ('ts', 'timeseries', 'timeseries', 'ts_array')
↳ based on shape "time_series_names".
WARNING: Unable to resolve dimension of ('ts', 'timeseries', 'timeseries', 'ts_array')
↳ based on shape "time_series_names".

```

Time series attributes, like `time_series_namerecord`, can be set using the `ghb.ts` object.

```

[9]: # set required time series attributes
ghb.ts.time_series_namerecord = "tides"

```

```

[10]: # clean up for next example
gwf.remove_package("ghb")

```

## Time Series Example 2

Another way to construct a time series is to initialize the time series through the `ghb.ts.initialize` method. Additional time series can then be appended using the `append_package` method.

First the GHB stress period data is built.

```

[11]: # build ghb stress period data
ghb_spd_ts = {}
ghb_period = []
for layer, cond in zip(range(1, 3), [15.0, 1500.0]):
    for row in range(0, 15):
        if row < 10:
            ghb_period.append(((layer, row, 9), "tides", cond, "Estuary-L2"))
        else:
            ghb_period.append(((layer, row, 9), "w1", cond, "Estuary-L2"))
ghb_spd_ts[0] = ghb_period

```

Next the time series data is built. The time series data is constructed as a list of tuples, with each tuple containing a time and the value (or values) at that time.

```

[12]: # build ts data
ts_data = []
for n in range(0, 365):
    time = float(n / 11.73)
    val = float(n / 60.0)
    ts_data.append((time, val))
ts_data2 = []
for n in range(0, 365):
    time = float(1.0 + (n / 12.01))

```

(continues on next page)

(continued from previous page)

```

    val = float(n / 60.0)
    ts_data2.append((time, val))
ts_data3 = []
for n in range(0, 365):
    time = float(10.0 + (n / 12.01))
    val = float(n / 60.0)
    ts_data3.append((time, val))

```

A ghb package is constructed without the time series data

```

[13]: # build ghb package
ghb = flop.mf6.modflow.mfgwfghb.ModflowGwfghb(
    gwf,
    print_input=True,
    print_flows=True,
    save_flows=True,
    boundnames=True,
    pname="ghb",
    maxbound=30,
    stress_period_data=ghb_spd_ts,
)

```

The first time series data are added by calling the initialize method from the `ghb.ts` object. The times series package's file name, name record, method record, and sfac record, along with the time series data are set in the initialize method.

```

[14]: # initialize first time series
ghb.ts.initialize(
    filename="tides.ts",
    timeseries=ts_data,
    time_series_namerecord="tides",
    interpolation_methodrecord="linearend",
    sfacrecord=1.1,
)

```

WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
 ↳ 'sfacval') based on shape "time\_series\_name".

WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
 ↳ 'sfacval') based on shape "time\_series\_name".

The remaining time series data are added using the `append_package` method. The `append_package` method takes the same parameters as the initialize method.

```

[15]: # append additional time series
ghb.ts.append_package(
    filename="wls.ts",
    timeseries=ts_data2,
    time_series_namerecord="wl",
    interpolation_methodrecord="stepwise",
    sfacrecord=1.2,
)
# append additional time series
ghb.ts.append_package(
    filename="wls2.ts",

```

(continues on next page)

(continued from previous page)

```

timeseries=ts_data3,
time_series_namerecord="w12",
interpolation_methodrecord="stepwise",
sfacrecord=1.3,
)

```

WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
↳ 'sfacval') based on shape "time\_series\_name".  
WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
↳ 'sfacval') based on shape "time\_series\_name".  
WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
↳ 'sfacval') based on shape "time\_series\_name".  
WARNING: Unable to resolve dimension of ('ts', 'attributes', 'sfacrecord\_single',  
↳ 'sfacval') based on shape "time\_series\_name".

Information can be retrieved from time series packages using the `ts` attribute of its parent package. Below the interpolation method record for each of the three time series are retrieved.

```

[16]: print(
      "{} is using {} interpolation".format(
          ghb.ts[0].filename,
          ghb.ts[0].interpolation_methodrecord.get_data()[0][0],
      )
    )
print(
    "{} is using {} interpolation".format(
        ghb.ts[1].filename,
        ghb.ts[1].interpolation_methodrecord.get_data()[0][0],
    )
)
print(
    "{} is using {} interpolation".format(
        ghb.ts[2].filename,
        ghb.ts[2].interpolation_methodrecord.get_data()[0][0],
    )
)

```

tides.ts is using linearend interpolation  
wls.ts is using stepwise interpolation  
wls2.ts is using stepwise interpolation

## MODFLOW 6: Time Array Series Packages

### Introduction to Time Array Series

Time array series can be set for any package through the `package.tas` object, and each `package.tas` object has several attributes that can be set:

Attribute	Type	Description
package.tas.filename	str	Name of time series file to create. The default is packagename + ".tas".
package.tas.tas_array	{double:[double]}	Array containing the time array series information for specific times.
package.tas.time_series_name	str	Name by which a package references a particular time-array series. The name must be unique among all time-array series used in a package.
package.tas.interpolation_method	list (of strings)	List of interpolation methods to use for time array series. Method must be either "stepwise" or "linear".
package.tas.sfarecord_single	float	Scale factor to multiply the time array series data column. Can only be used if there is one time series data column.

The following code sets up a simulation used in the time array series examples.

```
[1]: # package import
import os
```

```
[2]: import numpy as np
```

```
[3]: import flopy
```

```
[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)
```

```
[5]: # create the Flopy simulation and tdis objects
sim = flopy.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)
tdis_rc = [(1.0, 1, 1.0), (10.0, 5, 1.0), (10.0, 5, 1.0), (10.0, 1, 1.0)]
tdis_package = flopy.mf6.modflow.mftdis.ModflowTdis(
    sim, time_units="DAYS", nper=4, perioddata=tdis_rc
)
# create the Flopy groundwater flow (gwf) model object
model_name_file = f"{name}.nam"
gwf = flopy.mf6.ModflowGwf(sim, modelname=name, model_name_file=model_name_file)
# create the flopy iterative model solver (ims) package object
ims = flopy.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
# create the discretization package
bot = np.linspace(-3.0, -50.0 / 3.0, 3)
delrow = delcol = 4.0
dis = flopy.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
    nogrb=True,
    nlay=3,
    nrow=101,
    ncol=101,
```

(continues on next page)



(continued from previous page)

```

    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)
# create the initial condition (ic) and node property flow (npf) packages
ic_package = flopy.mf6.modflow.mfgwfic.ModflowGwfic(gwf, strt=50.0)
npf_package = flopy.mf6.modflow.mfgwfnpf.ModflowGwfnpf(
    gwf,
    save_flows=True,
    icelltype=[1, 0, 0],
    k=[5.0, 0.1, 4.0],
    k33=[0.5, 0.005, 0.1],
)

```

### Time Array Series Example 1

Time array series data can be passed into the `timearrayseries` parameter on construction of any package that supports time array series. This example uses the `timearrayseries` parameter to create a time array series and then uses the package's `tas` property to finish the time array series setup.

This example uses time array series data in a RCHA package. The time array series is built as a dictionary with the times as the keys and the recharge values as the values.

```
[6]: tas = {0.0: 0.0000002, 200.0: 0.0000001}
```

The time array series data is then passed into the `timearrayseries` parameter when the RCHA package is constructed.

```
[7]: rcha = flopy.mf6.modflow.mfgwfrcha.ModflowGwfrcha(
    gwf, timearrayseries=tas, recharge="TIMEARRAYSERIES rchararray_1"
)
```

WARNING: Time array series name rchararray\_1 not found in any time series file

Time array series attributes can be set by access the time array series package object through the `rcha.tas` attribute.

```
[8]: # finish defining the time array series properties
rcha.tas.time_series_namerecord = "rchararray_1"
rcha.tas.interpolation_methodrecord = "LINEAR"
```

The simulation is then written to files and run.

```
[9]: sim.write_simulation()
sim.run_simulation()

writing simulation...
  writing simulation name file...
  writing simulation tdis package...
  writing ims package ims...
  writing model example_1...
    writing model name file...
    writing package dis...
    writing package ic...
```

(continues on next page)

(continued from previous page)

```
writing package npf...
writing package rcha_0...
writing package tas_0...
FloPy is using the following executable to run the model: /home/runner/.local/bin/mf6
MODFLOW 6
U.S. GEOLOGICAL SURVEY MODULAR HYDROLOGIC MODEL
VERSION 6.3.0 03/04/2022

MODFLOW 6 compiled Mar 07 2022 10:55:23 with Intel(R) Fortran Intel(R) 64
Compiler Classic for applications running on Intel(R) 64, Version 2021.5.0
Build 20211109_000000
```

This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use. Also refer to the USGS Water Resources Software User Rights Notice for complete use, copyright, and distribution information.

```
Run start date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09 2:43:19
```

```
Writing simulation list file: mfsim.lst
Using Simulation name file: mfsim.nam
```

Solving:	Stress period:	1	Time step:	1
Solving:	Stress period:	2	Time step:	1
Solving:	Stress period:	2	Time step:	2
Solving:	Stress period:	2	Time step:	3
Solving:	Stress period:	2	Time step:	4
Solving:	Stress period:	2	Time step:	5
Solving:	Stress period:	3	Time step:	1
Solving:	Stress period:	3	Time step:	2
Solving:	Stress period:	3	Time step:	3
Solving:	Stress period:	3	Time step:	4
Solving:	Stress period:	3	Time step:	5
Solving:	Stress period:	4	Time step:	1

```
Run end date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09 2:43:20
Elapsed run time: 0.311 Seconds
```

```
Normal termination of simulation.
```

```
[9]: (True, [])
```

```
[10]: # clean up for next example
```

(continues on next page)

(continued from previous page)

```
gwf.remove_package("rcha")
```

## Time Array Series Example 2

A time array series can be added after a package is created by calling the package's `tas` attribute's `initialize` method. Initialize allows you to define all time array series attributes including file name, the time array series data, name record, and method record.

First a recharge package is built.

```
[11]: # create recharge package with recharge pointing to a time array series
# not yet defined. FloPy will generate a warning that there is not yet a
# time series name record for rchararray_1
rcha = flopy.mf6.modflow.mfgwfrcha.ModflowGwfrcha(
    gwf, recharge="TIMEARRAYSERIES rchararray_1"
)

WARNING: Time array series name rchararray_1 not found in any time series file
```

Then a time array series dictionary is created as done in example 1.

```
[12]: tas = {0.0: 0.0000002, 200.0: 0.0000001}
```

The time array series data are added by calling the `initialize` method from the 'RCHA' package's `tas` attribute. The time array series file name, name record, and method record, along with the time series data are set in the `initialize` method.

```
[13]: # initialize the time array series
rcha.tas.initialize(
    filename="method2.tas",
    tas_array=tas,
    time_series_namerecord="rchararray_1",
    interpolation_methodrecord="LINEAR",
)
```

## MODFLOW 6: Working with MODFLOW Scalar Data

This tutorial shows how to view, access, and change the underlying data variables for MODFLOW 6 objects in FloPy. Interaction with a FloPy MODFLOW 6 model is different from other models, such as MODFLOW-2005, MT3D, and SEAWAT, for example.

FloPy stores model data in data objects (`MFDataArray`, `MFDataList`, `MFDataScalar` objects) that are accessible from packages. Data can be added to a package by using the appropriate parameters when the package is constructed and through package attributes.

The MODFLOW 6 simulation structure is arranged in the following generalized way:

```
Simulation --> Package --> DATA

Simulation --> Model --> Package (--> Package) --> DATA
```

This tutorial focuses on MODFLOW Data that is a single integer or string, or consists of boolean flag(s). These data are stored by FloPy in a `MFScalar` object and are referred to as MODFLOW scalar data.

## Introduction to MODFLOW Scalar Data

MODFLOW single integer, strings, or boolean flag(s) are stored by FloPy as scalar data in `MFS` objects. The different types of scalar data are described below.

1. Single integer values. Examples include `nrow`, `ncol`, `nlay`, and `nper`.
2. Single string values. Examples include `time_units` and `length_units`.
3. Boolean flags. These can be found in the options section of most packages. These include `perched`, `nogrb`, `print_input`, and `save_flows`.
4. Boolean flags with an additional optional flag. These include `newton_under_relaxation` and `xt3d_rhs`.

In the following all four types of scalar data will be added to a model. Before adding data to your model first create a simulation (`MFSimulation`) and a model (`MFModel`) object in FloPy.

```
[1]: # package import
import os

[2]: import numpy as np

[3]: import flopy

[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)

[5]: # create the flopy simulation object
sim = flopy.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)

[6]: # create the flopy groundwater flow (gwf) model object
model_name_file = f"{name}.nam"
gwf = flopy.mf6.ModflowGwf(sim, modelname=name, model_name_file=model_name_file)
# create the flopy iterative model solver (ims) package object
# (both pname and complexity are scalar data)
ims = flopy.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
```

## Adding MODFLOW Single Integer and String Values

Single integer and string values can be assigned on construction of the `MFS` data object, and can be assigned or changed after construction.

Below, a `TDIS` package is constructed with the `time_units` and `nper` parameters being assigned “DAYS” and “2”, respectively.

```
[7]: # create the FloPy temporal discretization object
tdis = flopy.mf6.modflow.mftdis.ModflowTdis(
    sim,
```

(continues on next page)

(continued from previous page)

```

pname="tdis",
time_units="DAYS",
nper=2,
perioddata=[(1.0, 1, 1.0), (1.0, 1, 1.0)],
)

```

Next, `time_units` is reassigned a value after construction by using TDIS's `time_units` attribute.

```
[8]: tdis.time_units = "MONTHS"
```

## Setting MODFLOW Boolean Flags

Boolean flags can be assigned a True or False value. In the example below `nogrb` is assigned a value of True and then changed to false.

For this example, first some values are first defined for the discretization package

```
[9]: nlay = 3
h = 50.0
length = 400.0
n = 10
bot = np.linspace(-h / nlay, -h, nlay)
delrow = delcol = length / (n - 1)

```

Below the discretization package is created. The MODFLOW `nogrb` option assigned a value of True, switching this option on.

```
[10]: dis = flopy.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
    nogrb=True,
    nlay=nlay,
    nrow=n,
    ncol=n,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)

```

The `nogrb` option is then switched off by setting the DIS package's `nogrb` attribute to False.

```
[11]: dis.nogrb = False
```

Boolean flags with an additional optional flag can either be specified by:

1. Specifying the entire line as it would be displayed in the package file as a string (`xt3doptions="xt3d rhs"`)
2. Specifying each flag name in a list (`xt3doptions=["xt3d", "rhs"]`)

To turn off both flags use an empty string (`xt3doptions=""`) or an empty list (`xt3doptions=[]`).

First, an NPF package is created. `xt3doptions` can either be turned on or off, and if it is on `rhs` can optionally be turned on. `xt3doptions` is set to the string "xt3d rhs", turning both options on.

```
[12]: # create the node property flow package with xt3doptions as single
npf = flopy.mf6.modflow.mfgwfnpf.ModflowGwfnpf(
    gwf,
    rewet_record="REWET WETFCT 1.0 IWETIT 1 IHDWET 0",
    pname="npf",
    icelltype=1,
    k=1.0,
    save_flows=True,
    xt3doptions="xt3d rhs",
)

<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7fe366ea1a90>
<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7fe366ea1b80>
```

Next, the rhs option is turned off by setting `xt3doptions` to the string “xt3d”.

```
[13]: npf.xt3doptions = "xt3d"
```

Finally, both `xt3d` and `rhs` are turned off by setting `xt3doptions` to an empty string.

```
[14]: npf.xt3doptions = ""
```

## Retrieving MODFLOW Scalar Data

MODFLOW scalar data can be retrieved with `get_data`, `repr/str`, or `get_file_entry`.

Re-trieval Method	Description
<code>get_data</code>	Returns scalar value
<code>repr/str</code>	Returns string with a header describing how data is stored (internal, external) with a string representation of the data on the next line
<code>get_file_entry</code>	Returns string with the scalar keyword (if any) followed by a space and a string representation of the scalar value (if any). This is the format used by the MODFLOW-6 package file. This is the format used by the MODFLOW-6 package file.

The IMS package’s `complexity` option and the NPF package’s `xt3doptions` are printed below using the different data retrieval methods highlighted above.

First the complexity data is printed using the `get_data` method.

```
[15]: print(ims.complexity.get_data())

simple
```

The `xt3doptions` data can also be printed with `get_data`.

```
[16]: print(npf.xt3doptions.get_data())

[]
```

The complexity data is then printed with `repr`

```
[17]: print(repr(ims.complexity))
{internal}
('simple')
```

The xt3doptions data is printed with repr

```
[18]: print(str(npf.xt3doptions))
{internal}
([])
```

The complexity data is printed as it would appear in a MODFLOW 6 file using the `get_file_entry` method.

```
[19]: print(ims.complexity.get_file_entry())
COMPLEXITY  simple
```

The xt3doptions data is printed as it would appear in a MODFLOW 6 file using the `get_file_entry` method.

```
[20]: print(npf.xt3doptions.get_file_entry())
```

## MODFLOW 6: Working with MODFLOW List Data.

This tutorial shows how to view, access, and change the underlying data variables for MODFLOW 6 objects in FloPy. Interaction with a FloPy MODFLOW 6 model is different from other models, such as MODFLOW-2005, MT3D, and SEAWAT, for example.

FloPy stores model data in data objects (`MFDdataArray`, `MFDdataList`, `MFDdataScalar` objects) that are accessible from packages. Data can be added to a package by using the appropriate parameters when the package is constructed and through package attributes.

The MODFLOW 6 simulation structure is arranged in the following generalized way:

```
Simulation --> Package --> DATA

Simulation --> Model --> Package (--> Package) --> DATA
```

This tutorial focuses on MODFLOW Data from the `PackageData`, `ConnectionData`, `StressPeriodData`, and other similar blocks. These blocks contain data with columns, data that fits into a numpy recarray, pandas data frame, or a spreadsheet with column headers. These data are stored by FloPy in a `MFList` or `MFTtransientList` object and are referred to as MODFLOW list data.

## Introduction to MODFLOW List Data

MODFLOW contains list data that can be conveniently stored in a numpy recarray or a pandas dataframe. These data are either a single or multiple row of data, with each column containing the same data type.

Some MODFLOW list data only contains a single row, like the OC package's `head print_format` option and the NPF package's `rewet_record`. Other MODFLOW list data can contain multiple rows, like the MAW package's `packagedata` and `connectiondata`. FloPy stores both single row and multiple row list data in `MFList` objects.

MODFLOW stress period data can contain lists of data for one or more stress periods. FloPy stores stress period list data in `MFTransientList` objects. Note that not all MODFLOW stress period data is "list" data that fits neatly in a recarray or a panda's dataframe. Some packages including RCH and EVT have a `READASARRAYS` option that allows stress period data to be inputted as an array. When `READASARRAYS` is selected FloPy stores stress period array data in an `MFTransientArray` object (see tutorial 8).

Examples of using FloPy to store, update, and retrieve different types of MODFLOW list data are given below. The examples start by first creating a simulation (`MFSimulation`) and a model (`MFModel`) object in FloPy.

```
[1]: # package import
import os

[2]: import numpy as np

[3]: import flopy

[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)

[5]: # create the Flopy simulation and tdis objects
sim = flopy.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)
tdis = flopy.mf6.modflow.mftdis.ModflowTdis(
    sim,
    pname="tdis",
    time_units="DAYS",
    nper=2,
    perioddata=[(1.0, 1, 1.0), (1.0, 1, 1.0)],
)
# create the Flopy groundwater flow (gwf) model object
model_name_file = f"{name}.nam"
gwf = flopy.mf6.ModflowGwf(sim, modelname=name, model_name_file=model_name_file)
# create the flopy iterative model solver (ims) package object
ims = flopy.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
# create the discretization package
bot = np.linspace(-50.0 / 3.0, -3.0, 3)
delrow = delcol = 4.0
dis = flopy.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
```

(continues on next page)



(continued from previous page)

```

nogrb=True,
nlay=3,
nrow=10,
ncol=10,
delr=delrow,
delc=delcol,
top=0.0,
botm=bot,
)

```

## Adding MODFLOW Package Data, Connection Data, and Option Lists

MODFLOW Package data, connection data, and option lists are stored by FloPy as numpy recarrays. FloPy does accept numpy recarrays as input, but does has other supported formats discussed below.

MODFLOW option lists that only contain a single row or data can be either specified by:

1. Specifying a string containing the entire line as it would be displayed in the package file (`rewet_record="REWET WETFCT 1.0 IWETIT 1 IHDWET 0"`)
2. Specifying the data in a tuple within a list (`rewet_record=[("WETFCT", 1.0, "IWETIT", 1, "IHDWET", 0)]`)

In the example below the npf package is created setting the `rewet_record` option to a string of text as would be typed into the package file.

```

[6]: npf = flopy.mf6.modflow.mfgwfnf.ModflowGwfnf(
    gwf,
    rewet_record="REWET WETFCT 1.0 IWETIT 1 IHDWET 0",
    pname="npf",
    icelltype=1,
    k=1.0,
    save_flows=True,
    xt3doptions="xt3d rhs",
)

<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7cd6c1fbc40>
<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7cd6c1fbc70>

```

`rewet_record` is then set using the npf package's `rewet_record` property. This time 'rewet\_record' is defined using a tuple within a list.

```

[7]: npf.rewet_record = [("WETFCT", 1.1, "IWETIT", 0, "IHDWET", 1)]

```

MODFLOW multirow lists, like package data and connection data, can be specified:

1. As a list of tuples where each tuple represents a row in the list (`stress_period_data = [(1, 2, 3), (1, 7, 3), (25, 0)]`)
2. As a numpy recarray. Building a numpy recarray is more complicated and is beyond the scope of this guide.

In the example below the chd package is created, setting `stress_period_data` as a list of tuples.

We build the chd package using an array of tuples for `stress_period_data` `stress_period_data = [(first_chd_cell, head), (second_chd_cell, head), ...]` Note that the cellid information (layer, row, column) is encapsulated in a tuple.

```
[8]: stress_period_data = [((1, 10, 10), 100.0), ((1, 10, 11), 105.0)]
# build chd package
chd = flopy.mf6.modflow.mfgwfchd.ModflowGwfchd(
    gwf,
    pname="chd",
    maxbound=len(stress_period_data),
    stress_period_data=stress_period_data,
    save_flows=True,
)
```

### Adding Stress Period List Data

MODFLOW stress period data is stored by FloPy as a dictionary of numpy recarrays, where each dictionary key is a zero-based stress period and each dictionary value is a recarray containing the stress period data for that stress period. FloPy keeps this stress period data in a `MFTransientList` object and this data type is referred to as a transient list.

FloPy accepts stress period data as a dictionary of numpy recarrays, but also supports replacing the recarrays with lists of tuples discussed above. Stress period data spanning multiple stress periods must be specified as a dictionary of lists where the dictionary key is the stress period expressed as a zero-based integer.

The example below creates `stress_period_data` for the wel package with the first stress period containing a single well and the second stress period empty. When empty stress period data is entered FloPy writes an empty stress period block to the package file.

First we create wel package with `stress_period_data` dictionary keys as zero-based integers so key “0” is stress period 1

```
[9]: stress_period_data = {
    0: [((2, 3, 1), -25.0)], # stress period 1 well data
    1: [],
} # stress period 2 well data is empty
```

Then, using the dictionary created above, we build the wel package.

```
[10]: wel = flopy.mf6.ModflowGwfwel(
    gwf,
    print_input=True,
    print_flows=True,
    stress_period_data=stress_period_data,
    save_flows=False,
    pname="WEL-1",
)
```

### Retrieving MODFLOW Package Data, Connection Data, and Option Lists

MODFLOW package data, connection data, and option lists can be retrieved with `get_data`, `array`, `repr/str`, or `get_file_entry`.

Retrieval Method	Description
<code>get_data</code>	Returns recarray
<code>array</code>	Return recarray
<code>repr/str</code>	Returns string with storage information followed by recarray's <code>repr/str</code>
<code>get_file_entry</code>	Returns string containing data formatted for the MODFLOW-6 package file. Certain zero-based numbers, like layer, row, column, are converted to one-based numbers.

The NPF package's `rewet_record` is printed below using the different data retrieval methods highlighted above.

First we use the `get_data` method to get the `rewet_record` as a recarray.

```
[11]: print(npf.rewet_record.get_data())
[('WETFCT', 1.1, 'IWETIT', 0, 'IHDWET', 1)]
```

Next we use the `array` method, which also returns a recarray.

```
[12]: print(npf.rewet_record.array)
[('WETFCT', 1.1, 'IWETIT', 0, 'IHDWET', 1)]
```

Then we use `repr` to print a string representation of `rewet_record`.

```
[13]: print(repr(npf.rewet_record))
{internal}
(rec.array([('WETFCT', 1.1, 'IWETIT', 0, 'IHDWET', 1)],
          dtype=[('wetfct_label', '0'), ('wetfct', '<f8'), ('iwetit_label', '0'), (
→ 'iwetit', '<i8'), ('ihdwet_label', '0'), ('ihdwet', '<i8')]))
```

Using `str` prints a similar string representation of `rewet_record`.

```
[14]: print(str(npf.rewet_record))
{internal}
[('WETFCT', 1.1, 'IWETIT', 0, 'IHDWET', 1)]
```

Last, using the `get_file_entry` method the data is printed as it would appear in a MODFLOW 6 file.

```
[15]: print(npf.rewet_record.get_file_entry())
REWET  WETFCT      1.100000000 IWETIT  0  IHDWET  1
```

## Retrieving MODFLOW Stress Period List Data

Stress period data can be retrieved with `get_data`, `array`, `repr/str`, or `get_file_entry`.

Retrieval Method	Description
<code>get_data</code>	Returns dictionary of recarrays
<code>array</code>	Return single recarray for all stress periods
<code>repr/str</code>	Returns string with storage information followed by recarray <code>repr/str</code> for each recarray
<code>get_file_entry(key)</code>	Returns string containing data formatted for the MODFLOW-6 package file for the stress period specified by key

The WEL package's `stress_period_data` is printed below using the different data retrieval methods highlighted above.

First we use the `get_data` method to get the stress period data as a dictionary of recarrays.

```
[16]: print(wel.stress_period_data.get_data())
{0: rec.array([(2, 3, 1), -25.]),
      dtype=[('cellid', '0'), ('q', '<f8')])}
```

Next we use the `array` attribute to get the stress period data as a single recarray.

```
[17]: print(wel.stress_period_data.array)
[rec.array([(2, 3, 1), -25.]),
      dtype=[('cellid', '0'), ('q', '<f8')]), None]
```

`repr` can be used to generate a string representation of stress period data.

```
[18]: print(repr(wel.stress_period_data))
{internal}
(rec.array([(2, 3, 1), -25.]),
      dtype=[('cellid', '0'), ('q', '<f8')])}
```

`str` produces a similar string representation of stress period data.

```
[19]: print(str(wel.stress_period_data))
{internal}
([(2, 3, 1), -25.)]
```

The `get_file_entry` method prints the stress period data as it would appear in a MODFLOW 6 file.

```
[20]: print(wel.stress_period_data.get_file_entry(0))
 3 4 2      -25.00000000
```

## MODFLOW 6: Working with MODFLOW Grid Array Data

This tutorial shows how to view, access, and change the underlying data variables for MODFLOW 6 objects in FloPy. Interaction with a FloPy MODFLOW 6 model is different from other models, such as MODFLOW-2005, MT3D, and SEAWAT, for example.

FloPy stores model data in data objects (MFDataArray, MFDataList, MFDataScalar objects) that are accessible from packages. Data can be added to a package by using the appropriate parameters when the package is constructed and through package attributes.

The MODFLOW 6 simulation structure is arranged in the following generalized way:

```
Simulation --> Package --> DATA

Simulation --> Model --> Package (--> Package) --> DATA
```

This tutorial focuses on MODFLOW grid array data from the GridData and other similar blocks. These blocks contain data in a one or more dimensional array format organized by dimensions, which can include layer, row, column, and stress period. These data are stored by FloPy in a MFArray or MFTransientArray object and are referred to as array data.

### Introduction to MODFLOW Array Data

MODFLOW array data use the MFArray or MFTransientArray FloPy classes and are stored in numpy ndarrays. Most MODFLOW array data are two (row, column) or three (layer, row, column) dimensional and represent data on the model grid. Other MODFLOW array data contain data by stress period. The following list summarizes the different types of MODFLOW array data.

- Time-invariant multi-dimensional array data. This includes:
  1. One and two dimensional arrays that do not have a layer dimension. Examples include `top`, `delc`, and `delr`.
  2. Three dimensional arrays that can contain a layer dimension. Examples include `botm`, `idomain`, and `k`.
- Transient arrays that can change with time and therefore contain arrays of data for one or more stress periods. Examples include `irch` and `recharge` in the RCHA package.

In the example below a three dimensional ndarray is constructed for the DIS package's `botm` array. First, the a simulation and groundwater-flow model are set up.

```
[1]: # package import
import os

[2]: import numpy as np

[3]: import flopy

[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)
# create the FloPy simulation and tdis objects
sim = flopy.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
```

(continues on next page)

(continued from previous page)

```

)
tdis = flopy.mf6.modflow.mftdis.ModflowTdis(
    sim,
    pname="tdis",
    time_units="DAYS",
    nper=2,
    perioddata=[(1.0, 1, 1.0), (1.0, 1, 1.0)],
)
# create the Flopy groundwater flow (gwf) model object
model_name_file = f"{name}.nam"
gwf = flopy.mf6.ModflowGwf(sim, modelname=name, model_name_file=model_name_file)
# create the flopy iterative model solver (ims) package object
ims = flopy.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")

```

Then a three-dimensional ndarray of floating point values is created using numpy's linspace method.

```

[5]: bot = np.linspace(-50.0 / 3.0, -3.0, 3)
    delrow = delcol = 4.0

```

The DIS package is then created passing the three-dimensional array to the botm parameter. The botm array defines the model's cell bottom elevations.

```

[6]: dis = flopy.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
    nogrb=True,
    nlay=3,
    nrow=10,
    ncol=10,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)

```

## Adding MODFLOW Grid Array Data

MODFLOW grid array data, like the data found in the NPF package's GridData block, can be specified as:

1. A constant value
2. A n-dimensional list
3. A numpy ndarray

Additionally, layered grid data (generally arrays with a layer dimension) can be specified by layer.

In the example below icelltype is specified as constants by layer, k is specified as a numpy ndarray, k22 is specified as an array by layer, and k33 is specified as a constant.

First k is set up as a 3 layer, by 10 row, by 10 column array with all values set to 10.0 using numpy's full method.

```

[7]: k = np.full((3, 10, 10), 10.0)

```

Next k22 is set up as a three dimensional list of nested lists. This option can be useful for those that are familiar with python lists but are not familiar with the numpy library.

```
[8]: k22_row = []
    for row in range(0, 10):
        k22_row.append(8.0)
    k22_layer = []
    for col in range(0, 10):
        k22_layer.append(k22_row)
    k22 = [k22_layer, k22_layer, k22_layer]
```

K33 is set up as a single constant value. Whenever an array has all the same values the easiest and most efficient way to set it up is as a constant value. Constant values also take less space to store.

```
[9]: k33 = 1.0
```

The k, k22, and k33 values defined above are then passed in on construction of the npf package.

```
[10]: npf = flopy.mf6.ModflowGwfnpf(
    gwf,
    pname="npf",
    save_flows=True,
    icelltype=[1, 1, 1],
    k=k,
    k22=k22,
    k33=k33,
    xt3doptions="xt3d rhs",
    rewet_record="REWET WETFCT 1.0 IWETIT 1 IHDWET 0",
)

<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7fb26e5ff880>
<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7fb26e5ff8b0>
```

## Layered Data

When we look at what will be written to the npf input file, we see that the entire npf.k22 array is written as one long array with the number of values equal to nlay \* nrow \* ncol. And this whole-array specification may be of use in some cases. Often times, however, it is easier to work with each layer separately. An MFArray object, such as npf.k22 can be converted to a layered array as follows.

```
[11]: npf.k22.make_layered()
```

By changing npf.k22 to layered, we are then able to manage each layer separately. Before doing so, however, we need to pass in data that can be separated into three layers. An array of the correct size is one option.

```
[12]: shp = npf.k22.array.shape
    a = np.arange(shp[0] * shp[1] * shp[2]).reshape(shp)
    npf.k22.set_data(a)
```

Now that npf.k22 has been set to be layered, if we print information about it, we see that each layer is stored separately, however, npf.k22.array will still return a full three-dimensional array.

```
[13]: print(type(npf.k22))
    print(npf.k22)
```

```

<class 'flopY.mf6.data.mfdataarray.MFArray'>
Layer_1{internal}
([[ 0  1  2  3  4  5  6  7  8  9]
 [10 11 12 13 14 15 16 17 18 19]
 [20 21 22 23 24 25 26 27 28 29]
 [30 31 32 33 34 35 36 37 38 39]
 [40 41 42 43 44 45 46 47 48 49]
 [50 51 52 53 54 55 56 57 58 59]
 [60 61 62 63 64 65 66 67 68 69]
 [70 71 72 73 74 75 76 77 78 79]
 [80 81 82 83 84 85 86 87 88 89]
 [90 91 92 93 94 95 96 97 98 99]])
Layer_2{internal}
([[100 101 102 103 104 105 106 107 108 109]
 [110 111 112 113 114 115 116 117 118 119]
 [120 121 122 123 124 125 126 127 128 129]
 [130 131 132 133 134 135 136 137 138 139]
 [140 141 142 143 144 145 146 147 148 149]
 [150 151 152 153 154 155 156 157 158 159]
 [160 161 162 163 164 165 166 167 168 169]
 [170 171 172 173 174 175 176 177 178 179]
 [180 181 182 183 184 185 186 187 188 189]
 [190 191 192 193 194 195 196 197 198 199]])
Layer_3{internal}
([[200 201 202 203 204 205 206 207 208 209]
 [210 211 212 213 214 215 216 217 218 219]
 [220 221 222 223 224 225 226 227 228 229]
 [230 231 232 233 234 235 236 237 238 239]
 [240 241 242 243 244 245 246 247 248 249]
 [250 251 252 253 254 255 256 257 258 259]
 [260 261 262 263 264 265 266 267 268 269]
 [270 271 272 273 274 275 276 277 278 279]
 [280 281 282 283 284 285 286 287 288 289]
 [290 291 292 293 294 295 296 297 298 299]])

```

We also see that each layer is printed separately to the npf Package input file, and that the LAYERED keyword is activated:

```
[14]: print(npf.k22.get_file_entry())
```

```

k22  LAYERED
      INTERNAL  FACTOR  1.0
      0.00000000    1.00000000    2.00000000    3.00000000    4.
↪ 00000000    5.00000000    6.00000000    7.00000000    8.00000000    9.
↪ 00000000
      10.00000000   11.00000000   12.00000000   13.00000000   14.
↪ 00000000   15.00000000   16.00000000   17.00000000   18.00000000   19.
↪ 00000000
      20.00000000   21.00000000   22.00000000   23.00000000   24.
↪ 00000000   25.00000000   26.00000000   27.00000000   28.00000000   29.
↪ 00000000
      30.00000000   31.00000000   32.00000000   33.00000000   34.
↪ 00000000   35.00000000   36.00000000   37.00000000   38.00000000   39.
↪ 00000000

```

(continues on next page)



(continued from previous page)

```

40.00000000    41.00000000    42.00000000    43.00000000    44.
→ 00000000    45.00000000    46.00000000    47.00000000    48.00000000    49.
→ 00000000
50.00000000    51.00000000    52.00000000    53.00000000    54.
→ 00000000    55.00000000    56.00000000    57.00000000    58.00000000    59.
→ 00000000
60.00000000    61.00000000    62.00000000    63.00000000    64.
→ 00000000    65.00000000    66.00000000    67.00000000    68.00000000    69.
→ 00000000
70.00000000    71.00000000    72.00000000    73.00000000    74.
→ 00000000    75.00000000    76.00000000    77.00000000    78.00000000    79.
→ 00000000
80.00000000    81.00000000    82.00000000    83.00000000    84.
→ 00000000    85.00000000    86.00000000    87.00000000    88.00000000    89.
→ 00000000
90.00000000    91.00000000    92.00000000    93.00000000    94.
→ 00000000    95.00000000    96.00000000    97.00000000    98.00000000    99.
→ 00000000
INTERNAL FACTOR 1.0
100.00000000   101.00000000   102.00000000   103.00000000   104.
→ 00000000   105.00000000   106.00000000   107.00000000   108.00000000  109.
→ 00000000
110.00000000   111.00000000   112.00000000   113.00000000   114.
→ 00000000   115.00000000   116.00000000   117.00000000   118.00000000  119.
→ 00000000
120.00000000   121.00000000   122.00000000   123.00000000   124.
→ 00000000   125.00000000   126.00000000   127.00000000   128.00000000  129.
→ 00000000
130.00000000   131.00000000   132.00000000   133.00000000   134.
→ 00000000   135.00000000   136.00000000   137.00000000   138.00000000  139.
→ 00000000
140.00000000   141.00000000   142.00000000   143.00000000   144.
→ 00000000   145.00000000   146.00000000   147.00000000   148.00000000  149.
→ 00000000
150.00000000   151.00000000   152.00000000   153.00000000   154.
→ 00000000   155.00000000   156.00000000   157.00000000   158.00000000  159.
→ 00000000
160.00000000   161.00000000   162.00000000   163.00000000   164.
→ 00000000   165.00000000   166.00000000   167.00000000   168.00000000  169.
→ 00000000
170.00000000   171.00000000   172.00000000   173.00000000   174.
→ 00000000   175.00000000   176.00000000   177.00000000   178.00000000  179.
→ 00000000
180.00000000   181.00000000   182.00000000   183.00000000   184.
→ 00000000   185.00000000   186.00000000   187.00000000   188.00000000  189.
→ 00000000
190.00000000   191.00000000   192.00000000   193.00000000   194.
→ 00000000   195.00000000   196.00000000   197.00000000   198.00000000  199.
→ 00000000
INTERNAL FACTOR 1.0
200.00000000   201.00000000   202.00000000   203.00000000   204.
→ 00000000   205.00000000   206.00000000   207.00000000   208.00000000  209.
→ 00000000

```

(continues on next page)

(continued from previous page)

```

      210.000000000      211.000000000      212.000000000      213.000000000      214.
→ 000000000      215.000000000      216.000000000      217.000000000      218.000000000      219.
→ 000000000
      220.000000000      221.000000000      222.000000000      223.000000000      224.
→ 000000000      225.000000000      226.000000000      227.000000000      228.000000000      229.
→ 000000000
      230.000000000      231.000000000      232.000000000      233.000000000      234.
→ 000000000      235.000000000      236.000000000      237.000000000      238.000000000      239.
→ 000000000
      240.000000000      241.000000000      242.000000000      243.000000000      244.
→ 000000000      245.000000000      246.000000000      247.000000000      248.000000000      249.
→ 000000000
      250.000000000      251.000000000      252.000000000      253.000000000      254.
→ 000000000      255.000000000      256.000000000      257.000000000      258.000000000      259.
→ 000000000
      260.000000000      261.000000000      262.000000000      263.000000000      264.
→ 000000000      265.000000000      266.000000000      267.000000000      268.000000000      269.
→ 000000000
      270.000000000      271.000000000      272.000000000      273.000000000      274.
→ 000000000      275.000000000      276.000000000      277.000000000      278.000000000      279.
→ 000000000
      280.000000000      281.000000000      282.000000000      283.000000000      284.
→ 000000000      285.000000000      286.000000000      287.000000000      288.000000000      289.
→ 000000000
      290.000000000      291.000000000      292.000000000      293.000000000      294.
→ 000000000      295.000000000      296.000000000      297.000000000      298.000000000      299.
→ 000000000

```

Working with a layered array provides lots of flexibility. For example, constants can be set for some layers, but arrays for others:

```
[15]: npf.k22.set_data([1, a[2], 200])
print(npf.k22.get_file_entry())
```

```

k22  LAYERED
      CONSTANT      1.000000000
      INTERNAL FACTOR 1.0
      200.000000000      201.000000000      202.000000000      203.000000000      204.
→ 000000000      205.000000000      206.000000000      207.000000000      208.000000000      209.
→ 000000000
      210.000000000      211.000000000      212.000000000      213.000000000      214.
→ 000000000      215.000000000      216.000000000      217.000000000      218.000000000      219.
→ 000000000
      220.000000000      221.000000000      222.000000000      223.000000000      224.
→ 000000000      225.000000000      226.000000000      227.000000000      228.000000000      229.
→ 000000000
      230.000000000      231.000000000      232.000000000      233.000000000      234.
→ 000000000      235.000000000      236.000000000      237.000000000      238.000000000      239.
→ 000000000
      240.000000000      241.000000000      242.000000000      243.000000000      244.
→ 000000000      245.000000000      246.000000000      247.000000000      248.000000000      249.
→ 000000000

```

(continues on next page)

CONSTANT	200.000000000
----------	---------------

```
print(npf.k22.get_file_entry())
```

↔ 00000000

(continued from previous page)

	100.00000000	100.00000000	100.00000000	100.00000000	100.
→00000000	100.00000000	100.00000000	100.00000000	100.00000000	100.
→00000000					
CONSTANT	50.00000000				
INTERNAL	FACTOR	1.0	IPRN	14	
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					
	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000	30.00000000	30.00000000	30.00000000	30.00000000	30.
→00000000					

Here we say that the FACTOR has been set to 0.5 for the first layer and an alternative print flag is set for the last layer.

Because we are specifying a factor for the top layer, we can also see that the `get_data()` method returns the array without the factor applied

```
[17]: print(npf.k22.get_data())
```

[illegible]

(continues on next page)

(continued from previous page)

```
[100. 100. 100. 100. 100. 100. 100. 100. 100. 100.]]

[[ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]
 [ 50.  50.  50.  50.  50.  50.  50.  50.  50.  50.]]

[[ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]
 [ 30.  30.  30.  30.  30.  30.  30.  30.  30.  30.]]]
```

whereas the array property returns the array with the factor applied

```
[18]: print(npf.k22.array)
```

```
[[[50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]]

[[[50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]
 [50. 50. 50. 50. 50. 50. 50. 50. 50. 50.]]

[[[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
 [30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
 [30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
```

(continues on next page)

(continued from previous page)

```
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]
[30. 30. 30. 30. 30. 30. 30. 30. 30. 30.]]]
```

## Adding MODFLOW Stress Period Array Data

Transient array data spanning multiple stress periods must be specified as a dictionary of arrays, where the dictionary key is the stress period, expressed as a zero-based integer, and the dictionary value is the grid data for that stress period.

In the following example a RCHA package is created. First a dictionary is created that contains recharge for the model's two stress periods. Recharge is specified as a constant value in this example, though it could also be specified as a 3-dimensional ndarray or list of lists.

```
[19]: rch_sp1 = 0.01
      rch_sp2 = 0.03
      rch_spd = {0: rch_sp1, 1: rch_sp2}
```

The RCHA package is created and the dictionary constructed above is passed in as the `recharge` parameter.

```
[20]: rch = flopy.mf6.ModflowGwfrcha(
      gwf, readasarrays=True, pname="rch", print_input=True, recharge=rch_spd
      )
```

## Retrieving Grid Array Data

Grid data can be retrieved with `get_data`, `array`, `[]`, `repr/str`, or `get_file_entry`.

Retrieval Method	Description
<code>get_data</code>	Returns ndarray of data without multiplier applied, unless the <code>apply_mult</code> parameter is set to True
<code>array</code>	Returns ndarray of data with multiplier applied
<code>[]</code>	Returns a particular layer of data if data is layered, otherwise is an array index
<code>repr/str</code>	Returns string with storage information followed by ndarray repr/str
<code>get_file_entry(layer)</code>	Returns string containing data formatted for the MODFLOW-6 package file. If layer is not specified returns all layers, otherwise returns just the layer specified.

Below the NPF `k` array is retrieved using the various methods highlighted above.

First, we use the `get_data` method to get `k` as an ndarray.

```
[21]: print(npf.k.get_data())

[[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
```

(continues on next page)

(continued from previous page)

```

[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]

[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]

[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]

```

Next, we use the array attribute which also gets k as an ndarray.

```
[22]: print(npf.k.array)
```

```

[[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]

[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]

```

(continues on next page)

(continued from previous page)

```
[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]

[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]
```

We can also use the `[]` to get a single layer of data as an ndarray.

```
[23]: print(npf.k[0])
```

```
[[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
 [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]]
```

`repr` gives a string representation of the data.

```
[24]: print(repr(npf.k))
```

```
Layer_1{internal}
(array([[10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.]])
Layer_2{internal}
(array([[10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
       [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.]])
```

(continues on next page)



(continued from previous page)

```

        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.])))
Layer_3{internal}
(array([[10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.],
        [10., 10., 10., 10., 10., 10., 10., 10., 10., 10.])))

```

str gives a similar string representation of the data.

```
[25]: print(str(npf.k))
```

```

Layer_1{internal}
([[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]])
Layer_2{internal}
([[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]])
Layer_3{internal}
([[10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]
  [10. 10. 10. 10. 10. 10. 10. 10. 10. 10.]])

```

The method `get_file_entry` prints the data as it would appear in a MODFLOW 6 file.

```
[26]: print(npf.k.get_file_entry())
```

[illegible]

(continues on next page)

[illegible]

## Retrieving MODFLOW Stress Period Array Data

Transient array data can be retrieved with `get_data`, `array`, `repr/str`, or `get_file_entry`.

Retrieval Method	Description
<code>get_data</code>	Returns dictionary of ndarrays without multiplier applied. The dictionary key is the stress period as a zero-based integer.
<code>array</code>	Returns ndarray of data for all stress periods (stress period is an added dimension)
<code>repr/str</code>	Returns string with storage information followed by ndarray repr/str for all stress periods
<code>get_file_entry(layer)</code>	Returns string containing data formatted for the MODFLOW-6 package file. Use to specify a stress period (zero-based integer).

Below the RCHA recharge array is retrieved using the various methods highlighted above.

First, we use the `get_data` method to get the recharge data as a dictionary of ndarrays. The dictionary key is a the stress period (zero based).

```
[27]: print(rch.recharge.get_data())
{0: array([[0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01],
          [0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01, 0.01]]), 1: array([[0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03],
          [0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03, 0.03]])}
```

Next, we use the `array` attribute to get the data as an 4-dimensional ndarray.

```
[28]: print(rch.recharge.array)
[[[0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]
  [0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]]]
```

(continues on next page)

(continued from previous page)

```
[0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01]]]
```

```
[[[0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]
  [0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03 0.03]]]]
```

repr gives a string representation of the data.

```
[29]: print(repr(rch.recharge))
```

```
{constant 0.03}
```

str gives a similar representation of the data.

```
[30]: print(str(rch.recharge))
```

```
{constant 0.03}
```

We can use the `get_file_entry` method to get the data as it would appear in a MODFLOW 6 file for a specific stress period. In this case we are getting the data for stress period 2 (stress periods are treated as 0-based in FloPy).

```
[31]: print(rch.recharge.get_file_entry(1))
```

```
recharge
  CONSTANT      0.030000000
```

## MODFLOW 6: Data Storage Information - How and Where to Store MODFLOW-6 Data

This tutorial shows the different options for storing MODFLOW data in FloPy. Interaction with a FloPy MODFLOW 6 model is different from other models, such as MODFLOW-2005, MT3D, and SEAWAT, for example.

FloPy stores model data in data objects (`MFDdataArray`, `MFDdataList`, `MFDdataScalar` objects) that are accessible from packages. Data can be added to a package by using the appropriate parameters when the package is constructed and through package attributes.

The MODFLOW 6 simulation structure is arranged in the following generalized way:

```
Simulation --> Package --> DATA
Simulation --> Model --> Package (--> Package) --> DATA
```

This tutorial focuses on the different storage options for MODFLOW data.

## Introduction to Data Storage Information

MODFLOW array and list data can either be stored internally or externally in text or binary files. Additionally array data can have a factor applied to them and can have a format flag/code to define how these data will be formatted. This data storage information is specified within a python dictionary. The python dictionary must contain a “data” key where the data is stored and supports several other keys that determine how and where the data is stored.

The following code sets up a basic simulation with a groundwater flow model. for the example below.

```
[1]: # package import
import os

[2]: import numpy as np

[3]: import flopY

[4]: # set up where simulation workspace will be stored
workspace = os.path.join("data", "mf6_working_with_data")
name = "example_1"
if not os.path.exists(workspace):
    os.makedirs(workspace)
# create the FloPy simulation and tdis objects
sim = flopY.mf6.MFSimulation(
    sim_name=name, exe_name="mf6", version="mf6", sim_ws=workspace
)
tdis = flopY.mf6.modflow.mftdis.ModflowTdis(
    sim,
    pname="tdis",
    time_units="DAYS",
    nper=2,
    perioddata=[(1.0, 1, 1.0), (1.0, 1, 1.0)],
)
# create the Flopy groundwater flow (gwf) model object
model_nam_file = f"{name}.nam"
gwf = flopY.mf6.ModflowGwf(sim, modelname=name, model_nam_file=model_nam_file)
# create the flopY iterative model solver (ims) package object
ims = flopY.mf6.modflow.mfims.ModflowIms(sim, pname="ims", complexity="SIMPLE")
# create the discretization package
bot = np.linspace(-50.0 / 3.0, -3.0, 3)
delrow = delcol = 4.0
dis = flopY.mf6.modflow.mfgwfdis.ModflowGwfdis(
    gwf,
    pname="dis",
    nogrb=True,
    nlay=3,
    nrow=10,
    ncol=10,
    delr=delrow,
    delc=delcol,
    top=0.0,
    botm=bot,
)
```

## Setting up a Data Storage Information Dictionary

To store data externally add a `filename` key to the dictionary whose value is the file where you want to store the data. Add a `binary` key with value `True` to make the file a binary file. Add a `prn` key whose value is a format code to set the format code for the data. For array data add a `factor` key whose value is a positive floating point number to add a factor/multiplier for the array.

Below a dictionary is created that defines how a `k33` array will be stored. The dictionary specifies that the `k33` array be stored in the binary file `k33.txt` with a factor of 1.0 applied to the array and a print code of 1. The `k33` array data is constructed as a numpy array.

```
[5]: k33_values = np.full((3, 10, 10), 1.1)
k33 = {
    "filename": "k33.txt",
    "factor": 1.0,
    "data": k33_values,
    "iprn": 1,
    "binary": "True",
}
```

The NPF package is then created with the `k33` array in an external binary file. This binary file is created when the simulation method `write_simulation` is called.

```
[6]: npf = flopy.mf6.ModflowGwfnpf(
    gwf,
    pname="npf",
    save_flows=True,
    icelltype=[1, 1, 1],
    k=10.0,
    k22=5.0,
    k33=k33,
    xt3doptions="xt3d rhs",
    rewet_record="REWET WETFCT 1.0 IWETIT 1 IHDWET 0",
)

<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7f6bd6393100>
<flopy.mf6.data.mfstructure.MFDataItemStructure object at 0x7f6bd6393130>
```

External files can be set for specific layers of data. If we want to store the bottom elevations for the third model layer to an external file, then the dictionary that we pass in for the third layer can be given a “filename” key.

```
[7]: a0 = {"factor": 0.5, "iprn": 1, "data": np.ones((10, 10))}
a1 = -100
a2 = {
    "filename": "dis.botm.3.txt",
    "factor": 2.0,
    "iprn": 1,
    "data": -100 * np.ones((10, 10)),
}
```

A list containing data for the three specified layers is then passed in to the `botm` object’s `set_data` method.

```
[8]: dis.botm.set_data([a0, a1, a2])
print(dis.botm.get_file_entry())
```

```

botm LAYERED
INTERNAL FACTOR 0.5 IPRN 1
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
1.000000000 1.000000000 1.000000000 1.000000000 1.
→000000000 1.000000000 1.000000000 1.000000000 1.
→000000000
CONSTANT -100.000000000
OPEN/CLOSE 'dis.botm.3.txt' FACTOR 2.0 IPRN 1

```

Note that we could have also specified `botm` this way as part of the original `flopY.mf6.ModflowGwfdis` constructor:

```

[9]: a0 = {"factor": 0.5, "iprn": 1, "data": np.ones((10, 10))}
a1 = -100
a2 = {
    "filename": "dis.botm.3.bin",
    "factor": 2.0,
    "iprn": 1,
    "data": -100 * np.ones((4, 5)),
    "binary": True,
}
botm = [a0, a1, a2]
flopY.mf6.ModflowGwfdis(gwf, nlay=3, nrow=10, ncol=10, botm=botm)

```

WARNING: Package with type `dis` already exists. Replacing existing package.

```

[9]: package_name = dis
filename = example_1.dis

```

(continues on next page)



(continued from previous page)

```

package_type = dis
model_or_simulation_package = model
model_name = example_1

Block dimensions
-----
nlay
{internal}
(3)

nrow
{internal}
(10)

ncol
{internal}
(10)

Block griddata
-----
delr
{constant 1.0}

delc
{constant 1.0}

top
{constant 1.0}

botm
Layer_1{internal, factor 0.5, iprn 1}
(array([[1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.],
        [1., 1., 1., 1., 1., 1., 1., 1., 1., 1.]])
Layer_2{constant -100}

```

### 6.1.3 MODFLOW 6 Output Tutorials

Contents:

#### Accessing MODFLOW 6 Output

This tutorial shows how to access output from MODFLOW 6 models and packages by using the built in `.output` attribute on any MODFLOW 6 model or package object

```
[1]: import os
import platform

[2]: import numpy as np

[3]: # ## Package import
import flopy

[4]: # ## Load a simple demonstration model
exe_name = "mf6"
if platform.system().lower() == "windows":
    exe_name += ".exe"
ws = os.path.abspath(os.path.dirname(""))
if os.path.split(ws)[-1] == "modflow6output":
    sim_ws = os.path.join(ws, "..", "..", "data", "mf6", "test001e_UZF_3lay")
else:
    sim_ws = os.path.join(
        ws, "..", "..", "examples", "data", "mf6", "test001e_UZF_3lay"
    )
# load the model
sim = flopy.mf6.MFSimulation.load(
    sim_ws=sim_ws,
    exe_name=exe_name,
    verbosity_level=0,
)
# change the simulation path, rewrite the files, and run the model
sim_ws = os.path.join("...", "..", "autotest", "temp", "mf6_output")
sim.set_sim_path(sim_ws)
sim.write_simulation(silent=True)
sim.run_simulation(silent=True)

[4]: (True, [])
```

#### Get output using the `.output` attribute

The output attribute dynamically generates methods for each package based on the available output options within that package. A list of all available outputs are:



(continued from previous page)

[illegible]

(continues on next page)

(continues on next page)

## 6.1. Tutorials 81

(continued from previous page)

```

(1.24e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.28e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.32e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.36e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.40e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.44e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.48e+03, 0.000000000e+00, 0.      , 0., 0.      , 0., 0., 0.      ,
→ 0.      , 0.      , 0., 0., 0., 0.      , 0.      , 0.000000000e+00),
(1.52e+03, 0.000000000e+00, 0.      , 0., 128.0217841 , 0., 0., 0.02722978,
→ 108.61508013, 19.37931792, 0., 0., 0., 128.0217841 , 128.02162783, 1.22061576e-04),
(1.56e+03, 0.000000000e+00, 0.      , 0., 138.99381474, 0., 0., 0.02616677,
→ 103.79225125, 35.17524461, 0., 0., 0., 138.99381474, 138.99366263, 1.09439391e-04),
(1.60e+03, 0.000000000e+00, 0.      , 0., 136.4972012 , 0., 0., 0.0225728 ,
→ 89.06987566, 47.4046209 , 0., 0., 0., 136.4972012 , 136.49706937, 9.65814295e-05),
(1.64e+03, 0.000000000e+00, 0.      , 0., 134.35958704, 0., 0., 0.01957412,
→ 76.88688611, 57.45301299, 0., 0., 0., 134.35958704, 134.35947321, 8.47152128e-05),
(1.68e+03, 0.000000000e+00, 0.      , 0., 131.24481479, 0., 0., 0.01672315,
→ 65.43186869, 65.79613475, 0., 0., 0., 131.24481479, 131.24472659, 6.72047136e-05),
(1.72e+03, 0.000000000e+00, 0.      , 0., 123.13434058, 0., 0., 0.01312794,
→ 51.19484895, 71.92589496, 0., 0., 0., 123.13434058, 123.13387185, 3.80661214e-04),
(1.76e+03, 0.000000000e+00, 0.      , 0., 114.00353442, 0., 0., 0.0097074 ,
→ 37.75854966, 76.23496189, 0., 0., 0., 114.00353442, 114.00321895, 2.76719717e-04),
(1.80e+03, 0.000000000e+00, 0.      , 0., 110.11487407, 0., 0., 0.0078339 ,
→ 30.41322044, 79.693573 , 0., 0., 0., 110.11487407, 110.11462734, 2.24068325e-04),
(1.84e+03, 0.000000000e+00, 0.      , 0., 105.40602911, 0., 0., 0.00594997,
→ 23.06535254, 82.33456504, 0., 0., 0., 105.40602911, 105.40586755, 1.53273477e-04),
(1.88e+03, 0.000000000e+00, 0.      , 0., 95.08914871, 0., 0., 0.00307764,
→ 11.90628617, 83.17970019, 0., 0., 0., 95.08914871, 95.089064 , 8.90844871e-05),
(1.92e+03, 0.000000000e+00, 0.      , 0., 94.69475504, 0., 0., 0.00271043,
→ 10.48542653, 84.20654512, 0., 0., 0., 94.69475504, 94.69468209, 7.70440756e-05),
(1.96e+03, 0.000000000e+00, 0.      , 0., 89.77312957, 0., 0., 0.00134165,
→ 5.18451079, 84.58703172, 0., 0., 0., 89.77312957, 89.77288416, 2.73360282e-04),
(2.00e+03, 3.28550762e-05, 0.12927097, 0., 85.77949492, 0., 0., 0.00037754,
→ 1.45488492, 84.45346195, 0., 0., 0., 85.90879875, 85.90872441, 8.65285791e-05),
(2.04e+03, 1.11673220e-03, 4.33428447, 0., 79.06662935, 0., 0., 0.      ,
→ 0.      , 83.40218928, 0., 0., 0., 83.40203055, 83.40218928, -1.90324298e-04),
(2.08e+03, 9.50436281e-04, 3.6847171 , 0., 79.01606345, 0., 0., 0.      ,
→ 0.      , 82.70187216, 0., 0., 0., 82.70173099, 82.70187216, -1.70697486e-04),
(2.12e+03, 8.09420799e-04, 3.13589527, 0., 79.07017251, 0., 0., 0.      ,
→ 0.      , 82.20700075, 0., 0., 0., 82.2068772 , 82.20700075, -1.50282359e-04),
(2.16e+03, 1.74634716e-03, 6.76514808, 0., 74.44436606, 0., 0., 0.      ,
→ 0.      , 81.21149171, 0., 0., 0., 81.21126049, 81.21149171, -2.84711568e-04),
(2.20e+03, 2.91726961e-03, 11.31295605, 0., 67.97128273, 0., 0., 0.      ,
→ 0.      , 79.28753204, 0., 0., 0., 79.28715604, 79.28753204, -4.74219376e-04),
(2.24e+03, 3.18846934e-03, 12.36643397, 0., 65.05084871, 0., 0., 0.      ,
→ 0.      , 77.42085884, 0., 0., 0., 77.42047115, 77.42085884, -5.00756338e-04),

```

(continues on next page)

(continued from previous page)

```

(2.28e+03, 3.08245610e-03, 11.96212155, 0., 63.67724795, 0., 0., 0.
↳ 0.      , 75.64282768, 0., 0., 0., 75.64245196, 75.64282768, -4.96712518e-04),
(2.32e+03, 2.66394411e-03, 10.34112384, 0., 63.8844137 , 0., 0., 0.
↳ 0.      , 74.22852942, 0., 0., 0., 74.22820148, 74.22852942, -4.41794671e-04),
(2.36e+03, 2.31518433e-03, 8.99067397, 0., 64.05458652, 0., 0., 0.
↳ 0.      , 73.04786211, 0., 0., 0., 73.04757567, 73.04786211, -3.92124078e-04),
(2.40e+03, 2.17404830e-03, 8.44571365, 0., 63.52276663, 0., 0., 0.
↳ 0.      , 71.97090718, 0., 0., 0., 71.97065433, 71.97090718, -3.51328184e-04),
(2.44e+03, 2.81993508e-03, 10.96537535, 0., 59.39318153, 0., 0., 0.
↳ 0.      , 70.36169271, 0., 0., 0., 70.36137682, 70.36169271, -4.48957261e-04),
(2.48e+03, 2.99544059e-03, 11.65308129, 0., 57.07292771, 0., 0., 0.
↳ 0.      , 68.72930656, 0., 0., 0., 68.72900444, 68.72930656, -4.39583720e-04),
(2.52e+03, 4.00001313e-03, 15.57599202, 0., 50.80019371, 0., 0., 0.
↳ 0.      , 66.38055059, 0., 0., 0., 66.38018574, 66.38055059, -5.49633887e-04),
(2.56e+03, 3.81480656e-03, 14.86546946, 0., 49.32928447, 0., 0., 0.
↳ 0.      , 64.19891797, 0., 0., 0., 64.19856873, 64.19891797, -5.43997899e-04)],
dtype=[('totim', '<f8'), ('STOSSSTORAGE_IN', '<f8'), ('STOSYSTORAGE_IN', '<f8
↳ '), ('CHDCHD1_IN', '<f8'), ('UZFGWRCHUF1_IN', '<f8'), ('UZFGWDUZF1_IN', '<f8'), (
↳ 'UZFGWETUF1_IN', '<f8'), ('STOSSSTORAGE_OUT', '<f8'), ('STOSYSTORAGE_OUT', '<f8'), (
↳ 'CHDCHD1_OUT', '<f8'), ('UZFGWRCHUF1_OUT', '<f8'), ('UZFGWDUZF1_OUT', '<f8'), (
↳ 'UZFGWETUF1_OUT', '<f8'), ('TOTAL_IN', '<f8'), ('TOTAL_OUT', '<f8'), ('PERCENT_
↳ DIFFERENCE', '<f8')])

```

```

[8]: hds = ml.output.head()
hds.get_data()

```

```

[8]: array([[[-25.      , -24.93660487, -24.88816332, -24.85548043,
-24.83902108, -24.83902108, -24.85548043, -24.88816332,
-24.93660487, -25.      ]],

[[[-25.      , -24.93660487, -24.88816332, -24.85548043,
-24.83902108, -24.83902108, -24.85548043, -24.88816332,
-24.93660487, -25.      ]],

[[[-25.      , -24.93660487, -24.88816332, -24.85548043,
-24.83902108, -24.83902108, -24.85548043, -24.88816332,
-24.93660487, -25.      ]]])

```

```

[9]: bud = ml.oc.output.budget()
bud.get_data(idx=0, full3D=True)

```

```

[9]: [array([[ 0.,  0.,  0.,  0., -0.,  0.,  0.,  0., -0.,  0.,  0.,  0.,
-0.,  0.,  0.,  0., -0.,  0.,  0.,  0., -0.,  0.,  0.,  0.,
-0.,  0.,  0.,  0., -0.,  0.,  0.,  0., -0.,  0.,  0.,  0.,
-0.,  0.,  0., -0.,  0.,  0.,  0., -0., -0.,  0.,  0.,  0.,
-0., -0.,  0.,  0.,  0., -0., -0.,  0.,  0.,  0., -0., -0.,
0.,  0.,  0., -0., -0.,  0.,  0.,  0., -0., -0.,  0.,  0.,
0., -0., -0.,  0.,  0.,  0., -0., -0.,  0.,  0.,  0., -0.,
-0.,  0.,  0., -0.,  0.,  0., -0., -0.,  0.,  0., -0., -0.,
0.,  0., -0., -0.,  0.,  0., -0., -0.,  0.,  0., -0., -0.,
0.,  0., -0., -0.,  0.,  0., -0., -0.,  0.,  0., -0., -0.,
0.,  0., -0., -0.]]]])

```

```
[10]: hds = ml.oc.output.head()
      hds.get_data()

[10]: array([[[-25.          , -24.93660487, -24.88816332, -24.85548043,
            -24.83902108, -24.83902108, -24.85548043, -24.88816332,
            -24.93660487, -25.          ]],

            [[-25.          , -24.93660487, -24.88816332, -24.85548043,
            -24.83902108, -24.83902108, -24.85548043, -24.88816332,
            -24.93660487, -25.          ]],

            [[-25.          , -24.93660487, -24.88816332, -24.85548043,
            -24.83902108, -24.83902108, -24.85548043, -24.88816332,
            -24.93660487, -25.          ]]])
```

### Get output associated with a specific package

The `.output` attribute is tied to the package object and allows the user to get the output types specified in the MODFLOW 6 package. Here is an example with a UZF package that has UZF budget file output, budgetcsv file output, package convergence output, and observation data.

```
[11]: uzf = ml.uzf
      uzf_bud = uzf.output.budget()
      uzf_bud.get_data(id=0)

[11]: [rec.array([( 1,  9,  0., 100000.), ( 9,  1, -0., 100000.),
                ( 2, 10,  0., 100000.), (10,  2, -0., 100000.),
                ( 3, 11,  0., 100000.), (11,  3, -0., 100000.),
                ( 4, 12,  0., 100000.), (12,  4, -0., 100000.),
                ( 5, 13,  0., 100000.), (13,  5, -0., 100000.),
                ( 6, 14,  0., 100000.), (14,  6, -0., 100000.),
                ( 7, 15,  0., 100000.), (15,  7, -0., 100000.),
                ( 8, 16,  0., 100000.), (16,  8, -0., 100000.),
                ( 9, 17,  0., 100000.), (17,  9, -0., 100000.),
                (10, 18,  0., 100000.), (18, 10, -0., 100000.),
                (11, 19,  0., 100000.), (19, 11, -0., 100000.),
                (12, 20,  0., 100000.), (20, 12, -0., 100000.),
                (13, 21,  0., 100000.), (21, 13, -0., 100000.),
                (14, 22,  0., 100000.), (22, 14, -0., 100000.),
                (15, 23,  0., 100000.), (23, 15, -0., 100000.),
                (16, 24,  0., 100000.), (24, 16, -0., 100000.)],
              dtype=[('node', '<i4'), ('node2', '<i4'), ('q', '<f8'), ('FLOW-AREA', '<f8
→')])]
```

```
[12]: uzf_budcsv = uzf.output.budgetcsv()
      uzf_budcsv.data

[12]: rec.array([(2.00e+00, 0., 8000., 0., 0., 0.00000000e+00,  0.,  0., 0., 0.
→01124365, 7999.98875635, 8000.,  8000.,  3.41060513e-14),
                (4.00e+00, 0., 8000., 0., 0., 0.00000000e+00,  0.,  0., 0., 0.
→02248729, 7999.97751271, 8000.,  8000., -2.27373675e-14),
                (6.00e+00, 0., 8000., 0., 0., 0.00000000e+00,  0.,  0., 0., 0.
→03373091, 7999.96626909, 8000.,  8000.,  6.82121026e-14),
```

(continues on next page)



(continued from previous page)

```

(8.00e+00, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪04497452, 7999.95502458, 8000., , 7999.9999991, 1.12417183e-08),
(1.00e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪10119265, 7999.89880735, 8000., , 8000., 1.13686838e-13),
(1.20e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪15741054, 7999.84258946, 8000., , 8000., -1.13686838e-14),
(1.40e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪21362819, 7999.78637181, 8000., , 8000., 6.82121026e-14),
(1.60e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪26984561, 7999.73015439, 8000., , 8000., -5.68434189e-14),
(1.80e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪32606279, 7999.67393721, 8000., , 8000., -2.38742359e-13),
(2.00e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪38227973, 7999.61772027, 8000., , 8000., 6.82121026e-14),
(2.20e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪43849643, 7999.56150357, 8000., , 8000., 2.04636308e-13),
(2.40e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪13492205, 7999.86507795, 8000., , 8000., -9.09494702e-14),
(2.60e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪19113979, 7999.80886021, 8000., , 8000., -3.63797881e-13),
(2.80e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.2473573↪
↪, 7999.7526427, 8000., , 8000., 4.66116035e-13),
(3.00e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.3035747↪
↪, 7999.6964253, 8000., , 8000., -9.09494702e-14),
(3.20e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪35979212, 7999.64020788, 8000., , 8000., -7.95807864e-14),
(3.40e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.4160093↪
↪, 7999.5839907, 8000., , 8000., -9.09494702e-14),
(3.60e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪47222624, 7999.52777376, 8000., , 8000., -7.95807864e-14),
(3.80e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪52844295, 7999.47155705, 8000., , 8000., -9.09494702e-14),
(4.00e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪22486856, 7999.77513144, 8000., , 8000., 7.27595761e-13),
(4.20e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪28108631, 7999.71891369, 8000., , 8000., 2.04636308e-13),
(4.40e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪33475407, 7999.66524593, 8000., , 8000., -1.02318154e-13),
(4.60e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪38480503, 7999.61519497, 8000., , 8000., -5.11590770e-13),
(4.80e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪43407536, 7999.56558735, 8000., , 7999.99966271, 4.21615857e-06),
(5.00e+01, 0., 8000., 0., 0., 1.18939114e-01, 0., 0., 0., 0.
↪48208139, 7999.63685772, 8000.11893911, 8000.11893911, 4.54740590e-13),
(5.20e+01, 0., 8000., 0., 0., 2.40000000e-01, 0., 0., 0., 0.
↪62375028, 7999.61624972, 8000.24, 8000.24, 4.54733709e-14),
(5.40e+01, 0., 8000., 0., 0., 2.40000000e-01, 0., 0., 0., 0.
↪64056589, 7999.59943411, 8000.24, 8000.24, -1.13683427e-13),
(5.60e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪32744504, 7999.67255496, 8000., , 8000., -2.16004992e-13),
(5.80e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪36195984, 7999.63804016, 8000., , 8000., 1.93267624e-13),

```

(continues on next page)

(continued from previous page)

```

(6.00e+01, 0., 8000., 0., 0., 0.00000000e+00, 0., 0., 0., 0.
↪ 39268212, 7999.60731788, 8000., 8000., 4.66116035e-13),
(1.10e+02, 0., 0., 0., 3.78724873e+03, 0., 0., 0., 0.
↪ 41882422, 3786.82970478, 3787.24873018, 3787.24852899, 5.31225330e-06),
(1.60e+02, 0., 0., 0., 6.28239222e+02, 0., 0., 0., 0.
↪ 51502761, 627.69903841, 628.23922183, 628.21406602, 4.00425715e-03),
(2.10e+02, 0., 0., 0., 3.79980452e+02, 0., 0., 0., 0.
↪ 56814228, 379.36208201, 379.98045151, 379.9302243, 1.32192414e-02),
(2.60e+02, 0., 0., 0., 1.22681840e+02, 0., 0., 0., 0.
↪ 60336166, 122.00319618, 122.68183971, 122.60655784, 6.13823347e-02),
(3.10e+02, 0., 0., 0., 1.22634110e+02, 0., 0., 0., 0.
↪ 58736429, 121.9464052, 122.63410992, 122.53376948, 8.18544694e-02),
(3.60e+02, 0., 0., 0., 1.22586380e+02, 0., 0., 0., 0.
↪ 58904253, 121.8719518, 122.58638012, 122.46099433, 1.02335961e-01),
(4.10e+02, 0., 0., 0., 1.22538650e+02, 0., 0., 0., 0.
↪ 57596753, 121.81226742, 122.53865033, 122.38823496, 1.22824712e-01),
(4.60e+02, 0., 0., 0., 1.22490921e+02, 0., 0., 0., 0.
↪ 56435326, 121.75113567, 122.49092053, 122.31548892, 1.43322724e-01),
(5.10e+02, 0., 0., 0., 1.22443191e+02, 0., 0., 0., 0.
↪ 55419916, 121.68855904, 122.44319073, 122.2427582, 1.63828398e-01),
(5.60e+02, 0., 0., 0., 1.22395461e+02, 0., 0., 0., 0.
↪ 56040475, 121.60963737, 122.39546094, 122.17004212, 1.84342282e-01),
(6.00e+02, 0., 0., 0., 1.74018709e+01, 0., 0., 0., 0.
↪ 55999969, 16.82414951, 17.4018709, 17.3841492, 1.01889790e-01),
(6.40e+02, 0., 0., 0., 1.51944083e+02, 0., 0., 0., 0.
↪ 55144142, 151.39263928, 151.94408282, 151.9440807, 1.39256758e-06),
(6.80e+02, 0., 0., 0., 2.72064073e+02, 0., 0., 0., 0.
↪ 54288289, 271.52105105, 272.06407257, 272.06393394, 5.09554104e-05),
(7.20e+02, 0., 0., 0., 2.43435052e+02, 0., 0., 0., 0.
↪ 53432434, 242.90043095, 243.43505167, 243.43475529, 1.21747747e-04),
(7.60e+02, 0., 0., 0., 2.24436380e+02, 0., 0., 0., 0.
↪ 52576579, 223.91019007, 224.43638039, 224.43595586, 1.89152075e-04),
(8.00e+02, 0., 0., 0., 1.92144820e+02, 0., 0., 0., 0.
↪ 51720724, 191.62706411, 192.14481959, 192.14427135, 2.85328186e-04),
(8.40e+02, 0., 0., 0., 1.89295138e+02, 0., 0., 0., 0.
↪ 50864868, 188.7858185, 189.29513782, 189.29446718, 3.54282046e-04),
(8.80e+02, 0., 0., 0., 1.59711534e+02, 0., 0., 0., 0.
↪ 50009013, 159.2106566, 159.71153439, 159.71074673, 4.93175545e-04),
(9.20e+02, 0., 0., 0., 1.54912199e+02, 0., 0., 0., 0.
↪ 49153158, 154.41976469, 154.91219927, 154.91129626, 5.82916597e-04),
(9.60e+02, 0., 0., 0., 1.53348712e+02, 0., 0., 0., 0.
↪ 48297303, 152.8647234, 153.34871173, 153.34769643, 6.62088144e-04),
(1.00e+03, 0., 0., 0., 1.22470337e+02, 0., 0., 0., 0.
↪ 47441447, 121.99480078, 122.47033704, 122.46921525, 9.15973800e-04),
(1.04e+03, 0., 0., 0., 1.22428683e+02, 0., 0., 0., 0.
↪ 46585592, 121.9616002, 122.42868329, 122.42745612, 1.00236285e-03),
(1.08e+03, 0., 0., 0., 1.22381264e+02, 0., 0., 0., 0.
↪ 45729737, 121.92263707, 122.38126375, 122.37993444, 1.08621048e-03),
(1.12e+03, 0., 0., 0., 1.22333850e+02, 0., 0., 0., 0.
↪ 44873881, 121.88368331, 122.33385014, 122.33242212, 1.16731720e-03),
(1.16e+03, 0., 0., 0., 1.22274162e+02, 0., 0., 0., 0.
↪ 44018026, 121.83245857, 122.27416212, 122.27263883, 1.24580486e-03),

```

(continues on next page)

(continued from previous page)

```

(1.20e+03, 0., 0., 0., 0., 1.22222909e+02, 0., 0., 0., 0.
↪43162171, 121.78967189, 122.22290873, 122.2212936, 1.32147141e-03),
(1.24e+03, 0., 0., 0., 0., 1.22175517e+02, 0., 0., 0., 0.
↪42306316, 121.75075005, 122.17551675, 122.17381321, 1.39435034e-03),
(1.28e+03, 0., 0., 0., 0., 1.22128131e+02, 0., 0., 0., 0.4145046↪
↪, 121.71183756, 122.12813069, 122.12634217, 1.46447817e-03),
(1.32e+03, 0., 0., 0., 0., 1.22080751e+02, 0., 0., 0., 0.
↪40594605, 121.67293442, 122.08075056, 122.07888047, 1.53185243e-03),
(1.36e+03, 0., 0., 0., 0., 1.22022484e+02, 0., 0., 0., 0.3973875↪
↪, 121.62314831, 122.02248402, 122.0205358, 1.59661237e-03),
(1.40e+03, 0., 0., 0., 0., 1.21761590e+02, 0., 0., 0., 0.
↪38882895, 121.3707379, 121.76158975, 121.75956685, 1.66137130e-03),
(1.44e+03, 0., 0., 0., 0., 1.15127548e+02, 0., 0., 0., 0.
↪38027039, 114.74518428, 115.1275483, 115.12545468, 1.81853759e-03),
(1.48e+03, 0., 0., 0., 0., 1.06834995e+02, 0., 0., 0., 0.
↪37171184, 106.46112218, 106.83499475, 106.83283402, 2.02250892e-03),
(1.52e+03, 0., 0., 0., 0., 1.28387162e+02, 128.0217841, 0., 0., 0.
↪36315329, 0., 128.3871623, 128.38493739, 1.73299045e-03),
(1.56e+03, 0., 0., 0., 0., 1.39350694e+02, 138.99381474, 0., 0., 0.
↪35459473, 0., 139.35069441, 139.34840947, 1.63971258e-03),
(1.60e+03, 0., 0., 0., 0., 1.36845580e+02, 136.4972012, 0., 0., 0.
↪34603618, 0., 136.84557981, 136.84323738, 1.71174694e-03),
(1.64e+03, 0., 0., 0., 0., 1.34699461e+02, 134.35958704, 0., 0., 0.
↪33747763, 0., 134.69946073, 134.69706466, 1.77884019e-03),
(1.68e+03, 0., 0., 0., 0., 1.31576180e+02, 131.24481479, 0., 0., 0.
↪32891908, 0., 131.57617996, 131.57373387, 1.85908572e-03),
(1.72e+03, 0., 0., 0., 0., 1.23457194e+02, 123.13434058, 0., 0., 0.
↪32036052, 0., 123.45719445, 123.4547011, 2.01962857e-03),
(1.76e+03, 0., 0., 0., 0., 1.14317874e+02, 114.00353442, 0., 0., 0.
↪31180197, 0., 114.31787365, 114.31533639, 2.21950275e-03),
(1.80e+03, 0., 0., 0., 0., 1.10420694e+02, 110.11487407, 0., 0., 0.
↪30324342, 0., 110.42069432, 110.41811749, 2.33367700e-03),
(1.84e+03, 0., 0., 0., 0., 1.05703327e+02, 105.40602911, 0., 0., 0.
↪29468487, 0., 105.7033274, 105.70071398, 2.47244563e-03),
(1.88e+03, 0., 0., 0., 0., 9.53779221e+01, 95.08914871, 0., 0., 0.
↪28612631, 0., 95.37792207, 95.37527503, 2.77535835e-03),
(1.92e+03, 0., 0., 0., 0., 9.49750001e+01, 94.69475504, 0., 0., 0.
↪27756776, 0., 94.97500009, 94.9723228, 2.81897970e-03),
(1.96e+03, 0., 0., 0., 0., 9.00448429e+01, 89.77312957, 0., 0., 0.
↪26900921, 0., 90.0448429, 90.04213878, 3.00312769e-03),
(2.00e+03, 0., 0., 0., 0., 8.60426727e+01, 85.77949492, 0., 0., 0.
↪26045065, 0., 86.04267268, 86.03994557, 3.16952968e-03),
(2.04e+03, 0., 0., 0., 0., 7.93212676e+01, 79.06662935, 0., 0., 0.2518921↪
↪, 0., 79.3212676, 79.31852145, 3.46212104e-03),
(2.08e+03, 0., 0., 0., 0., 7.92621596e+01, 79.01606345, 0., 0., 0.
↪24333355, 0., 79.26215964, 79.259397, 3.48550200e-03),
(2.12e+03, 0., 0., 0., 0., 7.93077233e+01, 79.07017251, 0., 0., 0.234775 ↪
↪, 0., 79.30772334, 79.30494751, 3.50012862e-03),
(2.16e+03, 0., 0., 0., 0., 7.46733681e+01, 74.44436606, 0., 0., 0.
↪22621644, 0., 74.67336811, 74.67058251, 3.73045242e-03),
(2.20e+03, 0., 0., 0., 0., 6.81917326e+01, 67.97128273, 0., 0., 0.
↪21765789, 0., 68.19173259, 68.18894062, 4.09438250e-03),

```

(continues on next page)

(continued from previous page)

```

(2.24e+03, 0., 0., 0., 0., 6.52627430e+01, 65.05084871, 0., 0., 0.
→20909934, 0., 65.26274298, 65.25994805, 4.28268329e-03),
(2.28e+03, 0., 0., 0., 0., 6.38805832e+01, 63.67724795, 0., 0., 0.
→20054079, 0., 63.88058323, 63.87778874, 4.37465570e-03),
(2.32e+03, 0., 0., 0., 0., 6.40791861e+01, 63.8844137, 0., 0., 0.
→19198223, 0., 64.07918605, 64.07639593, 4.35427472e-03),
(2.36e+03, 0., 0., 0., 0., 6.42407922e+01, 64.05458652, 0., 0., 0.
→18342368, 0., 64.2407922, 64.2380102, 4.33067676e-03),
(2.40e+03, 0., 0., 0., 0., 6.37004030e+01, 63.52276663, 0., 0., 0.
→17486513, 0., 63.70040299, 63.69763176, 4.35050707e-03),
(2.44e+03, 0., 0., 0., 0., 5.95622453e+01, 59.39318153, 0., 0., 0.
→16630658, 0., 59.56224528, 59.55948811, 4.62916709e-03),
(2.48e+03, 0., 0., 0., 0., 5.72334154e+01, 57.07292771, 0., 0., 0.
→15774802, 0., 57.23341545, 57.23067573, 4.78702424e-03),
(2.52e+03, 0., 0., 0., 0., 5.09521020e+01, 50.80019371, 0., 0., 0.
→14918947, 0., 50.95210203, 50.94938318, 5.33623414e-03),
(2.56e+03, 0., 0., 0., 0., 4.94726100e+01, 49.32928447, 0., 0., 0.
→14063092, 0., 49.47260998, 49.46991539, 5.44677831e-03)],
dtype=[('totim', '<f8'), ('GWF_IN', '<f8'), ('INFILTRATION_IN', '<f8'), (
→'REJINF_IN', '<f8'), ('UZET_IN', '<f8'), ('STORAGE_IN', '<f8'), ('GWF_OUT', '<f8'), (
→'INFILTRATION_OUT', '<f8'), ('REJINF_OUT', '<f8'), ('UZET_OUT', '<f8'), ('STORAGE_OUT',
→'<f8'), ('TOTAL_IN', '<f8'), ('TOTAL_OUT', '<f8'), ('PERCENT_DIFFERENCE', '<f8')]]

```

```

[13]: uzf_conv = uzf.output.package_convergence()
      if uzf_conv is not None:
          uzf_conv.data[0:10]

```

```

[14]: uzf_obs = uzf.output.obs()
      uzf_obs.data[0:10]

```

```

[14]: rec.array([( 2., 0.05, 0.05, 0.), ( 4., 0.05, 0.05, 0.),
                ( 6., 0.05, 0.05, 0.), ( 8., 0.05, 0.05, 0.),
                (10., 0.05, 0.05, 0.), (12., 0.05, 0.05, 0.),
                (14., 0.05, 0.05, 0.), (16., 0.05, 0.05, 0.),
                (18., 0.05, 0.05, 0.), (20., 0.05, 0.05, 0.)],
          dtype=[('totim', '<f8'), ('ID3_DPTH80', '<f8'), ('ID3_DPTH240', '<f8'), ('ID3_
→RCH', '<f8')])

```

### Check which output types are available in a package

The `.output` attribute also has a `methods()` function that returns a list of available output functions for a given package. Here are a couple of examples

```

[15]: print("UZF package: ", uzf.output.methods())
      print("Model object: ", ml.output.methods())
      print("OC package: ", ml.oc.output.methods())
      print("DIS package: ", ml.dis.output.methods())

UZF package:  ['zonebudget()', 'budget()', 'budgetcsv()', 'package_convergence()', 'obs()
→']
Model object:  ['list()', 'zonebudget()', 'budget()', 'budgetcsv()', 'head()']

```

(continues on next page)

(continued from previous page)

```
OC package: ['list()', 'zonebudget()', 'budget()', 'budgetcsv()', 'head()']
DIS package: None
```

## Managing multiple observation and csv file outputs in the same package

For many packages, multiple observation output files can be used. The `obs()` and `csv()` functions allow the user to specify a observation file or csv file name. If no name is specified, the `obs()` and `csv()` methods will return the first file that is listed in the package.

```
[16]: output = ml.obs[0].output
      obs_names = output.obs_names
      output.obs(f=obs_names[0]).data[0:10]

[16]: rec.array([( 2., 0.05, 0.05, 0.), ( 4., 0.05, 0.05, 0.),
                ( 6., 0.05, 0.05, 0.), ( 8., 0.05, 0.05, 0.),
                (10., 0.05, 0.05, 0.), (12., 0.05, 0.05, 0.),
                (14., 0.05, 0.05, 0.), (16., 0.05, 0.05, 0.),
                (18., 0.05, 0.05, 0.), (20., 0.05, 0.05, 0.)],
              dtype=[('totim', '<f8'), ('ID3_DPTH80', '<f8'), ('ID3_DPTH240', '<f8'), ('ID3_
↪RCH', '<f8')])
```

## Creating and running ZoneBudget for MF6

For the model and many packages, zonebudget can be run on the cell budget file. The `.output` method allows the user to easily build a ZoneBudget6 instance, then run the model, and view output. First we'll build a layered zone array, then build and run zonebudget

```
[17]: zarr = np.ones(ml.modelgrid.shape, dtype=int)
      for i in range(1, 4):
          zarr[i - 1] *= i
```

```
[18]: zonbud = ml.output.zonebudget(zarr)
      zonbud.change_model_ws(sim_ws)
      zonbud.write_input()
      zonbud.run_model()
```

```
FloPy is using the following executable to run the model: /home/runner/.local/bin/zbud6
      ZONEBUDGET Version 6
      U.S. GEOLOGICAL SURVEY
      VERSION 6.3.0 03/04/2022
...
Normal Termination
```

```
[18]: (True, [])
```

```
[19]: df = zonbud.get_dataframes(net=True)
      df = df.reset_index()
      df
```

```
[19]:
```

	totim	name	ZONE_1	ZONE_2	ZONE_3
0	2.0	ZONE_0	0.0	0.000000e+00	0.000000e+00
1	2.0	ZONE_1	0.0	0.000000e+00	0.000000e+00
2	2.0	ZONE_2	0.0	0.000000e+00	0.000000e+00
3	2.0	ZONE_3	0.0	0.000000e+00	0.000000e+00
4	4.0	ZONE_0	0.0	0.000000e+00	0.000000e+00
...	...	...	...	...	...
355	2520.0	ZONE_3	0.0	0.000000e+00	0.000000e+00
356	2560.0	ZONE_0	0.0	0.000000e+00	0.000000e+00
357	2560.0	ZONE_1	0.0	0.000000e+00	0.000000e+00
358	2560.0	ZONE_2	0.0	0.000000e+00	-5.684342e-10
359	2560.0	ZONE_3	0.0	5.684342e-10	0.000000e+00

[360 rows x 5 columns]

## 6.1.4 MODFLOW Tutorials

Contents:

### MODFLOW Tutorial 1: Confined Steady-State Flow Model

This tutorial demonstrates use of FloPy to develop a simple MODFLOW-2005 model.

#### Getting Started

If FloPy has been properly installed, then it can be imported as follows:

```
[1]: import numpy as np
```

```
[2]: import flopy
```

Now that we can import flopy, we begin creating our simple MODFLOW model. numpy is imported to create arrays of model data.

#### Creating the MODFLOW Model

One of the nice things about creating models in python is that it is very easy to change one or two things and completely change the grid resolution for your model. So in this example, we will design our python script so that the number of layers, columns, and rows can be easily changed.

We can create a very simple MODFLOW model that has a basic package (BAS), discretization input file (DIS), layer-property flow (LPF) package, output control (OC), and preconditioned conjugate gradient (PCG) solver. Each one of these has its own input file, which will be created automatically by flopy, provided that we pass flopy the correct information.

## Discretization

We start by creating our flopY model object.

```
[3]: modelname = "tutorial1_mf"
mf = flopY.modflow.Modflow(modelname, exe_name="mf2005")
```

Next, let's proceed by defining our model domain and creating a MODFLOW grid to span the domain.

```
[4]: Lx = 1000.0
Ly = 1000.0
ztop = 0.0
zbot = -50.0
nlay = 1
nrow = 10
ncol = 10
delr = Lx / ncol
delc = Ly / nrow
delv = (ztop - zbot) / nlay
botm = np.linspace(ztop, zbot, nlay + 1)
```

With this information, we can now create the flopY discretization object by entering the following:

```
[5]: dis = flopY.modflow.ModflowDis(
    mf, nlay, nrow, ncol, delr=delr, delc=delc, top=ztop, botm=botm[1:]
)
```

## Basic Package

Next we can create a flopY object that represents the MODFLOW Basic Package. For this simple model, we will assign constant head values of 10. and 0. to the first and last model columns (in all layers), respectively. The python code for doing this is:

```
[6]: ibound = np.ones((nlay, nrow, ncol), dtype=np.int32)
ibound[:, :, 0] = -1
ibound[:, :, -1] = -1
strt = np.ones((nlay, nrow, ncol), dtype=np.float32)
strt[:, :, 0] = 10.0
strt[:, :, -1] = 0.0
bas = flopY.modflow.ModflowBas(mf, ibound=ibound, strt=strt)
```

## Layer-Property Flow Package

Constant values of 10. are assigned for the horizontal and vertical hydraulic conductivity:

```
[7]: lpf = flopY.modflow.ModflowLpf(mf, hk=10.0, vka=10.0, ipakcb=53)
```

Because we did not specify a value for laytyp, FlopY will use the default value of 0, which means that this model will be confined.

## Output Control

Here we can use the default OC settings by specifying the following:

```
[8]: spd = {(0, 0): ["print head", "print budget", "save head", "save budget"]}
      oc = flopY.modflow.ModflowOc(mf, stress_period_data=spd, compact=True)
```

The stress period dictionary is used to set what output is saved for the corresponding stress period and time step. In this case, the tuple (0, 0) means that stress period 1 and time step 1 for MODFLOW will have output saved. Head and budgets will be printed and head and budget information will be saved.

## Preconditioned Conjugate Gradient Package

The default settings used by flopY will be used by specifying the following commands:

```
[9]: pcg = flopY.modflow.ModflowPcg(mf)
```

## Writing the MODFLOW Data Files

The MODFLOW input data files are written by simply issuing the following:

```
[10]: mf.write_input()
```

## Running the Model

FlopY can also be used to run the model. The model object (mf in this example) has an attached method that will run the model. For this to work, the MODFLOW program must be located somewhere within the system path, or within the working directory. In this example, we have specified that the name of the executable program is 'mf2005'. Issue the following to run the model:

```
[11]: success, buff = mf.run_model()
      if not success:
          raise Exception("MODFLOW did not terminate normally.")
```

FloPy is using the following executable to run the model: /home/runner/.local/bin/mf2005

```

                                MODFLOW-2005
      U.S. GEOLOGICAL SURVEY MODULAR FINITE-DIFFERENCE GROUND-WATER FLOW MODEL
                                Version 1.12.00 2/3/2017
```

Using NAME file: tutorial1\_mf.nam

Run start date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09 2:42:35

Solving: Stress period: 1 Time step: 1 Ground-Water Flow Eqn.

Run end date and time (yyyy/mm/dd hh:mm:ss): 2022/03/09 2:42:35

Elapsed run time: 0.001 Seconds

Normal termination of simulation

Here we have used run\_model, and we could also have specified values for the optional keywords silent, pause, and report.



## Post-Processing the Results

Now that we have successfully built and run our MODFLOW model, we can look at the results. MODFLOW writes the simulated heads to a binary data output file. We cannot look at these heads with a text editor, but flop has a binary utility that can be used to read the heads. The following statements will read the binary head file and create a plot of simulated heads for layer 1:

```
[12]: import matplotlib.pyplot as plt
```

```
[13]: import flop.utils.binaryfile as bf
```


Extract the heads

```
[14]: hds = bf.HeadFile(f"{modelname}.hds")
      head = hds.get_data(totim=1.0)
```

Contour the heads

```
[15]: extent = (delr / 2.0, Lx - delr / 2.0, Ly - delc / 2.0, delc / 2.0)
      fig = plt.figure(figsize=(6, 6))
      ax = fig.add_subplot(1, 1, 1, aspect="equal")
      ax.contour(head[0, :, :], levels=np.arange(1, 10, 1), extent=extent)
```

```
[15]: <matplotlib.contour.QuadContourSet at 0x7feb0ea0c1f0>
```



Flop also has some pre-canned plotting capabilities that can be accessed using the `PlotMapView()` class. The following code shows how to use the `plotmapview` class to plot boundary conditions (IBOUND), plot the grid, plot head contours, and plot vectors:

```
[16]: # Extract the heads
      hds = bf.HeadFile(f"{modelname}.hds")
```

(continues on next page)

(continued from previous page)


```
times = hds.get_times()
head = hds.get_data(totim=times[-1])
```

Extract the cell-by-cell flows

```
[17]: cbb = bf.CellBudgetFile(f"{modelname}.cbc")
kstpker_list = cbb.get_kstpker()
frf = cbb.get_data(text="FLOW RIGHT FACE", totim=times[-1])[0]
fff = cbb.get_data(text="FLOW FRONT FACE", totim=times[-1])[0]
qx, qy, qz = flopy.utils.postprocessing.get_specific_discharge(
    (frf, fff, None), mf, head
)
```

Create the figure

```
[18]: fig = plt.figure(figsize=(6, 6))
ax = fig.add_subplot(1, 1, 1, aspect="equal")
modelmap = flopy.plot.PlotMapView(model=mf, layer=0, ax=ax)
qm = modelmap.plot_ibound()
lc = modelmap.plot_grid()
cs = modelmap.contour_array(head, levels=np.linspace(0, 10, 11))
quiver = modelmap.plot_vector(qx, qy)
```



## MODFLOW Tutorial 2: Unconfined Transient Flow Model

In this example, we will convert the tutorial 1 model into an unconfined, transient flow model with time varying boundaries. Instead of using constant heads for the left and right boundaries (by setting `ibound` to -1), we will use general head boundaries. We will have the model consider the following conditions:

- Initial conditions – head is 10.0 everywhere
- Period 1 (1 day) – steady state with left and right GHB stage = 10.
- Period 2 (100 days) – left GHB with stage = 10., right GHB with stage set to 0.
- Period 3 (100 days) – pumping well at model center with rate = -500., left and right GHB = 10., and 0.

We will start with selected model commands from the previous tutorial.

### Getting Started

As shown in the previous MODFLOW tutorial, import flopy.

```
[1]: import numpy as np
```

```
[2]: import flopy
```

### Creating the MODFLOW Model

#### Define the Model Extent, Grid Resolution, and Characteristics

Assign the model information

```
[3]: Lx = 1000.0
    Ly = 1000.0
    ztop = 10.0
    zbot = -50.0
    nlay = 1
    nrow = 10
    ncol = 10
    delr = Lx / ncol
    delc = Ly / nrow
    delv = (ztop - zbot) / nlay
    botm = np.linspace(ztop, zbot, nlay + 1)
    hk = 1.0
    vka = 1.0
    sy = 0.1
    ss = 1.0e-4
    laytyp = 1
```

Variables for the BAS package Note that changes from the MODFLOW tutorial 1

```
[4]: ibound = np.ones((nlay, nrow, ncol), dtype=np.int32)
    strt = 10.0 * np.ones((nlay, nrow, ncol), dtype=np.float32)
```

## Define the Stress Periods

To create a model with multiple stress periods, we need to define `nper`, `perlen`, `nstp`, and `steady`. This is done in the following block in a manner that allows us to pass these variable directly to the discretization object:

```
[5]: nper = 3
      perlen = [1, 100, 100]
      nstp = [1, 100, 100]
      steady = [True, False, False]
```

## Create Time-Invariant Flopy Objects

With this information, we can now create the static flopy objects that do not change with time:

```
[6]: modelname = "tutorial2_mf"
      mf = flopy.modflow.Modflow(modelname, exe_name="mf2005")
      dis = flopy.modflow.ModflowDis(
          mf,
          nlay,
          nrow,
          ncol,
          delr=delr,
          delc=delc,
          top=ztop,
          botm=botm[1:],
          nper=nper,
          perlen=perlen,
          nstp=nstp,
          steady=steady,
      )
      bas = flopy.modflow.ModflowBas(mf, ibound=ibound, strt=strt)
      lpf = flopy.modflow.ModflowLpf(
          mf, hk=hk, vka=vka, sy=sy, ss=ss, laytyp=laytyp, ipakcb=53
      )
      pcg = flopy.modflow.ModflowPcg(mf)
```

## Transient General-Head Boundary Package

At this point, our model is ready to add our transient boundary packages. First, we will create the GHB object, which is of the following type: `flopy.modflow.ModflowGhb()`.

The key to creating Flopy transient boundary packages is recognizing that the boundary data is stored in a dictionary with key values equal to the zero-based stress period number and values equal to the boundary conditions for that stress period. For a GHB the values can be a two-dimensional nested list of `[layer, row, column, stage, conductance]`.

```
[7]: stageleft = 10.0
      stageright = 10.0
      bound_sp1 = []
      for il in range(nlay):
          condleft = hk * (stageleft - zbot) * delc
```

(continues on next page)

(continued from previous page)

```

condright = hk * (stageright - zbot) * delc
for ir in range(nrow):
    bound_sp1.append([il, ir, 0, stageleft, condleft])
    bound_sp1.append([il, ir, ncol - 1, stageright, condright])
print("Adding ", len(bound_sp1), "GHBs for stress period 1.")

```

Adding 20 GHBs for stress period 1.

```

[8]: # Make list for stress period 2
stageleft = 10.0
stageright = 0.0
condleft = hk * (stageleft - zbot) * delc
condright = hk * (stageright - zbot) * delc
bound_sp2 = []
for il in range(nlay):
    for ir in range(nrow):
        bound_sp2.append([il, ir, 0, stageleft, condleft])
        bound_sp2.append([il, ir, ncol - 1, stageright, condright])
print("Adding ", len(bound_sp2), "GHBs for stress period 2.")

```

Adding 20 GHBs for stress period 2.

```

[9]: # We do not need to add a dictionary entry for stress period 3.
# Flopy will automatically take the list from stress period 2 and apply it
# to the end of the simulation
stress_period_data = {0: bound_sp1, 1: bound_sp2}

```

```

[10]: # Create the flopy ghb object
ghb = flopy.modflow.ModflowGhb(mf, stress_period_data=stress_period_data)

```

## Transient Well Package

Now we can create the well package object, which is of the type, `flopy.modflow.ModflowWel()`.

```

[11]: # Create the well package
# Remember to use zero-based layer, row, column indices!
pumping_rate = -500.0
wel_sp1 = [[0, nrow / 2 - 1, ncol / 2 - 1, 0.0]]
wel_sp2 = [[0, nrow / 2 - 1, ncol / 2 - 1, 0.0]]
wel_sp3 = [[0, nrow / 2 - 1, ncol / 2 - 1, pumping_rate]]
stress_period_data = {0: wel_sp1, 1: wel_sp2, 2: wel_sp3}
wel = flopy.modflow.ModflowWel(mf, stress_period_data=stress_period_data)

```

## Output Control

Here we create the output control package object, which is of the type `flopY.modflow.ModflowOc()`.

```
[12]: stress_period_data = {}
      for kper in range(nper):
          for kstp in range(nstp[kper]):
              stress_period_data[(kper, kstp)] = [
                  "save head",
                  "save drawdown",
                  "save budget",
                  "print head",
                  "print budget",
              ]
      oc = flopY.modflow.ModflowOc(
          mf, stress_period_data=stress_period_data, compact=True
      )
```

## Running the Model

Run the model with the `run_model` method, which returns a success flag and the stream of output. With `run_model`, we have some finer control, that allows us to suppress the output.

```
[13]: # Write the model input files
      mf.write_input()

[14]: # Run the model
      success, mfoutput = mf.run_model(silent=True, pause=False)
      if not success:
          raise Exception("MODFLOW did not terminate normally.")
```

## Post-Processing the Results

Once again, we can read heads from the MODFLOW binary output file, using the `flopY.utils.binaryfile()` module. Included with the `HeadFile` object are several methods that we will use here:

- `get_times()` will return a list of times contained in the binary head file
- `get_data()` will return a three-dimensional head array for the specified time
- `get_ts()` will return a time series array `[ntimes, headval]` for the specified cell

Using these methods, we can create head plots and hydrographs from the model results.

```
[15]: # Imports
      import matplotlib.pyplot as plt

[16]: import flopY.utils.binaryfile as bf

[17]: # Create the headfile and budget file objects
      headobj = bf.HeadFile(f"{modelname}.hds")
```

(continues on next page)

(continued from previous page)

```
times = headobj.get_times()
cbb = bf.CellBudgetFile(f"{modelname}.cbc")
```

```
[18]: # Setup contour parameters
levels = np.linspace(0, 10, 11)
extent = (delr / 2.0, Lx - delr / 2.0, delc / 2.0, Ly - delc / 2.0)
print("Levels: ", levels)
print("Extent: ", extent)
```

```
Levels:  [ 0.  1.  2.  3.  4.  5.  6.  7.  8.  9. 10.]
Extent:  (50.0, 950.0, 50.0, 950.0)
```

```
[19]: # Well point for plotting
wpt = (450.0, 550.0)
```

Create a figure with maps for three times

```
[20]: # Make the plots
fig = plt.figure(figsize=(5, 15))
mytimes = [1.0, 101.0, 201.0]
for iplot, time in enumerate(mytimes):
    print("*****Processing time: ", time)
    head = headobj.get_data(totim=time)
    # Print statistics
    print("Head statistics")
    print("  min: ", head.min())
    print("  max: ", head.max())
    print("  std: ", head.std())

    # Extract flow right face and flow front face
    frf = cbb.get_data(text="FLOW RIGHT FACE", totim=time)[0]
    fff = cbb.get_data(text="FLOW FRONT FACE", totim=time)[0]

    # Create a map for this time
    ax = fig.add_subplot(len(mytimes), 1, iplot + 1, aspect="equal")
    ax.set_title(f"stress period {iplot + 1}")

    pmv = flopy.plot.PlotMapView(model=mf, layer=0, ax=ax)
    qm = pmv.plot_ibound()
    lc = pmv.plot_grid()
    qm = pmv.plot_bc("GHB", alpha=0.5)
    if head.min() != head.max():
        cs = pmv.contour_array(head, levels=levels)
        plt.clabel(cs, inline=1, fontsize=10, fmt="%1.1f")
        quiver = pmv.plot_vector(frf, fff)

    mfc = "None"
    if (iplot + 1) == len(mytimes):
        mfc = "black"
    ax.plot(
        wpt[0],
        wpt[1],
```


(continues on next page)

(continued from previous page)

```
        lw=0,
        marker="o",
        markersize=8,
        markeredgewidth=0.5,
        markeredgecolor="black",
        markerfacecolor=mfc,
        zorder=9,
    )
    ax.text(wpt[0] + 25, wpt[1] - 25, "well", size=12, zorder=12)
```

```
*****Processing time:  1.0
Head statistics
  min:  10.0
  max:  10.0
  std:   0.0
*****Processing time: 101.0
Head statistics
  min:  0.025931068
  max:  9.998436
  std:  3.2574987
*****Processing time: 201.0
Head statistics
  min:  0.016297927
  max:  9.994038
  std:  3.1544707
```






Create a hydrograph

```
[21]: # Plot the head versus time
idx = (0, int(nrow / 2) - 1, int(ncol / 2) - 1)
ts = headobj.get_ts(idx)
fig = plt.figure(figsize=(6, 6))
ax = fig.add_subplot(1, 1, 1)
ttl = f"Head at cell ({idx[0] + 1},{idx[1] + 1},{idx[2] + 1})"
ax.set_title(ttl)
ax.set_xlabel("time")
ax.set_ylabel("head")
ax.plot(ts[:, 0], ts[:, 1], "bo-")
```

```
[21]: [<matplotlib.lines.Line2D at 0x7f33f342a7f0>]
```



## 6.1.5 SEAWAT Tutorials

Contents:

## SEAWAT Tutorial 1: Henry Saltwater Intrusion Problem

In this tutorial, we will use Flopy to create, run, and post process the Henry saltwater intrusion problem using SEAWAT Version 4.

### Getting Started

```
[1]: import numpy as np
```

```
[2]: import flopy
```

### Input variables for the Henry Problem

```
[3]: Lx = 2.0
     Lz = 1.0
     nlay = 50
     nrow = 1
     ncol = 100
     delr = Lx / ncol
     delc = 1.0
     delv = Lz / nlay
     henry_top = 1.0
     henry_botm = np.linspace(henry_top - delv, 0.0, nlay)
     qinflow = 5.702 # m3/day
     dmcoef = 0.57024 # m2/day Could also try 1.62925 as another case of the Henry problem
     hk = 864.0 # m/day
```

### Create the basic MODFLOW model structure

```
[4]: modelname = "henry"
     swt = flopy.seawat.Seawat(modelname, exe_name="swtv4")
     print(swt.namefile)
```

```
henry.nam
```

save cell fluxes to unit 53

```
[5]: ipakcb = 53
```

Add DIS package to the MODFLOW model

```
[6]: dis = flopy.modflow.ModflowDis(
     swt,
     nlay,
     nrow,
     ncol,
     nper=1,
     delr=delr,
     delc=delc,
```

(continues on next page)

(continued from previous page)

```

    laycbd=0,
    top=henry_top,
    botm=henry_botm,
    perlen=1.5,
    nstp=15,
)

```

```

[7]: # Variables for the BAS package
ibound = np.ones((nlay, nrow, ncol), dtype=np.int32)
ibound[:, :, -1] = -1

```

Add BAS package to the MODFLOW model

```

[8]: bas = flopy.modflow.ModflowBas(swt, ibound, 0)

```

Add LPF package to the MODFLOW model

```

[9]: lpf = flopy.modflow.ModflowLpf(swt, hk=hk, vka=hk, ipakcb=ipakcb)

```

Add PCG Package to the MODFLOW model

```

[10]: pcg = flopy.modflow.ModflowPcg(swt, hclose=1.0e-8)

```

Add OC package to the MODFLOW model

```

[11]: oc = flopy.modflow.ModflowOc(
    swt,
    stress_period_data={(0, 0): ["save head", "save budget"]},
    compact=True,
)

```

Create WEL and SSM data

```

[12]: itype = flopy.mt3d.Mt3dSsm.itype_dict()
wel_data = {}
ssm_data = {}
wel_sp1 = []
ssm_sp1 = []
for k in range(nlay):
    wel_sp1.append([k, 0, 0, qinflow / nlay])
    ssm_sp1.append([k, 0, 0, 0.0, itype["WEL"]])
    ssm_sp1.append([k, 0, ncol - 1, 35.0, itype["BAS6"]])
wel_data[0] = wel_sp1
ssm_data[0] = ssm_sp1
wel = flopy.modflow.ModflowWel(swt, stress_period_data=wel_data, ipakcb=ipakcb)

```

### Create the basic MT3DMS model structure

```
[13]: btn = flopy.mt3d.Mt3dBtn(
    swt,
    nprs=-5,
    prsity=0.35,
    scon=35.0,
    ifmtcn=0,
    chkmas=False,
    nprobs=10,
    nprmas=10,
    dt0=0.001,
)
adv = flopy.mt3d.Mt3dAdv(swt, mixelm=0)
dsp = flopy.mt3d.Mt3dDsp(swt, al=0.0, trpt=1.0, trpv=1.0, dmcoef=dmcoef)
gcg = flopy.mt3d.Mt3dGcg(swt, iter1=500, mxiter=1, isolve=1, cclose=1e-7)
ssm = flopy.mt3d.Mt3dSsm(swt, stress_period_data=ssm_data)
```

### Create the SEAWAT model structure

```
[14]: vdf = flopy.seawat.SeawatVdf(
    swt,
    iwtable=0,
    densemin=0,
    densemax=0,
    denseref=1000.0,
    denseslp=0.7143,
    firstdt=1e-3,
)
```

### Write the input files

```
[15]: swt.write_input()
```

## Run the model

```
[16]: success, buff = swt.run_model(silent=True, report=True)
      if not success:
          raise Exception("SEAWAT did not terminate normally.")
```

## Post-process the results

```
[17]: import numpy as np
```

```
[18]: import flop.utils.binaryfile as bf
```

## Load the concentration data

```
[19]: ucnobj = bf.UcnFile("MT3D001.UCN", model=swt)
      times = ucnobj.get_times()
      concentration = ucnobj.get_data(totim=times[-1])
```

## Load the cell-by-cell flow data


```
[20]: cbbobj = bf.CellBudgetFile("henry.cbc")
      times = cbbobj.get_times()
      qx = cbbobj.get_data(text="flow right face", totim=times[-1])[0]
      qy = np.zeros((nlay, nrow, ncol), dtype=float)
      qz = cbbobj.get_data(text="flow lower face", totim=times[-1])[0]
```

## Create a plot with concentrations and flow vectors

```
[21]: import matplotlib.pyplot as plt
```

```
[22]: fig = plt.figure(figsize=(12, 9))
      ax = fig.add_subplot(1, 1, 1, aspect="equal")
      pmv = flop.plot.PlotCrossSection(model=swt, ax=ax, line={"row": 0})
      arr = pmv.plot_array(concentration)
      pmv.plot_vector(qx, qy, -qz, color="white", kstep=3, hstep=3)
      plt.colorbar(arr, shrink=0.5, ax=ax)
      ax.set_title("Simulated Concentrations")
```

```
[22]: Text(0.5, 1.0, 'Simulated Concentrations')
```




### Load the head data

```
[23]: headobj = bf.HeadFile("henry.hds")
      times = headobj.get_times()
      head = headobj.get_data(totim=times[-1])
```

### Create a plot with heads

```
[24]: fig = plt.figure(figsize=(12, 9))
      ax = fig.add_subplot(1, 1, 1, aspect="equal")
      pmv = flopy.plot.PlotCrossSection(model=swt, ax=ax, line={"row": 0})
      arr = pmv.plot_array(head)
      contours = pmv.contour_array(head, colors="white")
      ax.clabel(contours, fmt="%2.2f")
      plt.colorbar(arr, shrink=0.5, ax=ax)
      ax.set_title("Simulated Heads")
```

```
[24]: Text(0.5, 1.0, 'Simulated Heads')
```



## 6.2 Jupyter Notebooks

A list of Jupyter Notebooks are available [here](#). After the [tutorials](#), the Jupyter Notebooks are the best resource for learning the underlying capabilities of FloPy.



## CODE DESCRIPTION

Contents:

### 7.1 Flopy Code

#### 7.1.1 MODFLOW 6

FloPy for MODFLOW 6 allows for the construction of multi-model simulations. In order to construct a MODFLOW 6 simulation using FloPy, first construct a simulation (MFSimulation) object. Then construct the MODFLOW 6 models (Modflowgwf and Modflowgwt) and the packages, like TDIS, that are associated with the simulation. Finally, construct the packages that are associated with each of your models.

#### MODFLOW 6 Base Classes

FloPy for MODFLOW 6 is object oriented code that uses inheritance. The FloPy classes used to define different types models and packages share common code that is defined in these base classes.

Contents:

#### **flopy.mf6.mfbase module**

Base classes for Modflow 6

**class ExtFileAction**(*value*)

Bases: `enum.Enum`

Defines what to do with external files when the simulation or model's path change.

**copy\_all** = 1

**copy\_none** = 2

**copy\_relative\_paths** = 3

**exception FlopyException**(*error, location=""*)

Bases: `Exception`

General FloPy exception

**exception MFDataException**(*model=None, package=None, path=None, current\_process=None, data\_element=None, method\_caught\_in=None, org\_type=None, org\_value=None, org\_traceback=None, message=None, debug=None, mfddata\_except=None*)

Bases: `Exception`

Exception with MODFLOW data. Exception includes detailed error information.

**class** **MFFileMgmt**(*path*, *mfsim=None*)

Bases: object

Class containing MODFLOW path data

**Parameters** **path** (*str*) – Path on disk to the simulation

**model\_relative\_path**

Dictionary of relative paths to each model folder

**Type** dict

**add\_ext\_file**(*file\_path*, *model\_name*)

Add an external file to the path list. For internal FloPy use, not intended for end user.

**copy\_files**(*copy\_relative\_only=True*)

Copy files external to updated path.

**Parameters** **copy\_relative\_only** (*bool*) – Only copy files with relative paths.

**get\_model\_path**(*key*, *last\_loaded\_path=False*)

Returns the model working path for the model *key*.

**Parameters**

- **key** (*str*) – Model name whose path flopy will retrieve
- **last\_loaded\_path** (*bool*) – Get the last path loaded by FloPy which may not be the most recent path.

**Returns** **model path**

**Return type** str

**get\_sim\_path**(*last\_loaded\_path=False*)

Get the simulation path.

**get\_updated\_path**(*external\_file\_path*, *model\_name*, *ext\_file\_action*)

For internal FloPy use, not intended for end user.

**resolve\_path**(*path*, *model\_name*, *last\_loaded\_path=False*, *move\_abs\_paths=False*)

Resolve a simulation or model path. For internal FloPy use, not intended for end user.

**set\_last\_accessed\_model\_path**()

Set the last accessed model path to the current model path. For internal FloPy use, not intended for end user.

**set\_last\_accessed\_path**()

Set the last accessed simulation path to the current simulation path. For internal FloPy use, not intended for end user.

**set\_sim\_path**(*path*, *internal\_use=False*)

Set the file path to the simulation files. Internal use only, call MFSimulation's set\_sim\_path method instead.

**Parameters** **path** (*str*) – Full path or relative path from working directory to simulation folder

## Examples

```
self.simulation_data.mfdata.set_sim_path('sim_folder')

static string_to_file_path(fp_string)
    Interpret string as a file path. For internal FloPy use, not intended for end user.

strip_model_relative_path(model_name, path)
    Strip out the model relative path part of path. For internal FloPy use, not intended for end user.

static unique_file_name(file_name, lookup)
    Generate a unique file name. For internal FloPy use, not intended for end user.

class MFFilePath(file_path, model_name)
    Bases: object

    Class that stores a single file path along with the associated model name.

    isabs()

exception MFInvalidTransientBlockHeaderException
    Bases: Exception

    Exception occurs when parsing a transient block header

class PackageContainer(simulation_data, name)
    Bases: object

    Base class for any class containing packages.

    Parameters
        • simulation_data (SimulationData) – The simulation’s SimulationData object
        • name (str) – Name of the package container object

package_type_dict
    Dictionary of packages by package type

    Type dictionary

package_name_dict
    Dictionary of packages by package name

    Type dictionary

package_key_dict
    Dictionary of packages by package key

    Type dictionary

static get_module_val(module, item, attrb)
    Static method that returns a python class module value. For internal FloPy use only, not intended for end users.

get_package(name=None)
    Finds a package by package name, package key, package type, or partial package name. returns either a single package, a list of packages, or None.

    Parameters name (str) – Name of the package, ‘RIV’, ‘LPF’, etc.

    Returns pp

    Return type Package object
```

**static** `model_factory(model_type)`

Static method that returns the appropriate model type object based on the `model_type` string. For internal FloPy use only, not intended for end users.

**Parameters** `model_type` (*str*) – Type of model that package is a part of

**Returns** `model`

**Return type** MFModel subclass

```
models_by_type = {'gwf': <class 'flopY.mf6.modflow.mfgwf.ModflowGwf'>, 'gwt': <class  
'flopY.mf6.modflow.mfgwt.ModflowGwt'>}
```

```
modflow_models = [<class 'flopY.mf6.modflow.mfgwf.ModflowGwf'>, <class  
'flopY.mf6.modflow.mfgwt.ModflowGwt'>]
```

```

modflow_packages = [<class 'flop.mf6.modflow.mfgwfgnc.ModflowGwfgnc'>, <class
'flop.mf6.modflow.mfgwfmvr.ModflowGwfmvr'>, <class
'flop.mf6.modflow.mfgwtmvt.ModflowGwtmvt'>, <class
'flop.mf6.modflow.mfims.ModflowIms'>, <class 'flop.mf6.modflow.mfnam.ModflowNam'>,
<class 'flop.mf6.modflow.mftdis.ModflowTdis'>, <class
'flop.mf6.modflow.mfgnc.ModflowGnc'>, <class
'flop.mf6.modflow.mfgwfapi.ModflowGwfapi'>, <class
'flop.mf6.modflow.mfgwfbuy.ModflowGwfbuy'>, <class
'flop.mf6.modflow.mfgwfchd.ModflowGwfchd'>, <class
'flop.mf6.modflow.mfgwfcsb.ModflowGwfcsb'>, <class
'flop.mf6.modflow.mfgwfdis.ModflowGwfdis'>, <class
'flop.mf6.modflow.mfgwfdisu.ModflowGwfdisu'>, <class
'flop.mf6.modflow.mfgwfdisv.ModflowGwfdisv'>, <class
'flop.mf6.modflow.mfgwfdrn.ModflowGwfdrn'>, <class
'flop.mf6.modflow.mfgwfevt.ModflowGwfevt'>, <class
'flop.mf6.modflow.mfgwfevta.ModflowGwfevta'>, <class
'flop.mf6.modflow.mfgwfgbh.ModflowGwfgbh'>, <class
'flop.mf6.modflow.mfgwfgwf.ModflowGwfgwf'>, <class
'flop.mf6.modflow.mfgwfgwt.ModflowGwfgwt'>, <class
'flop.mf6.modflow.mfgwfhib.ModflowGwfhib'>, <class
'flop.mf6.modflow.mfgwfic.ModflowGwfic'>, <class
'flop.mf6.modflow.mfgwflak.ModflowGwflak'>, <class
'flop.mf6.modflow.mfgwfmaw.ModflowGwfmaw'>, <class
'flop.mf6.modflow.mfgwfnam.ModflowGwfnam'>, <class
'flop.mf6.modflow.mfgwfnpf.ModflowGwfnpf'>, <class
'flop.mf6.modflow.mfgwfoc.ModflowGwfoc'>, <class
'flop.mf6.modflow.mfgwfrch.ModflowGwfrch'>, <class
'flop.mf6.modflow.mfgwfrcha.ModflowGwfrcha'>, <class
'flop.mf6.modflow.mfgwfriv.ModflowGwfriv'>, <class
'flop.mf6.modflow.mfgwfsfr.ModflowGwfsfr'>, <class
'flop.mf6.modflow.mfgwfsto.ModflowGwfsto'>, <class
'flop.mf6.modflow.mfgwfuzf.ModflowGwfuzf'>, <class
'flop.mf6.modflow.mfgfwel.ModflowGfwel'>, <class
'flop.mf6.modflow.mfgwtadv.ModflowGwtadv'>, <class
'flop.mf6.modflow.mfgwtapi.ModflowGwtapi'>, <class
'flop.mf6.modflow.mfgwtcnc.ModflowGwtcnc'>, <class
'flop.mf6.modflow.mfgwtdis.ModflowGwtdis'>, <class
'flop.mf6.modflow.mfgwtdisu.ModflowGwtdisu'>, <class
'flop.mf6.modflow.mfgwtdisv.ModflowGwtdisv'>, <class
'flop.mf6.modflow.mfgwt dsp.ModflowGwt dsp'>, <class
'flop.mf6.modflow.mfgwt fmi.ModflowGwt fmi'>, <class
'flop.mf6.modflow.mfgwt gwt.ModflowGwt gwt'>, <class
'flop.mf6.modflow.mfgwt ic.ModflowGwt ic'>, <class
'flop.mf6.modflow.mfgwt ist.ModflowGwt ist'>, <class
'flop.mf6.modflow.mfgwt lkt.ModflowGwt lkt'>, <class
'flop.mf6.modflow.mfgwt mst.ModflowGwt mst'>, <class
'flop.mf6.modflow.mfgwt mwt.ModflowGwt mwt'>, <class
'flop.mf6.modflow.mfgwt nam.ModflowGwt nam'>, <class
'flop.mf6.modflow.mfgwt oc.ModflowGwt oc'>, <class
'flop.mf6.modflow.mfgwt sft.ModflowGwt sft'>, <class
'flop.mf6.modflow.mfgwt src.ModflowGwt src'>, <class
'flop.mf6.modflow.mfgwt ssm.ModflowGwt ssm'>, <class
'flop.mf6.modflow.mfgwt uzt.ModflowGwt uzt'>, <class
'flop.mf6.modflow.mfmvr.ModflowMvr'>, <class 'flop.mf6.modflow.mfmvt.ModflowMvt'>,
<class 'flop.mf6.modflow.mfutlats.ModflowUtlats'>, <class
'flop.mf6.modflow.mfutlats.UtlatsPackages'>, <class
'flop.mf6.modflow.mfutllaktab.ModflowUtlaktab'>, <class
'flop.mf6.modflow.mfutllaktab.UtlaktabPackages'>, <class
'flop.mf6.modflow.mfutlobs.ModflowUtllobs'>, <class
'flop.mf6.modflow.mfutlobs.UtllobsPackages'>, <class

```

**property package\_dict**

Returns a copy of the package name dictionary.

**static package\_factory**(*package\_type: str, model\_type: str*)

Static method that returns the appropriate package type object based on the *package\_type* and *model\_type* strings. For internal FloPy use only, not intended for end users.

**Parameters**

- **package\_type** (*str*) – Type of package to create
- **model\_type** (*str*) – Type of model that package is a part of

**Returns package**

**Return type** MFPackage subclass

**static package\_list()**

Static method that returns the list of available packages. For internal FloPy use only, not intended for end users.

Returns a list of MFPackage subclasses

**property package\_names**

Returns a list of package names.

```

packages_by_abbr = {'gnc': <class 'flop.mf6.modflow.mfgnc.ModflowGnc'>, 'gwfapi':
<class 'flop.mf6.modflow.mfgwfapi.ModflowGwfapi'>, 'gwfbuy': <class
'flop.mf6.modflow.mfgwfbuy.ModflowGwfbuy'>, 'gwfchd': <class
'flop.mf6.modflow.mfgwfchd.ModflowGwfchd'>, 'gwfcsub': <class
'flop.mf6.modflow.mfgwfcsub.ModflowGwfcsub'>, 'gwfdis': <class
'flop.mf6.modflow.mfgwfdis.ModflowGwfdis'>, 'gwfdisu': <class
'flop.mf6.modflow.mfgwfdisu.ModflowGwfdisu'>, 'gwfdisv': <class
'flop.mf6.modflow.mfgwfdisv.ModflowGwfdisv'>, 'gwfdrn': <class
'flop.mf6.modflow.mfgwfdrn.ModflowGwfdrn'>, 'gwfevt': <class
'flop.mf6.modflow.mfgwfevt.ModflowGwfevt'>, 'gwfevta': <class
'flop.mf6.modflow.mfgwfevta.ModflowGwfevta'>, 'gwfgbh': <class
'flop.mf6.modflow.mfgwfgbh.ModflowGwfgbh'>, 'gwfgnc': <class
'flop.mf6.modflow.mfgwfgnc.ModflowGwfgnc'>, 'gwfgwf': <class
'flop.mf6.modflow.mfgwfgwf.ModflowGwfgwf'>, 'gwfgwt': <class
'flop.mf6.modflow.mfgwfgwt.ModflowGwfgwt'>, 'gwfhfb': <class
'flop.mf6.modflow.mfgwfhfb.ModflowGwfhfb'>, 'gwfic': <class
'flop.mf6.modflow.mfgwfic.ModflowGwfic'>, 'gwflak': <class
'flop.mf6.modflow.mfgwflak.ModflowGwflak'>, 'gwfmaw': <class
'flop.mf6.modflow.mfgwfmaw.ModflowGwfmaw'>, 'gwfmvr': <class
'flop.mf6.modflow.mfgwfmvr.ModflowGwfmvr'>, 'gwfnam': <class
'flop.mf6.modflow.mfgwfnam.ModflowGwfnam'>, 'gwfnpf': <class
'flop.mf6.modflow.mfgwfnpf.ModflowGwfnpf'>, 'gwfoc': <class
'flop.mf6.modflow.mfgwfoc.ModflowGwfoc'>, 'gwfrch': <class
'flop.mf6.modflow.mfgwfrch.ModflowGwfrch'>, 'gwfrcha': <class
'flop.mf6.modflow.mfgwfrcha.ModflowGwfrcha'>, 'gwfriv': <class
'flop.mf6.modflow.mfgwfriv.ModflowGwfriv'>, 'gwfsfr': <class
'flop.mf6.modflow.mfgwfsfr.ModflowGwfsfr'>, 'gwfsto': <class
'flop.mf6.modflow.mfgwfsto.ModflowGwfsto'>, 'gwzufz': <class
'flop.mf6.modflow.mfgwzufz.ModflowGwzufz'>, 'gwfwel': <class
'flop.mf6.modflow.mfgwfwel.ModflowGwfwel'>, 'gwtadv': <class
'flop.mf6.modflow.mfgwtadv.ModflowGwtadv'>, 'gwtapi': <class
'flop.mf6.modflow.mfgwtapi.ModflowGwtapi'>, 'gwtcnc': <class
'flop.mf6.modflow.mfgwtcnc.ModflowGwtcnc'>, 'gwtdis': <class
'flop.mf6.modflow.mfgwtdis.ModflowGwtdis'>, 'gwtdisu': <class
'flop.mf6.modflow.mfgwtdisu.ModflowGwtdisu'>, 'gwtdisv': <class
'flop.mf6.modflow.mfgwtdisv.ModflowGwtdisv'>, 'gwtdsp': <class
'flop.mf6.modflow.mfgwtdsp.ModflowGwtdsp'>, 'gwtfmi': <class
'flop.mf6.modflow.mfgwtfmi.ModflowGwtfmi'>, 'gwtgtw': <class
'flop.mf6.modflow.mfgwtgtw.ModflowGwtgtw'>, 'gwtic': <class
'flop.mf6.modflow.mfgwtic.ModflowGwtic'>, 'gwtist': <class
'flop.mf6.modflow.mfgwtist.ModflowGwtist'>, 'gwtlkt': <class
'flop.mf6.modflow.mfgwtlkt.ModflowGwtlkt'>, 'gwtmst': <class
'flop.mf6.modflow.mfgwtmst.ModflowGwtmst'>, 'gwtmvt': <class
'flop.mf6.modflow.mfgwtmvt.ModflowGwtmvt'>, 'gwtmwt': <class
'flop.mf6.modflow.mfgwtmwt.ModflowGwtmwt'>, 'gwtnam': <class
'flop.mf6.modflow.mfgwtnam.ModflowGwtnam'>, 'gwtoc': <class
'flop.mf6.modflow.mfgwtoc.ModflowGwtoc'>, 'gwtsft': <class
'flop.mf6.modflow.mfgwtsft.ModflowGwtsft'>, 'gwtsrc': <class
'flop.mf6.modflow.mfgwtsrc.ModflowGwtsrc'>, 'gwtssm': <class
'flop.mf6.modflow.mfgwtssm.ModflowGwtssm'>, 'gwtuzt': <class
'flop.mf6.modflow.mfgwtuzt.ModflowGwtuzt'>, 'ims': <class
'flop.mf6.modflow.mfims.ModflowIms'>, 'mvr': <class
'flop.mf6.modflow.mfmvr.ModflowMvr'>, 'mvt': <class
'flop.mf6.modflow.mfmvt.ModflowMvt'>, 'nam': <class
'flop.mf6.modflow.mfnam.ModflowNam'>, 'tdis': <class
'flop.mf6.modflow.mftdis.ModflowTdis'>, 'utlats': <class
'flop.mf6.modflow.mfutlats.ModflowUtlats'>, 'utlatspackages': <class
'flop.mf6.modflow.mfutlats.UtlatsPackages'>, 'utllaktab': <class
'flop.mf6.modflow.mfutllaktab.ModflowUtlaktab'>, 'utllaktabpackages': <class
'flop.mf6.modflow.mfutllaktab.UtlaktabPackages'>, 'utlobs': <class

```

**register\_package**(*package*)

Base method for registering a package. Should be overridden.

**class PackageContainerType**(*value*)

Bases: `enum.Enum`

Determines whether a package container is a simulation, model, or package.

**model** = 2

**package** = 3

**simulation** = 1

**exception ReadAsArraysException**

Bases: `Exception`

Exception occurs when loading ReadAsArrays package as non-ReadAsArrays package.

**exception StructException**(*error, location*)

Bases: `Exception`

Exception with the package file structure

**class VerbosityLevel**(*value*)

Bases: `enum.Enum`

Determines how much information FloPy writes to the console

**normal** = 2

**quiet** = 1

**verbose** = 3

## **flopy.mf6.mfmodel module**

**class MFModel**(*simulation, model\_type='gw6', modelname='model', model\_nam\_file=None, version='mf6', exe\_name='mf6.exe', add\_to\_simulation=True, structure=None, model\_rel\_path='.', verbose=False, \*\*kwargs*)

Bases: `flopy.mf6.mfbase.PackageContainer`, `flopy.mfbase.ModelInterface`

MODFLOW-6 model base class. Represents a single model in a simulation.

### **Parameters**

- **simulation\_data** (`MFSimulationData`) – Simulation data object of the simulation this model will belong to
- **structure** (`MFModelStructure`) – Structure of this type of model
- **modelname** (`str`) – Name of the model
- **model\_nam\_file** (`str`) – Relative path to the model name file from model working folder
- **version** (`str`) – Version of modflow
- **exe\_name** (`str`) – Model executable name
- **model\_ws** (`str`) – Model working folder path
- **disfile** (`str`) – Relative path to dis file from model working folder
- **grid\_type** (`str`) – Type of grid the model will use (structured, unstructured, vertices)
- **verbose** (`bool`) – Verbose setting for model operations (default False)



**name**

Name of the model

**Type** str**exe\_name**

Model executable name

**Type** str**packages**

Dictionary of model packages

**Type** dict of MFPackage**check**(*f=None, verbose=True, level=1*)

Check model data for common errors.

**Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If *f* is *None*, check method does not write results to a summary file. (default is *None*)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If *level=0*, summary checks are performed. If *level=1*, full checks are performed.

**Returns** success**Return type** bool**Examples**

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('model.nam')
>>> m.check()
```

**property exename**

MODFLOW executable name

**export**(*f, \*\*kwargs*)

Method to export a model to a shapefile or netcdf file

**Parameters**

- **f** (*str*) – File name (“*.nc*” for netcdf or “*.shp*” for shapefile) or dictionary of ...
- **\*\*kwargs** (*keyword arguments*) –
  - modelgrid**: **flopY.discretization.Grid** User supplied modelgrid object which will supercede the built in modelgrid object
  - epsg** [int] EPSG projection code
  - prj** [str] The prj file name
  - if *f* is set to ‘*vtk*’, parameters of *vtk.export\_model*

**get\_grid\_type()**

Return the type of grid used by model 'model\_name' in simulation containing simulation data 'simulation\_data'.

**Returns** grid type

**Return type** DiscretizationType

**get\_ims\_package()**

Get the IMS package associated with this model.

**Returns** IMS package

**Return type** *ModflowIms*

**get\_steadystate\_list()**

Returns a list of stress periods that are steady state.

**Returns** steady state list

**Return type** list

**property hdry**

Dry cell value

**property hnoflo**

No-flow cell value

**inspect\_cells(*cell\_list*, *stress\_period=None*, *output\_file\_path=None*, *inspect\_budget=True*, *inspect\_dependent\_var=True*)**

Inspect model cells. Returns model data associated with cells.

**Parameters**

- **cell\_list** (*list of tuples*) – List of model cells. Each model cell is a tuple of integers. ex: [(1,1,1), (2,4,3)]
- **stress\_period** (*int*) – For transient data only return data from this stress period. If not specified or None, all stress period data will be returned.
- **output\_file\_path** (*str*) – Path to output file that will contain the inspection results
- **inspect\_budget** (*bool*) – Inspect budget file
- **inspect\_dependent\_var** (*bool*) – Inspect head file

**Returns** output – Dictionary containing inspection results

**Return type** dict

**Examples**

```
>>> import flop
>>> sim = flop.mf6.MFSimulation.load("name", "mf6", "mf6.exe", ".")
>>> model = sim.get_model()
>>> inspect_list = [(2, 3, 2), (0, 4, 2), (0, 2, 4)]
>>> out_file = os.path.join("temp", "inspect_AdvGW_tidal.csv")
>>> model.inspect_cells(inspect_list, output_file_path=out_file)
```

**is\_valid()**

Checks the validity of the model and all of its packages

**Returns** valid

**Return type** bool

**property laycbd**

Quasi-3D confining bed. Not supported in MODFLOW-6.

**Returns** None

**Return type** None

**property laytyp**

Layering type

**classmethod load\_base**(*simulation, structure, modelname='NewModel',  
model\_name\_file='modflowtest.nam', mtype='gwf', version='mf6',  
exe\_name='mf6.exe', strict=True, model\_rel\_path='.', load\_only=None*)

Class method that loads an existing model.

**Parameters**

- **simulation** (*MFSimulation*) – simulation object that this model is a part of
- **simulation\_data** (*MFSimulationData*) – simulation data object
- **structure** (*MFModelStructure*) – structure of this type of model
- **model\_name** (*str*) – name of the model
- **model\_name\_file** (*str*) – relative path to the model name file from model working folder
- **version** (*str*) – version of modflow
- **exe\_name** (*str*) – model executable name
- **model\_ws** (*str*) – model working folder relative to simulation working folder
- **strict** (*bool*) – strict mode when loading files
- **model\_rel\_path** (*str*) – relative path of model folder to simulation folder
- **load\_only** (*list*) – list of package abbreviations or package names corresponding to packages that flop will load. default is None, which loads all packages. the discretization packages will load regardless of this setting. subpackages, like time series and observations, will also load regardless of this setting. example list: ['ic', 'maw', 'npf', 'oc', 'my\_well\_package\_1']

**Returns** model

**Return type** *MFModel*

## Examples

**load\_package**(*ftype, fname, pname, strict, ref\_path, dict\_package\_name=None, parent\_package=None*)

Loads a package from a file. This method is used internally by FloPy and is not intended for the end user.

**Parameters**

- **ftype** (*str*) – the file type
- **fname** (*str*) – the name of the file containing the package input
- **pname** (*str*) – the user-defined name for the package
- **strict** (*bool*) – strict mode when loading the file
- **ref\_path** (*str*) – path to the file. uses local path if set to None

- **dict\_package\_name** (*str*) – package name for dictionary lookup
- **parent\_package** (*MFPackage*) – parent package

## Examples

**match\_array\_cells**(*cell\_list*, *data\_shape*, *array\_data*, *key*, *data\_output*)

**property model\_ws**

Model file path.

**property modeldiscrit**

Basic model spatial discretization information. This is used internally prior to model spatial discretization information being fully loaded.

**Returns model grid** – FloPy object containing basic spatial discretization information for the model.

**Return type** Grid subclass

**property modelgrid**

Model spatial discretization information.

**Returns model grid** – FloPy object containing spatial discretization information for the model.

**Return type** Grid subclass

**property modeltime**

Model time discretization information.

**Returns modeltime** – FloPy object containing time discretization information for the simulation.

**Return type** *ModelTime*

**property namefile**

Model namefile object.

**property nper**

Number of stress periods.

**Returns nper** – Number of stress periods in the simulation.

**Return type** int

**property output**

**property packagelist**

List of model packages.

**plot**(*SelPackList=None*, *\*\*kwargs*)

Plot 2-D, 3-D, transient 2-D, and stress period list (MfList) model input data from a model instance

### Parameters

- **model** – Flopy model instance
- **SelPackList** – (list) list of package names to plot, if none all packages will be plotted
- **\*\*kwargs** – dict filename\_base : str

Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)

**file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')

**mflay** [int] MODFLOW zero-based layer number to return. If None, then all all layers will be included. (default is None)

**kper** [int] MODFLOW zero-based stress period number to return. (default is zero)

**key** [str] MfList dictionary key. (default is None)

#### Returns

**list** Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis are returned.

**Return type** axes

**register\_package**(package, add\_to\_package\_list=True, set\_package\_name=True, set\_package\_filename=True)

Registers a package with the model. This method is used internally by FloPy and is not intended for use by the end user.

#### Parameters

- **package** (MFPackage) – Package to register
- **add\_to\_package\_list** (bool) – Add package to lookup list
- **set\_package\_name** (bool) – Produce a package name for this package
- **set\_package\_filename** (bool) – Produce a filename for this package

**Returns** path, package structure

**Return type** tuple, MFPackageStructure

**remove\_package**(package\_name)

Removes package and all child packages from the model. *package\_name* can be the package's name, type, or package object to be removed from the model.

**Parameters** **package\_name** (str) – Package name, package type, or package object to be removed from the model.

**rename\_all\_packages**(name)

Renames all package files in the model.

**Parameters** **name** (str) – Prefix of package names. Packages files will be named <name>.<package ext>.

**set\_all\_data\_external**(check\_data=True, external\_data\_folder=None)

Sets the model's list and array data to be stored externally.

#### Parameters

- **check\_data** (bool) – Determines if data error checking is enabled during this process.
- **external\_data\_folder** – Folder, relative to the simulation path or model relative path (see use\_model\_relative\_path parameter), where external data will be stored

**set\_all\_data\_internal**(check\_data=True)

Sets the model's list and array data to be stored externally.

**Parameters** **check\_data** (bool) – Determines if data error checking is enabled during this process.

**set\_model\_relative\_path**(*model\_ws*)

Sets the file path to the model folder relative to the simulation folder and updates all model file paths, placing them in the model folder.

**Parameters** *model\_ws* (*str*) – Model working folder relative to simulation working folder

**property solver\_tols**

Returns the solver inner hclose and rclose values.

**Returns** *inner\_hclose*, *rclose*

**Return type** float, float

**update\_package\_filename**(*package*, *new\_name*)

Updates the filename for a package. For internal flop use only.

**Parameters**

- **package** (*MFPackage*) – Package object
- **new\_name** (*str*) – New package name

**property verbose**

Verbose setting for model operations (True/False)

**property version**

Version of MODFLOW

**write**(*ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Writes out model's package files.

**Parameters** *ext\_file\_action* (*ExtFileAction*) – Defines what to do with external files when the simulation path has changed. defaults to *copy\_relative\_paths* which copies only files with relative paths, leaving files defined by absolute paths fixed.

## flop.mf6.mfpackage module

**class MFBlock**(*simulation\_data*, *dimensions*, *structure*, *path*, *model\_or\_sim*, *container\_package*)

Bases: object

Represents a block in a MF6 input file. This class is used internally by FloPy and use by users of the FloPy library is not recommended.

**Parameters**

- **simulation\_data** (*MFSimulationData*) – Data specific to this simulation
- **dimensions** (*MFDimensions*) – Describes model dimensions including model grid and simulation time
- **structure** (*MFVariableStructure*) – Structure describing block
- **path** (*tuple*) – Unique path to block

**block\_headers**

Block header text (BEGIN/END), header variables, comments in the header

**Type** *MFBlockHeader*

**structure**

Structure describing block

**Type** *MFBlockStructure*

**path**

Unique path to block

**Type** tuple

**datasets**

Dictionary of dataset objects with keys that are the name of the dataset

**Type** OrderedDict

**datasets\_keyword**

Dictionary of dataset objects with keys that are key words to identify start of dataset

**Type** dict

**enabled**

If block is being used in the simulation

**Type** bool

**add\_dataset**(*dataset\_struct, data, var\_path*)

Add data to this block.

**data\_factory**(*sim\_data, model\_or\_sim, structure, enable, path, dimensions, data=None, package=None*)

Creates the appropriate data child object derived from MFData.

**header\_exists**(*key, data\_path=None*)**is\_allowed**()

Determine if block is valid based on the values of dependant MODFLOW variables.

**is\_empty**()

Returns true if this block is empty.

**is\_valid**()

Returns true if the block is valid.

**load**(*block\_header, fd, strict=True*)

Loads block from file object. file object must be advanced to beginning of block before calling.

**Parameters**

- **block\_header** ([MFBBlockHeader](#)) – Block header for block being loaded.
- **fd** (*file*) – File descriptor of file being loaded
- **strict** (*bool*) – Enforce strict MODFLOW 6 file format.

**set\_all\_data\_external**(*base\_name, check\_data=True, external\_data\_folder=None*)

Sets the block's list and array data to be stored externally, *base\_name* is external file name's prefix, *check\_data* determines if data error checking is enabled during this process.

**Parameters**

- **base\_name** (*str*) – Base file name of external files where data will be written to.
- **check\_data** (*bool*) – Whether to do data error checking.
- **external\_data\_folder** – Folder where external data will be stored

**set\_all\_data\_internal**(*check\_data=True*)

Sets the block's list and array data to be stored internally, *check\_data* determines if data error checking is enabled during this process.

**Parameters** **check\_data** (*bool*) – Whether to do data error checking.

**set\_model\_relative\_path**(*model\_ws*)

Sets *model\_ws* as the model path relative to the simulation's path.

**Parameters** *model\_ws* (*str*) – Model path relative to the simulation's path.

**write**(*fd*, *ext\_file\_action*=*ExtFileAction.copy\_relative\_paths*)

Writes block to a file object.

**Parameters** *fd* (*file object*) – File object to write to.

**class MFBlockHeader**(*name*, *variable\_strings*, *comment*, *simulation\_data*=*None*, *path*=*None*, *block*=*None*)

Bases: *object*

Represents the header of a block in a MF6 input file. This class is used internally by FloPy and its direct use by a user of this library is not recommend.

**Parameters**

- **name** (*str*) – Block name
- **variable\_strings** (*list*) – List of strings that appear after the block name
- **comment** (*MFComment*) – Comment text in the block header

**name**

Block name

**Type** *str*

**variable\_strings**

List of strings that appear after the block name

**Type** *list*

**comment**

Comment text in the block header

**Type** *MFComment*

**data\_items**

List of *MFVariable* of the variables contained in this block

**Type** *list*

**add\_data\_item**(*new\_data*, *data*)

Adds data to the block.

**build\_header\_variables**(*simulation\_data*, *block\_header\_structure*, *block\_path*, *data*, *dimensions*)

Builds data objects to hold header variables.

**connect\_to\_dict**(*simulation\_data*, *path*, *comment*=*None*)

Add comment to the simulation dictionary

**get\_comment**()

Get block header comment

**get\_transient\_key**(*data\_path*=*None*)

Get transient key associated with this block header.

**is\_same\_header**(*block\_header*)

Checks if *block\_header* is the same header as this header.

**write\_footer**(*fd*)

Writes block footer to file object *fd*.

**Parameters** *fd* (*file object*) – File object to write block footer to.



**write\_header**(*fd*)

Writes block header to file object *fd*.

**Parameters** *fd* (*file object*) – File object to write block header to.

**class MFChildPackages**(*model, parent, pkg\_type, filerecord, package=None, package\_class=None*)

Bases: `object`

Behind the scenes code for creating an interface to access child packages from a parent package. This class is automatically constructed by the FloPy library and is for internal library use only.

**class MFPackage**(*model\_or\_sim, package\_type, filename=None, pname=None, loading\_package=False, parent\_file=None*)

Bases: `flopy.mf6.mfbase.PackageContainer`, `flopy.pakbase.PackageInterface`

Provides an interface for the user to specify data to build a package.

**Parameters**

- **model\_or\_sim** (*MFModel of MFSimulation*) – The parent model or simulation containing this package
- **package\_type** (*str*) – String defining the package type
- **filename** (*str*) – Filename of file where this package is stored
- **quoted\_filename** (*str*) – Filename with quotes around it when there is a space in the name
- **pname** (*str*) – Package name
- **loading\_package** (*bool*) – Whether or not to add this package to the parent container's package list during initialization
- **parent\_file** (*MFPackage*) – Parent package that contains this package

**blocks**

Dictionary of blocks contained in this package by block name

**Type** `dict`

**path**

Data dictionary path to this package

**Type** `tuple`

**structure**

Describes the blocks and data contain in this package

**Type** `PackageStructure`

**dimensions**

Resolves data dimensions for data within this package

**Type** `PackageDimension`

**build\_child\_package**(*pkg\_type, data, parameter\_name, filerecord*)

Builds a child package. This method is only intended for FloPy internal use.

**build\_child\_packages\_container**(*pkg\_type, filerecord*)

Builds a container object for any child packages. This method is only intended for FloPy internal use.

**build\_mfdata**(*var\_name, data=None*)

Returns the appropriate data type object (`mfdatalist`, `mfddataArray`, or `mfdatascalar`) given that object the appropriate structure (looked up based on *var\_name*) and any data supplied. This method is for internal FloPy library use only.

**Parameters**

- **var\_name** (*str*) – Variable name
- **data** (*many supported types*) – Data contained in this object

**Returns data object**

**Return type** MFData subclass

**check**(*f=None, verbose=True, level=1, checktype=None*)

Data check, returns True on success.

**create\_package\_dimensions**()

Creates a package dimensions object. For internal FloPy library use.

**Returns package dimensions**

**Return type** PackageDimensions

**property data\_list**

List of data in this package.

**export**(*f, \*\*kwargs*)

Method to export a package to netcdf or shapefile based on the extension of the file name (.shp for shapefile, .nc for netcdf)

**Parameters**

- **f** (*str*) – Filename
- **kwargs** (*keyword arguments*) –
  - modelgrid** [flopY.discretization.Grid instance] User supplied modelgrid which can be used for exporting in lieu of the modelgrid associated with the model object

**Return type** None or Netcdf object

**property filename**

Package's file name.

**get\_file\_path**()

Returns the package file's path.

**Returns file path**

**Return type** str

**inspect\_cells**(*cell\_list, stress\_period=None*)

Inspect model cells. Returns package data associated with cells.

**Parameters**

- **cell\_list** (*list of tuples*) – List of model cells. Each model cell is a tuple of integers. ex: [(1,1,1), (2,4,3)]
- **stress\_period** (*int*) – For transient data, only return data from this stress period. If not specified or None, all stress period data will be returned.

**Returns output** – Array containing inspection results

**Return type** array

**is\_valid**()

Returns whether or not this package is valid.

**Returns is valid**

**Return type** bool

**load**(*strict=True*)

Loads the package from file.

**Parameters** **strict** (*bool*) – Enforce strict checking of data.

**Returns** **success**

**Return type** bool

**property name**

Name of package

**property output**

Method to get output associated with a specific package

**Return type** MF6Output object

**property package\_type**

String describing type of package

**property parent**

Parent package

**plot**(*\*\*kwargs*)

Plot 2-D, 3-D, transient 2-D, and stress period list (MfList) package input data

**Parameters** **\*\*kwargs** (*dict*) –

**filename\_base** [str] Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)

**file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')

**mflay** [int] MODFLOW zero-based layer number to return. If None, then all all layers will be included. (default is None)

**kper** [int] MODFLOW zero-based stress period number to return. (default is zero)

**key** [str] MfList dictionary key. (default is None)

**Returns** **axes** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis are returned.

**Return type** list

**property plottable**

If package is plottable

**property quoted\_filename**

Package's file name with quotes if there is a space.

**remove**()

Removes this package from the simulation/model it is currently a part of.

**set\_all\_data\_external**(*check\_data=True, external\_data\_folder=None*)

Sets the package's list and array data to be stored externally.

**Parameters**

- **check\_data** (*bool*) – Determine if data error checking is enabled
- **external\_data\_folder** – Folder where external data will be stored

**set\_all\_data\_internal**(*check\_data=True*)

Sets the package's list and array data to be stored internally.

**Parameters** **check\_data** (*bool*) – Determine if data error checking is enabled

**set\_model\_relative\_path**(*model\_ws*)

Sets the model path relative to the simulation's path.

**Parameters** **model\_ws** (*str*) – Model path relative to the simulation's path.

**write**(*ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Writes the package to a file.

**Parameters** **ext\_file\_action** ([ExtFileAction](#)) – How to handle pathing of external data files.

## MODFLOW 6 Simulation

MODFLOW 6 allows you to create simulations that can contain multiple models and packages. The FloPy for MODFLOW 6 simulation classes define functionality that applies to the entire MODFLOW 6 simulation. When using FloPy for MODFLOW 6 the first object you will most likely create is a simulation (MFSimulation) object.

Contents:

### `flopy.mf6.modflow.mfsimulation` module

**class** **MFSimulation**(*sim\_name='sim', version='mf6', exe\_name='mf6.exe', sim\_ws='.', verbosity\_level=1, continue\_=None, nocheck=None, memory\_print\_option=None, write\_headers=True*)

Bases: [flopy.mf6.mfbase.PackageContainer](#)

Entry point into any MODFLOW simulation.

MFSimulation is used to load, build, and/or save a MODFLOW 6 simulation. A MFSimulation object must be created before creating any of the MODFLOW 6 model objects.

#### Parameters

- **sim\_name** (*str*) – Name of the simulation.
- **version** (*str*) – Version of MODFLOW 6 executable
- **exe\_name** (*str*) – Relative path to MODFLOW 6 executable from the simulation working folder.
- **sim\_ws** (*str*) – Path to MODFLOW 6 simulation working folder. This is the folder containing the simulation name file.
- **verbosity\_level** (*int*) – Verbosity level of standard output from 0 to 2. When 0 is specified no standard output is written. When 1 is specified standard error/warning messages with some informational messages are written. When 2 is specified full error/warning/informational messages are written (this is ideal for debugging).
- **continue** (*bool*) – Sets the continue option in the simulation name file. The continue option is a keyword flag to indicate that the simulation should continue even if one or more solutions do not converge.
- **nocheck** (*bool*) – Sets the nocheck option in the simulation name file. The nocheck option is a keyword flag to indicate that the model input check routines should not be called prior to each time step. Checks are performed by default.

- **memory\_print\_option** (*str*) – Sets `memory_print_option` in the simulation name file. `Memory_print_option` is a flag that controls printing of detailed memory manager usage to the end of the simulation list file. `NONE` means do not print detailed information. `SUMMARY` means print only the total memory for each simulation component. `ALL` means print information for each variable stored in the memory manager. `NONE` is default if `memory_print_option` is not specified.
- **write\_headers** (*bool*) – When true flopY writes a header to each package file indicating that it was created by flopY.

## Examples

```
>>> s = MFSimulation.load('my simulation', 'simulation.nam')
```

### **sim\_name**

Name of the simulation

**Type** *str*

### **name\_file**

Simulation name file package

**Type** *MFPackage*

### **check**(*f=None, verbose=True, level=1*)

Check model data for common errors.

#### **Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If `f` is `None`, check method does not write results to a summary file. (default is `None`)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If `level=0`, summary checks are performed. If `level=1`, full checks are performed.

**Returns** **check list** – Python list containing simulation check results

**Return type** *list*

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('model.nam')
>>> m.check()
```

### **delete\_output\_files()**

Deletes simulation output files.

### **property\_exchange\_files**

Return list of exchange files associated with this simulation.

**Returns** *list*

**Return type** *list of exchange names*

**get\_exchange\_file**(*filename*)

Get a specified exchange file.

**Parameters** **filename** (*str*) – Name of exchange file to get

**Returns** exchange package

**Return type** *MFPackage*

**get\_gnc\_file**(*filename*)

Get a specified gnc file.

**Parameters** **filename** (*str*) – Name of gnc file to get

**Returns** gnc package

**Return type** *MFPackage*

**get\_ims\_package**(*key*)

Get the ims package with the specified *key*.

**Parameters** **key** (*str*) – ims package file name

**Returns** ims\_package

**Return type** *ModflowIms*

**get\_model**(*model\_name=None*)

Returns the models in the simulation with a given model name, name file name, or model type.

**Parameters** **model\_name** (*str*) – Name of the model to get. Passing in None or an empty list will get the first model.

**Returns** model

**Return type** *MFModel*

**get\_mvr\_file**(*filename*)

Get a specified mover file.

**Parameters** **filename** (*str*) – Name of mover file to get

**Returns** mover package

**Return type** *MFPackage*

**get\_mvt\_file**(*filename*)

Get a specified mvt file.

**Parameters** **filename** (*str*) – Name of mover transport file to get

**Returns** mover transport package

**Return type** *MFPackage*

**is\_valid**()

Checks the validity of the solution and all of its models and packages. Returns true if the solution is valid, false if it is not.

**Returns** **valid** – Whether this is a valid simulation

**Return type** bool

**classmethod** **load**(*sim\_name='modflowsim', version='mf6', exe\_name='mf6.exe', sim\_ws='.', strict=True, verbosity\_level=1, load\_only=None, verify\_data=False, write\_headers=True*)

Load an existing model.

**Parameters**

- **sim\_name** (*str*) – Name of the simulation.
- **version** (*str*) – MODFLOW version
- **exe\_name** (*str*) – Relative path to MODFLOW executable from the simulation working folder
- **sim\_ws** (*str*) – Path to simulation working folder
- **strict** (*bool*) – Strict enforcement of file formatting
- **verbosity\_level** (*int*) –

**Verbosity level of standard output** 0: No standard output 1: Standard error/warning messages with some informational

messages

**2: Verbose mode with full error/warning/informational** messages. This is ideal for debugging.

- **load\_only** (*list*) – List of package abbreviations or package names corresponding to packages that flopY will load. default is None, which loads all packages. the discretization packages will load regardless of this setting. subpackages, like time series and observations, will also load regardless of this setting. example list: ['ic', 'maw', 'npf', 'oc', 'ims', 'gwf6-gwf6']
- **verify\_data** (*bool*) – Verify data when it is loaded. this can slow down loading
- **write\_headers** (*bool*) – When true flopY writes a header to each package file indicating that it was created by flopY

**Returns** *sim*

**Return type** MFSimulation object

## Examples

```
>>> s = flopY.mf6.mfsimulation.load('my simulation')
```

**load\_package**(*ftype, fname, pname, strict, ref\_path, dict\_package\_name=None, parent\_package=None*)  
Load a package from a file.

### Parameters

- **ftype** (*str*) – the file type
- **fname** (*str*) – the name of the file containing the package input
- **pname** (*str*) – the user-defined name for the package
- **strict** (*bool*) – strict mode when loading the file
- **ref\_path** (*str*) – path to the file. uses local path if set to None
- **dict\_package\_name** (*str*) – package name for dictionary lookup
- **parent\_package** (MFPackage) – parent package

**property** *model\_dict*

Return a dictionary of models associated with this simulation.

**Returns** *model dict* – dictionary of models

**Return type** dict

**property model\_names**

Return a list of model names associated with this simulation.

**Returns** list

**Return type** list of model names

**plot**(*model\_list=None, SelPackList=None, \*\*kwargs*)

Plot simulation or models.

Method to plot a whole simulation or a series of models that are part of a simulation.

**Parameters**

- **model\_list** ((list)) – List of model names to plot, if none all models will be plotted
- **SelPackList** ((list)) – List of package names to plot, if none all packages will be plotted
- **kwargs** –
  - filename\_base** [str] Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
  - file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')
  - mflay** [int] MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)
  - kper** [int] MODFLOW zero-based stress period number to return. (default is zero)
  - key** [str] MFList dictionary key. (default is None)

**Returns** axes – matplotlib.pyplot.axes objects

**Return type** (list)

**register\_exchange\_file**(*package*)

Register an exchange package file with the simulation. This is a call-back method made from the package and should not be called directly.

**Parameters** **package** (MFPackage) – Exchange package object to register

**register\_ims\_package**(*ims\_file, model\_list*)

Register an ims package with the simulation.

**Parameters**

**ims\_file** [MFPackage] ims package to register

**model\_list** [list of strings] list of models using the ims package to be registered

**register\_model**(*model, model\_type, model\_name, model\_namefile*)

Add a model to the simulation. This is a call-back method made from the package and should not be called directly.

**Parameters**

- **model** (MFModel) – Model object to add to simulation
- **sln\_group** (str) – Solution group of model

**Returns** model\_structure\_object



**Return type** MFModelStructure

**register\_package**(*package*, *add\_to\_package\_list=True*, *set\_package\_name=True*,  
*set\_package\_filename=True*)

Register a package file with the simulation. This is a call-back method made from the package and should not be called directly.

**Parameters**

- **package** (MFPackage) – Package to register
- **add\_to\_package\_list** (*bool*) – Add package to lookup list
- **set\_package\_name** (*bool*) – Produce a package name for this package
- **set\_package\_filename** (*bool*) – Produce a filename for this package

**Returns** (*path*)

**Return type** tuple, package structure : MFPackageStructure)

**remove\_exchange\_file**(*package*)

Removes the exchange file “package”. This is for internal flopy library use only.

**Parameters** **package** (MFPackage) – Exchange package to be removed

**remove\_model**(*model\_name*)

Remove model with name *model\_name* from the simulation

**Parameters** **model\_name** (*str*) – Model name to remove from simulation

**remove\_package**(*package\_name*)

Removes package from the simulation. *package\_name* can be the package’s name, type, or package object to be removed from the model.

**Parameters** **package\_name** (*str*) – Name of package to be removed

**rename\_all\_packages**(*name*)

Rename all packages with name as prefix.

**Parameters** **name** (*str*) – Prefix of package names

**rename\_model\_namefile**(*model*, *new\_namefile*)

Rename a model’s namefile. For internal flopy library use only.

**Parameters**

- **model** (MFModel) – Model object whose namefile to rename
- **new\_namefile** (*str*) – Name of the new namefile

**run\_simulation**(*silent=None*, *pause=False*, *report=False*, *normal\_msg='normal termination'*,  
*use\_async=False*, *cargs=None*)

Run the simulation.

**Parameters**

- **silent** (*bool*) – Run in silent mode
- **pause** (*bool*) – Pause at end of run
- **report** (*bool*) – Save stdout lines to a list (buff)
- **normal\_msg** (*str or list*) – Normal termination message used to determine if the run terminated normally. More than one message can be provided using a list. (default is ‘normal termination’)

- **use\_async** (*bool*) – Asynchronously read model stdout and report with timestamps. good for models that take long time to run. not good for models that run really fast
- **cargs** (*str or list of strings*) – Additional command line arguments to pass to the executable. default is None

**Returns**

- **success** (*bool*)
- **buff** (*list of lines of stdout*)

**set\_all\_data\_external**(*check\_data=True, external\_data\_folder=None*)

Sets the simulation's list and array data to be stored externally.

**Parameters**

- **check\_data** (*bool*) – Determines if data error checking is enabled during this process. Data error checking can be slow on large datasets.
- **external\_data\_folder** – Folder, relative to the simulation path or model relative path (see `use_model_relative_path` parameter), where external data will be stored

**set\_all\_data\_internal**(*check\_data=True*)

**set\_sim\_path**(*path*)

Return a list of output data keys.

**Parameters** **path** (*str*) – Relative or absolute path to simulation root folder.

**property sim\_package\_list**

List of all “simulation level” packages

**update\_package\_filename**(*package, new\_name*)

Updates internal arrays to be consistent with a new file name. This is for internal flopY library use only.

**Parameters**

- **package** (*MFPackage*) – Package with new name
- **new\_name** (*str*) – Package's new name

**write\_simulation**(*ext\_file\_action=ExtFileAction.copy\_relative\_paths, silent=False*)

Write the simulation to files.

**Parameters**

**ext\_file\_action** [*ExtFileAction*] Defines what to do with external files when the simulation path has changed. Defaults to `copy_relative_paths` which copies only files with relative paths, leaving files defined by absolute paths fixed.

**silent** [*bool*] Writes out the simulation in silent mode (`verbosity_level = 0`)

**class MFSimulationData**(*path, mfsim*)

Bases: object

Class containing MODFLOW simulation data and file formatting data. Use `MFSimulationData` to set simulation-wide settings which include data formatting and file location settings.

**Parameters** **path** (*str*) – path on disk to the simulation

**indent\_string**

String used to define how much indent to use (file formatting)

**Type** *str*

**internal\_formatting**

List defining string to use for internal formatting

**Type** list

**external\_formatting**

List defining string to use for external formatting

**Type** list

**open\_close\_formatting**

List defining string to use for open/close

**Type** list

**max\_columns\_of\_data**

Maximum columns of data before line wraps. For structured grids this is set to ncol by default. For all other grids the default is 20.

**Type** int

**wrap\_multidim\_arrays**

Whether to wrap line for multi-dimensional arrays at the end of a row/column/layer

**Type** bool

**float\_precision**

Number of decimal points to write for a floating point number

**Type** int

**float\_characters**

Number of characters a floating point number takes up

**Type** int

**write\_headers**

When true flop writes a header to each package file indicating that it was created by flop

**Type** bool

**sci\_note\_upper\_thres**

Numbers greater than this threshold are written in scientific notation

**Type** float

**sci\_note\_lower\_thres**

Numbers less than this threshold are written in scientific notation

**Type** float

**mfp\_path**

File path location information for the simulation

**Type** *MFFileMgmt*

**model\_dimensions**

Dictionary containing discretization information for each model

**Type** dict

**mldata**

Custom dictionary containing all model data for the simulation

**Type** *SimulationDict*

**property max\_columns\_of\_data**

**set\_sci\_note\_lower\_thres**(*value*)

Sets threshold number where any number smaller than threshold is represented in scientific notation.

**Parameters** **value** (*float*) – threshold value

**set\_sci\_note\_upper\_thres**(*value*)

Sets threshold number where any number larger than threshold is represented in scientific notation.

**Parameters** **value** (*float*) – threshold value

**class SimulationDict**(*path=None*)

Bases: dict

Class containing custom dictionary for MODFLOW simulations. Dictionary contains model data. Dictionary keys are “paths” to the data that include the model and package containing the data.

Behaves as an dict with some additional features described below.

**Parameters** **path** (*MFFileMgmt*) – Object containing path information for the simulation

**find\_in\_path**(*key\_path, key\_leaf*)

Attempt to find *key\_leaf* in a partial key path *key\_path*.

**Parameters**

- **key\_path** (*str*) – partial path to the data
- **key\_leaf** (*str*) – name of the data

**Returns**

- **Data** (*MFData*.)
- **index** (*int*)

**input\_keys**()

Return a list of input data keys.

**Returns** **input keys**

**Return type** list

**keys**()

Return a list of all keys.

**Returns** **all keys**

**Return type** list

**observation\_keys**()

Return a list of observation keys.

**Returns** **observation keys**

**Return type** list

**output\_keys**(*print\_keys=True*)

Return a list of output data keys supported by the dictionary.

**Parameters** **print\_keys** (*bool*) – print keys to console

**Returns** **output keys**

**Return type** list

## MODFLOW 6 Simulation Packages

MODFLOW 6 simulation packages are the packages that are not necessarily tied to a specific model and can apply to the entire simulation or a group of models in the simulation.

Contents:

### flopY.mf6.modflow.mfgnc module

```
class ModflowGnc(simulation, loading_package=False, print_input=None, print_flows=None, explicit=None,
                  numgnc=None, numalphaj=None, gncdata=None, filename=None, pname=None,
                  parent_file=None)
```

Bases: `flopY.mf6.mfpackage.MFPackage`

ModflowGnc defines a gnc package.

#### Parameters

- **simulation** (`MFSimulation`) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (`boolean`) –
  - print\_input (boolean) keyword to indicate that the list of GNC information will be written to the listing file immediately after it is read.
- **print\_flows** (`boolean`) –
  - print\_flows (boolean) keyword to indicate that the list of GNC flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **explicit** (`boolean`) –
  - explicit (boolean) keyword to indicate that the ghost node correction is applied in an explicit manner on the right-hand side of the matrix. The explicit approach will likely require additional outer iterations. If the keyword is not specified, then the correction will be applied in an implicit manner on the left-hand side. The implicit approach will likely converge better, but may require additional memory. If the EXPLICIT keyword is not specified, then the BICGSTAB linear acceleration option should be specified within the LINEAR block of the Sparse Matrix Solver.
- **numgnc** (`integer`) –
  - numgnc (integer) is the number of GNC entries.
- **numalphaj** (`integer`) –
  - numalphaj (integer) is the number of contributing factors.
- **gncdata** (`[cellidn, cellidm, cellidsj, alphasj]`) –
  - cellidn ((integer, ...)) is the cellid of the cell, *n*, in which the ghost node is located. For a structured grid that uses the DIS input file, CELLIDN is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDN is the layer number and CELL2D number for the two cells. If the model uses the

unstructured discretization (DISU) input file, then CELLIDN is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- `cellidm` ((integer, ...)) is the cellid of the connecting cell,  $m$ , to which flow occurs from the ghost node. For a structured grid that uses the DIS input file, CELLIDM is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDM is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `cellidsj` ((integer, ...)) is the array of CELLIDS for the contributing  $j$  cells, which contribute to the interpolated head value at the ghost node. This item contains one CELLID for each of the contributing cells of the ghost node. Note that if the number of actual contributing cells needed by the user is less than NUMALPHAJ for any ghost node, then a dummy CELLID of zero(s) should be inserted with an associated contributing factor of zero. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLID is the layer number and cell2d number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `alphasj` (double) is the contributing factors for each contributing node in CELLIDSJ. Note that if the number of actual contributing cells is less than NUMALPHAJ for any ghost node, then dummy CELLIDS should be inserted with an associated contributing factor of zero. The sum of ALPHASJ should be less than one. This is because one minus the sum of ALPHASJ is equal to the alpha term (alpha  $n$  in equation 4-61 of the GWF Model report) that is multiplied by the head in cell  $n$ .
- **filename** (*String*) – File name for this package.
  - **pname** (*String*) – Package name for this package.
  - **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```

dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name explicit', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name numgnc', 'type integer', 'reader urword', 'optional false'], ['block
dimensions', 'name numalphaj', 'type integer', 'reader urword', 'optional false'],
['block gncdata', 'name gncdata', 'type recarray cellidn cellidm cellidsj alphasj',
'shape (maxbound)', 'reader urword'], ['block gncdata', 'name cellidn', 'type
integer', 'shape', 'tagged false', 'in_record true', 'reader urword', 'numeric_index
true'], ['block gncdata', 'name cellidm', 'type integer', 'shape', 'tagged false',
'in_record true', 'reader urword', 'numeric_index true'], ['block gncdata', 'name
cellidsj', 'type integer', 'shape (numalphaj)', 'tagged false', 'in_record true',
'reader urword', 'numeric_index true'], ['block gncdata', 'name alphasj', 'type
double precision', 'shape (numalphaj)', 'tagged false', 'in_record true', 'reader
urword']]

dfn_file_name = 'gwf-gnc.dfn'

gncdata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gnc'

```

## flopY.mf6.modflow.mfims module

```

class ModflowIms(simulation, loading_package=False, print_option=None, complexity=None,
    csv_output_filerecord=None, csv_outer_output_filerecord=None,
    csv_inner_output_filerecord=None, no_ptcrecord=None, ats_outer_maximum_fraction=None,
    outer_hclose=None, outer_dvclose=None, outer_rclosebnd=None, outer_maximum=None,
    under_relaxation=None, under_relaxation_gamma=None, under_relaxation_theta=None,
    under_relaxation_kappa=None, under_relaxation_momentum=None,
    backtracking_number=None, backtracking_tolerance=None,
    backtracking_reduction_factor=None, backtracking_residual_limit=None,
    inner_maximum=None, inner_hclose=None, inner_dvclose=None, rcloserecord=None,
    linear_acceleration=None, relaxation_factor=None, preconditioner_levels=None,
    preconditioner_drop_tolerance=None, number_orthogonalizations=None,
    scaling_method=None, reordering_method=None, filename=None, pname=None,
    parent_file=None)

```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowIms defines a ims package.

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_option** (*string*) –
  - print\_option (*string*) is a flag that controls printing of convergence information from the solver. NONE means print nothing. SUMMARY means print only the total number of iterations and nonlinear residual reduction summaries. ALL means print linear matrix solver convergence information to the solution listing file and model specific linear matrix solver convergence information to each model listing file in addition to SUMMARY information. NONE is default if PRINT\_OPTION is not specified.

- **complexity** (*string*) –
  - complexity (*string*) is an optional keyword that defines default non- linear and linear solver parameters. SIMPLE - indicates that default solver input values will be defined that work well for nearly linear models. This would be used for models that do not include nonlinear stress packages and models that are either confined or consist of a single unconfined layer that is thick enough to contain the water table within a single layer. MODERATE - indicates that default solver input values will be defined that work well for moderately nonlinear models. This would be used for models that include nonlinear stress packages and models that consist of one or more unconfined layers. The MODERATE option should be used when the SIMPLE option does not result in successful convergence. COMPLEX - indicates that default solver input values will be defined that work well for highly nonlinear models. This would be used for models that include nonlinear stress packages and models that consist of one or more unconfined layers representing complex geology and surface- water/groundwater interaction. The COMPLEX option should be used when the MODERATE option does not result in successful convergence. Non- linear and linear solver parameters assigned using a specified complexity can be modified in the NONLINEAR and LINEAR blocks. If the COMPLEXITY option is not specified, NONLINEAR and LINEAR variables will be assigned the simple complexity values.
- **csv\_output\_filerecord** (*[csvfile]*) –
  - csvfile (*string*) name of the ascii comma separated values output file to write solver convergence information. If PRINT\_OPTION is NONE or SUMMARY, comma separated values output includes maximum head change convergence information at the end of each outer iteration for each time step. If PRINT\_OPTION is ALL, comma separated values output includes maximum head change and maximum residual convergence information for the solution and each model (if the solution includes more than one model) and linear acceleration information for each inner iteration.
- **csv\_outer\_output\_filerecord** (*[outer\_csvfile]*) –
  - outer\_csvfile (*string*) name of the ascii comma separated values output file to write maximum dependent-variable (for example, head) change convergence information at the end of each outer iteration for each time step.
- **csv\_inner\_output\_filerecord** (*[inner\_csvfile]*) –
  - inner\_csvfile (*string*) name of the ascii comma separated values output file to write solver convergence information. Comma separated values output includes maximum dependent-variable (for example, head) change and maximum residual convergence information for the solution and each model (if the solution includes more than one model) and linear acceleration information for each inner iteration.
- **no\_ptcrecord** (*[no\_ptc\_option]*) –
  - no\_ptc\_option (*string*) is an optional keyword that is used to define options for disabling pseudo-transient continuation (PTC). FIRST is an optional keyword to disable PTC for the first stress period, if steady-state and one or more model is using the Newton-Raphson formulation. ALL is an optional keyword to disable PTC for all steady-state stress periods for models using the Newton-Raphson formulation. If NO\_PTC\_OPTION is not specified, the NO\_PTC ALL option is used.
- **ats\_outer\_maximum\_fraction** (*double*) –
  - ats\_outer\_maximum\_fraction (*double*) real value defining the fraction of the maximum allowable outer iterations used with the Adaptive Time Step (ATS) capability if it is active. If this value is set to zero by the user, then this solution will have no



effect on ATS behavior. This value must be greater than or equal to zero and less than or equal to 0.5 or the program will terminate with an error. If it is not specified by the user, then it is assigned a default value of one third. When the number of outer iterations for this solution is less than the product of this value and the maximum allowable outer iterations, then ATS will increase the time step length by a factor of DTADJ in the ATS input file. When the number of outer iterations for this solution is greater than the maximum allowable outer iterations minus the product of this value and the maximum allowable outer iterations, then the ATS (if active) will decrease the time step length by a factor of  $1 / \text{DTADJ}$ .

- **outer\_hclose** (*double*) –
  - outer\_hclose (double) real value defining the head change criterion for convergence of the outer (nonlinear) iterations, in units of length. When the maximum absolute value of the head change at all nodes during an iteration is less than or equal to OUTER\_HCLOSE, iteration stops. Commonly, OUTER\_HCLOSE equals 0.01. The OUTER\_HCLOSE option has been deprecated in favor of the more general OUTER\_DVCLOSE (for dependent variable), however either one can be specified in order to maintain backward compatibility.
- **outer\_dvclose** (*double*) –
  - outer\_dvclose (double) real value defining the dependent-variable (for example, head) change criterion for convergence of the outer (nonlinear) iterations, in units of the dependent-variable (for example, length for head). When the maximum absolute value of the dependent-variable change at all nodes during an iteration is less than or equal to OUTER\_DVCLOSE, iteration stops. Commonly, OUTER\_DVCLOSE equals 0.01. The keyword, OUTER\_HCLOSE can be still be specified instead of OUTER\_DVCLOSE for backward compatibility with previous versions of MODFLOW 6 but eventually OUTER\_HCLOSE will be deprecated and specification of OUTER\_HCLOSE will cause MODFLOW 6 to terminate with an error.
- **outer\_rclosebnd** (*double*) –
  - outer\_rclosebnd (double) real value defining the residual tolerance for convergence of model packages that solve a separate equation not solved by the IMS linear solver. This value represents the maximum allowable residual between successive outer iterations at any single model package element. An example of a model package that would use OUTER\_RCLOSEBND to evaluate convergence is the SFR package which solves a continuity equation for each reach. The OUTER\_RCLOSEBND option is deprecated and has no effect on simulation results as of version 6.1.1. The keyword, OUTER\_RCLOSEBND can be still be specified for backward compatibility with previous versions of MODFLOW 6 but eventually specification of OUTER\_RCLOSEBND will cause MODFLOW 6 to terminate with an error.
- **outer\_maximum** (*integer*) –
  - outer\_maximum (integer) integer value defining the maximum number of outer (nonlinear) iterations – that is, calls to the solution routine. For a linear problem OUTER\_MAXIMUM should be 1.
- **under\_relaxation** (*string*) –
  - under\_relaxation (string) is an optional keyword that defines the nonlinear under-relaxation schemes used. Under-relaxation is also known as dampening, and is used to reduce the size of the calculated dependent variable before proceeding to the next outer iteration. Under-relaxation can be an effective tool for highly nonlinear models when there are large and often counteracting changes in the calculated dependent variable between successive outer iterations. By default under-relaxation is not used.

NONE - under-relaxation is not used (default). SIMPLE - Simple under-relaxation scheme with a fixed relaxation factor (UNDER\_RELAXATION\_GAMMA) is used. COOLEY - Cooley under-relaxation scheme is used. DBD - delta-bar-delta under-relaxation is used. Note that the under-relaxation schemes are often used in conjunction with problems that use the Newton-Raphson formulation, however, experience has indicated that they also work well for non-Newton problems, such as those with the wet/dry options of MODFLOW 6.

- **under\_relaxation\_gamma** (*double*) –

- under\_relaxation\_gamma (double) real value defining either the relaxation factor for the SIMPLE scheme or the history or memory term factor of the Cooley and delta-bar-delta algorithms. For the SIMPLE scheme, a value of one indicates that there is no under-relaxation and the full head change is applied. This value can be gradually reduced from one as a way to improve convergence; for well behaved problems, using a value less than one can increase the number of outer iterations required for convergence and needlessly increase run times. UNDER\_RELAXATION\_GAMMA must be greater than zero for the SIMPLE scheme or the program will terminate with an error. For the Cooley and delta-bar-delta schemes, UNDER\_RELAXATION\_GAMMA is a memory term that can range between zero and one. When UNDER\_RELAXATION\_GAMMA is zero, only the most recent history (previous iteration value) is maintained. As UNDER\_RELAXATION\_GAMMA is increased, past history of iteration changes has greater influence on the memory term. The memory term is maintained as an exponential average of past changes. Retaining some past history can overcome granular behavior in the calculated function surface and therefore helps to overcome cyclic patterns of non-convergence. The value usually ranges from 0.1 to 0.3; a value of 0.2 works well for most problems. UNDER\_RELAXATION\_GAMMA only needs to be specified if UNDER\_RELAXATION is not NONE.

- **under\_relaxation\_theta** (*double*) –

- under\_relaxation\_theta (double) real value defining the reduction factor for the learning rate (under-relaxation term) of the delta-bar-delta algorithm. The value of UNDER\_RELAXATION\_THETA is between zero and one. If the change in the dependent-variable (for example, head) is of opposite sign to that of the previous iteration, the under-relaxation term is reduced by a factor of UNDER\_RELAXATION\_THETA. The value usually ranges from 0.3 to 0.9; a value of 0.7 works well for most problems. UNDER\_RELAXATION\_THETA only needs to be specified if UNDER\_RELAXATION is DBD.

- **under\_relaxation\_kappa** (*double*) –

- under\_relaxation\_kappa (double) real value defining the increment for the learning rate (under-relaxation term) of the delta-bar-delta algorithm. The value of UNDER\_RELAXATION\_kappa is between zero and one. If the change in the dependent-variable (for example, head) is of the same sign to that of the previous iteration, the under-relaxation term is increased by an increment of UNDER\_RELAXATION\_KAPPA. The value usually ranges from 0.03 to 0.3; a value of 0.1 works well for most problems. UNDER\_RELAXATION\_KAPPA only needs to be specified if UNDER\_RELAXATION is DBD.

- **under\_relaxation\_momentum** (*double*) –

- under\_relaxation\_momentum (double) real value defining the fraction of past history changes that is added as a momentum term to the step change for a nonlinear iteration. The value of UNDER\_RELAXATION\_MOMENTUM is between zero and one. A large momentum term should only be used when small learning rates

are expected. Small amounts of the momentum term help convergence. The value usually ranges from 0.0001 to 0.1; a value of 0.001 works well for most problems. UNDER\_RELAXATION\_MOMENTUM only needs to be specified if UNDER\_RELAXATION is DBD.

- **backtracking\_number** (*integer*) –
  - backtracking\_number (integer) integer value defining the maximum number of backtracking iterations allowed for residual reduction computations. If BACKTRACKING\_NUMBER = 0 then the backtracking iterations are omitted. The value usually ranges from 2 to 20; a value of 10 works well for most problems.
- **backtracking\_tolerance** (*double*) –
  - backtracking\_tolerance (double) real value defining the tolerance for residual change that is allowed for residual reduction computations. BACKTRACKING\_TOLERANCE should not be less than one to avoid getting stuck in local minima. A large value serves to check for extreme residual increases, while a low value serves to control step size more severely. The value usually ranges from 1.0 to  $10^6$ ; a value of  $10^4$  works well for most problems but lower values like 1.1 may be required for harder problems. BACKTRACKING\_TOLERANCE only needs to be specified if BACKTRACKING\_NUMBER is greater than zero.
- **backtracking\_reduction\_factor** (*double*) –
  - backtracking\_reduction\_factor (double) real value defining the reduction in step size used for residual reduction computations. The value of BACKTRACKING\_REDUCTION\_FACTOR is between zero and one. The value usually ranges from 0.1 to 0.3; a value of 0.2 works well for most problems. BACKTRACKING\_REDUCTION\_FACTOR only needs to be specified if BACKTRACKING\_NUMBER is greater than zero.
- **backtracking\_residual\_limit** (*double*) –
  - backtracking\_residual\_limit (double) real value defining the limit to which the residual is reduced with backtracking. If the residual is smaller than BACKTRACKING\_RESIDUAL\_LIMIT, then further backtracking is not performed. A value of 100 is suitable for large problems and residual reduction to smaller values may only slow down computations. BACKTRACKING\_RESIDUAL\_LIMIT only needs to be specified if BACKTRACKING\_NUMBER is greater than zero.
- **inner\_maximum** (*integer*) –
  - inner\_maximum (integer) integer value defining the maximum number of inner (linear) iterations. The number typically depends on the characteristics of the matrix solution scheme being used. For nonlinear problems, INNER\_MAXIMUM usually ranges from 60 to 600; a value of 100 will be sufficient for most linear problems.
- **inner\_hclose** (*double*) –
  - inner\_hclose (double) real value defining the head change criterion for convergence of the inner (linear) iterations, in units of length. When the maximum absolute value of the head change at all nodes during an iteration is less than or equal to INNER\_HCLOSE, the matrix solver assumes convergence. Commonly, INNER\_HCLOSE is set equal to or an order of magnitude less than the OUTER\_HCLOSE value specified for the NONLINEAR block. The INNER\_HCLOSE keyword has been deprecated in favor of the more general INNER\_DVCLOSE (for dependent variable), however either one can be specified in order to maintain backward compatibility.

- **inner\_dvclose** (*double*) –
  - inner\_dvclose (double) real value defining the dependent-variable (for example, head) change criterion for convergence of the inner (linear) iterations, in units of the dependent-variable (for example, length for head). When the maximum absolute value of the dependent-variable change at all nodes during an iteration is less than or equal to INNER\_DVCLOSE, the matrix solver assumes convergence. Commonly, INNER\_DVCLOSE is set equal to or an order of magnitude less than the OUTER\_DVCLOSE value specified for the NONLINEAR block. The keyword, INNER\_HCLOSE can be still be specified instead of INNER\_DVCLOSE for backward compatibility with previous versions of MODFLOW 6 but eventually INNER\_HCLOSE will be deprecated and specification of INNER\_HCLOSE will cause MODFLOW 6 to terminate with an error.
- **rcloserecord** (*[inner\_rclose, rclose\_option]*) –
  - inner\_rclose (double) real value that defines the flow residual tolerance for convergence of the IMS linear solver and specific flow residual criteria used. This value represents the maximum allowable residual at any single node. Value is in units of length cubed per time, and must be consistent with MODFLOW 6 length and time units. Usually a value of  $1.0 \times 10^{-1}$  is sufficient for the flow-residual criteria when meters and seconds are the defined MODFLOW 6 length and time.
  - rclose\_option (string) an optional keyword that defines the specific flow residual criterion used. STRICT—an optional keyword that is used to specify that INNER\_RCLOSE represents a infinity-Norm (absolute convergence criteria) and that the dependent-variable (for example, head) and flow convergence criteria must be met on the first inner iteration (this criteria is equivalent to the criteria used by the MODFLOW-2005 PCG package (Hill, 1990)). L2NORM\_RCLOSE—an optional keyword that is used to specify that INNER\_RCLOSE represents a L-2 Norm closure criteria instead of a infinity-Norm (absolute convergence criteria). When L2NORM\_RCLOSE is specified, a reasonable initial INNER\_RCLOSE value is 0.1 times the number of active cells when meters and seconds are the defined MODFLOW 6 length and time. RELATIVE\_RCLOSE—an optional keyword that is used to specify that INNER\_RCLOSE represents a relative L-2 Norm reduction closure criteria instead of a infinity-Norm (absolute convergence criteria). When RELATIVE\_RCLOSE is specified, a reasonable initial INNER\_RCLOSE value is  $1.0 \times 10^{-4}$  and convergence is achieved for a given inner (linear) iteration when  $\Delta h \leq \text{INNER\_DVCLOSE}$  and the current L-2 Norm is  $\leq$  the product of the RELATIVE\_RCLOSE and the initial L-2 Norm for the current inner (linear) iteration. If RCLOSE\_OPTION is not specified, an absolute residual (infinity-norm) criterion is used.
- **linear\_acceleration** (*string*) –
  - linear\_acceleration (string) a keyword that defines the linear acceleration method used by the default IMS linear solvers. CG - preconditioned conjugate gradient method. BICGSTAB - preconditioned bi-conjugate gradient stabilized method.
- **relaxation\_factor** (*double*) –
  - relaxation\_factor (double) optional real value that defines the relaxation factor used by the incomplete LU factorization preconditioners (MILU(0) and MILUT). RELAXATION\_FACTOR is unitless and should be greater than or equal to 0.0 and less than or equal to 1.0. RELAXATION\_FACTOR values of about 1.0 are commonly used, and experience suggests that convergence can be optimized in some cases with relax values of 0.97. A RELAXATION\_FACTOR value of 0.0 will result in either ILU(0) or ILUT preconditioning (depending on the value specified for PRECON-

DITIONER\_LEVELS and/or PRECONDITIONER\_DROP\_TOLERANCE). By default, RELAXATION\_FACTOR is zero.

- **preconditioner\_levels** (*integer*) –
  - preconditioner\_levels (*integer*) optional integer value defining the level of fill for ILU decomposition used in the ILUT and MILUT preconditioners. Higher levels of fill provide more robustness but also require more memory. For optimal performance, it is suggested that a large level of fill be applied (7 or 8) with use of a drop tolerance. Specification of a PRECONDITIONER\_LEVELS value greater than zero results in use of the ILUT preconditioner. By default, PRECONDITIONER\_LEVELS is zero and the zero-fill incomplete LU factorization preconditioners (ILU(0) and MILU(0)) are used.
- **preconditioner\_drop\_tolerance** (*double*) –
  - preconditioner\_drop\_tolerance (*double*) optional real value that defines the drop tolerance used to drop preconditioner terms based on the magnitude of matrix entries in the ILUT and MILUT preconditioners. A value of  $10^{-4}$  works well for most problems. By default, PRECONDITIONER\_DROP\_TOLERANCE is zero and the zero-fill incomplete LU factorization preconditioners (ILU(0) and MILU(0)) are used.
- **number\_orthogonalizations** (*integer*) –
  - number\_orthogonalizations (*integer*) optional integer value defining the interval used to explicitly recalculate the residual of the flow equation using the solver coefficient matrix, the latest dependent- variable (for example, head) estimates, and the right hand side. For problems that benefit from explicit recalculation of the residual, a number between 4 and 10 is appropriate. By default, NUMBER\_ORTHOGONALIZATIONS is zero.
- **scaling\_method** (*string*) –
  - scaling\_method (*string*) an optional keyword that defines the matrix scaling approach used. By default, matrix scaling is not applied. NONE - no matrix scaling applied. DIAGONAL - symmetric matrix scaling using the POLCG preconditioner scaling method in Hill (1992). L2NORM - symmetric matrix scaling using the L2 norm.
- **reordering\_method** (*string*) –
  - reordering\_method (*string*) an optional keyword that defines the matrix reordering approach used. By default, matrix reordering is not applied. NONE - original ordering. RCM - reverse Cuthill McKee ordering. MD - minimum degree ordering.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```
csv_inner_output_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```
csv_outer_output_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```
csv_output_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header'], ['block options', 'name print_option', 'type string', 'reader
urword', 'optional true'], ['block options', 'name complexity', 'type string',
'reader urword', 'optional true'], ['block options', 'name csv_output_filerecord',
'type record csv_output fileout csvfile', 'shape', 'reader urword', 'tagged true',
'optional true', 'deprecated 6.1.1'], ['block options', 'name csv_output', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false', 'deprecated 6.1.1'], ['block options', 'name csvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false', 'deprecated 6.1.1'], ['block options', 'name
csv_outer_output_filerecord', 'type record csv_outer_output fileout outer_csvfile',
'shape', 'reader urword', 'tagged true', 'optional true'], ['block options', 'name
csv_outer_output', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name fileout', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name outer_csvfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name csv_inner_output_filerecord', 'type record csv_inner_output
fileout inner_csvfile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name csv_inner_output', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
inner_csvfile', 'type string', 'preserve_case true', 'shape', 'in_record true',
'reader urword', 'tagged false', 'optional false'], ['block options', 'name
no_ptcrecord', 'type record no_ptc no_ptc_option', 'reader urword', 'optional
true'], ['block options', 'name no_ptc', 'type keyword', 'in_record true', 'reader
urword', 'optional false', 'tagged true'], ['block options', 'name no_ptc_option',
'type string', 'in_record true', 'reader urword', 'optional true', 'tagged false'],
['block options', 'name ats_outer_maximum_fraction', 'type double precision',
'reader urword', 'optional true'], ['block nonlinear', 'name outer_hclose', 'type
double precision', 'reader urword', 'optional true', 'deprecated 6.1.1'], ['block
nonlinear', 'name outer_dvclose', 'type double precision', 'reader urword',
'optional false'], ['block nonlinear', 'name outer_rclosebnd', 'type double
precision', 'reader urword', 'optional true', 'deprecated 6.1.1'], ['block
nonlinear', 'name outer_maximum', 'type integer', 'reader urword', 'optional
false'], ['block nonlinear', 'name under_relaxation', 'type string', 'reader
urword', 'optional true'], ['block nonlinear', 'name under_relaxation_gamma', 'type
double precision', 'reader urword', 'optional true'], ['block nonlinear', 'name
under_relaxation_theta', 'type double precision', 'reader urword', 'optional true'],
['block nonlinear', 'name under_relaxation_kappa', 'type double precision', 'reader
urword', 'optional true'], ['block nonlinear', 'name under_relaxation_momentum',
'type double precision', 'reader urword', 'optional true'], ['block nonlinear',
'name backtracking_number', 'type integer', 'reader urword', 'optional true'],
['block nonlinear', 'name backtracking_tolerance', 'type double precision', 'reader
urword', 'optional true'], ['block nonlinear', 'name backtracking_reduction_factor',
'type double precision', 'reader urword', 'optional true'], ['block nonlinear',
'name backtracking_residual_limit', 'type double precision', 'reader urword',
'optional true'], ['block linear', 'name inner_maximum', 'type integer', 'reader
urword', 'optional false'], ['block linear', 'name inner_hclose', 'type double
precision', 'reader urword', 'optional true', 'deprecated 6.1.1'], ['block linear',
'name inner_dvclose', 'type double precision', 'reader urword', 'optional false'],
['block linear', 'name rcloserecord', 'type record inner_rclose rclose_option',
'reader urword', 'optional false'], ['block linear', 'name inner_rclose', 'type
double precision', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block linear', 'name rclose_option', 'type string', 'tagged false',
'in_record true', 'reader urword', 'optional true'], ['block linear', 'name
linear_acceleration', 'type string', 'reader urword', 'optional false'], ['block
linear', 'name relaxation_factor', 'type double precision', 'reader urword',
'optional true'], ['block linear', 'name preconditioner_level', 'type integer',
'reader urword', 'optional true'], ['block linear', 'name
preconditioner_drop_tolerance', 'type double precision', 'reader urword', 'optional
true'], ['block linear', 'name number_orthogonalizations', 'type integer', 'reader

```

```

dfn_file_name = 'sln-ims.dfn'
no_ptcrecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'ims'
rcloserecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```

## flop.mf6.modflow.mfmvr module

```

class ModflowMvr(simulation, loading_package=False, print_input=None, print_flows=None,
                  modelnames=None, budget_filerecord=None, budgetcsv_filerecord=None, maxmvr=None,
                  maxpackages=None, packages=None, perioddata=None, filename=None, pname=None,
                  parent_file=None)

```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowMvr defines a mvr package. This package can only be used to move water between two different models. To move water between two packages in the same model use the “model level” mover package (ex. ModflowG-wfmvr).

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of MVR information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of MVR flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **modelnames** (*boolean*) –
  - modelnames (boolean) keyword to indicate that all package names will be preceded by the model name for the package. Model names are required when the Mover Package is used with a GWF-GWF Exchange. The MODELNAME keyword should not be used for a Mover Package that is for a single GWF Model.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (string) name of the output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **maxmvr** (*integer*) –
  - maxmvr (integer) integer value specifying the maximum number of water mover entries that will be specified for any stress period.

- **maxpackages** (*integer*) –
  - maxpackages (*integer*) integer value specifying the number of unique packages that are included in this water mover input file.
- **packages** (*[mname, pname]*) –
  - mname (*string*) name of model containing the package. Model names are assigned by the user in the simulation name file.
  - pname (*string*) is the name of a package that may be included in a subsequent stress period block. The package name is assigned in the name file for the GWF Model. Package names are optionally provided in the name file. If they are not provided by the user, then packages are assigned a default value, which is the package acronym followed by a hyphen and the package number. For example, the first Drain Package is named DRN-1. The second Drain Package is named DRN-2, and so forth.
- **perioddata** (*[mname1, pname1, id1, mname2, pname2, id2, mvrtype, value]*) –
  - mname1 (*string*) name of model containing the package, PNAME1.
  - pname1 (*string*) is the package name for the provider. The package PNAME1 must be designated to provide water through the MVR Package by specifying the keyword “MOVER” in its OPTIONS block.
  - id1 (*integer*) is the identifier for the provider. For the standard boundary packages, the provider identifier is the number of the boundary as it is listed in the package input file. (Note that the order of these boundaries may change by stress period, which must be accounted for in the Mover Package.) So the first well has an identifier of one. The second is two, and so forth. For the advanced packages, the identifier is the reach number (SFR Package), well number (MAW Package), or UZF cell number. For the Lake Package, ID1 is the lake outlet number. Thus, outflows from a single lake can be routed to different streams, for example. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - mname2 (*string*) name of model containing the package, PNAME2.
  - pname2 (*string*) is the package name for the receiver. The package PNAME2 must be designated to receive water from the MVR Package by specifying the keyword “MOVER” in its OPTIONS block.
  - id2 (*integer*) is the identifier for the receiver. The receiver identifier is the reach number (SFR Package), Lake number (LAK Package), well number (MAW Package), or UZF cell number. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - mvrtype (*string*) is the character string signifying the method for determining how much water will be moved. Supported values are “FACTOR” “EXCESS” “THRESHOLD” and “UPTO”. These four options determine how the receiver flow rate,  $Q_R$ , is calculated. These options mirror the options defined for the cprior variable in the SFR package, with the term “FACTOR” being functionally equivalent to the “FRACTION” option for cprior.
  - value (*double*) is the value to be used in the equation for calculating the amount of water to move. For the “FACTOR” option, VALUE is the  $\alpha$  factor. For the remaining options, VALUE is the specified flow rate,  $Q_S$ .



- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```

budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name modelnames', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block dimensions', 'name maxmvr', 'type integer', 'reader
urword', 'optional false'], ['block dimensions', 'name maxpackages', 'type integer',
'reader urword', 'optional false'], ['block packages', 'name packages', 'type
recarray mname pname', 'reader urword', 'shape (npackages)', 'optional false'],
['block packages', 'name mname', 'type string', 'reader urword', 'shape', 'tagged
false', 'in_record true', 'optional true'], ['block packages', 'name pname', 'type
string', 'reader urword', 'shape', 'tagged false', 'in_record true', 'optional
false'], ['block period', 'name iper', 'type integer', 'block_variable True',
'in_record true', 'tagged false', 'shape', 'valid', 'reader urword', 'optional
false'], ['block period', 'name perioddata', 'type recarray mname1 pname1 id1 mname2
pname2 id2 mvrtype value', 'shape (maxbound)', 'reader urword'], ['block period',
'name mname1', 'type string', 'reader urword', 'shape', 'tagged false', 'in_record
true', 'optional true'], ['block period', 'name pname1', 'type string', 'shape',
'tagged false', 'in_record true', 'reader urword'], ['block period', 'name id1',
'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name mname2', 'type string', 'reader
urword', 'shape', 'tagged false', 'in_record true', 'optional true'], ['block
period', 'name pname2', 'type string', 'shape', 'tagged false', 'in_record true',
'reader urword'], ['block period', 'name id2', 'type integer', 'shape', 'tagged
false', 'in_record true', 'reader urword', 'numeric_index true'], ['block period',
'name mvrtype', 'type string', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block period', 'name value', 'type double precision', 'shape', 'tagged
false', 'in_record true', 'reader urword']]

dfn_file_name = 'gwf-mvr.dfn'

package_abbr = 'mvr'

packages = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```

```
perioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flop.mf6.modflow.mfnam module

```
class ModflowNam(simulation, loading_package=False, continue_=None, nocheck=None,
                 memory_print_option=None, maxerrors=None, tdis6=None, models=None, exchanges=None,
                 mxiter=None, solutiongroup=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowNam defines a nam package.

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **continue** (*boolean*) –
  - continue (boolean) keyword flag to indicate that the simulation should continue even if one or more solutions do not converge.
- **nocheck** (*boolean*) –
  - nocheck (boolean) keyword flag to indicate that the model input check routines should not be called prior to each time step. Checks are performed by default.
- **memory\_print\_option** (*string*) –
  - memory\_print\_option (string) is a flag that controls printing of detailed memory manager usage to the end of the simulation list file. NONE means do not print detailed information. SUMMARY means print only the total memory for each simulation component. ALL means print information for each variable stored in the memory manager. NONE is default if MEMORY\_PRINT\_OPTION is not specified.
- **maxerrors** (*integer*) –
  - maxerrors (integer) maximum number of errors that will be stored and printed.
- **tdis6** (*string*) –
  - tdis6 (string) is the name of the Temporal Discretization (TDis) Input File.
- **models** (*[mtype, mfname, mname]*) –
  - mtype (string) is the type of model to add to simulation.
  - mfname (string) is the file name of the model name file.
  - mname (string) is the user-assigned name of the model. The model name cannot exceed 16 characters and must not have blanks within the name. The model name is case insensitive; any lowercase letters are converted and stored as upper case letters.
- **exchanges** (*[exgtype, exgfile, exgmnamea, exgmnameb]*) –
  - exgtype (string) is the exchange type.
  - exgfile (string) is the input file for the exchange.
  - exgmnamea (string) is the name of the first model that is part of this exchange.
  - exgmnameb (string) is the name of the second model that is part of this exchange.

- **mxiter** (*integer*) –
  - mxiter (*integer*) is the maximum number of outer iterations for this solution group. The default value is 1. If there is only one solution in the solution group, then MXITER must be 1.
- **solutiongroup** (*[slntype, slnfname, slnmnames]*) –
  - slntype (*string*) is the type of solution. The Integrated Model Solution (IMS6) is the only supported option in this version.
  - slnfname (*string*) name of file containing solution input.
  - slnmnames (*string*) is the array of model names to add to this solution. The number of model names is determined by the number of model names the user provides on this line.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```
dfn = [['header'], ['block options', 'name continue', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name nocheck', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name memory_print_option', 'type
string', 'reader urword', 'optional true'], ['block options', 'name maxerrors',
'type integer', 'reader urword', 'optional true'], ['block timing', 'name tdis6',
'preserve_case true', 'type string', 'reader urword', 'optional'], ['block models',
'name models', 'type recarray mtype mfname mname', 'reader urword', 'optional'],
['block models', 'name mtype', 'in_record true', 'type string', 'tagged false',
'reader urword'], ['block models', 'name mfname', 'in_record true', 'type string',
'preserve_case true', 'tagged false', 'reader urword'], ['block models', 'name
mname', 'in_record true', 'type string', 'tagged false', 'reader urword'], ['block
exchanges', 'name exchanges', 'type recarray exgtype exgfile exgmnamea exgmnameb',
'reader urword', 'optional'], ['block exchanges', 'name exgtype', 'in_record true',
'type string', 'tagged false', 'reader urword'], ['block exchanges', 'name exgfile',
'in_record true', 'type string', 'preserve_case true', 'tagged false', 'reader
urword'], ['block exchanges', 'name exgmnamea', 'in_record true', 'type string',
'tagged false', 'reader urword'], ['block exchanges', 'name exgmnameb', 'in_record
true', 'type string', 'tagged false', 'reader urword'], ['block solutiongroup',
'name group_num', 'type integer', 'block_variable True', 'in_record true', 'tagged
false', 'shape', 'reader urword'], ['block solutiongroup', 'name mxiter', 'type
integer', 'reader urword', 'optional true'], ['block solutiongroup', 'name
solutiongroup', 'type recarray slntype slnfname slnmnames', 'reader urword'],
['block solutiongroup', 'name slntype', 'type string', 'valid ims6', 'in_record
true', 'tagged false', 'reader urword'], ['block solutiongroup', 'name slnfname',
'type string', 'preserve_case true', 'in_record true', 'tagged false', 'reader
urword'], ['block solutiongroup', 'name slnmnames', 'type string', 'in_record true',
'shape (:)', 'tagged false', 'reader urword']]
```

```
dfn_file_name = 'sim-nam.dfn'
```

```
exchanges = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
models = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'nam'
```

```
solutiongroup = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flopY.mf6.modflow.mftdis module

```
class ModflowTdis(simulation, loading_package=False, time_units=None, start_date_time=None,
                  ats_filerecord=None, nper=1, perioddata=((1.0, 1, 1.0),), filename=None, pname=None,
                  parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowTdis defines a tdis package.

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **time\_units** (*string*) –
  - time\_units (*string*) is the time units of the simulation. This is a text string that is used as a label within model output files. Values for time\_units may be “unknown”, “seconds”, “minutes”, “hours”, “days”, or “years”. The default time unit is “unknown”.
- **start\_date\_time** (*string*) –
  - start\_date\_time (*string*) is the starting date and time of the simulation. This is a text string that is used as a label within the simulation list file. The value has no effect on the simulation. The recommended format for the starting date and time is described at <https://www.w3.org/TR/NOTE-datetime>.
- **ats\_filerecord** (*[ats6\_filename]*) –
  - ats6\_filename (*string*) defines an adaptive time step (ATS) input file defining ATS controls. Records in the ATS file can be used to override the time step behavior for selected stress periods.
- **nper** (*integer*) –
  - nper (*integer*) is the number of stress periods for the simulation.
- **perioddata** (*[perlen, nstp, tsmult]*) –
  - perlen (*double*) is the length of a stress period.
  - nstp (*integer*) is the number of time steps in a stress period.
  - tsmult (*double*) is the multiplier for the length of successive time steps. The length of a time step is calculated by multiplying the length of the previous time step by TSMULT. The length of the first time step,  $\Delta t_1$ , is related to PERLEN, NSTP, and TSMULT by the relation  $\Delta t_1 = \text{perlen} \frac{\text{tsmult}-1}{\text{tsmult}^{\text{nstp}}-1}$ .
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```
ats_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header'], ['block options', 'name time_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name start_date_time', 'type string',
'reader urword', 'optional true'], ['block options', 'name ats_filerecord', 'type
record ats6 filein ats6_filename', 'shape', 'reader urword', 'tagged true',
'optional true'], ['block options', 'name ats6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name ats6_filename', 'type string',
'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged
false'], ['block dimensions', 'name nper', 'type integer', 'reader urword',
'optional false', 'default_value 1'], ['block perioddata', 'name perioddata', 'type
recarray perlen nstp tsmult', 'reader urword', 'optional false', 'default_value
((1.0, 1, 1.0),)], ['block perioddata', 'name perlen', 'type double precision',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
perioddata', 'name nstp', 'type integer', 'in_record true', 'tagged false', 'reader
urword', 'optional false'], ['block perioddata', 'name tsmult', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false']]

dfn_file_name = 'sim-tdis.dfn'

package_abbr = 'tdis'

perioddata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

```

## MODFLOW 6 Models

MODFLOW 6 supports both groundwater flow (`mfgwf.ModflowGwf`) and groundwater transport (`mfgwt.ModflowGwt`) models. FloPy for MODFLOW 6 model objects can be constructed after a FloPy simulation (`MFSimulation`) object has been constructed.

Contents:

### `flopy.mf6.modflow.mfgwf` module

```

class ModflowGwf(simulation, modelname='model', model_nam_file=None, version='mf6', exe_name='mf6.exe',
                  model_rel_path='.', list=None, print_input=None, print_flows=None, save_flows=None,
                  newtonoptions=None, packages=None, **kwargs)

```

Bases: `flopy.mf6.mfmodel.MFModel`

Modflowgwf defines a gwf model

#### Parameters

- **modelname** (*string*) – name of the model
- **model\_nam\_file** (*string*) – relative path to the model name file from model working folder
- **version** (*string*) – version of modflow
- **exe\_name** (*string*) – model executable name
- **model\_ws** (*string*) – model working folder path
- **sim** (`MFSimulation`) – Simulation that this model is a part of. Model is automatically added to simulation when it is initialized.
- **list** (*string*) –

- list (string) is name of the listing file to create for this GWF model. If not specified, then the name of the list file will be the basename of the GWF model name file and the '.lst' extension. For example, if the GWF name file is called "my.model.nam" then the list file will be called "my.model.lst".
- **print\_input** (boolean) –
  - print\_input (boolean) keyword to indicate that the list of all model stress package information will be written to the listing file immediately after it is read.
- **print\_flows** (boolean) –
  - print\_flows (boolean) keyword to indicate that the list of all model package flow rates will be printed to the listing file for every stress period time step in which "BUDGET PRINT" is specified in Output Control. If there is no Output Control option and "PRINT\_FLOWS" is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (boolean) –
  - save\_flows (boolean) keyword to indicate that all model package flow terms will be written to the file specified with "BUDGET FILEOUT" in Output Control.
- **newtonoptions** ([under\_relaxation]) –
  - under\_relaxation (string) keyword that indicates whether the groundwater head in a cell will be under-relaxed when water levels fall below the bottom of the model below any given cell. By default, Newton-Raphson UNDER\_RELAXATION is not applied.
- **packages** ([ftype, fname, pname]) –
  - ftype (string) is the file type, which must be one of the following character values shown in table in mf6io.pdf. Ftype may be entered in any combination of uppercase and lowercase.
  - fname (string) is the name of the file containing the package input. The path to the file should be included if the file is not located in the folder where the program was run.
  - pname (string) is the user-defined name for the package. PNAME is restricted to 16 characters. No spaces are allowed in PNAME. PNAME character values are read and stored by the program for stress packages only. These names may be useful for labeling purposes when multiple stress packages of the same type are located within a single GWF Model. If PNAME is specified for a stress package, then PNAME will be used in the flow budget table in the listing file; it will also be used for the text entry in the cell-by-cell budget file. PNAME is case insensitive and is stored in all upper case letters.

```
load : (simulation : MFSimulationData, model_name : string,  
       namfile : string, version : string, exe_name : string, model_ws : string, strict : boolean) : MFSimulation  
a class method that loads a model from files
```

```
classmethod load(simulation, structure, modelname='NewModel', model_nam_file='modflowtest.nam',  
                version='mf6', exe_name='mf6.exe', strict=True, model_rel_path='.', load_only=None)
```

```
model_type = 'gwf'
```

## flopy.mf6.modflow.mfgwt module

```
class ModflowGwt(simulation, modelname='model', model_name_file=None, version='mf6', exe_name='mf6.exe',
                 model_rel_path='.', list=None, print_input=None, print_flows=None, save_flows=None,
                 packages=None, **kwargs)
```

Bases: `flopy.mf6.mfmodel.MFModel`

Modflowgwt defines a gwt model

### Parameters

- **modelname** (*string*) – name of the model
- **model\_name\_file** (*string*) – relative path to the model name file from model working folder
- **version** (*string*) – version of modflow
- **exe\_name** (*string*) – model executable name
- **model\_ws** (*string*) – model working folder path
- **sim** (`MFSimulation`) – Simulation that this model is a part of. Model is automatically added to simulation when it is initialized.
- **list** (*string*) –
  - list (*string*) is name of the listing file to create for this GWT model. If not specified, then the name of the list file will be the basename of the GWT model name file and the '.lst' extension. For example, if the GWT name file is called "my.model.name" then the list file will be called "my.model.lst".
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of all model stress package information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of all model package flow rates will be printed to the listing file for every stress period time step in which "BUDGET PRINT" is specified in Output Control. If there is no Output Control option and "PRINT\_FLOWS" is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that all model package flow terms will be written to the file specified with "BUDGET FILEOUT" in Output Control.
- **packages** (*[ftype, fname, pname]*) –
  - ftype (*string*) is the file type, which must be one of the following character values shown in table in mf6io.pdf. Ftype may be entered in any combination of uppercase and lowercase.
  - fname (*string*) is the name of the file containing the package input. The path to the file should be included if the file is not located in the folder where the program was run.
  - pname (*string*) is the user-defined name for the package. PNAME is restricted to 16 characters. No spaces are allowed in PNAME. PNAME character values are read and stored by the program for stress packages only. These names may be useful for labeling purposes when multiple stress packages of the same type are located within

a single GWT Model. If PNAME is specified for a stress package, then PNAME will be used in the flow budget table in the listing file; it will also be used for the text entry in the cell-by-cell budget file. PNAME is case insensitive and is stored in all upper case letters.

```
load : (simulation : MFSimulationData, model_name : string,  
       namfile : string, version : string, exe_name : string, model_ws : string, strict : boolean) : MFSimulation  
    a class method that loads a model from files  
  
classmethod load(simulation, structure, modelname='NewModel', model_nam_file='modflowtest.nam',  
                 version='mf6', exe_name='mf6.exe', strict=True, model_rel_path='.', load_only=None)  
  
model_type = 'gwt'
```

## MODFLOW 6 Groundwater Flow Model Packages

MODFLOW 6 groundwater flow models support a number of required and optional packages. Once a MODFLOW 6 groundwater flow model object (`mfgwf.ModflowGwf`) has been constructed various packages associated with the groundwater flow model can be constructed.

Contents:

### `flop.mf6.modflow.mfgwfapi` module

```
class ModflowGwfapi(model, loading_package=False, boundnames=None, print_input=None,  
                   print_flows=None, save_flows=None, observations=None, mover=None, maxbound=None,  
                   filename=None, pname=None, parent_file=None)  
Bases: flop.mf6.mfpackage.MFPackage
```

`ModflowGwfapi` defines a api package within a gw6 model.

#### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **boundnames** (`boolean`) –
  - `boundnames` (`boolean`) keyword to indicate that boundary names may be provided with the list of api boundary cells.
- **print\_input** (`boolean`) –
  - `print_input` (`boolean`) keyword to indicate that the list of api boundary information will be written to the listing file immediately after it is read.
- **print\_flows** (`boolean`) –
  - `print_flows` (`boolean`) keyword to indicate that the list of api boundary flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (`boolean`) –



- `save_flows` (boolean) keyword to indicate that api boundary flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (boolean) –
  - `mover` (boolean) keyword to indicate that this instance of the api boundary Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **maxbound** (integer) –
  - `maxbound` (integer) integer value specifying the maximum number of api boundary cells that will be specified for use during any stress period.
- **filename** (String) – File name for this package.
- **pname** (String) – Package name for this package.
- **parent\_file** (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name boundnames', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name print_input', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name print_flows',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
save_flows', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader
urword', 'tagged true', 'optional true', 'construct_package obs', 'construct_data
continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name maxbound', 'type integer', 'reader urword', 'optional false']]
```

```
dfn_file_name = 'gwf-api.dfn'
```

```
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'gwfapi'
```

## flop.mf6.modflow.mfgwfbuy module

```
class ModflowGwfbuy(model, loading_package=False, hhformulation_rhs=None, denseref=1000.0,
                    density_filerecord=None, dev_efh_formulation=None, nrhospecies=None,
                    packagedata=None, filename=None, pname=None, parent_file=None)
```

Bases: `flop.mf6.mfpackage.MFPackage`

ModflowGwfbuy defines a buy package within a gwf6 model.

### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **hhformulation\_rhs** (`boolean`) –
  - hhformulation\_rhs (`boolean`) use the variable-density hydraulic head formulation and add off-diagonal terms to the right-hand. This option will prevent the BUY Package from adding asymmetric terms to the flow matrix.
- **denseref** (`double`) –
  - denseref (`double`) fluid reference density used in the equation of state. This value is set to 1000. if not specified as an option.
- **density\_filerecord** (`[densityfile]`) –
  - densityfile (`string`) name of the binary output file to write density information. The density file has the same format as the head file. Density values will be written to the density file whenever heads are written to the binary head file. The settings for controlling head output are contained in the Output Control option.
- **dev\_efh\_formulation** (`boolean`) –
  - dev\_efh\_formulation (`boolean`) use the variable-density equivalent freshwater head formulation instead of the hydraulic head head formulation. This dev option has only been implemented for confined aquifer conditions and should generally not be used.
- **nrhospecies** (`integer`) –
  - nrhospecies (`integer`) number of species used in density equation of state. This value must be one or greater. The value must be one if concentrations are specified using the CONCENTRATION keyword in the PERIOD block below.
- **packagedata** (`[irhospec, drhodc, crhoref, modelname, auxspeciesname]`) –
  - irhospec (`integer`) integer value that defines the species number associated with the specified PACKAGEDATA data on the line. IRHOSPECIES must be greater than zero and less than or equal to NRHOSPECIES. Information must be specified for each of the NRHOSPECIES species or the program will terminate with an error. The program will also terminate with an error if information for a species is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - drhodc (`double`) real value that defines the slope of the density- concentration line for this species used in the density equation of state.

- `crhref` (double) real value that defines the reference concentration value used for this species in the density equation of state.
- `modelname` (string) name of GWT model used to simulate a species that will be used in the density equation of state. This name will have no effect if the simulation does not include a GWT model that corresponds to this GWF model.
- `auxspeciesname` (string) name of an auxiliary variable in a GWF stress package that will be used for this species to calculate a density value. If a density value is needed by the Buoyancy Package then it will use the concentration values in this AUXSPECIES-NAME column in the density equation of state. For advanced stress packages (LAK, SFR, MAW, and UZF) that have an associated advanced transport package (LKT, SFT, MWT, and UZT), the `FLOW_PACKAGE_AUXILIARY_NAME` option in the advanced transport package can be used to transfer simulated concentrations into the flow package auxiliary variable. In this manner, the Buoyancy Package can calculate density values for lakes, streams, multi-aquifer wells, and unsaturated zone flow cells using simulated concentrations.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```
density_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name hhformulation_rhs', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name denseref', 'type double',
'reader urword', 'optional true', 'default_value 1000.'], ['block options', 'name
density_filerecord', 'type record density fileout densityfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name density', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
densityfile', 'type string', 'preserve_case true', 'shape', 'in_record true',
'reader urword', 'tagged false', 'optional false'], ['block options', 'name
dev_efh_formulation', 'type keyword', 'reader urword', 'optional true'], ['block
dimensions', 'name nrhospecies', 'type integer', 'reader urword', 'optional false'],
['block packagedata', 'name packagedata', 'type recarray irhospec drhodc crhref
modelname auxspeciesname', 'shape (nrhospecies)', 'reader urword'], ['block
packagedata', 'name irhospec', 'type integer', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'numeric_index true'], ['block packagedata', 'name drhodc',
'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block packagedata', 'name crhref', 'type double precision', 'shape',
'tagged false', 'in_record true', 'reader urword'], ['block packagedata', 'name
modelname', 'type string', 'in_record true', 'tagged false', 'shape', 'reader
urword'], ['block packagedata', 'name auxspeciesname', 'type string', 'in_record
true', 'tagged false', 'shape', 'reader urword']]
```

```
dfn_file_name = 'gwf-buy.dfn'
```

```
package_abbr = 'gwfbuy'
```

```
packagedata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flop.mf6.modflow.mfgwfchd module

```
class ModflowGwfchd(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, maxbound=None, stress_period_data=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfchd defines a chd package within a gwf6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of CHD head value.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of constant-head cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of constant- head information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of constant- head flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that constant-head flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just

for the timeseries variable is also acceptable. See ts package documentation for more information.

- **observations** (*{varname:data}* or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **maxbound** (*integer*) –
  - maxbound (*integer*) integer value specifying the maximum number of constant-head cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, head, aux, boundname]*) –
  - cellid (*(integer, ...)*) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - head (*double*) is the head at the boundary. If the Options block includes a TIME-SERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (*double*) represents the values of the auxiliary variables for each constant head. The values of auxiliary variables must be present for each constant head. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIME-SERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (*string*) name of the constant head boundary cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

**auxiliary** = <flop.flop6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block
options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name print_input', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name save_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type
record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional
true', 'construct_package ts', 'construct_data timeseries', 'parameter_name
timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name ts6_filename', 'type string',
'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged
false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block dimensions', 'name maxbound',
'type integer', 'reader urword', 'optional false'], ['block period', 'name iper',
'type integer', 'block_variable True', 'in_record true', 'tagged false', 'shape',
'valid', 'reader urword', 'optional false'], ['block period', 'name
stress_period_data', 'type recarray cellid head aux boundname', 'shape (maxbound)',
'reader urword'], ['block period', 'name cellid', 'type integer', 'shape
(ncelldim)', 'tagged false', 'in_record true', 'reader urword'], ['block period',
'name head', 'type double precision', 'shape', 'tagged false', 'in_record true',
'reader urword', 'time_series true'], ['block period', 'name aux', 'type double
precision', 'in_record true', 'tagged false', 'shape (naux)', 'reader urword',
'optional true', 'time_series true'], ['block period', 'name boundname', 'type
string', 'shape', 'tagged false', 'in_record true', 'reader urword', 'optional
true']]

dfn_file_name = 'gwf-chd.dfn'

obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwfchd'

stress_period_data = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

**flop.mf6.modflow.mfgwfcs sub module**

```
class ModflowGwfcs sub(model, loading_package=False, boundnames=None, print_input=None,
    save_flows=None, gammaw=9806.65, beta=4.6512e-10, head_based=None,
    initial_preconsolidation_head=None, ndelaycells=None, compression_indices=None,
    update_material_properties=None, cell_fraction=None,
    specified_initial_interbed_state=None, specified_initial_preconsolidation_stress=None,
    specified_initial_delay_head=None, effective_stress_lag=None,
    strainib_filerecord=None, straincg_filerecord=None, compaction_filerecord=None,
    fileout=None, compaction_elastic_filerecord=None,
    compaction_inelastic_filerecord=None, compaction_interbed_filerecord=None,
    compaction_coarse_filerecord=None, zdisplacement_filerecord=None,
    package_convergence_filerecord=None, timeseries=None, observations=None,
    ninterbeds=None, maxsig0=None, cg_ske_cr=1e-05, cg_theta=0.2, sgm=None,
    sgs=None, packagedata=None, stress_period_data=None, filename=None,
    pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfcs sub defines a csub package within a gw6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of CSUB cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of CSUB information will be written to the listing file immediately after it is read.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that cell-by-cell flow terms will be written to the file specified with “BUDGET SAVE FILE” in Output Control.
- **gammaw** (*double*) –
  - gammaw (double) unit weight of water. For freshwater, GAMMAW is 9806.65 Newtons/cubic meters or 62.48 lb/cubic foot in SI and English units, respectively. By default, GAMMAW is 9806.65 Newtons/cubic meters.
- **beta** (*double*) –
  - beta (double) compressibility of water. Typical values of BETA are 4.6512e-10 1/Pa or 2.2270e-8 lb/square foot in SI and English units, respectively. By default, BETA is 4.6512e-10 1/Pa.
- **head\_based** (*boolean*) –
  - head\_based (boolean) keyword to indicate the head-based formulation will be used to simulate coarse-grained aquifer materials and no- delay and delay interbeds. Specifying HEAD\_BASED also specifies the INITIAL\_PRECONSOLIDATION\_HEAD option.

- **initial\_preconsolidation\_head** (*boolean*) –
  - initial\_preconsolidation\_head (boolean) keyword to indicate that preconsolidation heads will be specified for no-delay and delay interbeds in the PACKAGEDATA block. If the SPECIFIED\_INITIAL\_INTERBED\_STATE option is specified in the OPTIONS block, user-specified preconsolidation heads in the PACKAGEDATA block are absolute values. Otherwise, user-specified preconsolidation heads in the PACKAGEDATA block are relative to steady-state or initial heads.
- **ndelaycells** (*integer*) –
  - ndelaycells (integer) number of nodes used to discretize delay interbeds. If not specified, then a default value of 19 is assigned.
- **compression\_indices** (*boolean*) –
  - compression\_indices (boolean) keyword to indicate that the recompression (CR) and compression (CC) indices are specified instead of the elastic specific storage (SSE) and inelastic specific storage (SSV) coefficients. If not specified, then elastic specific storage (SSE) and inelastic specific storage (SSV) coefficients must be specified.
- **update\_material\_properties** (*boolean*) –
  - update\_material\_properties (boolean) keyword to indicate that the thickness and void ratio of coarse-grained and interbed sediments (delay and no-delay) will vary during the simulation. If not specified, the thickness and void ratio of coarse-grained and interbed sediments will not vary during the simulation.
- **cell\_fraction** (*boolean*) –
  - cell\_fraction (boolean) keyword to indicate that the thickness of interbeds will be specified in terms of the fraction of cell thickness. If not specified, interbed thickness must be specified.
- **specified\_initial\_interbed\_state** (*boolean*) –
  - specified\_initial\_interbed\_state (boolean) keyword to indicate that absolute preconsolidation stresses (heads) and delay bed heads will be specified for interbeds defined in the PACKAGEDATA block. The SPECIFIED\_INITIAL\_INTERBED\_STATE option is equivalent to specifying the SPECIFIED\_INITIAL\_PRECONSOLIDATION\_STRESS and SPECIFIED\_INITIAL\_DELAY\_HEAD. If SPECIFIED\_INITIAL\_INTERBED\_STATE is not specified then preconsolidation stress (head) and delay bed head values specified in the PACKAGEDATA block are relative to simulated values of the first stress period if steady-state or initial stresses and GWF heads if the first stress period is transient.
- **specified\_initial\_preconsolidation\_stress** (*boolean*) –
  - specified\_initial\_preconsolidation\_stress (boolean) keyword to indicate that absolute preconsolidation stresses (heads) will be specified for interbeds defined in the PACKAGEDATA block. If SPECIFIED\_INITIAL\_PRECONSOLIDATION\_STRESS and SPECIFIED\_INITIAL\_INTERBED\_STATE are not specified then preconsolidation stress (head) values specified in the PACKAGEDATA block are relative to simulated values if the first stress period is steady-state or initial stresses (heads) if the first stress period is transient.
- **specified\_initial\_delay\_head** (*boolean*) –
  - specified\_initial\_delay\_head (boolean) keyword to indicate that absolute initial delay bed head will be specified for interbeds defined in the PACK-



AGEDATA block. If SPECIFIED\_INITIAL\_DELAY\_HEAD and SPECIFIED\_INITIAL\_INTERBED\_STATE are not specified then delay bed head values specified in the PACKAGEDATA block are relative to simulated values if the first stress period is steady-state or initial GWF heads if the first stress period is transient.

- **effective\_stress\_lag** (*boolean*) –
  - effective\_stress\_lag (boolean) keyword to indicate the effective stress from the previous time step will be used to calculate specific storage values. This option can 1) help with convergence in models with thin cells and water table elevations close to land surface; 2) is identical to the approach used in the SUBWT package for MODFLOW-2005; and 3) is only used if the effective-stress formulation is being used. By default, current effective stress values are used to calculate specific storage values.
- **strainib\_filerecord** (*[interbedstrain\_filename]*) –
  - interbedstrain\_filename (string) name of the comma-separated-values output file to write final interbed strain information.
- **straincg\_filerecord** (*[coarsestrain\_filename]*) –
  - coarsestrain\_filename (string) name of the comma-separated-values output file to write final coarse-grained material strain information.
- **compaction\_filerecord** (*[compaction\_filename]*) –
  - compaction\_filename (string) name of the binary output file to write compaction information.
- **fileout** (*boolean*) –
  - fileout (boolean) keyword to specify that an output filename is expected next.
- **compaction\_elastic\_filerecord** (*[elastic\_compaction\_filename]*) –
  - elastic\_compaction\_filename (string) name of the binary output file to write elastic interbed compaction information.
- **compaction\_inelastic\_filerecord** (*[inelastic\_compaction\_filename]*) –
  - inelastic\_compaction\_filename (string) name of the binary output file to write inelastic interbed compaction information.
- **compaction\_interbed\_filerecord** (*[interbed\_compaction\_filename]*) –
  - interbed\_compaction\_filename (string) name of the binary output file to write interbed compaction information.
- **compaction\_coarse\_filerecord** (*[coarse\_compaction\_filename]*) –
  - coarse\_compaction\_filename (string) name of the binary output file to write elastic coarse-grained material compaction information.
- **zdisplacement\_filerecord** (*[zdisplacement\_filename]*) –
  - zdisplacement\_filename (string) name of the binary output file to write z-displacement information.
- **package\_convergence\_filerecord** (*[package\_convergence\_filename]*) –
  - package\_convergence\_filename (string) name of the comma spaced values output file to write package convergence information.
- **timeseries** (*{varname:data} or timeseries data*) –

- Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **ninterbeds** (*integer*) –
  - ninterbeds (integer) is the number of CSUB interbed systems. More than 1 CSUB interbed systems can be assigned to a GWF cell; however, only 1 GWF cell can be assigned to a single CSUB interbed system.
- **maxsig0** (*integer*) –
  - maxsig0 (integer) is the maximum number of cells that can have a specified stress offset. More than 1 stress offset can be assigned to a GWF cell. By default, MAXSIG0 is 0.
- **cg\_ske\_cr** (*[double]*) –
  - cg\_ske\_cr (double) is the initial elastic coarse-grained material specific storage or recompression index. The recompression index is specified if COMPRESSION\_INDICES is specified in the OPTIONS block. Specified or calculated elastic coarse-grained material specific storage values are not adjusted from initial values if HEAD\_BASED is specified in the OPTIONS block.
- **cg\_theta** (*[double]*) –
  - cg\_theta (double) is the initial porosity of coarse-grained materials.
- **sgm** (*[double]*) –
  - sgm (double) is the specific gravity of moist or unsaturated sediments. If not specified, then a default value of 1.7 is assigned.
- **sgs** (*[double]*) –
  - sgs (double) is the specific gravity of saturated sediments. If not specified, then a default value of 2.0 is assigned.
- **packagedata** (*([icsubno, cellid, cdelay, pcs0, thick\_frac, rnb, ssv\_cc,])*) –
  - **sse\_cr, theta, kv, h0, boundname**
    - icsubno (integer) integer value that defines the CSUB interbed number associated with the specified PACKAGEDATA data on the line. CSUBNO must be greater than zero and less than or equal to NINTERBEDS. CSUB information must be specified for every CSUB cell or the program will terminate with an error. The program will also terminate with an error if information for a CSUB interbed number is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
    - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID

is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- cdelay (string) character string that defines the subsidence delay type for the interbed. Possible subsidence package CDELAY strings include: NODELAY–character keyword to indicate that delay will not be simulated in the interbed. DELAY–character keyword to indicate that delay will be simulated in the interbed.
  - pcs0 (double) is the initial offset from the calculated initial effective stress or initial preconsolidation stress in the interbed, in units of height of a column of water. PCS0 is the initial preconsolidation stress if SPECIFIED\_INITIAL\_INTERBED\_STATE or SPECIFIED\_INITIAL\_PRECONSOLIDATION\_STRESS are specified in the OPTIONS block. If HEAD\_BASED is specified in the OPTIONS block, PCS0 is the initial offset from the calculated initial head or initial preconsolidation head in the CSUB interbed and the initial preconsolidation stress is calculated from the calculated initial effective stress or calculated initial geostatic stress, respectively.
  - thick\_frac (double) is the interbed thickness or cell fraction of the interbed. Interbed thickness is specified as a fraction of the cell thickness if CELL\_FRACTION is specified in the OPTIONS block.
  - rnb (double) is the interbed material factor equivalent number of interbeds in the interbed system represented by the interbed. RNB must be greater than or equal to 1 if CDELAY is DELAY. Otherwise, RNB can be any value.
  - ssv\_cc (double) is the initial inelastic specific storage or compression index of the interbed. The compression index is specified if COMPRESSION\_INDICES is specified in the OPTIONS block. Specified or calculated interbed inelastic specific storage values are not adjusted from initial values if HEAD\_BASED is specified in the OPTIONS block.
  - sse\_cr (double) is the initial elastic coarse-grained material specific storage or recompression index of the interbed. The recompression index is specified if COMPRESSION\_INDICES is specified in the OPTIONS block. Specified or calculated interbed elastic specific storage values are not adjusted from initial values if HEAD\_BASED is specified in the OPTIONS block.
  - theta (double) is the initial porosity of the interbed.
  - kv (double) is the vertical hydraulic conductivity of the delay interbed. KV must be greater than 0 if CDELAY is DELAY. Otherwise, KV can be any value.
  - h0 (double) is the initial offset from the head in cell cellid or the initial head in the delay interbed. H0 is the initial head in the delay bed if SPECIFIED\_INITIAL\_INTERBED\_STATE or SPECIFIED\_INITIAL\_DELAY\_HEAD are specified in the OPTIONS block. H0 can be any value if CDELAY is NODELAY.
  - boundname (string) name of the CSUB cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **stress\_period\_data([cellid, sig0])**–

- `cellid` ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
- `sig0` (double) is the stress offset for the cell. SIG0 is added to the calculated geostatic stress for the cell. SIG0 is specified only if MAXSIG0 is specified to be greater than 0 in the DIMENSIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```
cg_ske_cr = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
cg_theta = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
compaction_coarse_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
compaction_elastic_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
compaction_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
compaction_inelastic_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
compaction_interbed_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```

dfn = [['header'], ['block options', 'name boundnames', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name print_input', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name save_flows',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name gammaw',
'type double precision', 'reader urword', 'optional true', 'default_value 9806.65'],
['block options', 'name beta', 'type double precision', 'reader urword', 'optional
true', 'default_value 4.6512e-10'], ['block options', 'name head_based', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
initial_preconsolidation_head', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name ndelaycells', 'type integer', 'reader urword', 'optional
true'], ['block options', 'name compression_indices', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name update_material_properties',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
cell_fraction', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name specified_initial_interbed_state', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name specified_initial_preconsolidation_stress', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
specified_initial_delay_head', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name effective_stress_lag', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name strainib_filerecord', 'type record
strain_csv_interbed fileout interbedstrain_filename', 'shape', 'reader urword',
'tagged true', 'optional true'], ['block options', 'name strain_csv_interbed', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
interbedstrain_filename', 'type string', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name straincg_filerecord',
'type record strain_csv_coarse fileout coarsestrain_filename', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name
strain_csv_coarse', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name coarsestrain_filename',
'type string', 'shape', 'in_record true', 'reader urword', 'tagged false', 'optional
false'], ['block options', 'name compaction_filerecord', 'type record compaction
fileout compaction_filename', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name compaction', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
fileout', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name compaction_filename', 'type string',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name compaction_elastic_filerecord', 'type record
compaction_elastic fileout elastic_compaction_filename', 'shape', 'reader urword',
'tagged true', 'optional true'], ['block options', 'name compaction_elastic', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name elastic_compaction_filename', 'type string',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name compaction_inelastic_filerecord', 'type record
compaction_inelastic fileout inelastic_compaction_filename', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name
compaction_inelastic', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name
inelastic_compaction_filename', 'type string', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
compaction_interbed_filerecord', 'type record compaction_interbed fileout
interbed_compaction_filename', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name compaction_interbed', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name interbed_compaction_filename', 'type string', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block options', 'name
compaction_coarse_filerecord', 'type record compaction_coarse fileout
coarse_compaction_filename', 'shape', 'reader urword', 'tagged true', 'optional

```

```
dfn_file_name = 'gwf-csub.dfn'
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfcsub'
package_convergence_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator
object>
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
sgm = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
sgs = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
straincg_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
strainib_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
stress_period_data = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
zdisplacement_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwfdis module

```
class ModflowGwfdis(model, loading_package=False, length_units=None, nogrb=None, xorigin=None,
                    yorigin=None, angrot=None, nlay=1, nrow=2, ncol=2, delr=1.0, delc=1.0, top=1.0,
                    botm=0.0, idomain=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfdis defines a dis package within a gwf6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (*string*) –
  - length\_units (*string*) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (*boolean*) –
  - nogrb (*boolean*) keyword to deactivate writing of the binary grid file.
- **xorigin** (*double*) –
  - xorigin (*double*) x-position of the lower-left corner of the model grid. A default value of zero is assigned if not specified. The value for XORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **yorigin** (*double*) –
  - yorigin (*double*) y-position of the lower-left corner of the model grid. If not specified, then a default value equal to zero is used. The value for YORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.

- **angrot** (*double*) –
  - angrot (*double*) counter-clockwise rotation angle (in degrees) of the lower-left corner of the model grid. If not specified, then a default value of 0.0 is assigned. The value for ANGROT does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **nlay** (*integer*) –
  - nlay (*integer*) is the number of layers in the model grid.
- **nrow** (*integer*) –
  - nrow (*integer*) is the number of rows in the model grid.
- **ncol** (*integer*) –
  - ncol (*integer*) is the number of columns in the model grid.
- **delr** (*[double]*) –
  - delr (*double*) is the column spacing in the row direction.
- **delc** (*[double]*) –
  - delc (*double*) is the row spacing in the column direction.
- **top** (*[double]*) –
  - top (*double*) is the top elevation for each cell in the top model layer.
- **botm** (*[double]*) –
  - botm (*double*) is the bottom elevation for each cell.
- **idomain** (*[integer]*) –
  - idomain (*integer*) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution. If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1 or greater, the cell exists in the simulation. If the IDOMAIN value for a cell is -1, the cell does not exist in the simulation. Furthermore, the first existing cell above will be connected to the first existing cell below. This type of cell is referred to as a “vertical pass through” cell.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

**botm** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

**delc** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

**delr** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```
dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
dimensions', 'name nlay', 'type integer', 'reader urword', 'optional false',
'default_value 1'], ['block dimensions', 'name nrow', 'type integer', 'reader
urword', 'optional false', 'default_value 2'], ['block dimensions', 'name ncol',
'type integer', 'reader urword', 'optional false', 'default_value 2'], ['block
griddata', 'name delr', 'type double precision', 'shape (ncol)', 'reader readarray',
'default_value 1.0'], ['block griddata', 'name delc', 'type double precision',
'shape (nrow)', 'reader readarray', 'default_value 1.0'], ['block griddata', 'name
top', 'type double precision', 'shape (ncol, nrow)', 'reader readarray',
'default_value 1.0'], ['block griddata', 'name botm', 'type double precision',
'shape (ncol, nrow, nlay)', 'reader readarray', 'layered true', 'default_value 0.'],
['block griddata', 'name idomain', 'type integer', 'shape (ncol, nrow, nlay)',
'reader readarray', 'layered true', 'optional true']]

dfn_file_name = 'gwf-dis.dfn'

idomain = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

package_abbr = 'gwfdisu'

top = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

## flopY.mf6.modflow.mfmgwfdisu module

```
class ModflowGwfdisu(model, loading_package=False, length_units=None, nogrb=None, xorigin=None,
    yorigin=None, angrot=None, vertical_offset_tolerance=0.0, nodes=None, nja=None,
    nvert=None, top=None, bot=None, area=None, idomain=None, iac=None, ja=None,
    ihc=None, cl12=None, hwva=None, angldegx=None, vertices=None, cell2d=None,
    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfdisu defines a disu package within a gwf6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (*string*) –
  - length\_units (*string*) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (*boolean*) –
  - nogrb (*boolean*) keyword to deactivate writing of the binary grid file.
- **xorigin** (*double*) –
  - xorigin (*double*) x-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. A default value of zero is assigned if not specified. The value for XORIGIN does not affect the model simulation,



but it is written to the binary grid file so that postprocessors can locate the grid in space.

- **yorigin** (*double*) –
  - yorigin (*double*) y-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. If not specified, then a default value equal to zero is used. The value for YORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **angrot** (*double*) –
  - angrot (*double*) counter-clockwise rotation angle (in degrees) of the model grid coordinate system relative to a real-world coordinate system. If not specified, then a default value of 0.0 is assigned. The value for ANGROT does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **vertical\_offset\_tolerance** (*double*) –
  - vertical\_offset\_tolerance (*double*) checks are performed to ensure that the top of a cell is not higher than the bottom of an overlying cell. This option can be used to specify the tolerance that is used for checking. If top of a cell is above the bottom of an overlying cell by a value less than this tolerance, then the program will not terminate with an error. The default value is zero. This option should generally not be used.
- **nodes** (*integer*) –
  - nodes (*integer*) is the number of cells in the model grid.
- **nja** (*integer*) –
  - nj a (*integer*) is the sum of the number of connections and NODES. When calculating the total number of connections, the connection between cell n and cell m is considered to be different from the connection between cell m and cell n. Thus, NJA is equal to the total number of connections, including n to m and m to n, and the total number of cells.
- **nvert** (*integer*) –
  - nvert (*integer*) is the total number of (x, y) vertex pairs used to define the plan-view shape of each cell in the model grid. If NVERT is not specified or is specified as zero, then the VERTICES and CELL2D blocks below are not read. NVERT and the accompanying VERTICES and CELL2D blocks should be specified for most simulations. If the XT3D or SAVE\_SPECIFIC\_DISCHARGE options are specified in the NPF Package, then this information is required.
- **top** (*[double]*) –
  - top (*double*) is the top elevation for each cell in the model grid.
- **bot** (*[double]*) –
  - bot (*double*) is the bottom elevation for each cell.
- **area** (*[double]*) –
  - area (*double*) is the cell surface area (in plan view).
- **idomain** (*[integer]*) –
  - idomain (*integer*) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution.

If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1 or greater, the cell exists in the simulation. IDOMAIN values of -1 cannot be specified for the DISU Package.

- **iac** ([integer]) –
  - iac (integer) is the number of connections (plus 1) for each cell. The sum of all the entries in IAC must be equal to NJA.
- **ja** ([integer]) –
  - ja (integer) is a list of cell number (n) followed by its connecting cell numbers (m) for each of the m cells connected to cell n. The number of values to provide for cell n is IAC(n). This list is sequentially provided for the first to the last cell. The first value in the list must be cell n itself, and the remaining cells must be listed in an increasing order (sorted from lowest number to highest). Note that the cell and its connections are only supplied for the GWF cells and their connections to the other GWF cells. Also note that the JA list input may be divided such that every node and its connectivity list can be on a separate line for ease in readability of the file. To further ease readability of the file, the node number of the cell whose connectivity is subsequently listed, may be expressed as a negative number, the sign of which is subsequently converted to positive by the code. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **ihc** ([integer]) –
  - ihc (integer) is an index array indicating the direction between node n and all of its m connections. If IHC = 0 then cell n and cell m are connected in the vertical direction. Cell n overlies cell m if the cell number for n is less than m; cell m overlies cell n if the cell number for m is less than n. If IHC = 1 then cell n and cell m are connected in the horizontal direction. If IHC = 2 then cell n and cell m are connected in the horizontal direction, and the connection is vertically staggered. A vertically staggered connection is one in which a cell is horizontally connected to more than one cell in a horizontal connection.
- **cl12** ([double]) –
  - cl12 (double) is the array containing connection lengths between the center of cell n and the shared face with each adjacent m cell.
- **hwva** ([double]) –
  - hwva (double) is a symmetric array of size NJA. For horizontal connections, entries in HWVA are the horizontal width perpendicular to flow. For vertical connections, entries in HWVA are the vertical area for flow. Thus, values in the HWVA array contain dimensions of both length and area. Entries in the HWVA array have a one-to-one correspondence with the connections specified in the JA array. Likewise, there is a one-to-one correspondence between entries in the HWVA array and entries in the IHC array, which specifies the connection type (horizontal or vertical). Entries in the HWVA array must be symmetric; the program will terminate with an error if the value for HWVA for an n to m connection does not equal the value for HWVA for the corresponding n to m connection.
- **angldegx** ([double]) –

- `angldegx` (double) is the angle (in degrees) between the horizontal x-axis and the outward normal to the face between a cell and its connecting cells. The angle varies between zero and 360.0 degrees, where zero degrees points in the positive x-axis direction, and 90 degrees points in the positive y-axis direction. ANGLDEGX is only needed if horizontal anisotropy is specified in the NPF Package, if the XT3D option is used in the NPF Package, or if the SAVE\_SPECIFIC\_DISCHARGE option is specified in the NPF Package. ANGLDEGX does not need to be specified if these conditions are not met. ANGLDEGX is of size NJA; values specified for vertical connections and for the diagonal position are not used. Note that ANGLDEGX is read in degrees, which is different from MODFLOW-USG, which reads a similar variable (ANGLEX) in radians.
- **vertices** (`[iv, xv, yv]`) –
  - `iv` (integer) is the vertex number. Records in the VERTICES block must be listed in consecutive order from 1 to NVERT. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - `xv` (double) is the x-coordinate for the vertex.
  - `yv` (double) is the y-coordinate for the vertex.
- **cell2d** (`[icell2d, xc, yc, nvert, icvert]`) –
  - `icell2d` (integer) is the cell2d number. Records in the CELL2D block must be listed in consecutive order from 1 to NODES. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - `xc` (double) is the x-coordinate for the cell center.
  - `yc` (double) is the y-coordinate for the cell center.
  - `nvert` (integer) is the number of vertices required to define the cell. There may be a different number of vertices for each cell.
  - `icvert` (integer) is an array of integer values containing vertex numbers (in the VERTICES block) used to define the cell. Vertices must be listed in clockwise order. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```

angldegx = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
area = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
bot = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
cell2d = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
cl12 = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```

```
dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
options', 'name vertical_offset_tolerance', 'type double precision', 'reader
urword', 'optional true', 'default_value 0.0'], ['block dimensions', 'name nodes',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name nja',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name
nvert', 'type integer', 'reader urword', 'optional true'], ['block griddata', 'name
top', 'type double precision', 'shape (nodes)', 'reader readarray'], ['block
griddata', 'name bot', 'type double precision', 'shape (nodes)', 'reader
readarray'], ['block griddata', 'name area', 'type double precision', 'shape
(nodes)', 'reader readarray'], ['block griddata', 'name idomain', 'type integer',
'shape (nodes)', 'reader readarray', 'layered false', 'optional true'], ['block
connectiondata', 'name iac', 'type integer', 'shape (nodes)', 'reader readarray'],
['block connectiondata', 'name ja', 'type integer', 'shape (nja)', 'reader
readarray', 'numeric_index true', 'jagged_array iac'], ['block connectiondata',
'name ihc', 'type integer', 'shape (nja)', 'reader readarray', 'jagged_array iac'],
['block connectiondata', 'name cl12', 'type double precision', 'shape (nja)',
'reader readarray', 'jagged_array iac'], ['block connectiondata', 'name hwva', 'type
double precision', 'shape (nja)', 'reader readarray', 'jagged_array iac'], ['block
connectiondata', 'name angldegx', 'type double precision', 'optional true', 'shape
(nja)', 'reader readarray', 'jagged_array iac'], ['block vertices', 'name vertices',
'type recarray iv xv yv', 'reader urword', 'optional false'], ['block vertices',
'name iv', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false', 'numeric_index true'], ['block vertices', 'name xv', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block vertices', 'name yv', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block cell2d', 'name cell2d', 'type
recarray icell2d xc yc nvert icvert', 'reader urword', 'optional false'], ['block
cell2d', 'name icell2d', 'type integer', 'in_record true', 'tagged false', 'reader
urword', 'optional false', 'numeric_index true'], ['block cell2d', 'name xc', 'type
double precision', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block cell2d', 'name yc', 'type double precision', 'in_record true',
'tagged false', 'reader urword', 'optional false'], ['block cell2d', 'name nvert',
'type integer', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block cell2d', 'name icvert', 'type integer', 'shape (nvert)',
'in_record true', 'tagged false', 'reader urword', 'optional false', 'numeric_index
true']]
```

```
dfn_file_name = 'gwf-disu.dfn'
```

```
hwva = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
iac = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
idomain = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
ihc = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
ja = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
package_abbr = 'gwfdisu'
```

```
top = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

`vertices = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>`

## flopY.mf6.modflow.mfgwfdisc module

```
class ModflowGwfdisc(model, loading_package=False, length_units=None, nogrb=None, xorigin=None,
                      yorigin=None, angrot=None, nlay=None, ncpl=None, nvert=None, top=None,
                      botm=None, idomain=None, vertices=None, cell2d=None, filename=None,
                      pname=None, parent_file=None)
```

Bases: `flopY.mf6.mfpackage.MFPackage`

ModflowGwfdisc defines a disc package within a gwf6 model.

### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (`string`) –
  - `length_units` (`string`) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (`boolean`) –
  - `nogrb` (`boolean`) keyword to deactivate writing of the binary grid file.
- **xorigin** (`double`) –
  - `xorigin` (`double`) x-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. A default value of zero is assigned if not specified. The value for XORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **yorigin** (`double`) –
  - `yorigin` (`double`) y-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. If not specified, then a default value equal to zero is used. The value for YORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **angrot** (`double`) –
  - `angrot` (`double`) counter-clockwise rotation angle (in degrees) of the model grid coordinate system relative to a real-world coordinate system. If not specified, then a default value of 0.0 is assigned. The value for ANGROT does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **nlay** (`integer`) –
  - `nlay` (`integer`) is the number of layers in the model grid.
- **ncpl** (`integer`) –
  - `ncpl` (`integer`) is the number of cells per layer. This is a constant value for the grid and it applies to all layers.

- **nvert** (*integer*) –
  - nvert (*integer*) is the total number of (x, y) vertex pairs used to characterize the horizontal configuration of the model grid.
- **top** (*[double]*) –
  - top (*double*) is the top elevation for each cell in the top model layer.
- **botm** (*[double]*) –
  - botm (*double*) is the bottom elevation for each cell.
- **idomain** (*[integer]*) –
  - idomain (*integer*) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution. If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1 or greater, the cell exists in the simulation. If the IDOMAIN value for a cell is -1, the cell does not exist in the simulation. Furthermore, the first existing cell above will be connected to the first existing cell below. This type of cell is referred to as a “vertical pass through” cell.
- **vertices** (*[iv, xv, yv]*) –
  - iv (*integer*) is the vertex number. Records in the VERTICES block must be listed in consecutive order from 1 to NVERT. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - xv (*double*) is the x-coordinate for the vertex.
  - yv (*double*) is the y-coordinate for the vertex.
- **cell2d** (*[icell2d, xc, yc, nvert, icvert]*) –
  - icell2d (*integer*) is the CELL2D number. Records in the CELL2D block must be listed in consecutive order from the first to the last. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - xc (*double*) is the x-coordinate for the cell center.
  - yc (*double*) is the y-coordinate for the cell center.
  - nvert (*integer*) is the number of vertices required to define the cell. There may be a different number of vertices for each cell.
  - icvert (*integer*) is an array of integer values containing vertex numbers (in the VERTICES block) used to define the cell. Vertices must be listed in clockwise order. Cells that are connected must share vertices. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.

- `parent_file` (`MFPackage`) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```

botm = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
cell2d = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
dimensions', 'name nlay', 'type integer', 'reader urword', 'optional false'],
['block dimensions', 'name ncpl', 'type integer', 'reader urword', 'optional
false'], ['block dimensions', 'name nvert', 'type integer', 'reader urword',
'optional false'], ['block griddata', 'name top', 'type double precision', 'shape
(ncpl)', 'reader readarray'], ['block griddata', 'name botm', 'type double
precision', 'shape (nlay, ncpl)', 'reader readarray', 'layered true'], ['block
griddata', 'name idomain', 'type integer', 'shape (nlay, ncpl)', 'reader readarray',
'layered true', 'optional true'], ['block vertices', 'name vertices', 'type recarray
iv xv yv', 'reader urword', 'optional false'], ['block vertices', 'name iv', 'type
integer', 'in_record true', 'tagged false', 'reader urword', 'optional false',
'numeric_index true'], ['block vertices', 'name xv', 'type double precision',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
vertices', 'name yv', 'type double precision', 'in_record true', 'tagged false',
'reader urword', 'optional false'], ['block cell2d', 'name cell2d', 'type recarray
icell2d xc yc nvert icvert', 'reader urword', 'optional false'], ['block cell2d',
'name icell2d', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false', 'numeric_index true'], ['block cell2d', 'name xc', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block cell2d', 'name yc', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block cell2d', 'name nvert', 'type
integer', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block cell2d', 'name icvert', 'type integer', 'shape (nvert)', 'in_record true',
'tagged false', 'reader urword', 'optional false', 'numeric_index true']]

dfn_file_name = 'gwf-disv.dfn'

idomain = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
package_abbr = 'gwfdisv'

top = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
vertices = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```

**flop.mf6.modflow.mfgwfdn module**

```
class ModflowGwfdn(model, loading_package=False, auxiliary=None, auxmultname=None,
                    auxdepthname=None, boundnames=None, print_input=None, print_flows=None,
                    save_flows=None, timeseries=None, observations=None, mover=None, maxbound=None,
                    stress_period_data=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfdn defines a drn package within a gw6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of drain conductance.
- **auxdepthname** (*string*) –
  - auxdepthname (string) name of a variable listed in AUXILIARY that defines the depth at which drainage discharge will be scaled. If a positive value is specified for the AUXDEPTHNAME AUXILIARY variable, then ELEV is the elevation at which the drain starts to discharge and ELEV + DDRN (assuming DDRN is the AUXDEPTHNAME variable) is the elevation when the drain conductance (COND) scaling factor is 1. If a negative drainage depth value is specified for DDRN, then ELEV + DDRN is the elevation at which the drain starts to discharge and ELEV is the elevation when the conductance (COND) scaling factor is 1. A linear- or cubic-scaling is used to scale the drain conductance (COND) when the Standard or Newton-Raphson Formulation is used, respectively.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of drain cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of drain information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of drain flow rates will be printed to the listing file for every stress period time step in which “BUDGET



PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.

- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that drain flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (boolean) keyword to indicate that this instance of the Drain Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of drains cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, elev, cond, aux, boundname]*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - elev (double) is the elevation of the drain. If the Options block includes a TIME-SERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - cond (double) is the hydraulic conductance of the interface between the aquifer and the drain. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (double) represents the values of the auxiliary variables for each drain. The values of auxiliary variables must be present for each drain. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- `boundname` (string) name of the drain cell. `BOUNDNAME` is an ASCII character variable that can contain as many as 40 characters. If `BOUNDNAME` contains spaces in it, then the entire name must be enclosed within single quotes.
- `filename` (String) – File name for this package.
- `pname` (String) – Package name for this package.
- `parent_file` (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutlaktab package must have a mfg-wflak package `parent_file`.

```
auxiliary = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type  
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name  
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block  
options', 'name auxdepthname', 'type string', 'shape', 'reader urword', 'optional  
true'], ['block options', 'name boundnames', 'type keyword', 'shape', 'reader  
urword', 'optional true'], ['block options', 'name print_input', 'type keyword',  
'reader urword', 'optional true'], ['block options', 'name print_flows', 'type  
keyword', 'reader urword', 'optional true'], ['block options', 'name save_flows',  
'type keyword', 'reader urword', 'optional true'], ['block options', 'name  
ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader urword',  
'tagged true', 'optional true', 'construct_package ts', 'construct_data timeseries',  
'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape',  
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block  
options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword',  
'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type  
string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false',  
'tagged false'], ['block options', 'name obs_filerecord', 'type record obs6 filein  
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',  
'construct_package obs', 'construct_data continuous', 'parameter_name  
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record  
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name  
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged  
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type  
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',  
'name maxbound', 'type integer', 'reader urword', 'optional false'], ['block  
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',  
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block  
period', 'name stress_period_data', 'type recarray cellid elev cond aux boundname',  
'shape (maxbound)', 'reader urword'], ['block period', 'name cellid', 'type  
integer', 'shape (ncelldim)', 'tagged false', 'in_record true', 'reader urword'],  
['block period', 'name elev', 'type double precision', 'shape', 'tagged false',  
'in_record true', 'reader urword', 'time_series true'], ['block period', 'name  
cond', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader  
urword', 'time_series true'], ['block period', 'name aux', 'type double precision',  
'in_record true', 'tagged false', 'shape (naux)', 'reader urword', 'optional true',  
'time_series true'], ['block period', 'name boundname', 'type string', 'shape',  
'tagged false', 'in_record true', 'reader urword', 'optional true']]
```

```
dfn_file_name = 'gwf-drn.dfn'
```

```
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'gwfdn'
```

```
stress_period_data = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwfevt module

```
class ModflowGwfevt(model, loading_package=False, fixed_cell=None, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, surf_rate_specified=None, maxbound=None,
                    nseg=None, stress_period_data=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfevt defines a evt package within a gw6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **fixed\_cell** (*boolean*) –
  - fixed\_cell (*boolean*) indicates that evapotranspiration will not be reassigned to a cell underlying the cell specified in the list if the specified cell is inactive.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of evapotranspiration rate.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of evapotranspiration cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of evapotranspiration information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of evapotranspiration flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.

- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that evapotranspiration flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **surf\_rate\_specified** (*boolean*) –
  - surf\_rate\_specified (boolean) indicates that the proportion of the evapotranspiration rate at the ET surface will be specified as PETM0 in list input.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of evapotranspiration cells that will be specified for use during any stress period.
- **nseg** (*integer*) –
  - nseg (integer) number of ET segments. Default is one. When NSEG is greater than 1, PXDP and PETM arrays must be specified NSEG - 1 times each, in order from the uppermost segment down. PXDP defines the extinction-depth proportion at the bottom of a segment. PETM defines the proportion of the maximum ET flux rate at the bottom of a segment.
- **stress\_period\_data** (*([cellid, surface, rate, depth, pxdp, petm, petm0, aux,] – boundname)*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - surface (double) is the elevation of the ET surface ( $L$ ). If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - rate (double) is the maximum ET flux rate ( $LT^{-1}$ ). If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- `depth` (double) is the ET extinction depth ( $L$ ). If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `pxdp` (double) is the proportion of the ET extinction depth at the bottom of a segment (dimensionless). If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `petm` (double) is the proportion of the maximum ET flux rate at the bottom of a segment (dimensionless). If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `petm0` (double) is the proportion of the maximum ET flux rate that will apply when head is at or above the ET surface (dimensionless). `PETM0` is read only when the `SURF_RATE_SPECIFIED` option is used. If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `aux` (double) represents the values of the auxiliary variables for each evapotranspiration. The values of auxiliary variables must be present for each evapotranspiration. The values must be specified in the order of the auxiliary variables specified in the `OPTIONS` block. If the package supports time series and the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `boundname` (string) name of the evapotranspiration cell. `BOUNDNAME` is an ASCII character variable that can contain as many as 40 characters. If `BOUNDNAME` contains spaces in it, then the entire name must be enclosed within single quotes.
- **`filename`** (*String*) – File name for this package.
  - **`pname`** (*String*) – Package name for this package.
  - **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

**`auxiliary`** = `<flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

```
dfn = [['header', 'multi-package'], ['block options', 'name fixed_cell', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name auxmultname', 'type string', 'shape', 'reader urword',
'optional true'], ['block options', 'name boundnames', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name print_input', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name print_flows',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
save_flows', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader
urword', 'tagged true', 'optional true', 'construct_package ts', 'construct_data
timeseries', 'parameter_name timeseries'], ['block options', 'name ts6', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
ts6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader
urword', 'optional false', 'tagged false'], ['block options', 'name obs_filerecord',
'type record obs6 filein obs6_filename', 'shape', 'reader urword', 'tagged true',
'optional true', 'construct_package obs', 'construct_data continuous',
'parameter_name observations'], ['block options', 'name obs6', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name obs6_filename', 'type string', 'preserve_case true',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
options', 'name surf_rate_specified', 'type keyword', 'reader urword', 'optional
true'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword',
'optional false'], ['block dimensions', 'name nseg', 'type integer', 'reader
urword', 'optional false'], ['block period', 'name iper', 'type integer',
'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader
urword', 'optional false'], ['block period', 'name stress_period_data', 'type
recarray cellid surface rate depth pxdp petm petm0 aux boundname', 'shape
(maxbound)', 'reader urword'], ['block period', 'name cellid', 'type integer',
'shape (ncellid)', 'tagged false', 'in_record true', 'reader urword'], ['block
period', 'name surface', 'type double precision', 'shape', 'tagged false',
'in_record true', 'reader urword', 'time_series true'], ['block period', 'name
rate', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword', 'time_series true'], ['block period', 'name depth', 'type double
precision', 'shape', 'tagged false', 'in_record true', 'reader urword', 'time_series
true'], ['block period', 'name pxdp', 'type double precision', 'shape (nseg-1)',
'tagged false', 'in_record true', 'reader urword', 'time_series true'], ['block
period', 'name petm', 'type double precision', 'shape (nseg-1)', 'tagged false',
'in_record true', 'reader urword', 'time_series true'], ['block period', 'name
petm0', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword', 'optional true', 'time_series true'], ['block period', 'name aux', 'type
double precision', 'in_record true', 'tagged false', 'shape (naux)', 'reader
urword', 'optional true', 'time_series true'], ['block period', 'name boundname',
'type string', 'shape', 'tagged false', 'in_record true', 'reader urword', 'optional
true']]

dfn_file_name = 'gwf-evt.dfn'

obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwfEvt'

stress_period_data = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

`ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

## flop.mf6.modflow.mfgwfevta module

```
class ModflowGwfevta(model, loading_package=False, readasarrays=True, fixed_cell=None, auxiliary=None,
                      auxmultname=None, print_input=None, print_flows=None, save_flows=None,
                      timearrayseries=None, observations=None, ievt=None, surface=0.0, rate=0.001,
                      depth=1.0, aux=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfevta defines a evta package within a gw6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **readasarrays** (*boolean*) –
  - readasarrays (*boolean*) indicates that array-based input will be used for the Evapotranspiration Package. This keyword must be specified to use array-based input.
- **fixed\_cell** (*boolean*) –
  - fixed\_cell (*boolean*) indicates that evapotranspiration will not be reassigned to a cell underlying the cell specified in the list if the specified cell is inactive.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of evapotranspiration rate.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of evapotranspiration information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of evapotranspiration flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –

- `save_flows` (boolean) keyword to indicate that evapotranspiration flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timearrayseries** (*{varname:data} or tas\_array data*) –
  - Contains data for the tas package. Data can be stored in a dictionary containing data for the tas package with variable names as keys and package data as values. Data just for the timearrayseries variable is also acceptable. See tas package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **ievt** (*[integer]*) –
  - `ievt` (integer) IEVT is the layer number that defines the layer in each vertical column where evapotranspiration is applied. If IEVT is omitted, evapotranspiration by default is applied to cells in layer 1. If IEVT is specified, it must be specified as the first variable in the PERIOD block or MODFLOW will terminate with an error. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
- **surface** (*[double]*) –
  - `surface` (double) is the elevation of the ET surface ( $L$ ).
- **rate** (*[double]*) –
  - `rate` (double) is the maximum ET flux rate ( $LT^{-1}$ ).
- **depth** (*[double]*) –
  - `depth` (double) is the ET extinction depth ( $L$ ).
- **aux(iaux)** (*[double]*) –
  - `aux(iaux)` (double) is an array of values for auxiliary variable AUX(IAUX), where `iaux` is a value from 1 to NAUX, and AUX(IAUX) must be listed as part of the auxiliary variables. A separate array can be specified for each auxiliary variable. If an array is not specified for an auxiliary variable, then a value of zero is assigned. If the value specified here for the auxiliary variable is the same as `auxmultname`, then the evapotranspiration rate will be multiplied by this array.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (`mfutl*`). For example, `mfutllaktab` package must have a `mfg-wflak` package `parent_file`.

```
aux = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
auxiliary = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
depth = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```



```

dfn = [['header', 'multi-package'], ['block options', 'name readasarrays', 'type
keyword', 'shape', 'reader urword', 'optional false', 'default_value True'], ['block
options', 'name fixed_cell', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name auxiliary', 'type string', 'shape (naux)', 'reader
urword', 'optional true'], ['block options', 'name auxmultname', 'type string',
'shape', 'reader urword', 'optional true'], ['block options', 'name print_input',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
print_flows', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name save_flows', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name tas_filerecord', 'type record tas6 filein tas6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package tas',
'construct_data tas_array', 'parameter_name timearrayseries'], ['block options',
'name tas6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name filein', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name tas6_filename', 'type string', 'preserve_case true', 'in_record
true', 'reader urword', 'optional false', 'tagged false'], ['block options', 'name
obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader urword',
'tagged true', 'optional true', 'construct_package obs', 'construct_data
continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name obs6_filename', 'type string', 'preserve_case
true', 'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name ievt', 'type integer', 'shape (ncol*nrow; ncpl)', 'reader readarray',
'numeric_index true', 'optional true'], ['block period', 'name surface', 'type
double precision', 'shape (ncol*nrow; ncpl)', 'reader readarray', 'default_value
0.'], ['block period', 'name rate', 'type double precision', 'shape (ncol*nrow;
ncpl)', 'reader readarray', 'default_value 1.e-3'], ['block period', 'name depth',
'type double precision', 'shape (ncol*nrow; ncpl)', 'reader readarray',
'default_value 1.0'], ['block period', 'name aux(iaux)', 'type double precision',
'shape (ncol*nrow; ncpl)', 'reader readarray']]

dfn_file_name = 'gwf-evta.dfn'

ievt = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwf evta'
rate = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
surface = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
tas_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

```

**flop.mf6.modflow.mfgwfghb module**

```
class ModflowGwfghb(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, mover=None, maxbound=None,
                    stress_period_data=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfghb defines a ghb package within a gwf6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of general-head boundary conductance.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of general-head boundary cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of general-head boundary information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of general-head boundary flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that general-head boundary flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just

for the timeseries variable is also acceptable. See ts package documentation for more information.

- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (boolean) keyword to indicate that this instance of the General-Head Boundary Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of general-head boundary cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, bhead, cond, aux, boundname]*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - bhead (double) is the boundary head. If the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - cond (double) is the hydraulic conductance of the interface between the aquifer cell and the boundary. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (double) represents the values of the auxiliary variables for each general-head boundary. The values of auxiliary variables must be present for each general-head boundary. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the general-head boundary cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only

needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```
auxiliary = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block
options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name print_input', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name save_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type
record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional
true', 'construct_package ts', 'construct_data timeseries', 'parameter_name
timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name ts6_filename', 'type string',
'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged
false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name maxbound', 'type integer', 'reader urword', 'optional false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name stress_period_data', 'type recarray cellid bhead cond aux boundname',
'shape (maxbound)', 'reader urword'], ['block period', 'name cellid', 'type
integer', 'shape (ncelldim)', 'tagged false', 'in_record true', 'reader urword'],
['block period', 'name bhead', 'type double precision', 'shape', 'tagged false',
'in_record true', 'reader urword', 'time_series true'], ['block period', 'name
cond', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword', 'time_series true'], ['block period', 'name aux', 'type double precision',
'in_record true', 'tagged false', 'shape (naux)', 'reader urword', 'optional true',
'time_series true'], ['block period', 'name boundname', 'type string', 'shape',
'tagged false', 'in_record true', 'reader urword', 'optional true']]

dfn_file_name = 'gwf-ghb.dfn'

obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwfghb'

stress_period_data = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flopY.mf6.modflow.mfgwfgnc module

```
class ModflowGwfgnc(model, loading_package=False, print_input=None, print_flows=None, explicit=None,
                    numgnc=None, numalphaj=None, gncdata=None, filename=None, pname=None,
                    parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfgnc defines a gnc package within a gwf6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of GNC information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of GNC flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **explicit** (*boolean*) –
  - explicit (*boolean*) keyword to indicate that the ghost node correction is applied in an explicit manner on the right-hand side of the matrix. The explicit approach will likely require additional outer iterations. If the keyword is not specified, then the correction will be applied in an implicit manner on the left-hand side. The implicit approach will likely converge better, but may require additional memory. If the EXPLICIT keyword is not specified, then the BICGSTAB linear acceleration option should be specified within the LINEAR block of the Sparse Matrix Solver.
- **numgnc** (*integer*) –
  - numgnc (*integer*) is the number of GNC entries.
- **numalphaj** (*integer*) –
  - numalphaj (*integer*) is the number of contributing factors.
- **gncdata** (*[cellidn, cellidm, cellidsj, alphasj]*) –
  - cellidn (*((integer, ...))*) is the cellid of the cell, *n*, in which the ghost node is located. For a structured grid that uses the DIS input file, CELLIDN is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDN is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDN is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - cellidm (*((integer, ...))*) is the cellid of the connecting cell, *m*, to which flow occurs from the ghost node. For a structured grid that uses the DIS input file, CELLIDM is the layer, row, and column numbers of the cell. For a grid that uses the DISV input

file, CELLIDM is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- `cellidsj` ((integer, ...)) is the array of CELLIDS for the contributing `j` cells, which contribute to the interpolated head value at the ghost node. This item contains one CELLID for each of the contributing cells of the ghost node. Note that if the number of actual contributing cells needed by the user is less than NUMALPHAJ for any ghost node, then a dummy CELLID of zero(s) should be inserted with an associated contributing factor of zero. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLID is the layer number and cell2d number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `alphasj` (double) is the contributing factors for each contributing node in CELLIDSJ. Note that if the number of actual contributing cells is less than NUMALPHAJ for any ghost node, then dummy CELLIDS should be inserted with an associated contributing factor of zero. The sum of ALPHASJ should be less than one. This is because one minus the sum of ALPHASJ is equal to the alpha term (alpha  $n$  in equation 4-61 of the GWF Model report) that is multiplied by the head in cell  $n$ .
- `filename` (*String*) – File name for this package.
  - `pname` (*String*) – Package name for this package.
  - `parent_file` (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name explicit', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name numgnc', 'type integer', 'reader urword', 'optional false'], ['block
dimensions', 'name numalphaj', 'type integer', 'reader urword', 'optional false'],
['block gncdata', 'name gncdata', 'type recarray cellidn cellidm cellidsj alphasj',
'shape (maxbound)', 'reader urword'], ['block gncdata', 'name cellidn', 'type
integer', 'shape', 'tagged false', 'in_record true', 'reader urword', 'numeric_index
true'], ['block gncdata', 'name cellidm', 'type integer', 'shape', 'tagged false',
'in_record true', 'reader urword', 'numeric_index true'], ['block gncdata', 'name
cellidsj', 'type integer', 'shape (numalphaj)', 'tagged false', 'in_record true',
'reader urword', 'numeric_index true'], ['block gncdata', 'name alphasj', 'type
double precision', 'shape (numalphaj)', 'tagged false', 'in_record true', 'reader
urword']]
```

```
dfn_file_name = 'gwf-gnc.dfn'
```

```
gncdata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'gwfgnc'
```

## flop.mf6.modflow.mfgwfgwf module

```
class ModflowGwfgwf(simulation, loading_package=False, exgtype=None, exgmnamea=None,
                    exgmnameb=None, auxiliary=None, boundnames=None, print_input=None,
                    print_flows=None, save_flows=None, cell_averaging=None, cvoptions=None,
                    newton=None, xt3d=None, gnc_filerecord=None, mvr_filerecord=None,
                    observations=None, dev_interfacemodel_on=None, nexg=None, exchangedata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfgwf defines a gwfgwf package.

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **exgtype** (*<string>*) –
  - is the exchange type (GWF-GWF or GWF-GWT).
- **exgmnamea** (*<string>*) –
  - is the name of the first model that is part of this exchange.
- **exgmnameb** (*<string>*) –
  - is the name of the second model that is part of this exchange.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) an array of auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided. Most auxiliary variables will not be used by the GWF-GWF Exchange, but they will be available for use by other parts of the program. If an auxiliary variable with the name “ANGLDEGX” is found, then this information will be used as the angle (provided in degrees) between the connection face normal and the x axis, where a value of zero indicates that a normal vector points directly along the positive x axis. The connection face normal is a normal vector on the cell face shared between the cell in model 1 and the cell in model 2 pointing away from the model 1 cell. Additional information on “ANGLDEGX” is provided in the description of the DISU Package. If an auxiliary variable with the name “CDIST” is found, then this information will be used as the straight-line connection distance, including the vertical component, between the two cell centers. Both ANGLDEGX and CDIST are required if specific discharge is calculated for either of the groundwater models.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of GWF Exchange cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of exchange entries will be echoed to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –

- `print_flows` (boolean) keyword to indicate that the list of exchange flow rates will be printed to the listing file for every stress period in which “SAVE BUDGET” is specified in Output Control.
- **save\_flows** (*boolean*) –
  - `save_flows` (boolean) keyword to indicate that cell-by-cell flow terms will be written to the budget file for each model provided that the Output Control for the models are set up with the “BUDGET SAVE FILE” option.
- **cell\_averaging** (*string*) –
  - `cell_averaging` (string) is a keyword and text keyword to indicate the method that will be used for calculating the conductance for horizontal cell connections. The text value for CELL\_AVERAGING can be “HARMONIC”, “LOGARITHMIC”, or “AMT-LMK”, which means “arithmetic-mean thickness and logarithmic-mean hydraulic conductivity”. If the user does not specify a value for CELL\_AVERAGING, then the harmonic-mean method will be used.
- **cvoptions** (*[dewatered]*) –
  - `dewatered` (string) If the DEWATERED keyword is specified, then the vertical conductance is calculated using only the saturated thickness and properties of the overlying cell if the head in the underlying cell is below its top.
- **newton** (*boolean*) –
  - `newton` (boolean) keyword that activates the Newton-Raphson formulation for groundwater flow between connected, convertible groundwater cells. Cells will not dry when this option is used.
- **xt3d** (*boolean*) –
  - `xt3d` (boolean) keyword that activates the XT3D formulation between the cells connected with this GWF-GWF Exchange.
- **gnc\_filerecord** (*[gnc6\_filename]*) –
  - `gnc6_filename` (string) is the file name for ghost node correction input file. Information for the ghost nodes are provided in the file provided with these keywords. The format for specifying the ghost nodes is the same as described for the GNC Package of the GWF Model. This includes specifying OPTIONS, DIMENSIONS, and GNC-DATA blocks. The order of the ghost nodes must follow the same order as the order of the cells in the EXCHANGEDATA block. For the GNCDATA, `noden` and all of the `nodej` values are assumed to be located in model 1, and `nodem` is assumed to be in model 2.
- **mvr\_filerecord** (*[mvr6\_filename]*) –
  - `mvr6_filename` (string) is the file name of the water mover input file to apply to this exchange. Information for the water mover are provided in the file provided with these keywords. The format for specifying the water mover information is the same as described for the Water Mover (MVR) Package of the GWF Model, with two exceptions. First, in the PACKAGES block, the model name must be included as a separate string before each package. Second, the appropriate model name must be included before package name 1 and package name 2 in the BEGIN PERIOD block. This allows providers and receivers to be located in both models listed as part of this exchange.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just



for the observations variable is also acceptable. See obs package documentation for more information.

- **dev\_interfacemodel\_on** (*boolean*) –
  - dev\_interfacemodel\_on (*boolean*) activates the interface model mechanism for calculating the coefficients at (and possibly near) the exchange. This keyword should only be used for development purposes.
- **nextg** (*integer*) –
  - nextg (*integer*) keyword and integer value specifying the number of GWF-GWF exchanges.
- **exchangedata** (*[cellidm1, cellidm2, ihc, cl1, cl2, hwva, aux, boundname]*) –
  - cellidm1 (*(integer, ...)*) is the cellid of the cell in model 1 as specified in the simulation name file. For a structured grid that uses the DIS input file, CELLIDM1 is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDM1 is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM1 is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - cellidm2 (*(integer, ...)*) is the cellid of the cell in model 2 as specified in the simulation name file. For a structured grid that uses the DIS input file, CELLIDM2 is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDM2 is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM2 is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - ihc (*integer*) is an integer flag indicating the direction between node n and all of its m connections. If IHC = 0 then the connection is vertical. If IHC = 1 then the connection is horizontal. If IHC = 2 then the connection is horizontal for a vertically staggered grid.
  - cl1 (*double*) is the distance between the center of cell 1 and the its shared face with cell 2.
  - cl2 (*double*) is the distance between the center of cell 2 and the its shared face with cell 1.
  - hwva (*double*) is the horizontal width of the flow connection between cell 1 and cell 2 if IHC > 0, or it is the area perpendicular to flow of the vertical connection between cell 1 and cell 2 if IHC = 0.
  - aux (*double*) represents the values of the auxiliary variables for each GWFGWF Exchange. The values of auxiliary variables must be present for each exchange. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block.
  - boundname (*string*) name of the GWF Exchange cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.

- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

**auxiliary** = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name cell_averaging', 'type string', 'valid
harmonic logarithmic amt-lmk', 'reader urword', 'optional true'], ['block options',
'name cvoptions', 'type record variablecv dewatered', 'reader urword', 'optional
true'], ['block options', 'name variablecv', 'in_record true', 'type keyword',
'reader urword'], ['block options', 'name dewatered', 'in_record true', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name newton', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name xt3d', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
gnc_filerecord', 'type record gnc6 filein gnc6_filename', 'shape', 'reader urword',
'tagged true', 'optional true'], ['block options', 'name filein', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name gnc6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name gnc6_filename',
'type string', 'preserve_case true', 'in_record true', 'tagged false', 'reader
urword', 'optional false'], ['block options', 'name mvr_filerecord', 'type record
mvr6 filein mvr6_filename', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name mvr6', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
mvr6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name obs_filerecord',
'type record obs6 filein obs6_filename', 'shape', 'reader urword', 'tagged true',
'optional true', 'construct_package obs', 'construct_data continuous',
'parameter_name observations'], ['block options', 'name obs6', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name obs6_filename', 'type string', 'preserve_case true',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
options', 'name dev_interfacemodel_on', 'type keyword', 'reader urword', 'optional
true'], ['block dimensions', 'name nexg', 'type integer', 'reader urword', 'optional
false'], ['block exchangedata', 'name exchangedata', 'type recarray cellidm1
cellidm2 ihc cl1 cl2 hwva aux boundname', 'reader urword', 'optional false'],
['block exchangedata', 'name cellidm1', 'type integer', 'in_record true', 'tagged
false', 'reader urword', 'optional false', 'numeric_index true'], ['block
exchangedata', 'name cellidm2', 'type integer', 'in_record true', 'tagged false',
'reader urword', 'optional false', 'numeric_index true'], ['block exchangedata',
'name ihc', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false'], ['block exchangedata', 'name cl1', 'type double precision',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
exchangedata', 'name cl2', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block exchangedata', 'name hwva',
'type double precision', 'in_record true', 'tagged false', 'reader urword',
'optional false'], ['block exchangedata', 'name aux', 'type double precision',
'in_record true', 'tagged false', 'shape (naux)', 'reader urword', 'optional true'],
['block exchangedata', 'name boundname', 'type string', 'shape', 'tagged false',
'in_record true', 'reader urword', 'optional true']]

```

```
dfn_file_name = 'exg-gwfgwf.dfn'
```

```
exchangedata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
gnc_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
mvr_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfgwf'
```

### flopY.mf6.modflow.mfgwfgwt module

```
class ModflowGwfgwt(simulation, loading_package=False, exgtype=None, exgmnamea=None,
                    exgmnameb=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfgwt defines a gwfgwt package.

#### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **exgtype** (*<string>*) –
  - is the exchange type (GWF-GWF or GWF-GWT).
- **exgmnamea** (*<string>*) –
  - is the name of the first model that is part of this exchange.
- **exgmnameb** (*<string>*) –
  - is the name of the second model that is part of this exchange.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header']]
dfn_file_name = 'exg-gwfgwt.dfn'
package_abbr = 'gwfgwt'
```

### flopY.mf6.modflow.mfgwfxfb module

```
class ModflowGwfxfb(model, loading_package=False, print_input=None, maxhfb=None,
                    stress_period_data=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfxfb defines a hfb package within a gw6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.

- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*boolean*) –
  - `print_input` (*boolean*) keyword to indicate that the list of horizontal flow barriers will be written to the listing file immediately after it is read.
- **maxhfb** (*integer*) –
  - `maxhfb` (*integer*) integer value specifying the maximum number of horizontal flow barriers that will be entered in this input file. The value of MAXHFB is used to allocate memory for the horizontal flow barriers.
- **stress\_period\_data** (*[cellid1, cellid2, hydchr]*) –
  - `cellid1` ((*integer, ...*)) identifier for the first cell. For a structured grid that uses the DIS input file, CELLID1 is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLID1 is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLID1 is the node numbers for the cell. The barrier is located between cells designated as CELLID1 and CELLID2. For models that use the DIS and DISV grid types, the layer number for CELLID1 and CELLID2 must be the same. For all grid types, cells must be horizontally adjacent or the program will terminate with an error. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `cellid2` ((*integer, ...*)) identifier for the second cell. See CELLID1 for description of how to specify. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `hydchr` (*double*) is the hydraulic characteristic of the horizontal- flow barrier. The hydraulic characteristic is the barrier hydraulic conductivity divided by the width of the horizontal-flow barrier. If the hydraulic characteristic is negative, then the absolute value of HYDCHR acts as a multiplier to the conductance between the two model cells specified as containing the barrier. For example, if the value for HYDCHR was specified as -1.5, the conductance calculated for the two cells would be multiplied by 1.5.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block dimensions', 'name maxhfb', 'type integer',
'reader urword', 'optional false'], ['block period', 'name iper', 'type integer',
'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader
urword', 'optional false'], ['block period', 'name stress_period_data', 'type
recarray cellid1 cellid2 hydchr', 'shape (maxhfb)', 'reader urword'], ['block
period', 'name cellid1', 'type integer', 'shape (ncelldim)', 'tagged false',
'in_record true', 'reader urword'], ['block period', 'name cellid2', 'type integer',
'shape (ncelldim)', 'tagged false', 'in_record true', 'reader urword'], ['block
period', 'name hydchr', 'type double precision', 'shape', 'tagged false', 'in_record
true', 'reader urword']]
```

```
dfn_file_name = 'gwf-hfb.dfn'
package_abbr = 'gwf_hfb'
stress_period_data = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwfic module

**class** **ModflowGwfic**(*model*, *loading\_package=False*, *strt=1.0*, *filename=None*, *pname=None*, *parent\_file=None*)  
Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfic defines a ic package within a gwf6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **strt** (*[double]*) –
  - **strt** (*double*) is the initial (starting) head—that is, head at the beginning of the GWF Model simulation. STRT must be specified for all simulations, including steady-state simulations. One value is read for every model cell. For simulations in which the first stress period is steady state, the values used for STRT generally do not affect the simulation (exceptions may occur if cells go dry and (or) rewet). The execution time, however, will be less if STRT includes hydraulic heads that are close to the steady-state solution. A head value lower than the cell bottom can be provided if a cell should start as dry.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

```
dfn = [['header'], ['block griddata', 'name strt', 'type double precision', 'shape (nodes)', 'reader readarray', 'layered true', 'default_value 1.0']]
dfn_file_name = 'gwf-ic.dfn'
package_abbr = 'gwfic'
strt = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwflak module

**class** **ModflowGwflak**(*model*, *loading\_package=False*, *auxiliary=None*, *boundnames=None*, *print\_input=None*, *print\_stage=None*, *print\_flows=None*, *save\_flows=None*, *stage\_filerecord=None*, *budget\_filerecord=None*, *budgetcsv\_filerecord=None*, *package\_convergence\_filerecord=None*, *timeseries=None*, *observations=None*, *mover=None*, *surfdep=None*, *time\_conversion=None*, *length\_conversion=None*, *nlakes=None*, *noutlets=None*, *ntables=None*, *packagedata=None*, *connectiondata=None*, *tables=None*, *outlets=None*, *perioddata=None*, *filename=None*, *pname=None*, *parent\_file=None*)  
Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwflak defines a lak package within a gwfl6 model.

### Parameters

- **model** (*MFModel*) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of lake cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of lake information will be written to the listing file immediately after it is read.
- **print\_stage** (*boolean*) –
  - print\_stage (boolean) keyword to indicate that the list of lake stages will be printed to the listing file for every stress period in which “HEAD PRINT” is specified in Output Control. If there is no Output Control option and PRINT\_STAGE is specified, then stages are printed for the last time step of each stress period.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of lake flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that lake flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **stage\_filerecord** (*[stagefile]*) –
  - stagefile (string) name of the binary output file to write stage information.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (string) name of the binary output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.

- **package\_convergence\_filerecord** (*[package\_convergence\_filename]*) –
  - package\_convergence\_filename (string) name of the comma spaced values output file to write package convergence information.
- **timeseries** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data}* or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (boolean) keyword to indicate that this instance of the LAK Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **surfdep** (*double*) –
  - surfdep (double) real value that defines the surface depression depth for VERTICAL lake-GWF connections. If specified, SURFDEP must be greater than or equal to zero. If SURFDEP is not specified, a default value of zero is used for all vertical lake-GWF connections.
- **time\_conversion** (*double*) –
  - time\_conversion (double) value that is used in converting outlet flow terms that use Manning's equation or gravitational acceleration to consistent time units. TIME\_CONVERSION should be set to 1.0, 60.0, 3,600.0, 86,400.0, and 31,557,600.0 when using time units (TIME\_UNITS) of seconds, minutes, hours, days, or years in the simulation, respectively. CONVTIME does not need to be specified if no lake outlets are specified or TIME\_UNITS are seconds.
- **length\_conversion** (*double*) –
  - length\_conversion (double) real value that is used in converting outlet flow terms that use Manning's equation or gravitational acceleration to consistent length units. LENGTH\_CONVERSION should be set to 3.28081, 1.0, and 100.0 when using length units (LENGTH\_UNITS) of feet, meters, or centimeters in the simulation, respectively. LENGTH\_CONVERSION does not need to be specified if no lake outlets are specified or LENGTH\_UNITS are meters.
- **nlakes** (*integer*) –
  - nlakes (integer) value specifying the number of lakes that will be simulated for all stress periods.
- **noutlets** (*integer*) –
  - noutlets (integer) value specifying the number of outlets that will be simulated for all stress periods. If NOUTLETS is not specified, a default value of zero is used.
- **ntables** (*integer*) –



- ntables (integer) value specifying the number of lakes tables that will be used to define the lake stage, volume relation, and surface area. If NTABLES is not specified, a default value of zero is used.
- **packagedata** (*[lakeno, strt, nlakeconn, aux, boundname]*) –
  - lakeno (integer) integer value that defines the lake number associated with the specified PACKAGEDATA data on the line. LAKENO must be greater than zero and less than or equal to NLAKES. Lake information must be specified for every lake or the program will terminate with an error. The program will also terminate with an error if information for a lake is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - strt (double) real value that defines the starting stage for the lake.
  - nlakeconn (integer) integer value that defines the number of GWF cells connected to this (LAKENO) lake. There can only be one vertical lake connection to each GWF cell. NLAKECONN must be greater than zero.
  - aux (double) represents the values of the auxiliary variables for each lake. The values of auxiliary variables must be present for each lake. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the lake cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **connectiondata** (*[lakeno, iconn, cellid, claktype, bedleak, belev, telev,)* –

**connlen, connwidth]**

- lakeno (integer) integer value that defines the lake number associated with the specified CONNECTIONDATA data on the line. LAKENO must be greater than zero and less than or equal to NLAKES. Lake connection information must be specified for every lake connection to the GWF model (NLAKECONN) or the program will terminate with an error. The program will also terminate with an error if connection information for a lake connection to the GWF model is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- iconn (integer) integer value that defines the GWF connection number for this lake connection entry. ICONN must be greater than zero and less than or equal to NLAKECONN for lake LAKENO. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an

index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.

- `claktype` (string) character string that defines the lake-GWF connection type for the lake connection. Possible lake-GWF connection type strings include: `VERTICAL`—character keyword to indicate the lake-GWF connection is vertical and connection conductance calculations use the hydraulic conductivity corresponding to the  $K_{33}$  tensor component defined for `CELLID` in the NPF package. `HORIZONTAL`—character keyword to indicate the lake-GWF connection is horizontal and connection conductance calculations use the hydraulic conductivity corresponding to the  $K_{11}$  tensor component defined for `CELLID` in the NPF package. `EMBEDDEDH`—character keyword to indicate the lake-GWF connection is embedded in a single cell and connection conductance calculations use the hydraulic conductivity corresponding to the  $K_{11}$  tensor component defined for `CELLID` in the NPF package. `EMBEDDEDV`—character keyword to indicate the lake-GWF connection is embedded in a single cell and connection conductance calculations use the hydraulic conductivity corresponding to the  $K_{33}$  tensor component defined for `CELLID` in the NPF package. Embedded lakes can only be connected to a single cell (`NLAKECONN` = 1) and there must be a lake table associated with each embedded lake.
- `bedleak` (double) character string or real value that defines the bed leakance for the lake-GWF connection. `BEDLEAK` must be greater than or equal to zero or specified to be `NONE`. If `BEDLEAK` is specified to be `NONE`, the lake-GWF connection conductance is solely a function of aquifer properties in the connected GWF cell and lakebed sediments are assumed to be absent.
- `belev` (double) real value that defines the bottom elevation for a `HORIZONTAL` lake-GWF connection. Any value can be specified if `CLAKTYPE` is `VERTICAL`, `EMBEDDEDH`, or `EMBEDDEDV`. If `CLAKTYPE` is `HORIZONTAL` and `BELEV` is not equal to `TELEV`, `BELEV` must be greater than or equal to the bottom of the GWF cell `CELLID`. If `BELEV` is equal to `TELEV`, `BELEV` is reset to the bottom of the GWF cell `CELLID`.
- `telev` (double) real value that defines the top elevation for a `HORIZONTAL` lake-GWF connection. Any value can be specified if `CLAKTYPE` is `VERTICAL`, `EMBEDDEDH`, or `EMBEDDEDV`. If `CLAKTYPE` is `HORIZONTAL` and `TELEV` is not equal to `BELEV`, `TELEV` must be less than or equal to the top of the GWF cell `CELLID`. If `TELEV` is equal to `BELEV`, `TELEV` is reset to the top of the GWF cell `CELLID`.
- `connlen` (double) real value that defines the distance between the connected GWF `CELLID` node and the lake for a `HORIZONTAL`, `EMBEDDEDH`, or `EMBEDDEDV` lake-GWF connection. `CONLENN` must be greater than zero for a `HORIZONTAL`, `EMBEDDEDH`, or `EMBEDDEDV` lake-GWF connection. Any value can be specified if `CLAKTYPE` is `VERTICAL`.
- `connwidth` (double) real value that defines the connection face width for a `HORIZONTAL` lake-GWF connection. `CONNWIDTH` must be greater than zero for a `HORIZONTAL` lake-GWF connection. Any value can be specified if `CLAKTYPE` is `VERTICAL`, `EMBEDDEDH`, or `EMBEDDEDV`.
- `tables([lakeno, tab6_filename])` –
  - `lakeno` (integer) integer value that defines the lake number associated with the specified `TABLES` data on the line. `LAKENO` must be greater than zero and less than or equal to `NLAKES`. The program will terminate with an error if table information for

a lake is specified more than once or the number of specified tables is less than NTABLES. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- `tab6_filename` (string) character string that defines the path and filename for the file containing lake table data for the lake connection. The `TAB6_FILENAME` file includes the number of entries in the file and the relation between stage, volume, and surface area for each entry in the file. Lake table files for `EMBEDDEDH` and `EMBEDDEDV` lake-GWF connections also include lake-GWF exchange area data for each entry in the file. Instructions for creating the `TAB6_FILENAME` input file are provided in Lake Table Input File section.
- **outlets** (`[outletno, lakein, lakeout, couttype, invert, width, rough,)` –  
**slope]**
  - `outletno` (integer) integer value that defines the outlet number associated with the specified OUTLETS data on the line. `OUTLETNO` must be greater than zero and less than or equal to `NOUTLETS`. Outlet information must be specified for every outlet or the program will terminate with an error. The program will also terminate with an error if information for a outlet is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `lakein` (integer) integer value that defines the lake number that outlet is connected to. `LAKEIN` must be greater than zero and less than or equal to `NLAKES`. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `lakeout` (integer) integer value that defines the lake number that outlet discharge from lake outlet `OUTLETNO` is routed to. `LAKEOUT` must be greater than or equal to zero and less than or equal to `NLAKES`. If `LAKEOUT` is zero, outlet discharge from lake outlet `OUTLETNO` is discharged to an external boundary. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `couttype` (string) character string that defines the outlet type for the outlet `OUTLETNO`. Possible `COUTTYPE` strings include: `SPECIFIED`–character keyword to indicate the outlet is defined as a specified flow. `MANNING`–character keyword to indicate the outlet is defined using Manning’s equation. `WEIR`–character keyword to indicate the outlet is defined using a sharp weir equation.
  - `invert` (double) real value that defines the invert elevation for the lake outlet. Any value can be specified if `COUTTYPE` is `SPECIFIED`. If the Options block includes a `TIMESERIESFILE` entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `width` (double) real value that defines the width of the lake outlet. Any value can be specified if `COUTTYPE` is `SPECIFIED`. If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- rough (double) real value that defines the roughness coefficient for the lake outlet. Any value can be specified if COUTTYPE is not MANNING. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - slope (double) real value that defines the bed slope for the lake outlet. Any value can be specified if COUTTYPE is not MANNING. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- **perioddata** ([*number*, *laksetting*]) –
    - number (integer) integer value that defines the lake or outlet number associated with the specified PERIOD data on the line. NUMBER must be greater than zero and less than or equal to NLAKES for a lake number and less than or equal to NOUTLETS for an outlet number. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
    - laksetting (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the LAKSETTING string include both keywords for lake settings and keywords for outlet settings. Keywords for lake settings include: STATUS, STAGE, RAINFALL, EVAPORATION, RUNOFF, INFLOW, WITHDRAWAL, and AUXILIARY. Keywords for outlet settings include RATE, INVERT, WIDTH, SLOPE, and ROUGH.

**status** [[string]]

- \* status (string) keyword option to define lake status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE.

**stage** [[string]]

- \* stage (string) real or character value that defines the stage for the lake. The specified STAGE is only applied if the lake is a constant stage lake. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rainfall** [[string]]

- \* rainfall (string) real or character value that defines the rainfall rate ( $LT^{-1}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**evaporation** [[string]]

- \* evaporation (string) real or character value that defines the maximum evaporation rate ( $LT^{-1}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**runoff** [[string]]

- \* runoff (string) real or character value that defines the runoff rate ( $L^3T^{-1}$ ) for the lake. Value must be greater than or equal to zero. If the Options

block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**inflow** [[string]]

- \* inflow (string) real or character value that defines the volumetric inflow rate ( $L^3T^{-1}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, inflow rates are zero for each lake.

**withdrawal** [[string]]

- \* withdrawal (string) real or character value that defines the maximum withdrawal rate ( $L^3T^{-1}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rate** [[string]]

- \* rate (string) real or character value that defines the extraction rate for the lake outflow. A positive value indicates inflow and a negative value indicates outflow from the lake. RATE only applies to active (IBOUND > 0) lakes. A specified RATE is only applied if COUTTYPE for the OUTLETNO is SPECIFIED. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, the RATE for each SPECIFIED lake outlet is zero.

**invert** [[string]]

- \* invert (string) real or character value that defines the invert elevation for the lake outlet. A specified INVERT value is only used for active lakes if COUTTYPE for lake outlet OUTLETNO is not SPECIFIED. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**width** [[string]]

- \* width (string) real or character value that defines the width of the lake outlet. A specified WIDTH value is only used for active lakes if COUTTYPE for lake outlet OUTLETNO is not SPECIFIED. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**slope** [[string]]

- \* slope (string) real or character value that defines the bed slope for the lake outlet. A specified SLOPE value is only used for active lakes if COUTTYPE for lake outlet OUTLETNO is MANNING. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rough** [[string]]

- \* rough (string) real value that defines the roughness coefficient for the lake outlet. Any value can be specified if COUTTYPE is not MANNING. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**auxiliaryrecord** [[auxname, auxval]]

- \* auxname (string) name for the auxiliary variable to be assigned AUXVAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.
  - \* auxval (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- **filename** (*String*) – File name for this package.
  - **pname** (*String*) – Package name for this package.
  - **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfg-wflak package parent\_file.

**auxiliary** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**budget\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**budgetcsv\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**connectiondata** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_stage', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name print_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name stage_filerecord', 'type record
stage fileout stagefile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name stage', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name stagefile', 'type
string', 'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged
false', 'optional false'], ['block options', 'name budget_filerecord', 'type record
budget fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name budget', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name fileout',
'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name
package_convergence_filerecord', 'type record package_convergence fileout
package_convergence_filename', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name package_convergence', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name package_convergence_filename', 'type string', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block options', 'name
ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader urword',
'tagged true', 'optional true', 'construct_package ts', 'construct_data timeseries',
'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type
string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false',
'tagged false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block options', 'name
surfdep', 'type double precision', 'reader urword', 'optional true'], ['block
options', 'name time_conversion', 'type double precision', 'reader urword',
'optional true'], ['block options', 'name length_conversion', 'type double
precision', 'reader urword', 'optional true'], ['block dimensions', 'name nlakes',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name
noutlets', 'type integer', 'reader urword', 'optional false'], ['block dimensions',
'name ntables', 'type integer', 'reader urword', 'optional false'], ['block
packagedata', 'name packagedata', 'type recarray lakeno strt nlakeconn aux
boundname', 'shape (maxbound)', 'reader urword'], ['block packagedata', 'name
lakeno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'parameter_index true'], ['block packagedata', 'name strt', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block packagedata',
'name nlakeconn', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block packagedata', 'name aux', 'type double precision', 'in_record

```

```
dfn_file_name = 'gwflak.dfn'
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
outlets = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwflak'
package_convergence_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator
object>
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
perioddata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
stage_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
tables = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwfmaW module

```
class ModflowGwfmaW(model, loading_package=False, auxiliary=None, boundnames=None, print_input=None,
    print_head=None, print_flows=None, save_flows=None, head_filerecord=None,
    budget_filerecord=None, budgetcsv_filerecord=None, no_well_storage=None,
    flow_correction=None, flowing_wells=None, shutdown_theta=None,
    shutdown_kappa=None, timeseries=None, observations=None, mover=None,
    nmawwells=None, packagedata=None, connectiondata=None, perioddata=None,
    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfmaW defines a maw package within a gwfl6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for `naux`. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of multi-aquifer well cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of multi- aquifer well information will be written to the listing file immediately after it is read.



- **print\_head** (*boolean*) –
  - print\_head (boolean) keyword to indicate that the list of multi- aquifer well heads will be printed to the listing file for every stress period in which “HEAD PRINT” is specified in Output Control. If there is no Output Control option and PRINT\_HEAD is specified, then heads are printed for the last time step of each stress period.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of multi- aquifer well flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that multi-aquifer well flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **head\_filerecord** (*[headfile]*) –
  - headfile (string) name of the binary output file to write head information.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (string) name of the binary output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **no\_well\_storage** (*boolean*) –
  - no\_well\_storage (boolean) keyword that deactivates inclusion of well storage contributions to the multi-aquifer well package continuity equation.
- **flow\_correction** (*boolean*) –
  - flow\_correction (boolean) keyword that activates flow corrections in cases where the head in a multi-aquifer well is below the bottom of the screen for a connection or the head in a convertible cell connected to a multi-aquifer well is below the cell bottom. When flow corrections are activated, unit head gradients are used to calculate the flow between a multi-aquifer well and a connected GWF cell. By default, flow corrections are not made.
- **flowing\_wells** (*boolean*) –
  - flowing\_wells (boolean) keyword that activates the flowing wells option for the multi-aquifer well package.
- **shutdown\_theta** (*double*) –
  - shutdown\_theta (double) value that defines the weight applied to discharge rate for wells that limit the water level in a discharging well (defined using the HEAD\_LIMIT keyword in the stress period data). SHUTDOWN\_THETA is used to control discharge rate oscillations when the flow rate from the aquifer is less than the specified flow rate from the aquifer to the well. Values range between 0.0 and 1.0, and larger values increase the weight (decrease under-relaxation) applied to the well discharge rate. The HEAD\_LIMIT option has been included to facilitate backward compatibility with previous versions of MODFLOW but use of the

RATE\_SCALING option instead of the HEAD\_LIMIT option is recommended. By default, SHUTDOWN\_THETA is 0.7.

- **shutdown\_kappa** (*double*) –
  - shutdown\_kappa (double) value that defines the weight applied to discharge rate for wells that limit the water level in a discharging well (defined using the HEAD\_LIMIT keyword in the stress period data). SHUTDOWN\_KAPPA is used to control discharge rate oscillations when the flow rate from the aquifer is less than the specified flow rate from the aquifer to the well. Values range between 0.0 and 1.0, and larger values increase the weight applied to the well discharge rate. The HEAD\_LIMIT option has been included to facilitate backward compatibility with previous versions of MODFLOW but use of the RATE\_SCALING option instead of the HEAD\_LIMIT option is recommended. By default, SHUTDOWN\_KAPPA is 0.0001.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (boolean) keyword to indicate that this instance of the MAW Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **nmawwells** (*integer*) –
  - nmawwells (integer) integer value specifying the number of multi- aquifer wells that will be simulated for all stress periods.
- **packagedata** (*[wellno, radius, bottom, strt, condeqn, ngwfnodes, aux,)* –  
**boundname]**
  - wellno (integer) integer value that defines the well number associated with the specified PACKAGEDATA data on the line. WELLNO must be greater than zero and less than or equal to NMAWWELLS. Multi- aquifer well information must be specified for every multi-aquifer well or the program will terminate with an error. The program will also terminate with an error if information for a multi-aquifer well is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - radius (double) radius for the multi-aquifer well. The program will terminate with an error if the radius is less than or equal to zero.

- bottom (double) bottom elevation of the multi-aquifer well. If CONDEQN is SPECIFIED, THIEM, SKIN, or COMPOSITE, BOTTOM is set to the cell bottom in the lowermost GWF cell connection in cases where the specified well bottom is above the bottom of this GWF cell. If CONDEQN is MEAN, BOTTOM is set to the lowermost GWF cell connection screen bottom in cases where the specified well bottom is above this value. The bottom elevation defines the lowest well head that will be simulated when the NEWTON UNDER\_RELAXATION option is specified in the GWF model name file. The bottom elevation is also used to calculate volumetric storage in the well.
  - strt (double) starting head for the multi-aquifer well. The program will terminate with an error if the starting head is less than the specified well bottom.
  - condeqn (string) character string that defines the conductance equation that is used to calculate the saturated conductance for the multi-aquifer well. Possible multi-aquifer well CONDEQN strings include: SPECIFIED—character keyword to indicate the multi-aquifer well saturated conductance will be specified. THIEM—character keyword to indicate the multi-aquifer well saturated conductance will be calculated using the Thiem equation, which considers the cell top and bottom, aquifer hydraulic conductivity, and effective cell and well radius. SKIN—character keyword to indicate that the multi-aquifer well saturated conductance will be calculated using the cell top and bottom, aquifer and screen hydraulic conductivity, and well and skin radius. CUMULATIVE—character keyword to indicate that the multi-aquifer well saturated conductance will be calculated using a combination of the Thiem and SKIN equations. MEAN—character keyword to indicate the multi-aquifer well saturated conductance will be calculated using the aquifer and screen top and bottom, aquifer and screen hydraulic conductivity, and well and skin radius. The CUMULATIVE conductance equation is identical to the SKIN LOSSTYPE in the Multi-Node Well (MNW2) package for MODFLOW-2005. The program will terminate with an error condition if CONDEQN is SKIN or CUMULATIVE and the calculated saturated conductance is less than zero; if an error condition occurs, it is suggested that the THEIM or MEAN conductance equations be used for these multi-aquifer wells.
  - ngwfnodes (integer) integer value that defines the number of GWF nodes connected to this (WELLNO) multi-aquifer well. NGWFNODES must be greater than zero.
  - aux (double) represents the values of the auxiliary variables for each multi-aquifer well. The values of auxiliary variables must be present for each multi-aquifer well. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the multi-aquifer well cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **connectiondata** (*[wellno, icon, cellid, scrn\_top, scrn\_bot, hk\_skin,] – radius\_skin]*)
    - wellno (integer) integer value that defines the well number associated with the

specified CONNECTIONDATA data on the line. WELLNO must be greater than zero and less than or equal to NMAWWELLS. Multi-aquifer well connection information must be specified for every multi-aquifer well connection to the GWF model (NGWFNODES) or the program will terminate with an error. The program will also terminate with an error if connection information for a multi-aquifer well connection to the GWF model is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- icon (integer) integer value that defines the GWF connection number for this multi-aquifer well connection entry. ICONN must be greater than zero and less than or equal to NGWFNODES for multi-aquifer well WELLNO. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. One or more screened intervals can be connected to the same CELLID if CONDEQN for a well is MEAN. The program will terminate with an error if MAW wells using SPECIFIED, THIEM, SKIN, or CUMULATIVE conductance equations have more than one connection to the same CELLID. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- scrn\_top (double) value that defines the top elevation of the screen for the multi-aquifer well connection. If CONDEQN is SPECIFIED, THIEM, SKIN, or COMPOSITE, SCRN\_TOP can be any value and is set to the top of the cell. If CONDEQN is MEAN, SCRN\_TOP is set to the multi-aquifer well connection cell top if the specified value is greater than the cell top. The program will terminate with an error if the screen top is less than the screen bottom.
- scrn\_bot (double) value that defines the bottom elevation of the screen for the multi-aquifer well connection. If CONDEQN is SPECIFIED, THIEM, SKIN, or COMPOSITE, SCRN\_BOT can be any value is set to the bottom of the cell. If CONDEQN is MEAN, SCRN\_BOT is set to the multi-aquifer well connection cell bottom if the specified value is less than the cell bottom. The program will terminate with an error if the screen bottom is greater than the screen top.
- hk\_skin (double) value that defines the skin (filter pack) hydraulic conductivity (if CONDEQN for the multi-aquifer well is SKIN, CUMULATIVE, or MEAN) or conductance (if CONDEQN for the multi-aquifer well is SPECIFIED) for each GWF node connected to the multi-aquifer well (NGWFNODES). If CONDEQN is SPECIFIED, HK\_SKIN must be greater than or equal to zero. HK\_SKIN can be any value if CONDEQN is THIEM. Otherwise, HK\_SKIN must be greater than zero. If CONDEQN is SKIN, the contrast between the cell transmissivity (the product of geometric mean horizontal hydraulic conductivity and the cell thickness) and the well transmissivity (the product of HK\_SKIN and the screen thicknesses) must be greater than one in

node CELLID or the program will terminate with an error condition; if an error condition occurs, it is suggested that the HK\_SKIN be reduced to a value less than K11 and K22 in node CELLID or the THEIM or MEAN conductance equations be used for these multi-aquifer wells.

- radius\_skin (double) real value that defines the skin radius (filter pack radius) for the multi-aquifer well. RADIUS\_SKIN can be any value if CONDEQN is SPECIFIED or THIEM. If CONDEQN is SKIN, CUMULATIVE, or MEAN, the program will terminate with an error if RADIUS\_SKIN is less than or equal to the RADIUS for the multi-aquifer well.

• **perioddata** ([wellno, mawsetting]) –

- wellno (integer) integer value that defines the well number associated with the specified PERIOD data on the line. WELLNO must be greater than zero and less than or equal to NMAWWELLS. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- mawsetting (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the MAWSETTING string include: STATUS, FLOWING\_WELL, RATE, WELL\_HEAD, HEAD\_LIMIT, SHUT\_OFF, RATE\_SCALING, and AUXILIARY.

**status** [[string]]

- \* status (string) keyword option to define well status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE.

**flowing\_wellrecord** [[fwelev, fwcond, fwrlen]]

- \* fwelev (double) elevation used to determine whether or not the well is flowing.
- \* fwcond (double) conductance used to calculate the discharge of a free flowing well. Flow occurs when the head in the well is above the well top elevation (FWELEV).
- \* fwrlen (double) length used to reduce the conductance of the flowing well. When the head in the well drops below the well top plus the reduction length, then the conductance is reduced. This reduction length can be used to improve the stability of simulations with flowing wells so that there is not an abrupt change in flowing well rates.

**rate** [[double]]

- \* rate (double) is the volumetric pumping rate for the multi-aquifer well. A positive value indicates recharge and a negative value indicates discharge (pumping). RATE only applies to active (IBOUND > 0) multi-aquifer wells. If the Options block includes a TIMESERIES-FILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, the RATE for each multi-aquifer well is zero.

**well\_head** [[double]]

- \* well\_head (double) is the head in the multi-aquifer well. WELL\_HEAD is only applied to constant head (STATUS is

CONSTANT) and inactive (STATUS is INACTIVE) multi-aquifer wells. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. The program will terminate with an error if WELL\_HEAD is less than the bottom of the well.

**head\_limit** [[string]]

- \* head\_limit (string) is the limiting water level (head) in the well, which is the minimum of the well RATE or the well inflow rate from the aquifer. HEAD\_LIMIT can be applied to extraction wells (RATE < 0) or injection wells (RATE > 0). HEAD\_LIMIT can be deactivated by specifying the text string ‘OFF’. The HEAD\_LIMIT option is based on the HEAD\_LIMIT functionality available in the MNW2 (Konikow et al., 2009) package for MODFLOW-2005. The HEAD\_LIMIT option has been included to facilitate backward compatibility with previous versions of MODFLOW but use of the RATE\_SCALING option instead of the HEAD\_LIMIT option is recommended. By default, HEAD\_LIMIT is ‘OFF’.

**shutoffrecord** [[minrate, maxrate]]

- \* minrate (double) is the minimum rate that a well must exceed to shut-off a well during a stress period. The well will shut down during a time step if the flow rate to the well from the aquifer is less than MINRATE. If a well is shut down during a time step, reactivation of the well cannot occur until the next time step to reduce oscillations. MINRATE must be less than maxrate.
- \* maxrate (double) is the maximum rate that a well must exceed to re-activate a well during a stress period. The well will reactivate during a timestep if the well was shutdown during the previous time step and the flow rate to the well from the aquifer exceeds maxrate. Reactivation of the well cannot occur until the next time step if a well is shutdown to reduce oscillations. maxrate must be greater than MINRATE.

**rate\_scalingrecord** [[pump\_elevation, scaling\_length]]

- \* pump\_elevation (double) is the elevation of the multi-aquifer well pump (PUMP\_ELEVATION). PUMP\_ELEVATION should not be less than the bottom elevation (BOTTOM) of the multi-aquifer well.
- \* scaling\_length (double) height above the pump elevation (SCALING\_LENGTH). If the simulated well head is below this elevation (pump elevation plus the scaling length), then the pumping rate is reduced.

**auxiliaryrecord** [[auxname, auxval]]

- \* auxname (string) name for the auxiliary variable to be assigned AUXVAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.
- \* auxval (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input”

section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

**budget\_filerecord** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

**budgetcsv\_filerecord** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

**connectiondata** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_head', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name print_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name head_filerecord', 'type record
head fileout headfile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name head', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name headfile', 'type
string', 'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged
false', 'optional false'], ['block options', 'name budget_filerecord', 'type record
budget fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name budget', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name fileout',
'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name no_well_storage', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
flow_correction', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name flowing_wells', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name shutdown_theta', 'type double precision', 'reader urword',
'optional true'], ['block options', 'name shutdown_kappa', 'type double precision',
'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type
record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional
true', 'construct_package ts', 'construct_data timeseries', 'parameter_name
timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name ts6_filename', 'type string',
'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged
false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name nmawwells', 'type integer', 'reader urword', 'optional false'], ['block
packagedata', 'name packagedata', 'type recarray wellno radius bottom strt condeqn
ngwfnodes aux boundname', 'shape (nmawwells)', 'reader urword'], ['block
packagedata', 'name wellno', 'type integer', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'numeric_index true'], ['block packagedata', 'name radius',
'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block packagedata', 'name bottom', 'type double precision', 'shape',
'tagged false', 'in_record true', 'reader urword'], ['block packagedata', 'name
strt', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block packagedata', 'name condeqn', 'type string', 'shape', 'tagged
false', 'in_record true', 'reader urword'], ['block packagedata', 'name ngwfnodes',
'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword'], ['block
packagedata', 'name aux', 'type double precision', 'in_record true', 'tagged false',
'shape (naux)', 'reader urword', 'time_series true', 'optional true'], ['block

```



```

dfn_file_name = 'gwf-maw.dfn'
head_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfmaW'
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
perioddata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```

## flopY.mf6.modflow.mfgwfmvr module

```

class ModflowGwfmvr(model, loading_package=False, print_input=None, print_flows=None,
                    modelnames=None, budget_filerecord=None, budgetcsv_filerecord=None, maxmvr=None,
                    maxpackages=None, packages=None, perioddata=None, filename=None, pname=None,
                    parent_file=None)

```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfmvr defines a mvr package within a gw6 model. This package can only be used to move water between packages within a single model. To move water between models use ModflowMvr.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of MVR information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of MVR flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **modelnames** (*boolean*) –
  - modelnames (boolean) keyword to indicate that all package names will be preceded by the model name for the package. Model names are required when the Mover Package is used with a GWF-GWF Exchange. The MODELNAME keyword should not be used for a Mover Package that is for a single GWF Model.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (string) name of the output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **maxmvr** (*integer*) –

- maxmvr (integer) integer value specifying the maximum number of water mover entries that will specified for any stress period.
- **maxpackages** (*integer*) –
  - maxpackages (integer) integer value specifying the number of unique packages that are included in this water mover input file.
- **packages** (*[mname, pname]*) –
  - mname (string) name of model containing the package. Model names are assigned by the user in the simulation name file.
  - pname (string) is the name of a package that may be included in a subsequent stress period block. The package name is assigned in the name file for the GWF Model. Package names are optionally provided in the name file. If they are not provided by the user, then packages are assigned a default value, which is the package acronym followed by a hyphen and the package number. For example, the first Drain Package is named DRN-1. The second Drain Package is named DRN-2, and so forth.
- **perioddata** (*[mname1, pname1, id1, mname2, pname2, id2, mvrtype, value]*) –
  - mname1 (string) name of model containing the package, PNAME1.
  - pname1 (string) is the package name for the provider. The package PNAME1 must be designated to provide water through the MVR Package by specifying the keyword “MOVER” in its OPTIONS block.
  - id1 (integer) is the identifier for the provider. For the standard boundary packages, the provider identifier is the number of the boundary as it is listed in the package input file. (Note that the order of these boundaries may change by stress period, which must be accounted for in the Mover Package.) So the first well has an identifier of one. The second is two, and so forth. For the advanced packages, the identifier is the reach number (SFR Package), well number (MAW Package), or UZF cell number. For the Lake Package, ID1 is the lake outlet number. Thus, outflows from a single lake can be routed to different streams, for example. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - mname2 (string) name of model containing the package, PNAME2.
  - pname2 (string) is the package name for the receiver. The package PNAME2 must be designated to receive water from the MVR Package by specifying the keyword “MOVER” in its OPTIONS block.
  - id2 (integer) is the identifier for the receiver. The receiver identifier is the reach number (SFR Package), Lake number (LAK Package), well number (MAW Package), or UZF cell number. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - mvrtype (string) is the character string signifying the method for determining how much water will be moved. Supported values are “FACTOR” “EXCESS” “THRESHOLD” and “UPTO”. These four options determine how the receiver flow rate,  $Q_R$ , is calculated. These options mirror the options defined for the cprior variable in the SFR package, with the term “FACTOR” being functionally equivalent to the “FRACTION” option for cprior.

- value (double) is the value to be used in the equation for calculating the amount of water to move. For the “FACTOR” option, VALUE is the  $\alpha$  factor. For the remaining options, VALUE is the specified flow rate,  $Q_S$ .

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
budget_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budgetcsv_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name modelnames', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block dimensions', 'name maxmvr', 'type integer', 'reader
urword', 'optional false'], ['block dimensions', 'name maxpackages', 'type integer',
'reader urword', 'optional false'], ['block packages', 'name packages', 'type
recarray mname pname', 'reader urword', 'shape (npackages)', 'optional false'],
['block packages', 'name mname', 'type string', 'reader urword', 'shape', 'tagged
false', 'in_record true', 'optional true'], ['block packages', 'name pname', 'type
string', 'reader urword', 'shape', 'tagged false', 'in_record true', 'optional
false'], ['block period', 'name iper', 'type integer', 'block_variable True',
'in_record true', 'tagged false', 'shape', 'valid', 'reader urword', 'optional
false'], ['block period', 'name perioddata', 'type recarray mname1 pname1 id1 mname2
pname2 id2 mvrtype value', 'shape (maxbound)', 'reader urword'], ['block period',
'name mname1', 'type string', 'reader urword', 'shape', 'tagged false', 'in_record
true', 'optional true'], ['block period', 'name pname1', 'type string', 'shape',
'tagged false', 'in_record true', 'reader urword'], ['block period', 'name id1',
'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name mname2', 'type string', 'reader
urword', 'shape', 'tagged false', 'in_record true', 'optional true'], ['block
period', 'name pname2', 'type string', 'shape', 'tagged false', 'in_record true',
'reader urword'], ['block period', 'name id2', 'type integer', 'shape', 'tagged
false', 'in_record true', 'reader urword', 'numeric_index true'], ['block period',
'name mvrtype', 'type string', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block period', 'name value', 'type double precision', 'shape', 'tagged
false', 'in_record true', 'reader urword']]
```

```
dfn_file_name = 'gwf-mvr.dfn'
```

```
package_abbr = 'gwfmr'  
packages = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>  
perioddata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### **flopy.mf6.modflow.mfgwfnam module**

```
class ModflowGwfnam(model, loading_package=False, list=None, print_input=None, print_flows=None,  
                    save_flows=None, newtonoptions=None, packages=None, filename=None, pname=None,  
                    parent_file=None)
```

Bases: [flopy.mf6.mfpackage.MFPackage](#)

ModflowGwfnam defines a nam package within a gwfn6 model.

#### **Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **list** (*string*) –
  - list (*string*) is name of the listing file to create for this GWF model. If not specified, then the name of the list file will be the basename of the GWF model name file and the '.lst' extension. For example, if the GWF name file is called "my.model.nam" then the list file will be called "my.model.lst".
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of all model stress package information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of all model package flow rates will be printed to the listing file for every stress period time step in which "BUDGET PRINT" is specified in Output Control. If there is no Output Control option and "PRINT\_FLOWS" is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that all model package flow terms will be written to the file specified with "BUDGET FILEOUT" in Output Control.
- **newtonoptions** (*[under\_relaxation]*) –
  - under\_relaxation (*string*) keyword that indicates whether the groundwater head in a cell will be under-relaxed when water levels fall below the bottom of the model below any given cell. By default, Newton-Raphson UNDER\_RELAXATION is not applied.
- **packages** (*[ftype, fname, pname]*) –
  - ftype (*string*) is the file type, which must be one of the following character values shown in table in mf6io.pdf. Ftype may be entered in any combination of uppercase and lowercase.

- `fname` (string) is the name of the file containing the package input. The path to the file should be included if the file is not located in the folder where the program was run.
- `pname` (string) is the user-defined name for the package. PNAME is restricted to 16 characters. No spaces are allowed in PNAME. PNAME character values are read and stored by the program for stress packages only. These names may be useful for labeling purposes when multiple stress packages of the same type are located within a single GWF Model. If PNAME is specified for a stress package, then PNAME will be used in the flow budget table in the listing file; it will also be used for the text entry in the cell-by-cell budget file. PNAME is case insensitive and is stored in all upper case letters.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mftllaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name list', 'type string', 'reader urword',
'optional true'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name save_flows', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name newtonoptions',
'type record newton under_relaxation', 'reader urword', 'optional true'], ['block
options', 'name newton', 'in_record true', 'type keyword', 'reader urword'], ['block
options', 'name under_relaxation', 'in_record true', 'type keyword', 'reader
urword', 'optional true'], ['block packages', 'name packages', 'type recarray ftype
fname pname', 'reader urword', 'optional false'], ['block packages', 'name ftype',
'in_record true', 'type string', 'tagged false', 'reader urword'], ['block
packages', 'name fname', 'in_record true', 'type string', 'preserve_case true',
'tagged false', 'reader urword'], ['block packages', 'name pname', 'in_record true',
'type string', 'tagged false', 'reader urword', 'optional true']]
```

```
dfn_file_name = 'gwf-nam.dfn'
```

```
package_abbr = 'gwfnam'
```

```
packages = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flop.mf6.modflow.mfgwfnpf module

```
class ModflowGwfnpf(model, loading_package=False, save_flows=None, alternative_cell_averaging=None,
thickstr=None, cvoptions=None, perched=None, rewet_record=None, xt3doptions=None,
save_specific_discharge=None, save_saturation=None, k22overk=None, k33overk=None,
tvk_filerecord=None, icelltype=0, k=1.0, k22=None, k33=None, angle1=None,
angle2=None, angle3=None, wetdry=None, filename=None, pname=None,
parent_file=None)
```

Bases: [\*flop.mf6.mfpackage.MFPackage\*](#)

ModflowGwfnpf defines a npf package within a gw6 model.

### Parameters

- **`model`** (*MFModel*) – Model that this package is a part of. Package is automatically added to model when it is initialized.

- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that budget flow terms will be written to the file specified with “BUDGET SAVE FILE” in Output Control.
- **alternative\_cell\_averaging** (*string*) –
  - alternative\_cell\_averaging (string) is a text keyword to indicate that an alternative method will be used for calculating the conductance for horizontal cell connections. The text value for ALTERNATIVE\_CELL\_AVERAGING can be “LOGARITHMIC”, “AMT-LMK”, or “AMT-HMK”. “AMT-LMK” signifies that the conductance will be calculated using arithmetic-mean thickness and logarithmic-mean hydraulic conductivity. “AMT-HMK” signifies that the conductance will be calculated using arithmetic-mean thickness and harmonic-mean hydraulic conductivity. If the user does not specify a value for ALTERNATIVE\_CELL\_AVERAGING, then the harmonic-mean method will be used. This option cannot be used if the XT3D option is invoked.
- **thickstrt** (*boolean*) –
  - thickstrt (boolean) indicates that cells having a negative ICELLTYPE are confined, and their cell thickness for conductance calculations will be computed as STRT-BOT rather than TOP-BOT.
- **cvoptions** (*[dewatered]*) –
  - dewatered (string) If the DEWATERED keyword is specified, then the vertical conductance is calculated using only the saturated thickness and properties of the overlying cell if the head in the underlying cell is below its top.
- **perched** (*boolean*) –
  - perched (boolean) keyword to indicate that when a cell is overlying a dewatered convertible cell, the head difference used in Darcy’s Law is equal to the head in the overlying cell minus the bottom elevation of the overlying cell. If not specified, then the default is to use the head difference between the two cells.
- **rewet\_record** (*[wetfct, iwetit, ihdwet]*) –
  - wetfct (double) is a keyword and factor that is included in the calculation of the head that is initially established at a cell when that cell is converted from dry to wet.
  - iwetit (integer) is a keyword and iteration interval for attempting to wet cells. Wetting is attempted every IWETIT iteration. This applies to outer iterations and not inner iterations. If IWETIT is specified as zero or less, then the value is changed to 1.
  - ihdwet (integer) is a keyword and integer flag that determines which equation is used to define the initial head at cells that become wet. If IHDWET is 0,  $h = \text{BOT} + \text{WETFCT} (\text{hm} - \text{BOT})$ . If IHDWET is not 0,  $h = \text{BOT} + \text{WETFCT} (\text{THRESH})$ .
- **xt3doptions** (*[rhs]*) –
  - rhs (string) If the RHS keyword is also included, then the XT3D additional terms will be added to the right-hand side. If the RHS keyword is excluded, then the XT3D terms will be put into the coefficient matrix.
- **save\_specific\_discharge** (*boolean*) –

- `save_specific_discharge` (boolean) keyword to indicate that x, y, and z components of specific discharge will be calculated at cell centers and written to the budget file, which is specified with “BUDGET SAVE FILE” in Output Control. If this option is activated, then additional information may be required in the discretization packages and the GWF Exchange package (if GWF models are coupled). Specifically, ANGLDEGX must be specified in the CONNECTIONDATA block of the DISU Package; ANGLDEGX must also be specified for the GWF Exchange as an auxiliary variable.
- **save\_saturation** (*boolean*) –
  - `save_saturation` (boolean) keyword to indicate that cell saturation will be written to the budget file, which is specified with “BUDGET SAVE FILE” in Output Control. Saturation will be saved to the budget file as an auxiliary variable saved with the DATA-SAT text label. Saturation is a cell variable that ranges from zero to one and can be used by post processing programs to determine how much of a cell volume is saturated. If ICELLTYPE is 0, then saturation is always one.
- **k22overk** (*boolean*) –
  - `k22overk` (boolean) keyword to indicate that specified K22 is a ratio of K22 divided by K. If this option is specified, then the K22 array entered in the NPF Package will be multiplied by K after being read.
- **k33overk** (*boolean*) –
  - `k33overk` (boolean) keyword to indicate that specified K33 is a ratio of K33 divided by K. If this option is specified, then the K33 array entered in the NPF Package will be multiplied by K after being read.
- **tvk\_filerecord** (*[tvk\_filename]*) –
  - `tvk_filename` (string) defines a time-varying hydraulic conductivity (TVK) input file. Records in the TVK file can be used to change hydraulic conductivity properties at specified times or stress periods.
- **icelltype** (*[integer]*) –
  - `icelltype` (integer) flag for each cell that specifies how saturated thickness is treated. 0 means saturated thickness is held constant; >0 means saturated thickness varies with computed head when head is below the cell top; <0 means saturated thickness varies with computed head unless the THICKSTRT option is in effect. When THICKSTRT is in effect, a negative value of `icelltype` indicates that saturated thickness will be computed as STRT-BOT and held constant.
- **k** (*[double]*) –
  - `k` (double) is the hydraulic conductivity. For the common case in which the user would like to specify the horizontal hydraulic conductivity and the vertical hydraulic conductivity, then K should be assigned as the horizontal hydraulic conductivity, K33 should be assigned as the vertical hydraulic conductivity, and K22 and the three rotation angles should not be specified. When more sophisticated anisotropy is required, then K corresponds to the K11 hydraulic conductivity axis. All included cells (IDOMAIN > 0) must have a K value greater than zero.
- **k22** (*[double]*) –
  - `k22` (double) is the hydraulic conductivity of the second ellipsoid axis (or the ratio of K22/K if the K22OVERK option is specified); for an unrotated case this is the hydraulic conductivity in the y direction. If K22 is not included in the GRIDDATA block, then K22 is set equal to K. For a regular MODFLOW grid (DIS Package is

used) in which no rotation angles are specified, K22 is the hydraulic conductivity along columns in the y direction. For an unstructured DISU grid, the user must assign principal x and y axes and provide the angle for each cell face relative to the assigned x direction. All included cells (IDOMAIN > 0) must have a K22 value greater than zero.

- **k33** ([double]) –
  - k33 (double) is the hydraulic conductivity of the third ellipsoid axis (or the ratio of K33/K if the K33OVERK option is specified); for an unrotated case, this is the vertical hydraulic conductivity. When anisotropy is applied, K33 corresponds to the K33 tensor component. All included cells (IDOMAIN > 0) must have a K33 value greater than zero.
- **angle1** ([double]) –
  - angle1 (double) is a rotation angle of the hydraulic conductivity tensor in degrees. The angle represents the first of three sequential rotations of the hydraulic conductivity ellipsoid. With the K11, K22, and K33 axes of the ellipsoid initially aligned with the x, y, and z coordinate axes, respectively, ANGLE1 rotates the ellipsoid about its K33 axis (within the x - y plane). A positive value represents counter-clockwise rotation when viewed from any point on the positive K33 axis, looking toward the center of the ellipsoid. A value of zero indicates that the K11 axis lies within the x - z plane. If ANGLE1 is not specified, default values of zero are assigned to ANGLE1, ANGLE2, and ANGLE3, in which case the K11, K22, and K33 axes are aligned with the x, y, and z axes, respectively.
- **angle2** ([double]) –
  - angle2 (double) is a rotation angle of the hydraulic conductivity tensor in degrees. The angle represents the second of three sequential rotations of the hydraulic conductivity ellipsoid. Following the rotation by ANGLE1 described above, ANGLE2 rotates the ellipsoid about its K22 axis (out of the x - y plane). An array can be specified for ANGLE2 only if ANGLE1 is also specified. A positive value of ANGLE2 represents clockwise rotation when viewed from any point on the positive K22 axis, looking toward the center of the ellipsoid. A value of zero indicates that the K11 axis lies within the x - y plane. If ANGLE2 is not specified, default values of zero are assigned to ANGLE2 and ANGLE3; connections that are not user-designated as vertical are assumed to be strictly horizontal (that is, to have no z component to their orientation); and connection lengths are based on horizontal distances.
- **angle3** ([double]) –
  - angle3 (double) is a rotation angle of the hydraulic conductivity tensor in degrees. The angle represents the third of three sequential rotations of the hydraulic conductivity ellipsoid. Following the rotations by ANGLE1 and ANGLE2 described above, ANGLE3 rotates the ellipsoid about its K11 axis. An array can be specified for ANGLE3 only if ANGLE1 and ANGLE2 are also specified. An array must be specified for ANGLE3 if ANGLE2 is specified. A positive value of ANGLE3 represents clockwise rotation when viewed from any point on the positive K11 axis, looking toward the center of the ellipsoid. A value of zero indicates that the K22 axis lies within the x - y plane.
- **wetdry** ([double]) –
  - wetdry (double) is a combination of the wetting threshold and a flag to indicate which neighboring cells can cause a cell to become wet. If WETDRY < 0, only a cell below a dry cell can cause the cell to become wet. If WETDRY > 0, the cell below a dry cell and horizontally adjacent cells can cause a cell to become wet. If



WETDRY is 0, the cell cannot be wetted. The absolute value of WETDRY is the wetting threshold. When the sum of BOT and the absolute value of WETDRY at a dry cell is equaled or exceeded by the head at an adjacent cell, the cell is wetted. WETDRY must be specified if “REWET” is specified in the OPTIONS block. If “REWET” is not specified in the options block, then WETDRY can be entered, and memory will be allocated for it, even though it is not used.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
angle1 = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
angle2 = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
angle3 = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```

dfn = [['header'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name alternative_cell_averaging',
'type string', 'valid logarithmic amt-lmk amt-hmk', 'reader urword', 'optional
true'], ['block options', 'name thickstrt', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name cvoptions', 'type record variablecv
dewatered', 'reader urword', 'optional true'], ['block options', 'name variablecv',
'in_record true', 'type keyword', 'reader urword'], ['block options', 'name
dewatered', 'in_record true', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name perched', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name rewet_record', 'type record rewet wetfct iwetit ihdwet',
'reader urword', 'optional true'], ['block options', 'name rewet', 'type keyword',
'in_record true', 'reader urword', 'optional false'], ['block options', 'name
wetfct', 'type double precision', 'in_record true', 'reader urword', 'optional
false'], ['block options', 'name iwetit', 'type integer', 'in_record true', 'reader
urword', 'optional false'], ['block options', 'name ihdwet', 'type integer',
'in_record true', 'reader urword', 'optional false'], ['block options', 'name
xt3doptions', 'type record xt3d rhs', 'reader urword', 'optional true'], ['block
options', 'name xt3d', 'in_record true', 'type keyword', 'reader urword'], ['block
options', 'name rhs', 'in_record true', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_specific_discharge', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name save_saturation', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name k22overk', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name k33overk',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
tvk_filerecord', 'type record tvk6 filein tvk_filename', 'shape', 'reader urword',
'tagged true', 'optional true'], ['block options', 'name tvk6', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name tvk_filename',
'type string', 'preserve_case true', 'in_record true', 'reader urword', 'optional
false', 'tagged false'], ['block griddata', 'name icelltype', 'type integer', 'shape
(nodes)', 'valid', 'reader readarray', 'layered true', 'optional', 'default_value
0'], ['block griddata', 'name k', 'type double precision', 'shape (nodes)', 'valid',
'reader readarray', 'layered true', 'optional', 'default_value 1.0'], ['block
griddata', 'name k22', 'type double precision', 'shape (nodes)', 'valid', 'reader
readarray', 'layered true', 'optional true'], ['block griddata', 'name k33', 'type
double precision', 'shape (nodes)', 'valid', 'reader readarray', 'layered true',
'optional true'], ['block griddata', 'name angle1', 'type double precision', 'shape
(nodes)', 'valid', 'reader readarray', 'layered true', 'optional true'], ['block
griddata', 'name angle2', 'type double precision', 'shape (nodes)', 'valid', 'reader
readarray', 'layered true', 'optional true'], ['block griddata', 'name angle3',
'type double precision', 'shape (nodes)', 'valid', 'reader readarray', 'layered
true', 'optional true'], ['block griddata', 'name wetdry', 'type double precision',
'shape (nodes)', 'valid', 'reader readarray', 'layered true', 'optional true']]

dfn_file_name = 'gwf-npf.dfn'

icelltype = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
k = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
k22 = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
k33 = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
package_abbr = 'gwfnpf'

```

```
rewet_record = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
tvk_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
wetdry = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

## flopY.mf6.modflow.mfgwfoc module

```
class ModflowGwfoc(model, loading_package=False, budget_filerecord=None, budgetcsv_filerecord=None,
                    head_filerecord=None, headprintrecord=None, saverecord=None, printrecord=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfoc defines a oc package within a gwf6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
  - **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
  - **budget\_filerecord** (*[budgetfile]*) –
    - budgetfile (string) name of the output file to write budget information.
  - **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
    - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
  - **head\_filerecord** (*[headfile]*) –
    - headfile (string) name of the output file to write head information.
  - **headprintrecord** (*[columns, width, digits, format]*) –
    - columns (integer) number of columns for writing data.
    - width (integer) width for writing each number.
    - digits (integer) number of digits to use for writing a number.
    - format (string) write format can be EXPONENTIAL, FIXED, GENERAL, or SCIENTIFIC.
  - **saverecord** (*[rtype, ocsetting]*) –
    - rtype (string) type of information to save or print. Can be BUDGET or HEAD.
    - ocsetting (keystring) specifies the steps for which the data will be saved.
- all** *[[keyword]]*
- \* all (keyword) keyword to indicate save for all time steps in period.
- first** *[[keyword]]*
- \* first (keyword) keyword to indicate save for first step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.
- last** *[[keyword]]*

- \* last (keyword) keyword to indicate save for last step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**frequency** [[integer]]

- \* frequency (integer) save at the specified time step frequency. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**steps** [[integer]]

- \* steps (integer) save for each step specified in STEPS. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

- **printrecord** ([*rtype*, *ocsetting*]) –

- *rtype* (string) type of information to save or print. Can be BUDGET or HEAD.
- *ocsetting* (keysting) specifies the steps for which the data will be saved.

**all** [[keyword]]

- \* all (keyword) keyword to indicate save for all time steps in period.

**first** [[keyword]]

- \* first (keyword) keyword to indicate save for first step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**last** [[keyword]]

- \* last (keyword) keyword to indicate save for last step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**frequency** [[integer]]

- \* frequency (integer) save at the specified time step frequency. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**steps** [[integer]]

- \* steps (integer) save for each step specified in STEPS. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**budget\_filerecord** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

**budgetcsv\_filerecord** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header'], ['block options', 'name budget_filerecord', 'type record budget
fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name budget', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name fileout', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name head_filerecord', 'type
record head fileout headfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name head', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
headfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
headprintrecord', 'type record head print_format formatrecord', 'shape', 'reader
urword', 'optional true'], ['block options', 'name print_format', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name formatrecord', 'type record columns width digits format',
'shape', 'in_record true', 'reader urword', 'tagged', 'optional false'], ['block
options', 'name columns', 'type integer', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional'], ['block options', 'name width', 'type integer',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional'], ['block
options', 'name digits', 'type integer', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional'], ['block options', 'name format', 'type string', 'shape',
'in_record true', 'reader urword', 'tagged false', 'optional false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name saverecord', 'type record save rtype ocsetting', 'shape', 'reader
urword', 'tagged false', 'optional true'], ['block period', 'name save', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block period', 'name printrecord', 'type record print rtype ocsetting',
'shape', 'reader urword', 'tagged false', 'optional true'], ['block period', 'name
print', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block period', 'name rtype', 'type string', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block period', 'name
ocsetting', 'type keystring all first last frequency steps', 'shape', 'tagged
false', 'in_record true', 'reader urword'], ['block period', 'name all', 'type
keyword', 'shape', 'in_record true', 'reader urword'], ['block period', 'name
first', 'type keyword', 'shape', 'in_record true', 'reader urword'], ['block
period', 'name last', 'type keyword', 'shape', 'in_record true', 'reader urword'],
['block period', 'name frequency', 'type integer', 'shape', 'tagged true',
'in_record true', 'reader urword'], ['block period', 'name steps', 'type integer',
'shape (<nstp)', 'tagged true', 'in_record true', 'reader urword']]

dfn_file_name = 'gwf-oc.dfn'

head_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
headprintrecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfoc'

```

```
printrecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
saverecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwfrch module

```
class ModflowGwfrch(model, loading_package=False, fixed_cell=None, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, maxbound=None, stress_period_data=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfrch defines a rch package within a gw6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **fixed\_cell** (*boolean*) –
  - fixed\_cell (*boolean*) indicates that recharge will not be reassigned to a cell underlying the cell specified in the list if the specified cell is inactive.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of recharge.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of recharge cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of recharge information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of recharge flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.

- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that recharge flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of recharge cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, recharge, aux, boundname]*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - recharge (double) is the recharge flux rate ( $LT^{-1}$ ). This rate is multiplied inside the program by the surface area of the cell to calculate the volumetric recharge rate. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (double) represents the values of the auxiliary variables for each recharge. The values of auxiliary variables must be present for each recharge. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the recharge cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name fixed_cell', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name print_input', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name save_flows', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true', 'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true', 'construct_package obs', 'construct_data continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword', 'optional false'], ['block period', 'name iper', 'type integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block period', 'name stress_period_data', 'type recarray cellid recharge aux boundname', 'shape (maxbound)', 'reader urword'], ['block period', 'name cellid', 'type integer', 'shape (ncelldim)', 'tagged false', 'in_record true', 'reader urword'], ['block period', 'name recharge', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader urword', 'time_series true'], ['block period', 'name aux', 'type double precision', 'in_record true', 'tagged false', 'shape (naux)', 'reader urword', 'optional true', 'time_series true'], ['block period', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record true', 'reader urword', 'optional true']]

dfn_file_name = 'gwf-rch.dfn'

obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwf-rch'

stress_period_data = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```



**flopY.mf6.modflow.mfgwfrcha module**

```
class ModflowGwfrcha(model, loading_package=False, readasarrays=True, fixed_cell=None, auxiliary=None,
                    auxmultname=None, print_input=None, print_flows=None, save_flows=None,
                    timearrayseries=None, observations=None, irch=None, recharge=0.001, aux=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: *flopY.mf6.mfpackage.MFPackage*

ModflowGwfrcha defines a rcha package within a gwf6 model.

**Parameters**

- **model** (*MFModel*) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **readasarrays** (*boolean*) –
  - readasarrays (boolean) indicates that array-based input will be used for the Recharge Package. This keyword must be specified to use array-based input.
- **fixed\_cell** (*boolean*) –
  - fixed\_cell (boolean) indicates that recharge will not be reassigned to a cell underlying the cell specified in the list if the specified cell is inactive.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of recharge.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of recharge information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of recharge flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that recharge flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timearrayseries** (*{varname:data} or tas\_array data*) –

- Contains data for the tas package. Data can be stored in a dictionary containing data for the tas package with variable names as keys and package data as values. Data just for the timearrayseries variable is also acceptable. See tas package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **irch** (*[integer]*) –
  - irch (integer) IRCH is the layer number that defines the layer in each vertical column where recharge is applied. If IRCH is omitted, recharge by default is applied to cells in layer 1. IRCH can only be used if READASARRAYS is specified in the OPTIONS block. If IRCH is specified, it must be specified as the first variable in the PERIOD block or MODFLOW will terminate with an error. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **recharge** (*[double]*) –
  - recharge (double) is the recharge flux rate ( $LT^{-1}$ ). This rate is multiplied inside the program by the surface area of the cell to calculate the volumetric recharge rate. The recharge array may be defined by a time-array series (see the “Using Time-Array Series in a Package” section).
- **aux** (*[double]*) –
  - aux (double) is an array of values for auxiliary variable aux(iaux), where iaux is a value from 1 to naux, and aux(iaux) must be listed as part of the auxiliary variables. A separate array can be specified for each auxiliary variable. If an array is not specified for an auxiliary variable, then a value of zero is assigned. If the value specified here for the auxiliary variable is the same as auxmultname, then the recharge array will be multiplied by this array.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
aux = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
auxiliary = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header', 'multi-package'], ['block options', 'name readasarrays', 'type
keyword', 'shape', 'reader urword', 'optional false', 'default_value True'], ['block
options', 'name fixed_cell', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name auxiliary', 'type string', 'shape (naux)', 'reader
urword', 'optional true'], ['block options', 'name auxmultname', 'type string',
'shape', 'reader urword', 'optional true'], ['block options', 'name print_input',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
print_flows', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name save_flows', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name tas_filerecord', 'type record tas6 filein tas6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package tas',
'construct_data tas_array', 'parameter_name timearrayseries'], ['block options',
'name tas6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name filein', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name tas6_filename', 'type string', 'preserve_case true', 'in_record
true', 'reader urword', 'optional false', 'tagged false'], ['block options', 'name
obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader urword',
'tagged true', 'optional true', 'construct_package obs', 'construct_data
continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name obs6_filename', 'type string', 'preserve_case
true', 'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name irch', 'type integer', 'shape (ncol*nrow; ncpl)', 'reader readarray',
'numeric_index true', 'optional true'], ['block period', 'name recharge', 'type
double precision', 'shape (ncol*nrow; ncpl)', 'reader readarray', 'default_value
1.e-3'], ['block period', 'name aux', 'type double precision', 'shape (ncol*nrow;
ncpl)', 'reader readarray', 'optional true']]

dfn_file_name = 'gwfrcha.dfn'

irch = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>

obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwfrcha'

recharge = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>

tas_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

```

## flopy.mf6.modflow.mfmgwfriv module

```

class ModflowGwfriv(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, mover=None, maxbound=None,
                    stress_period_data=None, filename=None, pname=None, parent_file=None)
Bases: flopy.mf6.mfpackage.MFPackage

```

ModflowGwfriv defines a riv package within a gwfr6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.

- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for *naux*. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of riverbed conductance.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of river cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of river information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of river flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that river flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data}* or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (*boolean*) keyword to indicate that this instance of the River Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.

- **maxbound** (*integer*) –
  - maxbound (*integer*) integer value specifying the maximum number of rivers cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, stage, cond, rbot, aux, boundname]*) –
  - cellid (*(integer, ...)*) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - stage (*double*) is the head in the river. If the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - cond (*double*) is the riverbed hydraulic conductance. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - rbot (*double*) is the elevation of the bottom of the riverbed. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (*double*) represents the values of the auxiliary variables for each river. The values of auxiliary variables must be present for each river. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (*string*) name of the river cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block
options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name print_input', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name save_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type
record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional
true', 'construct_package ts', 'construct_data timeseries', 'parameter_name
timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name ts6_filename', 'type string',
'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged
false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name maxbound', 'type integer', 'reader urword', 'optional false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name stress_period_data', 'type recarray cellid stage cond rbot aux
boundname', 'shape (maxbound)', 'reader urword'], ['block period', 'name cellid',
'type integer', 'shape (ncelldim)', 'tagged false', 'in_record true', 'reader
urword'], ['block period', 'name stage', 'type double precision', 'shape', 'tagged
false', 'in_record true', 'reader urword', 'time_series true'], ['block period',
'name cond', 'type double precision', 'shape', 'tagged false', 'in_record true',
'reader urword', 'time_series true'], ['block period', 'name rbot', 'type double
precision', 'shape', 'tagged false', 'in_record true', 'reader urword', 'time_series
true'], ['block period', 'name aux', 'type double precision', 'in_record true',
'tagged false', 'shape (naux)', 'reader urword', 'optional true', 'time_series
true'], ['block period', 'name boundname', 'type string', 'shape', 'tagged false',
'in_record true', 'reader urword', 'optional true']]

dfn_file_name = 'gwf-riv.dfn'

obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwfriv'

stress_period_data = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

ts_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

**flop.mf6.modflow.mfgwfsfr module**

```
class ModflowGwfsfr(model, loading_package=False, auxiliary=None, boundnames=None, print_input=None,
    print_stage=None, print_flows=None, save_flows=None, stage_filerecord=None,
    budget_filerecord=None, budgetcsv_filerecord=None,
    package_convergence_filerecord=None, timeseries=None, observations=None,
    mover=None, maximum_picard_iterations=None, maximum_iterations=None,
    maximum_depth_change=None, unit_conversion=None, nreaches=None,
    packagedata=None, crosssections=None, connectiondata=None, diversions=None,
    perioddata=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfsfr defines a sfr package within a gw6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of stream reach cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of stream reach information will be written to the listing file immediately after it is read.
- **print\_stage** (*boolean*) –
  - print\_stage (*boolean*) keyword to indicate that the list of stream reach stages will be printed to the listing file for every stress period in which “HEAD PRINT” is specified in Output Control. If there is no Output Control option and PRINT\_STAGE is specified, then stages are printed for the last time step of each stress period.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of stream reach flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –

- `save_flows` (boolean) keyword to indicate that stream reach flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **`stage_filerecord`** (*[stagefile]*) –
  - `stagefile` (string) name of the binary output file to write stage information.
- **`budget_filerecord`** (*[budgetfile]*) –
  - `budgetfile` (string) name of the binary output file to write budget information.
- **`budgetcsv_filerecord`** (*[budgetcsvfile]*) –
  - `budgetcsvfile` (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **`package_convergence_filerecord`** (*[package\_convergence\_filename]*) –
  - `package_convergence_filename` (string) name of the comma spaced values output file to write package convergence information.
- **`timeseries`** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **`observations`** (*{varname:data}* or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **`mover`** (*boolean*) –
  - `mover` (boolean) keyword to indicate that this instance of the SFR Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **`maximum_picard_iterations`** (*integer*) –
  - `maximum_picard_iterations` (integer) value that defines the maximum number of Streamflow Routing picard iterations allowed when solving for reach stages and flows as part of the GWF formulate step. Picard iterations are used to minimize differences in SFR package results between subsequent GWF picard (non-linear) iterations as a result of non-optimal reach numbering. If reaches are numbered in order, from upstream to downstream, MAXIMUM\_PICARD\_ITERATIONS can be set to 1 to reduce model run time. By default, MAXIMUM\_PICARD\_ITERATIONS is equal to 100.
- **`maximum_iterations`** (*integer*) –
  - `maximum_iterations` (integer) value that defines the maximum number of Streamflow Routing Newton-Raphson iterations allowed for a reach. By default, MAXIMUM\_ITERATIONS is equal to 100.
- **`maximum_depth_change`** (*double*) –
  - `maximum_depth_change` (double) value that defines the depth closure tolerance. By default, DMAXCHG is equal to  $1 \times 10^{-5}$ .



- **unit\_conversion** (*double*) –
  - unit\_conversion (*double*) value (or conversion factor) that is used in calculating stream depth for stream reach. A constant of 1.486 is used for flow units of cubic feet per second, and a constant of 1.0 is used for units of cubic meters per second. The constant must be multiplied by 86,400 when using time units of days in the simulation.
- **nreaches** (*integer*) –
  - nreaches (*integer*) integer value specifying the number of stream reaches. There must be NREACHES entries in the PACKAGEDATA block.
- **packagedata** (*[rno, cellid, rlen, rwid, rgrd, rtp, rbth, rhk, man, ncon,)* –

**ustrf, ndv, aux, boundname]**

- rno (*integer*) integer value that defines the reach number associated with the specified PACKAGEDATA data on the line. RNO must be greater than zero and less than or equal to NREACHES. Reach information must be specified for every reach or the program will terminate with an error. The program will also terminate with an error if information for a reach is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- cellid (*((integer, ...))*) The keyword 'NONE' must be specified for reaches that are not connected to an underlying GWF cell. The keyword 'NONE' is used for reaches that are in cells that have IDOMAIN values less than one or are in areas not covered by the GWF model grid. Reach-aquifer flow is not calculated if the keyword 'NONE' is specified. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- rlen (*double*) real value that defines the reach length. RLEN must be greater than zero.
- rwid (*double*) real value that defines the reach width. RWID must be greater than zero.
- rgrd (*double*) real value that defines the stream gradient (slope) across the reach. RGRD must be greater than zero.
- rtp (*double*) real value that defines the bottom elevation of the reach.
- rbth (*double*) real value that defines the thickness of the reach streambed. RBTH can be any value if CELLID is 'NONE'. Otherwise, RBTH must be greater than zero.
- rhk (*double*) real value that defines the hydraulic conductivity of the reach streambed. RHK can be any positive value if CELLID is 'NONE'. Otherwise, RHK must be greater than zero.
- man (*string*) real or character value that defines the Manning's roughness coefficient for the reach. MAN must be greater than zero. If the Options block includes a TIMESERIESFILE entry (see the "Time- Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- `ncon` (integer) integer value that defines the number of reaches connected to the reach. If a value of zero is specified for `NCON` an entry for `RNO` is still required in the subsequent `CONNECTIONDATA` block.
  - `ustrf` (double) real value that defines the fraction of upstream flow from each upstream reach that is applied as upstream inflow to the reach. The sum of all `USTRF` values for all reaches connected to the same upstream reach must be equal to one and `USTRF` must be greater than or equal to zero. If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `ndv` (integer) integer value that defines the number of downstream diversions for the reach.
  - `aux` (double) represents the values of the auxiliary variables for each stream reach. The values of auxiliary variables must be present for each stream reach. The values must be specified in the order of the auxiliary variables specified in the `OPTIONS` block. If the package supports time series and the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `boundname` (string) name of the stream reach cell. `BOUNDNAME` is an ASCII character variable that can contain as many as 40 characters. If `BOUNDNAME` contains spaces in it, then the entire name must be enclosed within single quotes.
- **`crosssections`** (`[rno, tab6_filename]`) –
    - `rno` (integer) integer value that defines the reach number associated with the specified cross-section table file on the line. `RNO` must be greater than zero and less than or equal to `NREACHES`. The program will also terminate with an error if table information for a reach is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
    - `tab6_filename` (string) character string that defines the path and filename for the file containing cross-section table data for the reach. The `TAB6_FILENAME` file includes the number of entries in the file and the station elevation data in terms of the fractional width and the reach depth. Instructions for creating the `TAB6_FILENAME` input file are provided in SFR Reach Cross-Section Table Input File section.
  - **`connectiondata`** (`[rno, ic]`) –
    - `rno` (integer) integer value that defines the reach number associated with the specified `CONNECTIONDATA` data on the line. `RNO` must be greater than zero and less than or equal to `NREACHES`. Reach connection information must be specified for every reach or the program will terminate with an error. The program will also terminate with an error if connection information for a reach is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
    - `ic` (double\_precision) integer value that defines the reach number of the reach connected to the current reach and whether it is connected to the upstream or downstream end of the reach. Negative `IC` numbers indicate connected reaches are con-

nected to the downstream end of the current reach. Positive IC numbers indicate connected reaches are connected to the upstream end of the current reach. The absolute value of IC must be greater than zero and less than or equal to NREACHES. IC should not be specified when NCON is zero but must be specified otherwise. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

• **diversions** (*[rno, idv, iconr, cprior]*) –

- *rno* (integer) integer value that defines the reach number associated with the specified DIVERSIONS data on the line. RNO must be greater than zero and less than or equal to NREACHES. Reach diversion information must be specified for every reach with a NDV value greater than 0 or the program will terminate with an error. The program will also terminate with an error if diversion information for a given reach diversion is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- *idv* (integer) integer value that defines the downstream diversion number for the diversion for reach RNO. IDV must be greater than zero and less than or equal to NDV for reach RNO. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- *iconr* (integer) integer value that defines the downstream reach that will receive the diverted water. IDV must be greater than zero and less than or equal to NREACHES. Furthermore, reach ICONR must be a downstream connection for reach RNO. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- *cprior* (string) character string value that defines the the prioritization system for the diversion, such as when insufficient water is available to meet all diversion stipulations, and is used in conjunction with the value of FLOW value specified in the STRESS\_PERIOD\_DATA section. Available diversion options include: (1) CPRIOR = 'FRACTION', then the amount of the diversion is computed as a fraction of the streamflow leaving reach RNO ( $Q_{DS}$ ); in this case,  $0.0 \leq \text{DIVFLOW} \leq 1.0$ . (2) CPRIOR = 'EXCESS', a diversion is made only if  $Q_{DS}$  for reach RNO exceeds the value of DIVFLOW. If this occurs, then the quantity of water diverted is the excess flow ( $Q_{DS} - \text{DIVFLOW}$ ) and  $Q_{DS}$  from reach RNO is set equal to DIVFLOW. This represents a flood-control type of diversion, as described by Danskin and Hanson (2002). (3) CPRIOR = 'THRESHOLD', then if  $Q_{DS}$  in reach RNO is less than the specified diversion flow DIVFLOW, no water is diverted from reach RNO. If  $Q_{DS}$  in reach RNO is greater than or equal to DIVFLOW, DIVFLOW is diverted and  $Q_{DS}$  is set to the remainder ( $Q_{DS} - \text{DIVFLOW}$ ). This approach assumes that once flow in the stream is sufficiently low, diversions from the stream cease, and is the 'priority' algorithm that originally was programmed into the STR1 Package (Prudic, 1989). (4) CPRIOR = 'UPTO' – if  $Q_{DS}$  in reach RNO is greater than or equal to the specified diversion flow DIVFLOW,  $Q_{DS}$  is reduced by DIVFLOW. If  $Q_{DS}$  in reach RNO is less than DIVFLOW, DIVFLOW is set to  $Q_{DS}$  and there will be no flow available for reaches connected to downstream end of reach RNO.

• **perioddata** (*[rno, sfrsetting]*) –

- `rno` (integer) integer value that defines the reach number associated with the specified PERIOD data on the line. RNO must be greater than zero and less than or equal to NREACHES. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- `sfrsetting` (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the SFRSETTING string include: STATUS, MANNING, STAGE, INFLOW, RAINFALL, EVAPORATION, RUNOFF, DIVERSION, UPSTREAM\_FRACTION, and AUXILIARY.

**status** [[string]]

- \* `status` (string) keyword option to define stream reach status. STATUS can be ACTIVE, INACTIVE, or SIMPLE. The SIMPLE STATUS option simulates streamflow using a user-specified stage for a reach or a stage set to the top of the reach (depth = 0). In cases where the simulated leakage calculated using the specified stage exceeds the sum of inflows to the reach, the stage is set to the top of the reach and leakage is set equal to the sum of inflows. Upstream fractions should be changed using the UPSTREAM\_FRACTION SFRSETTING if the status for one or more reaches is changed to ACTIVE or INACTIVE. For example, if one of two downstream connections for a reach is inactivated, the upstream fraction for the active and inactive downstream reach should be changed to 1.0 and 0.0, respectively, to ensure that the active reach receives all of the downstream outflow from the upstream reach. By default, STATUS is ACTIVE.

**manning** [[string]]

- \* `manning` (string) real or character value that defines the Manning's roughness coefficient for the reach. MANNING must be greater than zero. If the Options block includes a TIMESERIESFILE entry (see the "Time-Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**stage** [[string]]

- \* `stage` (string) real or character value that defines the stage for the reach. The specified STAGE is only applied if the reach uses the simple routing option. If STAGE is not specified for reaches that use the simple routing option, the specified stage is set to the top of the reach. If the Options block includes a TIMESERIESFILE entry (see the "Time-Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**inflow** [[string]]

- \* `inflow` (string) real or character value that defines the volumetric inflow rate for the streamflow routing reach. If the Options block includes a TIMESERIESFILE entry (see the "Time-Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, inflow rates are zero for each reach.

**rainfall** [[string]]

- \* **rainfall** (string) real or character value that defines the volumetric rate per unit area of water added by precipitation directly on the streamflow routing reach. If the Options block includes a **TIMESERIESFILE** entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, rainfall rates are zero for each reach.

#### **evaporation** [[string]]

- \* **evaporation** (string) real or character value that defines the volumetric rate per unit area of water subtracted by evaporation from the streamflow routing reach. A positive evaporation rate should be provided. If the Options block includes a **TIMESERIESFILE** entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. If the volumetric evaporation rate for a reach exceeds the sources of water to the reach (upstream and specified inflows, rainfall, and runoff but excluding groundwater leakage into the reach) the volumetric evaporation rate is limited to the sources of water to the reach. By default, evaporation rates are zero for each reach.

#### **runoff** [[string]]

- \* **runoff** (string) real or character value that defines the volumetric rate of diffuse overland runoff that enters the streamflow routing reach. If the Options block includes a **TIMESERIESFILE** entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. If the volumetric runoff rate for a reach is negative and exceeds inflows to the reach (upstream and specified inflows, and rainfall but excluding groundwater leakage into the reach) the volumetric runoff rate is limited to inflows to the reach and the volumetric evaporation rate for the reach is set to zero. By default, runoff rates are zero for each reach.

#### **diversionrecord** [[idv, divflow]]

- \* **idv** (integer) an integer value specifying which diversion of reach RNO that **DIVFLOW** is being specified for. Must be less or equal to **ndv** for the current reach (RNO). This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
- \* **divflow** (double) real or character value that defines the volumetric diversion (**DIVFLOW**) rate for the streamflow routing reach. If the Options block includes a **TIMESERIESFILE** entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

#### **upstream\_fraction** [[double]]

- \* **upstream\_fraction** (double) real value that defines the fraction of upstream flow (**USTRF**) from each upstream reach that is applied as upstream inflow to the reach. The sum of all **USTRF** values for all reaches connected to the same upstream reach must be equal to one.

#### **cross\_sectionrecord** [[tab6\_filename]]

- \* `tab6_filename` (string) character string that defines the path and file-name for the file containing cross-section table data for the reach. The `TAB6_FILENAME` file includes the number of entries in the file and the station elevation data in terms of the fractional width and the reach depth. Instructions for creating the `TAB6_FILENAME` input file are provided in `SFR Reach Cross-Section Table Input File` section.

**auxiliaryrecord** `[[auxname, auxval]]`

- \* `auxname` (string) name for the auxiliary variable to be assigned `AUXVAL`. `AUXNAME` must match one of the auxiliary variable names defined in the `OPTIONS` block. If `AUXNAME` does not match one of the auxiliary variable names defined in the `OPTIONS` block the data are ignored.
- \* `auxval` (double) value for the auxiliary variable. If the `Options` block includes a `TIMESERIESFILE` entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, `mfutllaktab` package must have a `mfgwflak` package `parent_file`.

`auxiliary = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

`budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

`budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

`connectiondata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

`crosssections = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>`

```

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_stage', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name print_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name stage_filerecord', 'type record
stage fileout stagefile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name stage', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name stagefile', 'type
string', 'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged
false', 'optional false'], ['block options', 'name budget_filerecord', 'type record
budget fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name budget', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name fileout',
'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name
package_convergence_filerecord', 'type record package_convergence fileout
package_convergence_filename', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name package_convergence', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name package_convergence_filename', 'type string', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block options', 'name
ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader urword',
'tagged true', 'optional true', 'construct_package ts', 'construct_data timeseries',
'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type
string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false',
'tagged false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block options', 'name
maximum_picard_iterations', 'type integer', 'reader urword', 'optional true'],
['block options', 'name maximum_iterations', 'type integer', 'reader urword',
'optional true'], ['block options', 'name maximum_depth_change', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name
unit_conversion', 'type double precision', 'reader urword', 'optional true'],
['block dimensions', 'name nreaches', 'type integer', 'reader urword', 'optional
false'], ['block packagedata', 'name packagedata', 'type recarray rno cellid rlen
rwid rgrd rtp rbth rhk man ncon ustrf ndv aux boundname', 'shape (maxbound)',
'reader urword'], ['block packagedata', 'name rno', 'type integer', 'shape', 'tagged
false', 'in_record true', 'reader urword', 'numeric_index true'], ['block
packagedata', 'name cellid', 'type integer', 'shape (ncelldim)', 'tagged false',
'in_record true', 'reader urword'], ['block packagedata', 'name rlen', 'type double
precision', 'shape', 'tagged false', 'in_record true', 'reader urword'], ['block
packagedata', 'name rwid', 'type double precision', 'shape', 'tagged false',

```

```
dfn_file_name = 'gwf-sfr.dfn'
diversions = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfsfr'
package_convergence_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
packagedata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
perioddata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
stage_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### **flopy.mf6.modflow.mfgwfsto module**

```
class ModflowGwfsto(model, loading_package=False, save_flows=None, storagecoefficient=None,
                    ss_confined_only=None, tvs_filerecord=None, iconvert=0, ss=1e-05, sy=0.15,
                    steady_state=None, transient=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopy.mf6.mfpackage.MFPackage](#)

ModflowGwfsto defines a sto package within a gwf6 model.

#### **Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that cell-by-cell flow terms will be written to the file specified with “BUDGET SAVE FILE” in Output Control.
- **storagecoefficient** (*boolean*) –
  - storagecoefficient (*boolean*) keyword to indicate that the SS array is read as storage coefficient rather than specific storage.
- **ss\_confined\_only** (*boolean*) –
  - ss\_confined\_only (*boolean*) keyword to indicate that specific storage is only calculated when a cell is under confined conditions (head greater than or equal to the top of the cell). This option is identical to the approach used to calculate storage changes under confined conditions in MODFLOW-2005.
- **tvs\_filerecord** (*[tvs\_filename]*) –
  - tvs\_filename (*string*) defines a time-varying storage (TVS) input file. Records in the TVS file can be used to change specific storage and specific yield properties at specified times or stress periods.
- **iconvert** (*[integer]*) –
  - iconvert (*integer*) is a flag for each cell that specifies whether or not a cell is convertible for the storage calculation. 0 indicates confined storage is used. >0 indicates



confined storage is used when head is above cell top and a mixed formulation of unconfined and confined storage is used when head is below cell top.

- **ss** (*[double]*) –
  - ss (double) is specific storage (or the storage coefficient if STORAGECOEFFICIENT is specified as an option). Specific storage values must be greater than or equal to 0. If the CSUB Package is included in the GWF model, specific storage must be zero for every cell.
- **sy** (*[double]*) –
  - sy (double) is specific yield. Specific yield values must be greater than or equal to 0. Specific yield does not have to be specified if there are no convertible cells (ICONVERT=0 in every cell).
- **steady\_state** (*boolean*) –
  - steady-state (boolean) keyword to indicate that stress period IPER is steady-state. Steady-state conditions will apply until the TRANSIENT keyword is specified in a subsequent BEGIN PERIOD block. If the CSUB Package is included in the GWF model, only the first and last stress period can be steady-state.
- **transient** (*boolean*) –
  - transient (boolean) keyword to indicate that stress period IPER is transient. Transient conditions will apply until the STEADY-STATE keyword is specified in a subsequent BEGIN PERIOD block.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mftllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name storagecoefficient', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
ss_confined_only', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name tvs_filerecord', 'type record tvs6 filein tvs_filename', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name tvs6',
'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
tvs_filename', 'type string', 'preserve_case true', 'in_record true', 'reader
urword', 'optional false', 'tagged false'], ['block griddata', 'name iconvert',
'type integer', 'shape (nodes)', 'valid', 'reader readarray', 'layered true',
'optional false', 'default_value 0'], ['block griddata', 'name ss', 'type double
precision', 'shape (nodes)', 'valid', 'reader readarray', 'layered true', 'optional
false', 'default_value 1.e-5'], ['block griddata', 'name sy', 'type double
precision', 'shape (nodes)', 'valid', 'reader readarray', 'layered true', 'optional
false', 'default_value 0.15'], ['block period', 'name iper', 'type integer',
'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader
urword', 'optional false'], ['block period', 'name steady-state', 'type keyword',
'shape', 'valid', 'reader urword', 'optional true'], ['block period', 'name
transient', 'type keyword', 'shape', 'valid', 'reader urword', 'optional true']]
dfn_file_name = 'gwf-sto.dfn'
```

```
iconvert = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
package_abbr = 'gwfsto'
ss = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
sy = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
tvs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flop.mf6.modflow.mfgwfufz module

```
class ModflowGwfufz(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    wc_filerecord=None, budget_filerecord=None, budgetcsv_filerecord=None,
                    package_convergence_filerecord=None, timeseries=None, observations=None,
                    mover=None, simulate_et=None, linear_gwet=None, square_gwet=None,
                    simulate_gwseep=None, unsat_etwc=None, unsat_etae=None, nuzfcells=None,
                    ntrilwaves=7, nwavesets=40, packagedata=None, perioddata=None, filename=None,
                    pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwfufz defines a uzf package within a gw6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of GWF cell area used by UZF cell.
- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of UZF cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of UZF information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –

- `print_flows` (boolean) keyword to indicate that the list of UZF flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **`save_flows`** (*boolean*) –
  - `save_flows` (boolean) keyword to indicate that UZF flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **`wc_filerecord`** (*[wcfile]*) –
  - `wcfile` (string) name of the binary output file to write water content information.
- **`budget_filerecord`** (*[budgetfile]*) –
  - `budgetfile` (string) name of the binary output file to write budget information.
- **`budgetcsv_filerecord`** (*[budgetcsvfile]*) –
  - `budgetcsvfile` (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **`package_convergence_filerecord`** (*[package\_convergence\_filename]*) –
  - `package_convergence_filename` (string) name of the comma spaced values output file to write package convergence information.
- **`timeseries`** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **`observations`** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **`mover`** (*boolean*) –
  - `mover` (boolean) keyword to indicate that this instance of the UZF Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **`simulate_et`** (*boolean*) –
  - `simulate_et` (boolean) keyword specifying that ET in the unsaturated (UZF) and saturated zones (GWF) will be simulated. ET can be simulated in the UZF cell and not the GWF cell by omitting keywords `LINEAR_GWET` and `SQUARE_GWET`.
- **`linear_gwet`** (*boolean*) –
  - `linear_gwet` (boolean) keyword specifying that groundwater ET will be simulated using the original ET formulation of MODFLOW-2005.
- **`square_gwet`** (*boolean*) –

- `square_gwet` (boolean) keyword specifying that groundwater ET will be simulated by assuming a constant ET rate for groundwater levels between land surface (TOP) and land surface minus the ET extinction depth (TOP-EXTDP). Groundwater ET is smoothly reduced from the PET rate to zero over a nominal interval at TOP-EXTDP.
- **`simulate_gwseep` (boolean) –**
  - `simulate_gwseep` (boolean) keyword specifying that groundwater discharge (GWSEEP) to land surface will be simulated. Groundwater discharge is nonzero when groundwater head is greater than land surface.
- **`unsat_etwc` (boolean) –**
  - `unsat_etwc` (boolean) keyword specifying that ET in the unsaturated zone will be simulated as a function of the specified PET rate while the water content (THETA) is greater than the ET extinction water content (EXTWC).
- **`unsat_etae` (boolean) –**
  - `unsat_etae` (boolean) keyword specifying that ET in the unsaturated zone will be simulated using a capillary pressure based formulation. Capillary pressure is calculated using the Brooks-Corey retention function.
- **`nuzfcells` (integer) –**
  - `nuzfcells` (integer) is the number of UZF cells. More than one UZF cell can be assigned to a GWF cell; however, only one GWF cell can be assigned to a single UZF cell. If more than one UZF cell is assigned to a GWF cell, then an auxiliary variable should be used to reduce the surface area of the UZF cell with the AUX-MULTNAME option.
- **`ntrailwaves` (integer) –**
  - `ntrailwaves` (integer) is the number of trailing waves. A recommended value of 7 can be used for NTRAILWAVES. This value can be increased to lower mass balance error in the unsaturated zone.
- **`nwavesets` (integer) –**
  - `nwavesets` (integer) is the number of wave sets. A recommended value of 40 can be used for NWAVESETS. This value can be increased if more waves are required to resolve variations in water content within the unsaturated zone.
- **`packagedata` ([`iuzno`, `cellid`, `landflag`, `invertcon`, `surfdep`, `vks`, `thtr`, `thts`), –**

**`thti`, `eps`, `boundname`]**

  - `iuzno` (integer) integer value that defines the UZF cell number associated with the specified PACKAGEDATA data on the line. IUZNO must be greater than zero and less than or equal to NUZFCELLS. UZF information must be specified for every UZF cell or the program will terminate with an error. The program will also terminate with an error if information for a UZF cell is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `cellid` ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured

discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- **landflag** (integer) integer value set to one for land surface cells indicating that boundary conditions can be applied and data can be specified in the PERIOD block. A value of 0 specifies a non-land surface cell.
  - **ivertcon** (integer) integer value set to specify underlying UZF cell that receives water flowing to bottom of cell. If unsaturated zone flow reaches the water table before the cell bottom, then water is added to the GWF cell instead of flowing to the underlying UZF cell. A value of 0 indicates the UZF cell is not connected to an underlying UZF cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - **surfdep** (double) is the surface depression depth of the UZF cell.
  - **vks** (double) is the saturated vertical hydraulic conductivity of the UZF cell. This value is used with the Brooks-Corey function and the simulated water content to calculate the partially saturated hydraulic conductivity.
  - **thtr** (double) is the residual (irreducible) water content of the UZF cell. This residual water is not available to plants and will not drain into underlying aquifer cells.
  - **thts** (double) is the saturated water content of the UZF cell. The values for saturated and residual water content should be set in a manner that is consistent with the specific yield value specified in the Storage Package. The saturated water content must be greater than the residual content.
  - **thti** (double) is the initial water content of the UZF cell. The value must be greater than or equal to the residual water content and less than or equal to the saturated water content.
  - **eps** (double) is the exponent used in the Brooks-Corey function. The Brooks-Corey function is used by UZF to calculate hydraulic conductivity under partially saturated conditions as a function of water content and the user-specified saturated hydraulic conductivity.
  - **boundname** (string) name of the UZF cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **perioddata** (*[iuzno, finf, pet, extdp, extwc, ha, hroot, rootact, aux]*) –
    - **iuzno** (integer) integer value that defines the UZF cell number associated with the specified PERIOD data on the line. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
    - **finf** (string) real or character value that defines the applied infiltration rate of the UZF cell ( $LT^{-1}$ ). If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- pet (string) real or character value that defines the potential evapotranspiration rate of the UZF cell and specified GWF cell. Evapotranspiration is first removed from the unsaturated zone and any remaining potential evapotranspiration is applied to the saturated zone. If IVERTCON is greater than zero then residual potential evapotranspiration not satisfied in the UZF cell is applied to the underlying UZF and GWF cells. PET is always specified, but is only used if SIMULATE\_ET is specified in the OPTIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- extdp (string) real or character value that defines the evapotranspiration extinction depth of the UZF cell. If IVERTCON is greater than zero and EXTDP extends below the GWF cell bottom then remaining potential evapotranspiration is applied to the underlying UZF and GWF cells. EXTDP is always specified, but is only used if SIMULATE\_ET is specified in the OPTIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- extwc (string) real or character value that defines the evapotranspiration extinction water content of the UZF cell. EXTWC is always specified, but is only used if SIMULATE\_ET and UNSAT\_ETWC are specified in the OPTIONS block. The evapotranspiration rate from the unsaturated zone will be set to zero when the calculated water content is at or less than this value. The value for EXTWC cannot be less than the residual water content, and if it is specified as being less than the residual water content it is set to the residual water content. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- ha (string) real or character value that defines the air entry potential (head) of the UZF cell. HA is always specified, but is only used if SIMULATE\_ET and UNSAT\_ETAE are specified in the OPTIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- hroot (string) real or character value that defines the root potential (head) of the UZF cell. HROOT is always specified, but is only used if SIMULATE\_ET and UNSAT\_ETAE are specified in the OPTIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- rootact (string) real or character value that defines the root activity function of the UZF cell. ROOTACT is the length of roots in a given volume of soil divided by that volume. Values range from 0 to about  $3\text{ cm}^{-2}$ , depending on the plant community and its stage of development. ROOTACT is always specified, but is only used if SIMULATE\_ET and UNSAT\_ETAE are specified in the OPTIONS block. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- aux (double) represents the values of the auxiliary variables for each UZF. The values of auxiliary variables must be present for each UZF. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE

entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

**budget\_filerecord** = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

**budgetcsv\_filerecord** = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block
options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional
true'], ['block options', 'name print_input', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name save_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name wc_filerecord', 'type
record water_content fileout wcfile', 'shape', 'reader urword', 'tagged true',
'optional true'], ['block options', 'name water_content', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name wcfile', 'type string', 'preserve_case true', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'preserve_case true', 'type string', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name package_convergence_filerecord', 'type
record package_convergence fileout package_convergence_filename', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name
package_convergence', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name
package_convergence_filename', 'type string', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name ts_filerecord',
'type record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true',
'optional true', 'construct_package ts', 'construct_data timeseries',
'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type
string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false',
'tagged false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block options', 'name
simulate_et', 'type keyword', 'tagged true', 'reader urword', 'optional true'],
['block options', 'name linear_gwet', 'type keyword', 'tagged true', 'reader
urword', 'optional true'], ['block options', 'name square_gwet', 'type keyword',
'tagged true', 'reader urword', 'optional true'], ['block options', 'name
simulate_gwseep', 'type keyword', 'tagged true', 'reader urword', 'optional true'],
['block options', 'name unsat_etwc', 'type keyword', 'tagged true', 'reader urword',
'optional true'], ['block options', 'name unsat_etae', 'type keyword', 'tagged
true', 'reader urword', 'optional true'], ['block dimensions', 'name nuzfcells',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name
ntrailwaves', 'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name nwavesets', 'type integer', 'reader urword', 'optional
false', 'default_value 40'], ['block packagedata', 'name packagedata', 'type
recarray iuzno cellid landflag invertcon surfdep vks thtr thts thti eps boundname',

```



```

dfn_file_name = 'gwf-uzf.dfn'
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwfuzf'
package_convergence_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator
object>
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
perioddata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
wc_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```

### flopY.mf6.modflow.mfgwfwel module

```

class ModflowGwfwel(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    auto_flow_reduce=None, afrcsv_filerecord=None, timeseries=None, observations=None,
                    mover=None, maxbound=None, stress_period_data=None, filename=None, pname=None,
                    parent_file=None)

```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwfwel defines a wel package within a gw6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of well flow rate.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of well cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of well information will be written to the listing file immediately after it is read.

- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of well flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that well flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **auto\_flow\_reduce** (*double*) –
  - auto\_flow\_reduce (double) keyword and real value that defines the fraction of the cell thickness used as an interval for smoothly adjusting negative pumping rates to 0 in cells with head values less than or equal to the bottom of the cell. Negative pumping rates are adjusted to 0 or a smaller negative value when the head in the cell is equal to or less than the calculated interval above the cell bottom. AUTO\_FLOW\_REDUCE is set to 0.1 if the specified value is less than or equal to zero. By default, negative pumping rates are not reduced during a simulation.
- **afrcsv\_filerecord** (*[afrcsvfile]*) –
  - afrcsvfile (string) name of the comma-separated value (CSV) output file to write information about well extraction rates that have been reduced by the program. Entries are only written if the extraction rates are reduced.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (*boolean*) –
  - mover (boolean) keyword to indicate that this instance of the Well Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of wells cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, q, aux, boundname]*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an

index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.

- `q` (double) is the volumetric well rate. A positive value indicates recharge (injection) and a negative value indicates discharge (extraction). If the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- `aux` (double) represents the values of the auxiliary variables for each well. The values of auxiliary variables must be present for each well. The values must be specified in the order of the auxiliary variables specified in the `OPTIONS` block. If the package supports time series and the Options block includes a `TIMESERIESFILE` entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
- `boundname` (string) name of the well cell. `BOUNDNAME` is an ASCII character variable that can contain as many as 40 characters. If `BOUNDNAME` contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
afrcsv_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
auxiliary = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header', 'multi-package'], ['block options', 'name auxiliary', 'type  
string', 'shape (naux)', 'reader urword', 'optional true'], ['block options', 'name  
auxmultname', 'type string', 'shape', 'reader urword', 'optional true'], ['block  
options', 'name boundnames', 'type keyword', 'shape', 'reader urword', 'optional  
true'], ['block options', 'name print_input', 'type keyword', 'reader urword',  
'optional true'], ['block options', 'name print_flows', 'type keyword', 'reader  
urword', 'optional true'], ['block options', 'name save_flows', 'type keyword',  
'reader urword', 'optional true'], ['block options', 'name auto_flow_reduce', 'type  
double precision', 'reader urword', 'optional true'], ['block options', 'name  
afrcsv_filerecord', 'type record auto_flow_reduce_csv fileout afrcsvfile', 'shape',  
'reader urword', 'tagged true', 'optional true'], ['block options', 'name  
auto_flow_reduce_csv', 'type keyword', 'shape', 'in_record true', 'reader urword',  
'tagged true', 'optional false'], ['block options', 'name fileout', 'type keyword',  
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],  
['block options', 'name afrcsvfile', 'type string', 'preserve_case true', 'shape',  
'in_record true', 'reader urword', 'tagged false', 'optional false'], ['block  
options', 'name ts_filerecord', 'type record ts6 filein ts6_filename', 'shape',  
'reader urword', 'tagged true', 'optional true', 'construct_package ts',  
'construct_data timeseries', 'parameter_name timeseries'], ['block options', 'name  
ts6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',  
'optional false'], ['block options', 'name filein', 'type keyword', 'shape',  
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block  
options', 'name ts6_filename', 'type string', 'preserve_case true', 'in_record  
true', 'reader urword', 'optional false', 'tagged false'], ['block options', 'name  
obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader urword',  
'tagged true', 'optional true', 'construct_package obs', 'construct_data  
continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type  
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional  
false'], ['block options', 'name obs6_filename', 'type string', 'preserve_case  
true', 'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block  
options', 'name mover', 'type keyword', 'tagged true', 'reader urword', 'optional  
true'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword',  
'optional false'], ['block period', 'name iper', 'type integer', 'block_variable  
True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword',  
'optional false'], ['block period', 'name stress_period_data', 'type recarray cellid  
q aux boundname', 'shape (maxbound)', 'reader urword'], ['block period', 'name  
cellid', 'type integer', 'shape (ncellldim)', 'tagged false', 'in_record true',  
'reader urword'], ['block period', 'name q', 'type double precision', 'shape',  
'tagged false', 'in_record true', 'reader urword', 'time_series true'], ['block  
period', 'name aux', 'type double precision', 'in_record true', 'tagged false',  
'shape (naux)', 'reader urword', 'optional true', 'time_series true'], ['block  
period', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record true',  
'reader urword', 'optional true']]
```

```
dfn_file_name = 'gwf-wel.dfn'
```

```
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'gwfwel'
```

```
stress_period_data = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
ts_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## MODFLOW 6 Groundwater Transport Model Packages

MODFLOW 6 groundwater transport models support a number of required and optional packages. Once a MODFLOW 6 groundwater transport model object (`mfgwt.ModflowGwt`) has been constructed various packages associated with the groundwater transport model can be constructed.

Contents:

### `flopY.mf6.modflow.mfgwtadv` module

**class** `ModflowGwtadv`(*model*, *loading\_package=False*, *scheme=None*, *filename=None*, *pname=None*, *parent\_file=None*)

Bases: `flopY.mf6.mfpackage.MFPackage`

`ModflowGwtadv` defines an adv package within a gwt6 model.

#### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **scheme** (*string*) –
  - *scheme* (*string*) scheme used to solve the advection term. Can be upstream, central, or TVD. If not specified, upstream weighting is the default weighting scheme.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (`MFPackage`) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block options', 'name scheme', 'type string', 'valid central
upstream tvd', 'reader urword', 'optional true']]
```

```
dfn_file_name = 'gwt-adv.dfn'
```

```
package_abbr = 'gwtadv'
```

### `flopY.mf6.modflow.mfgwtapi` module

**class** `ModflowGwtapi`(*model*, *loading\_package=False*, *boundnames=None*, *print\_input=None*, *print\_flows=None*, *save\_flows=None*, *observations=None*, *mover=None*, *maxbound=None*, *filename=None*, *pname=None*, *parent\_file=None*)

Bases: `flopY.mf6.mfpackage.MFPackage`

`ModflowGwtapi` defines an api package within a gwt6 model.

#### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **boundnames** (*boolean*) –

- boundnames (boolean) keyword to indicate that boundary names may be provided with the list of api boundary cells.
- **print\_input** (boolean) –
  - print\_input (boolean) keyword to indicate that the list of api boundary information will be written to the listing file immediately after it is read.
- **print\_flows** (boolean) –
  - print\_flows (boolean) keyword to indicate that the list of api boundary flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (boolean) –
  - save\_flows (boolean) keyword to indicate that api boundary flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **observations** ({varname:data} or continuous data) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **mover** (boolean) –
  - mover (boolean) keyword to indicate that this instance of the api boundary Package can be used with the Water Mover (MVR) Package. When the MOVER option is specified, additional memory is allocated within the package to store the available, provided, and received water.
- **maxbound** (integer) –
  - maxbound (integer) integer value specifying the maximum number of api boundary cells that will be specified for use during any stress period.
- **filename** (String) – File name for this package.
- **pname** (String) – Package name for this package.
- **parent\_file** (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block options', 'name boundnames', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name print_input', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name print_flows',
'type keyword', 'reader urword', 'optional true'], ['block options', 'name
save_flows', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape', 'reader
urword', 'tagged true', 'optional true', 'construct_package obs', 'construct_data
continuous', 'parameter_name observations'], ['block options', 'name obs6', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name mover', 'type
keyword', 'tagged true', 'reader urword', 'optional true'], ['block dimensions',
'name maxbound', 'type integer', 'reader urword', 'optional false']]

dfn_file_name = 'gwt-api.dfn'

obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwtapi'
```

### flopY.mf6.modflow.mfmgwtcnc module

```
class ModflowGwtcnc(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, maxbound=None, stress_period_data=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwtcnc defines a cnc package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (string) name of auxiliary variable to be used as multiplier of concentration value.
- **boundnames** (*boolean*) –

- boundnames (boolean) keyword to indicate that boundary names may be provided with the list of constant concentration cells.
- **print\_input** (boolean) –
  - print\_input (boolean) keyword to indicate that the list of constant concentration information will be written to the listing file immediately after it is read.
- **print\_flows** (boolean) –
  - print\_flows (boolean) keyword to indicate that the list of constant concentration flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (boolean) –
  - save\_flows (boolean) keyword to indicate that constant concentration flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** ({varname:data} or timeseries data) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** ({varname:data} or continuous data) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **maxbound** (integer) –
  - maxbound (integer) integer value specifying the maximum number of constant concentrations cells that will be specified for use during any stress period.
- **stress\_period\_data** ([cellid, conc, aux, boundname]) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - conc (double) is the constant concentration value. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (double) represents the values of the auxiliary variables for each constant concentration. The values of auxiliary variables must be present for each constant concentration. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section),



values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **boundname** (string) name of the constant concentration cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (String) – File name for this package.
- **pname** (String) – Package name for this package.
- **parent\_file** (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header'], ['block options', 'name auxiliary', 'type string', 'shape
(naux)', 'reader urword', 'optional true'], ['block options', 'name auxmultname',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword',
'optional false'], ['block period', 'name iper', 'type integer', 'block_variable
True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword',
'optional false'], ['block period', 'name stress_period_data', 'type recarray cellid
conc aux boundname', 'shape (maxbound)', 'reader urword'], ['block period', 'name
cellid', 'type integer', 'shape (ncelldim)', 'tagged false', 'in_record true',
'reader urword'], ['block period', 'name conc', 'type double precision', 'shape',
'tagged false', 'in_record true', 'reader urword', 'time_series true'], ['block
period', 'name aux', 'type double precision', 'in_record true', 'tagged false',
'shape (naux)', 'reader urword', 'optional true', 'time_series true'], ['block
period', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record true',
'reader urword', 'optional true']]
```

**dfn\_file\_name** = 'gwt-cnc.dfn'

**obs\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**package\_abbr** = 'gwtcnc'

**stress\_period\_data** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flopY.mf6.modflow.mf6gwtdis module

```
class ModflowGwtdis(model, loading_package=False, length_units=None, nogrb=None, xorigin=None,
                    yorigin=None, angrot=None, nlay=1, nrow=2, ncol=2, delr=1.0, delc=1.0, top=1.0,
                    botm=0.0, idomain=None, filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwtdis defines a dis package within a gwt6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (*string*) –
  - length\_units (*string*) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (*boolean*) –
  - nogrb (*boolean*) keyword to deactivate writing of the binary grid file.
- **xorigin** (*double*) –
  - xorigin (*double*) x-position of the lower-left corner of the model grid. A default value of zero is assigned if not specified. The value for XORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **yorigin** (*double*) –
  - yorigin (*double*) y-position of the lower-left corner of the model grid. If not specified, then a default value equal to zero is used. The value for YORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **angrot** (*double*) –
  - angrot (*double*) counter-clockwise rotation angle (in degrees) of the lower-left corner of the model grid. If not specified, then a default value of 0.0 is assigned. The value for ANGROT does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **nlay** (*integer*) –
  - nlay (*integer*) is the number of layers in the model grid.
- **nrow** (*integer*) –
  - nrow (*integer*) is the number of rows in the model grid.
- **ncol** (*integer*) –
  - ncol (*integer*) is the number of columns in the model grid.
- **delr** (*[double]*) –
  - delr (*double*) is the column spacing in the row direction.

- **delc** (*[double]*) –
  - delc (double) is the row spacing in the column direction.
- **top** (*[double]*) –
  - top (double) is the top elevation for each cell in the top model layer.
- **botm** (*[double]*) –
  - botm (double) is the bottom elevation for each cell.
- **idomain** (*[integer]*) –
  - idomain (integer) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution. If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1, the cell exists in the simulation. If the IDOMAIN value for a cell is -1, the cell does not exist in the simulation. Furthermore, the first existing cell above will be connected to the first existing cell below. This type of cell is referred to as a “vertical pass through” cell.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
botm = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
delc = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
delr = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
dimensions', 'name nlay', 'type integer', 'reader urword', 'optional false',
'default_value 1'], ['block dimensions', 'name nrow', 'type integer', 'reader
urword', 'optional false', 'default_value 2'], ['block dimensions', 'name ncol',
'type integer', 'reader urword', 'optional false', 'default_value 2'], ['block
griddata', 'name delr', 'type double precision', 'shape (ncol)', 'reader readarray',
'default_value 1.0'], ['block griddata', 'name delc', 'type double precision',
'shape (nrow)', 'reader readarray', 'default_value 1.0'], ['block griddata', 'name
top', 'type double precision', 'shape (ncol, nrow)', 'reader readarray',
'default_value 1.0'], ['block griddata', 'name botm', 'type double precision',
'shape (ncol, nrow, nlay)', 'reader readarray', 'layered true', 'default_value 0.'],
['block griddata', 'name idomain', 'type integer', 'shape (ncol, nrow, nlay)',
'reader readarray', 'layered true', 'optional true']]
```

```
dfn_file_name = 'gwt-dis.dfn'
```

```
idomain = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
package_abbr = 'gwtdis'
```

```
top = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

## flopY.mf6.modflow.mf6gwtdisu module

```
class ModflowGwtdisu(model, loading_package=False, length_units=None, nogrb=None, xorigin=None,
    yorigin=None, angrot=None, vertical_offset_tolerance=0.0, nodes=None, nja=None,
    nvert=None, top=None, bot=None, area=None, idomain=None, iac=None, ja=None,
    ihc=None, cl12=None, hwva=None, angldegx=None, vertices=None, cell2d=None,
    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwtdisu defines a disu package within a gwt6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (*string*) –
  - length\_units (*string*) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (*boolean*) –
  - nogrb (*boolean*) keyword to deactivate writing of the binary grid file.
- **xorigin** (*double*) –
  - xorigin (*double*) x-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. A default value of zero is assigned if not specified. The value for XORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **yorigin** (*double*) –
  - yorigin (*double*) y-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. If not specified, then a default value equal to zero is used. The value for YORIGIN does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **angrot** (*double*) –
  - angrot (*double*) counter-clockwise rotation angle (in degrees) of the model grid coordinate system relative to a real-world coordinate system. If not specified, then a default value of 0.0 is assigned. The value for ANGROT does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **vertical\_offset\_tolerance** (*double*) –
  - vertical\_offset\_tolerance (*double*) checks are performed to ensure that the top of a cell is not higher than the bottom of an overlying cell. This option can be used to specify the tolerance that is used for checking. If top of a cell is above the bottom of an overlying cell by a value less than this tolerance, then the program will not

terminate with an error. The default value is zero. This option should generally not be used.

- **nodes** (*integer*) –
  - nodes (*integer*) is the number of cells in the model grid.
- **nja** (*integer*) –
  - nj (*integer*) is the sum of the number of connections and NODES. When calculating the total number of connections, the connection between cell *n* and cell *m* is considered to be different from the connection between cell *m* and cell *n*. Thus, NJA is equal to the total number of connections, including *n* to *m* and *m* to *n*, and the total number of cells.
- **nvert** (*integer*) –
  - nvert (*integer*) is the total number of (*x*, *y*) vertex pairs used to define the plan-view shape of each cell in the model grid. If NVERT is not specified or is specified as zero, then the VERTICES and CELL2D blocks below are not read. NVERT and the accompanying VERTICES and CELL2D blocks should be specified for most simulations. If the XT3D or SAVE\_SPECIFIC\_DISCHARGE options are specified in the NPF Package, then this information is required.
- **top** (*[double]*) –
  - top (*double*) is the top elevation for each cell in the model grid.
- **bot** (*[double]*) –
  - bot (*double*) is the bottom elevation for each cell.
- **area** (*[double]*) –
  - area (*double*) is the cell surface area (in plan view).
- **idomain** (*[integer]*) –
  - idomain (*integer*) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution. If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1 or greater, the cell exists in the simulation. IDOMAIN values of -1 cannot be specified for the DISU Package.
- **iac** (*[integer]*) –
  - iac (*integer*) is the number of connections (plus 1) for each cell. The sum of all the entries in IAC must be equal to NJA.
- **ja** (*[integer]*) –
  - ja (*integer*) is a list of cell number (*n*) followed by its connecting cell numbers (*m*) for each of the *m* cells connected to cell *n*. The number of values to provide for cell *n* is IAC(*n*). This list is sequentially provided for the first to the last cell. The first value in the list must be cell *n* itself, and the remaining cells must be listed in an increasing order (sorted from lowest number to highest). Note that the cell and its connections are only supplied for the GWT cells and their connections to the other GWT cells. Also note that the JA list input may be divided such that every node and its connectivity list can be on a separate line for ease in readability of the file. To further ease readability of the file, the node number of the cell whose connectivity is subsequently listed, may be expressed as a negative number, the sign of which is

subsequently converted to positive by the code. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- **ihc** (*[integer]*) –
  - ihc (integer) is an index array indicating the direction between node *n* and all of its *m* connections. If IHC = 0 then cell *n* and cell *m* are connected in the vertical direction. Cell *n* overlies cell *m* if the cell number for *n* is less than *m*; cell *m* overlies cell *n* if the cell number for *m* is less than *n*. If IHC = 1 then cell *n* and cell *m* are connected in the horizontal direction. If IHC = 2 then cell *n* and cell *m* are connected in the horizontal direction, and the connection is vertically staggered. A vertically staggered connection is one in which a cell is horizontally connected to more than one cell in a horizontal connection.
- **cl12** (*[double]*) –
  - cl12 (double) is the array containing connection lengths between the center of cell *n* and the shared face with each adjacent *m* cell.
- **hwva** (*[double]*) –
  - hwva (double) is a symmetric array of size NJA. For horizontal connections, entries in HWVA are the horizontal width perpendicular to flow. For vertical connections, entries in HWVA are the vertical area for flow. Thus, values in the HWVA array contain dimensions of both length and area. Entries in the HWVA array have a one-to-one correspondence with the connections specified in the JA array. Likewise, there is a one-to-one correspondence between entries in the HWVA array and entries in the IHC array, which specifies the connection type (horizontal or vertical). Entries in the HWVA array must be symmetric; the program will terminate with an error if the value for HWVA for an *n* to *m* connection does not equal the value for HWVA for the corresponding *n* to *m* connection.
- **angldegx** (*[double]*) –
  - angldegx (double) is the angle (in degrees) between the horizontal x-axis and the outward normal to the face between a cell and its connecting cells. The angle varies between zero and 360.0 degrees, where zero degrees points in the positive x-axis direction, and 90 degrees points in the positive y-axis direction. ANGLDEGX is only needed if horizontal anisotropy is specified in the NPF Package, if the XT3D option is used in the NPF Package, or if the SAVE\_SPECIFIC\_DISCHARGE option is specified in the NPF Package. ANGLDEGX does not need to be specified if these conditions are not met. ANGLDEGX is of size NJA; values specified for vertical connections and for the diagonal position are not used. Note that ANGLDEGX is read in degrees, which is different from MODFLOW-USG, which reads a similar variable (ANGLEX) in radians.
- **vertices** (*[iv, xv, yv]*) –
  - iv (integer) is the vertex number. Records in the VERTICES block must be listed in consecutive order from 1 to NVERT. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - xv (double) is the x-coordinate for the vertex.
  - yv (double) is the y-coordinate for the vertex.

- **cell12d**(*[icell12d, xc, yc, nvert, icvert]*) –
  - *icell12d* (integer) is the cell12d number. Records in the CELL2D block must be listed in consecutive order from 1 to NODES. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - *xc* (double) is the x-coordinate for the cell center.
  - *yc* (double) is the y-coordinate for the cell center.
  - *nvert* (integer) is the number of vertices required to define the cell. There may be a different number of vertices for each cell.
  - *icvert* (integer) is an array of integer values containing vertex numbers (in the VERTICES block) used to define the cell. Vertices must be listed in clockwise order. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**angldegx** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

**area** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

**bot** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

**cell12d** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

**cl12** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```
dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
options', 'name vertical_offset_tolerance', 'type double precision', 'reader
urword', 'optional true', 'default_value 0.0'], ['block dimensions', 'name nodes',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name nja',
'type integer', 'reader urword', 'optional false'], ['block dimensions', 'name
nvert', 'type integer', 'reader urword', 'optional true'], ['block griddata', 'name
top', 'type double precision', 'shape (nodes)', 'reader readarray'], ['block
griddata', 'name bot', 'type double precision', 'shape (nodes)', 'reader
readarray'], ['block griddata', 'name area', 'type double precision', 'shape
(nodes)', 'reader readarray'], ['block griddata', 'name idomain', 'type integer',
'shape (nodes)', 'reader readarray', 'layered false', 'optional true'], ['block
connectiondata', 'name iac', 'type integer', 'shape (nodes)', 'reader readarray'],
['block connectiondata', 'name ja', 'type integer', 'shape (nja)', 'reader
readarray', 'numeric_index true', 'jagged_array iac'], ['block connectiondata',
'name ihc', 'type integer', 'shape (nja)', 'reader readarray', 'jagged_array iac'],
['block connectiondata', 'name cl12', 'type double precision', 'shape (nja)',
'reader readarray', 'jagged_array iac'], ['block connectiondata', 'name hwva', 'type
double precision', 'shape (nja)', 'reader readarray', 'jagged_array iac'], ['block
connectiondata', 'name angldegx', 'type double precision', 'optional true', 'shape
(nja)', 'reader readarray', 'jagged_array iac'], ['block vertices', 'name vertices',
'type recarray iv xv yv', 'reader urword', 'optional false'], ['block vertices',
'name iv', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false', 'numeric_index true'], ['block vertices', 'name xv', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block vertices', 'name yv', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block cell2d', 'name cell2d', 'type
recarray icell2d xc yc nvert icvert', 'reader urword', 'optional false'], ['block
cell2d', 'name icell2d', 'type integer', 'in_record true', 'tagged false', 'reader
urword', 'optional false', 'numeric_index true'], ['block cell2d', 'name xc', 'type
double precision', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block cell2d', 'name yc', 'type double precision', 'in_record true',
'tagged false', 'reader urword', 'optional false'], ['block cell2d', 'name nvert',
'type integer', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block cell2d', 'name icvert', 'type integer', 'shape (nvert)',
'in_record true', 'tagged false', 'reader urword', 'optional false', 'numeric_index
true']]
```

```
dfn_file_name = 'gwt-disu.dfn'
```

```
hwva = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
iac = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
idomain = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
ihc = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
ja = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
package_abbr = 'gwtdisu'
```

```
top = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```



`vertices = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>`

## `flopys.mf6.modflow.mf6gwtdisv module`

**class** `ModflowGwtdisv`(*model, loading\_package=False, length\_units=None, nogrb=None, xorigin=None, yorigin=None, angrot=None, nlay=None, ncpl=None, nvert=None, top=None, botm=None, idomain=None, vertices=None, cell2d=None, filename=None, pname=None, parent\_file=None*)

Bases: `flopys.mf6.mfpackage.MFPackage`

`ModflowGwtdisv` defines a `disv` package within a `gwtdisv` model.

### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **length\_units** (`string`) –
  - `length_units` (`string`) is the length units used for this model. Values can be “FEET”, “METERS”, or “CENTIMETERS”. If not specified, the default is “UNKNOWN”.
- **nogrb** (`boolean`) –
  - `nogrb` (`boolean`) keyword to deactivate writing of the binary grid file.
- **xorigin** (`double`) –
  - `xorigin` (`double`) x-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. A default value of zero is assigned if not specified. The value for `XORIGIN` does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **yorigin** (`double`) –
  - `yorigin` (`double`) y-position of the origin used for model grid vertices. This value should be provided in a real-world coordinate system. If not specified, then a default value equal to zero is used. The value for `YORIGIN` does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **angrot** (`double`) –
  - `angrot` (`double`) counter-clockwise rotation angle (in degrees) of the model grid coordinate system relative to a real-world coordinate system. If not specified, then a default value of 0.0 is assigned. The value for `ANGROT` does not affect the model simulation, but it is written to the binary grid file so that postprocessors can locate the grid in space.
- **nlay** (`integer`) –
  - `nlay` (`integer`) is the number of layers in the model grid.
- **ncpl** (`integer`) –
  - `ncpl` (`integer`) is the number of cells per layer. This is a constant value for the grid and it applies to all layers.
- **nvert** (`integer`) –

- `nvert` (integer) is the total number of (x, y) vertex pairs used to characterize the horizontal configuration of the model grid.
- **`top`** (*[double]*) –
  - `top` (double) is the top elevation for each cell in the top model layer.
- **`botm`** (*[double]*) –
  - `botm` (double) is the bottom elevation for each cell.
- **`idomain`** (*[integer]*) –
  - `idomain` (integer) is an optional array that characterizes the existence status of a cell. If the IDOMAIN array is not specified, then all model cells exist within the solution. If the IDOMAIN value for a cell is 0, the cell does not exist in the simulation. Input and output values will be read and written for the cell, but internal to the program, the cell is excluded from the solution. If the IDOMAIN value for a cell is 1, the cell exists in the simulation. If the IDOMAIN value for a cell is -1, the cell does not exist in the simulation. Furthermore, the first existing cell above will be connected to the first existing cell below. This type of cell is referred to as a “vertical pass through” cell.
- **`vertices`** (*[iv, xv, yv]*) –
  - `iv` (integer) is the vertex number. Records in the VERTICES block must be listed in consecutive order from 1 to NVERT. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `xv` (double) is the x-coordinate for the vertex.
  - `yv` (double) is the y-coordinate for the vertex.
- **`cell2d`** (*[icell2d, xc, yc, nvert, icvert]*) –
  - `icell2d` (integer) is the CELL2D number. Records in the CELL2D block must be listed in consecutive order from the first to the last. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `xc` (double) is the x-coordinate for the cell center.
  - `yc` (double) is the y-coordinate for the cell center.
  - `nvert` (integer) is the number of vertices required to define the cell. There may be a different number of vertices for each cell.
  - `icvert` (integer) is an array of integer values containing vertex numbers (in the VERTICES block) used to define the cell. Vertices must be listed in clockwise order. Cells that are connected must share vertices. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.

- **parent\_file** (**MFPackage**) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
botm = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
cell2d = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name length_units', 'type string', 'reader
urword', 'optional true'], ['block options', 'name nogrb', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name xorigin', 'type double
precision', 'reader urword', 'optional true'], ['block options', 'name yorigin',
'type double precision', 'reader urword', 'optional true'], ['block options', 'name
angrot', 'type double precision', 'reader urword', 'optional true'], ['block
dimensions', 'name nlay', 'type integer', 'reader urword', 'optional false'],
['block dimensions', 'name ncpl', 'type integer', 'reader urword', 'optional
false'], ['block dimensions', 'name nvert', 'type integer', 'reader urword',
'optional false'], ['block griddata', 'name top', 'type double precision', 'shape
(ncpl)', 'reader readarray'], ['block griddata', 'name botm', 'type double
precision', 'shape (nlay, ncpl)', 'reader readarray', 'layered true'], ['block
griddata', 'name idomain', 'type integer', 'shape (nlay, ncpl)', 'reader readarray',
'layered true', 'optional true'], ['block vertices', 'name vertices', 'type recarray
iv xv yv', 'reader urword', 'optional false'], ['block vertices', 'name iv', 'type
integer', 'in_record true', 'tagged false', 'reader urword', 'optional false',
'numeric_index true'], ['block vertices', 'name xv', 'type double precision',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
vertices', 'name yv', 'type double precision', 'in_record true', 'tagged false',
'reader urword', 'optional false'], ['block cell2d', 'name cell2d', 'type recarray
icell2d xc yc nvert icvert', 'reader urword', 'optional false'], ['block cell2d',
'name icell2d', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false', 'numeric_index true'], ['block cell2d', 'name xc', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block cell2d', 'name yc', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block cell2d', 'name nvert', 'type
integer', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block cell2d', 'name icvert', 'type integer', 'shape (nvert)', 'in_record true',
'tagged false', 'reader urword', 'optional false', 'numeric_index true']]
```

```
dfn_file_name = 'gwt-disv.dfn'
```

```
idomain = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
package_abbr = 'gwtdisv'
```

```
top = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
vertices = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

**flop.modflow.mfgwtdsp module**

```
class ModflowGwtdsp(model, loading_package=False, xt3d_off=None, xt3d_rhs=None, diffc=None, alh=None,
                    alv=None, ath1=None, ath2=None, atv=None, filename=None, pname=None,
                    parent_file=None)
```

Bases: [flop.modflow.mfpackage.MFPackage](#)

ModflowGwtdsp defines a dsp package within a gwt6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **xt3d\_off** (*boolean*) –
  - xt3d\_off (*boolean*) deactivate the xt3d method and use the faster and less accurate approximation. This option may provide a fast and accurate solution under some circumstances, such as when flow aligns with the model grid, there is no mechanical dispersion, or when the longitudinal and transverse dispersivities are equal. This option may also be used to assess the computational demand of the XT3D approach by noting the run time differences with and without this option on.
- **xt3d\_rhs** (*boolean*) –
  - xt3d\_rhs (*boolean*) add xt3d terms to right-hand side, when possible. This option uses less memory, but may require more iterations.
- **diffc** (*[double]*) –
  - diffc (*double*) effective molecular diffusion coefficient.
- **alh** (*[double]*) –
  - alh (*double*) longitudinal dispersivity in horizontal direction. If flow is strictly horizontal, then this is the longitudinal dispersivity that will be used. If flow is not strictly horizontal or strictly vertical, then the longitudinal dispersivity is a function of both ALH and ALV. If mechanical dispersion is represented (by specifying any dispersivity values) then this array is required.
- **alv** (*[double]*) –
  - alv (*double*) longitudinal dispersivity in vertical direction. If flow is strictly vertical, then this is the longitudinal dispersivity value that will be used. If flow is not strictly horizontal or strictly vertical, then the longitudinal dispersivity is a function of both ALH and ALV. If this value is not specified and mechanical dispersion is represented, then this array is set equal to ALH.
- **ath1** (*[double]*) –
  - ath1 (*double*) transverse dispersivity in horizontal direction. This is the transverse dispersivity value for the second ellipsoid axis. If flow is strictly horizontal and directed in the x direction (along a row for a regular grid), then this value controls spreading in the y direction. If mechanical dispersion is represented (by specifying any dispersivity values) then this array is required.
- **ath2** (*[double]*) –

- `ath2` (double) transverse dispersivity in horizontal direction. This is the transverse dispersivity value for the third ellipsoid axis. If flow is strictly horizontal and directed in the `x` direction (along a row for a regular grid), then this value controls spreading in the `z` direction. If this value is not specified and mechanical dispersion is represented, then this array is set equal to `ATH1`.
- `atv` ([double]) –
  - `atv` (double) transverse dispersivity when flow is in vertical direction. If flow is strictly vertical and directed in the `z` direction, then this value controls spreading in the `x` and `y` directions. If this value is not specified and mechanical dispersion is represented, then this array is set equal to `ATH2`.
- `filename` (String) – File name for this package.
- `pname` (String) – Package name for this package.
- `parent_file` (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package `parent_file`.

```

alh = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
alv = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
ath1 = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
ath2 = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
atv = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

dfn = [['header'], ['block options', 'name xt3d_off', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name xt3d_rhs', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block griddata', 'name
diffc', 'type double precision', 'shape (nodes)', 'reader readarray', 'layered
true', 'optional true'], ['block griddata', 'name alh', 'type double precision',
'shape (nodes)', 'reader readarray', 'layered true', 'optional true'], ['block
griddata', 'name alv', 'type double precision', 'shape (nodes)', 'reader readarray',
'layered true', 'optional true'], ['block griddata', 'name ath1', 'type double
precision', 'shape (nodes)', 'reader readarray', 'layered true', 'optional true'],
['block griddata', 'name ath2', 'type double precision', 'shape (nodes)', 'reader
readarray', 'layered true', 'optional true'], ['block griddata', 'name atv', 'type
double precision', 'shape (nodes)', 'reader readarray', 'layered true', 'optional
true']]

dfn_file_name = 'gwt-dsp.dfn'

diffc = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

package_abbr = 'gwtdsp'

```

## flop.mf6.modflow.mfgwtfmi module

```
class ModflowGwtfmi(model, loading_package=False, save_flows=None, flow_imbalance_correction=None,
                    packagedata=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtfmi defines a fmi package within a gwt6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **save\_flows** (*boolean*) –
  - `save_flows` (*boolean*) keyword to indicate that FMI flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **flow\_imbalance\_correction** (*boolean*) –
  - `flow_imbalance_correction` (*boolean*) correct for an imbalance in flows by assuming that any residual flow error comes in or leaves at the concentration of the cell. When this option is activated, the GWT Model budget written to the listing file will contain two additional entries: FLOW-ERROR and FLOW-CORRECTION. These two entries will be equal but opposite in sign. The FLOW-CORRECTION term is a mass flow that is added to offset the error caused by an imprecise flow balance. If these terms are not relatively small, the flow model should be rerun with stricter convergence tolerances.
- **packagedata** (*[flowtype, fname]*) –
  - `flowtype` (*string*) is the word GWFBUDGET, GWFHEAD, GWFMOVER or the name of an advanced GWF stress package. If GWFBUDGET is specified, then the corresponding file must be a budget file from a previous GWF Model run. If an advanced GWF stress package name appears then the corresponding file must be the budget file saved by a LAK, SFR, MAW or UZF Package.
  - `fname` (*string*) is the name of the file containing flows. The path to the file should be included if the file is not located in the folder where the program was run.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name flow_imbalance_correction', 'type
keyword', 'reader urword', 'optional true'], ['block packagedata', 'name
packagedata', 'type recarray flowtype filein fname', 'reader urword', 'optional
false'], ['block packagedata', 'name flowtype', 'in_record true', 'type string',
'tagged false', 'reader urword'], ['block packagedata', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block packagedata', 'name fname', 'in_record true', 'type string',
'preserve_case true', 'tagged false', 'reader urword']]
```

```
dfn_file_name = 'gwt-fmi.dfn'
```

```
package_abbr = 'gwtfmi'
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flopY.mf6.modflow.mfgwtgwt module

```
class ModflowGwtgwt(simulation, loading_package=False, exgtype=None, exgmnamea=None,
                    exgmnameb=None, gwfname1=None, gwfname2=None, auxiliary=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    advscheme=None, xt3d_off=None, xt3d_rhs=None, filein=None, mvt_filerecord=None,
                    observations=None, dev_interfacemodel_on=None, nexg=None, exchangedata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowGwtgwt defines a gwtgwt package.

### Parameters

- **simulation** ([MFSimulation](#)) – Simulation that this package is a part of. Package is automatically added to simulation when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **exgtype** (*<string>*) –
  - is the exchange type (GWF-GWF or GWF-GWT).
- **exgmnamea** (*<string>*) –
  - is the name of the first model that is part of this exchange.
- **exgmnameb** (*<string>*) –
  - is the name of the second model that is part of this exchange.
- **gwfname1** (*string*) –
  - gwfname1 (*string*) keyword to specify name of first corresponding GWF Model. In the simulation name file, the GWT6-GWT6 entry contains names for GWT Models (exgmnamea and exgmnameb). The GWT Model with the name exgmnamea must correspond to the GWF Model with the name gwfname1.
- **gwfname2** (*string*) –
  - gwfname2 (*string*) keyword to specify name of second corresponding GWF Model. In the simulation name file, the GWT6-GWT6 entry contains names for GWT Models (exgmnamea and exgmnameb). The GWT Model with the name exgmnameb must correspond to the GWF Model with the name gwfname2.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) an array of auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided. Most auxiliary variables will not be used by the GWF-GWF Exchange, but they will be available for use by other parts of the program. If an auxiliary variable with the name “ANGLDEGX” is found, then this information will be used as the angle (provided in degrees) between the connection face normal and the x axis, where a value of zero indicates that a normal vector points directly along the positive x axis. The connection face normal is a normal vector on the cell face shared between the cell in model 1 and the cell in model 2 pointing away from the model 1 cell. Additional information on “ANGLDEGX” is provided in the description of the DISU Package. If an auxiliary variable with

the name “CDIST” is found, then this information will be used as the straight-line connection distance, including the vertical component, between the two cell centers. Both ANGLDEGX and CDIST are required if specific discharge is calculated for either of the groundwater models.

- **boundnames** (*boolean*) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of GWT Exchange cells.
- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of exchange entries will be echoed to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (boolean) keyword to indicate that the list of exchange flow rates will be printed to the listing file for every stress period in which “SAVE BUDGET” is specified in Output Control.
- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that cell-by-cell flow terms will be written to the budget file for each model provided that the Output Control for the models are set up with the “BUDGET SAVE FILE” option.
- **advscheme** (*string*) –
  - advscheme (string) scheme used to solve the advection term. Can be upstream, central, or TVD. If not specified, upstream weighting is the default weighting scheme.
- **xt3d\_off** (*boolean*) –
  - xt3d\_off (boolean) deactivate the xt3d method and use the faster and less accurate approximation for this exchange.
- **xt3d\_rhs** (*boolean*) –
  - xt3d\_rhs (boolean) add xt3d terms to right-hand side, when possible, for this exchange.
- **filein** (*boolean*) –
  - filein (boolean) keyword to specify that an input filename is expected next.
- **mvt\_filerecord** (*[mvt6\_filename]*) –
  - mvt6\_filename (string) is the file name of the transport mover input file to apply to this exchange. Information for the transport mover are provided in the file provided with these keywords.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **dev\_interfacemodel\_on** (*boolean*) –
  - dev\_interfacemodel\_on (boolean) activates the interface model mechanism for calculating the coefficients at (and possibly near) the exchange. This keyword should only be used for development purposes.



- **nextg** (*integer*) –
  - nextg (*integer*) keyword and integer value specifying the number of GWT-GWT exchanges.
- **exchangedata** (*[cellidm1, cellidm2, ihc, cl1, cl2, hwva, aux, boundname]*) –
  - cellidm1 (*(integer, ...)*) is the cellid of the cell in model 1 as specified in the simulation name file. For a structured grid that uses the DIS input file, CELLIDM1 is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDM1 is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM1 is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - cellidm2 (*(integer, ...)*) is the cellid of the cell in model 2 as specified in the simulation name file. For a structured grid that uses the DIS input file, CELLIDM2 is the layer, row, and column numbers of the cell. For a grid that uses the DISV input file, CELLIDM2 is the layer number and CELL2D number for the two cells. If the model uses the unstructured discretization (DISU) input file, then CELLIDM2 is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - ihc (*integer*) is an integer flag indicating the direction between node n and all of its m connections. If IHC = 0 then the connection is vertical. If IHC = 1 then the connection is horizontal. If IHC = 2 then the connection is horizontal for a vertically staggered grid.
  - cl1 (*double*) is the distance between the center of cell 1 and the its shared face with cell 2.
  - cl2 (*double*) is the distance between the center of cell 2 and the its shared face with cell 1.
  - hwva (*double*) is the horizontal width of the flow connection between cell 1 and cell 2 if IHC > 0, or it is the area perpendicular to flow of the vertical connection between cell 1 and cell 2 if IHC = 0.
  - aux (*double*) represents the values of the auxiliary variables for each GWTGWT Exchange. The values of auxiliary variables must be present for each exchange. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block.
  - boundname (*string*) name of the GWT Exchange cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name gwfname1', 'type
string', 'reader urword', 'optional false'], ['block options', 'name gwfname2',
'type string', 'reader urword', 'optional false'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name boundnames', 'type keyword', 'shape', 'reader urword',
'optional true'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name save_flows', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name advscheme',
'type string', 'valid upstream central tvd', 'reader urword', 'optional true'],
['block options', 'name xt3d_off', 'type keyword', 'shape', 'reader urword',
'optional true'], ['block options', 'name xt3d_rhs', 'type keyword', 'shape',
'reader urword', 'optional true'], ['block options', 'name filein', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name mvt_filerecord', 'type record mvt6 filein mvt6_filename',
'shape', 'reader urword', 'tagged true', 'optional true'], ['block options', 'name
mvt6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name mvt6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block options', 'name obs_filerecord', 'type record obs6 filein
obs6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package obs', 'construct_data continuous', 'parameter_name
observations'], ['block options', 'name obs6', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
obs6_filename', 'type string', 'preserve_case true', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block options', 'name
dev_interfacemodel_on', 'type keyword', 'reader urword', 'optional true'], ['block
dimensions', 'name nexg', 'type integer', 'reader urword', 'optional false'],
['block exchangedata', 'name exchangedata', 'type recarray cellidm1 cellidm2 ihc cl1
cl2 hwva aux boundname', 'reader urword', 'optional false'], ['block exchangedata',
'name cellidm1', 'type integer', 'in_record true', 'tagged false', 'reader urword',
'optional false', 'numeric_index true'], ['block exchangedata', 'name cellidm2',
'type integer', 'in_record true', 'tagged false', 'reader urword', 'optional false',
'numeric_index true'], ['block exchangedata', 'name ihc', 'type integer', 'in_record
true', 'tagged false', 'reader urword', 'optional false'], ['block exchangedata',
'name cl1', 'type double precision', 'in_record true', 'tagged false', 'reader
urword', 'optional false'], ['block exchangedata', 'name cl2', 'type double
precision', 'in_record true', 'tagged false', 'reader urword', 'optional false'],
['block exchangedata', 'name hwva', 'type double precision', 'in_record true',
'tagged false', 'reader urword', 'optional false'], ['block exchangedata', 'name
aux', 'type double precision', 'in_record true', 'tagged false', 'shape (naux)',
'reader urword', 'optional true'], ['block exchangedata', 'name boundname', 'type
string', 'shape', 'tagged false', 'in_record true', 'reader urword', 'optional
true']]
```

```
dfn_file_name = 'exg-gwtgwt.dfn'
```

```
exchangedata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
mvt_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
package_abbr = 'gwtgwt'
```

**flop.mf6.modflow.mfgwtic module**

**class ModflowGwtic**(*model*, *loading\_package=False*, *strt=0.0*, *filename=None*, *pname=None*, *parent\_file=None*)

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtic defines a ic package within a gwt6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **strt** (*[double]*) –
  - *strt* (double) is the initial (starting) concentration—that is, concentration at the beginning of the GWT Model simulation. STRT must be specified for all GWT Model simulations. One value is read for every model cell.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block griddata', 'name strt', 'type double precision', 'shape
(nodes)', 'reader readarray', 'layered true', 'default_value 0.0']]
```

```
dfn_file_name = 'gwt-ic.dfn'
```

```
package_abbr = 'gwtic'
```

```
strt = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

**flop.mf6.modflow.mfgwtist module**

**class ModflowGwtist**(*model*, *loading\_package=False*, *save\_flows=None*, *budget\_filerecord=None*, *budgetcsv\_filerecord=None*, *sorption=None*, *first\_order\_decay=None*, *zero\_order\_decay=None*, *cim\_filerecord=None*, *fileout=None*, *cimprintrecord=None*, *cim=None*, *thetaim=None*, *zetaim=None*, *decay=None*, *decay\_sorbed=None*, *bulk\_density=None*, *distcoef=None*, *filename=None*, *pname=None*, *parent\_file=None*)

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtist defines a ist package within a gwt6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **save\_flows** (*boolean*) –
  - *save\_flows* (boolean) keyword to indicate that IST flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **budget\_filerecord** (*[budgetfile]*) –
  - *budgetfile* (string) name of the binary output file to write budget information.

- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **sorption** (*boolean*) –
  - sorption (boolean) is a text keyword to indicate that sorption will be activated. Use of this keyword requires that BULK\_DENSITY and DISTCOEF are specified in the GRIDDATA block. The linear sorption isotherm is the only isotherm presently supported in the IST Package.
- **first\_order\_decay** (*boolean*) –
  - first\_order\_decay (boolean) is a text keyword to indicate that first- order decay will occur. Use of this keyword requires that DECAY and DECAY\_SORBED (if sorption is active) are specified in the GRIDDATA block.
- **zero\_order\_decay** (*boolean*) –
  - zero\_order\_decay (boolean) is a text keyword to indicate that zero- order decay will occur. Use of this keyword requires that DECAY and DECAY\_SORBED (if sorption is active) are specified in the GRIDDATA block.
- **cim\_filerecord** (*[cimfile]*) –
  - cimfile (string) name of the output file to write immobile concentrations. This file is a binary file that has the same format and structure as a binary head and concentration file. The value for the text variable written to the file is CIM. Immobile domain concentrations will be written to this file at the same interval as mobile domain concentrations are saved, as specified in the GWT Model Output Control file.
- **fileout** (*boolean*) –
  - fileout (boolean) keyword to specify that an output filename is expected next.
- **cimprintrecord** (*[columns, width, digits, format]*) –
  - columns (integer) number of columns for writing data.
  - width (integer) width for writing each number.
  - digits (integer) number of digits to use for writing a number.
  - format (string) write format can be EXPONENTIAL, FIXED, GENERAL, or SCIENTIFIC.
- **cim** (*[double]*) –
  - cim (double) initial concentration of the immobile domain in mass per length cubed. If CIM is not specified, then it is assumed to be zero.
- **thetaim** (*[double]*) –
  - thetaim (double) porosity of the immobile domain specified as the volume of immobile pore space per total volume (dimensionless).
- **zetaim** (*[double]*) –
  - zetaim (double) mass transfer rate coefficient between the mobile and immobile domains, in dimensions of per time.
- **decay** (*[double]*) –

- decay (double) is the rate coefficient for first or zero-order decay for the aqueous phase of the immobile domain. A negative value indicates solute production. The dimensions of decay for first-order decay is one over time. The dimensions of decay for zero-order decay is mass per length cubed per time. Decay will have no effect on simulation results unless either first- or zero-order decay is specified in the options block.
- **decay\_sorbed** ([double]) –
  - decay\_sorbed (double) is the rate coefficient for first or zero-order decay for the sorbed phase of the immobile domain. A negative value indicates solute production. The dimensions of decay\_sorbed for first-order decay is one over time. The dimensions of decay\_sorbed for zero-order decay is mass of solute per mass of aquifer per time. If decay\_sorbed is not specified and both decay and sorption are active, then the program will terminate with an error. decay\_sorbed will have no effect on simulation results unless the SORPTION keyword and either first- or zero-order decay are specified in the options block.
- **bulk\_density** ([double]) –
  - bulk\_density (double) is the bulk density of the aquifer in mass per length cubed. bulk\_density will have no effect on simulation results unless the SORPTION keyword is specified in the options block.
- **distcoef** ([double]) –
  - distcoef (double) is the distribution coefficient for the equilibrium-controlled linear sorption isotherm in dimensions of length cubed per mass. distcoef will have no effect on simulation results unless the SORPTION keyword is specified in the options block.
- **filename** (String) – File name for this package.
- **pname** (String) – Package name for this package.
- **parent\_file** (MFPackage) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```

budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
bulk_density = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
cim = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
cim_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
cimprintrecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
decay = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
decay_sorbed = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```

```

dfn = [['header'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name budget_filerecord', 'type record
budget fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name budget', 'type keyword', 'shape', 'in_record true',
'reader urword', 'tagged true', 'optional false'], ['block options', 'name fileout',
'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name sorption', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
first_order_decay', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name zero_order_decay', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name cim_filerecord', 'type record cim fileout cimfile',
'shape', 'reader urword', 'tagged true', 'optional true'], ['block options', 'name
cim', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name fileout', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
options', 'name cimfile', 'type string', 'preserve_case true', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block options', 'name
cimprintrecord', 'type record cim print_format formatrecord', 'shape', 'reader
urword', 'optional true'], ['block options', 'name print_format', 'type keyword',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'],
['block options', 'name formatrecord', 'type record columns width digits format',
'shape', 'in_record true', 'reader urword', 'tagged', 'optional false'], ['block
options', 'name columns', 'type integer', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional'], ['block options', 'name width', 'type integer',
'shape', 'in_record true', 'reader urword', 'tagged true', 'optional'], ['block
options', 'name digits', 'type integer', 'shape', 'in_record true', 'reader urword',
'tagged true', 'optional'], ['block options', 'name format', 'type string', 'shape',
'in_record true', 'reader urword', 'tagged false', 'optional false'], ['block
griddata', 'name cim', 'type double precision', 'shape (nodes)', 'reader readarray',
'optional true', 'layered true'], ['block griddata', 'name thetaim', 'type double
precision', 'shape (nodes)', 'reader readarray', 'layered true'], ['block griddata',
'name zetaim', 'type double precision', 'shape (nodes)', 'reader readarray',
'layered true'], ['block griddata', 'name decay', 'type double precision', 'shape
(nodes)', 'reader readarray', 'layered true', 'optional true'], ['block griddata',
'name decay_sorbed', 'type double precision', 'shape (nodes)', 'reader readarray',
'optional true', 'layered true'], ['block griddata', 'name bulk_density', 'type
double precision', 'shape (nodes)', 'reader readarray', 'layered true'], ['block
griddata', 'name distcoef', 'type double precision', 'shape (nodes)', 'reader
readarray', 'layered true']]

dfn_file_name = 'gwt-ist.dfn'

distcoef = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

package_abbr = 'gwtist'

thetaim = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

zetaim = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```

**flop.mf6.modflow.mfgwtlkt module**

```
class ModflowGwtlkt(model, loading_package=False, flow_package_name=None, auxiliary=None,
                    flow_package_auxiliary_name=None, boundnames=None, print_input=None,
                    print_concentration=None, print_flows=None, save_flows=None,
                    concentration_filerecord=None, budget_filerecord=None, budgetcsv_filerecord=None,
                    timeseries=None, observations=None, packagedata=None, lakeperioddata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtlkt defines a lkt package within a gwt6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **flow\_package\_name** (*string*) –
  - flow\_package\_name (*string*) keyword to specify the name of the corresponding flow package. If not specified, then the corresponding flow package must have the same name as this advanced transport package (the name associated with this package in the GWT name file).
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **flow\_package\_auxiliary\_name** (*string*) –
  - flow\_package\_auxiliary\_name (*string*) keyword to specify the name of an auxiliary variable in the corresponding flow package. If specified, then the simulated concentrations from this advanced transport package will be copied into the auxiliary variable specified with this name. Note that the flow package must have an auxiliary variable with this name or the program will terminate with an error. If the flows for this advanced transport package are read from a file, then this option will have no effect.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of lake cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of lake information will be written to the listing file immediately after it is read.
- **print\_concentration** (*boolean*) –

- `print_concentration` (boolean) keyword to indicate that the list of lake concentration will be printed to the listing file for every stress period in which “CONCENTRATION PRINT” is specified in Output Control. If there is no Output Control option and `PRINT_CONCENTRATION` is specified, then concentration are printed for the last time step of each stress period.
- **`print_flows` (boolean) –**
  - `print_flows` (boolean) keyword to indicate that the list of lake flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **`save_flows` (boolean) –**
  - `save_flows` (boolean) keyword to indicate that lake flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **`concentration_filerecord` ([*concfile*]) –**
  - *concfile* (string) name of the binary output file to write concentration information.
- **`budget_filerecord` ([*budgetfile*]) –**
  - *budgetfile* (string) name of the binary output file to write budget information.
- **`budgetcsv_filerecord` ([*budgetcsvfile*]) –**
  - *budgetcsvfile* (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **`timeseries` ({*varname:data*} or *timeseries data*) –**
  - Contains data for the `ts` package. Data can be stored in a dictionary containing data for the `ts` package with variable names as keys and package data as values. Data just for the `timeseries` variable is also acceptable. See `ts` package documentation for more information.
- **`observations` ({*varname:data*} or *continuous data*) –**
  - Contains data for the `obs` package. Data can be stored in a dictionary containing data for the `obs` package with variable names as keys and package data as values. Data just for the `observations` variable is also acceptable. See `obs` package documentation for more information.
- **`packagedata` ([*lakeno*, *strt*, *aux*, *boundname*]) –**
  - *lakeno* (integer) integer value that defines the lake number associated with the specified `PACKAGEDATA` data on the line. `LAKENO` must be greater than zero and less than or equal to `NLAKES`. Lake information must be specified for every lake or the program will terminate with an error. The program will also terminate with an error if information for a lake is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - *strt* (double) real value that defines the starting concentration for the lake.
  - *aux* (double) represents the values of the auxiliary variables for each lake. The values of auxiliary variables must be present for each lake. The values must be specified in the order of the auxiliary variables specified in the `OPTIONS` block. If



the package supports time series and the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **boundname** (string) name of the lake cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.

- **lakeperioddata** ([*lakeno*, *laksetting*]) –

- **lakeno** (integer) integer value that defines the lake number associated with the specified PERIOD data on the line. LAKENO must be greater than zero and less than or equal to NLAKES. This argument is an index variable, which means that it should be treated as zero- based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **laksetting** (keysting) line of information that is parsed into a keyword and values. Keyword values that can be used to start the LAKSETTING string include: STATUS, CONCENTRATION, RAINFALL, EVAPORATION, RUNOFF, and AUXILIARY. These settings are used to assign the concentration of associated with the corresponding flow terms. Concentrations cannot be specified for all flow terms. For example, the Lake Package supports a “WITHDRAWAL” flow term. If this withdrawal term is active, then water will be withdrawn from the lake at the calculated concentration of the lake.

**status** [[string]]

- \* **status** (string) keyword option to define lake status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE, which means that concentration will be calculated for the lake. If a lake is inactive, then there will be no solute mass fluxes into or out of the lake and the inactive value will be written for the lake concentration. If a lake is constant, then the concentration for the lake will be fixed at the user specified value.

**concentration** [[string]]

- \* **concentration** (string) real or character value that defines the concentration for the lake. The specified CONCENTRATION is only applied if the lake is a constant concentration lake. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rainfall** [[string]]

- \* **rainfall** (string) real or character value that defines the rainfall solute concentration ( $ML^{-3}$ ) for the lake. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**evaporation** [[string]]

- \* **evaporation** (string) real or character value that defines the concentration of evaporated water ( $ML^{-3}$ ) for the lake. If this concentration value is larger than the simulated concentration in the lake, then the evaporated water will be removed at the same concentration as the lake. If the Options block includes a TIMESERIESFILE entry (see

the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**runoff** [[string]]

- \* runoff (string) real or character value that defines the concentration of runoff ( $ML^{-3}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**ext\_inflow** [[string]]

- \* ext-inflow (string) real or character value that defines the concentration of external inflow ( $ML^{-3}$ ) for the lake. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**auxiliaryrecord** [[auxname, auxval]]

- \* auxname (string) name for the auxiliary variable to be assigned AUXVAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.
- \* auxval (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
auxiliary = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
concentration_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header', 'multi-package'], ['block options', 'name flow_package_name',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name flow_package_auxiliary_name', 'type string', 'shape',
'reader urword', 'optional true'], ['block options', 'name boundnames', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name
print_input', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name print_concentration', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name concentration_filerecord', 'type record
concentration fileout concfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name concentration', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
concfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block packagedata', 'name packagedata', 'type recarray lakeno strt aux
boundname', 'shape (maxbound)', 'reader urword'], ['block packagedata', 'name
lakeno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block packagedata', 'name strt', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block packagedata',
'name aux', 'type double precision', 'in_record true', 'tagged false', 'shape
(naux)', 'reader urword', 'time_series true', 'optional true'], ['block
packagedata', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'optional true'], ['block period', 'name iper', 'type
integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid',
'reader urword', 'optional false'], ['block period', 'name lakeperioddata', 'type
recarray lakeno laksetting', 'shape', 'reader urword'], ['block period', 'name
lakeno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name laksetting', 'type keystack status
rainfall evaporation runoff ext-inflow auxiliaryrecord', 'shape',
'tagged false', 'in_record true', 'reader urword'], ['block period', 'name status',
'type string', 'shape', 'tagged true', 'in_record true', 'reader urword'], ['block
period', 'name concentration', 'type string', 'shape', 'tagged true', 'in_record

```

```
dfn_file_name = 'gwt-lkt.dfn'
lakeperioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwtlkt'
packagedata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flop.mf6.modflow.mfgwtmst module

```
class ModflowGwtmst(model, loading_package=False, save_flows=None, first_order_decay=None,
                    zero_order_decay=None, sorption=None, porosity=None, decay=None,
                    decay_sorbed=None, bulk_density=None, distcoef=None, sp2=None, filename=None,
                    pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtmst defines a mst package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **save\_flows** (*boolean*) –
  - `save_flows` (*boolean*) keyword to indicate that MST flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **first\_order\_decay** (*boolean*) –
  - `first_order_decay` (*boolean*) is a text keyword to indicate that first- order decay will occur. Use of this keyword requires that DECAY and DECAY\_SORBED (if sorption is active) are specified in the GRIDDATA block.
- **zero\_order\_decay** (*boolean*) –
  - `zero_order_decay` (*boolean*) is a text keyword to indicate that zero- order decay will occur. Use of this keyword requires that DECAY and DECAY\_SORBED (if sorption is active) are specified in the GRIDDATA block.
- **sorption** (*string*) –
  - `sorption` (*string*) is a text keyword to indicate that sorption will be activated. Valid sorption options include LINEAR, FREUNDLICH, and LANGMUIR. Use of this keyword requires that BULK\_DENSITY and DISTCOEF are specified in the GRIDDATA block. If sorption is specified as FREUNDLICH or LANGMUIR then SP2 is also required in the GRIDDATA block.
- **porosity** (*[double]*) –
  - `porosity` (*double*) is the aquifer porosity.
- **decay** (*[double]*) –
  - `decay` (*double*) is the rate coefficient for first or zero-order decay for the aqueous phase of the mobile domain. A negative value indicates solute production. The dimensions of decay for first-order decay is one over time. The dimensions of decay

for zero-order decay is mass per length cubed per time. decay will have no effect on simulation results unless either first- or zero-order decay is specified in the options block.

- **decay\_sorbed** (*[double]*) –
  - decay\_sorbed (double) is the rate coefficient for first or zero-order decay for the sorbed phase of the mobile domain. A negative value indicates solute production. The dimensions of decay\_sorbed for first-order decay is one over time. The dimensions of decay\_sorbed for zero-order decay is mass of solute per mass of aquifer per time. If decay\_sorbed is not specified and both decay and sorption are active, then the program will terminate with an error. decay\_sorbed will have no effect on simulation results unless the SORPTION keyword and either first- or zero-order decay are specified in the options block.
- **bulk\_density** (*[double]*) –
  - bulk\_density (double) is the bulk density of the aquifer in mass per length cubed. bulk\_density is not required unless the SORPTION keyword is specified.
- **distcoef** (*[double]*) –
  - distcoef (double) is the distribution coefficient for the equilibrium-controlled linear sorption isotherm in dimensions of length cubed per mass. distcoef is not required unless the SORPTION keyword is specified.
- **sp2** (*[double]*) –
  - sp2 (double) is the exponent for the Freundlich isotherm and the sorption capacity for the Langmuir isotherm.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
bulk_density = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
decay = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
decay_sorbed = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name save_flows', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name first_order_decay', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
zero_order_decay', 'type keyword', 'reader urword', 'optional true'], ['block
options', 'name sorption', 'type string', 'valid linear freundlich langmuir',
'reader urword', 'optional true'], ['block griddata', 'name porosity', 'type double
precision', 'shape (nodes)', 'reader readarray', 'layered true'], ['block griddata',
'name decay', 'type double precision', 'shape (nodes)', 'reader readarray', 'layered
true', 'optional true'], ['block griddata', 'name decay_sorbed', 'type double
precision', 'shape (nodes)', 'reader readarray', 'optional true', 'layered true'],
['block griddata', 'name bulk_density', 'type double precision', 'shape (nodes)',
'reader readarray', 'optional true', 'layered true'], ['block griddata', 'name
distcoef', 'type double precision', 'shape (nodes)', 'reader readarray', 'layered
true', 'optional true'], ['block griddata', 'name sp2', 'type double precision',
'shape (nodes)', 'reader readarray', 'layered true', 'optional true']]
```

```
dfn_file_name = 'gwt-mst.dfn'
```

```
distcoef = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
package_abbr = 'gwtmst'
porosity = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
sp2 = <flop.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

### flop.mf6.modflow.mfgwtmvt module

```
class ModflowGwtmvt(model, loading_package=False, print_input=None, print_flows=None, save_flows=None,
                    budget_filerecord=None, budgetcsv_filerecord=None, filename=None, pname=None,
                    parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtmvt defines a mvt package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*bool*) –
  - print\_input (*bool*) keyword to indicate that the list of mover information will be written to the listing file immediately after it is read.
- **print\_flows** (*bool*) –
  - print\_flows (*bool*) keyword to indicate that the list of lake flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*bool*) –
  - save\_flows (*bool*) keyword to indicate that lake flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (*string*) name of the binary output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (*string*) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name save_flows', 'type
keyword', 'reader urword', 'optional true'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false']]

dfn_file_name = 'gwt-mvt.dfn'

package_abbr = 'gwtmvt'
```

### flop.mf6.modflow.mfgwtmwt module

```
class ModflowGwtmwt(model, loading_package=False, flow_package_name=None, auxiliary=None,
    flow_package_auxiliary_name=None, boundnames=None, print_input=None,
    print_concentration=None, print_flows=None, save_flows=None,
    concentration_filerecord=None, budget_filerecord=None, budgetcsv_filerecord=None,
    timeseries=None, observations=None, packagedata=None, mwtperioddata=None,
    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtmwt defines a mwt package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **flow\_package\_name** (*string*) –
  - flow\_package\_name (*string*) keyword to specify the name of the corresponding flow package. If not specified, then the corresponding flow package must have the same name as this advanced transport package (the name associated with this package in the GWT name file).
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use

by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.

- **flow\_package\_auxiliary\_name** (*string*) –
  - flow\_package\_auxiliary\_name (*string*) keyword to specify the name of an auxiliary variable in the corresponding flow package. If specified, then the simulated concentrations from this advanced transport package will be copied into the auxiliary variable specified with this name. Note that the flow package must have an auxiliary variable with this name or the program will terminate with an error. If the flows for this advanced transport package are read from a file, then this option will have no effect.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of well cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of well information will be written to the listing file immediately after it is read.
- **print\_concentration** (*boolean*) –
  - print\_concentration (*boolean*) keyword to indicate that the list of well concentration will be printed to the listing file for every stress period in which “CONCENTRATION PRINT” is specified in Output Control. If there is no Output Control option and PRINT\_CONCENTRATION is specified, then concentration are printed for the last time step of each stress period.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of well flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that well flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **concentration\_filerecord** (*[concfile]*) –
  - concfile (*string*) name of the binary output file to write concentration information.
- **budget\_filerecord** (*[budgetfile]*) –
  - budgetfile (*string*) name of the binary output file to write budget information.
- **budgetcsv\_filerecord** (*[budgetcsvfile]*) –
  - budgetcsvfile (*string*) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **timeseries** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.



- **observations** (*{varname:data}* or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **packagedata** (*[mawno, strt, aux, boundname]*) –
  - mawno (integer) integer value that defines the well number associated with the specified PACKAGEDATA data on the line. MAWNO must be greater than zero and less than or equal to NMAWWELLS. Well information must be specified for every well or the program will terminate with an error. The program will also terminate with an error if information for a well is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - strt (double) real value that defines the starting concentration for the well.
  - aux (double) represents the values of the auxiliary variables for each well. The values of auxiliary variables must be present for each well. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the well cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **mwtperioddata** (*[mawno, mwtsetting]*) –
  - mawno (integer) integer value that defines the well number associated with the specified PERIOD data on the line. MAWNO must be greater than zero and less than or equal to NMAWWELLS. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - mwtsetting (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the MWTSETTING string include: STATUS, CONCENTRATION, RAINFALL, EVAPORATION, RUNOFF, and AUXILIARY. These settings are used to assign the concentration of associated with the corresponding flow terms. Concentrations cannot be specified for all flow terms. For example, the Multi-Aquifer Well Package supports a “WITHDRAWAL” flow term. If this withdrawal term is active, then water will be withdrawn from the well at the calculated concentration of the well.

**status** *[[string]]*

- \* status (string) keyword option to define well status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE, which means that concentration will be calculated for the well. If a well is inactive, then there will be no solute mass fluxes into or out of the well and the inactive value will be written for the well concentration. If a well is constant, then the concentration for the well will be fixed at the user specified value.

**concentration** *[[string]]*

- \* **concentration** (string) real or character value that defines the concentration for the well. The specified CONCENTRATION is only applied if the well is a constant concentration well. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rate** [[string]]

- \* **rate** (string) real or character value that defines the injection solute concentration ( $ML^{-3}$ ) for the well. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**auxiliaryrecord** [[auxname, auxval]]

- \* **auxname** (string) name for the auxiliary variable to be assigned AUXVAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.
- \* **auxval** (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**auxiliary** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**budget\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**budgetcsv\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

**concentration\_filerecord** = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

```

dfn = [['header', 'multi-package'], ['block options', 'name flow_package_name',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name flow_package_auxiliary_name', 'type string', 'shape',
'reader urword', 'optional true'], ['block options', 'name boundnames', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name
print_input', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name print_concentration', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name concentration_filerecord', 'type record
concentration fileout concfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name concentration', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
concfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block packagedata', 'name packagedata', 'type recarray mawno strt aux
boundname', 'shape (maxbound)', 'reader urword'], ['block packagedata', 'name
mawno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block packagedata', 'name strt', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block packagedata',
'name aux', 'type double precision', 'in_record true', 'tagged false', 'shape
(naux)', 'reader urword', 'time_series true', 'optional true'], ['block
packagedata', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'optional true'], ['block period', 'name iper', 'type
integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid',
'reader urword', 'optional false'], ['block period', 'name mwtperioddata', 'type
recarray mawno mwtsetting', 'shape', 'reader urword'], ['block period', 'name
mawno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name mwtsetting', 'type keystack status
rate auxiliaryrecord', 'shape', 'tagged false', 'in_record true', 'reader urword'],
['block period', 'name status', 'type string', 'shape', 'tagged
true', 'in_record true', 'reader urword'], ['block period', 'name concentration',
'type string', 'shape', 'tagged true', 'in_record true', 'time_series true', 'reader

```

```
dfn_file_name = 'gwt-mwt.dfn'  
mwtperioddata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>  
obs_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>  
package_abbr = 'gwtmwt'  
packagedata = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>  
ts_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flopY.mf6.modflow.mfgwtname module

```
class ModflowGwtname(model, loading_package=False, list=None, print_input=None, print_flows=None,  
                      save_flows=None, packages=None, filename=None, pname=None, parent_file=None)  
Bases: flopY.mf6.mfpackage.MFPackage
```

ModflowGwtname defines a name package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **list** (*string*) –
  - list (*string*) is name of the listing file to create for this GWT model. If not specified, then the name of the list file will be the basename of the GWT model name file and the '.lst' extension. For example, if the GWT name file is called "my.model.name" then the list file will be called "my.model.lst".
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of all model stress package information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of all model package flow rates will be printed to the listing file for every stress period time step in which "BUDGET PRINT" is specified in Output Control. If there is no Output Control option and "PRINT\_FLOWS" is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - save\_flows (*boolean*) keyword to indicate that all model package flow terms will be written to the file specified with "BUDGET FILEOUT" in Output Control.
- **packages** (*[ftype, fname, pname]*) –
  - ftype (*string*) is the file type, which must be one of the following character values shown in table in mf6io.pdf. Ftype may be entered in any combination of uppercase and lowercase.
  - fname (*string*) is the name of the file containing the package input. The path to the file should be included if the file is not located in the folder where the program was run.

- `pname` (string) is the user-defined name for the package. PNAME is restricted to 16 characters. No spaces are allowed in PNAME. PNAME character values are read and stored by the program for stress packages only. These names may be useful for labeling purposes when multiple stress packages of the same type are located within a single GWT Model. If PNAME is specified for a stress package, then PNAME will be used in the flow budget table in the listing file; it will also be used for the text entry in the cell-by-cell budget file. PNAME is case insensitive and is stored in all upper case letters.

- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mftullaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name list', 'type string', 'reader urword',
'optional true'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name print_flows', 'type keyword',
'reader urword', 'optional true'], ['block options', 'name save_flows', 'type
keyword', 'reader urword', 'optional true'], ['block packages', 'name packages',
'type recarray ftype fname pname', 'reader urword', 'optional false'], ['block
packages', 'name ftype', 'in_record true', 'type string', 'tagged false', 'reader
urword'], ['block packages', 'name fname', 'in_record true', 'type string',
'preserve_case true', 'tagged false', 'reader urword'], ['block packages', 'name
pname', 'in_record true', 'type string', 'tagged false', 'reader urword', 'optional
true']]
```

```
dfn_file_name = 'gwt-nam.dfn'
```

```
package_abbr = 'gwt-nam'
```

```
packages = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flopY.mf6.modflow.mfgwtoc module

```
class ModflowGwtoc(model, loading_package=False, budget_filerecord=None, budgetcsv_filerecord=None,
concentration_filerecord=None, concentrationprintrecord=None, saverecord=None,
printrecord=None, filename=None, pname=None, parent_file=None)
```

Bases: *flopY.mf6.mfpackage.MFPackage*

ModflowGwtoc defines a oc package within a gwt6 model.

### Parameters

- **`model`** (*MFModel*) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **`loading_package`** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **`budget_filerecord`** (*[budgetfile]*) –
  - `budgetfile` (string) name of the output file to write budget information.
- **`budgetcsv_filerecord`** (*[budgetcsvfile]*) –
  - `budgetcsvfile` (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.

- **concentration\_filerecord** (*[concentrationfile]*) –
  - *concentrationfile* (string) name of the output file to write conc information.
- **concentrationprintrecord** (*[columns, width, digits, format]*) –
  - *columns* (integer) number of columns for writing data.
  - *width* (integer) width for writing each number.
  - *digits* (integer) number of digits to use for writing a number.
  - *format* (string) write format can be EXPONENTIAL, FIXED, GENERAL, or SCIENTIFIC.
- **saverecord** (*[rtype, ocsetting]*) –
  - *rtype* (string) type of information to save or print. Can be BUDGET or CONCENTRATION.
  - *ocsetting* (keysting) specifies the steps for which the data will be saved.
    - all** [[keyword]]
      - \* *all* (keyword) keyword to indicate save for all time steps in period.
    - first** [[keyword]]
      - \* *first* (keyword) keyword to indicate save for first step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.
    - last** [[keyword]]
      - \* *last* (keyword) keyword to indicate save for last step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.
    - frequency** [[integer]]
      - \* *frequency* (integer) save at the specified time step frequency. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.
    - steps** [[integer]]
      - \* *steps* (integer) save for each step specified in STEPS. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.
- **printrecord** (*[rtype, ocsetting]*) –
  - *rtype* (string) type of information to save or print. Can be BUDGET or CONCENTRATION.
  - *ocsetting* (keysting) specifies the steps for which the data will be saved.
    - all** [[keyword]]
      - \* *all* (keyword) keyword to indicate save for all time steps in period.
    - first** [[keyword]]
      - \* *first* (keyword) keyword to indicate save for first step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**last** `[[keyword]]`

- \* last (keyword) keyword to indicate save for last step in period. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**frequency** `[[integer]]`

- \* frequency (integer) save at the specified time step frequency. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

**steps** `[[integer]]`

- \* steps (integer) save for each step specified in STEPS. This keyword may be used in conjunction with other keywords to print or save results for multiple time steps.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
budget_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budgetcsv_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
concentration_filerecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
concentrationprintrecord = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
dfn = [['header'], ['block options', 'name budget_filerecord', 'type record budget
fileout budgetfile', 'shape', 'reader urword', 'tagged true', 'optional true'],
['block options', 'name budget', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name fileout', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name budgetfile', 'type string', 'preserve_case true',
'shape', 'in_record true', 'reader urword', 'tagged false', 'optional false'],
['block options', 'name budgetcsv_filerecord', 'type record budgetcsv fileout
budgetcsvfile', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
options', 'name budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name budgetcsvfile',
'type string', 'preserve_case true', 'shape', 'in_record true', 'reader urword',
'tagged false', 'optional false'], ['block options', 'name
concentration_filerecord', 'type record concentration fileout concentrationfile',
'shape', 'reader urword', 'tagged true', 'optional true'], ['block options', 'name
concentration', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name concentrationfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name concentrationprintrecord', 'type record
concentration print_format formatrecord', 'shape', 'reader urword', 'optional
true'], ['block options', 'name print_format', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
formatrecord', 'type record columns width digits format', 'shape', 'in_record true',
'reader urword', 'tagged', 'optional false'], ['block options', 'name columns',
'type integer', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional'], ['block options', 'name width', 'type integer', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional'], ['block options', 'name digits',
'type integer', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional'], ['block options', 'name format', 'type string', 'shape', 'in_record
true', 'reader urword', 'tagged false', 'optional false'], ['block period', 'name
iper', 'type integer', 'block_variable True', 'in_record true', 'tagged false',
'shape', 'valid', 'reader urword', 'optional false'], ['block period', 'name
saverecord', 'type record save rtype ocsetting', 'shape', 'reader urword', 'tagged
false', 'optional true'], ['block period', 'name save', 'type keyword', 'shape',
'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block
period', 'name printrecord', 'type record print rtype ocsetting', 'shape', 'reader
urword', 'tagged false', 'optional true'], ['block period', 'name print', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block period', 'name rtype', 'type string', 'shape', 'in_record true',
'reader urword', 'tagged false', 'optional false'], ['block period', 'name
ocsetting', 'type keystring all first last frequency steps', 'shape', 'tagged
false', 'in_record true', 'reader urword'], ['block period', 'name all', 'type
keyword', 'shape', 'in_record true', 'reader urword'], ['block period', 'name
first', 'type keyword', 'shape', 'in_record true', 'reader urword'], ['block
period', 'name last', 'type keyword', 'shape', 'in_record true', 'reader urword'],
['block period', 'name frequency', 'type integer', 'shape', 'tagged true',
'in_record true', 'reader urword'], ['block period', 'name steps', 'type integer',
'shape (<nstp)', 'tagged true', 'in_record true', 'reader urword']]

dfn_file_name = 'gwt-oc.dfn'

package_abbr = 'gwtoc'

printrecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

saverecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```



**flop.mf6.modflow.mfgwtsft module**

```
class ModflowGwtsft(model, loading_package=False, flow_package_name=None, auxiliary=None,
                    flow_package_auxiliary_name=None, boundnames=None, print_input=None,
                    print_concentration=None, print_flows=None, save_flows=None,
                    concentration_filerecord=None, budget_filerecord=None, budgetcsv_filerecord=None,
                    timeseries=None, observations=None, packagedata=None, reachperioddata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtsft defines a sft package within a gwt6 model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **flow\_package\_name** (*string*) –
  - flow\_package\_name (*string*) keyword to specify the name of the corresponding flow package. If not specified, then the corresponding flow package must have the same name as this advanced transport package (the name associated with this package in the GWT name file).
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **flow\_package\_auxiliary\_name** (*string*) –
  - flow\_package\_auxiliary\_name (*string*) keyword to specify the name of an auxiliary variable in the corresponding flow package. If specified, then the simulated concentrations from this advanced transport package will be copied into the auxiliary variable specified with this name. Note that the flow package must have an auxiliary variable with this name or the program will terminate with an error. If the flows for this advanced transport package are read from a file, then this option will have no effect.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of reach cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of reach information will be written to the listing file immediately after it is read.
- **print\_concentration** (*boolean*) –

- `print_concentration` (boolean) keyword to indicate that the list of reach concentration will be printed to the listing file for every stress period in which “CONCENTRATION PRINT” is specified in Output Control. If there is no Output Control option and `PRINT_CONCENTRATION` is specified, then concentration are printed for the last time step of each stress period.
- **`print_flows` (boolean) –**
  - `print_flows` (boolean) keyword to indicate that the list of reach flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **`save_flows` (boolean) –**
  - `save_flows` (boolean) keyword to indicate that reach flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **`concentration_filerecord` ([*concfile*]) –**
  - *concfile* (string) name of the binary output file to write concentration information.
- **`budget_filerecord` ([*budgetfile*]) –**
  - *budgetfile* (string) name of the binary output file to write budget information.
- **`budgetcsv_filerecord` ([*budgetcsvfile*]) –**
  - *budgetcsvfile* (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **`timeseries` ({*varname:data*} or *timeseries data*) –**
  - Contains data for the `ts` package. Data can be stored in a dictionary containing data for the `ts` package with variable names as keys and package data as values. Data just for the `timeseries` variable is also acceptable. See `ts` package documentation for more information.
- **`observations` ({*varname:data*} or *continuous data*) –**
  - Contains data for the `obs` package. Data can be stored in a dictionary containing data for the `obs` package with variable names as keys and package data as values. Data just for the `observations` variable is also acceptable. See `obs` package documentation for more information.
- **`packagedata` ([*rno*, *strt*, *aux*, *boundname*]) –**
  - *rno* (integer) integer value that defines the reach number associated with the specified `PACKAGEDATA` data on the line. `RNO` must be greater than zero and less than or equal to `NREACHES`. Reach information must be specified for every reach or the program will terminate with an error. The program will also terminate with an error if information for a reach is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - *strt* (double) real value that defines the starting concentration for the reach.
  - *aux* (double) represents the values of the auxiliary variables for each reach. The values of auxiliary variables must be present for each reach. The values must be specified in the order of the auxiliary variables specified in the `OPTIONS` block. If

the package supports time series and the Options block includes a TIMESERIES-FILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **boundname** (string) name of the reach cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.

- **reachperioddata** ([*rno*, *reachsetting*]) –

- **rno** (integer) integer value that defines the reach number associated with the specified PERIOD data on the line. RNO must be greater than zero and less than or equal to NREACHES. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **reachsetting** (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the REACHSETTING string include: STATUS, CONCENTRATION, RAINFALL, EVAPORATION, RUNOFF, and AUXILIARY. These settings are used to assign the concentration of associated with the corresponding flow terms. Concentrations cannot be specified for all flow terms. For example, the Streamflow Package supports a “DIVERSION” flow term. Diversion water will be routed using the calculated concentration of the reach.

**status** [[string]]

- \* **status** (string) keyword option to define reach status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE, which means that concentration will be calculated for the reach. If a reach is inactive, then there will be no solute mass fluxes into or out of the reach and the inactive value will be written for the reach concentration. If a reach is constant, then the concentration for the reach will be fixed at the user specified value.

**concentration** [[string]]

- \* **concentration** (string) real or character value that defines the concentration for the reach. The specified CONCENTRATION is only applied if the reach is a constant concentration reach. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**rainfall** [[string]]

- \* **rainfall** (string) real or character value that defines the rainfall solute concentration ( $ML^{-3}$ ) for the reach. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**evaporation** [[string]]

- \* **evaporation** (string) real or character value that defines the concentration of evaporated water ( $ML^{-3}$ ) for the reach. If this concentration value is larger than the simulated concentration in the reach, then the evaporated water will be removed at the same concentration as the reach. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from

a time series by entering the time-series name in place of a numeric value.

**runoff** [[string]]

- \* runoff (string) real or character value that defines the concentration of runoff ( $ML^{-3}$ ) for the reach. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**inflow** [[string]]

- \* inflow (string) real or character value that defines the concentration of inflow ( $ML^{-3}$ ) for the reach. Value must be greater than or equal to zero. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**auxiliaryrecord** [[auxname, auxval]]

- \* auxname (string) name for the auxiliary variable to be assigned AUX-VAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.
- \* auxval (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
auxiliary = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budget_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
budgetcsv_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
concentration_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header', 'multi-package'], ['block options', 'name flow_package_name',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name flow_package_auxiliary_name', 'type string', 'shape',
'reader urword', 'optional true'], ['block options', 'name boundnames', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name
print_input', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name print_concentration', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name concentration_filerecord', 'type record
concentration fileout concfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name concentration', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
concfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block packagedata', 'name packagedata', 'type recarray rno strt aux
boundname', 'shape (maxbound)', 'reader urword'], ['block packagedata', 'name rno',
'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block packagedata', 'name strt', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block packagedata',
'name aux', 'type double precision', 'in_record true', 'tagged false', 'shape
(naux)', 'reader urword', 'time_series true', 'optional true'], ['block
packagedata', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'optional true'], ['block period', 'name iper', 'type
integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid',
'reader urword', 'optional false'], ['block period', 'name reachperioddata', 'type
recarray rno reachsetting', 'shape', 'reader urword'], ['block period', 'name rno',
'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name reachsetting', 'type keystring status
rainfall evaporation runoff inflow auxiliaryrecord', 'shape', 'tagged
false', 'in_record true', 'reader urword'], ['block period', 'name status', 'type
string', 'shape', 'tagged true', 'in_record true', 'reader urword'], ['block
period', 'name concentration', 'type string', 'shape', 'tagged true', 'in_record

```

```
dfn_file_name = 'gwt-sft.dfn'
obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwtsft'
packagedata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
reachperioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## flop.mf6.modflow.mfgwtsrc module

```
class ModflowGwtsrc(model, loading_package=False, auxiliary=None, auxmultname=None,
                    boundnames=None, print_input=None, print_flows=None, save_flows=None,
                    timeseries=None, observations=None, maxbound=None, stress_period_data=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowGwtsrc defines a src package within a gwt6 model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **auxiliary** (*[string]*) –
  - auxiliary (*string*) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for `naux`. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **auxmultname** (*string*) –
  - auxmultname (*string*) name of auxiliary variable to be used as multiplier of mass loading rate.
- **boundnames** (*boolean*) –
  - boundnames (*boolean*) keyword to indicate that boundary names may be provided with the list of mass source cells.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that the list of mass source information will be written to the listing file immediately after it is read.
- **print\_flows** (*boolean*) –
  - print\_flows (*boolean*) keyword to indicate that the list of mass source flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and

“PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.

- **save\_flows** (*boolean*) –
  - save\_flows (boolean) keyword to indicate that mass source flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **timeseries** (*{varname:data} or timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (*{varname:data} or continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **maxbound** (*integer*) –
  - maxbound (integer) integer value specifying the maximum number of sources cells that will be specified for use during any stress period.
- **stress\_period\_data** (*[cellid, smassrate, aux, boundname]*) –
  - cellid ((integer, ...)) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - smassrate (double) is the mass source loading rate. A positive value indicates addition of solute mass and a negative value indicates removal of solute mass. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - aux (double) represents the values of the auxiliary variables for each mass source. The values of auxiliary variables must be present for each mass source. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIME-SERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - boundname (string) name of the mass source cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
auxiliary = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

dfn = [['header'], ['block options', 'name auxiliary', 'type string', 'shape
(naux)', 'reader urword', 'optional true'], ['block options', 'name auxmultname',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
boundnames', 'type keyword', 'shape', 'reader urword', 'optional true'], ['block
options', 'name print_input', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword',
'optional false'], ['block period', 'name iper', 'type integer', 'block_variable
True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword',
'optional false'], ['block period', 'name stress_period_data', 'type recarray cellid
smassrate aux boundname', 'shape (maxbound)', 'reader urword'], ['block period',
'name cellid', 'type integer', 'shape (ncelldim)', 'tagged false', 'in_record true',
'reader urword'], ['block period', 'name smassrate', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword', 'time_series true'],
['block period', 'name aux', 'type double precision', 'in_record true', 'tagged
false', 'shape (naux)', 'reader urword', 'optional true', 'time_series true'],
['block period', 'name boundname', 'type string', 'shape', 'tagged false',
'in_record true', 'reader urword', 'optional true']]

dfn_file_name = 'gwt-src.dfn'

obs_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwtsrc'

stress_period_data = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flop.mf6.modflow.mfgwtssm module

```
class ModflowGwtssm(model, loading_package=False, print_flows=None, save_flows=None, sources=None,
                    fileinput=None, filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpkg.MFPackage](#)

ModflowGwtssm defines a ssm package within a gwt6 model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.



- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_flows** (*boolean*) –
  - **print\_flows** (*boolean*) keyword to indicate that the list of SSM flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (*boolean*) –
  - **save\_flows** (*boolean*) keyword to indicate that SSM flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **sources** (*[pname, srctype, auxname]*) –
  - **pname** (*string*) name of the flow package for which an auxiliary variable contains a source concentration. If this flow package is represented using an advanced transport package (SFT, LKT, MWT, or UZT), then the advanced transport package will override SSM terms specified here.
  - **srctype** (*string*) keyword indicating how concentration will be assigned for sources and sinks. Keyword must be specified as either AUX or AUXMIXED. For both options the user must provide an auxiliary variable in the corresponding flow package. The auxiliary variable must have the same name as the AUXNAME value that follows. If the AUX keyword is specified, then the auxiliary variable specified by the user will be assigned as the concentration value for groundwater sources (flows with a positive sign). For negative flow rates (sinks), groundwater will be withdrawn from the cell at the simulated concentration of the cell. The AUXMIXED option provides an alternative method for how to determine the concentration of sinks. If the cell concentration is larger than the user-specified auxiliary concentration, then the concentration of groundwater withdrawn from the cell will be assigned as the user-specified concentration. Alternatively, if the user-specified auxiliary concentration is larger than the cell concentration, then groundwater will be withdrawn at the cell concentration. Thus, the AUXMIXED option is designed to work with the Evapotranspiration (EVT) and Recharge (RCH) Packages where water may be withdrawn at a concentration that is less than the cell concentration.
  - **auxname** (*string*) name of the auxiliary variable in the package PNAME. This auxiliary variable must exist and be specified by the user in that package. The values in this auxiliary variable will be used to set the concentration associated with the flows for that boundary package.
- **fileinput** (*[pname, spc6\_filename]*) –
  - **pname** (*string*) name of the flow package for which an SPC6 input file contains a source concentration. If this flow package is represented using an advanced transport package (SFT, LKT, MWT, or UZT), then the advanced transport package will override SSM terms specified here.
  - **spc6\_filename** (*string*) character string that defines the path and filename for the file containing source and sink input data for the flow package. The SPC6\_FILENAME file is a flexible input file that allows concentrations to be specified by stress period and with time series. Instructions for creating the SPC6\_FILENAME input file are provided in the next section on file input for boundary concentrations.
- **filename** (*String*) – File name for this package.

- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name save_flows', 'type keyword', 'reader urword', 'optional true'], ['block sources', 'name sources', 'type recarray', 'pname srctype auxname', 'reader urword', 'optional false'], ['block sources', 'name pname', 'in_record true', 'type string', 'tagged false', 'reader urword'], ['block sources', 'name srctype', 'in_record true', 'type string', 'tagged false', 'optional false', 'reader urword'], ['block sources', 'name auxname', 'in_record true', 'type string', 'tagged false', 'reader urword', 'optional false'], ['block fileinput', 'name fileinput', 'type recarray', 'pname spc6 filein spc6_filename mixed', 'reader urword'], ['block fileinput', 'name pname', 'in_record true', 'type string', 'tagged false', 'reader urword'], ['block fileinput', 'name spc6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block fileinput', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block fileinput', 'name spc6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block fileinput', 'name mixed', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional true']]

dfn_file_name = 'gwt-ssm.dfn'

fileinput = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>

package_abbr = 'gwtssm'

sources = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

### flop.mf6.modflow.mfgwtuzt module

```
class ModflowGwtuzt(model, loading_package=False, flow_package_name=None, auxiliary=None,
                    flow_package_auxiliary_name=None, boundnames=None, print_input=None,
                    print_concentration=None, print_flows=None, save_flows=None,
                    concentration_filerecord=None, budget_filerecord=None, budgetcsv_filerecord=None,
                    timeseries=None, observations=None, packagedata=None, uztperioddata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: *flop.mf6.mfpackage.MFPackage*

ModflowGwtuzt defines a uzt package within a gwt6 model.

#### Parameters

- **model** (*MFModel*) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **flow\_package\_name** (*string*) –
  - flow\_package\_name (*string*) keyword to specify the name of the corresponding flow package. If not specified, then the corresponding flow package must have the same name as this advanced transport package (the name associated with this package in the GWT name file).
- **auxiliary** (*[string]*) –

- auxiliary (string) defines an array of one or more auxiliary variable names. There is no limit on the number of auxiliary variables that can be provided on this line; however, lists of information provided in subsequent blocks must have a column of data for each auxiliary variable name defined here. The number of auxiliary variables detected on this line determines the value for naux. Comments cannot be provided anywhere on this line as they will be interpreted as auxiliary variable names. Auxiliary variables may not be used by the package, but they will be available for use by other parts of the program. The program will terminate with an error if auxiliary variables are specified on more than one line in the options block.
- **flow\_package\_auxiliary\_name** (string) –
  - flow\_package\_auxiliary\_name (string) keyword to specify the name of an auxiliary variable in the corresponding flow package. If specified, then the simulated concentrations from this advanced transport package will be copied into the auxiliary variable specified with this name. Note that the flow package must have an auxiliary variable with this name or the program will terminate with an error. If the flows for this advanced transport package are read from a file, then this option will have no effect.
- **boundnames** (boolean) –
  - boundnames (boolean) keyword to indicate that boundary names may be provided with the list of unsaturated zone flow cells.
- **print\_input** (boolean) –
  - print\_input (boolean) keyword to indicate that the list of unsaturated zone flow information will be written to the listing file immediately after it is read.
- **print\_concentration** (boolean) –
  - print\_concentration (boolean) keyword to indicate that the list of UZF cell concentration will be printed to the listing file for every stress period in which “CONCENTRATION PRINT” is specified in Output Control. If there is no Output Control option and PRINT\_CONCENTRATION is specified, then concentration are printed for the last time step of each stress period.
- **print\_flows** (boolean) –
  - print\_flows (boolean) keyword to indicate that the list of unsaturated zone flow rates will be printed to the listing file for every stress period time step in which “BUDGET PRINT” is specified in Output Control. If there is no Output Control option and “PRINT\_FLOWS” is specified, then flow rates are printed for the last time step of each stress period.
- **save\_flows** (boolean) –
  - save\_flows (boolean) keyword to indicate that unsaturated zone flow terms will be written to the file specified with “BUDGET FILEOUT” in Output Control.
- **concentration\_filerecord** ([concfile]) –
  - concfile (string) name of the binary output file to write concentration information.
- **budget\_filerecord** ([budgetfile]) –
  - budgetfile (string) name of the binary output file to write budget information.
- **budgetcsv\_filerecord** ([budgetcsvfile]) –

- `budgetcsvfile` (string) name of the comma-separated value (CSV) output file to write budget summary information. A budget summary record will be written to this file for each time step of the simulation.
- **timeseries** (`{varname:data}` or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **observations** (`{varname:data}` or *continuous data*) –
  - Contains data for the obs package. Data can be stored in a dictionary containing data for the obs package with variable names as keys and package data as values. Data just for the observations variable is also acceptable. See obs package documentation for more information.
- **packagedata** (`[uzfno, strt, aux, boundname]`) –
  - `uzfno` (integer) integer value that defines the UZF cell number associated with the specified PACKAGEDATA data on the line. UZFNO must be greater than zero and less than or equal to NUZFCELLS. Unsaturated zone flow information must be specified for every UZF cell or the program will terminate with an error. The program will also terminate with an error if information for a UZF cell is specified more than once. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `strt` (double) real value that defines the starting concentration for the unsaturated zone flow cell.
  - `aux` (double) represents the values of the auxiliary variables for each unsaturated zone flow. The values of auxiliary variables must be present for each unsaturated zone flow. The values must be specified in the order of the auxiliary variables specified in the OPTIONS block. If the package supports time series and the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.
  - `boundname` (string) name of the unsaturated zone flow cell. BOUNDNAME is an ASCII character variable that can contain as many as 40 characters. If BOUNDNAME contains spaces in it, then the entire name must be enclosed within single quotes.
- **uztperioddata** (`[uzfno, uztsetting]`) –
  - `uzfno` (integer) integer value that defines the UZF cell number associated with the specified PERIOD data on the line. UZFNO must be greater than zero and less than or equal to NUZFCELLS. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - `uztsetting` (keystring) line of information that is parsed into a keyword and values. Keyword values that can be used to start the UZTSETTING string include: STATUS, CONCENTRATION, INFILTRATION, UZET, and AUXILIARY. These settings are used to assign the concentration of associated with the corresponding flow terms. Concentrations cannot be specified for all flow terms.

**status** [[string]]

\* status (string) keyword option to define UZF cell status. STATUS can be ACTIVE, INACTIVE, or CONSTANT. By default, STATUS is ACTIVE, which means that concentration will be calculated for the UZF cell. If a UZF cell is inactive, then there will be no solute mass fluxes into or out of the UZF cell and the inactive value will be written for the UZF cell concentration. If a UZF cell is constant, then the concentration for the UZF cell will be fixed at the user specified value.

**concentration** [[string]]

\* concentration (string) real or character value that defines the concentration for the unsaturated zone flow cell. The specified CONCENTRATION is only applied if the unsaturated zone flow cell is a constant concentration cell. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**infiltration** [[string]]

\* infiltration (string) real or character value that defines the infiltration solute concentration ( $ML^{-3}$ ) for the UZF cell. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**uzet** [[string]]

\* uzet (string) real or character value that defines the concentration of unsaturated zone evapotranspiration water ( $ML^{-3}$ ) for the UZF cell. If this concentration value is larger than the simulated concentration in the UZF cell, then the unsaturated zone ET water will be removed at the same concentration as the UZF cell. If the Options block includes a TIMESERIESFILE entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**auxiliaryrecord** [[auxname, auxval]]

\* auxname (string) name for the auxiliary variable to be assigned AUXVAL. AUXNAME must match one of the auxiliary variable names defined in the OPTIONS block. If AUXNAME does not match one of the auxiliary variable names defined in the OPTIONS block the data are ignored.

\* auxval (double) value for the auxiliary variable. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
auxiliary = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
budget_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
budgetcsv_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
concentration_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```

dfn = [['header', 'multi-package'], ['block options', 'name flow_package_name',
'type string', 'shape', 'reader urword', 'optional true'], ['block options', 'name
auxiliary', 'type string', 'shape (naux)', 'reader urword', 'optional true'],
['block options', 'name flow_package_auxiliary_name', 'type string', 'shape',
'reader urword', 'optional true'], ['block options', 'name boundnames', 'type
keyword', 'shape', 'reader urword', 'optional true'], ['block options', 'name
print_input', 'type keyword', 'reader urword', 'optional true'], ['block options',
'name print_concentration', 'type keyword', 'reader urword', 'optional true'],
['block options', 'name print_flows', 'type keyword', 'reader urword', 'optional
true'], ['block options', 'name save_flows', 'type keyword', 'reader urword',
'optional true'], ['block options', 'name concentration_filerecord', 'type record
concentration fileout concfile', 'shape', 'reader urword', 'tagged true', 'optional
true'], ['block options', 'name concentration', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
concfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budget_filerecord', 'type record budget fileout budgetfile', 'shape', 'reader
urword', 'tagged true', 'optional true'], ['block options', 'name budget', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name fileout', 'type keyword', 'shape', 'in_record
true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name
budgetfile', 'type string', 'preserve_case true', 'shape', 'in_record true', 'reader
urword', 'tagged false', 'optional false'], ['block options', 'name
budgetcsv_filerecord', 'type record budgetcsv fileout budgetcsvfile', 'shape',
'reader urword', 'tagged true', 'optional true'], ['block options', 'name
budgetcsv', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block options', 'name budgetcsvfile', 'type string',
'preserve_case true', 'shape', 'in_record true', 'reader urword', 'tagged false',
'optional false'], ['block options', 'name ts_filerecord', 'type record ts6 filein
ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
options', 'name obs_filerecord', 'type record obs6 filein obs6_filename', 'shape',
'reader urword', 'tagged true', 'optional true', 'construct_package obs',
'construct_data continuous', 'parameter_name observations'], ['block options', 'name
obs6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true',
'optional false'], ['block options', 'name obs6_filename', 'type string',
'preserve_case true', 'in_record true', 'tagged false', 'reader urword', 'optional
false'], ['block packagedata', 'name packagedata', 'type recarray uzfn0 strt aux
boundname', 'shape (maxbound)', 'reader urword'], ['block packagedata', 'name
uzfn0', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block packagedata', 'name strt', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block packagedata',
'name aux', 'type double precision', 'in_record true', 'tagged false', 'shape
(naux)', 'reader urword', 'time_series true', 'optional true'], ['block
packagedata', 'name boundname', 'type string', 'shape', 'tagged false', 'in_record
true', 'reader urword', 'optional true'], ['block period', 'name iper', 'type
integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid',
'reader urword', 'optional false'], ['block period', 'name uztperioddata', 'type
recarray uzfn0 uztsetting', 'shape', 'reader urword'], ['block period', 'name
uzfn0', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword',
'numeric_index true'], ['block period', 'name uztsetting', 'type keystack status
concentration infiltration uzet auxiliaryrecord', 'shape', 'tagged false',
'in_record true', 'reader urword'], ['block period', 'name status', 'type string',
'shape', 'tagged true', 'in_record true', 'reader urword'], ['block period', 'name
concentration', 'type string', 'shape', 'tagged true', 'in_record true',

```

```
dfn_file_name = 'gwt-uzt.dfn'
obs_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
package_abbr = 'gwtuzt'
packagedata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
ts_filerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
uztperioddata = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

## MODFLOW 6 Utility Packages

MODFLOW 6 has several utility packages that can be associated with other packages. This includes the obs package, which can be used to output model results specific to its parent package, and the time series and time array series packages, which can be used to provide time series input for other packages.

Contents:

### `flopy.mf6.modflow.mfutlats` module

```
class ModflowUtlats(model, loading_package=False, maxats=1, perioddata=None, filename=None,
                    pname=None, parent_file=None)
```

Bases: `flopy.mf6.mfpackage.MFPackage`

ModflowUtlats defines a ats package within a utl model.

#### Parameters

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **maxats** (`integer`) –
  - maxats (`integer`) is the number of records in the subsequent perioddata block that will be used for adaptive time stepping.
- **perioddata** (`[iperats, dt0, dtmin, dtmax, dtadj, dtfailadj]`) –
  - iperats (`integer`) is the period number to designate for adaptive time stepping. The remaining ATS values on this line will apply to period iperats. iperats must be greater than zero. A warning is printed if iperats is greater than nper. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - dt0 (`double`) is the initial time step length for period iperats. If dt0 is zero, then the final step from the previous stress period will be used as the initial time step. The program will terminate with an error message if dt0 is negative.
  - dtmin (`double`) is the minimum time step length for this period. This value must be greater than zero and less than dtmax. dtmin must be a small value in order to ensure that simulation times end at the end of stress periods and the end of the simulation. A small value, such as 1.e-5, is recommended.
  - dtmax (`double`) is the maximum time step length for this period. This value must be greater than dtmin.



- dtadj (double) is the time step multiplier factor for this period. If the number of outer solver iterations are less than the product of the maximum number of outer iterations (OUTER\_MAXIMUM) and ATS\_OUTER\_MAXIMUM\_FRACTION (an optional variable in the IMS input file with a default value of 1/3), then the time step length is multiplied by dtadj. If the number of outer solver iterations are greater than the product of the maximum number of outer iterations and ATS\_OUTER\_MAXIMUM\_FRACTION, then the time step length is divided by dtadj. dtadj must be zero, one, or greater than one. If dtadj is zero or one, then it has no effect on the simulation. A value between 2.0 and 5.0 can be used as an initial estimate.
- dtfailadj (double) is the divisor of the time step length when a time step fails to converge. If there is solver failure, then the time step will be tried again with a shorter time step length calculated as the previous time step length divided by dtfailadj. dtfailadj must be zero, one, or greater than one. If dtfailadj is zero or one, then time steps will not be retried with shorter lengths. In this case, the program will terminate with an error, or it will continue if the CONTINUE option is set in the simulation name file. Initial tests with this variable should be set to 5.0 or larger to determine if convergence can be achieved.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block dimensions', 'name maxats', 'type integer', 'reader
urword', 'optional false', 'default_value 1'], ['block perioddata', 'name
perioddata', 'type recarray iperats dt0 dtmin dtmax dtadj dtfailadj', 'reader
urword', 'optional false'], ['block perioddata', 'name iperats', 'type integer',
'in_record true', 'tagged false', 'reader urword', 'optional false', 'numeric_index
true'], ['block perioddata', 'name dt0', 'type double precision', 'in_record true',
'tagged false', 'reader urword', 'optional false'], ['block perioddata', 'name
dtmin', 'type double precision', 'in_record true', 'tagged false', 'reader urword',
'optional false'], ['block perioddata', 'name dtmax', 'type double precision',
'in_record true', 'tagged false', 'reader urword', 'optional false'], ['block
perioddata', 'name dtadj', 'type double precision', 'in_record true', 'tagged
false', 'reader urword', 'optional false'], ['block perioddata', 'name dtfailadj',
'type double precision', 'in_record true', 'tagged false', 'reader urword',
'optional false']]
```

```
dfn_file_name = 'utl-ats.dfn'
```

```
package_abbr = 'utlats'
```

```
perioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtlatsPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

```
Bases: flop.mf6.mfpkg.MFChildPackages
```

UtlatsPackages is a container class for the ModflowUtlats class.

```
initialize()
```

Initializes a new ModflowUtlats package removing any sibling child packages attached to the same parent package. See ModflowUtlats init documentation for definition of parameters.

```
append_package()
```

Adds a new ModflowUtlats package to the container. See ModflowUtlats init documentation for definition

of parameters.

```
append_package(maxats=1, perioddata=None, filename=None, pname=None)
initialize(maxats=1, perioddata=None, filename=None, pname=None)
package_abbrev = 'utlatspackages'
```

### flop.mf6.modflow.mfutilaktab module

```
class ModflowUtilaktab(model, loading_package=False, nrow=None, ncol=None, table=None,
                        filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowUtilaktab defines a laktab package within a utl model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **nrow** (*integer*) –
  - nrow (*integer*) integer value specifying the number of rows in the lake table. There must be NROW rows of data in the TABLE block.
- **ncol** (*integer*) –
  - ncol (*integer*) integer value specifying the number of columns in the lake table. There must be NCOL columns of data in the TABLE block. For lakes with HORIZONTAL and/or VERTICAL CTYPE connections, NCOL must be equal to 3. For lakes with EMBEDDEDH or EMBEDDEDV CTYPE connections, NCOL must be equal to 4.
- **table** (*[stage, volume, sarea, barea]*) –
  - stage (*double*) real value that defines the stage corresponding to the remaining data on the line.
  - volume (*double*) real value that defines the lake volume corresponding to the stage specified on the line.
  - sarea (*double*) real value that defines the lake surface area corresponding to the stage specified on the line.
  - barea (*double*) real value that defines the lake-GWF exchange area corresponding to the stage specified on the line. BAREA is only specified if the CLAKTYPE for the lake is EMBEDDEDH or EMBEDDEDV.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutilaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block dimensions', 'name nrow', 'type integer', 'reader
urword', 'optional false'], ['block dimensions', 'name ncol', 'type integer',
'reader urword', 'optional false'], ['block table', 'name table', 'type recarray
stage volume sarea barea', 'shape (nrow)', 'reader urword'], ['block table', 'name
stage', 'type double precision', 'shape', 'tagged false', 'in_record true', 'reader
urword'], ['block table', 'name volume', 'type double precision', 'shape', 'tagged
false', 'in_record true', 'reader urword'], ['block table', 'name sarea', 'type
double precision', 'shape', 'tagged false', 'in_record true', 'reader urword'],
['block table', 'name barea', 'type double precision', 'shape', 'tagged false',
'in_record true', 'reader urword', 'optional true']]
```

```
dfn_file_name = 'utl-laktab.dfn'
```

```
package_abbr = 'utllaktab'
```

```
table = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtllaktabPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flopy.mf6.mfpackage.MFChildPackages](#)

UtllaktabPackages is a container class for the ModflowUtllaktab class.

**initialize()**

Initializes a new ModflowUtllaktab package removing any sibling child packages attached to the same parent package. See ModflowUtllaktab init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtllaktab package to the container. See ModflowUtllaktab init documentation for definition of parameters.

```
append_package(nrow=None, ncol=None, table=None, filename=None, pname=None)
```

```
initialize(nrow=None, ncol=None, table=None, filename=None, pname=None)
```

```
package_abbr = 'utllaktabpackages'
```

## flopy.mf6.modflow.mfutlobs module

```
class ModflowUtlobs(model, loading_package=False, digits=None, print_input=None, continuous=None,
filename=None, pname=None, parent_file=None)
```

Bases: [flopy.mf6.mfpackage.MFPackage](#)

ModflowUtlobs defines a obs package within a utl model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **digits** (*integer*) –
  - **digits** (*integer*) Keyword and an integer digits specifier used for conversion of simulated values to text on output. If not specified, the default is the maximum number of digits stored in the program (as written with the G0 Fortran specifier). When simulated values are written to a comma-separated value text file specified in a CONTINUOUS block below, the digits specifier controls the number of significant digits with which simulated values are written to the output file. The digits specifier has no effect on the number of significant digits with which the simulation

time is written for continuous observations. If DIGITS is specified as zero, then observations are written with the default setting, which is the maximum number of digits.

- **print\_input** (*boolean*) –
  - print\_input (boolean) keyword to indicate that the list of observation information will be written to the listing file immediately after it is read.
- **continuous** (*[obsname, obstype, id, id2]*) –
  - obsname (string) string of 1 to 40 nonblank characters used to identify the observation. The identifier need not be unique; however, identification and post-processing of observations in the output files are facilitated if each observation is given a unique name.
  - obstype (string) a string of characters used to identify the observation type.
  - id (string) Text identifying cell where observation is located. For packages other than NPF, if boundary names are defined in the corresponding package input file, ID can be a boundary name. Otherwise ID is a cellid. If the model discretization is type DIS, cellid is three integers (layer, row, column). If the discretization is DISV, cellid is two integers (layer, cell number). If the discretization is DISU, cellid is one integer (node number). This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
  - id2 (string) Text identifying cell adjacent to cell identified by ID. The form of ID2 is as described for ID. ID2 is used for intercell- flow observations of a GWF model, for three observation types of the LAK Package, for two observation types of the MAW Package, and one observation type of the UZF Package. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**continuous** = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name digits', 'type integer',
'shape', 'reader urword', 'optional true'], ['block options', 'name print_input',
'type keyword', 'reader urword', 'optional true'], ['block continuous', 'name
output', 'type record fileout obs_output_file_name binary', 'shape', 'block_variable
true', 'in_record false', 'reader urword', 'optional false'], ['block continuous',
'name fileout', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged
true', 'optional false'], ['block continuous', 'name obs_output_file_name', 'type
string', 'preserve_case true', 'in_record true', 'shape', 'tagged false', 'reader
urword'], ['block continuous', 'name binary', 'type keyword', 'in_record true',
'shape', 'reader urword', 'optional true'], ['block continuous', 'name continuous',
'type recarray obsname obstype id id2', 'shape', 'reader urword', 'optional false'],
['block continuous', 'name obsname', 'type string', 'shape', 'tagged false',
'in_record true', 'reader urword'], ['block continuous', 'name obstype', 'type
string', 'shape', 'tagged false', 'in_record true', 'reader urword'], ['block
continuous', 'name id', 'type string', 'shape', 'tagged false', 'in_record true',
'reader urword', 'numeric_index true'], ['block continuous', 'name id2', 'type
string', 'shape', 'tagged false', 'in_record true', 'reader urword', 'optional
true', 'numeric_index true']]
```

```
dfn_file_name = 'utl-obs.dfn'
```

```
package_abbr = 'utlobs'
```

```
class UtlobsPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flop.mf6.mfpackage.MFChildPackages](#)

UtlobsPackages is a container class for the ModflowUtlobs class.

**initialize()**

Initializes a new ModflowUtlobs package removing any sibling child packages attached to the same parent package. See ModflowUtlobs init documentation for definition of parameters.

```
initialize(digits=None, print_input=None, continuous=None, filename=None, pname=None)
```

```
package_abbr = 'utlobspackages'
```

## flop.mf6.modflow.mfutilsfrtab module

```
class ModflowUtilsfrtab(model, loading_package=False, nrow=None, ncol=None, table=None,
filename=None, pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowUtilsfrtab defines a sfrtab package within a utl model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **nrow** (*integer*) –
  - nrow (*integer*) integer value specifying the number of rows in the reach cross-section table. There must be NROW rows of data in the TABLE block.
- **ncol** (*integer*) –

- `ncol` (integer) integer value specifying the number of columns in the reach cross-section table. There must be `NCOL` columns of data in the `TABLE` block. `NCOL` must be equal to 2 if `MANFRACTION` is not specified or 3 otherwise.
- **`table`** (*[xfraction, height, manfraction]*) –
  - `xfraction` (double) real value that defines the station (`x`) data for the cross-section as a fraction of the width (`RWID`) of the reach. `XFRACTION` must be greater than or equal to zero but can be greater than one. `XFRACTION` values can be used to decrease or increase the width of a reach from the specified reach width (`RWID`).
  - `height` (double) real value that is the height relative to the top of the lowest elevation of the streambed (`RTP`) and corresponding to the station data on the same line. `HEIGHT` must be greater than or equal to zero and at least one cross-section height must be equal to zero.
  - `manfraction` (double) real value that defines the Manning’s roughness coefficient data for the cross-section as a fraction of the Manning’s roughness coefficient for the reach (`MAN`) and corresponding to the station data on the same line. `MANFRACTION` must be greater than zero. `MANFRACTION` is applied from the `XFRACTION` value on the same line to the `XFRACTION` value on the next line. Although a `MANFRACTION` value is specified on the last line, any value greater than zero can be applied to `MANFRACTION(NROW)`. `MANFRACTION` is only specified if `NCOL` is 3. If `MANFRACTION` is not specified, the Manning’s roughness coefficient for the reach (`MAN`) is applied to the entire cross-section.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (`mfutl*`). For example, `mfutllaktab` package must have a `mfgwflak` package `parent_file`.

```
dfn = [['header'], ['block dimensions', 'name nrow', 'type integer', 'reader
urword', 'optional false'], ['block dimensions', 'name ncol', 'type integer',
'reader urword', 'optional false'], ['block table', 'name table', 'type recarray
xfraction height manfraction', 'shape (nrow)', 'reader urword'], ['block table',
'name xfraction', 'type double precision', 'shape', 'tagged false', 'in_record
true', 'reader urword'], ['block table', 'name height', 'type double precision',
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block table', 'name
manfraction', 'type double precision', 'shape', 'tagged false', 'in_record true',
'reader urword', 'optional true']]
```

```
dfn_file_name = 'utl-sfrtab.dfn'
```

```
package_abbr = 'utlsfrtab'
```

```
table = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtlsfrtabPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

```
Bases: flop.mf6.mfppackage.MFChildPackages
```

UtlsfrtabPackages is a container class for the ModflowUtlsfrtab class.

**`initialize()`**

Initializes a new ModflowUtlsfrtab package removing any sibling child packages attached to the same parent package. See ModflowUtlsfrtab init documentation for definition of parameters.

**`append_package()`**

Adds a new ModflowUtlsfrtab package to the container. See ModflowUtlsfrtab init documentation for definition of parameters.

```

append_package(nrow=None, ncol=None, table=None, filename=None, pname=None)
initialize(nrow=None, ncol=None, table=None, filename=None, pname=None)
package_abbr = 'utlsfrtabpackages'

```

### flopY.mf6.modflow.mfutlspc module

```

class ModflowUtlspc(model, loading_package=False, print_input=None, timeseries=None, maxbound=None,
                    perioddata=None, filename=None, pname=None, parent_file=None)

```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowUtlspc defines a spc package within a utl model.

#### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
  - **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
  - **print\_input** (*boolean*) –
    - print\_input (*boolean*) keyword to indicate that the list of spc information will be written to the listing file immediately after it is read.
  - **timeseries** (*{varname:data} or timeseries data*) –
    - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
  - **maxbound** (*integer*) –
    - maxbound (*integer*) integer value specifying the maximum number of spc cells that will be specified for use during any stress period.
  - **perioddata** (*[bndno, spcsetting]*) –
    - bndno (*integer*) integer value that defines the boundary package feature number associated with the specified PERIOD data on the line. BNDNO must be greater than zero and less than or equal to MAXBOUND. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.
    - spcsetting (*keystring*) line of information that is parsed into a keyword and values. Keyword values that can be used to start the MAWSETTING string include: CONCENTRATION.
- concentration** *[[double]]*
- \* concentration (*double*) is the boundary concentration. If the Options block includes a TIMESERIESFILE entry (see the “Time- Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value. By default, the CONCENTRATION for each boundary feature is zero.
- **filename** (*String*) – File name for this package.
  - **pname** (*String*) – Package name for this package.



- **parent\_file** ([MFPackage](#)) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header', 'multi-package'], ['block options', 'name print_input', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true', 'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'], ['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block dimensions', 'name maxbound', 'type integer', 'reader urword', 'optional false'], ['block period', 'name iper', 'type integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block period', 'name perioddata', 'type recarray bndno spcsetting', 'shape', 'reader urword'], ['block period', 'name bndno', 'type integer', 'shape', 'tagged false', 'in_record true', 'reader urword', 'numeric_index true'], ['block period', 'name spcsetting', 'type keystring concentration', 'shape', 'tagged false', 'in_record true', 'reader urword'], ['block period', 'name concentration', 'type double precision', 'shape', 'tagged true', 'in_record true', 'reader urword', 'time_series true']]
```

```
dfn_file_name = 'utl-spc.dfn'
```

```
package_abbr = 'utlspc'
```

```
perioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtlspcPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flop.mf6.mfpackage.MFChildPackages](#)

UtlspcPackages is a container class for the ModflowUtlspc class.

**initialize()**

Initializes a new ModflowUtlspc package removing any sibling child packages attached to the same parent package. See ModflowUtlspc init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtlspc package to the container. See ModflowUtlspc init documentation for definition of parameters.

```
append_package(print_input=None, timeseries=None, maxbound=None, perioddata=None, filename=None, pname=None)
```

```
initialize(print_input=None, timeseries=None, maxbound=None, perioddata=None, filename=None, pname=None)
```

```
package_abbr = 'utlspcpackages'
```



**flopY.mf6.modflow.mfutlspca module**

```
class ModflowUtlspca(model, loading_package=False, readasarrays=True, print_input=None,
                    timearrayseries=None, concentration=0.0, filename=None, pname=None,
                    parent_file=None)
```

Bases: `flopY.mf6.mfpackage.MFPackage`

ModflowUtlspca defines a spca package within a utl model.

**Parameters**

- **model** (`MFModel`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (`bool`) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **readasarrays** (`boolean`) –
  - readasarrays (`boolean`) indicates that array-based input will be used for the SPC Package. This keyword must be specified to use array- based input.
- **print\_input** (`boolean`) –
  - print\_input (`boolean`) keyword to indicate that the list of spc information will be written to the listing file immediately after it is read.
- **timearrayseries** (`{varname:data}` or `tas_array data`) –
  - Contains data for the tas package. Data can be stored in a dictionary containing data for the tas package with variable names as keys and package data as values. Data just for the timearrayseries variable is also acceptable. See tas package documentation for more information.
- **concentration** (`[double]`) –
  - concentration (`double`) is the concentration of the associated Recharge or Evapo-transpiration stress package. The concentration array may be defined by a time-array series (see the “Using Time- Array Series in a Package” section).
- **filename** (`String`) – File name for this package.
- **pname** (`String`) – Package name for this package.
- **parent\_file** (`MFPackage`) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

**concentration** = <flopY.mf6.data.mfdatautil.ArrayTemplateGenerator object>

```
dfn = [['header', 'multi-package'], ['block options', 'name readasarrays', 'type keyword', 'shape', 'reader urword', 'optional false', 'default_value True'], ['block options', 'name print_input', 'type keyword', 'reader urword', 'optional true'], ['block options', 'name tas_filerecord', 'type record tas6 filein tas6_filename', 'shape', 'reader urword', 'tagged true', 'optional true', 'construct_package tas', 'construct_data tas_array', 'parameter_name timearrayseries'], ['block options', 'name tas6', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional false'], ['block options', 'name tas6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block period', 'name iper', 'type integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block period', 'name concentration', 'type double precision', 'shape (ncol*nrow; ncpl)', 'reader readarray', 'default_value 0.']]
```

```
dfn_file_name = 'utl-spca.dfn'
```

```
package_abbr = 'utlspca'
```

```
tas_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtlspcaPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flop.mf6.mfpackage.MFChildPackages](#)

UtlspcaPackages is a container class for the ModflowUtlspca class.

**initialize()**

Initializes a new ModflowUtlspca package removing any sibling child packages attached to the same parent package. See ModflowUtlspca init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtlspca package to the container. See ModflowUtlspca init documentation for definition of parameters.

```
append_package(readasarrays=True, print_input=None, timearrayseries=None, concentration=0.0,
                filename=None, pname=None)
```

```
initialize(readasarrays=True, print_input=None, timearrayseries=None, concentration=0.0,
            filename=None, pname=None)
```

```
package_abbr = 'utlspcapackages'
```

## flop.mf6.modflow.mfutltas module

```
class ModflowUtltas(model, loading_package=False, time_series_namerecord=None,
                    interpolation_methodrecord=None, sfacrecord=None, tas_array=None, filename=None,
                    pname=None, parent_file=None)
```

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowUtltas defines a tas package within a utl model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **time\_series\_namerecord** (*[time\_series\_name]*) –

- `time_series_name` (string) Name by which a package references a particular time-array series. The name must be unique among all time- array series used in a package.
- **`interpolation_methodrecord`** (*[interpolation\_method]*) –
  - `interpolation_method` (string) Interpolation method, which is either STEPWISE or LINEAR.
- **`sfacrecord`** (*[sfacval]*) –
  - `sfacval` (double) Scale factor, which will multiply all array values in time series. SFAC is an optional attribute; if omitted, SFAC = 1.0.
- **`tas_array`** (*[double]*) –
  - `tas_array` (double) An array of numeric, floating-point values, or a constant value, readable by the U2DREL array-reading utility.
- **`filename`** (*String*) – File name for this package.
- **`pname`** (*String*) – Package name for this package.
- **`parent_file`** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header', 'multi-package'], ['block attributes', 'name
time_series_namerecord', 'type record name time_series_name', 'shape', 'reader
urword', 'tagged false', 'optional false'], ['block attributes', 'name name', 'type
keyword', 'shape', 'reader urword', 'optional false'], ['block attributes', 'name
time_series_name', 'type string', 'shape anyld', 'tagged false', 'reader urword',
'optional false'], ['block attributes', 'name interpolation_methodrecord', 'type
record method interpolation_method', 'shape', 'reader urword', 'tagged false',
'optional true'], ['block attributes', 'name method', 'type keyword', 'shape',
'reader urword', 'optional false'], ['block attributes', 'name
interpolation_method', 'type string', 'valid stepwise linear linearend', 'shape',
'tagged false', 'reader urword', 'optional false'], ['block attributes', 'name
sfacrecord', 'type record sfac sfacval', 'shape', 'reader urword', 'tagged true',
'optional true'], ['block attributes', 'name sfac', 'type keyword', 'shape', 'reader
urword', 'optional false'], ['block attributes', 'name sfacval', 'type double
precision', 'shape time_series_name', 'tagged false', 'reader urword', 'optional
false'], ['block time', 'name time_from_model_start', 'type double precision',
'block_variable True', 'in_record true', 'shape', 'tagged false', 'valid', 'reader
urword', 'optional false'], ['block time', 'name tas_array', 'type double
precision', 'tagged false', 'just_data true', 'shape (unknown)', 'reader readarray',
'optional false', 'repeating true']]
```

```
dfn_file_name = 'utl-tas.dfn'
```

```
interpolation_methodrecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```
package_abbr = 'utltas'
```

```
sfacrecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
tas_array = <flopy.mf6.data.mfdatautil.ArrayTemplateGenerator object>
```

```
time_series_namerecord = <flopy.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtltasPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

```
Bases: flopy.mf6.mfppackage.MFChildPackages
```

UtltsPackages is a container class for the ModflowUtlts class.

**initialize()**

Initializes a new ModflowUtlts package removing any sibling child packages attached to the same parent package. See ModflowUtlts init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtlts package to the container. See ModflowUtlts init documentation for definition of parameters.

**append\_package**(*time\_series\_namerecord=None, interpolation\_methodrecord=None, sfacrecord=None, tas\_array=None, filename=None, pname=None*)

**initialize**(*time\_series\_namerecord=None, interpolation\_methodrecord=None, sfacrecord=None, tas\_array=None, filename=None, pname=None*)

**package\_abbr** = 'utltaspackages'

### flop.mf6.modflow.mfutilts module

**class ModflowUtlts**(*model, loading\_package=False, time\_series\_namerecord=None, interpolation\_methodrecord=None, interpolation\_methodrecord\_single=None, sfacrecord=None, sfacrecord\_single=None, timeseries=None, filename=None, pname=None, parent\_file=None*)

Bases: [flop.mf6.mfpackage.MFPackage](#)

ModflowUtlts defines a ts package within a utl model.

**Parameters**

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **time\_series\_namerecord** (*[time\_series\_names]*) –
  - *time\_series\_names* (string) Name by which a package references a particular time-array series. The name must be unique among all time- array series used in a package.
- **interpolation\_methodrecord** (*[interpolation\_method]*) –
  - *interpolation\_method* (string) Interpolation method, which is either STEPWISE or LINEAR.
- **interpolation\_methodrecord\_single** (*[interpolation\_method\_single]*) –
  - *interpolation\_method\_single* (string) Interpolation method, which is either STEPWISE or LINEAR.
- **sfacrecord** (*[sfacval]*) –
  - *sfacval* (double) Scale factor, which will multiply all array values in time series. SFAC is an optional attribute; if omitted, SFAC = 1.0.
- **sfacrecord\_single** (*[sfacval]*) –
  - *sfacval* (double) Scale factor, which will multiply all array values in time series. SFAC is an optional attribute; if omitted, SFAC = 1.0.
- **timeseries** (*[ts\_time, ts\_array]*) –

- `ts_time` (double) A numeric time relative to the start of the simulation, in the time unit used in the simulation. Times must be strictly increasing.
- `ts_array` (double) A 2-D array of numeric, floating-point values, or a constant value, readable by the U2DREL array-reading utility.
- `filename` (*String*) – File name for this package.
- `pname` (*String*) – Package name for this package.
- `parent_file` (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header', 'multi-package'], ['block attributes', 'name
time_series_namerecord', 'type record names time_series_names', 'shape', 'reader
urword', 'tagged false', 'optional false'], ['block attributes', 'name names',
'other_names name', 'type keyword', 'shape', 'reader urword', 'optional false'],
['block attributes', 'name time_series_names', 'type string', 'shape anyld', 'tagged
false', 'reader urword', 'optional false'], ['block attributes', 'name
interpolation_methodrecord', 'type record methods interpolation_method', 'shape',
'reader urword', 'tagged false', 'optional true'], ['block attributes', 'name
methods', 'type keyword', 'shape', 'reader urword', 'optional false'], ['block
attributes', 'name interpolation_method', 'type string', 'valid stepwise linear
linearend', 'shape time_series_names', 'tagged false', 'reader urword', 'optional
false'], ['block attributes', 'name interpolation_methodrecord_single', 'type record
method interpolation_method_single', 'shape', 'reader urword', 'tagged false',
'optional true'], ['block attributes', 'name method', 'type keyword', 'shape',
'reader urword', 'optional false'], ['block attributes', 'name
interpolation_method_single', 'type string', 'valid stepwise linear linearend',
'shape', 'tagged false', 'reader urword', 'optional false'], ['block attributes',
'name sfacrecord', 'type record sfacs sfacval', 'shape', 'reader urword', 'tagged
true', 'optional true'], ['block attributes', 'name sfacs', 'type keyword', 'shape',
'reader urword', 'optional false'], ['block attributes', 'name sfacval', 'type
double precision', 'shape <time_series_name', 'tagged false', 'reader urword',
'optional false'], ['block attributes', 'name sfacrecord_single', 'type record sfac
sfacval', 'shape', 'reader urword', 'tagged true', 'optional true'], ['block
attributes', 'name sfac', 'type keyword', 'shape', 'tagged false', 'reader urword',
'optional false'], ['block timeseries', 'name timeseries', 'type recarray ts_time
ts_array', 'shape', 'reader urword', 'tagged true', 'optional false'], ['block
timeseries', 'name ts_time', 'type double precision', 'shape', 'tagged false',
'reader urword', 'optional false', 'repeating false'], ['block timeseries', 'name
ts_array', 'type double precision', 'shape time_series_names', 'tagged false',
'reader urword', 'optional false']]
```

```
dfn_file_name = 'utl-ts.dfn'
```

```
interpolation_methodrecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```
interpolation_methodrecord_single = <flop.mf6.data.mfdatautil.ListTemplateGenerator
object>
```

```
package_abbr = 'utlts'
```

```
sfacrecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
sfacrecord_single = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
time_series_namerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
timeseries = <flopY.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtltsPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flopY.mf6.mfpackage.MFChildPackages](#)

UtltsPackages is a container class for the ModflowUtlts class.

```
initialize()
```

Initializes a new ModflowUtlts package removing any sibling child packages attached to the same parent package. See ModflowUtlts init documentation for definition of parameters.

```
append_package()
```

Adds a new ModflowUtlts package to the container. See ModflowUtlts init documentation for definition of parameters.

```
append_package(time_series_namerecord=None, interpolation_methodrecord=None,
                interpolation_methodrecord_single=None, sfacrecord=None, sfacrecord_single=None,
                timeseries=None, filename=None, pname=None)
```

```
initialize(time_series_namerecord=None, interpolation_methodrecord=None,
            interpolation_methodrecord_single=None, sfacrecord=None, sfacrecord_single=None,
            timeseries=None, filename=None, pname=None)
```

```
package_abbr = 'utltspackages'
```

## flopY.mf6.modflow.mfutlvtk module

```
class ModflowUtlvtk(model, loading_package=False, print_input=None, timeseries=None, perioddata=None,
                    filename=None, pname=None, parent_file=None)
```

Bases: [flopY.mf6.mfpackage.MFPackage](#)

ModflowUtlvtk defines a tvk package within a utl model.

### Parameters

- **model** ([MFModel](#)) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **print\_input** (*boolean*) –
  - print\_input (*boolean*) keyword to indicate that information for each change to the hydraulic conductivity in a cell will be written to the model listing file.
- **timeseries** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **perioddata** (*[cellid, tvksetting]*) –
  - cellid (*(integer, ...)*) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, CELLID is the layer, row, and column. For a grid that uses the DISV input file, CELLID is the layer and CELL2D number. If the model uses the unstructured discretization (DISU) input file, CELLID is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working

with FloPy and Python. Flopy will automatically subtract one when loading index variables and add one when writing index variables.

- `tvksetting` (keystring) line of information that is parsed into a property name keyword and values. Property name keywords that can be used to start the TVKSETTING string include: K, K22, and K33.

**k** `[[double]]`

- \* `k` (double) is the new value to be assigned as the cell’s hydraulic conductivity from the start of the specified stress period, as per K in the NPF package. If the OPTIONS block includes a TS6 entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**k22** `[[double]]`

- \* `k22` (double) is the new value to be assigned as the cell’s hydraulic conductivity of the second ellipsoid axis (or the ratio of K22/K if the K22OVERK NPF package option is specified) from the start of the specified stress period, as per K22 in the NPF package. For an unrotated case this is the hydraulic conductivity in the y direction. If the OPTIONS block includes a TS6 entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

**k33** `[[double]]`

- \* `k33` (double) is the new value to be assigned as the cell’s hydraulic conductivity of the third ellipsoid axis (or the ratio of K33/K if the K33OVERK NPF package option is specified) from the start of the specified stress period, as per K33 in the NPF package. For an unrotated case, this is the vertical hydraulic conductivity. If the OPTIONS block includes a TS6 entry (see the “Time-Variable Input” section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package `parent_file`.

```
dfn = [['header'], ['block options', 'name print_input', 'type keyword', 'reader
urword', 'optional true'], ['block options', 'name ts_filerecord', 'type record ts6
filein ts6_filename', 'shape', 'reader urword', 'tagged true', 'optional true',
'construct_package ts', 'construct_data timeseries', 'parameter_name timeseries'],
['block options', 'name ts6', 'type keyword', 'shape', 'in_record true', 'reader
urword', 'tagged true', 'optional false'], ['block options', 'name filein', 'type
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional
false'], ['block options', 'name ts6_filename', 'type string', 'preserve_case true',
'in_record true', 'reader urword', 'optional false', 'tagged false'], ['block
period', 'name iper', 'type integer', 'block_variable True', 'in_record true',
'tagged false', 'shape', 'valid', 'reader urword', 'optional false'], ['block
period', 'name perioddata', 'type recarray cellid tvksetting', 'shape', 'reader
urword'], ['block period', 'name cellid', 'type integer', 'shape (ncelldim)',
'tagged false', 'in_record true', 'reader urword'], ['block period', 'name
tvksetting', 'type keystring k k22 k33', 'shape', 'tagged false', 'in_record true',
'reader urword'], ['block period', 'name k', 'type double precision', 'shape',
'tagged true', 'in_record true', 'reader urword', 'time_series true'], ['block
period', 'name k22', 'type double precision', 'shape', 'tagged true', 'in_record
true', 'reader urword', 'time_series true'], ['block period', 'name k33', 'type
double precision', 'shape', 'tagged true', 'in_record true', 'reader urword',
'time_series true']]
```

```
dfn_file_name = 'utl-tvk.dfn'
```

```
package_abbr = 'utltvk'
```

```
perioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtltvkPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flop.mf6.mfpackage.MFChildPackages](#)

UtltvkPackages is a container class for the ModflowUtltvk class.

**initialize()**

Initializes a new ModflowUtltvk package removing any sibling child packages attached to the same parent package. See ModflowUtltvk init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtltvk package to the container. See ModflowUtltvk init documentation for definition of parameters.

**append\_package**(*print\_input=None, timeseries=None, perioddata=None, filename=None, pname=None*)

**initialize**(*print\_input=None, timeseries=None, perioddata=None, filename=None, pname=None*)

```
package_abbr = 'utltvkpackages'
```



**flopY.mf6.modflow.mfutltsv module**

```
class ModflowUtltsv(model, loading_package=False, disable_storage_change_integration=None,
                    print_input=None, timeseries=None, perioddata=None, filename=None, pname=None,
                    parent_file=None)
```

Bases: `flopY.mf6.mfpackage.MFPackage`

ModflowUtltsv defines a tvs package within a utl model.

**Parameters**

- **model** (`MFPackage`) – Model that this package is a part of. Package is automatically added to model when it is initialized.
- **loading\_package** (*bool*) – Do not set this parameter. It is intended for debugging and internal processing purposes only.
- **disable\_storage\_change\_integration** (*boolean*) –
  - `disable_storage_change_integration` (*boolean*) keyword that deactivates inclusion of storage derivative terms in the STO package matrix formulation. In the absence of this keyword (the default), the groundwater storage formulation will be modified to correctly adjust heads based on transient variations in stored water volumes arising from changes to SS and SY properties.
- **print\_input** (*boolean*) –
  - `print_input` (*boolean*) keyword to indicate that information for each change to a storage property in a cell will be written to the model listing file.
- **timeseries** (*{varname:data}* or *timeseries data*) –
  - Contains data for the ts package. Data can be stored in a dictionary containing data for the ts package with variable names as keys and package data as values. Data just for the timeseries variable is also acceptable. See ts package documentation for more information.
- **perioddata** (*[cellid, tvssetting]*) –
  - `cellid` (*(integer, ...)*) is the cell identifier, and depends on the type of grid that is used for the simulation. For a structured grid that uses the DIS input file, `CELLID` is the layer, row, and column. For a grid that uses the DISV input file, `CELLID` is the layer and `CELL2D` number. If the model uses the unstructured discretization (DISU) input file, `CELLID` is the node number for the cell. This argument is an index variable, which means that it should be treated as zero-based when working with FloPy and Python. FloPy will automatically subtract one when loading index variables and add one when writing index variables.
  - `tvssetting` (*keystring*) line of information that is parsed into a property name keyword and values. Property name keywords that can be used to start the TVSSETTING string include: SS and SY.
 

`ss` *[[double]]*

    - \* `ss` (*double*) is the new value to be assigned as the cell's specific storage (or storage coefficient if the `STORAGECOEFFICIENT` STO package option is specified) from the start of the specified stress period, as per SS in the STO package. Specific storage values must be greater than or equal to 0. If the `OPTIONS` block includes a TS6 entry (see the "Time-Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

sy [[double]]

\* sy (double) is the new value to be assigned as the cell's specific yield from the start of the specified stress period, as per SY in the STO package. Specific yield values must be greater than or equal to 0. If the OPTIONS block includes a TS6 entry (see the "Time-Variable Input" section), values can be obtained from a time series by entering the time-series name in place of a numeric value.

- **filename** (*String*) – File name for this package.
- **pname** (*String*) – Package name for this package.
- **parent\_file** (*MFPackage*) – Parent package file that references this package. Only needed for utility packages (mfutl\*). For example, mfutllaktab package must have a mfgwflak package parent\_file.

```
dfn = [['header'], ['block options', 'name disable_storage_change_integration',  
'type keyword', 'reader urword', 'optional true'], ['block options', 'name  
print_input', 'type keyword', 'reader urword', 'optional true'], ['block options',  
'name ts_filerecord', 'type record ts6 filein ts6_filename', 'shape', 'reader  
urword', 'tagged true', 'optional true', 'construct_package ts', 'construct_data  
timeseries', 'parameter_name timeseries'], ['block options', 'name ts6', 'type  
keyword', 'shape', 'in_record true', 'reader urword', 'tagged true', 'optional  
false'], ['block options', 'name filein', 'type keyword', 'shape', 'in_record true',  
'reader urword', 'tagged true', 'optional false'], ['block options', 'name  
ts6_filename', 'type string', 'preserve_case true', 'in_record true', 'reader  
urword', 'optional false', 'tagged false'], ['block period', 'name iper', 'type  
integer', 'block_variable True', 'in_record true', 'tagged false', 'shape', 'valid',  
'reader urword', 'optional false'], ['block period', 'name perioddata', 'type  
recarray cellid tvssetting', 'shape', 'reader urword'], ['block period', 'name  
cellid', 'type integer', 'shape (ncellidim)', 'tagged false', 'in_record true',  
'reader urword'], ['block period', 'name tvssetting', 'type keystring ss sy',  
'shape', 'tagged false', 'in_record true', 'reader urword'], ['block period', 'name  
ss', 'type double precision', 'shape', 'tagged true', 'in_record true', 'reader  
urword', 'time_series true'], ['block period', 'name sy', 'type double precision',  
'shape', 'tagged true', 'in_record true', 'reader urword', 'time_series true']]
```

```
dfn_file_name = 'utl-tvs.dfn'
```

```
package_abbr = 'utltvs'
```

```
perioddata = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
ts_filerecord = <flop.mf6.data.mfdatautil.ListTemplateGenerator object>
```

```
class UtltvsPackages(model, parent, pkg_type, filerecord, package=None, package_class=None)
```

Bases: [flop.mf6.mfpkg.MFChildPackages](#)

UtltvsPackages is a container class for the ModflowUtltvs class.

**initialize()**

Initializes a new ModflowUtltvs package removing any sibling child packages attached to the same parent package. See ModflowUtltvs init documentation for definition of parameters.

**append\_package()**

Adds a new ModflowUtltvs package to the container. See ModflowUtltvs init documentation for definition of parameters.

**append\_package**(*disable\_storage\_change\_integration=None, print\_input=None, timeseries=None, perioddata=None, filename=None, pname=None*)

```

initialize(disable_storage_change_integration=None, print_input=None, timeseries=None,
           perioddata=None, filename=None, pname=None)

package_abbr = 'utlvtspackages'

```

## MODFLOW 6 Utility Functions

MODFLOW 6 has several utility functions that can be used to process MODFLOW 6 results.

Contents:

### `flopy.mf6.utils.binaryfile_utils` module

**class** `MFOutput`(*mfdict*, *path*, *key*)

Bases: object

Wrapper class for Binary Arrays. This class enables directly getting slices from the binary output. It is intended to be called from the `__getitem__` method of the `SimulationDict()` class. Implemented to conserve memory.

#### Parameters

- **path** (binary file path location) –
- **mfdict** (`SimulationDict()` object) –
- **key** (dict key ex. ('flow15', 'CBC', 'FLOW RIGHT FACE')) –

#### Returns

- Xarray of [n,n,n,n] dimension
- Usage
- —
- `>>> val = MFOutput(mfdict, path, key)`
- `>>> return val.data`
- User interaction
- —————
- `>>> data[(‘flow15’, ‘CBC’, ‘FLOW RIGHT FACE’)][(0,1,:)]`
- or
- `>>> data[(‘flow15’, ‘CBC’, ‘FLOW RIGHT FACE’)]`

**class** `MFOutputRequester`(*mfdict*, *path*, *key*)

Bases: object

`MFOutputRequest` class is a helper function to enable the user to query binary data from the `SimulationDict()` object on the fly without actually storing it in the `SimulationDict()` object.

**mfdict:** dict local instance of the `SimulationDict()` object

**path:** pointer to the `MFSimulationPath` object

**key:** tuple user requested data key

**`MFOutputRequester.querybinarydata`** returns: Xarray object

```

>>> data = MFOutputRequester(mfdict, path, key)
>>> data.querybinarydata

```

```
static getkeys(mfdict, path, print_keys=True)
```

## flopY.mf6.utils.binarygrid\_util module

Module to read MODFLOW 6 binary grid files (\*.grb) that define the model grid binary output files. The module contains the MfGrdFile class that can be accessed by the user.

```
class MfGrdFile(filename, precision='double', verbose=False)
```

Bases: `flopY.utils.utils_def.FlopYBinaryData`

The MfGrdFile class.

### Parameters

- **filename** (*str*) – Name of the MODFLOW 6 binary grid file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.
- **verbose** (*bool*) – Write information to standard output. Default is False.

## Notes

The MfGrdFile class provides simple ways to retrieve data from binary MODFLOW 6 binary grid files (.grb). The binary grid file contains data that can be used for post processing MODFLOW 6 model results. For example, the ia and ja arrays for a model grid.

## Examples

```
>>> import flopY
>>> gobj = flopY.utils.MfGrdFile('test.dis.grb')
```

### property angrot

Model grid rotation angle. None if not defined in the MODFLOW 6 grid file.

**Returns** angrot

**Return type** float

### property bot

Bottom of the model cells.

**Returns** bot

**Return type** ndarray of floats

### property cell2d

cell2d data for a DISV grid. None for DIS and DISU grids.

**Returns** cell2d

**Return type** list of lists

### property cellcenters

Cell centers (x,y).

**Returns** cellcenters

**Return type** ndarray of floats

### property delc

Cell size in the column direction (x-direction). None if not defined in the MODFLOW 6 grid file.

**Returns** `dele`

**Return type** ndarray of floats

**property** `delr`

Cell size in the row direction (y-direction). None if not defined in the MODFLOW 6 grid file.

**Returns** `delr`

**Return type** ndarray of floats

**property** `grid_type`

Grid type defined in the MODFLOW 6 grid file.

**Returns** `grid_type`

**Return type** str

**property** `ia`

CRS row pointers for the model grid.

**Returns** `ia`

**Return type** ndarray of ints

**property** `iavert`

CRS cell pointers for cell vertices.

**Returns** `iavert`

**Return type** ndarray of ints

**property** `idomain`

IDOMAIN for the model grid. None if not defined in the MODFLOW 6 grid file.

**Returns** `idomain`

**Return type** ndarray of ints

**property** `iverts`

Vertex numbers comprising each cell for every cell in model grid.

**Returns** `iverts`

**Return type** list of lists of ints

**property** `ja`

CRS column pointers for the model grid.

**Returns** `ja`

**Return type** ndarray of ints

**property** `javert`

CRS vertex numbers for the vertices comprising each cell.

**Returns** `javerts`

**Return type** ndarray of ints

**property** `modelgrid`

Model grid object.

**Returns** `modelgrid`

**Return type** *StructuredGrid*, *VertexGrid*, *UnstructuredGrid*

**property ncells**

Number of cells.

**Returns ncells**

**Return type** int

**property ncol**

Number of columns. None for DISV and DISU grids.

**Returns ncol**

**Return type** int

**property ncpl**

Number of cells per layer. None for DISU grids.

**Returns ncpl**

**Return type** int

**property nja**

Number of non-zero entries in the CRS column pointer vector.

**Returns nja**

**Return type** int

**property nlay**

Number of layers. None for DISU grids.

**Returns nlay**

**Return type** int

**property nodes**

Number of nodes.

**Returns nodes**

**Return type** int

**property nrow**

Number of rows. None for DISV and DISU grids.

**Returns nrow**

**Return type** int

**property shape**

Shape of the model grid (tuple).

**Returns shape**

**Return type** tuple

**property top**

Top of the model cells in the upper model layer for DIS and DISV grids. Top of the model cells for DISU grids.

**Returns top**

**Return type** ndarray of floats

**property verts**

x,y location of each vertex that defines the model grid.

**Returns verts**

**Return type** ndarray of floats

**property xorigin**

x-origin of the model grid. None if not defined in the MODFLOW 6 grid file.

**Returns xorigin**

**Return type** float

**property yorigin**

y-origin of the model grid. None if not defined in the MODFLOW 6 grid file.

**Returns yorigin**

**Return type** float

## flop.mf6.utils.mfobservation module

**class MFObservation**(*mfdict, path, key*)

Bases: object

Wrapper class to request the MFObservation object: Class is called by the MFSimulation.SimulationDict() class and is not called by the user

mfdict: (dict) the sim.simulation\_dict.mfdict object for the flop project path: (object) the path object detailing model names and paths key: (tuple, strings) user supplied dictionary key to request observation utility data

Returns: ——— self.data: (xarray) array of observations

**class MFObservationRequester**(*mfdict, path, key, \*\*kwargs*)

Bases: object

Wrapper class for MFObservation.Observations. Class checks which observation data is available, and creates a dictionary key to access the set of observation data from the SimulationDict()

**static getkeys**(*mfdict, path*)

**class Observations**(*fi*)

Bases: object

Simple class to extract and view Observation files for Uzf models (possibly all obs/hobs)?

fi = (string) name of the observation binary output file

**get\_data(): (np.array) returns array of observation data** text = (str) specific modflow record name contained in Obs.out file idx = (int), (slice(start, stop)) integer or slice of data to be returned. corresponds to kstp\*kper - 1 totim = (float) model time value to return data from

list\_records(): prints a list of all valid record names contained within the Obs.out file get\_times(): (list) returns list of time values contained in Obs.out get\_nrecords(): (int) returns number of records get\_ntimes(): (int) returns number of times get\_nobs(): (int) returns total number of observations (ntimes \* nrecords)

**get\_data**(*key=None, idx=None, totim=None*)

Method to request and return array of data from an Observation output file

### Parameters

- **key** ((str) dictionary key for a specific observation contained within) – the observation file (optional)
- **idx** ((int) time index (optional)) –
- **totim** ((float) simulation time (optional)) –

**Returns data**

**Return type** (list) observation file data in list

**get\_dataframe**(*keys=None, idx=None, totim=None, start\_datetime=None, timeunit='D'*)

Creates a pandas dataframe object from the observation data, useful backend if the user does not like the x-array format!

**Parameters**

- **keys** ((string) sting of dictionary/observation keys separated by comma.) – (optional)
- **idx** ((int) time index location (optional)) –
- **totim** ((float) simulation time (optional)) –
- **start\_datetime** ((string) format is 'dd/mm/yyyy' or) – 'dd/mm/yyyy hh:mm:ss' (optional)
- **timeunit** ((string) specifies the time unit associated with totim when) – setting a datetime

**Return type** pd.DataFrame

**get\_nobs**()

**get\_nrecords**()

**get\_ntimes**()

**get\_obs\_data**(*key=None, idx=None, totim=None*)

Method to request observation output data as an x-array :param key: within the observation file (optional)  
:type key: (string) dictionary key for a specific observation contained :param idx: :type idx: (int) time index (optional) :param totim: :type totim: (float) simulation time (optional)

**Returns** xarray.DataArray

**Return type** (NxN) dimensions are totim, header == keys\*

**get\_times**()

**list\_records**()

**try\_float**(*data*)

## **flopy.mf6.utils.output\_util module**

**class MF6Output**(*obj*)

Bases: object

A class that uses meta programming to get output

**Parameters** **obj** (*PackageInterface object*) –

**property csv\_names**

Method to get csv file names

**Return type** list

**methods**()

Method that returns a list of available method calls

**Return type** list

**property obs\_names**

Method to get obs file names



**Return type** list

## flopypy.mf6.utils.postprocessing module

**get\_residuals**(*flowja*, *grb\_file=None*, *ia=None*, *ja=None*, *shape=None*, *verbose=False*)

Get the residual from the MODFLOW 6 flowja flows. The residual is stored in the diagonal position of the flowja vector.

### Parameters

- **flowja** (*ndarray*) – flowja array for a structured MODFLOW 6 model
- **grbfile** (*str*) – MODFLOW 6 binary grid file path
- **ia** (*list or ndarray*) – CRS row pointers. Only required if grb\_file is not provided.
- **ja** (*list or ndarray*) – CRS column pointers. Only required if grb\_file is not provided.
- **shape** (*tuple*) – shape of returned residual. A flat array is returned if shape is None and grbfile is None.
- **verbose** (*bool*) – Write information to standard output

**Returns** **residual** – Residual for each cell

**Return type** ndarray

**get\_structured\_faceflows**(*flowja*, *grb\_file=None*, *ia=None*, *ja=None*, *verbose=False*)

Get the face flows for the flow right face, flow front face, and flow lower face from the MODFLOW 6 flowja flows. This method can be useful for building face flow arrays for MT3DMS, MT3D-USGS, and RT3D. This method only works for a structured MODFLOW 6 model.

### Parameters

- **flowja** (*ndarray*) – flowja array for a structured MODFLOW 6 model
- **grbfile** (*str*) – MODFLOW 6 binary grid file path
- **ia** (*list or ndarray*) – CRS row pointers. Only required if grb\_file is not provided.
- **ja** (*list or ndarray*) – CRS column pointers. Only required if grb\_file is not provided.
- **verbose** (*bool*) – Write information to standard output

### Returns

- **frf** (*ndarray*) – right face flows
- **fff** (*ndarray*) – front face flows
- **flf** (*ndarray*) – lower face flows

**flop.mf6.utils.reference module**

Module spatial referencing for flop model objects

```
class SpatialReference(delr=1.0, delc=1.0, xvdict=None, yvdict=None, lenuni=1, nlay=1, xul=None,
                        yul=None, xadj=0.0, yadj=0.0, rotation=0.0, proj4_str=None, distype='structured')
```

Bases: object

A dynamic inheritance class that locates a gridded model in space

**delr** [numpy ndarray] the model discretization delr vector

**delc** [numpy ndarray] the model discretization delc vector

**lenuni** [int] the length units flag from the discretization package

**xul** [float] the x coordinate of the upper left corner of the grid

**yul** [float] the y coordinate of the upper left corner of the grid

**rotation** [float] the counter-clockwise rotation (in degrees) of the grid

**proj4\_str: str** a PROJ4 string that identifies the grid in space. warning: case sensitive!

**xadj** [float] vertex grid: x vertex adjustment factor

**yadj** [float] vertex grid: y vertex adjustment factor

**xvdict: dict** dictionary of x-vertices by cellnum ex. {0: (0,1,1,0)}

**yvdict: dict** dictionary of y-vertices by cellnum ex. {0: (1,1,0,0)}

**distype: str** model grid discretization type

```
class StructuredSpatialReference(delr=1.0, delc=1.0, lenuni=1, nlay=1, xul=None, yul=None,
                                  rotation=0.0, proj4_str=None, **kwargs)
```

Bases: object

a simple class to locate the model grid in x-y space

**Parameters**

- **delr** (*numpy ndarray*) – the model discretization delr vector
- **delc** (*numpy ndarray*) – the model discretization delc vector
- **lenuni** (*int*) – the length units flag from the discretization package
- **xul** (*float*) – the x coordinate of the upper left corner of the grid
- **yul** (*float*) – the y coordinate of the upper left corner of the grid
- **rotation** (*float*) – the counter-clockwise rotation (in degrees) of the grid
- **proj4\_str** (*str*) – a PROJ4 string that identifies the grid in space. warning: case sensitive!

**xedge**

array of column edges

**Type** ndarray

**yedge**

array of row edges

**Type** ndarray

**xgrid**

numpy meshgrid of xedges

**Type** ndarray

**ygrid**  
numpy meshgrid of yedges

**Type** ndarray

**xcenter**  
array of column centers

**Type** ndarray

**ycenter**  
array of row centers

**Type** ndarray

**xcentergrid**  
numpy meshgrid of column centers

**Type** ndarray

**ycentergrid**  
numpy meshgrid of row centers

**Type** ndarray

## Notes

xul and yul can be explicitly (re)set after SpatialReference instantiation, but only before any of the other attributes and methods are accessed

**property attribute\_dict**

**classmethod from\_gridspec**(*gridspec\_file*, *lenuni=0*)

**classmethod from\_namfile\_header**(*namefile*)

**get\_extent**()

Get the extent of the rotated and offset grid

Return (xmin, xmax, ymin, ymax)

**get\_grid\_lines**()

get the grid lines as a list

**get\_vertices**(*i, j*)

**get\_xcenter\_array**()

Return a numpy one-dimensional float array that has the cell center x coordinate for every column in the grid in model space - not offset or rotated.

**get\_xedge\_array**()

Return a numpy one-dimensional float array that has the cell edge x coordinates for every column in the grid in model space - not offset or rotated. Array is of size (ncol + 1)

**get\_ycenter\_array**()

Return a numpy one-dimensional float array that has the cell center x coordinate for every row in the grid in model space - not offset or rotated.

**get\_yedge\_array**()

Return a numpy one-dimensional float array that has the cell edge y coordinates for every row in the grid in model space - not offset or rotated. Array is of size (nrow + 1)

**interpolate**(*a*, *xi*, *method*='nearest')

Use the griddata method to interpolate values from an array onto the points defined in xi. For any values outside of the grid, use 'nearest' to find a value for them.

**Parameters**

- **a** (*numpy.ndarray*) – array to interpolate from. It must be of size nrow, ncol
- **xi** (*numpy.ndarray*) – array containing x and y point coordinates of size (npts, 2). xi also works with broadcasting so that if a is a 2d array, then xi can be passed in as (xgrid, ygrid).
- **method** ({'linear', 'nearest', 'cubic'}) – method to use for interpolation (default is 'nearest')

**Returns** **b** – array of size (npts)

**Return type** *numpy.ndarray*

**property** **ncol**

**property** **nrow**

**reset**(\*\**kwargs*)

**static rotate**(*x*, *y*, *theta*, *xorigin*=0.0, *yorigin*=0.0)

Given x and y array-like values calculate the rotation about an arbitrary origin and then return the rotated coordinates. theta is in degrees.

**set\_spatialreference**(*xul*=None, *yul*=None, *rotation*=0.0)

set spatial reference - can be called from model instance

**write\_gridSpec**(*filename*)

write a PEST-style grid specification file

**property** **xcenter**

**property** **xcentergrid**

**property** **xedge**

**property** **xgrid**

**property** **ycenter**

**property** **ycentergrid**

**property** **yedge**

**property** **ygrid**

**class VertexSpatialReference**(*xvdict*=None, *yvdict*=None, *nlay*=1, *xadj*=0, *yadj*=0, *rotation*=0.0, *lenuni*=1.0, *proj4\_str*=None, \*\**kwargs*)

Bases: object

a simple class to locate the model grid in x-y space

**Parameters**

- **xvdict** (*dictionary*) – dictionary of x-vertices {1: (0,1,1,0)}
- **yvdict** (*dictionary*) – dictionary of y-vertices {1: (1,0,1,0)}
- **lenuni** (*int*) – the length units flag from the discretization package
- **xadj** (*float*) – the x coordinate of the upper left corner of the grid
- **yadj** (*float*) – the y coordinate of the upper left corner of the grid

- **rotation** (*float*) – the counter-clockwise rotation (in degrees) of the grid
- **proj4\_str** (*str*) – a PROJ4 string that identifies the grid in space. warning: case sensitive!

**xedge**

array of column edges

**Type** ndarray**yedge**

array of row edges

**Type** ndarray**xgrid**

numpy meshgrid of xedges

**Type** ndarray**ygrid**

numpy meshgrid of yedges

**Type** ndarray**xcenter**

array of column centers

**Type** ndarray**ycenter**

array of row centers

**Type** ndarray**xcentergrid**

numpy meshgrid of column centers

**Type** ndarray**ycentergrid**

numpy meshgrid of row centers

**Type** ndarray**Notes**

xadj and yuadj can be explicitly (re)set after SpatialReference instantiation, but only before any of the other attributes and methods are accessed

**classmethod** **from\_namfile\_header**(*namefile*)

**get\_extent**()

Get the extent of the rotated and offset grid

Return (xmin, xmax, ymin, ymax)

**property** **ncpl**

**static** **rotate**(*x, y, theta, xorigin=0.0, yorigin=0.0*)

Given x and y array-like values calculate the rotation about an arbitrary origin and then return the rotated coordinates. theta is in degrees.

**set\_spatialreference**(*xadj=0.0, yadj=0.0, rotation=0.0*)

set spatial reference - can be called from model instance xadj, yadj should be named xadj, yadj since they represent an adjustment factor

property **xarr**

property **xcenter\_array**

property **xdict**

property **xydict**

property **yarr**

property **ycenter\_array**

property **ydict**

### flop.mf6.utils.lakpak\_utils module

**get\_lak\_connections**(*modelgrid, lake\_map, idomain=None, bedleak=None*)

Function to create lake package connection data from a zero-based integer array of lake numbers. If the shape of lake number array is equal to (nrow, ncol) or (ncpl) then the lakes are on top of the model and are vertically connected to cells at the top of the model. Otherwise the lakes are embedded in the grid.

TODO: implement embedded lakes for VertexGrid

TODO: add support for UnstructuredGrid

#### Parameters

- **modelgrid** (*StructuredGrid, VertexGrid*) – model grid
- **lake\_map** (*MaskedArray, ndarray, list, tuple*) – location and zero-based lake number for lakes in the model domain. If lake\_map is of size (nrow, ncol) or (ncpl) lakes are located on top of the model and vertically connected to cells in model layer 1. If lake\_map is of size (nlay, nrow, ncol) or (nlay, ncpl) lakes are embedded in the model domain and horizontal and vertical lake connections are defined.
- **idomain** (*int or ndarray*) – location of inactive cells, which are defined with a zero value. If a ndarray is passed it must be of size (nlay, nrow, ncol) or (nlay, ncpl).
- **bedleak** (*ndarray, list, tuple, float*) – bed leakance for lakes in the model domain. If bedleak is a float the same bed leakance is applied to each lake connection in the model. If bedleak is of size (nrow, ncol) or (ncpl) then all lake connections for the cellid are given the same bed leakance value. If bedleak is None, lake conductance is only a function of aquifer properties for all lakes. Can also pass mixed values as list or ndarray of size (nrow, ncol) or (ncpl) with floats and 'none' strings.

#### Returns

- **idomain** (*ndarray*) – idomain adjusted to inactivate cells with lakes
- **connection\_dict** (*dict*) – dictionary with the zero-based lake number keys and number of connections in a lake values
- **connectiondata** (*list of lists*) – connectiondata block for the lake package

## MODFLOW 6 Data

FloPy for MODFLOW 6 data objects (MFDataArray, MFDataList, MFDataScalar) are automatically constructed by FloPy when you construct a package. These data objects provide an interface for getting MODFLOW 6 data in different formats and setting MODFLOW 6 data.

Contents:

### `flopy.mf6.data.mfdataarray` module

**class** `MFArray`(*sim\_data*, *model\_or\_sim*, *structure*, *data=None*, *enable=True*, *path=None*, *dimensions=None*, *block=None*)

Bases: `flopy.mf6.data.mfdata.MFMultiDimVar`

Provides an interface for the user to access and update MODFLOW array data. MFArray objects are not designed to be directly constructed by the end user. When a FloPy for MODFLOW 6 package object is constructed, the appropriate MFArray objects are automatically built.

#### Parameters

- **sim\_data** (`MFSimulationData`) – data contained in the simulation
- **structure** (`MFDataStructure`) – describes the structure of the data
- **data** (*list or ndarray*) – actual data
- **enable** (*bool*) – enable/disable the array
- **path** (*tuple*) – path in the data dictionary to this MFArray
- **dimensions** (`MFDataDimensions`) – dimension information related to the model, package, and array

#### property data

Returns array data. Calls `get_data` with default parameters.

#### property data\_type

Type of data (`DataType`) stored in the array

#### property dtype

Type of data (`numpy.dtype`) stored in the array

**get\_data**(*layer=None*, *apply\_mult=False*, *\*\*kwargs*)

Returns the data associated with layer “layer\_num”. If “layer\_num” is None, returns all data.

**Parameters** **layer\_num** (*int*) –

**Returns** **data** – Array data in an ndarray

**Return type** ndarray

**get\_file\_entry**(*layer=None*, *ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Returns a string containing the data in layer “layer” formatted for a MODFLOW 6 file. For unlayered data do not pass in “layer”.

#### Parameters

- **layer** (*int*) – The layer to return file entry for.
- **ext\_file\_action** (`ExtFileAction`) – How to handle external paths.

**Returns** file entry

**Return type** str

**has\_data**(*layer=None*)

Returns whether layer “layer\_num” has any data associated with it.

**Parameters** **layer\_num** (*int*) – Layer number to check for data. For unlayered data do not pass anything in

**Returns** **has data** – Returns if there is data.

**Return type** bool

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from first\_line (the first line of data) and open file file\_handle which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file. This method is for internal flop use and is not intended for the end user.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data in this array.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data for this array
- **block\_header** (*MFBBlockHeader*) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** (*MFComment*) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**Returns**

- **more data** (*bool*),
- **next data line** (*str*)

**make\_layered**()

Changes the data to be stored by layer instead of as a single array.

**new\_simulation**(*sim\_data*)

Initialize MFArray object for a new simulation

**Parameters** **sim\_data** (*MFSimulationData*) – Data dictionary containing simulation data.

**plot**(*filename\_base=None, file\_extension=None, mflay=None, fignum=None, title=None, \*\*kwargs*)

Plot 3-D model input data

**Parameters**

- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is ‘png’)
- **mflay** (*int*) – MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)
- **\*\*kwargs** (*dict*) –
  - axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)



**pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)

**colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)

**inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)

**contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**Returns out** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

#### property plottable

If the array is plottable

#### set\_data(data, multiplier=None, layer=None)

Sets the contents of the data at layer *layer* to *data* with multiplier *multiplier*. For unlayered data do not pass in *layer*. Data can have the following formats: 1) ndarray - numpy ndarray containing all of the data 2) [data] - python list containing all of the data 3) val - a single constant value to be used for all of the data 4) {'filename':filename, 'factor':fct, 'iprn':print, 'data':data} - dictionary defining external file information 5) {'data':data, 'factor':fct, 'iprn':print} - dictionary defining internal information. Data that is layered can also be set by defining a list with a length equal to the number of layers in the model. Each layer in the list contains the data as defined in the formats above:

```
[layer_1_val,    [layer_2_array_vals],    {'filename':file_with_layer_3_data,    'factor':fct,
'iprn':print}]
```

#### Parameters

- **data** (*ndarray/list*) – An ndarray or nested lists containing the data to set.
- **multiplier** (*float*) – Multiplier to apply to data
- **layer** (*int*) – Data layer that is being set

#### set\_layered\_data(layered\_data)

Sets whether this MFArry supports layered data

**Parameters** **layered\_data** (*bool*) – Whether data is layered or not.

#### store\_as\_external\_file(external\_file\_path, layer=None, binary=False, replace\_existing\_external=True, check\_data=True)

Stores data from layer *layer* to an external file at *external\_file\_path*. For unlayered data do not pass in *layer*. If layer is not specified all layers will be stored with each layer as a separate file. If *replace\_existing\_external* is set to False, this method will not do anything if the data is already in an external file.

#### Parameters

- **external\_file\_path** (*str*) – Path to external file

- **layer** (*int*) – Which layer to store in external file, *None* value stores all layers.
- **binary** (*bool*) – Store data in a binary file
- **replace\_existing\_external** (*bool*) – Whether to replace an existing external file.
- **check\_data** (*bool*) – Verify data prior to storing

**store\_internal** (*layer=None, check\_data=True*)

Stores data from layer *layer* internally. For unlayered data do not pass in *layer*. If layer is not specified all layers will be stored internally

#### Parameters

- **layer** (*int*) – Which layer to store in external file, *None* value stores all layers.
- **check\_data** (*bool*) – Verify data prior to storing

**supports\_layered**()

Returns whether this MFArry supports layered data

**Returns layered data supported** – Whether or not this data object supports layered data

**Return type** bool

**class MFTransientArray** (*sim\_data, model\_or\_sim, structure, enable=True, path=None, dimensions=None, block=None*)

Bases: [flop.mf6.data.mfdataarray.MFArry](#), [flop.mf6.data.mfdata.MFTransient](#)

Provides an interface for the user to access and update MODFLOW transient array data. MFTransientArray objects are not designed to be directly constructed by the end user. When a FloPy for MODFLOW 6 package object is constructed, the appropriate MFArry objects are automatically built.

#### Parameters

- **sim\_data** ([MFSimulationData](#)) – data contained in the simulation
- **structure** ([MFDataStructure](#)) – describes the structure of the data
- **data** (*list or ndarray*) – actual data
- **enable** (*bool*) – enable/disable the array
- **path** (*tuple*) – path in the data dictionary to this MFArry
- **dimensions** ([MFDataDimensions](#)) – dimension information related to the model, package, and array

## Examples

**add\_transient\_key** (*transient\_key*)

Adds a new transient time allowing data for that time to be stored and retrieved using the key *transient\_key*. This method is intended for internal library usage only.

**Parameters transient\_key** (*int*) – Zero-based stress period

**property data\_type**

Type of data (DataType) stored in the array

**get\_data** (*layer=None, apply\_mult=True, \*\*kwargs*)

Returns the data associated with stress period key *layer*. If *layer* is None, returns all data for time *layer*.

#### Parameters

- **layer** (*int*) – Zero-based stress period of data to return

- **apply\_mult** (*bool*) – Whether to apply multiplier to data prior to returning it

**get\_file\_entry**(*key=0, ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Returns a string containing the data in stress period “key”.

**Parameters**

- **key** (*int*) – The stress period to return file entry for.
- **ext\_file\_action** ([ExtFileAction](#)) – How to handle external paths.

**Returns** file entry

**Return type** str

**has\_data**(*layer=None*)

Returns whether layer “layer\_num” has any data associated with it.

**Parameters** **layer\_num** (*int*) – Layer number to check for data. For unlayered data do not pass anything in

**Returns** **has data** – Returns if there is data.

**Return type** bool

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from first\_line (the first line of data) and open file handle which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file. This method is for internal flop use and is not intended to be called by the end user.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data in this array.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data for this array
- **block\_header** ([MFBlockHeader](#)) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** ([MFComment](#)) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**Returns**

- **more data** (*bool*,)
- **next data line** (*str*)

**plot**(*kper=None, filename\_base=None, file\_extension=None, mflay=None, fignum=None, \*\*kwargs*)

Plot transient array model input data

**Parameters**

- **transient2d** (*flop.utils.util\_array.Transient2D object*) –
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is ‘png’)
- **\*\*kwargs** (*dict*) –

**axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)

**pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)

**colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)

**inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)

**contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**kper** [str] MODFLOW zero-based stress period number to return. If kper='all' then data for all stress period will be extracted. (default is zero).

**Returns axes** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

**remove\_transient\_key**(*transient\_key*)

Removes a new transient time *transient\_key* and any data stored at that time. This method is intended for internal library usage only.

**Parameters transient\_key** (*int*) – Zero-based stress period

**set\_data**(*data*, *multiplier=None*, *layer=None*, *key=None*)

Sets the contents of the data at layer *layer* and time *key* to *data* with multiplier *multiplier*. For unlayered data do not pass in *layer*.

**Parameters**

- **data** (*dict*, *ndarray*, *list*) – Data being set. Data can be a dictionary with keys as zero-based stress periods and values as the data. If data is an ndarray or list of lists, it will be assigned to the the stress period specified in *key*. If any is set to None, that stress period of data will be removed.
- **multiplier** (*int*) – multiplier to apply to data
- **layer** (*int*) – Layer of data being set. Keep default of None of data is not layered.
- **key** (*int*) – Zero based stress period to assign data too. Does not apply if *data* is a dictionary.

**store\_as\_external\_file**(*external\_file\_path*, *layer=None*, *binary=False*, *replace\_existing\_external=True*, *check\_data=True*)

Stores data from layer *layer* to an external file at *external\_file\_path*. For unlayered data do not pass in *layer*. If layer is not specified all layers will be stored with each layer as a separate file. If *replace\_existing\_external* is set to False, this method will not do anything if the data is already in an external file.

**Parameters**

- **external\_file\_path** (*str*) – Path to external file
- **layer** (*int*) – Which layer to store in external file, *None* value stores all layers.
- **binary** (*bool*) – Store data in a binary file
- **replace\_existing\_external** (*bool*) – Whether to replace an existing external file.
- **check\_data** (*bool*) – Verify data prior to storing

**store\_internal** (*layer=None, check\_data=True*)

Stores data from layer *layer* internally. For unlayered data do not pass in *layer*. If layer is not specified all layers will be stored internally.

#### Parameters

- **layer** (*int*) – Which layer to store internally file, *None* value stores all layers.
- **check\_data** (*bool*) – Verify data prior to storing

### flop.mf6.data.mfdatalist module

**class MFList** (*sim\_data, model\_or\_sim, structure, data=None, enable=True, path=None, dimensions=None, package=None, block=None*)

Bases: flop.mf6.data.mfdata.MFMultiDimVar, flop.database.DataListInterface

Provides an interface for the user to access and update MODFLOW list data. MFList objects are not designed to be directly constructed by the end user. When a flop for MODFLOW 6 package object is constructed, the appropriate MFList objects are automatically built.

#### Parameters

- **sim\_data** (*MFSimulationData*) – data contained in the simulation
- **structure** (*MFDataStructure*) – describes the structure of the data
- **data** (*list or ndarray*) – actual data
- **enable** (*bool*) – enable/disable the array
- **path** (*tuple*) – path in the data dictionary to this MFArray
- **dimensions** (*MFDataDimensions*) – dimension information related to the model, package, and array

**append\_data** (*data*)

Appends “data” to the end of this list. Assumes data is in a format that can be appended directly to a numpy recarray.

**Parameters** *data* (*list(tuple)*) – Data to append.

**append\_list\_as\_record** (*record*)

Appends the list *record* as a single record in this list’s recarray. Assumes “data” has the correct dimensions.

**Parameters** *record* (*list*) – List to be appended as a single record to the data’s existing recarray.

**property data\_type**

Type of data (*DataType*) stored in the list

**property dtype**

Type of data (*numpy.dtype*) stored in the list

**get\_data**(*apply\_mult=False, \*\*kwargs*)

Returns the list's data.

**Parameters** **apply\_mult** (*bool*) – Whether to apply a multiplier.

**Returns** **data**

**Return type** recarray

**get\_file\_entry**(*ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Returns a string containing the data formatted for a MODFLOW 6 file.

**Parameters** **ext\_file\_action** (*ExtFileAction*) – How to handle external paths.

**Returns** **file entry**

**Return type** str

**has\_data**(*key=None*)

Returns whether this MFList has any data associated with it.

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from *first\_line* (the first line of data) and open file *file\_handle* which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file. This method was only designed for internal FloPy use and is not recommended for end users.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data in this list.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data for this list
- **block\_header** (*MFBBlockHeader*) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** (*MFComment*) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**Returns**

- **more data** (*bool*),
- **next data line** (*str*)

**new\_simulation**(*sim\_data*)

Initialize MFList object for a new simulation.

**Parameters** **sim\_data** (*MFSimulationData*) – Simulation data object for the simulation containing this data.

**property package**

Package object that this data belongs to.

**plot**(*key=None, names=None, filename\_base=None, file\_extension=None, mflay=None, \*\*kwargs*)

Plot boundary condition (MfList) data

**Parameters**

- **key** (*str*) – MfList dictionary key. (default is None)
- **names** (*list*) – List of names for figure titles. (default is None)

- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if `file_name_base` is not `None`. (default is `None`)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for `savefig()`. Only used if `filename_base` is not `None`. (default is `'png'`)
- **mflay** (*int*) – MODFLOW zero-based layer number to return. If `None`, then all layers will be included. (default is `None`)
- **\*\*kwargs** (*dict*) –
  - axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If `axes=None` axes will be generated. (default is `None`)
  - pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is `True`)
  - colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if `pcolor=True`. (default is `False`)
  - inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is `True`)
  - contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is `False`)
  - clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if `contour=True`. (default is `False`)
  - grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is `False`)
  - masked\_values** [list] List of unique values to be excluded from the plot.

**Returns** **out** – Empty list is returned if `filename_base` is not `None`. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

#### property **plottable**

If this list data is plottable

#### **search\_data**(*search\_term*, *col=None*)

Searches the list data at column “col” for “search\_term”. If `col` is `None` `search_data` searches the entire list.

#### Parameters

- **search\_term** (*str*) – String to search for
- **col** (*int*) – Column number to search

#### **set\_data**(*data*, *autofill=False*, *check\_data=True*)

Sets the contents of the data to “data” with. Data can have the following formats:

- 1) recarray - recarray containing the datalist
- 2) [(line\_one), (line\_two), ...] - list where each line of the datalist is a tuple within the list
- 3) {'filename': filename, factor=fct, iprn=print\_code, data=data} - dictionary defining the external file containing the datalist.

If the data is transient, a dictionary can be used to specify each stress period where the dictionary key is `<stress period> - 1` and the dictionary value is the datalist data defined above: `{0:ndarray, 1:[(line_one), (line_two), ...], 2:{'filename':filename}}`

#### Parameters

- **data** (*ndarray/list/dict*) – Data to set
- **autofill** (*bool*) – Automatically correct data
- **check\_data** (*bool*) – Whether to verify the data

**store\_as\_external\_file**(*external\_file\_path*, *binary=False*, *replace\_existing\_external=True*, *check\_data=True*)

Store all data externally in file *external\_file\_path*. the binary allows storage in a binary file. If *replace\_existing\_external* is set to *False*, this method will not do anything if the data is already in an external file.

#### Parameters

- **external\_file\_path** (*str*) – Path to external file
- **binary** (*bool*) – Store data in a binary file
- **replace\_existing\_external** (*bool*) – Whether to replace an existing external file.
- **check\_data** (*bool*) – Verify data prior to storing

**store\_internal**(*check\_data=True*)

Store all data internally.

**Parameters** **check\_data** (*bool*) – Verify data prior to storing

**to\_array**(*kper=0*, *mask=False*)

Convert stress period boundary condition (MFDDataList) data for a specified stress period to a 3-D numpy array.

#### Parameters

- **kper** (*int*) – MODFLOW zero-based stress period number to return. (default is zero)
- **mask** (*bool*) – return array with np.NaN instead of zero

**Returns** **out** – Dictionary of 3-D numpy arrays containing the stress period data for a selected stress period. The dictionary keys are the MFDDataList dtype names for the stress period data.

**Return type** dict of numpy.ndarrays

**update\_record**(*record*, *key\_index*)

Updates a record at index “*key\_index*” with the contents of “*record*”. If the index does not exist *update\_record* appends the contents of “*record*” to this list’s recarray.

#### Parameters

- **record** (*list*) – New record to update data with
- **key\_index** (*int*) – Stress period key of record to update. Only used in transient data types.

**class MFMultipleList**(*sim\_data*, *model\_or\_sim*, *structure*, *enable=True*, *path=None*, *dimensions=None*, *package=None*, *block=None*)

Bases: [\*flop.mf6.data.mfdatalist.MFTransientList\*](#)



Provides an interface for the user to access and update MODFLOW multiple list data. This is list data that is in the same format as the MFTransientList, but is not time based.

#### Parameters

- **sim\_data** (MFSimulationData) – data contained in the simulation
- **structure** (MFDataStructure) – describes the structure of the data
- **data** (list or ndarray) – actual data
- **enable** (bool) – enable/disable the array
- **path** (tuple) – path in the data dictionary to this MFArray
- **dimensions** (MFDataDimensions) – dimension information related to the model, package, and array

**get\_data**(key=None, apply\_mult=False, \*\*kwargs)

Returns the data for stress period *key*.

#### Parameters

- **key** (int) – Zero-based stress period to return data from.
- **apply\_mult** (bool) – Apply multiplier

#### Returns data

**Return type** ndarray

**class MFTransientList**(sim\_data, model\_or\_sim, structure, enable=True, path=None, dimensions=None, package=None, block=None)

Bases: [flopy.mf6.data.mfdatalist.MFList](#), [flopy.mf6.data.mfdata.MFTransient](#), [flopy.database.DataListInterface](#)

Provides an interface for the user to access and update MODFLOW transient list data.

#### Parameters

- **sim\_data** (MFSimulationData) – data contained in the simulation
- **structure** (MFDataStructure) – describes the structure of the data
- **data** (list or ndarray) – actual data
- **enable** (bool) – enable/disable the array
- **path** (tuple) – path in the data dictionary to this MFArray
- **dimensions** (MFDataDimensions) – dimension information related to the model, package, and array

**add\_transient\_key**(transient\_key)

Adds a new transient time allowing data for that time to be stored and retrieved using the key *transient\_key*. Method is used internally by FloPy and is not intended to the end user.

**Parameters** **transient\_key** (int) – Zero-based stress period to add

**append\_list\_as\_record**(record, key=0)

Appends the list *data* as a single record in this list's recarray at time *key*. Assumes *data* has the correct dimensions.

#### Parameters

- **data** (list) – Data to append
- **key** (int) – Zero based stress period to append data too.

**property data**

Returns list data. Calls `get_data` with default parameters.

**property data\_type**

Type of data (`DataType`) stored in the list

**property dtype**

Type of data (`numpy.dtype`) stored in the list

**get\_data**(*key=None, apply\_mult=False, \*\*kwargs*)

Returns the data for stress period *key*.

**Parameters**

- **key** (*int*) – Zero-based stress period to return data from.
- **apply\_mult** (*bool*) – Apply multiplier

**Returns data**

**Return type** `recarray`

**get\_file\_entry**(*key=0, ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Returns a string containing the data at time *key* formatted for a MODFLOW 6 file.

**Parameters**

- **key** (*int*) – Zero based stress period to return data from.
- **ext\_file\_action** (`ExtFileAction`) – How to handle external paths.

**Returns file entry**

**Return type** `str`

**has\_data**(*key=None*)

Returns whether this `MFList` has any data associated with it in key “key”.

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from *first\_line* (the first line of data) and open file *file\_handle* which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data in this list.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data for this array
- **block\_header** (`MFBBlockHeader`) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** (`MFComment`) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**property masked\_4D\_arrays**

Returns list data as a masked 4D array.

**masked\_4D\_arrays\_itr**()

Returns list data as an iterator of a masked 4D array.

**plot**(*key=None, names=None, kper=0, filename\_base=None, file\_extension=None, mflay=None, \*\*kwargs*)

Plot stress period boundary condition (`MFList`) data for a specified stress period

**Parameters**

- **key** (*str*) – MfList dictionary key. (default is None)
- **names** (*list*) – List of names for figure titles. (default is None)
- **kper** (*int*) – MODFLOW zero-based stress period number to return. (default is zero)
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if `file_name_base` is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for `savefig()`. Only used if `filename_base` is not None. (default is 'png')
- **mflay** (*int*) – MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)
- **\*\*kwargs** (*dict*) –
  - axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If `axes=None` axes will be generated. (default is None)
  - pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)
  - colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if `pcolor=True`. (default is False)
  - inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)
  - contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)
  - clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if `contour=True`. (default is False)
  - grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)
  - masked\_values** [list] List of unique values to be excluded from the plot.

**Returns** **out** – Empty list is returned if `filename_base` is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

**remove\_transient\_key**(*transient\_key*)

Remove transient stress period key. Method is used internally by FloPy and is not intended to the end user.

**set\_data**(*data*, *key=None*, *autofill=False*)

Sets the contents of the data at time *key* to *data*.

**Parameters**

- **data** (*dict*, *recarray*, *list*) – Data being set. Data can be a dictionary with keys as zero-based stress periods and values as the data. If data is an recarray or list of tuples, it will be assigned to the the stress period specified in *key*. If any is set to None, that stress period of data will be removed.
- **key** (*int*) – Zero based stress period to assign data too. Does not apply if *data* is a dictionary.

- **autofill** (*bool*) – Automatically correct data.

**store\_as\_external\_file**(*external\_file\_path*, *binary=False*, *replace\_existing\_external=True*, *check\_data=True*)

Store all data externally in file *external\_file\_path*. the binary allows storage in a binary file. If *replace\_existing\_external* is set to *False*, this method will not do anything if the data is already in an external file.

#### Parameters

- **external\_file\_path** (*str*) – Path to external file
- **binary** (*bool*) – Store data in a binary file
- **replace\_existing\_external** (*bool*) – Whether to replace an existing external file.
- **check\_data** (*bool*) – Verify data prior to storing

**store\_internal**(*check\_data=True*)

Store all data internally.

**Parameters** **check\_data** (*bool*) – Verify data prior to storing

**to\_array**(*kper=0*, *mask=False*)

Returns list data as an array.

**update\_record**(*record*, *key\_index*, *key=0*)

Updates a record at index *key\_index* and time *key* with the contents of *record*. If the index does not exist *update\_record* appends the contents of *record* to this list's recarray.

#### Parameters

- **record** (*list*) – Record to append
- **key\_index** (*int*) – Index to update
- **key** (*int*) – Zero based stress period to append data too

## flop.mf6.data.mfdatascalar module

**class MFScalar**(*sim\_data*, *model\_or\_sim*, *structure*, *data=None*, *enable=True*, *path=None*, *dimensions=None*)

Bases: `flop.mf6.data.mfdata.MFData`

Provides an interface for the user to access and update MODFLOW scalar data. MFScalar objects are not designed to be directly constructed by the end user. When a flop for MODFLOW 6 package object is constructed, the appropriate MFScalar objects are automatically built.

#### Parameters

- **sim\_data** (`MFSimulationData`) – data contained in the simulation
- **structure** (`MFDataStructure`) – describes the structure of the data
- **data** (*list or ndarray*) – actual data
- **enable** (*bool*) – enable/disable the array
- **path** (*tuple*) – path in the data dictionary to this MFArray
- **dimensions** (`MFDataDimensions`) – dimension information related to the model, package, and array

**add\_one**()

Adds one if this is an integer scalar

**property data**

Returns the scalar data. Calls `get_data` with default parameters.

**property data\_type**

Type of data (`DataType`) stored in the scalar

**property dtype**

The scalar's numpy data type (`numpy.dtype`).

**get\_data**(*apply\_mult=False, \*\*kwargs*)

Returns the data associated with this object.

**Parameters** **apply\_mult** (*bool*) – Parameter does not apply to scalar data.

**Returns data**

**Return type** *str*, *int*, *float*, *recarray*

**get\_file\_entry**(*values\_only=False, one\_based=False, ext\_file\_action=ExtFileAction.copy\_relative\_paths*)

Returns a string containing the data formatted for a MODFLOW 6 file.

**Parameters**

- **values\_only** (*bool*) – Return values only excluding keywords
- **one\_based** (*bool*) – Return one-based integer values
- **ext\_file\_action** (`ExtFileAction`) – How to handle external paths.

**Returns file entry**

**Return type** *str*

**has\_data**(*key=None*)

Returns whether this object has data associated with it.

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from *first\_line* (the first line of data) and open file *file\_handle* which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file. This method was only designed for internal FloPy use and is not recommended for end users.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data
- **block\_header** (`MFBBlockHeader`) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** (`MFComment`) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**Returns**

- **more data** (*bool*,)
- **next data line** (*str*)

**plot**(*filename\_base=None, file\_extension=None, \*\*kwargs*)

Helper method to plot scalar objects

**Parameters**

- **scalar** – flopy.mf6.data.mfscalar object
- **filename\_base** – str Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **file\_extension** – str Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')

**Returns** list matplotlib.axes object

**Return type** axes

**property plottable**

If the scalar is plottable. Currently all scalars are not plottable.

**set\_data(data)**

Sets the contents of the data to *data*.

**Parameters** *data* (str/int/float/recarray/list) – Data to set

**class MFScalarTransient**(*sim\_data, model\_or\_sim, structure, enable=True, path=None, dimensions=None*)

Bases: *flopy.mf6.data.mfdatascalar.MFScalar*, *flopy.mf6.data.mfdata.MFTransient*

Provides an interface for the user to access and update MODFLOW transient scalar data. Transient scalar data is used internally by FloPy and should not be used directly by the end user.

**Parameters**

- **sim\_data** (*MFSimulationData*) – data contained in the simulation
- **structure** (*MFDataStructure*) – describes the structure of the data
- **data** (*list or ndarray*) – actual data
- **enable** (*bool*) – enable/disable the array
- **path** (*tuple*) – path in the data dictionary to this MFArray
- **dimensions** (*MFDataDimensions*) – dimension information related to the model, package, and array

**add\_one(key=0)**

Adds one to the data stored at key *key*. Method is used internally by FloPy and is not intended to the end user.

**Parameters** *key* (*int*) – Zero-based stress period to add

**add\_transient\_key(key)**

Adds a new transient time allowing data for that time to be stored and retrieved using the key *key*. Method is used internally by FloPy and is not intended to the end user.

**Parameters** *key* (*int*) – Zero-based stress period to add

**property data\_type**

Type of data (*DataType*) stored in the scalar

**get\_data(key=0, \*\*kwargs)**

Returns the data for stress period *key*.

**Parameters** *key* (*int*) – Zero-based stress period to return data from.

**Returns** data

**Return type** str/int/float/recarray

**get\_file\_entry(key=None, ext\_file\_action=ExtFileAction.copy\_relative\_paths)**

Returns a string containing the data at time *key* formatted for a MODFLOW 6 file.

**Parameters**

- **key** (*int*) – Zero based stress period to return data from.
- **ext\_file\_action** (*ExtFileAction*) – How to handle external paths.

**Returns** file entry**Return type** str

**has\_data**(*key=None*)

Returns whether this object has data associated with it.

**load**(*first\_line, file\_handle, block\_header, pre\_data\_comments=None, external\_file\_info=None*)

Loads data from *first\_line* (the first line of data) and open file *file\_handle* which is pointing to the second line of data. Returns a tuple with the first item indicating whether all data was read and the second item being the last line of text read from the file.

**Parameters**

- **first\_line** (*str*) – A string containing the first line of data in this scalar.
- **file\_handle** (*file descriptor*) – A file handle for the data file which points to the second line of data for this array
- **block\_header** (*MFBBlockHeader*) – Block header object that contains block header information for the block containing this data
- **pre\_data\_comments** (*MFComment*) – Comments immediately prior to the data
- **external\_file\_info** (*list*) – Contains information about storing files externally

**plot**(*filename\_base=None, file\_extension=None, kper=0, fignum=None, \*\*kwargs*)

Plot transient scalar model data

**Parameters**

- **transientscalar** (*flop.mf6.data.mfdatascalar.MFScalarTransient object*) –
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if *file\_name\_base* is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for savefig(). Only used if *filename\_base* is not None. (default is 'png')
- **\*\*kwargs** (*dict*) –
  - axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If *axes=None* axes will be generated. (default is None)
  - pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)
  - colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if *pcolor=True*. (default is False)
  - inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)
  - contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**kper** [str] MODFLOW zero-based stress period number to return. If kper='all' then data for all stress period will be extracted. (default is zero).

**Returns axes** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

**property plottable**

If the scalar is plottable

**set\_data**(data, key=None)

Sets the contents of the data at time key to data.

**Parameters**

- **data** (str/int/float/reccarray/list) – Data being set. Data can be a dictionary with keys as zero-based stress periods and values as the data. If data is a string, integer, double, reccarray, or list of tuples, it will be assigned to the the stress period specified in key. If any is set to None, that stress period of data will be removed.
- **key** (int) – Zero based stress period to assign data too. Does not apply if data is a dictionary.

## Build MODFLOW 6 Classes

MODFLOW 6 FloPy classes can be rebuild from MODFLOW 6 definition files. This will allow creation of MODFLOW 6 FloPy classes for development versions of MODFLOW 6.

Contents:

### flop.fmf6.utils.createpackages module

**class PackageLevel**(value)

Bases: enum.Enum

An enumeration.

**model\_level** = 1

**sim\_level** = 0

**add\_var**(init\_vars, class\_vars, init\_param\_list, package\_properties, doc\_string, data\_structure\_dict, default\_value, name, python\_name, description, path, data\_type, basic\_init=False, construct\_package=None, construct\_data=None, parameter\_name=None, set\_param\_list=None)

**build\_dfn\_string**(dfn\_list, header)

**build\_doc\_string**(param\_name, param\_type, param\_desc, indent)

**build\_init\_string**(init\_string, init\_param\_list, whitespace=' ')

**build\_model\_init\_vars**(param\_list)



```

build_model_load(model_type)
clean_class_string(name)
create_basic_init(clean_ds_name)
create_init_var(clean_ds_name, data_structure_name, init_val=None)
create_package_init_var(parameter_name, package_abbr, data_name)
create_packages()
create_property(clean_ds_name)
format_var_list(base_string, var_list, is_tuple=False)
generator_type(data_type)

```

### flopY.mf6.utils.generate\_classes module

```

backup_existing_dfns(flopY_dfn_path)
delete_files(files, pth, allow_failure=False, exclude=None)
delete_mf6_classes()
download_dfn(branch, new_dfn_pth)
generate_classes(branch='master', dfnpath=None, backup=True)

```

Generate the MODFLOW 6 flopY classes using definition files from the MODFLOW 6 GitHub repository or a set of definition files in a folder provided by the user.

#### Parameters

- **branch** (*str*) – Branch name of the MODFLOW 6 repository to use to update the definition files and generate the MODFLOW 6 classes. Default is master.
- **dfnpath** (*str*) – Path to a definition file folder that will be used to generate the MODFLOW 6 classes. Default is none, which means that the branch will be used instead. dfnpath will take precedence over branch if dfnpath is specified.
- **backup** (*bool*) – Keep a backup of the definition files in dfn\_backup with a date and time stamp from when the definition files were replaced.

```

list_files(pth, exts=['py'])
replace_dfn_files(new_dfn_pth, flopY_dfn_path)

```

## 7.1.2 Previous Versions of MODFLOW

### MODFLOW Base Classes

Contents:

## flop.mbase module

**mbase module** This module contains the base model class from which all of the other models inherit from.

**class BaseModel**(*modelname*='modflowtest', *namefile\_ext*='nam', *exe\_name*='mf2k.exe', *model\_ws*=None, *structured*=True, *verbose*=False, *\*\*kwargs*)

Bases: [flop.mbase.ModelInterface](#)

MODFLOW-based models base class.

### Parameters

- **modelname** (*str*, *default* "modflowtest") – Name of the model, which is also used for model file names.
- **namefile\_ext** (*str*, *default* "nam") – Name file extension, without “.”
- **exe\_name** (*str*, *default* "mf2k.exe") – Name of the modflow executable.
- **model\_ws** (*str*, *optional*) – Path to the model workspace. Model files will be created in this directory. Default is None, in which case model\_ws is assigned to the current working directory.
- **structured** (*bool*, *default* True) – Specify if model grid is structured (default) or unstructured.
- **verbose** (*bool*, *default* False) – Print additional information to the screen.
- **\*\*kwargs** (*dict*, *optional*) – Used to define: *x11/y11* for the x- and y-coordinates of the lower-left corner of the grid, *xu1/yu1* for the x- and y-coordinates of the upper-left corner of the grid (deprecated), *rotation* for the grid rotation (default 0.0), *proj4\_str* for a PROJ string, and *start\_datetime* for model start date (default “1-1-1970”).

**add\_existing\_package**(*filename*, *ptype*=None, *copy\_to\_model\_ws*=True)

Add an existing package to a model instance.

### Parameters

- **filename** (*str*) – the name of the file to add as a package
- **ptype** (*optional*) – the model package type (e.g. “lpf”, “wel”, etc). If None, then the file extension of the filename arg is used
- **copy\_to\_model\_ws** (*bool*) – flag to copy the package file into the model\_ws directory.

**Return type** None

**add\_external**(*fname*, *unit*, *binflag*=False, *output*=False)

Assign an external array so that it will be listed as a DATA or DATA(BINARY) entry in the name file. This will allow an outside file package to refer to it.

### Parameters

- **fname** (*str*) – filename of external array
- **unit** (*int*) – unit number of external array
- **binflag** (*boolean*) – binary or not. (default is False)

**add\_output**(*fname*, *unit*, *binflag*=False, *package*=None)

Assign an external array so that it will be listed as a DATA or DATA(BINARY) entry in the name file. This will allow an outside file package to refer to it.

### Parameters

- **fname** (*str*) – filename of external array

- **unit** (*int*) – unit number of external array
- **binflag** (*boolean*) – binary or not. (default is False)

**add\_output\_file**(*unit, fname=None, extension='cbc', binflag=True, package=None*)

Add an ascii or binary output file for a package

**Parameters**

- **unit** (*int*) – unit number of external array
- **fname** (*str*) – filename of external array. (default is None)
- **extension** (*str*) – extension to use for the cell-by-cell file. Only used if fname is None. (default is cbc)
- **binflag** (*bool*) – boolean flag indicating if the output file is a binary file. Default is True
- **package** (*str*) – string that defines the package the output file is attached to. Default is None

**add\_package**(*p*)

Add a package.

**Parameters** **p** (*Package object*) –

**add\_pop\_key\_list**(*key*)

Add a external file unit number to a list that will be used to remove model output (typically binary) files from ext\_unit\_dict.

**Parameters** **key** (*int*) – file unit number

## Examples

**change\_model\_ws**(*new\_pth=None, reset\_external=False*)

Change the model work space.

**Parameters** **new\_pth** (*str*) – Location of new model workspace. If this path does not exist, it will be created. (default is None, which will be assigned to the present working directory).

**Returns** **val** – Can be used to see what packages are in the model, and can then be used with `get_package` to pull out individual packages.

**Return type** list of strings

**check**(*f=None, verbose=True, level=1*)

Check model data for common errors.

**Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('model.nam')
>>> m.check()
```

### property `exename`

**export**(*f*, **\*\*kwargs**)

Method to export a model to netcdf or shapefile based on the extension of the file name (.shp for shapefile, .nc for netcdf)

#### Parameters

- **f** (*str*) – filename
- **kwargs** (*keyword arguments*) –  
**modelgrid** [flopY.discretization.Grid instance] user supplied modelgrid which can be used for exporting in lieu of the modelgrid associated with the model object

**Return type** None or Netcdf object

**get\_ext\_dict\_attr**(*ext\_unit\_dict=None*, *unit=None*, *filetype=None*, *pop\_key=True*)

**get\_name\_file\_entries**()

Get a string representation of the name file.

**get\_output**(*fname=None*, *unit=None*)

Get an output file from the model by specifying either the file name or the unit number.

#### Parameters

- **fname** (*str*) – filename of output array
- **unit** (*int*) – unit number of output array

**get\_output\_attribute**(*fname=None*, *unit=None*, *attr=None*)

Get a attribute for an output file from the model by specifying either the file name or the unit number.

#### Parameters

- **fname** (*str*) – filename of output array
- **unit** (*int*) – unit number of output array

**get\_package**(*name*)

Get a package.

**Parameters** **name** (*str*) – Name of the package, 'RIV', 'LPF', etc. (case-insensitive).

**Returns** **pp** – Package object of type *flopY.pakbase.Package*

**Return type** Package object

**has\_package**(*name*)

Check if package name is in package list.

**Parameters** **name** (*str*) – Name of the package, 'DIS', 'BAS6', etc. (case-insensitive).

**Returns** True if package name exists, otherwise False if not found.

**Return type** bool

### property `hdry`

### property `hnoflo`

**property** laycbd

**property** laytyp

**load\_results()**

**property** model\_ws

**property** modelgrid

**property** modeltime

**property** name

Get model name

**Returns** **name** – name of model

**Return type** str

**property** namefile

**next\_ext\_unit()**

Function to encapsulate next\_ext\_unit attribute

**next\_unit**(*i=None*)

**property** packagelist

**plot**(*SelPackList=None, \*\*kwargs*)

Plot 2-D, 3-D, transient 2-D, and stress period list (MfList) model input data

**Parameters**

- **SelPackList** (*bool or list*) – List of packages to plot. If SelPackList=None all packages are plotted. (default is None)

- **\*\*kwargs** (*dict*) –

**filename\_base** [str] Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)

**file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')

**mflay** [int] MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)

**kper** [int] MODFLOW zero-based stress period number to return. (default is zero)

**key** [str] MfList dictionary key. (default is None)

**Returns** **axes** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis are returned.

**Return type** list

## Notes

## Examples

```
>>> import flop
>>> ml = flop.modflow.Modflow.load('test.nam')
>>> ml.plot()
```

**remove\_external**(*fname=None, unit=None*)

Remove an external file from the model by specifying either the file name or the unit number.

### Parameters

- **fname** (*str*) – filename of external array
- **unit** (*int*) – unit number of external array

**remove\_output**(*fname=None, unit=None*)

Remove an output file from the model by specifying either the file name or the unit number.

### Parameters

- **fname** (*str*) – filename of output array
- **unit** (*int*) – unit number of output array

**remove\_package**(*pname*)

Remove a package from this model

**Parameters** **pname** (*string*) – Name of the package, such as 'RIV', 'BAS6', etc.

**run\_model**(*silent=False, pause=False, report=False, normal\_msg='normal termination'*)

This method will run the model using subprocess.Popen.

### Parameters

- **silent** (*boolean*) – Echo run information to screen (default is True).
- **pause** (*boolean, optional*) – Pause upon completion (default is False).
- **report** (*boolean, optional*) – Save stdout lines to a list (buff) which is returned by the method . (default is False).
- **normal\_msg** (*str*) – Normal termination message used to determine if the run terminated normally. (default is 'normal termination')

### Returns

- (*success, buff*)
- **success** (*boolean*)
- **buff** (*list of lines of stdout*)

**set\_model\_units**()

Every model needs its own set\_model\_units method

**set\_output\_attribute**(*fname=None, unit=None, attr=None*)

Set a variable in an output file from the model by specifying either the file name or the unit number and a dictionary with attributes to change.

### Parameters

- **fname** (*str*) – filename of output array
- **unit** (*int*) – unit number of output array

**set\_version**(*version*)

**to\_shapefile**(*filename*, *package\_names=None*, *\*\*kwargs*)

Wrapper function for writing a shapefile for the model grid. If *package\_names* is not *None*, then search through the requested packages looking for arrays that can be added to the shapefile as attributes

#### Parameters

- **filename** (*string*) – name of the shapefile to write
- **package\_names** (*list of package names (e.g. ["dis", "lpf"])*) – Packages to export data arrays to shapefile. (default is *None*)

**Return type** *None*

#### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> m.to_shapefile('model.shp', SelPackList)
```

**property verbose**

**property version**

**write\_input**(*SelPackList=False*, *check=False*)

Write the input.

**Parameters** *SelPackList* (*False or list of packages*) –

**write\_name\_file**()

Every Package needs its own writenamefile function

**class FileData**

Bases: *object*

**add\_file**(*fname*, *unit*, *binflag=False*, *output=False*, *package=None*)

**class FileDataEntry**(*fname*, *unit*, *binflag=False*, *output=False*, *package=None*)

Bases: *object*

**class ModelInterface**

Bases: *object*

**abstract check**(*f=None*, *verbose=True*, *level=1*)

**abstract property exename**

**abstract export**(*f*, *\*\*kwargs*)

**get\_package\_list**(*ftype=None*)

Get a list of all the package names.

**Parameters** *ftype* (*str*) – Type of package, ‘RIV’, ‘LPF’, etc.

**Returns** *val* – Can be used to see what packages are in the model, and can then be used with *get\_package* to pull out individual packages.

**Return type** *list of strings*

**abstract property hdry**

**abstract property hnoflo**

```
abstract property laycbd
abstract property laytyp
abstract property model_ws
abstract property modelgrid
abstract property namefile
abstract property packagelist
abstract property solver_tols
update_modelgrid()
abstract property verbose
abstract property version
```

**exception** `PackageLoadException(error, location="")`

Bases: `Exception`

FloPy package load exception.

**run\_model**(*exe\_name*, *namefile*, *model\_ws*='./', *silent*=False, *pause*=False, *report*=False, *normal\_msg*='normal termination', *use\_async*=False, *cargs*=None)

This function will run the model using `subprocess.Popen`. It communicates with the model's stdout asynchronously and reports progress to the screen with timestamps

#### Parameters

- **exe\_name** (*str*) – Executable name (with path, if necessary) to run.
- **namefile** (*str*) – Namefile of model to run. The namefile must be the filename of the namefile without the path. Namefile can be `None` to allow programs that do not require a control file (name file) to be passed as a command line argument.
- **model\_ws** (*str*) – Path to the location of the namefile. (default is the current working directory - './')
- **silent** (*boolean*) – Echo run information to screen (default is `True`).
- **pause** (*boolean*, *optional*) – Pause upon completion (default is `False`).
- **report** (*boolean*, *optional*) – Save stdout lines to a list (buff) which is returned by the method . (default is `False`).
- **normal\_msg** (*str or list*) – Normal termination message used to determine if the run terminated normally. More than one message can be provided using a list. (Default is 'normal termination')
- **use\_async** (*boolean*) – asynchronously read model stdout and report with timestamps. good for models that take long time to run. not good for models that run really fast
- **cargs** (*str or list of strings*) – additional command line arguments to pass to the executable. Default is `None`

#### Returns

- (*success*, *buff*)
- **success** (*boolean*)
- **buff** (*list of lines of stdout*)



## flopy.pakbase module

**pakbase module** This module contains the base package class from which all of the other packages inherit from.

**class Package**(*parent, extension='glo', name='GLOBAL', unit\_number=1, filenames=None, allowDuplicates=False*)

Bases: [flopy.pakbase.PackageInterface](#)

Base package class from which most other packages are derived.

### Parameters

- **parent** (*object*) – Parent model object.
- **extension** (*str or list, default "glo"*) – File extension, without “.”, use list to describe more than one.
- **name** (*str or list, default "GLOBAL"*) – Package name, use list to describe more than one.
- **unit\_number** (*int or list, default 1*) – Unit number, use list to describe more than one.
- **filenames** (*str or list, default None*) –
- **allowDuplicates** (*bool, default False*) – Allow more than one instance of package in parent.

**static add\_to\_dtype**(*dtype, field\_names, field\_types*)

Add one or more fields to a structured array data type

### Parameters

- **dtype** (*numpy.dtype*) – Input structured array datatype to add to.
- **field\_names** (*str or list*) – One or more field names.
- **field\_types** (*numpy.dtype or list*) – One or more data types. If one data type is supplied, it is repeated for each field name.

## property data\_list

**export**(*f, \*\*kwargs*)

Method to export a package to netcdf or shapefile based on the extension of the file name (.shp for shapefile, .nc for netcdf)

### Parameters

- **f** (*str*) – filename
- **kwargs** (*keyword arguments*) –
- **modelgrid** [*flopy.discretization.Grid instance*] user supplied modelgrid which can be used for exporting in lieu of the modelgrid associated with the model object

**Return type** None or Netcdf object

**level1\_arraylist**(*idx, v, name, txt*)

**static load**(*f, model, pak\_type, ext\_unit\_dict=None, \*\*kwargs*)

Default load method for standard boundary packages.

**property name**

**property package\_type**

**property parent**

**plot**(\*\*kwargs)

Plot 2-D, 3-D, transient 2-D, and stress period list (MfList) package input data

**Parameters** **\*\*kwargs** (*dict*) –**filename\_base** [str] Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)**file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')**mflay** [int] MODFLOW zero-based layer number to return. If None, then all all layers will be included. (default is None)**kper** [int] MODFLOW zero-based stress period number to return. (default is zero)**key** [str] MfList dictionary key. (default is None)**Returns** **axes** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis are returned.**Return type** list

## Notes

## Examples

```
>>> import flopY
>>> ml = flopY.modflow.Modflow.load('test.nam')
>>> ml.dis.plot()
```

**property** **plottable****to\_shapefile**(filename, \*\*kwargs)

Export 2-D, 3-D, and transient 2-D model data to shapefile (polygons). Adds an attribute for each layer in each data array

**Parameters** **filename** (*str*) – Shapefile name to write**Return type** None

## Notes

## Examples

```
>>> import flopY
>>> ml = flopY.modflow.Modflow.load('test.nam')
>>> ml.lpf.to_shapefile('test_hk.shp')
```

**webdoc**()**write\_file**(f=None, check=False)

Every Package needs its own write\_file function

**class** **PackageInterface**

Bases: object

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check package data for common errors.

#### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If *f* is *None*, check method does not write results to a summary file. (default is *None*)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If *level=0*, summary checks are performed. If *level=1*, full checks are performed.
- **checktype** (*check*) – Checker type to be used. By default class *check* is used from *check.py*.

**Return type** *None*

#### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow.load('model.nam')
>>> m.dis.check()
```

**abstract property data\_list**

**abstract export**(*f, \*\*kwargs*)

**property has\_stress\_period\_data**

**abstract property name**

**abstract property package\_type**

**abstract property parent**

**abstract property plottable**

## MODFLOW Packages

Contents:

### flop.modflow.mf module

mf module. Contains the *ModflowGlobal*, *ModflowList*, and *Modflow* classes.

**class Modflow**(*modelname='modflowtest', namefile\_ext='nam', version='mf2005', exe\_name='mf2005.exe', structured=True, listunit=2, model\_ws='.', external\_path=None, verbose=False, \*\*kwargs*)

Bases: *flop.mbase.BaseModel*

MODFLOW Model Class.

#### Parameters

- **modelname** (*str, default "modflowtest"*) – Name of model. This string will be used to name the MODFLOW input that are created with *write\_model*.
- **namefile\_ext** (*str, default "nam"*) – Extension for the namefile.

- **version**(*str*, *default* "mf2005") – MODFLOW version. Choose one of: “mf2k”, “mf2005” (default), “mfnwt”, or “mfusg”.
- **exe\_name**(*str*, *default* "mf2005.exe") – The name of the executable to use.
- **structured**(*bool*, *default* True) – Specify if model grid is structured (default) or unstructured.
- **listunit**(*int*, *default* 2) – Unit number for the list file.
- **model\_ws**(*str*, *default* ".") – Model workspace. Directory name to create model data sets. (default is the present working directory).
- **external\_path**(*str*, *optional*) – Location for external files.
- **verbose**(*bool*, *default* False) – Print additional information to the screen.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
```

**get\_ifrefm()**

**get\_nrow\_ncol\_nlay\_nper()**

**classmethod load**(*f*, *version*='mf2005', *exe\_name*='mf2005.exe', *verbose*=False, *model\_ws*='.',  
*load\_only*=None, *forgive*=False, *check*=True)

Load an existing MODFLOW model.

### Parameters

- **f** (*str*) – Path to MODFLOW name file to load.
- **version** (*str*, *default* "mf2005") – MODFLOW version. Choose one of: “mf2k”, “mf2005” (default), or “mfnwt”. Note that this can be modified on loading packages unique to different MODFLOW versions.
- **exe\_name** (*str*, *default* "mf2005.exe") – MODFLOW executable name.
- **verbose** (*bool*, *default* False) – Show messages that can be useful for debugging.
- **model\_ws** (*str*, *default* ".") – Model workspace path. Default is the current directory.
- **load\_only** (*list*, *str* or None) – List of case insensitive packages to load, e.g. ["bas6", "lpf"]. One package can also be specified, e.g. "rch". Default is None, which attempts to load all files. An empty list [] will not load any additional packages than is necessary. At a minimum, “dis” is always loaded.
- **forgive** (*bool*, *optional*) – Option to raise exceptions on package load failure, which can be useful for debugging. Default False.
- **check** (*boolean*, *optional*) – Check model input for common errors. Default True.

**Return type** *flopY.modflow.mf.Modflow*

## Examples

```
>>> import flopY
>>> m1 = flopY.modflow.Modflow.load('model.nam')
```

**load\_results(\*\*kwargs)**

**property modelgrid**

**property modeltime**

**property ncol**

**property ncpl**

**property nlay**

**property nper**

**property nrow**

**property nrow\_ncol\_nlay\_nper**

**set\_ifrefm(value=True)**

**set\_model\_units(iunit0=None)**

Write the model name file.

**property solver\_tols**

**write\_name\_file()**

Write the model name file.

**class ModflowGlobal(model, extension='glo')**

Bases: [flopY.pakbase.Package](#)

ModflowGlobal Package class

**write\_file()**

Every Package needs its own write\_file function

**class ModflowList(model, extension='list', unitnumber=2)**

Bases: [flopY.pakbase.Package](#)

ModflowList Package class

**write\_file()**

Every Package needs its own write\_file function

## flopY.modflow.mfaddoutsidefile module

**class mfaddoutsidefile(model, name, extension, unitnumber)**

Bases: [flopY.pakbase.Package](#)

Add a file for which you have a MODFLOW input file

**write\_file()**

Every Package needs its own write\_file function

## flopY.modflow.mfag module

mfag module which contains the ModflowAg class.

Note that the user can access the ModflowAg class as *flopY.modflow.ModflowAg*.

Additional information for this MODFLOW package can be found at <<https://www.sciencedirect.com/science/article/pii/S1364815219305080>>`\_.

**class ModflowAg**(*model, options=None, time\_series=None, well\_list=None, irrdiversion=None, irrwell=None, supwell=None, extension='ag', unitnumber=None, filenames=None, nper=0*)

Bases: *flopY.pakbase.Package*

The ModflowAg class is used to build read, write, and edit data from the MODFLOW-NWT AG package.

### Parameters

- **model** (*flopY.modflow.Modflow object*) – model object
- **options** (*flopY.utils.OptionBlock object*) – option block object
- **time\_series** (*np.recarray*) – numpy recarray for the time series block
- **well\_list** (*np.recarray*) – recarray of the well\_list block
- **irrdiversion** (*dict {per: np.recarray}*) – dictionary of the irrdiversion block
- **irrwell** (*dict {per: np.recarray}*) – dictionary of the irrwell block
- **supwell** (*dict {per: np.recarray}*) – dictionary of the supwell block
- **extension** (*str, optional*) – default is .ag
- **unitnumber** (*list, optional*) – fortran unit number for modflow, default 69
- **filenames** (*list, optional*) – file name for ModflowAwu package to write input
- **nper** (*int*) – number of stress periods in the model

## Examples

load a ModflowAg file

```
>>> import flopY
>>> ml = flopY.modflow.Modflow('agtest')
>>> ag = flopY.modflow.ModflowAg.load('test.ag', ml, nper=2)
```

**static get\_default\_dtype**(*maxells=0, block='well'*)

Function that gets a default dtype for a block

### Parameters

- **maxells** (*int*) – maximum number of irrigation links
- **block** (*str*) – str which indicates data set valid options are “well” “tabfile\_well” “timeseries” “irrdiversion” “irrwell” “supwell”

### Returns dtype

**Return type** (list, tuple)

**static get\_empty**(*numrecords, maxells=0, block='well'*)

Creates an empty record array corresponding to the block data type it is associated with.

### Parameters

- **numrecords** (*int*) – number of records to create recarray with
- **maxells** (*int*, *optional*) – maximum number of irrigation links
- **block** (*str*) – str which indicates data set valid options are “well”, “tabfile\_well”, “timeseries”, “irrddiversion\_modflow”, “irrddiversion\_gsflow”, “irrwel\_modflow”, “irrwel\_gsflow”, “supwell”

**Return type** np.recarray

**classmethod** `load(f, model, nper=0, ext_unit_dict=None)`

Method to load the AG package from file

**Parameters**

- **f** (*str*) – filename
- **model** (*gsflow.modflow.Modflow object*) – model to attach the ag package to
- **nper** (*int*) – number of stress periods in model
- **ext\_unit\_dict** (*dict*, *optional*) –

**Return type** ModflowAg object

**property** `plottable`

**property** `segment_list`

Method to get a unique list of segments from irrddiversion

**Return type** list

**write\_file** (*check=False*)

Write method for ModflowAg

**Parameters** **check** (*bool*) – not implemented

## flop.modflow.mfbas module

mfbas module. Contains the ModflowBas class. Note that the user can access the ModflowBas class as `flop.modflow.ModflowBas`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowBas(model, ibound=1, strt=1.0, ifrefm=True, ixsec=False, ichflg=False, stoper=None, hnoflo=-999.99, extension='bas', unitnumber=None, filenames=None)`

Bases: `flop.pakbase.Package`

MODFLOW Basic Package Class.

**Parameters**

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **ibound** (*array of ints*, *optional*) – The ibound array (the default is 1).
- **strt** (*array of floats*, *optional*) – An array of starting heads (the default is 1.0).
- **ifrefm** (*bool*, *optional*) – Indication if data should be read using free format (the default is True).
- **ixsec** (*bool*, *optional*) – Indication of whether model is cross sectional or not (the default is False).

- **ichflg** (*bool, optional*) – Flag indicating that flows between constant head cells should be calculated (the default is False).
- **stoper** (*float*) – percent discrepancy that is compared to the budget percent discrepancy continue when the solver convergence criteria are not met. Execution will unless the budget percent discrepancy is greater than stoper (default is None). MODFLOW-2005 only
- **hnoflo** (*float*) – Head value assigned to inactive cells (default is -999.99).
- **extension** (*str, optional*) – File extension (default is 'bas').
- **unitnumber** (*int, optional*) – FORTRAN unit number for this package (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package name will be set to the string. Default is None.

**heading**

Text string written to top of package input file.

**Type** str

**options**

Can be either or a combination of XSECTION, CHTOCH or FREE.

**Type** list of str

**ifrefm**

Indicates whether or not packages will be written as free format.

**Type** bool

**Notes****Examples**

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> bas = flopy.modflow.ModflowBas(m)
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check package data for common errors.

**Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a sting is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None



## Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow.load('model.nam')
>>> m.bas6.check()
```

### property ifrefm

**classmethod** `load(f, model, ext_unit_dict=None, check=True, **kwargs)`

Load an existing package.

#### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)
- **kwargs** (*dictionary*) – Keyword arguments that are passed to load. Possible keyword arguments are nlay, nrow, and ncol. If not provided, then the model must contain a discretization package with correct values for these parameters.

**Returns** **bas** – ModflowBas object (of type `flopy.modflow.ModflowBas`)

**Return type** ModflowBas object

## Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow()
>>> bas = floppy.modflow.ModflowBas.load('test.bas', m, nlay=1, nrow=10,
>>>                                     ncol=10)
```

**write\_file**(*check=True*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopy.modflow.mfbcf module

**class** `ModflowBcf(model, ipakcb=None, intercellt=0, laycon=3, trpy=1.0, hdry=- 1e+30, iwdflg=0, wetfct=0.1, iwetit=1, ihdwet=0, tran=1.0, hy=1.0, vcont=1.0, sf1=1e-05, sf2=0.15, wetdry=- 0.01, extension='bcf', unitnumber=None, filenames=None, add_package=True)`

Bases: `flopy.pakbase.Package`

MODFLOW Block Centered Flow Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.Modflow`) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 53)
- **intercellt** (*int*) – Intercell transmissivities, harmonic mean (0), arithmetic mean (1), logarithmic mean (2), combination (3). (default is 0)
- **laycon** (*int*) – Layer type, confined (0), unconfined (1), constant T, variable S (2), variable T, variable S (default is 3)
- **trpy** (*float or array of floats (nlay)*) – horizontal anisotropy ratio (default is 1.0)
- **hdry** (*float*) – head assigned when cell is dry - used as indicator (default is -1E+30)
- **iwdflg** (*int*) – flag to indicate if wetting is inactive (0) or not (non zero) (default is 0)
- **wetfct** (*float*) – factor used when cell is converted from dry to wet (default is 0.1)
- **iwetit** (*int*) – iteration interval in wetting/drying algorithm (default is 1)
- **ihdwet** (*int*) – flag to indicate how initial head is computed for cells that become wet (default is 0)
- **tran** (*float or array of floats (nlay, nrow, ncol), optional*) – transmissivity (only read if laycon is 0 or 2) (default is 1.0)
- **hy** (*float or array of floats (nlay, nrow, ncol)*) – hydraulic conductivity (only read if laycon is 1 or 3) (default is 1.0)
- **vcont** (*float or array of floats (nlay-1, nrow, ncol)*) – vertical leakance between layers (default is 1.0)
- **sf1** (*float or array of floats (nlay, nrow, ncol)*) – specific storage (confined) or storage coefficient (unconfined), read when there is at least one transient stress period. (default is 1e-5)
- **sf2** (*float or array of floats (nrow, ncol)*) – specific yield, only read when laycon is 2 or 3 and there is at least one transient stress period (default is 0.15)
- **wetdry** (*float*) – a combination of the wetting threshold and a flag to indicate which neighboring cells can cause a cell to become wet (default is -0.01)
- **extension** (*string*) – Filename extension (default is 'bcf')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output name will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.
- **add\_package** (*bool*) – Flag to add the initialised package object to the parent model object. Default is True.

## Notes

## Examples

```
>>> import flopY
>>> m1 = flopY.modflow.Modflow()
>>> bcf = flopY.modflow.ModflowBcf(m1)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is `None`, then `nper` will be obtained from the model object. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** `wel` – `ModflowBcf` object.

**Return type** `ModflowBcf` object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> wel = flopY.modflow.ModflowBcf.load('test.bcf', m)
```

**write\_file(f=None)**

Write the package file.

**Return type** `None`

## flopY.modflow.mfbct module

**class** `ModflowBct(model, itrnsp=1, ibctcb=0, mcomp=1, ic_ibound_flg=1, itvd=1, iadsorb=0, ict=0, cinact=-999.0, ciclose=1e-06, idisp=1, ixdisp=0, diffnc=0.0, izod=0, ifod=0, icbund=1, porosity=0.1, bulkd=1.0, arad=0.0, dlh=0.0, dlv=0.0, dth=0.0, dtv=0.0, sconc=0.0, extension='bct', unitnumber=None)`

Bases: `flopY.pakbase.Package`

Block centered transport package class for MODFLOW-USG

**write\_file()**

Write the package file.

**Return type** `None`

## flop.modflow.mfchd module

mfchd module. Contains the ModflowChd class. Note that the user can access the ModflowChd class as `flop.modflow.ModflowChd`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowChd**(*model*, *stress\_period\_data*=None, *dtype*=None, *options*=None, *extension*='chd', *unitnumber*=None, *filenames*=None, *\*\*kwargs*)

Bases: [flop.pakbase.Package](#)

MODFLOW Constant Head Package Class.

### Parameters

- **model** (*model object*) – The model object (of type [flop.modflow.mf.Modflow](#)) to which this package will be added.
- **stress\_period\_data** (*list of boundaries, recarrays, or dictionary of*) – boundaries.

Each chd cell is defined through definition of layer (int), row (int), column (int), shead (float), ehead (float) shead is the head at the start of the stress period, and ehead is the head at the end of the stress period. The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead]
],
1: [
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead]
], ...
kper:
[
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead],
    [lay, row, col, shead, ehead]
]
}
```

Note that if the number of lists is smaller than the number of stress periods, then the last list of chds will apply until the end of the simulation. Full details of all options to specify stress\_period\_data can be found in the flop3 boundaries Notebook in the basic subdirectory of the examples directory.

- **extension** (*string*) – Filename extension (default is 'chd')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is

None.

#### **mxactc**

Maximum number of chds for all stress periods. This is calculated automatically by FloPy based on the information in `stress_period_data`.

**Type** int

### Notes

Parameters are supported in FloPy only when reading in existing models. Parameter values are converted to native values in FloPy and the connection to “parameters” is thus nonexistent.

### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lrcd = {0:[[2, 3, 4, 10., 10.1]]}  #this chd will be applied to all
>>>                                     #stress periods
>>> chd = flopy.modflow.ModflowChd(m, stress_period_data=lrcd)
```

**add\_record**(*kper*, *index*, *values*)

**static get\_default\_dtype**(*structured=True*)

**static get\_empty**(*ncells=0*, *aux\_names=None*, *structured=True*)

**classmethod load**(*f*, *model*, *nper=None*, *ext\_unit\_dict=None*, *check=True*)

Load an existing package.

#### **Parameters**

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If *nper* is `None`, then *nper* will be obtained from the model object. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** **chd** – `ModflowChd` object.

**Return type** `ModflowChd` object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> wel = flopY.modflow.ModflowChd.load('test.chd', m)
```

### `write_file()`

Write the package file.

**Return type** None

## flopY.modflow.mfde4 module

mfde4 module. Contains the ModflowDe4 class. Note that the user can access the ModflowDe4 class as *flopY.modflow.ModflowDe4*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowDe4**(*model*, *itmx*=50, *mxup*=0, *mxlow*=0, *mxbw*=0, *ifreq*=3, *mutd4*=0, *accl*=1.0, *hclose*=1e-05, *iprd4*=1, *extension*='de4', *unitnumber*=None, *filenames*=None)

Bases: *flopY.pakbase.Package*

MODFLOW DE4 - Direct Solver Package

### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **itmx** (*int*) – Maximum number of iterations for each time step. Specify ITMAX = 1 if iteration is not desired. Ideally iteration would not be required for direct solution. However, it is necessary to iterate if the flow equation is nonlinear or if computer precision limitations result in inaccurate calculations as indicated by a large water budget error (default is 50).
- **mxup** (*int*) – Maximum number of equations in the upper part of the equations to be solved. This value impacts the amount of memory used by the DE4 Package. If specified as 0, the program will calculate MXUP as half the number of cells in the model, which is an upper limit (default is 0).
- **mxlow** (*int*) – Maximum number of equations in the lower part of equations to be solved. This value impacts the amount of memory used by the DE4 Package. If specified as 0, the program will calculate MXLOW as half the number of cells in the model, which is an upper limit (default is 0).
- **mxbw** (*int*) – Maximum band width plus 1 of the lower part of the head coefficients matrix. This value impacts the amount of memory used by the DE4 Package. If specified as 0, the program will calculate MXBW as the product of the two smallest grid dimensions plus 1, which is an upper limit (default is 0).
- **ifreq** (*int*) – Flag indicating the frequency at which coefficients in head matrix change. IFREQ = 1 indicates that the flow equations are linear and that coefficients of simulated head for all stress terms are constant for all stress periods. IFREQ = 2 indicates that the flow equations are linear, but coefficients of simulated head for some stress terms may change at the start of each stress period. IFREQ = 3 indicates that a nonlinear flow equation is being solved, which means that some terms in the head coefficients matrix depend on simulated head (default is 3).

- **mutd4** (*int*) – Flag that indicates the quantity of information that is printed when convergence information is printed for a time step. MUTD4 = 0 indicates that the number of iterations in the time step and the maximum head change each iteration are printed. MUTD4 = 1 indicates that only the number of iterations in the time step is printed. MUTD4 = 2 indicates no information is printed (default is 0).
- **accl** (*int*) – Multiplier for the computed head change for each iteration. Normally this value is 1. A value greater than 1 may be useful for improving the rate of convergence when using external iteration to solve nonlinear problems (default is 1).
- **hclose** (*float*) – Head change closure criterion. If iterating (ITMX > 1), iteration stops when the absolute value of head change at every node is less than or equal to HCLOSE. HCLOSE is not used if not iterating, but a value must always be specified (default is 1e-5).
- **iprd4** (*int*) – Time step interval for printing out convergence information when iterating (ITMX > 1). If IPRD4 is 2, convergence information is printed every other time step. A value must always be specified even if not iterating (default is 1).
- **extension** (*string*) – Filename extension (default is 'de4')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> de4 = flopy.modflow.ModflowDe4(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns de4

**Return type** ModflowDe4 object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> de4 = flopY.modflow.ModflowDe4.load('test.de4', m)
```

### `write_file()`

Write the package file.

**Return type** None

## flopY.modflow.mfdis module

mfdis module. Contains the `ModflowDis` class. Note that the user can access the `ModflowDis` class as `flopY.modflow.ModflowDis`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowDis`(*model*, *nlay*=1, *nrow*=2, *ncol*=2, *nper*=1, *delr*=1.0, *delc*=1.0, *laycbd*=0, *top*=1, *botm*=0, *perlen*=1, *nstp*=1, *tsmult*=1, *steady*=True, *ituni*=4, *lenuni*=2, *extension*='dis', *unitnumber*=None, *filenames*=None, *xul*=None, *yul*=None, *rotation*=None, *proj4\_str*=None, *start\_datetime*=None)

Bases: `flopY.pakbase.Package`

MODFLOW Discretization Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.Modflow`) to which this package will be added.
- **nlay** (*int*) – Number of model layers (the default is 1).
- **nrow** (*int*) – Number of model rows (the default is 2).
- **ncol** (*int*) – Number of model columns (the default is 2).
- **nper** (*int*) – Number of model stress periods (the default is 1).
- **delr** (*float or array of floats (ncol), optional*) – An array of spacings along a row (the default is 1.0).
- **delc** (*float or array of floats (nrow), optional*) – An array of spacings along a column (the default is 0.0).
- **laycbd** (*int or array of ints (nlay), optional*) – An array of flags indicating whether or not a layer has a Quasi-3D confining bed below it. 0 indicates no confining bed, and not zero indicates a confining bed. LAYCBD for the bottom layer must be 0. (the default is 0)
- **top** (*float or array of floats (nrow, ncol), optional*) – An array of the top elevation of layer 1. For the common situation in which the top layer represents a water-table aquifer, it may be reasonable to set Top equal to land-surface elevation (the default is 1.0)
- **botm** (*float or array of floats (nlay, nrow, ncol), optional*) – An array of the bottom elevation for each model cell (the default is 0.)
- **perlen** (*float or array of floats (nper)*) – An array of the stress period lengths.



- **nstp** (*int or array of ints (nper)*) – Number of time steps in each stress period (default is 1).
- **tsmult** (*float or array of floats (nper)*) – Time step multiplier (default is 1.0).
- **steady** (*bool or array of bool (nper)*) – true or False indicating whether or not stress period is steady state (default is True).
- **itmuni** (*int*) – Time units, default is days (4)
- **lenuni** (*int*) – Length units, default is meters (2)
- **extension** (*string*) – Filename extension (default is 'dis')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.
- **xul** (*float*) – x coordinate of upper left corner of the grid, default is None, which means xul will be set to zero.
- **yul** (*float*) – y coordinate of upper-left corner of the grid, default is None, which means yul will be calculated as the sum of the delc array. This default, combined with the xul and rotation defaults will place the lower-left corner of the grid at (0, 0).
- **rotation** (*float*) – counter-clockwise rotation (in degrees) of the grid about the lower-left corner. default is 0.0
- **proj4\_str** (*str*) – PROJ4 string that defines the projected coordinate system (e.g. '+proj=utm +zone=14 +datum=WGS84 +units=m +no\_defs '). Can be an EPSG code (e.g. 'EPSG:32614'). Default is None.
- **start\_datetime** (*str*) – starting datetime of the simulation. default is '1/1/1970'

**heading**

Text string written to top of package input file.

**Type** str

**Notes****Examples**

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> dis = flopy.modflow.ModflowDis(m)
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check dis package data for zero and negative thicknesses.

**Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a sting is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen

- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

### Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow.load('model.nam')
>>> m.dis.check()
```

#### **checklayerthickness()**

Check layer thickness.

#### **get\_cell\_volumes()**

Get an array of cell volumes.

**Returns** **vol**

**Return type** array of floats (nlay, nrow, ncol)

#### **get\_final\_totim()**

Get the totim at the end of the simulation

**Returns** **totim** – maximum simulation totim

**Return type** float

#### **get\_kstp\_kper\_toffset**(*t=0.0, use\_cached\_totim=False*)

Get the stress period, time step, and time offset from passed time.

##### **Parameters**

- **t** (*float*) – totim to return the stress period, time step, and toffset for based on time discretization data. Default is 0.
- **use\_cached\_totim** (*bool*) – optional flag to use a cached calculation of totim, vs. dynamically calculating totim. Setting to True significantly speeds up looped operations that call this function (default is False).

##### **Returns**

- **kstp** (*int*) – time step in stress period corresponding to passed totim
- **kper** (*int*) – stress period corresponding to passed totim
- **toffset** (*float*) – time offset of passed totim from the beginning of kper

#### **get\_layer**(*i, j, elev*)

Return the layer for an elevation at an i, j location.

##### **Parameters**

- **i** (*row index (zero-based)*) –
- **j** (*column index*) –
- **elev** (*elevation (in same units as model)*) –

**Returns** **k**

**Return type** zero-based layer index

**get\_lrc(nodes)**

Get zero-based layer, row, column from a list of zero-based MODFLOW node numbers.

**Returns** **v** – and column (j) for each node in the input list

**Return type** list of tuples containing the layer (k), row (i),

**get\_node(lrc\_list)**

Get zero-based node number from a list of zero-based MODFLOW layer, row, column tuples.

**Returns** **v** – and column (j) tuple in the input list

**Return type** list of MODFLOW nodes for each layer (k), row (i),

**get\_node\_coordinates()**

Get y, x, and z cell centroids in local model coordinates.

**Returns**

- **y** (*list of cell y-centroids*)
- **x** (*list of cell x-centroids*)
- **z** (*array of floats (nlay, nrow, ncol)*)

**get\_rc\_from\_node\_coordinates(x, y, local=True)**

Get the row and column of a point or sequence of points in model coordinates.

**Parameters**

- **x** (*float or sequence of floats*) – x coordinate(s) of points to find in model grid
- **y** (*float or sequence floats*) – y coordinate(s) of points to find in model grid
- **local** (*bool*) – x and y coordinates are in model local coordinates. If false, then x and y are in world coordinates. (default is True)

**Returns**

- **r** (*row or sequence of rows (zero-based)*)
- **c** (*column or sequence of columns (zero-based)*)

**get\_totim(use\_cached=False)**

Get the totim at the end of each time step

**Parameters** **use\_cached** (*bool*) – method to use cached totim values instead of calculating totim dynamically

**Returns** **totim** – numpy array with simulation totim at the end of each time step

**Return type** numpy array

**get\_totim\_from\_kper\_toffset(kper=0, toffset=0.0, use\_cached\_totim=False)**

Get totim from a passed kper and time offset from the beginning of a stress period

**Parameters**

- **kper** (*int*) – stress period. Default is 0
- **toffset** (*float*) – time offset relative to the beginning of kper
- **use\_cached\_totim** (*bool*) – optional flag to use a cached calculation of totim, vs. dynamically calculating totim. Setting to True significantly speeds up looped operations that call this function (default is False).

**Returns** **t** – totim to return the stress period, time step, and toffset for based on time discretization data. Default is 0.

**Return type** float

**getbotm**(*k=None*)

Get the bottom array.

**Returns**

- **botm** (array of floats (*nlay*, *nrow*, *ncol*), or)
- **botm** (array of floats (*nrow*, *ncol*) if *k* is not none)

**gettop**()

Get the top array.

**Returns** **top**

**Return type** array of floats (*nrow*, *ncol*)

**classmethod** **load**(*f*, *model*, *ext\_unit\_dict=None*, *check=True*)

Load an existing package.

**Parameters**

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.
- **check** (*bool*) – Check package data for common errors. (default True)

**Returns** **dis** – ModflowDis object.

**Return type** ModflowDis object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> dis = flopy.modflow.ModflowDis.load('test.dis', m)
```

**write\_file**(*check=True*)

Write the package file.

**Parameters** **check** (*bool*) – Check package data for common errors. (default True)

**Return type** None

**property** **zcentroids**

**get\_layer**(*dis*, *i*, *j*, *elev*)

Return the layers for elevations at *i*, *j* locations.

**Parameters**

- **dis** (*flopy.modflow.ModflowDis object*) –
- **i** (*scalar or sequence*) – row index (zero-based)

- **j** (*scaler or sequence*) – column index
- **elev** (*scaler or sequence*) – elevation (in same units as model)

**Returns** **k** – zero-based layer index

**Return type** np.ndarray (1-D) or scalar

### flopY.modflow.mfdrn module

mfdrn module. Contains the ModflowDrn class. Note that the user can access the ModflowDrn class as *flopY.modflow.ModflowDrn*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowDrn**(*model*, *ipakcb=None*, *stress\_period\_data=None*, *dtype=None*, *extension='drn'*, *unitnumber=None*, *options=None*, *filenames=None*, *\*\*kwargs*)

Bases: *flopY.pakbase.Package*

MODFLOW Drain Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is None).
- **stress\_period\_data** (*list of boundaries, recarrays, or dictionary of*) – boundaries. Each drain cell is defined through definition of layer(int), row(int), column(int), elevation(float), conductance(float). The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
  ],
 1: [
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
  ], ...
kper:
  [
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
  ]
}
```

Note that if no values are specified for a certain stress period, then the list of boundaries for the previous stress period for which values were defined is used. Full details of all options to specify stress\_period\_data can be found in the flopY3boundaries Notebook in the basic subdirectory of the examples directory.

- **dtype** (*dtype definition*) – if data type is different from default
- **options** (*list of strings*) – Package options. (default is None).
- **extension** (*string*) – Filename extension (default is 'drn')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy. If "RETURNFLOW" is passed in options, the drain return package (DRT) is activated, which expects a different (longer) dtype for stress\_period\_data

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> lrcec = {0:[2, 3, 4, 10., 100.]} #this drain will be applied to all
>>>                                     #stress periods
>>> drn = flopy.modflow.ModflowDrn(m1, stress_period_data=lrcec)
```

**add\_record**(*kper, index, values*)

**static get\_default\_dtype**(*structured=True, is\_drt=False*)

**static get\_empty**(*ncells=0, aux\_names=None, structured=True, is\_drt=False*)

**classmethod load**(*f, model, nper=None, ext\_unit\_dict=None, check=True*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function *flopy.utils.mfreadnam.parsenamefile*.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** *drn* – ModflowDrn object.

**Return type** ModflowDrn object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> drn = flopY.modflow.ModflowDrn.load('test.drn', m)
```

**write\_file**(*check=True*)  
Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopY.modflow.mfdrt module

mfdrt module. Contains the ModflowDrt class. Note that the user can access the ModflowDrt class as *flopY.modflow.ModflowDrt*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowDrt**(*model, ipakcb=None, stress\_period\_data=None, dtype=None, extension='drt', unitnumber=None, options=None, filenames=None, \*\*kwargs*)

Bases: *flopY.pakbase.Package*

MODFLOW Drain Return Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is None).
- **stress\_period\_data** (*list of boundaries, recarrays, or dictionary of*) – boundaries. Each drain return cell is defined through definition of layer(int), row(int), column(int), elevation(float), conductance(float), layerR (int) , rowR (int), colR (int) and rfprop (float). The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
  ],
 1: [
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
  ], ...
kper:
  [
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
    [lay, row, col, stage, cond, layerr, rowr, colr, rfprop],
```

(continues on next page)

(continued from previous page)

```
]
}
```

Note that if no values are specified for a certain stress period, then the list of boundaries for the previous stress period for which values were defined is used. Full details of all options to specify `stress_period_data` can be found in the `flopy3boundaries` Notebook in the basic subdirectory of the examples directory.

- **dtype** (*dtype definition*) – if data type is different from default
- **options** (*list of strings*) – Package options. (default is None).
- **extension** (*string*) – Filename extension (default is 'drt')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If `filenames=None` the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, `modflowtest.cbc`), if `ipakcbc` is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if `ipakcbc` is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> lrcec = {0:[2, 3, 4, 10., 100., 1, 1, 1, 1.0]} #this drain will be applied to
↳all
>>>                                     #stress periods
>>> drt = flopy.modflow.ModflowDrt(m1, stress_period_data=lrcec)
```

**add\_record**(*kper, index, values*)

**static get\_default\_dtype**(*structured=True*)

**static get\_empty**(*ncells=0, aux\_names=None, structured=True, is\_drt=False*)

**classmethod load**(*f, model, nper=None, ext\_unit\_dict=None, check=True*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file



handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `drn` – ModflowDrt object.

**Return type** ModflowDrt object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> drn = flopY.modflow.ModflowDrt.load('test.drt', m)
```

**write\_file**(*check=True*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopY.modflow.mfevt module

`mfgghb` module. Contains the `ModflowEvt` class. Note that the user can access the `ModflowEvt` class as `flopY.modflow.ModflowEvt`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowEvt**(*model, nevtop=3, ipakcb=None, surf=0.0, evtr=0.001, exdp=1.0, ievt=1, extension='evt', unitnumber=None, filenames=None, external=True*)

Bases: `flopY.pakbase.Package`

MODFLOW Evapotranspiration Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.ModflowEvt`) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If `ipakcb` is non-zero cell-by-cell budget data will be saved. (default is 0).
- **nevtop** (*int*) – is the recharge option code. 1: ET is calculated only for cells in the top grid layer 2: ET to layer defined in `ievt` 3: ET to highest active cell (default is 3).
- **surf** (*float or filename or ndarray or dict keyed on kper (zero-based)*) – is the ET surface elevation. (default is 0.0, which is used for all stress periods).
- **evtr** (*float or filename or ndarray or dict keyed on kper (zero-based)*) – is the maximum ET flux (default is 1e-3, which is used for all stress periods).
- **exdp** (*float or filename or ndarray or dict keyed on kper (zero-based)*) – is the ET extinction depth (default is 1.0, which is used for all stress periods).
- **ievt** (*int or filename or ndarray or dict keyed on kper (zero-based)*) – is the layer indicator variable (default is 1, which is used for all stress periods).

- **extension** (*string*) – Filename extension (default is 'evt')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> evt = flopY.modflow.ModflowEvt(m, nevtop=3, evtr=1.2e-4)
```

**classmethod** `load(f, model, nper=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If nper is None, then nper will be obtained from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** `evt` – ModflowEvt object.

**Return type** ModflowEvt object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> evt = flopY.modflow.mfevt.load('test.evt', m)
```

**write\_file**(*f=None*)

Write the package file.

**Return type** None

**flop.modflow.mffhb module**

mffhb module. Contains the ModflowFhb class. Note that the user can access the ModflowFhb class as *flop.modflow.ModflowFhb*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowFhb(model, nbdtim=1, nflw=0, nhed=0, ifhbss=0, ipakcb=None, nfhb1=0, nfhb2=0, ifhbpt=0,
                  bdtimcnstm=1.0, bdtim=[0.0], cnstm5=1.0, ds5=None, cnstm7=1.0, ds7=None,
                  extension='fhb', unitnumber=None, filenames=None)
```

Bases: *flop.pakbase.Package*

MODFLOW Flow and Head Boundary Package Class.

**Parameters**

- **model** (*model object*) – The model object (of type *flop.modflow.mf.ModflowFhb*) to which this package will be added.
- **nbdtim** (*int*) – The number of times at which flow and head will be specified for all selected cells. (default is 1)
- **nflw** (*int*) – Number of cells at which flows will be specified. (default is 0)
- **nhed** (*int*) – Number of cells at which heads will be specified. (default is 0)
- **ifhbss** (*int*) – FHB steady-state option flag. If the simulation includes any transient-state stress periods, the flag is read but not used; in this case, specified-flow, specified-head, and auxiliary-variable values will be interpolated for steady-state stress periods in the same way that values are interpolated for transient stress periods. If the simulation includes only steady-state stress periods, the flag controls how flow, head, and auxiliary-variable values will be computed for each steady-state solution. (default is 0)
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is None).
- **nfhb1** (*int*) – Number of auxiliary variables whose values will be computed for each time step for each specified-flow cell. Auxiliary variables are currently not supported. (default is 0)
- **nfhb2** (*int*) – Number of auxiliary variables whose values will be computed for each time step for each specified-head cell. Auxiliary variables are currently not supported. (default is 0)
- **ifhbpt** (*int*) – Flag for printing values of data list. Applies to datasets 4b, 5b, 6b, 7b, and 8b. If ifhbpt > 0, datasets read at the beginning of the simulation will be printed. Otherwise, the datasets will not be printed. (default is 0).
- **bdtimecnstm** (*float*) – A constant multiplier for data list bdtim. (default is 1.0)
- **bdtime** (*float or list of floats*) – Simulation time at which values of specified flow and (or) values of specified head will be read. nbdtim values are required. (default is 0.0)
- **cnstm5** (*float*) – A constant multiplier for data list flwrat. (default is 1.0)
- **ds5** (*list or numpy array or recarray*) – Each FHB flwrat cell (dataset 5) is defined through definition of layer(int), row(int), column(int),iaux(int), flwrat[nbdtim](float). There should be nflw entries. (default is None) The simplest form is a list of lists with the FHB flow boundaries. This gives the form of:

```
ds5 =
[
    [lay, row, col,iaux, flwrat1, flwra2, ..., flwrat(nbdtime)],
    [lay, row, col,iaux, flwrat1, flwra2, ..., flwrat(nbdtime)],
    [lay, row, col,iaux, flwrat1, flwra2, ..., flwrat(nbdtime)],
    [lay, row, col,iaux, flwrat1, flwra2, ..., flwrat(nbdtime)]
]
```

- **cnstm7** (*float*) – A constant multiplier for data list sbhedt. (default is 1.0)
- **ds7** (*list or numpy array or recarray*) – Each FHB sbhed cell (dataset 7) is defined through definition of layer(int), row(int), column(int),iaux(int), sbhed[nbdtime](float). There should be nhed entries. (default is None) The simplest form is a list of lists with the FHB flow boundaries. This gives the form of:

```
ds7 =
[
    [lay, row, col,iaux, sbhed1, sbhed2, ..., sbhed(nbdtime)],
    [lay, row, col,iaux, sbhed1, sbhed2, ..., sbhed(nbdtime)],
    [lay, row, col,iaux, sbhed1, sbhed2, ..., sbhed(nbdtime)],
    [lay, row, col,iaux, sbhed1, sbhed2, ..., sbhed(nbdtime)]
]
```

- **extension** (*string*) – Filename extension (default is 'fhb')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> fhb = flopy.modflow.ModflowFhb(m)
```

```
static get_default_dtype(nbdtim=1, structured=True, head=False)
```

```
static get_empty(ncells=0, nbdtim=1, structured=True, head=False)
```

```
classmethod load(f, model, nper=None, ext_unit_dict=None)
```

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is `None`, then `nper` will be obtained from the model object. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `fhb` – ModflowFhb object.

**Return type** ModflowFhb object

### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> fhb = flopy.modflow.ModflowFhb.load('test.fhb', m)
```

#### `write_file()`

Write the package file.

**Return type** `None`

### `flopy.modflow.mfflwb module`

```
class ModflowFlwb(model, nqfb=0, nqcfb=0, nqtfb=0, iufbobsv=0, tomultfb=1.0, nqobfb=None, nqclfb=None,
    obsnam=None, irefsp=None, toffset=None, flwobs=None, layer=None, row=None,
    column=None, factor=None, flowtype=None, extension=None, no_print=False,
    options=None, filenames=None, unitnumber=None)
```

Bases: `flopy.pakbase.Package`

Head-dependent flow boundary Observation package class. Minimal working example that will be refactored in a future version.

#### Parameters

- **nqfb** (*int*) – Number of cell groups for the head-dependent flow boundary observations
- **nqcfb** (*int*) – Greater than or equal to the total number of cells in all cell groups
- **nqtfb** (*int*) – Total number of head-dependent flow boundary observations for all cell groups
- **iufbobsv** (*int*) – unit number where output is saved
- **tomultfb** (*float*) – Time-offset multiplier for head-dependent flow boundary observations. The product of `tomultfb` and `toffset` must produce a time value in units consistent with other model input. `tomultfb` can be dimensionless or can be used to convert the units of `toffset` to the time unit used in the simulation.
- **nqobfb** (*int list of length nqfb*) – The number of times at which flows are observed for the group of cells

- **nqclfb** (*int list of length nqfb*) – Is a flag, and the absolute value of nqclfb is the number of cells in the group. If nqclfb is less than zero, factor = 1.0 for all cells in the group.
- **obsnam** (*string list of length nqtfb*) – Observation name
- **irefsp** (*int of length nqtfb*) – The zero-based stress period to which the observation time is referenced. The reference point is the beginning of the specified stress period.
- **toffset** (*float list of length nqtfb*) – Is the time from the beginning of the stress period irefsp to the time of the observation. toffset must be in units such that the product of toffset and tomultfb are consistent with other model input. For steady state observations, specify irefsp as the steady state stress period and toffset less than or equal to perlen of the stress period. If perlen is zero, set toffset to zero. If the observation falls within a time step, linearly interpolation is used between values at the beginning and end of the time step.
- **flwobs** (*float list of length nqtfb*) – Observed flow value from the head-dependent flow boundary into the aquifer (+) or the flow from the aquifer into the boundary (-)
- **layer** (*int list of length (nqfb, nqclfb)*) – The zero-based layer index for the cell included in the cell group.
- **row** (*int list of length (nqfb, nqclfb)*) – The zero-based row index for the cell included in the cell group.
- **column** (*int list of length (nqfb, nqclfb)*) – The zero-based column index of the cell included in the cell group.
- **factor** (*float list of length (nqfb, nqclfb)*) – Is the portion of the simulated gain or loss in the cell that is included in the total gain or loss for this cell group (fn of eq. 5).
- **flowtype** (*string*) – String that corresponds to the head-dependent flow boundary condition type (CHD, GHB, DRN, RIV)
- **extension** (*list of string*) – Filename extension. If extension is None, extension is set to ['chob','obc','gbob','obg','drob','obd', 'rvob','obr'] (default is None).
- **no\_print** (*boolean*) – When True or 1, a list of flow observations will not be written to the Listing File (default is False)
- **options** (*list of strings*) – Package options (default is None).
- **unitnumber** (*list of int*) – File unit number. If unitnumber is None, unitnumber is set to [40, 140, 41, 141, 42, 142, 43, 143] (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the flwob output name will be created using the model name and .out extension (for example, modflowtest.out), if iufbobsv is a number greater than zero. If a single string is passed the package will be set to the string and flwob output name will be created using the model name and .out extension, if iufbobsv is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

This represents a minimal working example that will be refactored in a future version.

### ftype()

**classmethod** `load(f, model, ext_unit_dict=None, check=True)`

Load an existing package.

#### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `flwob` – ModflowFlwob package object.

**Return type** ModflowFlwob package object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> hobs = flopy.modflow.ModflowFlwob.load('test.drob', m)
```

### write\_file()

Write the package file

**Return type** None

## flopy.modflow.mfgage module

mfgage module. Contains the ModflowGage class. Note that the user can access the ModflowGage class as `flopy.modflow.ModflowGage`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowGage(model, numgage=0, gage_data=None, files=None, extension='gage', unitnumber=None, filenames=None, **kwargs)`

Bases: `flopy.pakbase.Package`

MODFLOW Gage Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **numgage** (*int*) – The total number of gages included in the gage file (default is 0).
- **gage\_data** (*list or numpy array*) – data for dataset 2a and 2b in the gage package. If a list is provided then the list includes 2 to 3 entries (LAKE UNIT [OUTTYPE]) for each LAK Package entry and 4 entries (GAGESEG GAGERCH UNIT OUTTYPE)

for each SFR Package entry. If a numpy array is passed each gage location must have 4 entries, where LAK Package gages can have any value for the second column. The numpy array can be created using the `get_empty()` method available in `ModflowGage`. Default is `None`

- **files** (*list of strings*) – Names of gage output files. A file name must be provided for each gage. If files are not provided and `filenames=None` then a gage name will be created using the model name and the gage number (for example, `modflowtest.gage1.go`). Default is `None`.
- **extension** (*string*) – Filename extension (default is `'gage'`)
- **unitnumber** (*int*) – File unit number (default is `None`).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If `filenames=None` the package name will be created using the model name and package extension and gage output names will be created using the model name and the gage number (for example, `modflowtest.gage1.go`). If a single string is passed the package will be set to the string and gage output names will be created using the model name and the gage number. To define the names for all gage files (input and output) the length of the list of strings should be `numgage + 1`. Default is `None`.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> gages = [[-1, -26, 1], [-2, -27, 1]]
>>> files = ['gage1.go', 'gage2.go']
>>> gage = flopy.modflow.ModflowGage(m, numgage=2,
>>>                                     gage_data=gages, files=files)
```

**static** `get_default_dtype()`

**static** `get_empty(ncells=0, aux_names=None, structured=True)`

**classmethod** `load(f, model, nper=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is `None`, then `nper` will be obtained from the model object. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `str` – `ModflowStr` object.



**Return type** ModflowStr object

### Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> gage = flopY.modflow.ModflowGage.load('test.gage', m)
```

**write\_file()**

Write the package file.

**Return type** None

### flopY.modflow.mfghb module

mfghb module. Contains the ModflowGhb class. Note that the user can access the ModflowGhb class as *flopY.modflow.ModflowGhb*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowGhb**(*model*, *ipakcb*=None, *stress\_period\_data*=None, *dtype*=None, *no\_print*=False, *options*=None, *extension*='ghb', *unitnumber*=None, *filenames*=None)

Bases: *flopY.pakbase.Package*

MODFLOW General-Head Boundary Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **stress\_period\_data** (*list of boundaries, recarray of boundaries or,*) – dictionary of boundaries.

Each ghb cell is defined through definition of layer(int), row(int), column(int), stage(float), conductance(float) The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
  ],
1: [
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
    [lay, row, col, stage, cond],
  ], ...
kper:
  [
    [lay, row, col, stage, cond],
```

(continues on next page)

(continued from previous page)

```
[lay, row, col, stage, cond],
[lay, row, col, stage, cond],
]
}
```

Note that if no values are specified for a certain stress period, then the list of boundaries for the previous stress period for which values were defined is used. Full details of all options to specify `stress_period_data` can be found in the `flopY3boundaries` Notebook in the `basic` subdirectory of the `examples` directory

- **dtype** (*dtype definition*) – if data type is different from default
- **options** (*list of strings*) – Package options. (default is `None`).
- **extension** (*string*) – Filename extension (default is `'ghb'`)
- **unitnumber** (*int*) – File unit number (default is `None`).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If `filenames=None` the package name will be created using the model name and package extension and the cbc output name will be created using the model name and `.cbc` extension (for example, `modflowtest.cbc`), if `ipakcbc` is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and `.cbc` extension, if `ipakcbc` is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is `None`.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> lrcsc = {0:[2, 3, 4, 10., 100.]} #this ghb will be applied to all
>>>                                     #stress periods
>>> ghb = flopy.modflow.ModflowGhb(m1, stress_period_data=lrcsc)
```

**add\_record**(*kper, index, values*)

**static get\_default\_dtype**(*structured=True*)

**static get\_empty**(*ncells=0, aux\_names=None, structured=True*)

**classmethod load**(*f, model, nper=None, ext\_unit\_dict=None, check=True*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is `None`, then `nper` will be obtained from the model object. (default is `None`).

- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `ghb` – ModflowGhb object.

**Return type** ModflowGhb object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> ghb = flopy.modflow.ModflowGhb.load('test.ghb', m)
```

**write\_file**(*check=True*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopy.modflow.mfgmg module

mfgmg module. Contains the ModflowGmg class. Note that the user can access the ModflowGmg class as `flopy.modflow.ModflowGmg`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowGmg**(*model, mxiter=50, iiter=30, iadamp=0, hclose=1e-05, rclose=1e-05, relax=1.0, ioutgmg=0, iunitmhc=None, ism=0, isc=0, damp=1.0, dup=0.75, dlow=0.01, chglimit=1.0, extension='gmg', unitnumber=None, filenames=None*)

Bases: `flopy.pakbase.Package`

MODFLOW GMG Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **mxiter** (*int*) – maximum number of outer iterations. (default is 50)
- **iiter** (*int*) – maximum number of inner iterations. (default is 30)
- **iadamp** (*int*) – is a flag that controls adaptive damping. The possible values of `iadamp` are.

If `iadamp = 0`, then the value assigned to DAMP is used as a constant damping parameter.

If `iadamp = 1`, the value of `damp` is used for the first nonlinear iteration. The damping parameter is adaptively varied on the basis of the head change, using Cooley's method as described in Mehl and Hill (2001), for subsequent iterations.

If `iadamp = 2`, the relative reduced residual damping method documented in Mehl and Hill (2001) and modified by Banta (2006) is used.

When `iadamp` is specified as 2 and the value specified for DAMP is less than 0.5, the closure criterion for the inner iterations (`drclose`) is assigned simply as `rclose`. When

damp is between 0.5 and 1.0, inclusive, or when iadamp is specified as 0 or 1, drclose is calculated according to equation 20 on p. 9 of Wilson and Naff (2004).

- **hclose** (*float*) – is the head change criterion for convergence. (default is 1e-5).
- **rclose** (*float*) – is the residual criterion for convergence. (default is 1e-5)
- **relax** (*float*) – is a relaxation parameter for the ILU preconditioned conjugate gradient method. The relax parameter can be used to improve the spectral condition number of the ILU preconditioned system. The value of relax should be approximately one. However, the relaxation parameter can cause the factorization to break down. If this happens, then the gm solver will report an assembly error and a value smaller than one for relax should be tried. This item is read only if isc = 4.
- **ioutgm** (*int*) – is a flag that controls the output of the gm solver. The possible values of ioutgm are.

If ioutgm = 0, then only the solver inputs are printed.

If ioutgm = 1, then for each linear solve, the number of pcg iterations, the value of the damping parameter, the l2norm of the residual, and the maxnorm of the head change and its location (column, row, layer) are printed. At the end of a time/stress period, the total number of gm calls, pcg iterations, and a running total of pcg iterations for all time/stress periods are printed.

If ioutgm = 2, then the convergence history of the pcg iteration is printed, showing the l2norm of the residual and the convergence factor for each iteration.

ioutgm = 3 is the same as ioutgm = 1 except output is sent to the terminal instead of the modflow list output file.

ioutgm = 4 is the same as ioutgm = 2 except output is sent to the terminal instead of the modflow list output file.

(default is 0)

- **iunitmhc** (*int*) – is a flag and a unit number, which controls output of maximum head change values. If iunitmhc = 0, maximum head change values are not written to an output file. If iunitmhc > 0, maximum head change values are written to unit iunitmhc. Unit iunitmhc should be listed in the Name file with 'DATA' as the file type. If iunitmhc < 0 or is not present, iunitmhc defaults to 0. (default is 0)
- **ism** (*int*) – is a flag that controls the type of smoother used in the multigrid preconditioner. If ism = 0, then ilu(0) smoothing is implemented in the multigrid preconditioner; this smoothing requires an additional vector on each multigrid level to store the pivots in the ilu factorization. If ism = 1, then symmetric gaussseidel (sgs) smoothing is implemented in the multigrid preconditioner. No additional storage is required if ism = 1; users may want to use this option if available memory is exceeded or nearly exceeded when using ism = 0. Using sgs smoothing is not as robust as ilu smoothing; additional iterations are likely to be required in reducing the residuals. In extreme cases, the solver may fail to converge as the residuals cannot be reduced sufficiently. (default is 0)
- **isc** (*int*) – is a flag that controls semicoarsening in the multigrid preconditioner. If isc = 0, then the rows, columns and layers are all coarsened. If isc = 1, then the rows and columns are coarsened, but the layers are not. If isc = 2, then the columns and layers are coarsened, but the rows are not. If isc = 3, then the rows and layers are coarsened, but the columns are not. If isc = 4, then there is no coarsening. Typically, the value of isc should be 0 or 1. In the case that there are large vertical variations in the hydraulic conductivities, then a value of 1 should be used. If no coarsening is implemented (isc =

4), then the gmg solver is comparable to the pcg2 ilu(0) solver described in Hill (1990) and uses the least amount of memory. (default is 0)

- **damp** (*float*) – is the value of the damping parameter. For linear problems, a value of 1.0 should be used. For nonlinear problems, a value less than 1.0 but greater than 0.0 may be necessary to achieve convergence. A typical value for nonlinear problems is 0.5. Damping also helps control the convergence criterion of the linear solve to alleviate excessive pcg iterations. (default 1.)
- **dup** (*float*) – is the maximum damping value that should be applied at any iteration when the solver is not oscillating; it is dimensionless. An appropriate value for dup will be problem-dependent. For moderately nonlinear problems, reasonable values for dup would be in the range 0.5 to 1.0. For a highly nonlinear problem, a reasonable value for dup could be as small as 0.1. When the solver is oscillating, a damping value as large as 2.0 x DUP may be applied. (default is 0.75)
- **dlow** (*float*) – is the minimum damping value to be generated by the adaptive-damping procedure; it is dimensionless. An appropriate value for dlow will be problem-dependent and will be smaller than the value specified for dup. For a highly nonlinear problem, an appropriate value for dlow might be as small as 0.001. Note that the value specified for the variable, chglimit, could result in application of a damping value smaller than dlow. (default is 0.01)
- **chglimit** (*float*) – is the maximum allowed head change at any cell between outer iterations; it has units of length. The effect of chglimit is to determine a damping value that, when applied to all elements of the head-change vector, will produce an absolute maximum head change equal to chglimit. (default is 1.0)
- **extension** (*list string*) – Filename extension (default is 'gmg')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the gmg output name will be created using the model name and .cbc extension (for example, modflowtest.gmg.out), if iunitmhc is a number greater than zero. If a single string is passed the package will be set to the string and gmg output names will be created using the model name and .gmg.out extension, if iunitmhc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

**Return type** None

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> gmg = flopy.modflow.ModflowGmg(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.

- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `gmg`

**Return type** `ModflowGmg` object

### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> gmg = flopy.modflow.ModflowGmg.load('test.gmg', m)
```

**write\_file()**

Write the package file.

**Return type** `None`

### `flopy.modflow.mfhfb` module

`mfhfb` module. Contains the `ModflowHfb` class. Note that the user can access the `ModflowHfb` class as `flopy.modflow.ModflowHfb`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowHfb`(*model*, *nphfb*=0, *mxfb*=0, *nhfbnp*=0, *hfb\_data*=None, *nacthfb*=0, *no\_print*=False, *options*=None, *extension*='hfb', *unitnumber*=None, *filenames*=None)

Bases: `flopy.pakbase.Package`

MODFLOW HFB6 - Horizontal Flow Barrier Package

#### Parameters

- **model** (*model object*) – The model object (of type: `class:flopy.modflow.mf.Modflow`) to which this package will be added.
- **nphfb** (*int*) – Number of horizontal-flow barrier parameters. Note that for an HFB parameter to have an effect in the simulation, it must be defined and made active using NACTHFB to have an effect in the simulation (default is 0).
- **mxfb** (*int*) – Maximum number of horizontal-flow barrier barriers that will be defined using parameters (default is 0).
- **nhfbnp** (*int*) – Number of horizontal-flow barriers not defined by parameters. This is calculated automatically by FloPy based on the information in `layer_row_column_data` (default is 0).
- **hfb\_data** (*list of records*) – In its most general form, this is a list of horizontal-flow barrier records. A barrier is conceptualized as being located on the boundary between two adjacent finite difference cells in the same layer. The innermost list is the layer, `row1`, `column1`, `row2`, `column2`, and hydrologic characteristics for a single hfb between the cells. The hydraulic characteristic is the barrier hydraulic conductivity divided by the width of the horizontal-flow barrier. (default is None). This gives the form of:

```
hfb_data = [
    [lay, row1, col1, row2, col2, hydchr],
    [lay, row1, col1, row2, col2, hydchr],
    [lay, row1, col1, row2, col2, hydchr],
].
```

- **nacthfb** (*int*) – The number of active horizontal-flow barrier parameters (default is 0).
- **no\_print** (*boolean*) – When True or 1, a list of horizontal flow barriers will not be written to the Listing File (default is False)
- **options** (*list of strings*) – Package options (default is None).
- **extension** (*string*) – Filename extension (default is ‘hfb’).
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If file-names=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> hfb_data = [[0, 10, 4, 10, 5, 0.01],[1, 10, 4, 10, 5, 0.01]]
>>> hfb = flopy.modflow.ModflowHfb(m, hfb_data=hfb_data)
```

**static get\_default\_dtype**(*structured=True*)

Get the default dtype for hfb data

**static get\_empty**(*ncells=0, aux\_names=None, structured=True*)

Get an empty recarray that corresponds to hfb dtype and has been extended to include aux variables and associated aux names.

**classmethod load**(*f, model, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type: `class:flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** **hfb** – ModflowHfb object (of type `flopy.modflow.mfbas.ModflowHfb`)

**Return type** ModflowHfb object

### Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> hfb = flopY.modflow.ModflowHfb.load('test.hfb', m)
```

**write\_file()**

Write the package file.

**Return type** None

### flopY.modflow.mfhob module

**class HeadObservation**(*model, tomulth=1.0, obsname='HOBS', layer=0, row=0, column=0, irefsp=None, roff=0.0, coff=0.0, itt=1, tmax=None, mlay=None, time\_series\_data=None, names=None*)

Bases: object

Create single HeadObservation instance from a time series array. A list of HeadObservation instances are passed to the ModflowHob package.

#### Parameters

- **tomulth** (*float*) – Time-offset multiplier for head observations. Default is 1.
- **obsname** (*string*) – Observation name. Default is 'HOBS'
- **layer** (*int*) – The zero-based layer index of the cell in which the head observation is located. If layer is less than zero, hydraulic heads from multiple layers are combined to calculate a simulated value. The number of layers equals the absolute value of layer, or abs(layer). Default is 0.
- **row** (*int*) – The zero-based row index for the observation. Default is 0.
- **column** (*int*) – The zero-based column index of the observation. Default is 0.
- **irefsp** (*int*) – The zero-based stress period to which the observation time is referenced.
- **roff** (*float*) – Fractional offset from center of cell in Y direction (between rows). Default is 0.
- **coff** (*float*) – Fractional offset from center of cell in X direction (between columns). Default is 0.
- **itt** (*int*) – Flag that identifies whether head or head changes are used as observations. itt = 1 specified for heads and itt = 2 specified if initial value is head and subsequent changes in head. Only specified if irefsp is < 0. Default is 1.
- **tmax** (*float*) – Maximum simulation time calculated using get\_final\_totim function of ModflowDis. Added to avoid repetitive calls.
- **mlay** (*dictionary of length (abs(irefsp))*) – Key represents zero-based layer numbers for multilayer observations and value represents the fractional value for each layer of multilayer observations. If mlay is None, a default mlay of {0: 1.} will be used (default is None).



- **time\_series\_data** (*list or numpy array*) – Two-dimensional list or numpy array containing the simulation time of the observation and the observed head `[[totim, hob]]`. If `time_series_data` is `None`, a default observation of 0. at totim 0. will be created (default is `None`).
- **names** (*list*) – List of specified observation names. If `names` is `None`, observation names will be automatically generated from `obsname` and the order of the timeseries data (default is `None`).

**Returns** `obs` – `HeadObservation` object.

**Return type** *HeadObservation*

## Examples

```
>>> import flopY
>>> model = flopY.modflow.Modflow()
>>> dis = flopY.modflow.ModflowDis(model, nlay=1, nrow=11, ncol=11, nper=2,
...                               perlen=[1,1])
>>> tsd = [[1.,54.4], [2., 55.2]]
>>> obsdata = flopY.modflow.HeadObservation(model, layer=0, row=5,
...                                         column=5, time_series_data=tsd)
```

**class** `ModflowHob`(*model, iuhobsv=None, hobjdry=0, tomulth=1.0, obs\_data=None, hobname=None, extension='hob', no\_print=False, options=None, unitnumber=None, filenames=None*)

Bases: *flopY.pakbase.Package*

Head Observation package class

### Parameters

- **iuhobsv** (*int*) – unit number where output is saved. If `iuhobsv` is `None`, a unit number will be assigned (default is `None`).
- **hobjdry** (*float*) – Value of the simulated equivalent written to the observation output file when the observation is omitted because a cell is dry (default is 0).
- **tomulth** (*float*) – Time step multiplier for head observations. The product of `tomulth` and `toffset` must produce a time value in units consistent with other model input. `tomulth` can be dimensionless or can be used to convert the units of `toffset` to the time unit used in the simulation (default is 1).
- **obs\_data** (*HeadObservation or list of HeadObservation instances*) – A single `HeadObservation` instance or a list of `HeadObservation` instances containing all of the data for each observation. If `obs_data` is `None` a default `HeadObservation` with an observation in layer, row, column (0, 0, 0) and a head value of 0 at totim 0 will be created (default is `None`).
- **hobname** (*str*) – Name of head observation output file. If `iuhobsv` is greater than 0, and `hobname` is `None`, the model basename with a `‘.hob.out’` extension will be used (default is `None`).
- **extension** (*string*) – Filename extension (default is `hob`)
- **no\_print** (*boolean*) – When `True` or 1, a list of head observations will not be written to the Listing File (default is `False`)
- **options** (*list of strings*) – Package options (default is `None`).
- **unitnumber** (*int*) – File unit number (default is `None`)

- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames is None the package name will be created using the model name and package extension and the hob output name will be created using the model name and .hob.out extension (for example, modflowtest.hob.out), if iuhobsv is a number greater than zero. If a single string is passed the package will be set to the string and hob output name will be created using the model name and .hob.out extension, if iuhobsv is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

See also:

Notes

## Examples

```
>>> import flopy
>>> model = flopy.modflow.Modflow()
>>> dis = flopy.modflow.ModflowDis(model, nlay=1, nrow=11, ncol=11, nper=2,
...                               perlen=[1,1])
>>> tsd = [[1.,54.4], [2., 55.2]]
>>> obsdata = flopy.modflow.HeadObservation(model, layer=0, row=5,
...                                         column=5, time_series_data=tsd)
>>> hob = flopy.modflow.ModflowHob(model, iuhobsv=51, hobjdry=-9999.,
...                                obs_data=obsdata)
```

**classmethod** `load(f, model, ext_unit_dict=None, check=True)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** **hob** – ModflowHob package object.

**Return type** ModflowHob package object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> hobs = flopy.modflow.ModflowHob.load('test.hob', m)
```

**write\_file()**

Write the package file

**Return type** None

## flop.modflow.mfhyd module

mfhyd module. Contains the ModflowHydclass. Note that the user can access the ModflowHyd class as *flop.modflow.ModflowHyd*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowHyd**(*model*, *nhyd*=1, *ihydun*=None, *hydnoh*=- 999.0, *obsdata*=[['BAS', 'HD', 'T', 0, 0.0, 0.0, 'HOBS1']], *extension*=['hyd', 'hyd.bin'], *unitnumber*=None, *filenames*=None)

Bases: *flop.pakbase.Package*

MODFLOW HYDMOD (HYD) Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flop.modflow.mf.Modflow*) to which this package will be added.
- **nhyd** (*int*) – the maximum number of observation points. (default is 1).
- **ihydun** (*int*) – A flag that is used to determine if hydmod data should be saved. If ihydun is non-zero hydmod data will be saved. (default is 1).
- **hydnoh** (*float*) – is a user-specified value that is output if a value cannot be computed at a hydrograph location. For example, the cell in which the hydrograph is located may be a no-flow cell. (default is -999.)
- **obsdata** – Each row of obsdata includes data defining pkg (3 character string), arr (2 character string), intyp (1 character string) klay (int), xl (float), yl (float), hydlbl (14 character string) for each observation.

**pkg** [str] is a 3-character flag to indicate which package is to be addressed by hydmod for the hydrograph of each observation point.

**arr** [str] is a text code indicating which model data value is to be accessed for the hydrograph of each observation point.

**intyp** [str] is a 1-character value to indicate how the data from the specified feature are to be accessed; The two options are 'I' for interpolated value or 'C' for cell value (intyp must be 'C' for STR and SFR Package hydrographs).

**klay** [int] is the layer sequence number (zero-based) of the array to be addressed by HYDMOD.

**xl** [float] is the coordinate of the hydrograph point in model units of length measured parallel to model rows, with the origin at the lower left corner of the model grid.

**yl** [float] is the coordinate of the hydrograph point in model units of length measured parallel to model columns, with the origin at the lower left corner of the model grid.

**hydlbl** [str] is used to form a label for the hydrograph.

**extension** [list string] Filename extension (default is ['hyd', 'hyd.bin'])

**unitnumber** [int] File unit number (default is None).

**filenames** [str or list of str] Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the hydmod output name will be created using the model name and .hyd.bin extension (for example, modflowtest.hyd.bin). If a single string is passed the package will be set to the string and hydmod output name will be created using the model name and .hyd.bin extension. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> hyd = flopy.modflow.ModflowHyd(m)
```

**static** `get_default_dtype()`

**static** `get_empty(ncells=0)`

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns hyd

**Return type** ModflowHyd object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> hyd = flopy.modflow.ModflowHyd.load('test.hyd', m)
```

**write\_file()**

Write the package file.

**Return type** None

## flopy.modflow.mflak module

mflak module. Contains the ModflowLak class. Note that the user can access the ModflowLak class as `flopy.modflow.ModflowLak`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowLak(model, nlakes=1, ipakcb=None, theta=- 1.0, nssitr=0, sscncr=0.0, surfdep=0.0, stages=1.0, stage_range=None, tab_files=None, tab_units=None, lakarr=None, bdlknc=None, sill_data=None, flux_data=None, extension='lak', unitnumber=None, filenames=None, options=None, lwrt=0, **kwargs)`

Bases: `flopy.pakbase.Package`

MODFLOW Lake Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nlakes** (*int*) – NLAKES Number of separate lakes. Sublakes of multiple-lake systems are considered separate lakes for input purposes. The variable NLAKES is used, with certain internal assumptions and approximations, to dimension arrays for the simulation.
- **ipakcb** (*int*) – (ILKCB in MODFLOW documentation) Whether or not to write cell-by-cell flows (yes if ILKCB > 0, no otherwise). If ILKCB < 0 and “Save Budget” is specified in the Output Control or ICBCFL is not equal to 0, the cell-by-cell flows will be printed in the standard output file. ICBCFL is specified in the input to the Output Control Option of MODFLOW.
- **lwrt** (*int or list of ints (one per SP)*) – lwrt > 0, suppresses printout from the lake package. Default is 0 (to print budget information)
- **theta** (*float*) – Explicit (THETA = 0.0), semi-implicit (0.0 < THETA < 1.0), or implicit (THETA = 1.0) solution for lake stages. SURFDEPTH is read only if THETA is assigned a negative value (the negative value of THETA is then changed to a positive value internally by the code). \* A new method of solving for lake stage uses only the time-weighting

factor THETA (Merritt and Konikow, 2000, p. 52) for transient simulations. THETA is automatically set to a value of 1.0 for all steady-state stress periods. For transient stress periods, Explicit (THETA = 0.0), semi-implicit (0.0 < THETA < 1.0), or implicit (THETA = 1.0) solutions can be used to calculate lake stages. The option to specify negative values for THETA is supported to allow specification of additional variables (NSSITER, SSCNCR, SURFDEP) for simulations that only include transient stress periods. If THETA is specified as a negative value, then it is converted to a positive value for calculations of lake stage.

- In MODFLOW-2000 and later, ISS is not part of the input. Instead NSSITR or SSCNCR should be included if one or more stress periods is a steady state stress period as defined in Ss/tr in the Discretization file.
- SSCNCR and NSSITR can be read for a transient only simulation by placing a negative sign immediately in front of THETA. A negative THETA sets a flag which assumes input values for NSSITR and SSCNCR will follow THETA in the format as described by Merritt and Konikow (p. 52). A negative THETA is automatically reset to a positive value after values of NSSITR and SSCNCR are read.
- **nssitr** (*int*) – Maximum number of iterations for Newton’s method of solution for equilibrium lake stages in each MODFLOW iteration for steady-state aquifer head solution. Only read if ISS (option flag input to DIS Package of MODFLOW indicating steady-state solution) is not zero or if THETA is specified as a negative value. \* NSSITR and SSCNCR may be omitted for transient solutions (ISS = 0). \* In MODFLOW-2000 and later, ISS is not part of the input.

Instead NSSITR or SSCNCR should be included if one or more stress periods is a steady state stress period as defined in Ss/tr in the Discretization file.

- SSCNCR and NSSITR can be read for a transient only simulation by placing a negative sign immediately in front of THETA. A negative THETA sets a flag which assumes input values for NSSITR and SSCNCR will follow THETA in the format as described by Merritt and Konikow (p. 52). A negative THETA is automatically reset to a positive value after values of NSSITR and SSCNCR are read.

- If NSSITR = 0, a value of 100 will be used instead.
- **sscnr** (*float*) – Convergence criterion for equilibrium lake stage solution by Newton's method. Only read if ISS is not zero or if THETA is specified as a negative value. See notes above for nssitr.
- **surfdepth** (*float*) – The height of small topological variations (undulations) in lake-bottom elevations that can affect groundwater discharge to lakes. SURFDEPTH decreases the lakebed conductance for vertical flow across a horizontal lakebed caused both by a groundwater head that is between the lakebed and the lakebed plus SURFDEPTH and a lake stage that is also between the lakebed and the lakebed plus SURFDEPTH. This method provides a smooth transition from a condition of no groundwater discharge to a lake, when groundwater head is below the lakebed, to a condition of increasing groundwater discharge to a lake as groundwater head becomes greater than the elevation of the dry lakebed. The method also allows for the transition of seepage from a lake to groundwater when the lake stage decreases to the lakebed elevation. Values of SURFDEPTH ranging from 0.01 to 0.5 have been used successfully in test simulations. SURFDEP is read only if THETA is specified as a negative value.
- **stages** (*float or list of floats*) – The initial stage of each lake at the beginning of the run.
- **stage\_range** (*list of tuples (ssmn, ssmx) of length nlakes*) – Where ssmn and ssmx are the minimum and maximum stages allowed for each lake in steady-state solution. \* SSMN and SSMX are not needed for a transient run and must be omitted when the solution is transient.

- When the first stress period is a steady-state stress period, SSMN is defined in record 3.

For subsequent steady-state stress periods, SSMN is defined in record 9a.

- **lakarr** (*array of integers (nlay, nrow, ncol)*) – LKARR A value is read in for every grid cell. If LKARR(I,J,K) = 0, the grid cell is not a lake volume cell. If LKARR(I,J,K) > 0, its value is the identification number of the lake occupying the grid cell. LKARR(I,J,K) must not exceed the value NLAKES. If it does, or if LKARR(I,J,K) < 0, LKARR(I,J,K) is set to zero. Lake cells cannot be overlain by non-lake cells in a higher layer. Lake cells must be inactive cells (IBOUND = 0) and should not be convertible to active cells (WETDRY = 0).

The Lake package can be used when all or some of the model layers containing the lake are confined. The authors recommend using the Layer-Property Flow Package (LPF) for this case, although the BCF and HUF Packages will work too. However, when using the BCF6 package to define aquifer properties, lake/aquifer conductances in the lateral direction are based solely on the lakebed leakance (and not on the lateral transmissivity of the aquifer layer). As before, when the BCF6 package is used, vertical lake/aquifer conductances are based on lakebed conductance and on the vertical hydraulic conductivity of the aquifer layer underlying the lake when the wet/dry option is implemented, and only on the lakebed leakance when the wet/dry option is not implemented.

- **bdlknc** (*array of floats (nlay, nrow, ncol)*) – BDLKNC A value is read in for every grid cell. The value is the lakebed leakance that will be assigned to lake/aquifer interfaces that occur in the corresponding grid cell. If the wet-dry option flag (IWD-FLG) is not active (cells cannot rewet if they become dry), then the BDLKNC values are assumed to represent the combined leakances of the lakebed material and the aquifer material between the lake and the centers of the underlying grid cells, i. e., the vertical

conductance values (CV) will not be used in the computation of conductances across lake/aquifer boundary faces in the vertical direction.

IBOUND and WETDRY should be set to zero for every cell for which LKARR is not equal to zero. IBOUND is defined in the input to the Basic Package of MODFLOW. WETDRY is defined in the input to the BCF or other flow package of MODFLOW if the IWDFLG option is active. When used with the HUF package, the Lake Package has been modified to compute effective lake-aquifer conductance solely on the basis of the user-specified value of lakebed leakance; aquifer hydraulic conductivities are not used in this calculation. An appropriate informational message is now printed after the lakebed conductances are written to the main output file.

- **sill\_data** (*dict*) – (dataset 8 in documentation) Dict of lists keyed by stress period. Each list has a tuple of dataset 8a, 8b for every multi-lake system, where dataset 8a is another tuple of

**IC** [int] The number of sublakes

**ISUB** [list of ints] The identification numbers of the sublakes in the sublake system being described in this record. The center lake number is listed first.

#### And dataset 8b contains

**SILLVT** [sequence of floats] A sequence of sill elevations for each sublakes that determines whether the center lake is connected with a given sublake. Values are entered for each sublake in the order the sublakes are listed in the previous record.

- **flux\_data** (*dict*) – (dataset 9 in documentation) Dict of lists keyed by stress period. The list for each stress period is a list of lists, with each list containing the variables PRCPLK EVAPLK RNF WTHDRW [SSMN] [SSMX] from the documentation.

**PRCPLK** [float] The rate of precipitation per unit area at the surface of a lake (L/T).

**EVAPLK** [float] The rate of evaporation per unit area from the surface of a lake (L/T).

**RNF** [float] Overland runoff from an adjacent watershed entering the lake. If  $RNF > 0$ , it is specified directly as a volumetric rate, or flux ( $L^3/T$ ). If  $RNF < 0$ , its absolute value is used as a dimensionless multiplier applied to the product of the lake precipitation rate per unit area (PRCPLK) and the surface area of the lake at its full stage (occupying all layer 1 lake cells). When RNF is entered as a dimensionless multiplier ( $RNF < 0$ ), it is considered to be the product of two proportionality factors. The first is the ratio of the area of the basin contributing runoff to the surface area of the lake when it is at full stage. The second is the fraction of the current rainfall rate that becomes runoff to the lake. This procedure provides a means for the automated computation of runoff rate from a watershed to a lake as a function of varying rainfall rate. For example, if the basin area is 10 times greater than the surface area of the lake, and 20 percent of the precipitation on the basin becomes overland runoff directly into the lake, then set  $RNF = -2.0$ .

**WTHDRW** [float] The volumetric rate, or flux ( $L^3/T$ ), of water removal from a lake by means other than rainfall, evaporation, surface outflow, or groundwater seepage. A negative value indicates augmentation. Normally,

this would be used to specify the rate of artificial withdrawal from a lake for human water use, or if negative, artificial augmentation of a lake volume for aesthetic or recreational purposes.

**SSMN** [float] Minimum stage allowed for each lake in steady-state solution. See notes on `ssmn` and `ssmx` above.

**SSMX** [float] SSMX Maximum stage allowed for each lake in steady-state solution.

- **options** (*list of strings*) – Package options. (default is None).
- **extension** (*string*) – Filename extension (default is 'lak')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If `filenames=None` the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, `modflowtest.cbc`), if `ipakcbc` is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if `ipakcbc` is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lak = {}
>>> lak[0] = [[2, 3, 4, 15.6, 1050., -4]] #this lake boundary will be
>>>                                     #applied to all stress periods
>>> lak = flopy.modflow.ModflowLak(m, nstress_period_data=strd)
```

**classmethod** `load(f, model, nper=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is None, then `nper` will be obtained from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `str` – ModflowLak object.

**Return type** ModflowLak object



## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lak = flopy.modflow.ModflowStr.load('test.lak', m)
```

### write\_file()

Write the package file.

**Return type** None

## flopy.modflow.mflmt module

mflmt module. Contains the ModflowLmt class. Note that the user can access the ModflowLmt class as *flopy.modflow.ModflowLmt*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowLmt(model, output_file_name='mt3d_link.ftl', output_file_unit=54, output_file_header='extended',
                  output_file_format='unformatted', extension='lmt6', package_flows=[], unitnumber=None,
                  filenames=None)
```

Bases: *flopy.pakbase.Package*

MODFLOW Link-MT3DMS Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **output\_file\_name** (*string*) – Filename for output file (default is 'mt3d\_link.ftl')
- **unitnumber** (*int*) – File unit number (default is 24).
- **output\_file\_unit** (*int*) – Output file unit number, pertaining to the file identified by output\_file\_name (default is 54).
- **output\_file\_header** (*string*) – Header for the output file (default is 'extended')
- **output\_file\_format** (*{'formatted', 'unformatted'}*) – Format of the output file (default is 'unformatted')
- **package\_flows** (*['sfr', 'lak', 'uzf']*) – Specifies which of the advanced package flows should be added to the flow-transport link (FTL) file. The addition of these flags may quickly increase the FTL file size. Thus, the user must specifically request their amendment within the FTL file. Default is not to add these terms to the FTL file by omitting the keyword package\_flows from the LMT input file. One or multiple strings can be passed as a list to the argument.
- **extension** (*string*) – Filename extension (default is 'lmt6')
- **unitnumber** – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lmt = flopy.modflow.ModflowLmt(m, output_file_name='mt3d_linkage.ftl')
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `lmt` – ModflowLmt object.

**Return type** ModflowLmt object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lmt = flopy.modflow.ModflowGhb.load('test.lmt', m)
```

**write\_file()**

Write the package file.

**Return type** None

## flopy.modflow.mflpf module

mflpf module. Contains the ModflowLpf class. Note that the user can access the ModflowLpf class as `flopy.modflow.ModflowLpf`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowLpf(model, laytyp=0, layavg=0, chani=1.0, layvka=0, laywet=0, ipakcb=None, hdry=- 1e+30,
    iwdflg=0, wetfct=0.1, iwetit=1, ihdwet=0, hk=1.0, hani=1.0, vka=1.0, ss=1e-05, sy=0.15,
    vkcb=0.0, wetdry=- 0.01, storagecoefficient=False, constantcv=False, thickstrt=False,
    nocvcorrection=False, novfc=False, extension='lpf', unitnumber=None, filenames=None,
    add_package=True)
```

Bases: `flopy.pakbase.Package`

MODFLOW Layer Property Flow Package Class.

## Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0)
- **hdry** (*float*) – Is the head that is assigned to cells that are converted to dry during a simulation. Although this value plays no role in the model calculations, it is useful as an indicator when looking at the resulting heads that are output from the model. HDRY is thus similar to HNOFLO in the Basic Package, which is the value assigned to cells that are no-flow cells at the start of a model simulation. (default is -1.e30).
- **laytyp** (*int or array of ints (nlay)*) – Layer type, contains a flag for each layer that specifies the layer type. 0 confined >0 convertible <0 convertible unless the THICK-STRT option is in effect. (default is 0).
- **layavg** (*int or array of ints (nlay)*) – Layer average 0 is harmonic mean 1 is logarithmic mean 2 is arithmetic mean of saturated thickness and logarithmic mean of hydraulic conductivity (default is 0).
- **chani** (*float or array of floats (nlay)*) – contains a value for each layer that is a flag or the horizontal anisotropy. If CHANI is less than or equal to 0, then variable HANI defines horizontal anisotropy. If CHANI is greater than 0, then CHANI is the horizontal anisotropy for the entire layer, and HANI is not read. If any HANI parameters are used, CHANI for all layers must be less than or equal to 0. Use as many records as needed to enter a value of CHANI for each layer. The horizontal anisotropy is the ratio of the hydraulic conductivity along columns (the Y direction) to the hydraulic conductivity along rows (the X direction). (default is 1).
- **layvka** (*int or array of ints (nlay)*) – a flag for each layer that indicates whether variable VKA is vertical hydraulic conductivity or the ratio of horizontal to vertical hydraulic conductivity. 0: VKA is vertical hydraulic conductivity not 0: VKA is the ratio of horizontal to vertical hydraulic conductivity (default is 0).
- **laywet** (*int or array of ints (nlay)*) – contains a flag for each layer that indicates if wetting is active. 0 wetting is inactive not 0 wetting is active (default is 0).
- **wetfct** (*float*) – is a factor that is included in the calculation of the head that is initially established at a cell when it is converted from dry to wet. (default is 0.1).
- **iwetit** (*int*) – is the iteration interval for attempting to wet cells. Wetting is attempted every IWETIT iteration. If using the PCG solver (Hill, 1990), this applies to outer iterations, not inner iterations. If IWETIT less than or equal to 0, it is changed to 1. (default is 1).
- **ihdwet** (*int*) – is a flag that determines which equation is used to define the initial head at cells that become wet. (default is 0)
- **hk** (*float or array of floats (nlay, nrow, ncol)*) – is the hydraulic conductivity along rows. HK is multiplied by horizontal anisotropy (see CHANI and HANI) to obtain hydraulic conductivity along columns. (default is 1.0).
- **hani** (*float or array of floats (nlay, nrow, ncol)*) – is the ratio of hydraulic conductivity along columns to hydraulic conductivity along rows, where HK of item 10 specifies the hydraulic conductivity along rows. Thus, the hydraulic conductivity along columns is the product of the values in HK and HANI. (default is 1.0).

- **vka** (*float or array of floats (nlay, nrow, ncol)*) – is either vertical hydraulic conductivity or the ratio of horizontal to vertical hydraulic conductivity depending on the value of LAYVKA. (default is 1.0).
- **ss** (*float or array of floats (nlay, nrow, ncol)*) – is specific storage unless the STORAGECOEFFICIENT option is used. When STORAGECOEFFICIENT is used, Ss is confined storage coefficient. (default is 1.e-5).
- **sy** (*float or array of floats (nlay, nrow, ncol)*) – is specific yield. (default is 0.15).
- **vkcb** (*float or array of floats (nlay, nrow, ncol)*) – is the vertical hydraulic conductivity of a Quasi-three-dimensional confining bed below a layer. (default is 0.0). Note that if an array is passed for vkcb it must be of size (nlay, nrow, ncol) even though the information for the bottom layer is not needed.
- **wetdry** (*float or array of floats (nlay, nrow, ncol)*) – is a combination of the wetting threshold and a flag to indicate which neighboring cells can cause a cell to become wet. (default is -0.01).
- **storagecoefficient** (*boolean*) – indicates that variable Ss and SS parameters are read as storage coefficient rather than specific storage. (default is False).
- **constantcv** (*boolean*) – indicates that vertical conductance for an unconfined cell is computed from the cell thickness rather than the saturated thickness. The CONSTANTCV option automatically invokes the NOCVCORRECTION option. (default is False).
- **thickstrt** (*boolean*) – indicates that layers having a negative LAYTYP are confined, and their cell thickness for conductance calculations will be computed as STRT-BOT rather than TOP-BOT. (default is False).
- **nocvcorrection** (*boolean*) – indicates that vertical conductance is not corrected when the vertical flow correction is applied. (default is False).
- **novfc** (*boolean*) – turns off the vertical flow correction under dewatered conditions. This option turns off the vertical flow calculation described on p. 5-8 of USGS Techniques and Methods Report 6-A16 and the vertical conductance correction described on p. 5-18 of that report. (default is False).
- **extension** (*string*) – Filename extension (default is 'lpf')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output name will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.
- **add\_package** (*bool*) – Flag to add the initialised package object to the parent model object. Default is True.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> lpf = flopY.modflow.ModflowLpf(m)
```

**classmethod** `load(f, model, ext_unit_dict=None, check=True)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `lpf` – ModflowLpf object.

**Return type** ModflowLpf object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> lpf = flopY.modflow.ModflowLpf.load('test.lpf', m)
```

**write\_file**(*check=True, f=None*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopY.modflow.mfmult module

mfmult module. Contains the ModflowMlt class. Note that the user can access the ModflowMlt class as `flopY.modflow.ModflowMlt`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowMlt(model, mult_dict=None, extension='mlt', unitnumber=None, filenames=None)`

Bases: `flopY.pakbase.Package`

MODFLOW Mult Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.

- **mult\_dict** (*dict*) – Dictionary with mult data for the model. mult\_dict is typically instantiated using load method.
- **extension** (*string*) – Filename extension (default is 'drn')
- **unitnumber** (*int*) – File unit number (default is 21).

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> mlt = flopy.modflow.ModflowZon(m, mult_dict=mult_dict)
```

**classmethod** `load(f, model, nrow=None, ncol=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nrow** (*int*) – number of rows. If not specified it will be retrieved from the model object. (default is None).
- **ncol** (*int*) – number of columns. If not specified it will be retrieved from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns zone

**Return type** ModflowMult dict

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> mlt = flopy.modflow.ModflowMlt.load('test.mlt', m)
```

**static** `mult_function(mult_dict, line)`

Construct a multiplier for the ‘FUNCTION’ option

**write\_file()**

Write the package file.

**Return type** None

## Notes

Not implemented because parameters are only supported on load

## flopY.modflow.mfmnw1 module

```
class ModflowMnw1(model, mxmnw=0, ipakcb=None, iwelpt=0, nomoiter=0, kspref=1,
                  well_bynode_qsum=None, losstype='skin', stress_period_data=None, dtype=None,
                  mnwname=None, extension='mnw1', unitnumber=None, filenames=None)
```

Bases: `flopY.pakbase.Package`

MODFLOW Multi-Node Well 1 Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **mxmnw** (*integer*) – maximum number of multi-node wells to be simulated
- **ipakcb** (*integer*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **iwelpt** (*integer*) – verbosity flag
- **nomoiter** (*integer*) – the number of iterations for which flow in MNW wells is calculated
- **kspref** (*string*) – which set of water levels are to be used as reference values for calculating drawdown
- **losstype** (*string*) – head loss type for each well
- **well\_bynode\_qsum** (*list of lists or None*) – nested list containing file names, unit numbers, and ALLTIME flag for auxiliary output, e.g. `[[‘test.ByNode’,92,‘ALLTIME’]]` if None, these optional external filenames and unit numbers are not written out
- **itmp** (*array*) – number of wells to be simulated for each stress period (shape : (NPER))
- **lay\_row\_col\_qdes\_mn\_multi** (*list of arrays*) – lay, row, col, qdes, and MN or MULTI flag for all well nodes (length : NPER)
- **mnwname** (*string*) – prefix name of file for outputting time series data from MNW1
- **extension** (*string*) – Filename extension (default is ‘mnw1’)
- **unitnumber** (*int*) – File unit number (default is 33).
- **filenames** (*string or list of strings*) – File name of the package (with extension) or a list with the filename of the package and the cell-by-cell budget file for ipakcb. Default is None.

## Notes

Parameters are not supported in FloPy.

The functionality of the ADD flag in data set 4 is not supported. Also not supported are all water-quality parameters (Qwval Iqwgrp), water-level limitations (Hlim, Href, DD), non-linear well losses, and pumping limitations (QCUT, Q-%CUT, Qfrcmn, Qfrcmx, DEFAULT).

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> mnw1 = flopy.modflow.ModflowMnw1(m1, ...)
```

**static** `get_default_dtype(structured=True)`

**static** `get_empty_stress_period_data(itmp, structured=True, default_value=0)`

**classmethod** `load(f, model, nper=None, gwt=False, nsol=1, ext_unit_dict=None)`

Default load method for standard boundary packages.

**write\_file()**

Write the package file.

**Return type** None

**skipcomments**(*line, f*)

## flopy.modflow.mfmnw2 module

**exception** `ItmpError(itmp, nactiwells)`

Bases: Exception

**class** `Mnw(wellid, nnodes=1, nper=1, losstype='skin', pumoloc=0, qlimit=0, ppflag=0, pumpcap=0, rw=1, rskin=2, kskin=10, B=None, C=0, P=2.0, cwc=None, pp=1, k=0, i=0, j=0, ztop=0, zbotm=0, node_data=None, stress_period_data=None, pumplay=0, pumprow=0, pumpcol=0, zpump=None, hlim=None, qcut=None, qfrcmn=None, qfrcmx=None, hlift=None, liftq0=None, liftqmax=None, hwtol=None, liftn=None, qn=None, mnwpackage=None)`

Bases: object

Multi-Node Well object class

### Parameters

- **wellid** (*str* or *int*) – is the name of the well. This is a unique alphanumeric identification label for each well. The text string is limited to 20 alphanumeric characters. If the name of the well includes spaces, then enclose the name in quotes. Flopy converts wellid string to lower case.
- **nnodes** (*int*) – is the number of cells (nodes) associated with this well. NNODES normally is > 0, but for the case of a vertical borehole, setting NNODES < 0 will allow the user to specify the elevations of the tops and bottoms of well screens or open intervals (rather than grid layer numbers), and the absolute value of NNODES equals the number of open intervals (or well screens) to be specified in dataset 2d. If this option is used, then the model will compute the layers in which the open intervals occur, the lengths of the open intervals, and the relative vertical position of the open interval within a model layer (for example, see figure 14 and related discussion).



- **losstype** (*str*) – is a character flag to determine the user-specified model for well loss (equation 2). Available options (that is, place one of the following approved words in this field) are: NONE there are no well corrections and the head in the well is

assumed to equal the head in the cell. This option ( $hWELL = hn$ ) is only valid for a single-node well ( $NNODES = 1$ ). (This is equivalent to using the original WEL Package of MODFLOW, but specifying the single-node well within the MNW2 Package enables the use of constraints.)

**THIEM** this option allows for only the cell-to-well correction at the well based on the Thiem (1906) equation; head in the well is determined from equation 2 as ( $hWELL = hn + AQ_n$ ), and the model computes A on the basis of the user-specified well radius ( $R_w$ ) and previously defined values of cell transmissivity and grid spacing. Coefficients B and C in equation 2 are automatically set = 0.0. User must define  $R_w$  in dataset 2c or 2d.

**SKIN** this option allows for formation damage or skin corrections at the well.  $hWELL = hn + AQ_n + BQ_n$  (from equation 2), where A is determined by the model from the value of  $R_w$ , and B is determined by the model from  $R_{skin}$  and  $K_{skin}$ . User must define  $R_w$ ,  $R_{skin}$ , and  $K_{skin}$  in dataset 2c or 2d.

**GENERAL** head loss is defined with coefficients A, B, and C and power exponent P ( $hWELL = hn + AQ_n + BQ_n + CQ_n^P$ ). A is determined by the model from the value of  $R_w$ . User must define  $R_w$ , B, C, and P in dataset 2c or 2d. A value of  $P = 2.0$  is suggested if no other data are available (the model allows  $1.0 \leq P \leq 3.5$ ). Entering a value of  $C = 0$  will result in a “linear” model in which the value of B is entered directly (rather than entering properties of the skin, as with the SKIN option).

**SPECIFYCWC** the user specifies an effective conductance value (equivalent to the combined effects of the A, B, and C well-loss coefficients expressed in equation 15) between the well and the cell representing the aquifer, CWC. User must define CWC in dataset 2c or 2d. If there are multiple screens within the grid cell or if partial penetration corrections are to be made, then the effective value of CWC for the node may be further adjusted automatically by MNW2.

- **pumploc** (*int*) – is an integer flag pertaining to the location along the borehole of the pump intake (if any). If  $PUMPLOC = 0$ , then either there is no pump or the intake location (or discharge point for an injection well) is assumed to occur above the first active node associated with the multi- node well (that is, the node closest to the land surface or to the wellhead). If  $PUMPLOC > 0$ , then the cell in which the intake (or outflow) is located will be specified in dataset 2e as a LAY-ROW-COL grid location. For a vertical well only, specifying  $PUMPLOC < 0$ , will enable the option to define the vertical position of the pump intake (or outflow) as an elevation in dataset 2e (for the given spatial grid location [ROW-COL] defined for this well in 2d).
- **qlimit** (*int*) – is an integer flag that indicates whether the water level (head) in the well will be used to constrain the pumping rate. If  $Qlimit = 0$ , then there are no constraints for this well. If  $Qlimit > 0$ , then pumpage will be limited (constrained) by the water level in the well, and relevant parameters are constant in time and defined below in dataset 2f. If  $Qlimit < 0$ , then pumpage will be limited (constrained) by the water level in the well, and relevant parameters can vary with time and are defined for every stress period in dataset 4b.
- **ppflag** (*int*) – is an integer flag that determines whether the calculated head in the well will be corrected for the effect of partial penetration of the well screen in the cell. If  $PPFLAG = 0$ , then the head in the well will not be adjusted for the effects of partial

penetration. If `PPFLAG > 0`, then the head in the well will be adjusted for the effects of partial penetration if the section of well containing the well screen is vertical (as indicated by identical row-column locations in the grid). If `NNODES < 0` (that is, the open intervals of the well are defined by top and bottom elevations), then the model will automatically calculate the fraction of penetration for each node and the relative vertical position of the well screen. If `NNODES > 0`, then the fraction of penetration for each node must be defined in dataset 2d (see below) and the well screen will be assumed to be centered vertically within the thickness of the cell (except if the well is located in the uppermost model layer that is under unconfined conditions, in which case the bottom of the well screen will be assumed to be aligned with the bottom boundary of the cell and the assumed length of well screen will be based on the initial head in that cell).

- **pumpcap** (*int*) – is an integer flag and value that determines whether the discharge of a pumping (withdrawal) well ( $Q < 0.0$ ) will be adjusted for changes in the lift (or total dynamic head) with time. If `PUMPCAP = 0`, then the discharge from the well will not be adjusted on the basis of changes in lift. If `PUMPCAP > 0` for a withdrawal well, then the discharge from the well will be adjusted on the basis of the lift, as calculated from the most recent water level in the well. In this case, data describing the head-capacity relation for the pump must be listed in datasets 2g and 2h, and the use of that relation can be switched on or off for each stress period using a flag in dataset 4a. The number of entries (lines) in dataset 2h corresponds to the value of `PUMPCAP`. If `PUMPCAP` does not equal 0, it must be set to an integer value of between 1 and 25, inclusive.
- **rw** (*float*) – radius of the well (losstype == ‘THIEM’, ‘SKIN’, or ‘GENERAL’)
- **rskin** (*float*) – radius to the outer limit of the skin (losstype == ‘SKIN’)
- **kskin** (*float*) – hydraulic conductivity of the skin
- **B** (*float*) – coefficient of the well-loss eqn. (eqn. 2 in MNW2 documentation) (losstype == ‘GENERAL’)
- **C** (*float*) – coefficient of the well-loss eqn. (eqn. 2 in MNW2 documentation) (losstype == ‘GENERAL’)
- **P** (*float*) – coefficient of the well-loss eqn. (eqn. 2 in MNW2 documentation) (losstype == ‘GENERAL’)
- **cwc** (*float*) – cell-to-well conductance. (losstype == ‘SPECIFYcwc’)
- **pp** (*float*) – fraction of partial penetration for the cell. Only specify if `PFLAG > 0` and `NNODES > 0`.
- **k** (*int*) – layer index of well (zero-based)
- **i** (*int*) – row index of well (zero-based)
- **j** (*int*) – column index of well (zero-based)
- **ztop** (*float*) – top elevation of open intervals of vertical well.
- **zbotm** (*float*) – bottom elevation of open intervals of vertical well.
- **node\_data** (*numpy record array*) – table containing MNW data by node. A blank `node_data` template can be created via the `ModflowMnw2.get_empty_mnw_data()` static method.

Note: Variables in dataset 2d (e.g. `rw`) can be entered as a single value for the entire well (above), or in `node_data` (or dataset 2d) by node. Variables not in dataset 2d (such as `pumplay`) can be included in node data for convenience (to allow construction of MNW2 package from a table), but are only written to MNW2 as a single variable. When writing non-dataset 2d variables to MNW2 input, the first value for the well will be used.

Other variables (e.g. `hlim`) can be entered here as constant for all stress periods, or by stress period below in `stress_period_data`. See MNW2 input instructions for more details.

**Columns are:**

**k** [int] layer index of well (zero-based)

**i** [int] row index of well (zero-based)

**j** [int] column index of well (zero-based)

**ztop** [float] top elevation of open intervals of vertical well.

**zbotm** [float] bottom elevation of open intervals of vertical well.

`wellid` : str `losstype` : str `pumploc` : int `qlimit` : int `ppflag` : int `pumpcap` : int `rw` : float `rskin` : float `kskin` : float `B` : float `C` : float `P` : float `cwc` : float `pp` : float `pumplay` : int `pumprow` : int `pumpcol` : int `zpump` : float `hlim` : float `qcut` : int `qfrcmn` : float `qfrcmx` : float `hlift` : float `liftq0` : float `liftqmax` : float `hwtol` : float `liftn` : float `qn` : float

- **stress\_period\_data** (*numpy record array*) – table containing MNW pumping data for all stress periods (dataset 4 in the MNW2 input instructions). A blank `stress_period_data` template can be created via the `Mnw.get_empty_stress_period_data()` static method. Columns are:

**per** [int] stress period

**qdes** [float] is the actual (or maximum desired, if constraints are to be applied) volumetric pumping rate (negative for withdrawal or positive for injection) at the well (L3/T). `Qdes` should be set to 0 for nonpumping wells. If constraints are applied, then the calculated volumetric withdrawal or injection rate may be adjusted to range from 0 to `Qdes` and is not allowed to switch directions between withdrawal and injection conditions during any stress period. When `PUMPCAP` > 0, in the first stress period in which `Qdes` is specified with a negative value, `Qdes` represents the maximum operating discharge for the pump; in subsequent stress periods, any different negative values of `Qdes` are ignored, although values are subject to adjustment for `CapMult`. If `Qdes` >= 0.0, then pump-capacity adjustments are not applied.

**capmult** [int] is a flag and multiplier for implementing head-capacity relations during a given stress period. Only specify if `PUMPCAP` > 0 for this well. If `CapMult` <= 0, then head-capacity relations are ignored for this stress period. If `CapMult` = 1.0, then head-capacity relations defined in datasets 2g and 2h are used. If `CapMult` equals any other positive value (for example, 0.6 or 1.1), then head-capacity relations are used but adjusted and shifted by multiplying the discharge value indicated by the head-capacity curve by the value of `CapMult`.

**cprime** [float] is the concentration in the injected fluid. Only specify if `Qdes` > 0 and GWT process is active.

`hlim` : float `qcut` : int `qfrcmn` : float `qfrcmx` : float

Note: If auxiliary variables are also being used, additional columns for these must be included.

- **pumplay** (*int*) –
- **pumprow** (*int*) –

- **pumpcol** (*int*) – PUMPLAY, PUMPROW, and PUMPCOL are the layer, row, and column numbers, respectively, of the cell (node) in this multi-node well where the pump intake (or outflow) is located. The location defined in dataset 2e should correspond with one of the nodes listed in 2d for this multi-node well. These variables are only read if PUMPLOC > 0 in 2b.
- **zpump** (*float*) – is the elevation of the pump intake (or discharge pipe location for an injection well). Zpump is read only if PUMPLOC < 0; in this case, the model assumes that the borehole is vertical and will compute the layer of the grid in which the pump intake is located.
- **hlim** (*float*) – is the limiting water level (head) in the well, which is a minimum for discharging wells and a maximum for injection wells. For example, in a discharging well, when hWELL falls below hlim, the flow from the well is constrained.
- **qcut** (*int*) – is an integer flag that indicates how pumping limits Qfrcmn and Qfrcmx will be specified. If pumping limits are to be specified as a rate (L3/T), then set QCUT > 0; if pumping limits are to be specified as a fraction of the specified pumping rate (Qdes), then set QCUT < 0. If there is not a minimum pumping rate below which the pump becomes inactive, then set QCUT = 0.
- **qfrcmn** (*float*) – is the minimum pumping rate or fraction of original pumping rate (a choice that depends on QCUT) that a well must exceed to remain active during a stress period. The absolute value of Qfrcmn must be less than the absolute value of Qfrcmx (defined next). Only specify if QCUT != 0.
- **qfrcmx** (*float*) – is the minimum pumping rate or fraction of original pumping rate that must be exceeded to reactivate a well that had been shut off based on Qfrcmn during a stress period. The absolute value of Qfrcmx must be greater than the absolute value of Qfrcmn. Only specify if QCUT != 0.
- **hlift** (*float*) – is the reference head (or elevation) corresponding to the discharge point for the well. This is typically at or above the land surface, and can be increased to account for additional head loss due to friction in pipes.
- **liftq0** (*float*) – is the value of lift (total dynamic head) that exceeds the capacity of the pump. If the calculated lift equals or exceeds this value, then the pump is shut off and discharge from the well ceases.
- **liftqmax** (*float*) – is the value of lift (total dynamic head) corresponding to the maximum pumping (discharge) rate for the pump. If the calculated lift is less than or equal to LIFTqmax, then the pump will operate at its design capacity, assumed to equal the user-specified value of Qdes (in dataset 4a). LIFTqmax will be associated with the value of Qdes in the first stress period in which Qdes for the well is less than 0.0.
- **hwtol** (*float*) – is a minimum absolute value of change in the computed water level in the well allowed between successive iterations; if the value of hWELL changes from one iteration to the next by a value smaller than this tolerance, then the value of discharge computed from the head capacity curves will be locked for the remainder of that time step. It is recommended that HWTol be set equal to a value approximately one or two orders of magnitude larger than the value of HCLOSE, but if the solution fails to converge, then this may have to be adjusted.
- **liftn** (*float*) – is a value of lift (total dynamic head) that corresponds to a known value of discharge (Qn) for the given pump, specified as the second value in this line.
- **qn** (*float*) – is the value of discharge corresponding to the height of lift (total dynamic head) specified previously on this line. Sign (positive or negative) is ignored.
- **mnwpackage** (*ModflowMnw2 instance*) – package that mnw is attached to

**Return type** None

**by\_node\_variables** = ['k', 'i', 'j', 'ztop', 'zbotm', 'rw', 'rskin', 'kskin', 'B', 'C', 'P', 'cwc', 'pp']

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check mnw object for common errors.

#### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

#### Returns chk

**Return type** flopy.utils.check object

**static get\_default\_spd\_dtype**(*structured=True*)

Get the default stress period data dtype

**Parameters** **structured** (*bool*) – Boolean that defines if a structured (True) or unstructured (False) dtype will be created (default is True). Not implemented for unstructured.

#### Returns dtype

**Return type** np.dtype

**static get\_empty\_stress\_period\_data**(*nper=0, aux\_names=None, structured=True, default\_value=0*)

Get an empty stress\_period\_data recarray that corresponds to dtype

#### Parameters

- **nper** (*int*) –
- **aux\_names** –
- **structured** –
- **default\_value** –

#### Returns ra – Recarray

**Return type** np.recarray

**static get\_item2\_names**(*mnw2obj=None, node\_data=None*)

Get names for unknown things...

#### Parameters

- **mnw2obj** (*Mnw object*) – Mnw object (default is None)
- **node\_data** (*unknown*) – Unknown what is in this parameter (default is None)

#### Returns

- **names** (*list*)
- *List of dtype names.*

**static get\_nnodes**(*node\_data*)

Get the number of MNW2 nodes.

**Parameters** `node_data` (*list*) – List of nodes???

**Returns** `nnodes` – Number of MNW2 nodes

**Return type** `int`

**make\_node\_data()**

Make the node data array from variables entered individually.

**Return type** `None`

**static sort\_node\_data**(*node\_data*)

**class ModflowMnw2**(*model*, *mnwmax*=0, *nodtot*=None, *ipakcb*=0, *mnwprnt*=0, *aux*=[], *node\_data*=None, *mnw*=None, *stress\_period\_data*=None, *itmp*=[], *extension*='mnw2', *unitnumber*=None, *filenames*=None, *gwt*=False)

Bases: [\*flop.pakbase.Package\*](#)

Multi-Node Well 2 Package Class

**Parameters**

- **model** (*model object*) – The model object (of type :class:'flop.modflow.mf.Modflow') to which this package will be added.
- **mnwmax** (*int*) – The absolute value of MNWMAX is the maximum number of multi-node wells (MNW) to be simulated. If MNWMAX is a negative number, NODTOT is read.
- **nodtot** (*int*) – Maximum number of nodes. The code automatically estimates the maximum number of nodes (NODTOT) as required for allocation of arrays. However, if a large number of horizontal wells are being simulated, or possibly for other reasons, this default estimate proves to be inadequate, a new input option has been added to allow the user to directly specify a value for NODTOT. If this is a desired option, then it can be implemented by specifying a negative value for “MNWMAX”–the first value listed in Record 1 (Line 1) of the MNW2 input data file. If this is done, then the code will assume that the very next value on that line will be the desired value of “NODTOT”. The model will then reset “MNWMAX” to its absolute value. The value of “ipakcb” will become the third value on that line, etc.
- **ipakcb** (*int*) –  
**is a flag and a unit number:** if `ipakcb > 0`, then it is the unit number to which MNW cell-by-cell flow terms will be recorded whenever cell-by-cell budget data are written to a file (as determined by the outputcontrol options of MODFLOW). if `ipakcb = 0`, then MNW cell-by-cell flow terms will not be printed  
or recorded.  
  
**if `ipakcb < 0`, then well injection or withdrawal rates and water** levels in the well and its multiple cells will be printed in the main MODFLOW listing (output) file whenever cell-by-cell budget data are written to a file (as determined by the output control options of MODFLOW).
- **mnwprnt** (*integer*) – Flag controlling the level of detail of information about multi-node wells to be written to the main MODFLOW listing (output) file. If `MNWPRNT = 0`, then only basic well information will be printed in the main MODFLOW output file; increasing the value of `MNWPRNT` yields more information, up to a maximum level of detail corresponding with `MNWPRNT = 2`. (default is 0)
- **aux** (*list of strings*) – (listed as “OPTION” in MNW2 input instructions) is an optional list of character values in the style of “AUXILIARY abc” or “AUX abc” where

“abc” is the name of an auxiliary parameter to be read for each multi-node well as part of dataset 4a. Up to 20 parameters can be specified, each of which must be preceded by “AUXILIARY” or “AUX.” These parameters will not be used by the MNW2 Package, but they will be available for use by other packages. (default is None)

- **node\_data** (*numpy record array*) – master table describing multi-node wells in package. Same format as node\_data tables for each Mnw object. See Mnw class documentation for more information.
- **mnw** (*list or dict of Mnw objects*) – Can be supplied instead of node\_data and stress\_period\_data tables (in which case the tables are constructed from the Mnw objects). Otherwise the a dict of Mnw objects (keyed by wellid) is constructed from the tables.
- **stress\_period\_data** (*dict of numpy record arrays*) – master dictionary of record arrays (keyed by stress period) containing transient input for multi-node wells. Format is the same as stress period data for individual Mnw objects, except the ‘per’ column is replaced by ‘wellid’ (containing wellid for each MNW). See Mnw class documentation for more information.
- **itmp** (*list of ints*) – is an integer value for reusing or reading multi-node well data; it can change each stress period. ITMP must be  $\geq 0$  for the first stress period of a simulation. if  $ITMP > 0$ , then ITMP is the total number of active multi-node wells

simulated during the stress period, and only wells listed in dataset 4a will be active during the stress period. Characteristics of each well are defined in datasets 2 and 4.

**if ITMP = 0, then no multi-node wells are active for the stress period** and the following dataset is skipped.

**if ITMP < 0, then the same number of wells and well information will be reused** from the previous stress period and dataset 4 is skipped.

- **extension** (*string*) – Filename extension (default is ‘mnw2’)
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.
- **gwt** (*boolean*) – Flag indicating whether GW transport process is active

## Notes

## Examples

```
>>> import flop
>>> m1 = flop.modflow.Modflow()
>>> mnw2 = flop.modflow.ModflowMnw2(m1, ...)
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check mnw2 package data for common errors.

### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If *f* is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

### Returns **chk**

**Return type** check object

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow.load('model.nam')
>>> m.mnw2.check()
```

**export**(*f, \*\*kwargs*)

Export MNW2 data

### Parameters

- **f** (*file*) –
- **kwargs** –

### Returns **e**

**Return type** export object

**get\_allnode\_data**()

Get a version of the `node_data` array that has all MNW2 nodes listed explicitly. For example, MNWs with open intervals encompassing multiple layers would have a row entry for each layer. Ztop and zbotm values indicate the top and bottom elevations of the node (these are the same as the layer top and bottom if the node fully penetrates that layer).

**Returns allnode\_data** – Numpy record array of same form as `node_data`, except each row represents only one node.

**Return type** np.recarray

**static get\_default\_node\_dtype**(*structured=True*)

Get default dtype for node data



**Parameters** **structured** (*bool*) – Boolean indicating if a structured (True) or unstructured (False) model (default is True).

**Returns** **dtype** – node data dtype

**Return type** np.dtype

**static** **get\_default\_spd\_dtype**(*structured=True*)

Get default dtype for stress period data

**Parameters** **structured** (*bool*) – Boolean indicating if a structured (True) or unstructured (False) model (default is True).

**Returns** **dtype** – node data dtype

**Return type** np.dtype

**static** **get\_empty\_node\_data**(*maxnodes=0, aux\_names=None, structured=True, default\_value=0*)

get an empty recarray that corresponds to dtype

**Parameters**

- **maxnodes** (*int*) – Total number of nodes to be simulated (default is 0)
- **aux\_names** (*list*) – List of aux name strings (default is None)
- **structured** (*bool*) – Boolean indicating if a structured (True) or unstructured (False) model (default is True).
- **default\_value** (*float*) – Default value for float variables (default is 0).

**Returns** **r** – Recarray of default dtype of shape maxnode

**Return type** np.recarray

**static** **get\_empty\_stress\_period\_data**(*itmp=0, aux\_names=None, structured=True, default\_value=0*)

Get an empty stress period data recarray

**Parameters**

- **itmp** (*int*) – Number of entries in this stress period (default is 0).
- **aux\_names** (*list*) – List of aux names (default is None).
- **structured** (*bool*) – Boolean indicating if a structured (True) or unstructured (False) model (default is True).
- **default\_value** (*float*) – Default value for float variables (default is 0).

**Returns** **r** – Recarray of default dtype of shape itmp

**Return type** np.recarray

**classmethod** **load**(*f, model, nper=None, gwt=False, nsol=1, ext\_unit\_dict=None*)

**Parameters**

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flop.modflow.ModflowMnw2`) to which this package will be added.
- **nper** (*int*) – Number of periods
- **gwt** (*bool*) –
- **nsol** (*int*) –

- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**make\_mnw\_objects()**

Make a Mnw object

**Return type** None

**make\_node\_data**(*mnwobjs*)

Make node\_data recarray from Mnw objects

**Parameters** *mnwobjs* (*Mnw object*) –

**Return type** None

**make\_stress\_period\_data**(*mnwobjs*)

Make stress\_period\_data recarray from Mnw objects

**Parameters** *mnwobjs* (*Mnw object*) –

**Return type** None

**write\_file**(*filename=None, float\_format='{:15.7E}', use\_tables=True*)

Write the package file.

**Parameters**

- **filename** (*str*) –
- **float\_format** –
- **use\_tables** –

**Return type** None

## flop.modflow.mfmnwi module

**class ModflowMnwi**(*model, wellflag=None, qsumflag=None, byndflag=None, mnwobs=1, wellid\_unit\_qndflag\_qhbflag\_concflag=None, extension='mnwi', unitnumber=None, filenames=None*)

Bases: `flop.pakbase.Package`

‘Multi-Node Well Information Package Class’

**Parameters**

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **wellflag** (*integer*) – Flag indicating output to be written for each MNW node at the end of each stress period
- **qsumflag** (*integer*) – Flag indicating output to be written for each multi-node well
- **byndflag** (*integer*) – Flag indicating output to be written for each MNW node
- **mnwobs** (*integer*) – Number of multi-node wells for which detailed flow, head, and solute data to be saved
- **wellid\_unit\_qndflag\_qhbflag\_concflag** (*list of lists*) – Containing wells and related information to be output (length : [MNWOBS][4or5])

- **extension** (*string*) – Filename extension (default is ‘mnwi’)
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the output names will be created using the model name and output extensions. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> ghb = flopy.modflow.ModflowMnwi(m1, ...)
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check mnwi package data for common errors.

### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow.load('model.nam')
>>> m.mnwi.check()
```

**classmethod load**(*f, model, nper=None, gwt=False, nsol=1, ext\_unit\_dict=None*)

Default load method for standard boundary packages.

**write\_file**()

Write the package file.

**Return type** None

## flopY.modflow.mfnwt module

mfnwt module. Contains the ModflowNwt class. Note that the user can access the ModflowNwt class as *flopY.modflow.ModflowNwt*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowNwt(model, headtol=0.01, fluxtol=500, maxiterout=100, thickfact=1e-05, linmeth=1, iprnwt=0,
    ibotav=0, options='COMPLEX', Continue=False, dbdtheta=0.4, dbdkappa=1e-05,
    dbdgamma=0.0, momfact=0.1, backflag=1, maxbackiter=50, backtol=1.1, backreduce=0.7,
    maxitinner=50, ilumethod=2, levfill=5, stoptol=1e-10, msdr=15, iacl=2, norder=1, level=5,
    north=7, iredsys=0, rrctols=0.0, idroptol=1, epsrn=0.0001, hclosexmd=0.0001,
    mxiterxmd=50, extension='nwt', unitnumber=None, filenames=None)
```

Bases: [flopY.pakbase.Package](#)

MODFLOW Nwt Package Class.

### Parameters

- **model** (*model object*) – The model object (of type [flopY.modflow.mf.Modflow](#)) to which this package will be added.
- **headtol** (*float*) – is the maximum head change between outer iterations for solution of the nonlinear problem. (default is 1e-4).
- **fluxtol** (*float*) – is the maximum l2 norm for solution of the nonlinear problem. (default is 500).
- **maxiterout** (*int*) – is the maximum number of iterations to be allowed for solution of the outer (nonlinear) problem. (default is 100).
- **thickfact** (*float*) – is the portion of the cell thickness (length) used for smoothly adjusting storage and conductance coefficients to zero. (default is 1e-5).
- **linmeth** (*int*) – is a flag that determines which matrix solver will be used. A value of 1 indicates GMRES will be used A value of 2 indicates XMD will be used. (default is 1).
- **iprnwt** (*int*) – is a flag that indicates whether additional information about solver convergence will be printed to the main listing file. (default is 0).
- **ibotav** (*int*) – is a flag that indicates whether corrections will be made to groundwater head relative to the cell-bottom altitude if the cell is surrounded by dewatered cells (integer). A value of 1 indicates that a correction will be made and a value of 0 indicates no correction will be made. (default is 0).
- **options** (*string*) – SPECIFIED indicates that the optional solver input values listed for items 1 and 2 will be specified in the NWT input file by the user. SIMPLE indicates that default solver input values will be defined that work well for nearly linear models. This would be used for models that do not include nonlinear stress packages, and models that are either confined or consist of a single unconfined layer that is thick enough to contain the water table within a single layer. MODERATE indicates that default solver input values will be defined that work well for moderately nonlinear models. This would be used for models that include nonlinear stress packages, and models that consist of one or more unconfined layers. The MODERATE option should be used when the SIMPLE option does not result in successful convergence. COMPLEX indicates that default solver input values will be defined that work well for highly nonlinear models. This would be used for models that include nonlinear stress packages, and models that consist of one or more unconfined layers representing complex geology and sw/gw interaction. The COMPLEX option should be used when the MODERATE option does not result in successful convergence. (default is COMPLEX).

- **Continue** (*bool*) – if the model fails to converge during a time step then it will continue to solve the following time step. (default is False). Note the capital C on this option so that it doesn't conflict with a reserved Python language word.
- **dbdtheta** (*float*) – is a coefficient used to reduce the weight applied to the head change between nonlinear iterations. dbdtheta is used to control oscillations in head. Values range between 0.0 and 1.0, and larger values increase the weight (decrease under-relaxation) applied to the head change. (default is 0.4).
- **dbdkappa** (*float*) – is a coefficient used to increase the weight applied to the head change between nonlinear iterations. dbdkappa is used to control oscillations in head. Values range between 0.0 and 1.0, and larger values increase the weight applied to the head change. (default is 1.e-5).
- **dbdgamma** (*float*) – is a factor (used to weight the head change for the previous and current iteration. Values range between 0.0 and 1.0, and greater values apply more weight to the head change calculated during the current iteration. (default is 0.)
- **momfact** (*float*) – is the momentum coefficient and ranges between 0.0 and 1.0. Greater values apply more weight to the head change for the current iteration. (default is 0.1).
- **backflag** (*int*) – is a flag used to specify whether residual control will be used. A value of 1 indicates that residual control is active and a value of 0 indicates residual control is inactive. (default is 1).
- **maxbackiter** (*int*) – is the maximum number of reductions (backtracks) in the head change between nonlinear iterations (integer). A value between 10 and 50 works well. (default is 50).
- **backtol** (*float*) – is the proportional decrease in the root-mean-squared error of the groundwater-flow equation used to determine if residual control is required at the end of a nonlinear iteration. (default is 1.1).
- **backreduce** (*float*) – is a reduction factor used for residual control that reduces the head change between nonlinear iterations. Values should be between 0.0 and 1.0, where smaller values result in smaller head-change values. (default 0.7).
- **maxitinner** (*int*) – (GMRES) is the maximum number of iterations for the linear solution. (default is 50).
- **ilumethod** (*int*) – (GMRES) is the index for selection of the method for incomplete factorization (ILU) used as a preconditioner. (default is 2).  
  
 ilumethod = 1 is ILU with drop tolerance and fill limit. Fill-in terms less than drop tolerance times the diagonal are discarded. The number of fill-in terms in each row of L and U is limited to the fill limit. The fill-limit largest elements are kept in the L and U factors.  
  
 ilumethod=2 is ILU(k) order k incomplete LU factorization. Fill-in terms of higher order than k in the factorization are discarded.
- **levfill** (*int*) – (GMRES) is the fill limit for ILUMETHOD = 1 and is the level of fill for ilumethod = 2. Recommended values: 5-10 for method 1, 0-2 for method 2. (default is 5).
- **stoptol** (*float*) – (GMRES) is the tolerance for convergence of the linear solver. This is the residual of the linear equations scaled by the norm of the root mean squared error. Usually 1.e-8 to 1.e-12 works well. (default is 1.e-10).

- **msdr** (*int*) – (GMRES) is the number of iterations between restarts of the GMRES Solver. (default is 15).
- **iacl** (*int*) – (XMD) is a flag for the acceleration method: 0 is conjugate gradient, 1 is ORTHOMIN, 2 is Bi-CGSTAB. (default is 2).
- **norder** (*int*) – (XMD) is a flag for the scheme of ordering the unknowns: 0 is original ordering, 1 is RCM ordering, 2 is Minimum Degree ordering. (default is 1).
- **level** (*int*) – (XMD) is the level of fill for incomplete LU factorization. (default is 5).
- **north** (*int*) – (XMD) is the number of orthogonalization for the ORTHOMIN acceleration scheme. A number between 4 and 10 is appropriate. Small values require less storage but more iterations may be required. This number should equal 2 for the other acceleration methods. (default is 7).
- **iredsys** (*int*) – (XMD) is a flag for reduced system preconditioning (integer): 0-do not apply reduced system preconditioning, 1-apply reduced system preconditioning. (default is 0)
- **rrctols** (*int*) – (XMD) is the residual reduction-convergence criteria. (default is 0.).
- **idroptol** (*int*) – (XMD) is a flag for using drop tolerance in the preconditioning: 0-don't use drop tolerance, 1-use drop tolerance. (default is 1).
- **epsrn** (*float*) – (XMD) is the drop tolerance for preconditioning. (default is 1.e-4).
- **hclosexmd** (*float*) – (XMD) is the head closure criteria for inner (linear) iterations. (default is 1.e-4).
- **mxiterxmd** (*int*) – (XMD) is the maximum number of iterations for the linear solution. (default is 50).
- **extension** (*list string*) – Filename extension (default is 'nwt')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> nwt = flopY.modflow.ModflowNwt(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.

- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**Returns** `nwt`

**Return type** `ModflowNwt` object

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> nwt = flop.modflow.ModflowPcg.load('test.nwt', m)
```

**write\_file()**

Write the package file.

**Return type** `None`

## flop.modflow.mfoc module

mfoc module. Contains the `ModflowOc` class. Note that the user can access the `ModflowOc` class as `flop.modflow.ModflowOc`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowOc`(*model*, *ihedfm*=0, *iddnfm*=0, *chedfm*=None, *cddnfm*=None, *cboufm*=None, *compact*=True, *stress\_period\_data*={(0, 0): ['save head']}, *extension*=['oc', 'hds', 'ddn', 'cbc', 'ibo'], *unitnumber*=None, *filenames*=None, *label*='LABEL', *\*\*kwargs*)

Bases: `flop.pakbase.Package`

MODFLOW Output Control Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **ihedfm** (*int*) – is a code for the format in which heads will be printed. (default is 0).
- **iddnfm** (*int*) – is a code for the format in which drawdown will be printed. (default is 0).
- **chedfm** (*string*) – is a character value that specifies the format for saving heads. The format must contain 20 characters or less and must be a valid Fortran format that is enclosed in parentheses. The format must be enclosed in apostrophes if it contains one or more blanks or commas. The optional word LABEL after the format is used to indicate that each layer of output should be preceded with a line that defines the output (simulation time, the layer being output, and so forth). If there is no record specifying CHEDFM, then heads are written to a binary (unformatted) file. Binary files are usually more compact than text files, but they are not generally transportable among different computer operating systems or different Fortran compilers. (default is None)
- **cddnfm** (*string*) – is a character value that specifies the format for saving drawdown. The format must contain 20 characters or less and must be a valid Fortran format that is enclosed in parentheses. The format must be enclosed in apostrophes if it contains one or more blanks or commas. The optional word LABEL after the format is used to

indicate that each layer of output should be preceded with a line that defines the output (simulation time, the layer being output, and so forth). If there is no record specifying CDDNFM, then drawdowns are written to a binary (unformatted) file. Binary files are usually more compact than text files, but they are not generally transportable among different computer operating systems or different Fortran compilers. (default is None)

- **cboufm** (*string*) – is a character value that specifies the format for saving ibound. The format must contain 20 characters or less and must be a valid Fortran format that is enclosed in parentheses. The format must be enclosed in apostrophes if it contains one or more blanks or commas. The optional word LABEL after the format is used to indicate that each layer of output should be preceded with a line that defines the output (simulation time, the layer being output, and so forth). If there is no record specifying CBOUFM, then ibounds are written to a binary (unformatted) file. Binary files are usually more compact than text files, but they are not generally transportable among different computer operating systems or different Fortran compilers. (default is None)
- **stress\_period\_data** (*dictionary of lists*) – Dictionary key is a tuple with the zero-based period and step (IPERO, ITSOC) for each print/save option list. If stress\_period\_data is None, then heads are saved for the last time step of each stress period. (default is None)

**The list can have any valid MODFLOW OC print/save option:** PRINT HEAD  
PRINT DRAWDOWN PRINT BUDGET SAVE HEAD SAVE DRAWDOWN  
SAVE BUDGET SAVE IBOUND

The lists can also include (1) DDREFERENCE in the list to reset drawdown reference to the period and step and (2) a list of layers for PRINT HEAD, SAVE HEAD, PRINT DRAWDOWN, SAVE DRAWDOWN, and SAVE IBOUND.

stress\_period\_data = {(0,1):['save head']}) would save the head for the second timestep in the first stress period.

- **compact** (*boolean*) – Save results in compact budget form. (default is True).
- **extension** (*list of strings*) – (default is ['oc', 'hds', 'ddn', 'cbc', 'ibo']).
- **unitnumber** (*list of ints*) – (default is [14, 51, 52, 53, 0]).
- **filenames** (*str or list of str*) – Filenames to use for the package and the head, drawdown, budget (not used), and ibound output files. If filenames=None the package name will be created using the model name and package extension and the output file names will be created using the model name and extensions. If a single string is passed the package will be set to the string and output names will be created using the model name and head, drawdown, budget, and ibound extensions. To define the names for all package files (input and output) the length of the list of strings should be 5. Default is None.

## Notes

The “words” method for specifying output control is the only option available. Also, the “compact” budget should normally be used as it produces files that are typically much smaller. The compact budget form is also a requirement for using the MODPATH particle tracking program.



## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> spd = {(0, 0): ['print head'],
... (0, 1): [],
... (0, 249): ['print head'],
... (0, 250): [],
... (0, 499): ['print head', 'save ibound'],
... (0, 500): [],
... (0, 749): ['print head', 'ddreference'],
... (0, 750): [],
... (0, 999): ['print head']}
>>> oc = flopy.modflow.ModflowOc(m, stress_period_data=spd, cboufm='(20i5)')
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check package data for common errors.

### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If *f* is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen.
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow.load('model.nam')
>>> m.oc.check()
```

**get\_budgetunit**()

Get the budget file unit number(s).

**Parameters** None –

**Returns** **iubud** – Unit number or list of cell-by-cell budget output unit numbers. None is returned if ipakcb is less than one for all packages.

**Return type** integer or list of integers

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> dis = flopy.modflow.ModflowDis(m)
>>> bas = flopy.modflow.ModflowBas(m)
>>> lpf = flopy.modflow.ModflowLpf(m, ipakcb=100)
>>> wel_data = {0: [[0, 0, 0, -1000.]]}
>>> wel = flopy.modflow.ModflowWel(m, ipakcb=101,
... stress_period_data=wel_data)
>>> spd = {(0, 0): ['save head', 'save budget']}
>>> oc = flopy.modflow.ModflowOc(m, stress_period_data=spd)
>>> oc.get_budgetunit()
[100, 101]
```

**static** `get_ocoutput_units(f, ext_unit_dict=None)`

Get head and drawdown units from a OC file.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns

- **ihedun** (*integer*) – Unit number of the head file.
- **fhead** (*str*) – File name of the head file. Is only defined if *ext\_unit\_dict* is passed and the unit number is a valid key. , headfilename, oc : ModflowOc object ModflowOc object.
- **iddnun** (*integer*) – Unit number of the drawdown file.
- **fddn** (*str*) – File name of the drawdown file. Is only defined if *ext\_unit\_dict* is passed and the unit number is a valid key.

## Examples

```
>>> import flopy
>>> ihds, hf, iddn, df = flopy.modflow.ModflowOc.get_ocoutput_units('test.oc')
```

**classmethod** `load(f, model, nper=None, nstp=None, nlay=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If *nper* is None, then *nper* will be obtained from the model object. (default is None).

- **nstp** (*int or list of ints*) – Integer of list of integers containing the number of time steps in each stress period. If nstp is None, then nstp will be obtained from the DIS or DISU packages attached to the model object. The length of nstp must be equal to nper. (default is None).
- **nlay** (*int*) – The number of model layers. If nlay is None, then nlay will be obtained from the model object. nlay only needs to be specified if an empty model object is passed in and the oc file being loaded is defined using numeric codes. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**Returns** oc – ModflowOc object.

**Return type** ModflowOc object

### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> oc = flop.modflow.ModflowOc.load('test.oc', m)
```

**reset\_budgetunit** (*budgetunit=None, fname=None*)

Reset the cell-by-cell budget unit (ipakcb) for every package that can write cell-by-cell data when SAVE BUDGET is specified in the OC file to the specified budgetunit.

#### Parameters

- **budgetunit** (*int, optional*) – Unit number for cell-by-cell output data. If budgetunit is None then the next available external unit number is assigned. Default is None
- **fname** (*string, optional*) – Filename to use for cell-by-cell output file. If fname=None the cell-by-cell output file will be created using the model name and a '.cbc' file extension. Default is None.

**Return type** None

### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> dis = flop.modflow.ModflowDis(m)
>>> bas = flop.modflow.ModflowBas(m)
>>> lpf = flop.modflow.ModflowLpf(m, ipakcb=100)
>>> wel_data = {0: [[0, 0, 0, -1000.]]}
>>> wel = flop.modflow.ModflowWel(m, ipakcb=101,
... stress_period_data=wel_data)
>>> spd = {(0, 0): ['save head', 'save budget']}
>>> oc = flop.modflow.ModflowOc(m, stress_period_data=spd)
>>> oc.reset_budgetunit(budgetunit=1053, fname='test.cbc')
```

**write\_file()**

Write the package file.

**Return type** None

## flop.modflow.mfpar module

mfpar module. Contains the ModflowPar class. Note that the user can access the ModflowPar class as *flop.modflow.ModflowPar*.

**class ModflowPar**

Bases: object

Class for loading mult, zone, pval, and parameter data for MODFLOW packages that use array data (LPF, UPW, RCH, EVT). Class also includes methods to create data arrays using mult, zone, pval, and parameter data (not used for boundary conditions).

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

**static load**(*f*, *npar*, *verbose=False*)

Load property parameters from an existing package.

### Parameters

- **f** (*file handle*) –
- **npar** (*int*) – The number of parameters.
- **verbose** (*bool*) – Boolean flag to control output. (default is False)

### Returns

- **list** (*list object of unique par\_types in file f*)
- **dictionary** (*dictionary object with parameters in file f*)

## Examples

```
>>>par_types, parm_dict = flop.modflow.mfpar.ModflowPar.load(f, np)
```

**static parameter\_fill**(*model*, *shape*, *findkey*, *parm\_dict*, *findlayer=None*)

Fill an array with parameters using zone, mult, and pval data.

### Parameters

- **model** (*model object*) – The model object (of type *flop.modflow.mf.Modflow*) to which this package will be added.
- **shape** (*tuple*) – The shape of the returned data array. Typically shape is (nrow, ncol)
- **findkey** (*string*) – the parameter array to be constructed,
- **parm\_dict** (*dict*) – dictionary that includes all of the parameter data for a package
- **findlayer** (*int*) – Layer that will be filled. Not required for array boundary condition data.

**Returns data** – Filled array resulting from applications of zone, mult, pval, and parameter data.

**Return type** numpy array

### Examples

for lpf and upw:

```
>>> data = flopy.modflow.mfpar.ModflowPar.parameter_fill(m, (nrow, ncol), 'vkcb
↳ ',
>>> .....parm_dict,
↳ findlayer=1)
```

**set\_mult**(*model*, *ext\_unit\_dict*)

Load an existing mult package and set mult data for a model.

#### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function *flopy.utils.mfreadnam.parsenamefile*.

### Examples

```
>>> ml.mfpar.set_mult(ml, ext_unit_dict)
```

**set\_pval**(*model*, *ext\_unit\_dict*)

Load an existing pval package and set pval data for a model.

#### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function *flopy.utils.mfreadnam.parsenamefile*.

### Examples

```
>>> ml.mfpar.set_pval(ml, ext_unit_dict)
```

**set\_zone**(*model*, *ext\_unit\_dict*)

Load an existing zone package and set zone data for a model.

#### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.

- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

## Examples

```
>>> ml.mfpar.set_zone(ml, ext_unit_dict)
```

## flopY.modflow.mfparbc module

mfparbc module. Contains the ModflowParBc class. Note that the user can access the ModflowParBc class as `flopY.modflow.ModflowParBc`.

**class** `ModflowParBc(bc_parms)`

Bases: `object`

Class for loading boundary condition parameter data for MODFLOW packages that use list data (WEL, GHB, DRN, etc.). This Class is also used to create hfb6 data from hfb parameters. Class also includes methods to create data arrays using `pval` and boundary condition parameter data.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

**get** (*fkey*)

overload get to return a value from the `bc_parms` dictionary

**classmethod** `load(f, npar, dt, model, ext_unit_dict=None, verbose=False)`

Load bc property parameters from an existing bc package that uses list data (e.g. WEL, RIV, etc.).

### Parameters

- **f** (*file handle*) –
- **npar** (*int*) – The number of parameters.
- **dt** (*numpy.dtype*) – `numpy.dtype` for the particular list boundary condition.
- **verbose** (*bool*) – Boolean flag to control output. (default is `False`)

### Returns dictionary

**Return type** dictionary object with parameters in file *f*

## Examples

**static loadarray**(*f*, *npar*, *verbose=False*)

Load bc property parameters from an existing bc package that uses array data (e.g. RCH, EVT).

### Parameters

- **f** (*file handle*) –
- **npar** (*int*) – The number of parameters.
- **verbose** (*bool*) – Boolean flag to control output. (default is False)

### Returns dictionary

**Return type** dictionary object with parameters in file *f*

## Examples

**static parameter\_bcfill**(*model*, *shape*, *parm\_dict*, *pak\_parms*)

Fill an array with parameters using zone, mult, and pval data.

### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **shape** (*tuple*) – The shape of the returned data array. Typically shape is (nrow, ncol)
- **parm\_dict** (*list*) – dictionary of parameter instances
- **pak\_parms** (*dict*) – dictionary that includes all of the parameter data for a package

**Returns data** – Filled array resulting from applications of zone, mult, pval, and parameter data.

**Return type** numpy array

## Examples

```
for rch and evt >>> data = flopY.modflow.mfparbc.ModflowParBc.parameter_bcfill(m, (nrow, ncol), >>>
.....'rech', parm_dict, pak_parms)
```

## flopY.modflow.mfpbc module

**class ModflowPbc**(*model*, *layer\_row\_column\_data=None*, *layer\_row\_column\_shead\_ehead=None*, *cosines=None*, *extension='pbc'*, *unitnumber=None*, *zerobase=True*)

Bases: *flopY.pakbase.Package*

Periodic boundary condition class

**write\_file**()

Write the package file.

**Return type** None

## flop.modflow.mfpcg module

mfpcg module. Contains the ModflowPcg class. Note that the user can access the ModflowPcg class as `flop.modflow.ModflowPcg`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowPcg(model, mxiter=50, iter1=30, npcond=1, hclose=1e-05, rclose=1e-05, relax=1.0, nbpol=0,
                 iprpcg=0, mutpcg=3, damp=1.0, damp1=1.0, ihcofadd=0, extension='pcg', unitnumber=None,
                 filenames=None)
```

Bases: `flop.pakbase.Package`

MODFLOW Pcg Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **mxiter** (*int*) – maximum number of outer iterations. (default is 50)
- **iter1** (*int*) – maximum number of inner iterations. (default is 30)
- **npcond** (*int*) – flag used to select the matrix conditioning method. (default is 1). specify npcond = 1 for Modified Incomplete Cholesky. specify npcond = 2 for Polynomial.
- **hclose** (*float*) – is the head change criterion for convergence. (default is 1e-5).
- **rclose** (*float*) – is the residual criterion for convergence. (default is 1e-5)
- **relax** (*float*) – is the relaxation parameter used with npcond = 1. (default is 1.0)
- **nbpol** (*int*) – is only used when npcond = 2 to indicate whether the estimate of the upper bound on the maximum eigenvalue is 2.0, or whether the estimate will be calculated. nbpol = 2 is used to specify the value is 2.0; for any other value of nbpol, the estimate is calculated. Convergence is generally insensitive to this parameter. (default is 0).
- **iprpcg** (*int*) – solver print out interval. (default is 0).
- **mutpcg** (*int*) – If mutpcg = 0, tables of maximum head change and residual will be printed each iteration. If mutpcg = 1, only the total number of iterations will be printed. If mutpcg = 2, no information will be printed. If mutpcg = 3, information will only be printed if convergence fails. (default is 3).
- **damp** (*float*) – is the steady-state damping factor. (default is 1.)
- **damp1** (*float*) – is the transient damping factor. (default is 1.)
- **ihcofadd** (*int*) – is a flag that determines what happens to an active cell that is surrounded by dry cells. (default is 0). If ihcofadd=0, cell converts to dry regardless of HCOF value. This is the default, which is the way PCG2 worked prior to the addition of this option. If ihcofadd<>0, cell converts to dry only if HCOF has no head-dependent stresses or storage terms.
- **extension** (*list string*) – Filename extension (default is 'pcg')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.



## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> pcg = flopY.modflow.ModflowPcg(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

### Returns

**pcg** ModflowPcg object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> pcg = flopY.modflow.ModflowPcg.load('test.pcg', m)
```

**write\_file()**

Write the package file.

**Return type** None

## flopY.modflow.mfpcgn module

mfpcgn module. Contains the ModflowPcgn class. Note that the user can access the ModflowStr class as `flopY.modflow.ModflowPcgn`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowPcgn(model, iter_mo=50, iter_mi=30, close_r=1e-05, close_h=1e-05, relax=1.0, ifill=0, unit_pc=None, unit_ts=None, adamp=0, damp=1.0, damp_lb=0.001, rate_d=0.1, chglimit=0.0, acnvg=0, cnvg_lb=0.001, mcnvg=2, rate_c=-1.0, ipunit=None, extension='pcgn', unitnumber=None, filenames=None)`

Bases: `flopY.pakbase.Package`

MODFLOW Pcgn Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.

- **iter\_mo** (*int*) – The maximum number of picard (outer) iterations allowed. For nonlinear problems, this variable must be set to some number greater than one, depending on the problem size and degree of nonlinearity. If iter\_mo is set to 1, then the pcgn solver assumes that the problem is linear and the input requirements are greatly truncated. (default is 50)
- **iter\_mi** (*int*) – maximum number of pcg (inner) iterations allowed. Generally, this variable is set to some number greater than one, depending on the matrix size, degree of convergence called for, and the nature of the problem. For a nonlinear problem, iter\_mi should be set large enough that the pcg iteration converges freely with the relative convergence parameter epsilon described in the Parameters Related to Convergence of Inner Iteration: Line 4 subsection. (default is 30)
- **close\_r** (*float*) – The residual-based stopping criterion for iteration. This parameter is used differently, depending on whether it is applied to a linear or nonlinear problem.

If iter\_mo = 1: For a linear problem, the variant of the conjugate gradient method outlined in algorithm 2 is employed, but uses the absolute convergence criterion in place of the relative convergence criterion. close\_r is used as the value in the absolute convergence criterion for quitting the pcg iterative solver. close\_r is compared to the square root of the weighted residual norm. In particular, if the square root of the weighted residual norm is less than close\_r, then the linear Pcg iterative solve is said to have converged, causing the pcg iteration to cease and control of the program to pass out of the pcg solver.

If iter\_mo > 1: For a nonlinear problem, close\_r is used as a criterion for quitting the picard (outer) iteration. close\_r is compared to the square root of the inner product of the residuals (the residual norm) as calculated on entry to the pcg solver at the beginning of every picard iteration. if this norm is less than close\_r, then the picard iteration is considered to have converged.

- **close\_h** (*float*) – close\_h is used as an alternate stopping criterion for the picard iteration needed to solve a nonlinear problem. The maximum value of the head change is obtained for each picard iteration, after completion of the inner, pcg iteration. If this maximum head change is less than close\_h, then the picard iteration is considered tentatively to have converged. However, as nonlinear problems can demonstrate oscillation in the head solution, the picard iteration is not declared to have converged unless the maximum head change is less than close\_h for three picard iterations. If these picard iterations are sequential, then a good solution is assumed to have been obtained. If the picard iterations are not sequential, then a warning is issued advising that the convergence is conditional and the user is urged to examine the mass balance of the solution.
- **relax** (*float*) – is the relaxation parameter used with npcond = 1. (default is 1.0)
- **ifill** (*int*) – is the fill level of the mic preconditioner. Preconditioners with fill levels of 0 and 1 are available (ifill = 0 and ifill = 1, respectively). (default is 0)
- **unit\_pc** (*int*) – is the unit number of an optional output file where progress for the inner PCG iteration can be written. (default is 0)
- **unit\_ts** (*int*) – is the unit number of an optional output file where the actual time in the PCG solver is accumulated. (default is 0)
- **adamp** (*int*) – defines the mode of damping applied to the linear solution. In general, damping determines how much of the head changes vector shall be applied to the hydraulic head vector hj in picard iteration j. If adamp = 0, Ordinary damping is employed and a constant value of damping parameter will be used throughout the picard iteration; this option requires a valid value for damp. If adamp = 1, Adaptive damping is employed. If adamp = 2: Enhanced damping algorithm in which the damping value is

increased (but never decreased) provided the picard iteration is proceeding satisfactorily. (default is 0)

- **damp** (*float*) – is the damping factor. (default is 1.)
- **damp\_lb** (*float*) – is the lower bound placed on the dampening; generally,  $0 < \text{damp\_lb} < \text{damp}$ . (default is 0.001)
- **rate\_d** (*float*) – is a rate parameter; generally,  $0 < \text{rate\_d} < 1$ . (default is 0.1)
- **chglimit** (*float*) – this variable limits the maximum head change applicable to the updated hydraulic heads in a Picard iteration. If `chglimit = 0.0`, then adaptive damping proceeds without this feature. (default is 0.)
- **acnvg** (*int*) – defines the mode of convergence applied to the PCG solver. (default is 0)
- **cnvg\_lb** (*int*) – is the minimum value that the relative convergence is allowed to take under the self-adjusting convergence option. `cnvg_lb` is used only in convergence mode `acnvg = 1`. (default is 0.001)
- **mcnvg** (*float*) – increases the relative PCG convergence criteria by a power equal to MCNVG. MCNVG is used only in convergence mode `acnvg = 2`. (default is 2)
- **rate\_c** (*float*) – this option results in variable enhancement of epsilon. If  $0 < \text{rate\_c} < 1$ , then enhanced relative convergence is allowed to decrease by increasing `epsilon(j) = epsilon(j-1) + rate_c * epsilon(j-1)`, where `j` is the Picard iteration number; this change in epsilon occurs so long as the Picard iteration is progressing satisfactorily. If `rate_c ≤ 0`, then the value of epsilon set by `mcnvg` remains unchanged through the picard iteration. It should be emphasized that `rate_c` must have a value greater than 0 for the variable enhancement to be effected; otherwise epsilon remains constant. `rate_c` is used only in convergence mode `acnvg = 2`. (default is -1.)
- **ipunit** (*int*) – enables progress reporting for the picard iteration. If `ipunit ≥ 0`, then a record of progress made by the picard iteration for each time step is printed in the MODFLOW Listing file (Harbaugh and others, 2000). This record consists of the total number of dry cells at the end of each time step as well as the total number of PCG iterations necessary to obtain convergence. In addition, if `ipunit > 0`, then extensive diagnostics for each Picard iteration is also written in comma-separated format to a file whose unit number corresponds to `ipunit`; the name for this file, along with its unit number and type 'data' should be entered in the modflow Name file. If `ipunit < 0` then printing of all progress concerning the Picard iteration is suppressed, as well as information on the nature of the convergence of the picard iteration. (default is 0)
- **extension** (*list string*) – Filename extension (default is 'pcgn')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If `filenames=None` the package name will be created using the model name and package extension and the `pcgn` output names will be created using the model name and `.pcgni`, `.pcgnt`, and `.pcgno` extensions. If a single string is passed the package will be set to the string and `pcgn` output names will be created using the model name and `pcgn` output extensions. To define the names for all package files (input and output) the length of the list of strings should be 4. Default is None.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> pcgn = flopY.modflow.ModflowPcgn(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

### Returns pcgn

**Return type** ModflowPcgn object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> pcgn = flopY.modflow.ModflowPcgn.load('test.pcgn', m)
```

**write\_file()**

Write the package file.

**Return type** None

## flopY.modflow.mfpks module

mfpks module. Contains the ModflowPks class. Note that the user can access the ModflowPks class as `flopY.modflow.ModflowPks`.

**class** `ModflowPks(model, mxiter=100, innerit=50, isolver=1, npc=2, iscl=0, iord=0, ncoresm=1, ncoresv=1, damp=1.0, dampit=1.0, relax=0.97, ifill=0, droptol=0.0, hclose=0.001, rclose=0.1, l2norm=None, iprpks=0, mutpks=3, mpi=False, partopt=0, novlapimpsol=1, stenimpsol=2, verbose=0, partdata=None, extension='pks', unitnumber=None, filenames=None)`

Bases: `flopY.pakbase.Package`

MODFLOW Pks Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **mxiter** (*int*) – maximum number of outer iterations. (default is 100)
- **innerit** (*int*) – maximum number of inner iterations. (default is 30)

- **hclose** (*float*) – is the head change criterion for convergence. (default is 1.e-3).
- **rclose** (*float*) – is the residual criterion for convergence. (default is 1.e-1)
- **relax** (*float*) – is the relaxation parameter used with npcond = 1. (default is 1.0)
- . –
- . –
- . –
- **iprpks** (*int*) – solver print out interval. (default is 0).
- **mutpks** (*int*) –

If **mutpcg = 0**, tables of maximum head change and residual will be printed each iteration.

If **mutpcg = 1**, only the total number of iterations will be printed. If **mutpcg = 2**, no information will be printed. If **mutpcg = 3**, information will only be printed if convergence fails.

(default is 3).

- **damp** (*float*) – is the steady-state damping factor. (default is 1.)
- **damp1** (*float*) – is the transient damping factor. (default is 1.)
- **extension** (*list string*) – Filename extension (default is 'pks')
- **unitnumber** (*int*) – File unit number (default is 27).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> pks = flopy.modflow.ModflowPks(m)
```

**classmethod** **load**(*f, model, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function *flopy.utils.mfreadnam.parsenamefile*.

### Returns pks

**Return type** ModflowPks object

### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> pks = flop.modflow.ModflowPks.load('test.pks', m)
```

**write\_file()**

Write the package file.

**Return type** None

### flop.modflow.mfpval module

mfpval module. Contains the ModflowPval class. Note that the user can access the ModflowPval class as *flop.modflow.ModflowPval*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowPval**(*model*, *pval\_dict*=None, *extension*='pval', *unitnumber*=None, *filenames*=None)

Bases: *flop.pakbase.Package*

MODFLOW Mult Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type *flop.modflow.mf.Modflow*) to which this package will be added.
- **pval\_dict** (*dict*) – Dictionary with pval data for the model. pval\_dict is typically instantiated using load method.
- **extension** (*string*) – Filename extension (default is 'pval')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

### Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow()
>>> pval_dict = floppy.modflow.ModflowZon(m, pval_dict=pval_dict)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsepackagefile`.

### Returns

**Return type** ModflowPval dict

## Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow()
>>> mlt = floppy.modflow.ModflowPval.load('test.pval', m)
```

**write\_file()**

Write the package file.

**Return type** None

## Notes

Not implemented because parameters are only supported on load

## flop.modflow.mfrch module

mfrch module. Contains the ModflowRch class. Note that the user can access the ModflowRch class as `flop.modflow.ModflowRch`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowRch(model, nrchop=3, ipakcb=None, rech=0.001, irch=0, extension='rch', unitnumber=None, filenames=None)`

Bases: `flop.pakbase.Package`

MODFLOW Recharge Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.

- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **nrchop** (*int*) – is the recharge option code. 1: Recharge to top grid layer only 2: Recharge to layer defined in irch 3: Recharge to highest active cell (default is 3).
- **rech** (*float or filename or ndarray or dict keyed on kper (zero-based)*) – Recharge flux (default is 1.e-3, which is used for all stress periods)
- **irch** (*int or filename or ndarray or dict keyed on kper (zero-based)*) – Layer (for an unstructured grid) or node (for an unstructured grid) to which recharge is applied in each vertical column (only used when nrchop=2). Default is 0, which is used for all stress periods.
- **extension** (*string*) – Filename extension (default is 'rch')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> #steady state
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> rch = flopy.modflow.ModflowRch(m, nrchop=3, rech=1.2e-4)
```

```
>>> #transient with time-varying recharge
>>> import flopy
>>> rech = {}
>>> rech[0] = 1.2e-4 #stress period 1 to 4
>>> rech[4] = 0.0 #stress period 5 and 6
>>> rech[6] = 1.2e-3 #stress period 7 to the end
>>> m = flopy.modflow.Modflow()
>>> rch = flopy.modflow.ModflowRch(m, nrchop=3, rech=rech)
```

**check**(*f=None, verbose=True, level=1, RTmin=2e-08, RTmax=0.0002, checktype=None*)  
Check package data for common errors.

## Parameters



- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If *f* is *None*, check method does not write results to a summary file. (default is *None*)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If *level*=0, summary checks are performed. If *level*=1, full checks are performed.
- **RTmin** (*float*) – Minimum product of recharge and transmissivity. Default is 2e-8
- **RTmax** (*float*) – Maximum product of recharge and transmissivity. Default is 2e-4

**Return type** *None*

## Notes

Unstructured models not checked for extreme recharge transmissivity ratios.

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('model.nam')
>>> m.rch.check()
```

**classmethod** `load(f, model, nper=None, ext_unit_dict=None, check=True)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If *nper* is *None*, then *nper* will be obtained from the model object. (default is *None*).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default *True*)

**Returns** `rch` – `ModflowRch` object.

**Return type** `ModflowRch` object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> rch = flopY.modflow.ModflowRch.load('test.rch', m)
```

**write\_file**(*check=True, f=None*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopY.modflow.mfriv module

mfriv module. Contains the ModflowRiv class. Note that the user can access the ModflowRiv class as *flopY.modflow.ModflowRiv*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowRiv**(*model, ipakcb=None, stress\_period\_data=None, dtype=None, extension='riv', options=None, unitnumber=None, filenames=None, \*\*kwargs*)

Bases: *flopY.pakbase.Package*

MODFLOW River Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **stress\_period\_data** (*list of boundaries, or recarray of boundaries, or*) – dictionary of boundaries. Each river cell is defined through definition of layer (int), row (int), column (int), stage (float), cond (float), rbot (float). The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot]
],
1: [
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot]
], ...
kper:
[
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot],
    [lay, row, col, stage, cond, rbot]
```

(continues on next page)

(continued from previous page)

```
]
}
```

Note that if the number of lists is smaller than the number of stress periods, then the last list of rivers will apply until the end of the simulation. Full details of all options to specify `stress_period_data` can be found in the flopy3 boundaries Notebook in the basic subdirectory of the examples directory.

- **dtype** (*custom datatype of stress\_period\_data.*) – (default is None) If None the default river datatype will be applied.
- **naux** (*int*) – number of auxiliary variables
- **extension** (*string*) – Filename extension (default is 'riv')
- **options** (*list of strings*) – Package options. (default is None).
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

**mxactr**

Maximum number of river cells for a stress period. This is calculated automatically by FloPy based on the information in `layer_row_column_data`.

**Type** int

**Notes**

Parameters are not supported in FloPy.

**Examples**

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lrcd = {}
>>> lrcd[0] = [[2, 3, 4, 15.6, 1050., -4]] #this river boundary will be
>>>                                         #applied to all stress periods
>>> riv = flopy.modflow.ModflowRiv(m, stress_period_data=lrcd)
```

**add\_record**(*kper, index, values*)

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check package data for common errors.

**Parameters**

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)

- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen.
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

### Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('model.nam')
>>> m.riv.check()
```

**static** `get_default_dtype(structured=True)`

**static** `get_empty(ncells=0, aux_names=None, structured=True)`

**classmethod** `load(f, model, nper=None, ext_unit_dict=None, check=True)`

Load an existing package.

#### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If nper is None, then nper will be obtained from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `rch` – ModflowRiv object.

**Return type** ModflowRiv object

### Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> riv = flopY.modflow.ModflowRiv.load('test.riv', m)
```

**write\_file**(*check=True*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flop.modflow.mfsfr2 module

```
class ModflowSfr2(model, nstrm=- 2, nss=1, nsfrpar=0, nparseg=0, const=None, dleak=0.0001, ipakcb=None,
istcb2=None, isfropt=0, nstrail=10, isuzn=1, nsfrsets=30, irtflg=0, numtim=2, weight=0.75,
flwtol=0.0001, reach_data=None, segment_data=None, channel_geometry_data=None,
channel_flow_data=None, dataset_5=None, irdflag=0, iptflag=0, reachinput=False,
transroute=False, tabfiles=False, tabfiles_dict=None, extension='sfr', unit_number=None,
filenames=None, options=None)
```

Bases: [flop.pakbase.Package](#)

Streamflow-Routing (SFR2) Package Class

## Parameters

- **model** (*model object*) – The model object (of type :class:'flop.modflow.mf.Modflow') to which this package will be added.
- **nstrm** (*integer*) – An integer value that can be specified to be positive or negative. The absolute value of NSTRM is equal to the number of stream reaches (finite-difference cells) that are active during the simulation and the number of lines of data to be included in Item 2, described below. When NSTRM is specified to be a negative integer, it is also used as a flag for changing the format of the data input, for simulating unsaturated flow beneath streams, and (or) for simulating transient streamflow routing (for MODFLOW-2005 simulations only), depending on the values specified for variables ISFROPT and IRTFLG, as described below. When NSTRM is negative, NSFRPAR must be set to zero, which means that parameters cannot be specified. By default, nstrm is set to negative.
- **nss** (*integer*) – An integer value equal to the number of stream segments (consisting of one or more reaches) that are used to define the complete stream network. The value of NSS represents the number of segments that must be defined through a combination of parameters and variables in Item 4 or variables in Item 6.
- **nparseg** (*integer*) – An integer value equal to (or exceeding) the number of stream-segment definitions associated with all parameters. This number can be more than the total number of segments (NSS) in the stream network because the same segment can be defined in multiple parameters, and because parameters can be time-varying. NPARSEG must equal or exceed the sum of NLST x N for all parameters, where N is the greater of 1 and NUMINST; that is, NPARSEG must equal or exceed the total number of repetitions of item 4b. This variable must be zero when NSTRM is negative.
- **const** (*float*) – A real value (or conversion factor) used in calculating stream depth for stream reach. If stream depth is not calculated using Manning's equation for any stream segment (that is, ICALC does not equal 1 or 2), then a value of zero can be entered. If Manning's equation is used, a constant of 1.486 is used for flow units of cubic feet per second, and a constant of 1.0 is used for units of cubic meters per second. The constant must be multiplied by 86,400 when using time units of days in the simulation. An explanation of time units used in MODFLOW is given by Harbaugh and others (2000, p. 10).
- **dleak** (*float*) – A real value equal to the tolerance level of stream depth used in computing leakage between each stream reach and active model cell. Value is in units of length. Usually a value of 0.0001 is sufficient when units of feet or meters are used in model.
- **ipakcb** (*integer*) – An integer value used as a flag for writing stream-aquifer leakage values. If ipakcb > 0, unformatted leakage between each stream reach and corresponding model cell will be saved to the main cell-by-cell budget file whenever when a cell-by-cell budget has been specified in Output Control (see Harbaugh and others, 2000, pages

52-55). If `ipakcb = 0`, leakage values will not be printed or saved. Printing to the listing file (`ipakcb < 0`) is not supported.

- **istcb2** (*integer*) – An integer value used as a flag for writing to a separate formatted file all information on inflows and outflows from each reach; on stream depth, width, and streambed conductance; and on head difference and gradient across the streambed. If `ISTCB2 > 0`, then `ISTCB2` also represents the unit number to which all information for each stream reach will be saved to a separate file when a cell-by-cell budget has been specified in Output Control. If `ISTCB2 < 0`, it is the unit number to which unformatted streamflow out of each reach will be saved to a file whenever the cell-by-cell budget has been specified in Output Control. Unformatted output will be saved to `<model name>.sfq`.

- **isfropt** (*integer*) – An integer value that defines the format of the input data and whether or not unsaturated flow is simulated beneath streams. Values of `ISFROPT` are defined as follows

**0 No vertical unsaturated flow beneath streams. Streambed elevations,** stream slope, streambed thickness, and streambed hydraulic conductivity are read for each stress period using variables defined in Items 6b and 6c; the optional variables in Item 2 are not used.

**1 No vertical unsaturated flow beneath streams. Streambed elevation,** stream slope, streambed thickness, and streambed hydraulic conductivity are read for each reach only once at the beginning of the simulation using optional variables defined in Item 2; Items 6b and 6c are used to define stream width and depth for `ICALC = 0` and stream width for `ICALC = 1`.

**2 Streambed and unsaturated-zone properties are read for each reach** only once at the beginning of the simulation using optional variables defined in Item 2; Items 6b and 6c are used to define stream width and depth for `ICALC = 0` and stream width for `ICALC = 1`. When using the LPF Package, saturated vertical hydraulic conductivity for the unsaturated zone is the same as the vertical hydraulic conductivity of the corresponding layer in LPF and input variable `UHC` is not read.

**3 Same as 2 except saturated vertical hydraulic conductivity for the** unsaturated zone (input variable `UHC`) is read for each reach.

**4 Streambed and unsaturated-zone properties are read for the** beginning and end of each stream segment using variables defined in Items 6b and 6c; the optional variables in Item 2 are not used. Streambed properties can vary each stress period. When using the LPF Package, saturated vertical hydraulic conductivity for the unsaturated zone is the same as the vertical hydraulic conductivity of the corresponding layer in LPF and input variable `UHC1` is not read.

**5 Same as 4 except saturated vertical hydraulic conductivity for the** unsaturated zone (input variable `UHC1`) is read for each segment at the beginning of the first stress period only.

- **nstrail** (*integer*) – An integer value that is the number of trailing wave increments used to represent a trailing wave. Trailing waves are used to represent a decrease in the surface infiltration rate. The value can be increased to improve mass balance in the unsaturated zone. Values between 10 and 20 work well and result in unsaturated-zone mass balance errors beneath streams ranging between 0.001 and 0.01 percent. Please see Smith (1983) for further details. (default is 10; for MODFLOW-2005 simulations only when `isfropt > 1`)
- **isuzn** (*integer*) – An integer value that is the maximum number of vertical cells used to define the unsaturated zone beneath a stream reach. If `ICALC` is 1 for all segments

then ISUZN should be set to 1. (default is 1; for MODFLOW-2005 simulations only when isfrop > 1)

- **nsfrsets** (*integer*) – An integer value that is the maximum number of different sets of trailing waves used to allocate arrays. Arrays are allocated by multiplying NSTRAIL by NSFRSETS. A value of 30 is sufficient for problems where the stream depth varies often. NSFRSETS does not affect model run time. (default is 30; for MODFLOW-2005 simulations only when isfrop > 1)
- **irtflg** (*integer*) – An integer value that indicates whether transient streamflow routing is active. IRTFLG must be specified if NSTRM < 0. If IRTFLG > 0, streamflow will be routed using the kinematic-wave equation (see USGS Techniques and Methods 6-D1, p. 68-69); otherwise, IRTFLG should be specified as 0. Transient streamflow routing is only available for MODFLOW-2005; IRTFLG can be left blank for MODFLOW-2000 simulations. (default is 1)
- **numtim** (*integer*) – An integer value equal to the number of sub time steps used to route streamflow. The time step that will be used to route streamflow will be equal to the MODFLOW time step divided by NUMTIM. (default is 2; for MODFLOW-2005 simulations only when irtflg > 0)
- **weight** (*float*) – A real number equal to the time weighting factor used to calculate the change in channel storage. WEIGHT has a value between 0.5 and 1. Please refer to equation 83 in USGS Techniques and Methods 6-D1 for further details. (default is 0.75; for MODFLOW-2005 simulations only when irtflg > 0)
- **flwtol** (*float*) – A real number equal to the streamflow tolerance for convergence of the kinematic wave equation used for transient streamflow routing. A value of 0.00003 cubic meters per second has been used successfully in test simulations (and would need to be converted to whatever units are being used in the particular simulation). (default is 0.0001; for MODFLOW-2005 simulations only when irtflg > 0)
- **reach\_data** (*recarray*) – Numpy record array of length equal to nstrm, with columns for each variable entered in item 2 (see SFR package input instructions). In following flop convention, layer, row, column and node number (for unstructured grids) are zero-based; segment and reach are one-based.
- **segment\_data** (*recarray*) – Numpy record array of length equal to nss, with columns for each variable entered in items 6a, 6b and 6c (see SFR package input instructions). Segment numbers are one-based.
- **dataset\_5** (*dict of lists*) – Optional; will be built automatically from segment\_data unless specified. Dict of lists, with key for each stress period. Each list contains the variables [itmp, irdflag, iptflag]. (see SFR documentation for more details):
- **itmp** (*list of integers (len = NPER)*) – For each stress period, an integer value for reusing or reading stream segment data that can change each stress period. If ITMP = 0 then all stream segment data are defined by Item 4 (NSFRPAR > 0; number of stream parameters is greater than 0). If ITMP > 0, then stream segment data are not defined in Item 4 and must be defined in Item 6 below for a number of segments equal to the value of ITMP. If ITMP < 0, then stream segment data not defined in Item 4 will be reused from the last stress period (Item 6 is not read for the current stress period). ITMP must be defined >= 0 for the first stress period of a simulation.
- **irdflag** (*int or list of integers (len = NPER)*) – For each stress period, an integer value for printing input data specified for this stress period. If IRDFLAG = 0, input data for this stress period will be printed. If IRDFLAG > 0, then input data for this stress period will not be printed.

- **iptflag** (*int or list of integers (len = NPER)*) – For each stress period, an integer value for printing streamflow- routing results during this stress period. If IPTFLG = 0, or whenever the variable ICBCFL or “Save Budget” is specified in Output Control, the results for specified time steps during this stress period will be printed. If IPTFLG > 0, then the results during this stress period will not be printed.
- **extension** (*string*) – Filename extension (default is ‘sfr’)
- **unit\_number** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output and sfr output name will be created using the model name and .cbc the .sfr.bin/.sfr.out extensions (for example, modflowtest.cbc, and modflowtest.sfr.bin), if ipakcbc and istcb2 are numbers greater than zero. If a single string is passed the package name will be set to the string and other uzf output files will be set to the model name with the appropriate output file extensions. To define the names for all package files (input and output) the length of the list of strings should be 3. Default is None.

#### outlets

Contains the outlet for each SFR segment; format is {per: {segment: outlet}} This attribute is created by the `get_outlets()` method.

**Type** nested dictionary

#### outsegs

Each array is of shape nss rows x maximum of nss columns. The first column contains the SFR segments, the second column contains the outsegs of those segments; the third column the outsegs of the outsegs, and so on, until all outlets have been encountered, or nss is reached. The latter case indicates circular routing. This attribute is created by the `get_outlets()` method.

**Type** dictionary of arrays

#### Notes

Parameters are not supported in FloPy.

MODFLOW-OWHM is not supported.

The Ground-Water Transport (GWT) process is not supported.

Limitations on which features are supported...

#### Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> sfr2 = flopy.modflow.ModflowSfr2(m1, ...)
```

**assign\_layers** (*adjust\_botms=False, pad=1.0*)

Assigns the appropriate layer for each SFR reach, based on cell bottoms at location of reach.

#### Parameters

- **adjust\_botms** (*bool*) – Streambed bottom elevations below the model bottom will cause an error in MODFLOW. If True, adjust bottom elevations in lowest layer of the model so they are at least pad distance below any co-located streambed elevations.



- **pad** (*scalar*) – Minimum distance below streambed bottom to set any conflicting model bottom elevations.

## Notes

Streambed bottom = strtotop - strthick This routine updates the elevations in the botm array of the flopy.model.ModflowDis instance. To produce a new DIS package file, model.write() or flopy.model.ModflowDis.write() must be run.

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check sfr2 package data for common errors.

### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a string is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow.load('model.nam')
>>> m.sfr2.check()
```

**property const**

**property dataset\_5**

auto-update itmp so it is consistent with segment\_data.

**deactivate\_ibound\_above()**

Sets ibound to 0 for all cells above active SFR cells.

**Parameters** none –

## Notes

This routine updates the ibound array of the flopy.model.ModflowBas6 instance. To produce a new BAS6 package file, model.write() or flopy.model.ModflowBas6.write() must be run.

**default\_value** = 0.0

**property df**

**export**(*f, \*\*kwargs*)

Method to export a package to netcdf or shapefile based on the extension of the file name (.shp for shapefile, .nc for netcdf)

### Parameters

- **f** (*str*) – filename

- **kwargs** (*keyword arguments*) –

**modelgrid** [flopy.discretization.Grid instance] user supplied modelgrid which can be used for exporting in lieu of the modelgrid associated with the model object

**Return type** None or Netcdf object

**export\_linkages**(*f*, **\*\*kwargs**)

Export linework shapefile showing all routing connections between SFR reaches. A length field containing the distance between connected reaches can be used to filter for the longest connections in a GIS.

**export\_outlets**(*f*, **\*\*kwargs**)

Export point shapefile showing locations where streamflow is leaving the model (outset=0).

**export\_transient\_variable**(*f*, *varname*, **\*\*kwargs**)

Export point shapefile showing locations with a given segment\_data variable applied. For example, segments where streamflow is entering or leaving the upstream end of a stream segment (FLOW) or where RUNOFF is applied. Cell centroids of the first reach of segments with non-zero terms of varname are exported; values of varname are exported by stress period in the attribute fields (e.g. flow0, flow1, flow2... for FLOW in stress periods 0, 1, 2...).

#### Parameters

- **f** (*str*, *filename*) –
- **varname** (*str*) – Variable in SFR Package dataset 6a (see SFR package documentation)

**static get\_default\_reach\_dtype**(*structured=True*)

**static get\_default\_segment\_dtype**()

**static get\_empty\_reach\_data**(*nreaches=0*, *aux\_names=None*, *structured=True*, *default\_value=0.0*)

**static get\_empty\_segment\_data**(*nsegments=0*, *aux\_names=None*, *default\_value=0.0*)

**get\_outlets**(*level=0*, *verbose=True*)

Traces all routing connections from each headwater to the outlet.

**get\_slopes**(*default\_slope=0.001*, *minimum\_slope=0.0001*, *maximum\_slope=1.0*)

Compute slopes by reach using values in strtotop (streambed top) and rchlen (reach length) columns of reach\_data. The slope for a reach *n* is computed as strtotop(*n*+1) - strtotop(*n*) / rchlen(*n*). Slopes for outlet reaches are set equal to a default value (default\_slope). Populates the slope column in reach\_data.

#### Parameters

- **default\_slope** (*float*) – Slope value applied to outlet reaches (where water leaves the model). Default value is 0.001
- **minimum\_slope** (*float*) – Assigned to reaches with computed slopes less than this value. This ensures that the Manning's equation won't produce unreasonable values of stage (in other words, that stage is consistent with assumption that streamflow is primarily drive by the streambed gradient). Default value is 0.0001.
- **maximum\_slope** (*float*) – Assigned to reaches with computed slopes more than this value. Default value is 1.

**get\_upsegs**()

From segment\_data, returns nested dict of all upstream segments by segment, by stress period.

**Returns** **all\_upsegs** – Nested dictionary of form {stress period: {segment: [list of upsegs]}}

**Return type** dict

## Notes

This method will not work if there are instances of circular routing.

**get\_variable\_by\_stress\_period**(*varname*)

**property graph**

Dictionary of routing connections between segments.

**len\_const** = {1: 1.486, 2: 1.0, 3: 100.0}

**classmethod load**(*f, model, nper=None, gwt=False, nsol=1, ext\_unit\_dict=None*)

Default load method for standard boundary packages.

**property nper**

**nsfrpar** = 0

**property nss**

**property nstrm**

**property paths**

**plot\_path**(*start\_seg=None, end\_seg=0, plot\_segment\_lines=True*)

Plot a profile of streambed elevation and model top along a path of segments.

### Parameters

- **start\_seg** (*int*) – Number of first segment in path.
- **end\_seg** (*int*) – Number of last segment in path (defaults to 0/outlet).
- **plot\_segment\_lines** (*bool*) – Controls plotting of segment end locations along profile. (default True)

### Returns

**ax** matplotlib.axes.\_subplots.AxesSubplot object

**renumber\_segments**()

Renumber segments so that segment numbering is continuous and always increases in the downstream direction. This may speed convergence of the NWT solver in some situations.

### Returns

**r** dictionary mapping old segment numbers to new

**repair\_outsegs**()

**reset\_reaches**()

**set\_outreaches**()

Determine the outreach for each SFR reach (requires a reachID column in reach\_data). Uses the segment routing specified for the first stress period to route reaches between segments.

**time\_const** = {1: 1.0, 2: 60.0, 3: 3600.0, 4: 86400.0, 5: 31557600.0}

**write\_file**(*filename=None*)

Write the package file.

**Return type** None

**class check**(*sfrpackage, verbose=True, level=1*)

Bases: object

Check SFR2 package for common errors

### Parameters

- **sfrpackage** (*object*) – Instance of Flopy ModflowSfr2 class.
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

### Notes

Daniel Feinstein’s top 10 SFR problems (7/16/2014): 1) cell gaps btw adjacent reaches in a single segment 2) cell gaps btw routed segments. possibly because of re-entry problems at domain edge 3) adjacent reaches with STOP sloping the wrong way 4) routed segments with end/start sloping the wrong way 5) STOP>TOP1 violations, i.e., floaters 6) STOP<<TOP1 violations, i.e., exaggerated incisions 7) segments that end within one diagonal cell distance from another segment, inviting linkage 8) circular routing of segments 9) multiple reaches with non-zero conductance in a single cell 10) reaches in inactive cells

Also after running the model they will want to check for backwater effects.

**elevations**(*min\_strtop=- 10, max\_strtop=15000*)

Checks streambed elevations for downstream rises and inconsistencies with model grid

**for\_nans**()

Check for nans in reach or segment data

**numbering**()

Checks for continuity in segment and reach numbering

**overlapping\_conductance**(*tol=1e-06*)

Checks for multiple SFR reaches in one cell; and whether more than one reach has Cond > 0

**routing**()

Checks for breaks in routing and does comprehensive check for circular routing

**run\_all**()

**slope**(*minimum\_slope=0.0001, maximum\_slope=1.0*)

Checks that streambed slopes are greater than or equal to a specified minimum value. Low slope values can cause “backup” or unrealistic stream stages with icalc options where stage is computed.

**find\_path**(*graph, start, end=0*)

Get a path through the routing network, from a segment to an outlet.

#### Parameters

- **graph** (*dict*) – Dictionary of seg : outseg numbers
- **start** (*int*) – Starting segment
- **end** (*int*) – Ending segment (default 0)

**Returns** **path** – List of segment numbers along routing path.

**Return type** list

**flop.modflow.mfsip module**

mfsip module. Contains the ModflowSip class. Note that the user can access the ModflowSip class as *flop.modflow.ModflowSip*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowSip(model, mxiter=200, nparm=5, accl=1, hclose=1e-05, ipcalc=1, wseed=0, iprsip=0,
                 extension='sip', unitnumber=None, filenames=None)
```

Bases: *flop.pakbase.Package*

MODFLOW Strongly Implicit Procedure Package Class.

**Parameters**

- **model** (*model object*) – The model object (of type :class:flop.modflow.mf.Modflow) to which this package will be added.
- **mxiter** (*integer*) – The maximum number of times through the iteration loop in one time step in an attempt to solve the system of finite-difference equations. (default is 200)
- **nparm** (*integer*) – The number of iteration variables to be used. Five variables are generally sufficient. (default is 5)
- **accl** (*float*) – The acceleration variable, which must be greater than zero and is generally equal to one. If a zero is entered, it is changed to one. (default is 1)
- **hclose** (*float > 0*) – The head change criterion for convergence. When the maximum absolute value of head change from all nodes during an iteration is less than or equal to hclose, iteration stops. (default is 1e-5)
- **ipcalc** (*0 or 1*) – A flag indicating where the seed for calculating iteration variables will come from. 0 is the seed entered by the user will be used. 1 is the seed will be calculated at the start of the simulation from problem variables. (default is 0)
- **wseed** (*float > 0*) – The seed for calculating iteration variables. wseed is always read, but is used only if ipcalc is equal to zero. (default is 0)
- **iprsip** (*integer > 0*) – the printout interval for sip. iprsip, if equal to zero, is changed to 999. The maximum head change (positive or negative) is printed for each iteration of a time step whenever the time step is an even multiple of iprsip. This printout also occurs at the end of each stress period regardless of the value of iprsip. (default is 0)
- **extension** (*string*) – Filename extension (default is 'sip')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopY
>>> m1 = flopY.modflow.Modflow()
>>> sip = flopY.modflow.ModflowSip(m1, mxiter=100, hclose=0.0001)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** `sip`

**Return type** `ModflowSip` object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> sip = flopY.modflow.ModflowSip.load('test.sip', m)
```

**write\_file()**

Write the package file.

**Return type** `None`

## flopY.modflow.mfsor module

mfsor module. Contains the `ModflowSor` class. Note that the user can access the `ModflowSor` class as `flopY.modflow.ModflowSor`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowSor(model, mxiter=200, accl=1, hclose=1e-05, iprsor=0, extension='sor', unitnumber=None, filenames=None)`

Bases: `flopY.pakbase.Package`

MODFLOW Slice-successive overrelaxation Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `:class:flopY.modflow.mf.Modflow`) to which this package will be added.
- **mxiter** (*integer*) – The maximum number of iterations allowed in a time step. (default is 200)

- **accl** (*float*) – The acceleration variable, which must be greater than zero and is generally between 1. and 2. (default is 1)
- **hclose** (*float* > 0) – The head change criterion for convergence. When the maximum absolute value of head change from all nodes during an iteration is less than or equal to hclose, iteration stops. (default is 1e-5)
- **iprsor** (*integer* > 0) – the printout interval for sor. iprsor, if equal to zero, is changed to 999. The maximum head change (positive or negative) is printed for each iteration of a time step whenever the time step is an even multiple of iprsor. This printout also occurs at the end of each stress period regardless of the value of iprsor. (default is 0)
- **extension** (*string*) – Filename extension (default is 'sor')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> sor = flopy.modflow.ModflowSor(m1)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns sor

**Return type** ModflowSor object

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> sor = flop.modflow.ModflowSor.load('test.sor', m)
```

### `write_file()`

Write the package file.

**Return type** None

## flop.modflow.mfstr module

mfstr module. Contains the ModflowStr class. Note that the user can access the ModflowStr class as *flop.modflow.ModflowStr*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowStr**(*model*, *mxacts*=0, *nss*=0, *ntrib*=0, *ndiv*=0, *icalc*=0, *const*=86400.0, *ipakcb*=None, *istcb2*=None, *dtype*=None, *stress\_period\_data*=None, *segment\_data*=None, *irdflg*=None, *iptflg*=None, *extension*='str', *unitnumber*=None, *filenames*=None, *options*=None, **\*\*kwargs**)

Bases: *flop.pakbase.Package*

MODFLOW Stream Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flop.modflow.mf.Modflow*) to which this package will be added.
- **mxacts** (*int*) – Maximum number of stream reaches that will be in use during any stress period. (default is 0)
- **nss** (*int*) – Number of stream segments. (default is 0)
- **ntrib** (*int*) – The number of stream tributaries that can connect to one segment. The program is currently dimensioned so that NTRIB cannot exceed 10. (default is 0)
- **ndiv** (*int*) – A flag, which when positive, specifies that diversions from segments are to be simulated. (default is 0)
- **icalc** (*int*) – A flag, which when positive, specifies that stream stages in reaches are to be calculated. (default is 0)
- **const** (*float*) – Constant value used in calculating stream stage in reaches whenever ICALC is greater than 0. This constant is 1.486 for flow units of cubic feet per second and 1.0 for units of cubic meters per second. The constant must be multiplied by 86,400 when using time units of days in the simulation. If ICALC is 0, const can be any real value. (default is 86400.)
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **istcb2** (*int*) – A flag that is used flag and a unit number for the option to store streamflow out of each reach in an unformatted (binary) file. If istcb2 is greater than zero streamflow data will be saved. (default is None).
- **dtype** (*tuple, list, or numpy array of numpy dtypes*) – is a tuple, list, or numpy array containing the dtype for datasets 6 and 8 and the dtype for datasets 9 and 10 data in stress\_period\_data and segment\_data dictionaries. (default is None)



- **irdflg** (*integer or dictionary*) – is a integer or dictionary containing a integer flag, when positive suppresses printing of the stream input data for a stress period. If an integer is passed, all stress periods will use the same value. If a dictionary is passed, stress periods not in the dictionary will assigned a value of 1. Default is None which will assign a value of 1 to all stress periods.
- **iptflg** (*integer or dictionary*) – is a integer or dictionary containing a integer flag, when positive suppresses printing of stream results for a stress period. If an integer is passed, all stress periods will use the same value. If a dictionary is passed, stress periods not in the dictionary will assigned a value of 1. Default is None which will assign a value of 1 to all stress periods.
- **stress\_period\_data** (*dictionary of reach data*) – Each dictionary contains a list of str reach data for a stress period.

Each stress period in the dictionary data contains data for datasets 6 and 8.

The value for stress period data for a stress period can be an integer (-1 or 0), a list of lists, a numpy array, or a numpy recarray. If stress period data for a stress period contains an integer, a -1 denotes data from the previous stress period will be reused and a 0 indicates there are no str reaches for this stress period.

Otherwise stress period data for a stress period should contain mxacts or fewer rows of data containing data for each reach. Reach data are specified through definition of layer (int), row (int), column (int), segment number (int), sequential reach number (int), flow entering a segment (float), stream stage (float), streambed hydraulic conductance (float), streambed bottom elevation (float), streambed top elevation (float), stream width (float), stream slope (float), roughness coefficient (float), and auxiliary variable data for auxiliary variables defined in options (float).

If icalc=0 is specified, stream width, stream slope, and roughness coefficients, are not used and can be any value for each stress period. If data are specified for dataset 6 for a given stress period and icalc>0, then stream width, stream slope, and roughness coefficients should be appropriately set.

The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. For example, if mxacts=3 this gives the form of:

```
stress_period_data =
{0: [
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough]]
],
1: [
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop,
    ↪width, slope, rough]]
], ...
kper:
```

(continues on next page)

(continued from previous page)

```
[
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop, ↵
↵width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop, ↵
↵width, slope, rough],
    [lay, row, col, seg, reach, flow, stage, cond, sbot, stop, ↵
↵width, slope, rough]]
]
```

- **segment\_data** (*dictionary of str segment data*) – Each dictionary contains a list of segment str data for a stress period.

Each stress period in the dictionary data contains data for datasets 9, and 10. Segment data for a stress period are ignored if a integer value is specified for stress period data.

The value for segment data for a stress period can be an integer (-1 or 0), a list of lists, a numpy array, or a numpy recarray. If segment data for a stress period contains an integer, a -1 denotes data from the previous stress period will be reused and a 0 indicates there are no str segments for this stress period.

Otherwise stress period data for a stress period should contain nss rows of data containing data for each segment. Segment data are specified through definition of itrib (int) data for up to 10 tributaries and iupseg (int) data.

If ntrib=0 is specified, itrib values are not used and can be any value for each stress period. If data are specified for dataset 6 for a given stress period and ntrib>0, then itrib data should be specified for columns 0:ntrib.

If ndiv=0 is specified, iupseg values are not used and can be any value for each stress period. If data are specified for dataset 6 for a given stress period and ndiv>0, then iupseg data should be specified for the column in the dataset [10].

The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. For example, if nss=2 and ntrib>0 and/or ndiv>0 this gives the form of:

```
segment_data =
{0: [
    [itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7, ↵
↵itrib8, itrib9, itrib10, iupseg],
    [itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7, ↵
↵itrib8, itrib9, itrib10, iupseg],
    ],
1: [
    [itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7, ↵
↵itrib8, itrib9, itrib10, iupseg],
    [itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7, ↵
↵itrib8, itrib9, itrib10, iupseg],
    ], ...
kper:
    [
        [itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7, ↵
↵itrib8, itrib9, itrib10, iupseg],
```

(continues on next page)

(continued from previous page)

```
[itrib1, itrib2, itrib3, itrib4, itrib5, itrib6, itrib7,
↪itrib8, itrib9, itrib10, iupseg],
]
}
```

- **options** (*list of strings*) – Package options. Auxiliary variables included as options should be constructed as options=['AUXILIARY IFACE', 'AUX xyz']. Either 'AUXILIARY' or 'AUX' can be specified (case insensitive). (default is None).
- **extension** (*string*) – Filename extension (default is 'str')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output and str output name will be created using the model name and .cbc the .sfr.bin/.sfr.out extensions (for example, modflowtest.cbc, and modflowtest.str.bin), if ipakcbc and istcb2 are numbers greater than zero. If a single string is passed the package will be set to the string and cbc and sf routput names will be created using the model name and .cbc and .str.bin/.str.out extensions, if ipakcbc and istcb2 are numbers greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 3. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> strd = {}
>>> strd[0] = [[2, 3, 4, 15.6, 1050., -4]] #this str boundary will be
>>>                                         #applied to all stress periods
>>> str = flopy.modflow.ModflowStr(m, stress_period_data=strd)
```

```
static get_default_dtype(structured=True)
```

```
static get_empty(ncells=0, nss=0, aux_names=None, structured=True)
```

```
classmethod load(f, model, nper=None, ext_unit_dict=None)
```

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If nper is None, then nper will be obtained from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file

handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**Returns** `str` – ModflowStr object.

**Return type** ModflowStr object

### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> strm = flop.modflow.ModflowStr.load('test.str', m)
```

**write\_file()**

Write the package file.

**Return type** None

### flop.modflow.mfsub module

mfsub module. Contains the ModflowSub class. Note that the user can access the ModflowSub class as `flop.modflow.ModflowSub`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowSub(model, ipakcb=None, isuboc=0, idsave=None, idrest=None, idbit=None, nndb=1, ndb=1,
                  nmz=1, nn=20, ac1=0.0, ac2=1.0, itmin=5, ln=0, ldn=0, rnb=1, hc=100000.0, sfe=0.0001,
                  sfv=0.001, com=0.0, dp=[[1e-06, 6e-06, 0.0006]], dstart=1.0, dhc=100000.0, dcom=0.0,
                  dz=1.0, nz=1, ids15=None, ids16=None, extension='sub', unitnumber=None,
                  filenames=None)
```

Bases: `flop.pakbase.Package`

MODFLOW SUB Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **isuboc** (*int*) – isuboc is a flag used to control output of information generated by the SUB Package. (default is 0).
- **idsave** (*int*) – idsave is a flag and a unit number on which restart records for delay interbeds will be saved at the end of the simulation. (default is 0).
- **idrest** (*int*) – idrest is a flag and a unit number on which restart records for delay interbeds will be read in at the start of the simulation (default is 0).
- **idbit** (*int*) – idrest is an optional flag that defines if iteration will be used for the delay bed solution of heads. If idbit is 0 or less than 0, iteration will not be used (this is identical to the approach used in MODFLOW-2005 versions less than 1.13. if idbit is greater than 0, iteration of the delay bed solution will continue until convergence is achieved. (default is 0).
- **nndb** (*int*) – nndb is the number of systems of no-delay interbeds. (default is 1).
- **ndb** (*int*) – ndb is the number of systems of delay interbeds. (default is 1).

- **nmz** (*int*) – nmz is the number of material zones that are needed to define the hydraulic properties of systems of delay interbeds. Each material zone is defined by a combination of vertical hydraulic conductivity, elastic specific storage, and inelastic specific storage. (default is 1).
- **nn** (*int*) – nn is the number of nodes used to discretize the half space to approximate the head distributions in systems of delay interbeds. (default is 20).
- **ac1** (*float*) – ac1 is an acceleration parameter. This parameter is used to predict the aquifer head at the interbed boundaries on the basis of the head change computed for the previous iteration. A value of 0.0 results in the use of the aquifer head at the previous iteration. Limited experience indicates that optimum values may range from 0.0 to 0.6. (default is 0).
- **ac2** (*float*) – ac2 is an acceleration parameter. This acceleration parameter is a multiplier for the head changes to compute the head at the new iteration. Values are normally between 1.0 and 2.0, but the optimum is probably closer to 1.0 than to 2.0. However this parameter also can be used to help convergence of the iterative solution by using values between 0 and 1. (default is 1.0).
- **itmin** (*int*) – ITMIN is the minimum number of iterations for which one-dimensional equations will be solved for flow in interbeds when the Strongly Implicit Procedure (SIP) is used to solve the ground-water flow equations. If the current iteration level is greater than ITMIN and the SIP convergence criterion for head closure (HCLOSE) is met at a particular cell, the one-dimensional equations for that cell will not be solved. The previous solution will be used. The value of ITMIN is not used if a solver other than SIP is used to solve the ground-water flow equations. (default is 5).
- **ln** (*int or array of ints (nndb)*) – ln is a one-dimensional array specifying the model layer assignments for each system of no-delay interbeds. (default is 0).
- **ldn** (*int or array of ints (ndb)*) – ldn is a one-dimensional array specifying the model layer assignments for each system of delay interbeds. (default is 0).
- **rnb** (*float or array of floats (ndb, nrow, ncol)*) – rnb is an array specifying the factor nequiv at each cell for each system of delay interbeds. The array also is used to define the areal extent of each system of interbeds. For cells beyond the areal extent of the system of interbeds, enter a number less than 1.0 in the corresponding element of this array. (default is 1).
- **hc** (*float or array of floats (nndb, nrow, ncol)*) – hc is an array specifying the preconsolidation head or preconsolidation stress in terms of head in the aquifer for systems of no-delay interbeds. For any model cells in which specified HC is greater than the corresponding value of starting head, the value of HC will be set to that of starting head. (default is 100000).
- **sfe** (*float or array of floats (nndb, nrow, ncol)*) – sfe is an array specifying the dimensionless elastic skeletal storage coefficient for systems of no-delay interbeds. (default is 1.e-4).
- **sfv** (*float or array of floats (nndb, nrow, ncol)*) – sfv is an array specifying the dimensionless inelastic skeletal storage coefficient for systems of no-delay interbeds. (default is 1.e-3).
- **com** (*float or array of floats (nndb, nrow, ncol)*) – com is an array specifying the starting compaction in each system of no-delay interbeds. Compaction values computed by the package are added to values in this array so that printed or stored values of compaction and land subsidence may include previous components. Values in this array do not affect calculations of storage changes or resulting compaction. For

- simulations in which output values are to reflect compaction and subsidence since the start of the simulation, enter zero values for all elements of this array. (default is 0).
- **dp** (*list or array of floats (nmz, 3)*) – Data item includes nmz records, each with a value of vertical hydraulic conductivity, elastic specific storage, and inelastic specific storage. (default is [1.e-6, 6.e-6, 6.e-4]).
  - **dstart** (*float or array of floats (ndb, nrow, ncol)*) – dstart is an array specifying starting head in interbeds for systems of delay interbeds. For a particular location in a system of interbeds, the starting head is applied to every node in the string of nodes that approximates flow in half of a doubly draining interbed. (default is 1).
  - **dhc** (*float or array of floats (ndb, nrow, ncol)*) – dhc is an array specifying the starting preconsolidation head in interbeds for systems of delay interbeds. For a particular location in a system of interbeds, the starting preconsolidation head is applied to every node in the string of nodes that approximates flow in half of a doubly draining interbed. For any location at which specified starting preconsolidation head is greater than the corresponding value of the starting head, Dstart, the value of the starting preconsolidation head will be set to that of the starting head. (default is 100000).
  - **dcom** (*float or array of floats (ndb, nrow, ncol)*) – dcom is an array specifying the starting compaction in each system of delay interbeds. Compaction values computed by the package are added to values in this array so that printed or stored values of compaction and land subsidence may include previous components. Values in this array do not affect calculations of storage changes or resulting compaction. For simulations in which output values are to reflect compaction and subsidence since the start of the simulation, enter zero values for all elements of this array. (default is 0).
  - **dz** (*float or array of floats (ndb, nrow, ncol)*) – dz is an array specifying the equivalent thickness for a system of delay interbeds. (default is 1).
  - **nz** (*int or array of ints (ndb, nrow, ncol)*) – nz is an array specifying the material zone numbers for systems of delay interbeds. The zone number for each location in the model grid selects the hydraulic conductivity, elastic specific storage, and inelastic specific storage of the interbeds. (default is 1).
  - **ids15** (*list or array of ints (12)*) – Format codes and unit numbers for subsidence, compaction by model layer, compaction by interbed system, vertical displacement, no-delay preconsolidation, and delay preconsolidation will be printed. If ids15 is None and isuboc>0 then print code 0 will be used for all data which is output to the binary subsidence output file (unit=1051). The 12 entries in ids15 correspond to ifm1, iun1, ifm2, iun2, ifm3, iun3, ifm4, iun4, ifm5, iun5, ifm6, and iun6 variables. (default is None).
  - **ids16** (*list or array of ints (isuboc, 17)*) – Stress period and time step range and print and save flags used to control printing and saving of information generated by the SUB Package during program execution. Each row of ids16 corresponds to isp1, isp2, its1, its2, ifl1, ifl2, ifl3, ifl4, ifl5, ifl6, ifl7, ifl8, ifl9, ifl10, ifl11, ifl12, and ifl13 variables for isuboc entries. isp1, isp2, its1, and its2 are stress period and time step ranges. ifl1 and ifl2 control subsidence printing and saving. ifl3 and ifl4 control compaction by model layer printing and saving. ifl5 and ifl6 control compaction by interbed system printing and saving. ifl7 and ifl8 control vertical displacement printing and saving. ifl9 and ifl10 control critical head for no-delay interbeds printing and saving. ifl11 and ifl12 control critical head for delay interbeds printing and saving. ifl13 controls volumetric budget for delay interbeds printing. If ids16 is None and isuboc>0 then all available subsidence output will be printed and saved to the binary subsidence output file (unit=1051). (default is None).

- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name and other sub output files will be created using the model name and .cbc and swt output extensions (for example, modflowtest.cbc), if ipakcbc and other sub output files (dataset 15) are numbers greater than zero. If a single string is passed the package name will be set to the string and other sub output files will be set to the model name with the appropriate output file extensions. To define the names for all package files (input and output) the length of the list of strings should be 9. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent. Parameters are not supported in the SUB Package.

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> sub = flopY.modflow.ModflowSub(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case ext\_unit\_dict is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** `sub`

**Return type** ModflowSub object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> sub = flopY.modflow.ModflowSub.load('test.sub', m)
```

**write\_file**(*check=False, f=None*)

Write the package file.

**Return type** None

## flop.modflow.mfswi2 module

mfswi2 module. Contains the ModflowSwi2 class. Note that the user can access the ModflowSwi2 class as *flop.modflow.ModflowSwi2*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowSwi2(model, nsrf=1, istrat=1, nobs=0, iswizt=None, ipakcb=None, iswiobs=0, options=None,
    nsolver=1, iprsol=0, mutsol=3, solver2params={'damp': 1.0, 'damp1': 1.0, 'iter1': 20,
    'mxiter': 100, 'nbpol': 2, 'npcond': 1, 'rclose': 0.0001, 'relax': 1.0, 'zclose': 0.001},
    toeslope=0.05, tipslope=0.05, alpha=None, beta=0.1, nadptmx=1, nadptmn=1, adptfct=1.0,
    nu=0.025, zeta=[0.0], ssz=0.25, isource=0, obsnam=None, obslrc=None, npln=None,
    extension='swi2', unitnumber=None, filenames=None)
```

Bases: [flop.pakbase.Package](#)

MODFLOW SWI2 Package Class.

### Parameters

- **model** (*model object*) – The model object (of type [flop.modflow.mf.Modflow](#)) to which this package will be added.
- **nsrf** (*int*) – number of active surfaces (interfaces). This equals the number of zones minus one. (default is 1).
- **istrat** (*int*) – flag indicating the density distribution. (default is 1).
- **iswizt** (*int*) – unit number for zeta output. (default is None).
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is None).
- **iswiobs** (*int*) – flag and unit number SWI2 observation output. (default is 0).
- **options** (*list of strings*) – Package options. If 'adaptive' is one of the options adaptive SWI2 time steps will be used. (default is None).
- **nsolver** (*int*) – DE4 solver is used if nsolver=1. PCG solver is used if nsolver=2. (default is 1).
- **iprsol** (*int*) – solver print out interval. (default is 0).
- **mutsol** (*int*) – If MUTSOL = 0, tables of maximum head change and residual will be printed each iteration. If MUTSOL = 1, only the total number of iterations will be printed. If MUTSOL = 2, no information will be printed. If MUTSOL = 3, information will only be printed if convergence fails. (default is 3).
- **solver2parameters** (*dict*) – only used if nsolver = 2
  - mxiter** [int] maximum number of outer iterations. (default is 100)
  - iter1** [int] maximum number of inner iterations. (default is 20)
  - npcond** [int] flag used to select the matrix conditioning method. (default is 1). specify NPCOND = 1 for Modified Incomplete Cholesky. specify NPCOND = 2 for Polynomial.
  - zclose** [float] is the ZETA change criterion for convergence. (default is 1e-3).
  - rclose** [float] is the residual criterion for convergence. (default is 1e-4)
  - relax** [float] is the relaxation parameter used with NPCOND = 1. (default is 1.0)
  - nbpol** [int] is only used when NPCOND = 2 to indicate whether the estimate of the upper bound on the maximum eigenvalue is 2.0, or whether the estimate will be



calculated. NBPOL = 2 is used to specify the value is 2.0; for any other value of NBPOL, the estimate is calculated. Convergence is generally insensitive to this parameter. (default is 2).

**damp** [float] is the steady-state damping factor. (default is 1.)

**damp1** [float] is the transient damping factor. (default is 1.)

- **toeslope** (*float*) – Maximum slope of toe cells. (default is 0.05)
- **tipslope** (*float*) – Maximum slope of tip cells. (default is 0.05)
- **alpha** (*float*) – fraction of threshold used to move the tip and toe to adjacent empty cells when the slope exceeds user-specified TOESLOPE and TIPSLOPE values. (default is None)
- **beta** (*float*) – Fraction of threshold used to move the toe to adjacent non-empty cells when the surface is below a minimum value defined by the user-specified TOESLOPE value. (default is 0.1).
- **nadptmx** (*int*) – only used if adaptive is True. Maximum number of SWI2 time steps per MODFLOW time step. (default is 1).
- **nadptmn** (*int*) – only used if adaptive is True. Minimum number of SWI2 time steps per MODFLOW time step. (default is 1).
- **adptfct** (*float*) – is the factor used to evaluate tip and toe thicknesses and control the number of SWI2 time steps per MODFLOW time step. When the maximum tip or toe thickness exceeds the product of TOESLOPE or TIPSLOPE the cell size and ADPTFCT, the number of SWI2 time steps are increased to a value less than or equal to NADPT. When the maximum tip or toe thickness is less than the product of TOESLOPE or TIPSLOPE the cell size and ADPTFCT, the number of SWI2 time steps is decreased in the next MODFLOW time step to a value greater than or equal to 1. ADPTFCT must be greater than 0.0 and is reset to 1.0 if NADPTMX is equal to NADPTMN. (default is 1.0).
- **nu** (*array of floats*) – if *istart* = 1, density of each zone (*nsrf* + 1 values). if *istart* = 0, density along top of layer, each surface, and bottom of layer (*nsrf* + 2 values). (default is 0.025)
- **zeta** (*list of floats or list of array of floats [(nlay, nrow, ncol), ...]*) – (*nlay, nrow, ncol*) initial elevations of the active surfaces. The list should contain an entry for each surface and be of size *nsrf*. (default is [0.])
- **ssz** (*float or array of floats (nlay, nrow, ncol)*) – effective porosity. (default is 0.25)
- **isource** (*integer or array of integers (nlay, nrow, ncol)*) – Source type of any external sources or sinks, specified with any outside package (i.e. WEL Package, RCH Package, GHB Package). (default is 0).  
 If ISOURCE > 0 sources and sinks have the same fluid density as the zone ISOURCE. If such a zone is not present in the cell, sources and sinks have the same fluid density as the active zone at the top of the aquifer. If ISOURCE = 0 sources and sinks have the same fluid density as the active zone at the top of the aquifer. If ISOURCE < 0 sources have the same fluid density as the zone with a number equal to the absolute value of ISOURCE. Sinks have the same fluid density as the active zone at the top of the aquifer. This option is useful for the modeling of the ocean bottom where infiltrating water is salt, yet exfiltrating water is of the same type as the water at the top of the aquifer.
- **obsnam** (*list of strings*) – names for nob observations.

- **obslrc** (*list of lists*) – zero-based [layer, row, column] lists for nobs observations.
- **extension** (*string*) – Filename extension (default is 'swi2')
- **npln** (*int*) – Deprecated - use nsrf instead.
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the zeta, cbc, obs output files. If filenames=None the package name will be created using the model name and package extension and the output file names will be created using the model name and output extensions. If a single string is passed the package will be set to the string and output names will be created using the model name and zeta, cbc, and observation extensions. To define the names for all package files (input and output) the length of the list of strings should be 4. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> swi2 = flopy.modflow.ModflowSwi2(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `swi2`

**Return type** `ModflowSwi2` object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> swi2 = flopy.modflow.ModflowSwi2.load('test.swi2', m)
```

**write\_file** (*check=True, f=None*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flop.modflow.mfswr1 module

mfswr module. Contains the ModflowSwr1 class. Note that the user can access the ModflowSwr1 class as `flop.modflow.ModflowSwr1`.

Additional information for this MODFLOW process can be found at the [Online MODFLOW Guide](#).

**class** `ModflowSwr1(model, extension='swr', unitnumber=None, filenames=None)`

Bases: `flop.pakbase.Package`

MODFLOW Surface-Water Routing Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **extension** (*string*) – Filename extension (default is 'swr')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

SWR1 Class is only used to write SWR1 filename to name file. Full functionality still needs to be implemented.

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> swr = flop.modflow.ModflowSwr1(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type: `class:flop.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**Returns** `swr` – ModflowSwr1 object (of type `flop.modflow.mfbas.ModflowSwr1`)

**Return type** ModflowSwr1 object

## Notes

Load method still needs to be implemented.

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow()
>>> swr = flop.modflow.ModflowSwt1.load('test.swr', m)
```

### `write_file()`

Write the package file.

**Return type** None

## `flop.modflow.mfswt` module

mfswt module. Contains the `ModflowSwt` class. Note that the user can access the `ModflowSub` class as `flop.modflow.ModflowSwt`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

```
class ModflowSwt(model, ipakcb=None, iswtoc=0, nsystm=1, ithk=0, ivoi=0, istpcs=1, icrcc=0, lnwt=0,
                 izcfl=0, izcfm=0, iglfl=0, iglfn=0, iestfl=0, iestfn=0, ipcsfl=0, ipcsfn=0, istfl=0, istfn=0,
                 gl0=0.0, sgm=1.7, sgs=2.0, thick=1.0, sse=1.0, ssv=1.0, cr=0.01, cc=0.25, void=0.82,
                 sub=0.0, pcsoff=0.0, pcs=0.0, ids16=None, ids17=None, extension='swt', unitnumber=None,
                 filenames=None)
```

Bases: `flop.pakbase.Package`

MODFLOW SUB-WT Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **iswtoc** (*int*) – iswtoc is a flag used to control output of information generated by the SUB Package. (default is 0).
- **nsystm** (*int*) – nsystm is the number of systems of interbeds. (default is 1).
- **ithk** (*int*) – ithk is a flag to determine how thicknesses of compressible sediments vary in response to changes in saturated thickness. If ithk < 1, thickness of compressible sediments is constant. If ithk > 0, thickness of compressible sediments varies in response to changes in saturated thickness. (default is 1).
- **ivoi** (*int*) – ivoi is a flag to determine how void ratios of compressible sediments vary in response to changes in saturated thickness. If ivoi < 1, void ratio will be treated as a constant. If ivoi > 0, void ratio will be treated as a variable. (default is 0).
- **nn** (*int*) – nn is the number of nodes used to discretize the half space to approximate the head distributions in systems of delay interbeds. (default is 20).
- **istpcs** (*int*) – istpcs is a flag to determine how initial preconsolidation stress will be obtained. If istpcs does not equal 0, an array of offset values will be read in for each model layer. The offset values will be added to the initial effective stress to get initial

preconsolidation stress. If `istpcs = 0`, an array with initial preconsolidation stress values will be read. (default is 1).

- **icrcc** (*int*) – `icrcc` is a flag to determine how recompression and compression indices will be obtained. If `ICRCC` is not equal to 0, arrays of elastic specific storage and inelastic skeletal specific storage will be read for each system of interbeds; the recompression index and compression index will not be read. If `icrcc = 0`, arrays of recompression index and compression index will be read for each system of interbeds; elastic skeletal specific storage and inelastic skeletal specific storage will not be read. (default is 0).
- **lnwt** (*int or array of ints (nsystem)*) – `lnwt` is a one-dimensional array specifying the model layer assignments for each system of interbeds. (default is 0).
- **izcfl** (*int*) – `izcfl` is a flag to specify whether or not initial calculated values of layer-center elevation will be printed. (default is 0).
- **izcfm** (*int*) – `izcfm` is a code for the format in which layer-center elevation will be printed. (default is 0).
- **iglfl** (*int*) – `iglfl` is a flag to specify whether or not initial calculated values of geostatic stress will be printed. (default is 0).
- **iglfm** (*int*) – `iglfm` is a code for the format in which geostatic stress will be printed. (default is 0).
- **iestfl** (*int*) – `iestfl` is a flag to specify whether or not initial calculated values of effective stress will be printed. (default is 0).
- **iestfm** (*int*) – `iestfm` is a code for the format in which effective stress will be printed. (default is 0).
- **ipcsfl** (*int*) – `ipcsfl` is a flag to specify whether or not initial calculated values of preconsolidation stress will be printed. (default is 0).
- **ipcsfm** (*int*) – `ipcsfm` is a code for the format in which preconsolidation stress will be printed. (default is 0).
- **istfl** (*int*) – `istfl` is a flag to specify whether or not initial equivalent storage properties will be printed for each system of interbeds. If `icrcc` is not equal to 0, the equivalent storage properties that can be printed are recompression and compression indices (`cr` and `cc`), which are calculated from elastic and inelastic skeletal specific storage (`sske` and `sskv`). If `icrcc = 0`, equivalent storage properties that can be printed are elastic and inelastic skeletal specific storage, which are calculated from the recompression and compression indices. (default is 0).
- **istfm** (*int*) – `istfm` is a code for the format in which equivalent storage properties will be printed. (default is 0).
- **gl0** (*float or array of floats (nrow, ncol)*) – `gl0` is an array specifying the geostatic stress above model layer 1. If the top of model layer 1 is the land surface, enter values of zero for this array. (default is 0.).
- **sgm** (*float or array of floats (nrow, ncol)*) – `sgm` is an array specifying the specific gravity of moist or unsaturated sediments. (default is 1.7).
- **sgs** (*float or array of floats (nrow, ncol)*) – `sgs` is an array specifying the specific gravity of saturated sediments. (default is 2.).
- **thick** (*float or array of floats (nsystem, nrow, ncol)*) – `thick` is an array specifying the thickness of compressible sediments. (default is 1.).

- **sse** (*float or array of floats (nsystm, nrow, ncol)*) – sse is an array specifying the initial elastic skeletal specific storage of compressible beds. sse is not used if icrcc = 0. (default is 1.).
- **ssv** (*float or array of floats (nsystm, nrow, ncol)*) – ssv is an array specifying the initial inelastic skeletal specific storage of compressible beds. ssv is not used if icrcc = 0. (default is 1.).
- **cr** (*float or array of floats (nsystm, nrow, ncol)*) – cr is an array specifying the recompression index of compressible beds. cr is not used if icrcc is not equal to 0. (default is 0.01).
- **cc** (*float or array of floats (nsystm, nrow, ncol)*) – cc is an array specifying the compression index of compressible beds cc is not used if icrcc is not equal to 0. (default is 0.25).
- **void** (*float or array of floats (nsystm, nrow, ncol)*) – void is an array specifying the initial void ratio of compressible beds. (default is 0.82).
- **sub** (*float or array of floats (nsystm, nrow, ncol)*) – sub is an array specifying the initial compaction in each system of interbeds. Compaction values computed by the package are added to values in this array so that printed or stored values of compaction and land subsidence may include previous components. Values in this array do not affect calculations of storage changes or resulting compaction. For simulations in which output values will reflect compaction and subsidence since the start of the simulation, enter zero values for all elements of this array. (default is 0.).
- **pcsoff** (*float or array of floats (nlay, nrow, ncol)*) – pcsoff is an array specifying the offset from initial effective stress to initial preconsolidation stress at the bottom of the model layer in units of height of a column of water. pcsoff is not used if istpcs=0. (default is 0.).
- **pcs** (*float or array of floats (nlay, nrow, ncol)*) – pcs is an array specifying the initial preconsolidation stress, in units of height of a column of water, at the bottom of the model layer. pcs is not used if istpcs is not equal to 0. (default is 0.).
- **ids16** (*list or array of ints (26)*) – Format codes and unit numbers for swt-sidence, compaction by model layer, compaction by interbed system, vertical displacement, preconsolidation stress, change in preconsolidation stress, geostatic stress, change in geostatic stress, effective stress, void ration, thickness of compressible sediments, and layer-center elevation will be printed. If ids16 is None and iswtoc>0 then print code 0 will be used for all data which is output to the binary swtsidence output file (unit=1054). The 26 entries in ids16 correspond to ifm1, iun1, ifm2, iun2, ifm3, iun3, ifm4, iun4, ifm5, iun5, ifm6, iun6, ifm7, iun7, ifm8, iun8, ifm9, iun9, ifm10, iun11, ifm12, iun12, ifm13, and iun13 variables. (default is None).
- **ids17** (*list or array of ints (iswtoc, 30)*) – Stress period and time step range and print and save flags used to control printing and saving of information generated by the SUB-WT Package during program execution. Each row of ids17 corresponds to isp1, isp2, its1, its2, ifl1, ifl2, ifl3, ifl4, ifl5, ifl6, ifl7, ifl8, ifl9, ifl10, ifl11, ifl12, ifl13, ifl14, ifl15, ifl16, ifl17, ifl18, ifl19, ifl20, ifl21, ifl22, ifl23, ifl24, ifl25, and ifl26 variables for iswtoc entries. isp1, isp2, its1, and its2 are stress period and time step ranges. ifl1 and ifl2 control subsidence printing and saving. ifl3 and ifl4 control compaction by model layer printing and saving. ifl5 and ifl6 control compaction by interbed system printing and saving. ifl7 and ifl8 control vertical displacement printing and saving. ifl9 and ifl10 control preconsolidation stress printing and saving. ifl11 and ifl12 control change in preconsolidation stress printing and saving. ifl13 and ifl14 control geostatic stress printing and saving. ifl15 and ifl16 control change in geostatic stress printing and saving. ifl17

and ifl18 control effective stress printing and saving. ifl19 and ifl20 control change in effective stress printing and saving. ifl21 and ifl22 control void ratio printing and saving. ifl23 and ifl24 control compressible bed thickness printing and saving. ifl25 and ifl26 control layer-center elevation printing and saving. If ids17 is None and iswtoc>0 then all available subsidence output will be printed and saved to the binary subsidence output file (unit=1054). (default is None).

- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name and other swt output files will be created using the model name and .cbc and swt output extensions (for example, modflowtest.cbc), if ipakcbc and other swt output files (dataset 16) are numbers greater than zero. If a single string is passed the package name will be set to the string and other swt output files will be set to the model name with the appropriate output file extensions. To define the names for all package files (input and output) the length of the list of strings should be 15. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent. Parameters are not supported in the SUB-WT Package.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> swt = flopy.modflow.ModflowSwt(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

### Returns swt

**Return type** ModflowSwt object

## Examples

```
>>> import floppy
>>> m = floppy.modflow.Modflow()
>>> swt = floppy.modflow.ModflowSwt.load('test.swt', m)
```

**write\_file**(*f=None*)  
Write the package file.

**Return type** None

## flopy.modflow.mfupw module

mfupw module. Contains the ModflowUpw class. Note that the user can access the ModflowUpw class as *flopy.modflow.ModflowUpw*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowUpw**(*model*, *laytyp=0*, *layavg=0*, *chani=1.0*, *layvka=0*, *laywet=0*, *ipakcb=None*, *hdry=-1e+30*, *iphdry=0*, *hk=1.0*, *hani=1.0*, *vka=1.0*, *ss=1e-05*, *sy=0.15*, *vkcb=0.0*, *noparcheck=False*, *extension='upw'*, *unitnumber=None*, *filenames=None*)

Bases: *flopy.pakbase.Package*

Upstream weighting package class

### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **hdry** (*float*) – Is the head that is assigned to cells that are converted to dry during a simulation. Although this value plays no role in the model calculations, it is useful as an indicator when looking at the resulting heads that are output from the model. Hdry is thus similar to HNOFLO in the Basic Package, which is the value assigned to cells that are no-flow cells at the start of a model simulation. (default is -1.e30).
- **iphdry** (*int*) – iphdry is a flag that indicates whether groundwater head will be set to hdry when the groundwater head is less than 0.0001 above the cell bottom (units defined by lenuni in the discretization package). If iphdry=0, then head will not be set to hdry. If iphdry>0, then head will be set to hdry. If the head solution from one simulation will be used as starting heads for a subsequent simulation, or if the Observation Process is used (Harbaugh and others, 2000), then hdry should not be printed to the output file for dry cells (that is, the upw package input variable should be set as iphdry=0). (default is 0)
- **noparcheck** (*bool*) – noparcheck turns off the checking that a value is defined for all cells when parameters are used to define layer data.
- **laytyp** (*int or array of ints (nlay)*) – Layer type (default is 0).
- **layavg** (*int or array of ints (nlay)*) – Layer average (default is 0). 0 is harmonic mean 1 is logarithmic mean 2 is arithmetic mean of saturated thickness and logarithmic mean of hydraulic conductivity
- **chani** (*float or array of floats (nlay)*) – contains a value for each layer that is a flag or the horizontal anisotropy. If CHANI is less than or equal to 0, then variable HANI defines horizontal anisotropy. If CHANI is greater than 0, then CHANI is the



horizontal anisotropy for the entire layer, and HANI is not read. If any HANI parameters are used, CHANI for all layers must be less than or equal to 0. Use as many records as needed to enter a value of CHANI for each layer. The horizontal anisotropy is the ratio of the hydraulic conductivity along columns (the Y direction) to the hydraulic conductivity along rows (the X direction).

- **layvka** (*int or array of ints (nlay)*) – a flag for each layer that indicates whether variable VKA is vertical hydraulic conductivity or the ratio of horizontal to vertical hydraulic conductivity.
- **laywet** (*int or array of ints (nlay)*) – contains a flag for each layer that indicates if wetting is active. laywet should always be zero for the UPW Package because all cells initially active are wettable.
- **hk** (*float or array of floats (nlay, nrow, ncol)*) – is the hydraulic conductivity along rows. HK is multiplied by horizontal anisotropy (see CHANI and HANI) to obtain hydraulic conductivity along columns. (default is 1.0).
- **hani** (*float or array of floats (nlay, nrow, ncol)*) – is the ratio of hydraulic conductivity along columns to hydraulic conductivity along rows, where HK of item 10 specifies the hydraulic conductivity along rows. Thus, the hydraulic conductivity along columns is the product of the values in HK and HANI. (default is 1.0).
- **vka** (*float or array of floats (nlay, nrow, ncol)*) – is either vertical hydraulic conductivity or the ratio of horizontal to vertical hydraulic conductivity depending on the value of LAYVKA. (default is 1.0).
- **ss** (*float or array of floats (nlay, nrow, ncol)*) – is specific storage unless the STORAGECOEFFICIENT option is used. When STORAGECOEFFICIENT is used, Ss is confined storage coefficient. (default is 1.e-5).
- **sy** (*float or array of floats (nlay, nrow, ncol)*) – is specific yield. (default is 0.15).
- **vkcb** (*float or array of floats (nlay, nrow, ncol)*) – is the vertical hydraulic conductivity of a Quasi-three-dimensional confining bed below a layer. (default is 0.0).
- **extension** (*string*) – Filename extension (default is 'upw')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output name will be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> lpf = flopY.modflow.ModflowLpf(m)
```

**classmethod** `load(f, model, ext_unit_dict=None, check=True)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.
- **check** (*boolean*) – Check package data for common errors. (default True)

**Returns** `dis` – ModflowLpf object.

**Return type** ModflowUPW object

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> upw = flopY.modflow.ModflowUpw.load('test.upw', m)
```

**write\_file**(*check=True, f=None*)

Write the package file.

**Parameters** **check** (*boolean*) – Check package data for common errors. (default True)

**Return type** None

## flopY.modflow.mfufz1 module

mfufz1 module. Contains the ModflowUzf1 class. Note that the user can access the ModflowUzf1 class as `flopY.modflow.ModflowUzf1`.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class** `ModflowUzf1(model, nuztop=1, iuzfopt=0, irunflg=0, ietflg=0, ipakcb=None, iuzfcb2=None, ntrail2=10, nsets=20, surfdep=1.0, iuzfbnd=1, irunbnd=0, vks=1e-06, eps=3.5, this=0.35, thtr=0.15, thti=0.2, specifythtr=False, specifythti=False, nosurfleak=False, finf=1e-08, pet=5e-08, extdp=15.0, extwc=0.1, air_entry=0.0, hroot=0.0, rootact=0.0, nwt_11_fmt=False, specifysurfkc=False, rejectsurfkc=False, seepsurfkc=False, etsquare=None, netflux=None, capillaryuzet=False, nuzgag=None, uzgag=None, extension='uzf', unitnumber=None, filenames=None, options=None, surfk=0.1)`

Bases: `flopY.pakbase.Package`

MODFLOW Unsaturated Zone Flow 1 Boundary Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **nuztop** (*integer*) – used to define which cell in a vertical column that recharge and discharge is simulated. (default is 1)
  - 1 Recharge to and discharge from only the top model layer.** This option assumes land surface is defined as top of layer 1.
  - 2 Recharge to and discharge from the specified layer in variable IUZFBND.** This option assumes land surface is defined as top of layer specified in IUZFBND.
  - 3 Recharge to and discharge from the highest active cell in each** vertical column. Land surface is determined as top of layer specified in IUZFBND. A constant head node intercepts any recharge and prevents deeper percolation.
- **iuzfopt** (*integer*) – equal to 1 or 2. A value of 1 indicates that the vertical hydraulic conductivity will be specified within the UZF1 Package input file using array VKS. A value of 2 indicates that the vertical hydraulic conductivity will be specified within either the BCF or LPF Package input file. (default is 0)
- **irunflg** (*integer*) – specifies whether ground water that discharges to land surface will be routed to stream segments or lakes as specified in the IRUNBND array (IRUNFLG not equal to zero) or if ground-water discharge is removed from the model simulation and accounted for in the ground-water budget as a loss of water (IRUNFLG=0). The Streamflow-Routing (SFR2) and/or the Lake (LAK3) Packages must be active if IRUNFLG is not zero. (default is 0)
- **ietflg** (*integer*) – specifies whether or not evapotranspiration (ET) will be simulated. ET will not be simulated if IETFLG is zero, otherwise it will be simulated. (default is 0)
- **ipakcb** (*integer*) – flag for writing ground-water recharge, ET, and ground-water discharge to land surface rates to a separate unformatted file using subroutine UBDSV. If ipakcb>0, it is the unit number to which the cell-by-cell rates will be written when ‘SAVE BUDGET’ or a non-zero value for ICBCFL is specified in Output Control. If ipakcb less than or equal to 0, cell-by-cell rates will not be written to a file. (default is 57)
- **iuzfcb2** (*integer*) – flag for writing ground-water recharge, ET, and ground-water discharge to land surface rates to a separate unformatted file using module UBDSV3. If IUZFCB2>0, it is the unit number to which cell-by-cell rates will be written when ‘SAVE BUDGET’ or a non-zero value for ICBCFL is specified in Output Control. If IUZFCB2 less than or equal to 0, cell-by-cell rates will not be written to file. (default is 0)
- **ntrail2** (*integer*) – equal to the number of trailing waves used to define the water-content profile following a decrease in the infiltration rate. The number of trailing waves varies depending on the problem, but a range between 10 and 20 is usually adequate. More trailing waves may decrease mass-balance error and will increase computational requirements and memory usage. (default is 10)
- **nsets** (*integer*) – equal to the number of wave sets used to simulate multiple infiltration periods. The number of wave sets should be set to 20 for most problems involving time varying infiltration. The total number of waves allowed within an unsaturated zone cell is equal to NTRAIL2\*NSETS2. An error will occur if the number of waves in a cell exceeds this value. (default is 20)

- **surfdep** (*float*) – The average height of undulations, D (Figure 1 in UZF documentation), in the land surface altitude. (default is 1.0)
- **iuzfbnd** (*integer*) – used to define the aerial extent of the active model in which recharge and discharge will be simulated. (default is 1)
- **irunbnd** (*integer*) – used to define the stream segments within the Streamflow-Routing (SFR2) Package or lake numbers in the Lake (LAK3) Package that overland runoff from excess infiltration and ground-water discharge to land surface will be added. A positive integer value identifies the stream segment and a negative integer value identifies the lake number. (default is 0)
- **vks** (*float*) – used to define the saturated vertical hydraulic conductivity of the unsaturated zone (LT-1). (default is 1.0E-6)
- **eps** (*float*) – values for each model cell used to define the Brooks-Corey epsilon of the unsaturated zone. Epsilon is used in the relation of water content to hydraulic conductivity (Brooks and Corey, 1966). (default is 3.5)
- **thts** (*float*) – used to define the saturated water content of the unsaturated zone in units of volume of water to total volume (L3L-3). (default is 0.35)
- **thtr** (*float*) – used to define the residual water content for each vertical column of cells in units of volume of water to total volume (L3L-3). THTR is the irreducible water content and the unsaturated water content cannot drain to water contents less than THTR. This variable is not included unless the key word SPECIFYTHTR is specified. (default is 0.15)
- **thti** (*float*) – used to define the initial water content for each vertical column of cells in units of volume of water at start of simulation to total volume (L3L-3). THTI should not be specified for steady-state simulations. (default is 0.20)
- **row\_col\_iftunit\_iuzopt** (*list*) – used to specify where information will be printed for each time step. row and col are zero-based. IUZOPT specifies what that information will be. (default is []) IUZOPT is
  - 1 Prints time, ground-water head, and thickness of unsaturated zone, and cumulative volumes of infiltration, recharge, storage, change in storage and ground-water discharge to land surface.
  - 2 Same as option 1 except rates of infiltration, recharge, change in storage, and ground-water discharge also are printed.
  - 3 Prints time, ground-water head, thickness of unsaturated zone, followed by a series of depths and water contents in the unsaturated zone.
- **nwt\_11\_fmt** (*boolean*) – flag indicating whether or not to utilize a newer (MODFLOW-NWT version 1.1 or later) format style, i.e., uzf1 optional variables appear line-by-line rather than in a specific order on a single line. True means that optional variables (e.g., SPECIFYTHTR, SPECIFYTHTI, NOSURFLEAK) appear on new lines. True also supports a number of newer optional variables (e.g., SPECIFYSURFK, REJECTSURFK, SEEPSURFK). False means that optional variables appear on one line. (default is False)
- **specifythtr** (*boolean*) – key word for specifying optional input variable THTR (default is 0)
- **specifythti** (*boolean*) – key word for specifying optional input variable THTI. (default is 0)

- **nosurfleak** (*boolean*) – key word for inactivating calculation of surface leakage. (default is 0)
- **specifysurfk** (*boolean*) – (MODFLOW-NWT version 1.1 and MODFLOW-2005 1.12 or later) An optional character variable. When SPECIFYSURFK is specified, the variable SURFK is specified in Data Set 4b.
- **rejectsurfk** (*boolean*) – (MODFLOW-NWT version 1.1 and MODFLOW-2005 1.12 or later) An optional character variable. When REJECTSURFK is specified, SURFK instead of VKS is used for calculating rejected infiltration. REJECTSURFK only is included if SPECIFYSURFK is included.
- **seepsurfk** (*boolean*) – (MODFLOW-NWT version 1.1 and MODFLOW-2005 1.12 or later) An optional character variable. When SEEPSURFK is specified, SURFK instead of VKS is used for calculating surface leakage. SEEPSURFK only is included if SPECIFYSURFK is included.
- **etsquare** (*float (smoothfact)*) – (MODFLOW-NWT version 1.1 and MODFLOW-2005 1.12 or later) An optional character variable. When ETSQUARE is specified, groundwater ET is simulated using a constant potential ET rate, and is smoothed over a specified smoothing interval. This option is recommended only when using the NWT solver.

etsquare is activated in flop by specifying a real value for smoothfact (default is None). For example, if the interval factor (smoothfact) is specified as smoothfact=0.1 (recommended), then the smoothing interval will be calculated as:  $SMOOTHINT = 0.1 * EXTDP$  and is applied over the range for groundwater head (h):  $* h < CELTOP - EXTDP$ , ET is zero;  $* CELTOP - EXTDP < h < CELTOP - EXTDP + SMOOTHINT$ , ET is smoothed;  $CELTOP - EXTDP + SMOOTHINT < h$ , ET is equal to potential ET.

- **uzgage** (*dict of lists or list of lists*) – Dataset 8 in UZF Package documentation. Each entry in the dict is keyed by iftunit.

Dict of lists: If iftunit is negative, the list is empty. If iftunit is positive, the list includes [IUZROW, IUZCOL, IUZOPT] List of lists: Lists follow the format described in the documentation: [[IUZROW, IUZCOL, IFTUNIT, IUZOPT]] or [[-IFTUNIT]]

- **netflux** (*list of [Unitrech (int), Unitdis (int)]*) – (MODFLOW-NWT version 1.1 and MODFLOW-2005 1.12 or later) An optional character variable. When NETFLUX is specified, the sum of recharge (L3/T) and the sum of discharge (L3/T) is written to separate unformatted files using module UBDSV3.

netflux is activated in flop by specifying a list for Unitrech and Unitdis (default is None). Unitrech and Unitdis are the unit numbers to which these values are written when “SAVE BUDGET” is specified in Output Control. Values written to Unitrech are the sum of recharge values for the UZF, SFR2, and LAK packages, and values written to Unitdis are the sum of discharge values for the UZF, SFR2, and LAK packages. Values are averaged over the period between output times.

[NETFLUX unitrech unitdis]

- **finf** (*float, 2-D array, or dict of {kper:value}*) – where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time. Used to define the infiltration rates (LT-1) at land surface for each vertical column of cells. If FINF is specified as being greater than the vertical hydraulic conductivity then FINF is set equal to the vertical unsaturated hydraulic conductivity. Excess water is routed to streams or lakes when IRUNFLG is not zero, and if SFR2 or LAK3 is active. (default is 1.0E-8)

- **pet** (*float, 2-D array, or dict of {kper:value}*) – where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time. Used to define the ET demand rates (LT-1) within the ET extinction depth interval for each vertical column of cells. (default is 5.0E-8)
- **extdp** (*float, 2-D array, or dict of {kper:value}*) – where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time. Used to define the ET extinction depths. The quantity of ET removed from a cell is limited by the volume of water stored in the unsaturated zone above the extinction depth. If ground water is within the ET extinction depth, then the rate removed is based on a linear decrease in the maximum rate at land surface and zero at the ET extinction depth. The linear decrease is the same method used in the Evapotranspiration Package (McDonald and Harbaugh, 1988, chap. 10). (default is 15.0)
- **extwc** (*float, 2-D array, or dict of {kper:value}*) –

where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time. Used to define the extinction water content below which ET cannot be removed from the unsaturated zone. EXTWC must have a value between (THTS-Sy) and THTS, where Sy is the specific yield specified in either the LPF or BCF Package. (default is 0.1)

**air\_entry** [*float, 2-D array, or dict of {kper: value}*] where kper is the zero-based stress period. Used to define the air entry pressure of the unsaturated zone in MODFLOW-NWT simulations

- **hroot** (*float, 2-D array, or dict of {kper: value}*) – where kper is the zero-based stress period. Used to define the pressure potential at roots in the unsaturated zone in MODFLOW-NWT simulations
- **rootact** (*float, 2-D array, or dict of {kper: value}*) – where kper is the zero-based stress period. Used to define the root activity in the unsaturated zone in MODFLOW-NWT simulations
- **uzfbud\_ext** (*list*) – appears to be used for sequential naming of budget output files (default is [])
- **extension** (*string*) – Filename extension (default is 'uzf')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output, uzf output, and uzf observation names will be created using the model name and .cbc, uzfcb2.bin, and .uzf#.out extensions (for example, modflowtest.cbc, and modflowtest.uzfcd2.bin), if ipakcbc, iuzfcb2, and len(uzgag) are numbers greater than zero. For uzf observations the file extension is created using the uzf observation file unit number (for example, for uzf observations written to unit 123 the file extension would be .uzf123.out). If a single string is passed the package name will be set to the string and other uzf output files will be set to the model name with the appropriate output file extensions. To define the names for all package files (input and output) the length of the list of strings should be 3 + len(uzgag). Default is None.
- **surfk** (*float*) – An optional array of positive real values used to define the hydraulic conductivity (LT-1). SURFK is used for calculating the rejected infiltration and/or surface leakage. IF SURFK is set greater than VKS then it is set equal to VKS. Only used

if SEEPSURFK is True.

#### nuzgag

equal to the number of cells (one per vertical column) that will be specified for printing detailed information on the unsaturated zone water budget and water content. A gage also may be used to print the budget summed over all model cells. (default is None)

**Type** integer (deprecated - counter is set based on length of uzgag)

#### Notes

Parameters are not supported in FloPy.

#### Examples

```
>>> import flopy
>>> m1 = flopy.modflow.Modflow()
>>> uzf = flopy.modflow.ModflowUzf1(m1, ...)
```

**classmethod** `load(f, model, ext_unit_dict=None, check=False)`

Load an existing package.

#### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `uzf` – ModflowUZF1 object.

**Return type** ModflowUZF1 object

#### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> uzf = flopy.modflow.ModflowUZF1.load('test.uzf', m)
```

#### property nuzgag

Number of uzf gages

**Returns** `nuzgag` – Number of uzf gages

**Return type** int

#### property uzgag

Get the uzf gage data

**Returns** `uzgag` – Dictionary containing uzf gage data for each gage

**Return type** dict

**write\_file**(*f=None*)  
Write the package file.

**Return type** None

### flopY.modflow.mfwel module

mfwel module. Contains the ModflowWel class. Note that the user can access the ModflowWel class as *flopY.modflow.ModflowWel*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowWel**(*model*, *ipakcb=None*, *stress\_period\_data=None*, *dtype=None*, *extension='wel'*, *options=None*, *binary=False*, *unitnumber=None*, *filenames=None*, *add\_package=True*)

Bases: *flopY.pakbase.Package*

MODFLOW Well Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type *flopY.modflow.mf.Modflow*) to which this package will be added.
- **ipakcb** (*int*) – A flag that is used to determine if cell-by-cell budget data should be saved. If ipakcb is non-zero cell-by-cell budget data will be saved. (default is 0).
- **stress\_period\_data** (*list of boundaries, or recarray of boundaries, or*) – dictionary of boundaries Each well is defined through definition of layer (int), row (int), column (int), flux (float). The simplest form is a dictionary with a lists of boundaries for each stress period, where each list of boundaries itself is a list of boundaries. Indices of the dictionary are the numbers of the stress period. This gives the form of:

```
stress_period_data = {0: [  
    [lay, row, col, flux], [lay, row, col, flux], [lay, row, col, flux] ],  
  
    1: [ [lay, row, col, flux], [lay, row, col, flux], [lay, row, col, flux] ], ...  
    kper: [ [lay, row, col, flux], [lay, row, col, flux], [lay, row, col, flux] ]  
}
```

Note that if the number of lists is smaller than the number of stress periods, then the last list of wells will apply until the end of the simulation. Full details of all options to specify stress\_period\_data can be found in the flopY3 boundaries Notebook in the basic subdirectory of the examples directory

- **dtype** (*custom datatype of stress\_period\_data.*) – If None the default well datatype will be applied (default is None).
- **extension** (*string*) – Filename extension (default is 'wel')
- **options** (*list of strings*) – Package options (default is None).
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the cbc output name will be created using the model name and .cbc extension (for example, modflowtest.cbc), if ipakcbc is a number greater than zero. If a single string is passed the package will be set to the string and cbc output names will



be created using the model name and .cbc extension, if ipakcbc is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

- **add\_package** (*bool*) – Flag to add the initialised package object to the parent model object. Default is True.

#### **mxactw**

Maximum number of wells for a stress period. This is calculated automatically by FloPy based on the information in `stress_period_data`.

**Type** int

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> lrcq = {0:[[2, 3, 4, -100.]], 1:[[2, 3, 4, -100.]]}
>>> wel = flopy.modflow.ModflowWel(m, stress_period_data=lrcq)
```

**add\_record**(*kper, index, values*)

**static get\_default\_dtype**(*structured=True*)

**static get\_empty**(*ncells=0, aux\_names=None, structured=True*)

**classmethod load**(*f, model, nper=None, ext\_unit\_dict=None, check=True*)

Load an existing package.

#### **Parameters**

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.modflow.mf.Modflow`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If *nper* is None, then *nper* will be obtained from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `wel` – ModflowWel object.

**Return type** ModflowWel object

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> wel = flopy.modflow.ModflowWel.load('test.wel', m)
```

**write\_file**(*f=None*)

Write the package file.

**Parameters** *f* – (str) optional file name

**Return type** None

## flopy.modflow.mfzon module

mfzon module. Contains the ModflowZone class. Note that the user can access the ModflowZone class as *flopy.modflow.ModflowZone*.

Additional information for this MODFLOW package can be found at the [Online MODFLOW Guide](#).

**class ModflowZon**(*model, zone\_dict=None, extension='zon', unitnumber=None, filenames=None*)

Bases: *flopy.pakbase.Package*

MODFLOW Zone Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **zone\_dict** (*dict*) – Dictionary with zone data for the model. *zone\_dict* is typically instantiated using load method.
- **extension** (*string*) – Filename extension (default is 'zon')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If *filenames=None* the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

Parameters are supported in Flopy only when reading in existing models. Parameter values are converted to native values in Flopy and the connection to “parameters” is thus nonexistent.

## Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow()
>>> zonedict = flopy.modflow.ModflowZon(m, zone_dict=zone_dict)
```

**classmethod load**(*f, model, nrow=None, ncol=None, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **nrow** (*int*) – number of rows. If not specified it will be retrieved from the model object. (default is None).
- **ncol** (*int*) – number of columns. If not specified it will be retrieved from the model object. (default is None).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** zone

**Return type** ModflowZone dict

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> zon = flopY.modflow.ModflowZon.load('test.zon', m)
```

### write\_file()

Write the package file.

**Return type** None

## Notes

Not implemented because parameters are only supported on load

## MT3DMS Packages

Contents:

### flopY.mt3d.mt module

**class** `Mt3dList`(*model, extension='list', listunit=7*)

Bases: `flopY.pakbase.Package`

List package class

### write\_file()

Every Package needs its own write\_file function

**class** `Mt3dms`(*modelname='mt3dtest', namefile\_ext='nam', modflowmodel=None, filfilename='mt3d\_link.ftl', filfree=False, version='mt3dms', exe\_name='mt3dms.exe', structured=True, listunit=16, flunit=10, model\_ws='.', external\_path=None, verbose=False, load=True, silent=0*)

Bases: `flopY.mbase.BaseModel`

MT3DMS Model Class.

**Parameters**

- **modelname** (*str*, *default* "mt3dtest") – Name of model. This string will be used to name the MODFLOW input that are created with `write_model`.
- **namefile\_ext** (*str*, *default* "nam") – Extension for the namefile.
- **modflowmodel** (`flopY.modflow.mf.Modflow`) – This is a flopY Modflow model object upon which this Mt3dms model is based.
- **ftlfilename** (*str*, *default* "mt3d\_link.ftl") – Name of flow-transport link file.
- **ftlfree** (*TYPE*, *default* *False*) – If flow-link transport file is formatted (True) or unformatted (False, default).
- **version** (*str*, *default* "mt3dms") – Mt3d version. Choose one of: "mt3dms" (default) or "mt3d-usgs".
- **exe\_name** (*str*, *default* "mt3dms.exe") – The name of the executable to use.
- **structured** (*bool*, *default* *True*) – Specify if model grid is structured (default) or unstructured.
- **listunit** (*int*, *default* 16) – Unit number for the list file.
- **ftlunit** (*int*, *default* 10) – Unit number for flow-transport link file.
- **model\_ws** (*str*, *optional*) – Model workspace. Directory name to create model data sets. Default is the present working directory.
- **external\_path** (*str*, *optional*) – Location for external files.
- **verbose** (*bool*, *default* *False*) – Print additional information to the screen.
- **load** (*bool*, *default* *True*) – Load model.
- **silent** (*int*, *default* 0) – Silent option.

## Notes

## Examples

```
>>> import flopY
>>> m = flopY.mt3d.mt.Mt3dms()
```

**get\_nrow\_ncol\_nlay\_nper()**

**classmethod load** (*f*, *version*='mt3dms', *exe\_name*='mt3dms.exe', *verbose*=*False*, *model\_ws*='.',  
*load\_only*=*None*, *forgive*=*False*, *modflowmodel*=*None*)

Load an existing model.

### Parameters

- **f** (*str*) – Path to MT3D name file to load.
- **version** (*str*, *default* "mt3dms") – Mt3d version. Choose one of: "mt3dms" (default) or "mt3d-usgs".
- **exe\_name** (*str*, *default* "mt3dms.exe") – The name of the executable to use.
- **verbose** (*bool*, *default* *False*) – Print information on the load process if True.
- **model\_ws** (*str*, *default* ".") – Model workspace path. Default is the current directory.

- **load\_only** (*list of str, optional*) – Packages to load (e.g. ['btn', 'adv']). Default None means that all packages will be loaded.
- **forgive** (*bool, default False*) – Option to raise exceptions on package load failure, which can be useful for debugging.
- **modflowmodel** (*flopy.modflow.mf.Modflow, optional*) – This is a flopy Modflow model object upon which this Mt3dms model is based.

**Return type** *flopy.mt3d.mt.Mt3dms*

## Notes

The load method does not retain the name for the MODFLOW-generated FTL file. This can be added manually after the MT3D model has been loaded. The syntax for doing this manually is `mt.ftlfilename = 'example.ftl'`.

## Examples

```
>>> import flopy
>>> mt = flopy.mt3d.mt.Mt3dms.load('example.nam')
>>> mt.ftlfilename = 'example.ftl'
```

**static load\_mas**(*fname*)

Load an mt3d mas file and return a numpy recarray

**Parameters** *fname* (*str*) – name of MT3D mas file

**Returns** *r*

**Return type** *np.ndarray*

**static load\_obs**(*fname*)

Load an mt3d obs file and return a numpy recarray

**Parameters** *fname* (*str*) – name of MT3D obs file

**Returns** *r*

**Return type** *np.ndarray*

**load\_results**(*\*\*kwargs*)

property *mcomp*

property *modelgrid*

property *modeltime*

property *ncol*

property *ncomp*

property *nlay*

property *nper*

property *nrow*

property *nrow\_ncol\_nlay\_nper*

property *solver\_tols*

property **sr**

write\_name\_file()

Write the name file.

## flop.mt3d.mtadv module

**class Mt3dAdv**(*model*, *mixelm*=3, *percel*=0.75, *mxpart*=800000, *nadvfd*=1, *itrack*=3, *wd*=0.5, *dceps*=1e-05, *nplane*=2, *npl*=10, *nph*=40, *npmin*=5, *npmax*=80, *nlsink*=0, *npsink*=15, *dchmoc*=0.0001, *extension*='adv', *unitnumber*=None, *filenames*=None)

Bases: [\*flop.pakbase.Package\*](#)

MT3DMS Advection Package Class.

### Parameters

- **model** (*model object*) – The model object (of type [\*flop.mt3d.mt.Mt3dms\*](#)) to which this package will be added.
- **mixelm** (*int*) – MIXELM is an integer flag for the advection solution option. MIXELM = 0, the standard finite-difference method with upstream or central-in-space weighting, depending on the value of NADVFD; = 1, the forward-tracking method of characteristics (MOC); = 2, the backward-tracking modified method of characteristics (MMOC); = 3, the hybrid method of characteristics (HMOC) with MOC or MMOC automatically and dynamically selected; = -1, the third-order TVD scheme (ULTIMATE).
- **percel** (*float*) – PERCEL is the Courant number (i.e., the number of cells, or a fraction of a cell) advection will be allowed in any direction in one transport step. For implicit finite-difference or particle-tracking-based schemes, there is no limit on PERCEL, but for accuracy reasons, it is generally not set much greater than one. Note, however, that the PERCEL limit is checked over the entire model grid. Thus, even if PERCEL > 1, advection may not be more than one cell's length at most model locations. For the explicit finite-difference or the third-order TVD scheme, PERCEL is also a stability constraint which must not exceed one and will be automatically reset to one if a value greater than one is specified.
- **mxpart** (*int*) – MXPART is the maximum total number of moving particles allowed and is used only when MIXELM = 1 or 3.
- **nadvfd** (*int*) – NADVFD is an integer flag indicating which weighting scheme should be used; it is needed only when the advection term is solved using the implicit finite-difference method. NADVFD = 0 or 1, upstream weighting (default); = 2, central-in-space weighting.
- **itrack** (*int*) – ITRACK is a flag indicating which particle-tracking algorithm is selected for the Eulerian-Lagrangian methods. ITRACK = 1, the first-order Euler algorithm is used. = 2, the fourth-order Runge-Kutta algorithm is used; this option is computationally demanding and may be needed only when PERCEL is set greater than one. = 3, the hybrid first- and fourth-order algorithm is used; the Runge-Kutta algorithm is used in sink/source cells and the cells next to sinks/sources while the Euler algorithm is used elsewhere.
- **wd** (*float*) – is a concentration weighting factor between 0.5 and 1. It is used for operator splitting in the particle- tracking-based methods. The value of 0.5 is generally adequate. The value of WD may be adjusted to achieve better mass balance. Generally, it can be increased toward 1.0 as advection becomes more dominant.
- **dceps** (*float*) – is a small Relative Cell Concentration Gradient below which advective transport is considered

- **nplane** (*int*) – NPLANE is a flag indicating whether the random or fixed pattern is selected for initial placement of moving particles. If NPLANE = 0, the random pattern is selected for initial placement. Particles are distributed randomly in both the horizontal and vertical directions by calling a random number generator (Figure 18b). This option is usually preferred and leads to smaller mass balance discrepancy in nonuniform or diverging/converging flow fields. If NPLANE > 0, the fixed pattern is selected for initial placement. The value of NPLANE serves as the number of vertical ‘planes’ on which initial particles are placed within each cell block (Figure 18a). The fixed pattern may work better than the random pattern only in relatively uniform flow fields. For two-dimensional simulations in plan view, set NPLANE = 1. For cross sectional or three-dimensional simulations, NPLANE = 2 is normally adequate. Increase NPLANE if more resolution in the vertical direction is desired.
- **npl** (*int*) – NPL is the number of initial particles per cell to be placed at cells where the Relative Cell Concentration Gradient is less than or equal to DCEPS. Generally, NPL can be set to zero since advection is considered insignificant when the Relative Cell Concentration Gradient is less than or equal to DCEPS. Setting NPL equal to NPH causes a uniform number of particles to be placed in every cell over the entire grid (i.e., the uniform approach).
- **nph** (*int*) – NPH is the number of initial particles per cell to be placed at cells where the Relative Cell Concentration Gradient is greater than DCEPS. The selection of NPH depends on the nature of the flow field and also the computer memory limitation. Generally, a smaller number should be used in relatively uniform flow fields and a larger number should be used in relatively nonuniform flow fields. However, values exceeding 16 in two-dimensional simulation or 32 in three-dimensional simulation are rarely necessary. If the random pattern is chosen, NPH particles are randomly distributed within the cell block. If the fixed pattern is chosen, NPH is divided by NPLANE to yield the number of particles to be placed per vertical plane, which is rounded to one of the values shown in Figure 30.
- **npmin** (*int*) – is the minimum number of particles allowed per cell. If the number of particles in a cell at the end of a transport step is fewer than NPMIN, new particles are inserted into that cell to maintain a sufficient number of particles. NPMIN can be set to zero in relatively uniform flow fields and to a number greater than zero in diverging/converging flow fields. Generally, a value between zero and four is adequate.
- **npmax** (*int*) – NPMAX is the maximum number of particles allowed per cell. If the number of particles in a cell exceeds NPMAX, all particles are removed from that cell and replaced by a new set of particles equal to NPH to maintain mass balance. Generally, NPMAX can be set to approximately two times of NPH.
- **interp** (*int*) – is a flag indicating the concentration interpolation method for use in the MMOC scheme. Currently, only linear interpolation is implemented.
- **nlsink** (*int*) – is a flag indicating whether the random or fixed pattern is selected for initial placement of particles to approximate sink cells in the MMOC scheme. The convention is the same as that for NPLANE. It is generally adequate to set NLSINK equivalent to NPLANE.
- **npsink** (*int*) – is the number of particles used to approximate sink cells in the MMOC scheme. The convention is the same as that for NPH. It is generally adequate to set NPSINK equivalent to NPH.
- **dchmoc** (*float*) – DCHMOC is the critical Relative Concentration Gradient for controlling the selective use of either MOC or MMOC in the HMOC solution scheme. The MOC solution is selected at cells where the Relative Concentration Gradient is greater

than DCHMOC. The MMOC solution is selected at cells where the Relative Concentration Gradient is less than or equal to DCHMOC.

- **extension** (*string*) – Filename extension (default is 'adv')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.mt3d.Mt3dms()
>>> adv = flopy.mt3d.Mt3dAdv(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `adv` – Mt3dAdv object.

**Return type** Mt3dAdv object

## Examples

```
>>> import flopy
>>> mt = flopy.mt3d.Mt3dms()
>>> adv = flopy.mt3d.Mt3dAdv.load('test.adv', m)
```

**write\_file()**

Write the package file

**Return type** None



## flopY.mt3d.mtbtn module

mtbtn module. Contains the Mt3dBtn class. Note that the user can access the Mt3dBtn class as `flopY.mt3d.Mt3dBtn`.

Additional information for this MT3DMS package can be found in the MT3DMS User's Manual.

```
class Mt3dBtn(model, MFStyleArr=False, DRYCell=False, Legacy99Stor=False, FTLPrint=False,
              NoWetDryPrint=False, OmitDryBud=False, AltWTSorb=False, nlay=None, nrow=None,
              ncol=None, nper=None, ncomp=1, mcomp=1, tunit='D', lunit='M', munit='KG', laycon=None,
              delr=None, delc=None, htop=None, dz=None, prsity=0.3, icbund=1, sconc=0.0, cinact=1e+30,
              thkmin=0.01, ifmtcn=0, ifmtnp=0, ifmtrf=0, ifmtdp=0, savucn=True, nprs=0, timprs=None,
              obs=None, nprobs=1, chkmas=True, nprmas=1, perlen=None, nstp=None, tsmult=None,
              ssflag=None, dt0=0, mxstrn=50000, ttsmult=1.0, ttsmax=0, species_names=None,
              extension='btn', unitnumber=None, filenames=None, **kwargs)
```

Bases: [flopY.pakbase.Package](#)

Basic Transport Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopY.mt3dms.mt.Mt3dms`) to which this package will be added.
- **MFStyleArr** (*str*) – Specifies whether or not to read arrays using the MODFLOW array reader format or the original MT3DMS array reader
- **DRYCell** (*str*) – Specifies whether or not to route mass through dry cells. When MF-NWT is used to generate the flow-transport link file, this is a distinct possibility.
- **Legacy99Stor** (*str*) – Specifies whether or not to use the storage formulation used in MT3DMS
- **FTLPrint** (*str*) – Specifies if flow-transport link terms (cell-by-cell flows) should be echoed to the MT3D-USGS listing file.
- **NoWetDryPrint** (*str*) – Specifies whether or not to suppress wet/dry messaging in the MT3D-USGS listing file.
- **OmitDryBudg** (*str*) – Specifies whether or not to include the mass flux terms through dry cells in the mass budget written to the listing file.
- **AltWTSorb** (*str*) – Specifies whether or not to use the MT3DMS formulation (this keyword omitted) for the solid phase, whereby the entire cell thickness is available for interacting with the aqueous phase, even though the aqueous phase may only occupy a portion of the cell's thickness. When used, only the saturated portion of the cell is available for sorbing
- **ncomp** (*int*) – The total number of chemical species in the simulation. (default is None, will be changed to 1 if sconc is single value)
- **mcomp** (*int*) – The total number of 'mobile' species (default is 1). mcomp must be equal or less than ncomp.
- **tunit** (*str*) – The name of unit for time (default is 'D', for 'days'). Used for identification purposes only.
- **lunit** (*str*) – The name of unit for length (default is 'M', for 'meters'). Used for identification purposes only.
- **munit** (*str*) – The name of unit for mass (default is 'KG', for 'kilograms'). Used for identification purposes only.

- **prsim** (*float or array of floats (nlay, nrow, ncol)*) – The effective porosity of the porous medium in a single porosity system, or the mobile porosity in a dual-porosity medium (the immobile porosity is defined through the Chemical Reaction Package. (default is 0.25).
- **icbund** (*int or array of ints (nlay, nrow, ncol)*) – The icbund array specifies the boundary condition type for solute species (shared by all species). If icbund = 0, the cell is an inactive concentration cell; If icbund < 0, the cell is a constant-concentration cell; If icbund > 0, the cell is an active concentration cell where the concentration value will be calculated. (default is 1).
- **sconc** (*float, array of (nlay, nrow, ncol), or filename*) – sconc is the starting concentration for the first species. To specify starting concentrations for other species in a multi-species simulation, include additional keywords, such as sconc2, sconc3, and so forth.
- **cinact** (*float*) – The value for indicating an inactive concentration cell. (default is 1e30).
- **thkmin** (*float*) – The minimum saturated thickness in a cell, expressed as the decimal fraction of its thickness, below which the cell is considered inactive. (default is 0.01).
- **ifmtcn** (*int*) – A flag/format code indicating how the calculated concentration should be printed to the standard output text file. Format codes for printing are listed in Table 3 of the MT3DMS manual. If ifmtcn > 0 printing is in wrap form; if ifmtcn < 0 printing is in strip form; if ifmtcn = 0 concentrations are not printed. (default is 0).
- **ifmtnp** (*int*) – A flag/format code indicating how the number of particles should be printed to the standard output text file. The convention is the same as for ifmtcn. (default is 0).
- **ifmtrf** (*int*) – A flag/format code indicating how the calculated retardation factor should be printed to the standard output text file. The convention is the same as for ifmtcn. (default is 0).
- **ifmtdp** (*int*) – A flag/format code indicating how the distance-weighted dispersion coefficient should be printed to the standard output text file. The convention is the same as for ifmtcn. (default is 0).
- **savucn** (*bool*) – A logical flag indicating whether the concentration solution should be saved in an unformatted file. (default is True).
- **nprs** (*int*) – A flag indicating (i) the frequency of the output and (ii) whether the output frequency is specified in terms of total elapsed simulation time or the transport step number. If nprs > 0 results will be saved at the times as specified in timprs; if nprs = 0, results will not be saved except at the end of simulation; if NPRS < 0, simulation results will be saved whenever the number of transport steps is an even multiple of nprs. (default is 0).
- **timprs** (*list of floats*) – The total elapsed time at which the simulation results are saved. The number of entries in timprs must equal nprs. (default is None).
- **obs** (*array of int*) – An array with the cell indices (layer, row, column) for which the concentration is to be printed at every transport step. (default is None). obs indices must be entered as zero-based numbers as a 1 is added to them before writing to the btn file.
- **nprobs** (*int*) – An integer indicating how frequently the concentration at the specified observation points should be saved. (default is 1).

- **chkmas** (*bool*) – A logical flag indicating whether a one-line summary of mass balance information should be printed. (default is True).
- **nprmas** (*int*) – An integer indicating how frequently the mass budget information should be saved. (default is 1).
- **dt0** (*float*) – The user-specified initial transport step size within each time-step of the flow solution. (default is 0).
- **mxstrn** (*int*) – The maximum number of transport steps allowed within one time step of the flow solution. (default is 50000).
- **ttsmult** (*float*) – The multiplier for successive transport steps within a flow time-step if the GCG solver is used and the solution option for the advection term is the standard finite-difference method. (default is 1.0).
- **ttsmax** (*float*) – The maximum transport step size allowed when transport step size multiplier TTSMULT > 1.0. (default is 0).
- **species\_names** (*list of str*) – A list of names for every species in the simulation.
- **extension** (*string*) – Filename extension (default is 'btn')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> mt = flopy.mt3dms.Mt3dms()
>>> btn = flopy.mt3dms.Mt3dBtn(mt)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `btn` – `Mt3dBtn` object.

**Return type** `Mt3dBtn` object

## Examples

```
>>> import flopY
>>> mt = flopY.mt3d.Mt3dms()
>>> btn = flopY.mt3d.Mt3dBtn.load('test.btn', mt)
```

**setmodflowvars**(*nlay, nrow, ncol, nper, laycon, delr, delc, htop, dz, perlen, nstp, tsmult*)

Set these variables from the MODFLOW model, if it exists

**write\_file**()

Write the package file

**Return type** None

## flopY.mt3d.mtcts module

**class Mt3dCts**

Bases: *flopY.pakbase.Package*

MT3D-USGS Contaminant Treatment System package class

### Parameters

- **model** (*model object*) – The model object (of type *flopY.mt3dms.mt.Mt3dms*) to which this package will be added.
- **mxcts** (*int*) – The maximum number of contaminant transport systems implemented in a simulation.
- **ictsout** (*int*) – The unit number on which well-by-well output information is written. The default file extension assigned to the output file is TSO
- **mxext** (*int*) – The maximum number of extraction wells specified as part of a contaminant treatment system
- **mxinj** (*int*) – The maximum number of injection wells specified as part of a contaminant treatment system
- **mxwel** (*int*) – The maximum number of wells in the flow model. MXWEL is recommended to be set equal to MXWEL as specified in the WEL file
- **iforce** (*int*) – A flag to force concentration in treatment systems to satisfy specified concentration/mass values based on the treatment option selected without considering whether treatment is necessary or not. This flag is ignored if ‘no treatment’ option is selected.

**0 Concentration for all injection wells is set to satisfy** treatment levels only if blended concentration exceeds the desired concentration/mass level for a treatment system. If the blended concentration in a treatment system is less than the specified concentration/mass level, then injection wells inject water with blended concentrations.

**1 Concentration for all injection wells is forced to satisfy** specified concentration/mass values.

- **ncts** (*int*) – The number of contaminant treatment systems. If NCTS  $\geq 0$ , NCTS is the number of contaminant treatment systems. If NCTS = -1, treatment system information from the previous stress period is reused for the current stress period.
- **icts** (*int*) – The contaminant treatment system index number.

- **next** (*int*) – The number of extraction wells for the treatment system number ICTS.
- **ninj** (*int*) – The number of injection wells for the treatment system number ICTS.
- **itrtnj** (*int*) – Is the level of treatment provided for the treatment system number ICTS. Each treatment system blends concentration collected from all extraction wells contributing to the treatment system and assigns a treated concentration to all injection wells associated with that treatment system based on the treatment option selected
  - 0 no treatment is provided
  - 1 same level of treatment is provided to all injection wells.
  - 2 different level of treatment can be provided to each individual injection well.
- **qincts** (*float*) – The external flow entering a treatment system. External flow may be flow entering a treatment system that is not a part of the model domain but plays an important role in influencing the blended concentration of a treatment system
- **cincts** (*float*) – The concentration with which the external flow enters a treatment system
- **ioptinj** (*int*) – Is a treatment option. Negative values indicate removal of concentration/mass and positive values indicate addition of concentration/mass.
  - 1 Percentage concentration/mass addition/removal is performed.** Percentages must be specified as fractions. Example, for 50% concentration/mass removal is desired, -0.5 must be specified.
  - 2 Concentration is added/removed from the blended concentration.** Specified concentration CMCHGINJ is added to the blended concentration. If the specified concentration removal, CMCHGINJ, is greater than the blended concentration, the treated concentration is set to zero.
  - 3 Mass is added/removed from the blended concentration.** Specified mass CMCHGINJ is added to the blended concentration. If the specified mass removal, CMCHGINJ, is greater than the blended total mass, the treated concentration is set to zero.
  - 4 Specified concentration is set equal to the entered value CMCHGINJ.** A positive value is expected for CMCHGINJ with this option.
- **cmchginj** (*float*) – Is the addition, removal, or specified concentration/mass values set for the treatment system. Concentration/mass is added, removed, or used as specified concentrations depending on the treatment option IOPTINJ. Note that concentration/mass values as specified by CMCHGINJ are enforced if the option IFORCE is set to 1. If IFORCE is set to 0, then CMCHGINJ is enforced only when the blended concentration exceeds the specified concentration CNTE.
- **cnte** (*float*) – The concentration that is not to be exceeded for a treatment system. Treatment is applied to blended concentration only if it exceeds CNTE, when IFORCE is set to 0.
- **kinj** (*int*) – Layer index for a CTS injection well
- **iinj** (*int*) – Row index for a CTS injection well
- **jinj** (*int*) – Column index for a CTS injection well
- **iwinj** (*int*) – The well index number. This number corresponds to the well number as it appears in the WEL file of the flow model.
- **qoutcts** (*float*) – the flow rate of outflow from a treatment system to an external sink. This flow rate must be specified to maintain an overall treatment system mass balance.

QOUTCTS must be set equal to total inflow into a treatment system minus total outflow to all injection wells for a treatment system

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>>
>>>
>>>
>>>
```

**static** `get_default_CTS_dtype(ncomp=1, iforce=0)`

Construct a dtype for the recarray containing the list of cts systems

**classmethod** `load(f, model, nlay=None, nrow=None, ncol=None, nper=None, ncomp=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- `f (filename or file handle)` – File to load.
- `model (model object)` – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- `ext_unit_dict (dictionary, optional)` – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `cts` – `Mt3dCts` object

**Return type** `Mt3dCts` object

## Examples

```
>>>
```

## `flopy.mt3d.mtdsp` module

**class** `Mt3dDsp(model, al=0.01, trpt=0.1, trpv=0.01, dmcoef=1e-09, extension='dsp', multiDiff=False, unitnumber=None, filenames=None, **kwargs)`

Bases: `flopy.pakbase.Package`

MT3DMS Dispersion Package Class.

### Parameters

- `model (model object)` – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- `al (float or array of floats (nlay, nrow, ncol))` – AL is the longitudinal dispersivity, for every cell of the model grid (unit, L). (default is 0.01)

- **trpt** (*float or array of floats (nlay)*) – s a 1D real array defining the ratio of the horizontal transverse dispersivity to the longitudinal dispersivity. Each value in the array corresponds to one model layer. Some recent field studies suggest that TRPT is generally not greater than 0.1. (default is 0.1)
- **trpv** (*float or array of floats (nlay)*) – is the ratio of the vertical transverse dispersivity to the longitudinal dispersivity. Each value in the array corresponds to one model layer. Some recent field studies suggest that TRPT is generally not greater than 0.01. Set TRPV equal to TRPT to use the standard isotropic dispersion model (Equation 10 in Chapter 2). Otherwise, the modified isotropic dispersion model is used (Equation 11 in Chapter 2). (default is 0.01)
- **dmcoef** (*float or array of floats (nlay) or (nlay, nrow, ncol) if the*) – multiDiff option is used. DMCOEF is the effective molecular diffusion coefficient (unit, L<sup>2</sup>T<sup>-1</sup>). Set DMCOEF = 0 if the effect of molecular diffusion is considered unimportant. Each value in the array corresponds to one model layer. The value for dmcoef applies only to species 1. See kwargs for entering dmcoef for other species. (default is 1.e-9).
- **multiDiff** (*boolean*) – To activate the component-dependent diffusion option, a keyword input record must be inserted to the beginning of the Dispersion (DSP) input file. The symbol \$ in the first column of an input line signifies a keyword input record containing one or more predefined keywords. Above the keyword input record, comment lines marked by the symbol # in the first column are allowed. Comment lines are processed but have no effect on the simulation. Furthermore, blank lines are also acceptable above the keyword input record. Below the keyword input record, the format of the DSP input file must remain unchanged from the previous versions except for the diffusion coefficient as explained below. If no keyword input record is specified, the input file remains backward compatible with all previous versions of MT3DMS. The predefined keyword for the component-dependent diffusion option is MultiDiffusion. The keyword is case insensitive so “MultiDiffusion” is equivalent to either “Multidiffusion” or “multidiffusion”. If this keyword is specified in the keyword input record that has been inserted into the beginning of the DSP input file, the component-dependent diffusion option has been activated and the user needs to specify one diffusion coefficient for each mobile solute component and at each model cell. This is done by specifying one mobile component at a time, from the first component to the last component (MCOMP). For each mobile component, the real array reader utility (RARRAY) is used to input the 3-D diffusion coefficient array, one model layer at a time. (default is False)
- **extension** (*string*) – Filename extension (default is ‘dsp’)
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.
- **kwargs** (*dictionary*) – If a multi-species simulation, then dmcoef values can be specified for other species as dmcoef2, dmcoef3, etc. For example: dmcoef1=1.e-10, dmcoef2=4.e-10, ... If a value is not specified, then dmcoef is set to 0.0.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.mt3d.Mt3dms()
>>> dsp = flopy.mt3d.Mt3dDsp(m)
```

**classmethod** `load(f, model, nlay=None, nrow=None, ncol=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **nlay** (*int*) – number of model layers. If None it will be retrieved from the model.
- **nrow** (*int*) – number of model rows. If None it will be retrieved from the model.
- **ncol** (*int*) – number of model columns. If None it will be retrieved from the model.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `dsk` – Mt3dDsp object.

**Return type** Mt3dDsp object

## Examples

```
>>> import flopy
>>> mt = flopy.mt3d.Mt3dms()
>>> dsp = flopy.mt3d.Mt3dAdv.load('test.dsp', m)
```

**write\_file()**

Write the package file

**Return type** None

## flopy.mt3d.mtgcg module

**class** `Mt3dGcg(model, mxiter=1, iter1=50, isolve=3, ncrs=0, accl=1, cclose=1e-05, iprgcg=0, extension='gcg', unitnumber=None, filenames=None)`

Bases: `flopy.pakbase.Package`

MT3DMS Generalized Conjugate Gradient Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.



- **mxiter** (*int*) – is the maximum number of outer iterations; it should be set to an integer greater than one only when a nonlinear sorption isotherm is included in simulation. (default is 1)
- **iter1** (*int*) – is the maximum number of inner iterations; a value of 30-50 should be adequate for most problems. (default is 50)
- **isolve** (*int*) – is the type of preconditioners to be used with the Lanczos/ORTHOMIN acceleration scheme: = 1, Jacobi = 2, SSOR = 3, Modified Incomplete Cholesky (MIC) (MIC usually converges faster, but it needs significantly more memory) (default is 3)
- **ncrs** (*int*) – is an integer flag for treatment of dispersion tensor cross terms: = 0, lump all dispersion cross terms to the right-hand-side (approximate but highly efficient). = 1, include full dispersion tensor (memory intensive). (default is 0)
- **accl** (*float*) – is the relaxation factor for the SSOR option; a value of 1.0 is generally adequate. (default is 1)
- **cclose** (*float*) – is the convergence criterion in terms of relative concentration; a real value between 10-4 and 10-6 is generally adequate. (default is 1.E-5)
- **iprgcg** (*int*) – IPRGCG is the interval for printing the maximum concentration changes of each iteration. Set IPRGCG to zero as default for printing at the end of each stress period. (default is 0)
- **extension** (*string*) – Filename extension (default is 'gcg')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package. If filenames=None the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is None.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.mt3d.Mt3dms()
>>> gcg = flopy.mt3d.Mt3dGcg(m)
```

**classmethod** `load(f, model, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case *ext\_unit\_dict* is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `gcg` – Mt3dGcg object.

**Return type** Mt3dGcg object

## Examples

```
>>> import flopY
>>> mt = flopY.mt3d.Mt3dms()
>>> gcg = flopY.mt3d.Mt3dGcg.load('test.gcg', m)
```

**unitnumber** = 35

**write\_file()**

Write the package file

**Return type** None

## flopY.mt3d.mtlkt module

**class Mt3dLkt**(*model*, *nlkinit*=0, *mxlkb*=0, *icbclk*=None, *ietlak*=0, *coldlak*=0.0, *lk\_stress\_period\_data*=None, *dtype*=None, *extension*='lkt', *unitnumber*=None, *filenames*=None, *iprn*=- 1, *\*\*kwargs*)

Bases: [flopY.pakbase.Package](#)

MT3D-USGS LaKe Transport package class

### Parameters

- **model** (*model object*) – The model object (of type `flopY.mt3dms.mt.Mt3dms`) to which this package will be added.
- **nlkinit** (*int*) – is equal to the number of simulated lakes as specified in the flow simulation
- **mxlkb** (*int*) – must be greater than or equal to the sum total of boundary conditions applied to each lake
- **icbclk** (*int*) – is equal to the unit number on which lake-by-lake transport information will be printed. This unit number must appear in the NAM input file required for every MT3D-USGS simulation.
- **ietlak** (*int*) – specifies whether or not evaporation as simulated in the flow solution will act as a mass sink. = 0, Mass does not exit the model via simulated lake evaporation != 0, Mass may leave the lake via simulated lake evaporation
- **coldlak** (*array of floats*) – is a vector of real numbers representing the initial concentrations in the simulated lakes. The length of the vector is equal to the number of simulated lakes, NLKINIT. Initial lake concentrations should be in the same order as the lakes appearing in the LAK input file corresponding to the MODFLOW simulation.
- **ntmp** (*int*) – is an integer value corresponding to the number of specified lake boundary conditions to follow. For the first stress period, this value must be greater than or equal to zero, but may be less than zero in subsequent stress periods.
- **ilkbc** (*int*) – is the lake number for which the current boundary condition will be specified
- **ilkbctyp** (*int*) –

specifies what the boundary condition type is for ilakbc

**1 a precipitation boundary. If precipitation directly to lakes** is simulated in the flow model and a non-zero concentration (default is zero) is desired, use ISFBCTYP = 1;

- 2 a runoff boundary condition that is not the same thing as** runoff simulated in the UZF1 package and routed to a lake (or stream) using the IRNBND array. Users who specify runoff in the LAK input via the RNF variable appearing in record set 9a and want to assign a non-zero concentration (default is zero) associated with this specified source, use ISFBCTYP=2;
  - 3 a Pump boundary condition. Users who specify a withdrawal** from a lake via the WTHDRW variable appearing in record set 9a and want to assign a non-zero concentration (default is zero) associated with this specified source, use ISFBCTYP=2;
  - 4 an evaporation boundary condition. In models where evaporation** is simulated directly from the surface of the lake, users can use this boundary condition to specify a non-zero concentration (default is zero) associated with the evaporation losses.
- **extension** (*string*) – Filename extension (default is 'lkt')
  - **unitnumber** (*int*) – File unit number (default is None).
  - **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the lake output name will be created using the model name and lake concentration observation extension (for example, modflowtest.cbc and modflowtest.lkcobs.out), if icbclk is a number greater than zero. If a single string is passed the package will be set to the string and lake concentration observation output name will be created using the model name and .lkcobs.out extension, if icbclk is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopY
>>> mt = flopY.mt3d.Mt3dms()
>>> lkt = flopY.mt3d.Mt3dLkt(mt)
```

**static get\_default\_dtype**(*ncomp=1*)

Construct a dtype for the recarray containing the list of boundary conditions interacting with the lake (i.e., pumps, specified runoff...)

**classmethod load**(*f, model, nlak=None, nper=None, ncomp=None, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopY.mt3d.mt.Mt3dms`) to which this package will be added.
- **nlak** (*int*) – number of lakes to be simulated
- **nper** (*int*) – number of stress periods

- **ncomp** (*int*) – number of species to be simulated
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `lkt` – MT3D-USGS object.

**Return type** MT3D-USGS object

## Examples

```
>>> import flopy
>>> datadir = 'examples/data/mt3d_test/mfnwt_mt3dusgs/lkt'
>>> mt = flopy.mt3d.Mt3dms.load(
...     'lkt_mt.nam', exe_name='mt3d-usgs_1.0.00.exe',
...     model_ws=datadir, load_only='btn')
>>> lkt = flopy.mt3d.Mt3dLkt.load('test.lkt', mt)
```

**write\_file()**

Write the package file

**Return type** None

## flopy.mt3d.mtphc module

**class** `Mt3dPhc`(*model, os=2, temp=25, asbin=0, eps\_aqu=0, eps\_ph=0, scr\_output=1, cb\_offset=0, smse=['pH', 'pe'], mine=[], ie=[], surf=[], mobkin=[], minkin=[], surfkin=[], imobkin=[], extension='phc', unitnumber=None, filenames=None*)

Bases: `flopy.pakbase.Package`

PHC package class for PHT3D

**unitnumber** = 38

**write\_file()**

Write the package file

**Return type** None

## flopy.mt3d.mtrct module

**class** `Mt3dRct`(*model, isothm=0, ireact=0, igetsc=1, rhob=None, prsity2=None, srconc=None, sp1=None, sp2=None, rc1=None, rc2=None, extension='rct', unitnumber=None, filenames=None, \*\*kwargs*)

Bases: `flopy.pakbase.Package`

Chemical reaction package class.

**Parameters**

- **model** (*model object*) – The model object (of type `flopy.mt3dms.mt.Mt3dms`) to which this package will be added.

- **isothm** (*int*) – isothm is a flag indicating which type of sorption (or dual-domain mass transfer) is simulated: isothm = 0, no sorption is simulated; isothm = 1, linear isotherm (equilibrium-controlled); isothm = 2, Freundlich isotherm (equilibrium-controlled); isothm = 3, Langmuir isotherm (equilibrium-controlled); isothm = 4, first-order kinetic sorption (nonequilibrium); isothm = 5, dual-domain mass transfer (without sorption); isothm = 6, dual-domain mass transfer (with sorption). (default is 0).
- **ireact** (*int*) – ireact is a flag indicating which type of kinetic rate reaction is simulated: ireact = 0, no kinetic rate reaction is simulated; ireact = 1, first-order irreversible reaction, ireact = 100, zero-order reactions (decay or production). Note that this reaction package is not intended for modeling chemical reactions between species. An add-on reaction package developed specifically for that purpose may be used. (default is 0).
- **igetsc** (*int*) – igetsc is an integer flag indicating whether the initial concentration for the nonequilibrium sorbed or immobile phase of all species should be read when nonequilibrium sorption (isothm = 4) or dual-domain mass transfer (isothm = 5 or 6) is simulated: igetsc = 0, the initial concentration for the sorbed or immobile phase is not read. By default, the sorbed phase is assumed to be in equilibrium with the dissolved phase (isothm = 4), and the immobile domain is assumed to have zero concentration (isothm = 5 or 6). igetsc > 0, the initial concentration for the sorbed phase or immobile liquid phase of all species will be read. (default is 1).
- **rhob** (*float or array of floats (nlay, nrow, ncol)*) – rhob is the bulk density of the aquifer medium (unit, ML-3). rhob is used if isothm = 1, 2, 3, 4, or 6. If rhob is not user-specified and isothm is not 5 then rhob is set to 1.8e3. (default is None)
- **prsty2** (*float or array of floats (nlay, nrow, ncol)*) – prsty2 is the porosity of the immobile domain (the ratio of pore spaces filled with immobile fluids over the bulk volume of the aquifer medium) when the simulation is intended to represent a dual-domain system. prsty2 is used if isothm = 5 or 6. If prsty2 is not user-specified and isothm = 5 or 6 then prsty2 is set to 0.1. (default is None)
- **srconc** (*float or array of floats (nlay, nrow, ncol)*) – srconc is the user-specified initial concentration for the sorbed phase of the first species if isothm = 4 (unit, MM-1). Note that for equilibrium-controlled sorption, the initial concentration for the sorbed phase cannot be specified. srconc is the user-specified initial concentration of the first species for the immobile liquid phase if isothm = 5 or 6 (unit, ML-3). If srconc is not user-specified and isothm = 4, 5, or 6 then srconc is set to 0. (default is None).
- **sp1** (*float or array of floats (nlay, nrow, ncol)*) – sp1 is the first sorption parameter for the first species. The use of sp1 depends on the type of sorption selected (the value of isothm). For linear sorption (isothm = 1) and nonequilibrium sorption (isothm = 4), sp1 is the distribution coefficient (Kd) (unit, L3M-1). For Freundlich sorption (isothm = 2), sp1 is the Freundlich equilibrium constant (Kf) (the unit depends on the Freundlich exponent a). For Langmuir sorption (isothm = 3), sp1 is the Langmuir equilibrium constant (Kl) (unit, L3M-1). For dual-domain mass transfer without sorption (isothm = 5), sp1 is not used, but still must be entered. For dual-domain mass transfer with sorption (isothm = 6), sp1 is also the distribution coefficient (Kd) (unit, L3M-1). If sp1 is not specified and isothm > 0 then sp1 is set to 0. (default is None).
- **sp2** (*float or array of floats (nlay, nrow, ncol)*) – sp2 is the second sorption or dual-domain model parameter for the first species. The use of sp2 depends on the type of sorption or dual-domain model selected. For linear sorption (isothm = 1), sp2 is read but not used. For Freundlich sorption (isothm = 2), sp2 is the Freundlich exponent a. For Langmuir sorption (isothm = 3), sp2 is the total concentration of the sorption sites available (S) (unit, MM-1). For nonequilibrium sorption (isothm = 4), sp2 is the first-order mass transfer rate between the dissolved and sorbed phases (unit,

T-1). For dual-domain mass transfer (isothm = 5 or 6), sp2 is the first-order mass transfer rate between the two domains (unit, T-1). If sp2 is not specified and isothm > 0 then sp2 is set to 0. (default is None).

- **rc1** (*float or array of floats (nlay, nrow, ncol)*) – rc1 is the first-order reaction rate for the dissolved (liquid) phase for the first species (unit, T-1). rc1 is not used ireact = 0. If a dual-domain system is simulated, the reaction rates for the liquid phase in the mobile and immobile domains are assumed to be equal. If rc1 is not specified and ireact > 0 then rc1 is set to 0. (default is None).
- **rc2** (*float or array of floats (nlay, nrow, ncol)*) – rc2 is the first-order reaction rate for the sorbed phase for the first species (unit, T-1). rc2 is not used ireact = 0. If a dual-domain system is simulated, the reaction rates for the sorbed phase in the mobile and immobile domains are assumed to be equal. Generally, if the reaction is radioactive decay, rc2 should be set equal to rc1, while for biodegradation, rc2 may be different from rc1. Note that rc2 is read but not used, if no sorption is included in the simulation. If rc2 is not specified and ireact > 0 then rc2 is set to 0. (default is None).
- **extension** (*string*) – Filename extension (default is 'rct')
- **unitnumber** (*int*) –

**File unit number. If file unit number is None then an unused unit number if used.** (default is None).

- **srconcn** (*float or array of floats (nlay, nrow, ncol)*) – srconcn is the user-specified initial concentration for the sorbed phase of species n. If srconcn is not passed as a **\*\*kwarg** and isothm = 4, 5, or 6 then srconcn for species n is set to 0. See description of srconcn for a more complete description of srconcn.
- **sp1n** (*float or array of floats (nlay, nrow, ncol)*) – sp1n is the first sorption parameter for species n. If sp1n is not passed as a **\*\*kwarg** and isothm > 0 then sp1 for species n is set to 0. See description of sp1 for a more complete description of sp1n.
- **sp2n** (*float or array of floats (nlay, nrow, ncol)*) – sp2n is the second sorption or dual-domain model parameter for species n. If sp2n is not passed as a **\*\*kwarg** and isothm > 0 then sp2 for species n is set to 0. See description of sp2 for a more complete description of sp2n.
- **rc1n** (*float or array of floats (nlay, nrow, ncol)*) – rc1n is the first-order reaction rate for the dissolved (liquid) phase for species n. If rc1n is not passed as a **\*\*kwarg** and ireact > 0 then rc1 for species n is set to 0. See description of rc1 for a more complete description of rc1n.
- **rc2n** (*float or array of floats (nlay, nrow, ncol)*) – rc2n is the first-order reaction rate for the sorbed phase for species n. If rc2n is not passed as a **\*\*kwarg** and ireact > 0 then rc2 for species n is set to 0. See description of rc2 for a more complete description of rc2n.

## Notes

## Examples

```
>>> import flopy
>>> mt = flopy.mt3dms.Mt3dms()
>>> rct = flopy.mt3dms.Mt3dRct(mt)
```

**classmethod** `load(f, model, nlay=None, nrow=None, ncol=None, ncomp=None, ext_unit_dict=None)`  
Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **nlay** (*int*) – Number of model layers in the reaction package. If `nlay` is not specified, the number of layers in the passed model object is used. (default is `None`).
- **nrow** (*int*) – Number of model rows in the reaction package. If `nrow` is not specified, the number of rows in the passed model object is used. (default is `None`).
- **ncol** (*int*) – Number of model columns in the reaction package. If `nlay` is not specified, the number of columns in the passed model object is used. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then `f` should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `rct` – `Mt3dRct` object.

**Return type** `Mt3dRct` object

## Examples

```
>>> import flopy
>>> mt = flopy.mt3d.Mt3dms()
>>> rct = flopy.mt3d.Mt3dRct.load('test.rct', mt)
```

**write\_file()**

Write the package file

**Return type** `None`

## flopY.mt3d.mtsft module

```
class Mt3dSft(model, nsfinit=0, mxsfbc=0, icbcsf=0, ioutobs=0, ietsfr=0, isfsolv=1, wimp=0.5, wups=1.0,
              cclosesf=1e-06, mxitersf=10, crntsf=1.0, iprtxmd=0, coldsf=0.0, dispsf=0.0, nobssf=0,
              obs_sf=None, sf_stress_period_data=None, unitnumber=None, filenames=None, dtype=None,
              extension='sft', **kwargs)
```

Bases: [\*flopY.pakbase.Package\*](#)

MT3D-USGS StreamFlow Transport package class

### Parameters

- **model** (*model object*) – The model object (of type `flopY.mt3dms.mt.Mt3dms`) to which this package will be added.
- **nsfinit** (*int*) – Is the number of simulated stream reaches (in SFR2, the number of stream reaches is greater than or equal to the number of stream segments). This is equal to NSTRM found on the first line of the SFR2 input file. If NSFINIT > 0 then surface-water transport is solved in the stream network while taking into account groundwater exchange and precipitation and evaporation sources and sinks. Otherwise, if NSFINIT < 0, the surface-water network as represented by the SFR2 flow package merely acts as a boundary condition to the groundwater transport problem; transport in the surface-water network is not simulated.
- **mxsfbc** (*int*) – Is the maximum number of stream boundary conditions.
- **icbcsf** (*int*) – Is an integer value that directs MT3D-USGS to write reach-by-reach concentration information to unit ICBCSF.
- **ioutobs** (*int*) – Is the unit number of the output file for simulated concentrations at specified gage locations. The NAM file must also list the unit number to which observation information will be written.
- **ietsfr** (*int*) – Specifies whether or not mass will exit the surface-water network with simulated evaporation. If IETSFR = 0, then mass does not leave via stream evaporation. If IETSFR > 0, then mass is allowed to exit the simulation with the simulated evaporation.
- **isfsolv** (*int*) – Specifies the numerical technique that will be used to solve the transport problem in the surface water network. The first release of MT3D-USGS (version 1.0) only allows for a finite-difference formulation and regardless of what value the user specifies, the variable defaults to 1, meaning the finite-difference solution is invoked.
- **wimp** (*float*) – Is the stream solver time weighting factor. Ranges between 0.0 and 1.0. Values of 0.0, 0.5, or 1.0 correspond to explicit, Crank-Nicolson, and fully implicit schemes, respectively.
- **wups** (*float*) – Is the space weighting factor employed in the stream network solver. Ranges between 0.0 and 1.0. Values of 0.0 and 1.0 correspond to a central-in-space and upstream weighting factors, respectively.
- **cclosesf** (*float*) – Is the closure criterion for the SFT solver
- **mxitersf** (*int*) – Limits the maximum number of iterations the SFT solver can use to find a solution of the stream transport problem.
- **crntsf** (*float*) – Is the Courant constraint specific to the SFT time step, its value has no bearing upon the groundwater transport solution time step.
- **iprtxmd** (*int*) – A flag to print SFT solution information to the standard output file. IPRTXMD = 0 means no SFT solution information is printed; IPRTXMD = 1 means SFT solution summary information is printed at the end of every MT3D-USGS outer



iteration; and IPRTXMD = 2 means SFT solution details are written for each SFT outer iteration that calls the xMD solver that solved SFT equations.

- **coldsf** (*array of floats*) – Represents the initial concentrations in the surface water network. The length of the array is equal to the number of stream reaches and starting concentration values should be entered in the same order that individual reaches are entered for record set 2 in the SFR2 input file. To specify starting concentrations for other species in a multi-species simulation, include additional keywords, such as coldsf2, coldsf3, and so forth.
- **dispsf** (*array of floats*) – Is the dispersion coefficient [L<sup>2</sup> T<sup>-1</sup>] for each stream reach in the simulation and can vary for each simulated component of the simulation. That is, the length of the array is equal to the number of simulated stream reaches times the number of simulated components. Values of dispersion for each reach should be entered in the same order that individual reaches are entered for record set 2 in the SFR2 input file. To specify dispsf for other species in a multi-species simulation, include additional keywords, such as dispsf2, dispsf3, and so forth.
- **nobssf** (*int*) – Specifies the number of surface flow observation points for monitoring simulated concentrations in streams.
- **isobs** (*int*) – The segment number for each stream flow concentration observation point.
- **irobs** (*int*) – The reach number for each stream flow concentration observation point.
- **ntmp** (*int*) – The number of specified stream boundary conditions to follow. For the first stress period, this value must be greater than or equal to zero, but may be less than zero in subsequent stress periods.
- **isegbc** (*int*) – Is the segment number for which the current boundary condition will be applied.
- **irchbc** (*int*) – Is the reach number for which the current boundary condition will be applied.
- **isfbctyp** (*int*) –

Specifies, for ISEGBC/IRCHBC, what the boundary condition type is

**0 A headwater boundary. That is, for streams entering at the** boundary of the simulated domain that need a specified concentration, use ISFBCTYP = 0

**1 a precipitation boundary. If precipitation directly to** channels is simulated in the flow model and a non-zero concentration (default is zero) is desired, use ISFBCTYP = 1

**2 a runoff boundary condition that is not the same thing as** runoff simulated in the UZF1 package and routed to a stream (or lake) using the IRNBND array. Users who specify runoff in the SFR2 input via the RUNOFF variable appearing in either record sets 4b or 6a and want to assign a non-zero concentration (default is zero) associated with this specified source, use ISFBCTYP=2;

**3 a constant-concentration boundary. Any ISEGBC/IRCHBC** combination may set equal to a constant concentration boundary condition.

4 a pumping boundary condition. 5 an evaporation boundary condition. In models where

evaporation is simulated directly from the surface of the channel, users can use this boundary condition to specify a non-zero concentration (default is zero) associated with the evaporation losses.

- **cbscf** (*float*) – Is the specified concentration associated with the current boundary condition entry. Repeat CBCSF for each simulated species (NCOMP).
- **extension** (*string*) – Filename extension (default is 'sft')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the sfr output name will be created using the model name and lake concentration observation extension (for example, modflowtest.cbc and modflowtest.sftcobs.out), if ioutobs is a number greater than zero. If a single string is passed the package will be set to the string and sfr concentration observation output name will be created using the model name and .sftcobs.out extension, if ioutobs is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> datadir = 'examples/data/mt3d_test/mfnwt_mt3dusgs/sft_crnkNic'
>>> mf = flopy.modflow.Modflow.load(
...     'CrnkNic.nam', model_ws=datadir, load_only=['dis', 'bas6'])
>>> sfr = flopy.modflow.ModflowSfr2.load('CrnkNic.sfr2', mf)
>>> chk = sfr.check()
>>> # initialize an MT3D-USGS model
>>> mt = flopy.mt3d.Mt3dms.load(
...     'CrnkNic.mtnam', exe_name='mt3d-usgs_1.0.00.exe',
>>>     model_ws=datadir, load_only='btn')
>>> sft = flopy.mt3d.Mt3dSft.load(mt, 'CrnkNic.sft')
```

**static** `get_default_dtype(ncomp=1)`

Construct a dtype for the recarray containing the list of surface water boundary conditions.

**classmethod** `load(f, model, nsfinit=None, nper=None, ncomp=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **nsfinit** (*int*) – number of simulated stream reaches in the surface-water transport process.
- **isfsolv** (*int*) – Specifies the numerical technique that will be used to solve the transport problem in the surface water network. The first release of MT3D-USGS (version 1.0) only allows for a finite-difference formulation and regardless of what value the user specifies, the variable defaults to 1, meaning the finite-difference solution is invoked.

- **wimp** (*float*) – Is the stream solver time weighting factor. Ranges between 0.0 and 1.0. Values of 0.0, 0.5, or 1.0 correspond to explicit, Crank-Nicolson, and fully implicit schemes, respectively.
- **wups** (*float*) – Is the space weighting factor employed in the stream network solver. Ranges between 0.0 and 1.0. Values of 0.0 and 1.0 correspond to a central-in-space and upstream weighting factors, respectively.
- **cclosesf** (*float*) – Is the closure criterion for the SFT solver
- **mxitersf** (*int*) – Limits the maximum number of iterations the SFT solver can use to find a solution of the stream transport problem.
- **crnts** (*float*) – Is the Courant constraint specific to the SFT time step, its value has no bearing upon the groundwater transport solution time step.
- **iprtxmd** (*int*) – a flag to print SFT solution information to the standard output file. IPRTXMD can equal 0, 1, or 2, and will write increasing amounts of solver information to the standard output file, respectively.

**Returns** **sft** – MT3D-USGS object

**Return type** MT3D-USGS object

### Examples

```
>>> import os
>>> import flopy
>>> mf = flopy.modflow.Modflow.load('CrnkNic_mf.nam',
...                               load_only=['dis', 'bas6'])
>>> sfr = flopy.modflow.ModflowSfr2.load('CrnkNic.sfr2', mf)
>>> mt = flopy.mt3d.Mt3dms.load('CrnkNic_mt.nam', load_only='btn')
>>> sft = flopy.mt3d.Mt3dSft.load('CrnkNic.sft', mt)
```

### write\_file()

Write the package file

**Return type** None

### Examples

```
>>> import flopy
>>> datadir = '.examples/data/mt3d_test/mfnwt_mt3dusgs/sft_crnkNic'
>>> mt = flopy.mt3d.Mt3dms.load(
...     'CrnkNic.mtnam', exe_name='mt3d-usgs_1.0.00.exe',
...     model_ws=datadir, verbose=True)
>>> mt.name = 'CrnkNic_rewrite'
>>> mt.sft.dispsf.fmtin = '(10F12.2)'
>>> mt.write_input()
```

## flop.mt3d.mtssm module

**class** `Mt3dSsm`(*model*, *crch*=None, *cevt*=None, *mxss*=None, *stress\_period\_data*=None, *dtype*=None, *extension*='ssm', *unitnumber*=None, *filenames*=None, *\*\*kwargs*)

Bases: `flop.pakbase.Package`

MT3DMS Source and Sink Mixing Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.mt3d.mt.Mt3dms`) to which this package will be added.
- **crch** (*Transient2d, scalar, array of floats, or dictionary*) – CRCH is the concentration of recharge for species 1. If the recharge flux is positive, it acts as a source whose concentration can be specified as desired. If the recharge flux is negative, it acts as a sink (discharge) whose concentration is always set equal to the concentration of groundwater at the cell where discharge occurs. Note that the location and flow rate of recharge/discharge are obtained from the flow model directly through the unformatted flow-transport link file. *crch* can be specified as an array, if the array is constant for the entire simulation. If *crch* changes by stress period, then the user must provide a dictionary, where the key is the stress period number (zero based) and the value is the recharge array. The recharge concentration can be specified for additional species by passing additional arguments to the `Mt3dSsm` constructor. For example, to specify the recharge concentration for species two one could use `crch2={0: 0., 1: 10*np.ones((nrow, ncol), dtype=float)}` as and additional keyword argument that is passed to `Mt3dSsm` when making the `ssm` object.
- **cevt** (*Transient2d, scalar, array of floats, or dictionary*) – is the concentration of evapotranspiration flux for species 1. Evapotranspiration is the only type of sink whose concentration may be specified externally. Note that the concentration of a sink cannot be greater than that of the aquifer at the sink cell. Thus, if the sink concentration is specified greater than that of the aquifer, it is automatically set equal to the concentration of the aquifer. Also note that the location and flow rate of evapotranspiration are obtained from the flow model directly through the unformatted flow-transport link file. For multi-species simulations, see *crch* for a description of how to specify additional concentrations arrays for each species.
- **stress\_period\_data** (*dictionary*) – Keys in the dictionary are stress zero-based stress period numbers; values in the dictionary are recarrays of SSM boundaries. The dtype for the recarray can be obtained using `ssm.dtype` (after the `ssm` package has been created). The default dtype for the recarray is `np.dtype([('k', int), ('i', int), ('j', int), ('css', np.float32), ('itype', int), ((cssms(n), float), n=1, ncomp)])`. If there are more than one component species, then additional entries will be added to the dtype as indicated by `cssm(n)`. Note that if the number of dictionary entries is less than the number of stress periods, then the last recarray of boundaries will apply until the end of the simulation. Full details of all options to specify *stress\_period\_data* can be found in the `flop3_multi-component_SSM` ipython notebook in the Notebook subdirectory of the examples directory. *css* is the specified source concentration or mass-loading rate, depending on the value of *ITYPE*, in a single-species simulation, (For a multispecies simulation, *CSS* is not used, but a dummy value still needs to be entered here.) Note that for most types of sources, *CSS* is interpreted as the source concentration with the unit of mass per unit volume (ML-3), which, when multiplied by its corresponding flow rate (L3T-1) from the flow model, yields the mass-loading rate (MT-1) of the source. For a special type of sources (*ITYPE* = 15), *CSS* is taken directly as the mass-loading rate (MT-1) of the source so that no flow rate is required from the flow model. Furthermore, if the source is specified as a constant-concentration cell (*itype* = -1), the specified value of *CSS* is

assigned directly as the concentration of the designated cell. If the designated cell is also associated with a sink/source term in the flow model, the flow rate is not used. `itype` is an integer indicating the type of the point source. An `itype` dictionary can be retrieved from the `ssm` object as `itype = mt3d.Mt3dSsm.itype_dict()` (`CSSMS(n)`, `n=1`, `NCOMP`) defines the concentrations of a point source for multispecies simulation with `NCOMP>1`. In a multispecies simulation, it is necessary to define the concentrations of all species associated with a point source. As an example, if a chemical of a certain species is injected into a multispecies system, the concentration of that species is assigned a value greater than zero while the concentrations of all other species are assigned zero. `CSSMS(n)` can be entered in free format, separated by a comma or space between values. Several important notes on assigning concentration for the constant-concentration condition (`ITYPE = -1`) are listed below: The constant-concentration condition defined in this input file takes precedence to that defined in the Basic Transport Package input file. In a multiple stress period simulation, a constant-concentration cell, once defined, will remain a constant-concentration cell in the duration of the simulation, but its concentration value can be specified to vary in different stress periods. In a multispecies simulation, if it is only necessary to define different constant-concentration conditions for selected species at the same cell location, specify the desired concentrations for those species, and assign a negative value for all other species. The negative value is a flag used by `MT3DMS` to skip assigning the constant-concentration condition for the designated species.

- **dtype** (*np.dtype*) – dtype to use for the recarray of boundaries. If left as `None` (the default) then the dtype will be automatically constructed.
- **extension** (*string*) – Filename extension (default is 'ssm')
- **unitnumber** (*int*) – File unit number (default is `None`).
- **filenames** (*str or list of str*) – Filenames to use for the package. If `filenames=None` the package name will be created using the model name and package extension. If a single string is passed the package will be set to the string. Default is `None`.

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.mt3d.Mt3dms()
>>> itype = mt3d.Mt3dSsm.itype_dict()
>>> ssm_data = {}
>>> ssm_data[0] = [(4, 4, 4, 1.0, itype['GHB'], 1.0, 100.0)]
>>> ssm_data[5] = [(4, 4, 4, 0.5, itype['GHB'], 0.5, 200.0)]
>>> ssm = flopy.mt3d.Mt3dSsm(m, stress_period_data=ssm_data)
```

**from\_package**(*package, ncomp\_aux\_names*)

read the point source and sink info from a package `ncomp_aux_names` (list): the aux variable names in the package that are the component concentrations

**static get\_default\_dtype**(*ncomp=1*)

Construct a dtype for the recarray containing the list of sources and sinks

**static itype\_dict**()

**classmethod** `load(f, model, nlay=None, nrow=None, ncol=None, nper=None, ncomp=None, ext_unit_dict=None)`

Load an existing package.

**Parameters**

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.mt.Mt3dms`) to which this package will be added.
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `ssm` – `Mt3dSsm` object.

**Return type** `Mt3dSsm` object

**Examples**

```
>>> import flopy
>>> mt = flopy.mt3d.Mt3dms()
>>> ssm = flopy.mt3d.Mt3dSsm.load('test.ssm', mt)
```

**write\_file()**

Write the package file

**Return type** `None`

**class** `SsmPackage(label="", instance=None, needTFstr=False)`

Bases: `object`

**flopy.mt3d.mttob module**

**class** `Mt3dTob(model, outnam='tob_output', CScale=1.0, FluxGroups=[], FScale=1.0, iOutFlux=0, extension='tob', unitnumber=None, filenames=None)`

Bases: `flopy.pakbase.Package`

Transport Observation package class

**write\_file()**

Write the package file

**Return type** `None`

**flopY.mt3d.mtuzt module**

**class Mt3dUzt**(*model*, *icbcuz*=None, *iet*=0, *iuzfbnd*=None, *cuzinf*=None, *cuzet*=None, *cgwet*=None, *extension*='uzt', *unitnumber*=None, *filenames*=None, *\*\*kwargs*)

Bases: [flopY.pakbase.Package](#)

MT3D-USGS Unsaturated-Zone Transport package class

**Parameters**

- **model** (*model object*) – The model object (of type `flopY.mt3dms.mt.Mt3dms`) to which this package will be added.
- **icbcuz** (*int*) – Is the unit number to which unsaturated-zone concentration will be written out.
- **iet** (*int*) – Is a flag that indicates whether or not ET is being simulated in the UZF1 flow package (=0 indicates that ET is not being simulated). If ET is not being simulated, IET informs FMI package not to look for UZET and GWET arrays in the flow-transport link file.
- **iuzfbnd** (*array of ints*) – Specifies which row/column indices variably-saturated transport will be simulated in.
 

>0 indicates variably-saturated transport will be simulated; =0 indicates variably-saturated transport will not be simulated; <0 Corresponds to IUZF-BND < 0 in the UZF1 input package, meaning

that user-supplied values for FINF are specified recharge and therefore transport through the unsaturated zone is not simulated.
- **incuzinf** (*int*) – (This value is repeated for each stress period as explained next) A flag indicating whether an array containing the concentration of infiltrating water (FINF) for each simulated species (ncomp) will be read for the current stress period. If INCUZINF >= 0, an array containing the concentration of infiltrating flux for each species will be read. If INCUZINF < 0, the concentration of infiltrating flux will be reused from the previous stress period. If INCUZINF < 0 is specified for the first stress period, then by default the concentration of positive infiltrating flux (source) is set equal to zero. There is no possibility of a negative infiltration flux being specified. If infiltrating water is rejected due to an infiltration rate exceeding the vertical hydraulic conductivity, or because saturation is reached in the unsaturated zone and the water table is therefore at land surface, the concentration of the runoff will be equal to CUZINF specified next. The runoff is routed if IRNBND is specified in the MODFLOW simulation.
- **cuzinf** (*array of floats*) – Is the concentration of the infiltrating flux for a particular species. An array for each species will be read.
- **incuzet** (*int*) – (This value is repeated for each stress period as explained next) A flag indicating whether an array containing the concentration of evapotranspiration flux originating from the unsaturated zone will be read for the current stress period. If INCUZET >= 0, an array containing the concentration of evapotranspiration flux originating from the unsaturated zone for each species will be read. If INCUZET < 0, the concentration of evapotranspiration flux for each species will be reused from the last stress period. If INCUZET < 0 is specified for the first stress period, then by default, the concentration of negative evapotranspiration flux (sink) is set equal to the aquifer concentration, while the concentration of positive evapotranspiration flux (source) is set to zero.
- **cuzet** (*array of floats*) – Is the concentration of ET fluxes originating from the unsaturated zone. As a default, this array is set equal to 0 and only overridden if the user specifies INCUZET > 1. If empirical evidence suggest volatilization of simulated

constituents from the unsaturated zone, this may be one mechanism for simulating this process, though it would depend on the amount of simulated ET originating from the unsaturated zone. An array for each species will be read.

- **incgwet** (*int*) – (This value is repeated for each stress period as explained next) Is a flag indicating whether an array containing the concentration of evapotranspiration flux originating from the saturated zone will be read for the current stress period. If INCGWET  $\geq 0$ , an array containing the concentration of evapotranspiration flux originating from the saturated zone for each species will be read. If INCGWET  $< 0$ , the concentration of evapotranspiration flux for each species will be reused from the last stress period. If INCUZET  $< 0$  is specified for the first stress period, then by default, the concentration of negative evapotranspiration flux (sink) is set to the aquifer concentration, while the concentration of positive evapotranspiration flux (source) is set to zero.
- **cgwet** (*array of floats*) – Is the concentration of ET fluxes originating from the saturated zone. As a default, this array is set equal to 0 and only overridden if the user specifies INCUZET  $> 1$ . An array for each species will be read.
- **extension** (*string*) – Filename extension (default is 'uzt')
- **unitnumber** (*int*) – File unit number (default is None).
- **filenames** (*str or list of str*) – Filenames to use for the package and the output files. If filenames=None the package name will be created using the model name and package extension and the uzf output name will be created using the model name and uzf concentration observation extension (for example, modflowtest.cbc and modflowtest.uzcobs.out), if icbcuz is a number greater than zero. If a single string is passed the package will be set to the string and uzf concentration observation output name will be created using the model name and .uzcobs.out extension, if icbcuz is a number greater than zero. To define the names for all package files (input and output) the length of the list of strings should be 2. Default is None.

## Notes

Parameters are not supported in FloPy.

## Examples

```
>>> import flopy
>>> datadir = 'examples/data/mt3d_test/mfnwt_mt3dusgs/keat_uzf'
>>> mt = flopy.mt3d.Mt3dms.load(
...     'Keat_UZF_mt.nam', exe_name='mt3d-usgs_1.0.00.exe',
...     model_ws=datadir, load_only='btn')
>>> uzt = flopy.mt3d.Mt3dUzt('Keat_UZF.uzt', mt)
```

**classmethod load**(*f, model, nlay=None, nrow=None, ncol=None, nper=None, ncomp=None, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.mt3d.Mt3dms`) to which this package will be added.



- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopY.utils.mfreadnam.parsenamefile`.

**Returns** `uzt` – `Mt3dUzt` object.

**Return type** `Mt3dSsm` object

## Examples

```
>>> import flopY
>>> mt = flopY.mt3d.Mt3dms()
>>> uzt = flopY.mt3d.Mt3dUzt.load('test.uzt', mt)
```

### `write_file()`

Write the package file

**Return type** `None`

## SEAWAT Packages

Contents:

### `flopY.seawat.swt` module

```
class Seawat(modelname='swttest', namefile_ext='nam', modflowmodel=None, mt3dmodel=None,  
             version='seawat', exe_name='swtv4', structured=True, listunit=2, model_ws='.',  
             external_path=None, verbose=False, load=True, silent=0)
```

Bases: `flopY.mbase.BaseModel`

SEAWAT Model Class.

#### Parameters

- **modelname** (*str, default "swttest"*) – Name of model. This string will be used to name the SEAWAT input that are created with `write_model`.
- **namefile\_ext** (*str, default "nam"*) – Extension for the namefile.
- **modflowmodel** (`Modflow`, *default None*) – Instance of a Modflow object.
- **mt3dmodel** (`Mt3dms`, *default None*) – Instance of a `Mt3dms` object.
- **version** (*str, default "seawat"*) – Version of SEAWAT to use. Valid versions are “seawat” (default).
- **exe\_name** (*str, default "swtv4"*) – The name of the executable to use.
- **structured** (*bool, default True*) – Specify if model grid is structured (default) or unstructured.
- **listunit** (*int, default 2*) – Unit number for the list file.
- **model\_ws** (*str, default "."*) – Model workspace. Directory name to create model data sets. Default is the present working directory.
- **external\_path** (*str, optional*) – Location for external files.
- **verbose** (*bool, default False*) – Print additional information to the screen.

- **load** (*bool*, *default* *True*) – Load model.
- **silent** (*int*, *default* *0*) – Silent option.

## Notes

## Examples

```
>>> import flop
>>> m = flop.seawat.swt.Seawat()
```

**change\_model\_ws** (*new\_pth=None*, *reset\_external=False*)

Change the model work space.

**Parameters** **new\_pth** (*str*) – Location of new model workspace. If this path does not exist, it will be created. (default is *None*, which will be assigned to the present working directory).

**Returns** **val** – Can be used to see what packages are in the model, and can then be used with **get\_package** to pull out individual packages.

**Return type** list of strings

**get\_ifrefm**()

**get\_nrow\_ncol\_nlay\_nper**()

**classmethod** **load** (*f*, *version='seawat'*, *exe\_name='swtv4'*, *verbose=False*, *model\_ws='.'*, *load\_only=None*)

Load an existing model.

### Parameters

- **f** (*str*) – Path to SEAWAT name file to load.
- **version** (*str*, *default* *"seawat"*) – Version of SEAWAT to use. Valid versions are “seawat” (default).
- **exe\_name** (*str*, *default* *"swtv4"*) – The name of the executable to use.
- **verbose** (*bool*, *default* *False*) – Print additional information to the screen.
- **model\_ws** (*str*, *default* *"."*) – Model workspace. Directory name to create model data sets. Default is the present working directory.
- **load\_only** (*list of str*, *optional*) – Packages to load (e.g. [“lpf”, “adv”]). Default *None* means that all packages will be loaded.

**Return type** *flop.seawat.swt.Seawat*

## Examples

```
>>> import flop
>>> m = flop.seawat.swt.Seawat.load(f)
```

property **mcomp**

property **modelgrid**

property **modeltime**

property **ncol**

```

property ncomp
property nlay
property nper
property nrow
property nrow_ncol_nlay_nper
write_name_file()
    Write the name file

```

**Return type** None

```

class SeawatList(model, extension='list', listunit=7)
    Bases: flop.pakbase.Package
    List Package class
    write_file()
        Every Package needs its own write_file function

```

### [flop.seawat.swtvdf module](#)

```

class SeawatVdf(model, mtdnconc=1, mfnadvfd=1, nswtcpl=1, iwtbl=1, densemin=0, densemax=0,
    dnscrit=0.01, denseref=1.0, denseslp=0.025, crhoref=0, firstdt=0.001, indense=1, dense=1.0,
    nsrhoeos=1, drhodprhd=0.00446, prhdref=0.0, extension='vdf', unitnumber=None,
    filenames=None, **kwargs)
    Bases: flop.pakbase.Package
    SEAWAT Variable-Density Flow Package Class.
    Parameters

```

- **model** (*model object*) – The model object (of type [flop.seawat.swt.Seawat](#)) to which this package will be added.
- **mt3drhoflg** (*mtdnconc (or)*) – is the MT3DMS species number that will be used in the equation of state to compute fluid density. This input variable was formerly referred to as MTDNCONC (Langevin and others, 2003). If MT3DRHOFLG = 0, fluid density is specified using items 6 and 7, and flow will be uncoupled with transport if the IMT Process is active. If MT3DRHOFLG > 0, fluid density is calculated using the MT3DMS species number that corresponds with MT3DRHOFLG. A value for MT3DRHOFLG greater than zero indicates that flow will be coupled with transport. If MT3DRHOFLG = -1, fluid density is calculated using one or more MT3DMS species. Items 4a, 4b, and 4c will be read instead of item 4. The dependence of fluid density on pressure head can only be activated when MT3DRHOFLG = -1. A value for MT3DRHOFLG of -1 indicates that flow will be coupled with transport.
- **mfnadvfd** (*int*) – is a flag that determines the method for calculating the internodal density values used to conserve fluid mass. If MFNADVFD = 2, internodal conductance values used to conserve fluid mass are calculated using a central-in-space algorithm. If MFNADVFD <> 2, internodal conductance values used to conserve fluid mass are calculated using an upstream-weighted algorithm.
- **nswtcpl** (*int*) – is a flag used to determine the flow and transport coupling procedure. If NSWTCPL = 0 or 1, flow and transport will be explicitly coupled using a one-timestep lag. The explicit coupling option is normally much faster than the iterative option and is recommended for most applications. If NSWTCPL > 1, NSWTCPL is the maximum

number of non-linear coupling iterations for the flow and transport solutions. SEAWAT-2000 will stop execution after NSWTCPL iterations if convergence between flow and transport has not occurred. If NSWTCPL = -1, the flow solution will be recalculated only for: The first transport step of the simulation, or The last transport step of the MODFLOW timestep, or The maximum density change at a cell is greater than DNSCRIT.

- **iwtable** (*int*) – is a flag used to activate the variable-density water-table corrections (Guo and Langevin, 2002, eq. 82). If IWTABLE = 0, the water-table correction will not be applied. If IWTABLE > 0, the water-table correction will be applied.
- **densem** (*float*) – is the minimum fluid density. If the resulting density value calculated with the equation of state is less than DENSEMIN, the density value is set to DENSEMIN. If DENSEMIN = 0, the computed fluid density is not limited by DENSEMIN (this is the option to use for most simulations). If DENSEMIN > 0, a computed fluid density less than DENSEMIN is automatically reset to DENSEMIN.
- **densem** (*float*) – is the maximum fluid density. If the resulting density value calculated with the equation of state is greater than DENSEMAX, the density value is set to DENSEMAX. If DENSEMAX = 0, the computed fluid density is not limited by DENSEMAX (this is the option to use for most simulations). If DENSEMAX > 0, a computed fluid density larger than DENSEMAX is automatically reset to DENSEMAX.
- **dnscrit** (*float*) – is a user-specified density value. If NSWTCPL is greater than 1, DNSCRIT is the convergence criterion, in units of fluid density, for convergence between flow and transport. If the maximum fluid density difference between two consecutive implicit coupling iterations is not less than DNSCRIT, the program will continue to iterate on the flow and transport equations, or will terminate if NSWTCPL is reached. If NSWTCPL is -1, DNSCRIT is the maximum density threshold, in units of fluid density. If the fluid density change (between the present transport timestep and the last flow solution) at one or more cells is greater than DNSCRIT, then SEAWAT\_V4 will update the flow field (by solving the flow equation with the updated density field).
- **denseref** (*float*) – is the fluid density at the reference concentration, temperature, and pressure. For most simulations, DENSEREF is specified as the density of freshwater at 25 degrees C and at a reference pressure of zero.
- **drhodc** (*float*) – formerly referred to as DENSESLP (Langevin and others, 2003), is the slope of the linear equation of state that relates fluid density to solute concentration. In SEAWAT\_V4, separate values for DRHODC can be entered for as many MT3DMS species as desired. If DRHODC is not specified for a species, then that species does not affect fluid density. Any measurement unit can be used for solute concentration, provided DENSEREF and DRHODC are set properly. DRHODC can be approximated by the user by dividing the density difference over the range of end-member fluids by the difference in concentration between the end-member fluids.
- **drhodprhd** (*float*) – is the slope of the linear equation of state that relates fluid density to the height of the pressure head (in terms of the reference density). Note that DRHODPRHD can be calculated from the volumetric expansion coefficient for pressure using equation 15. If the simulation is formulated in terms of kilograms and meters, DRHODPRHD has an approximate value of  $4.46 \times 10^{-3} \text{ kg/m}^4$ . A value of zero, which is typically used for most problems, inactivates the dependence of fluid density on pressure.
- **prhdref** (*float*) – is the reference pressure head. This value should normally be set to zero.
- **nsrhoeos** (*int*) – is the number of MT3DMS species to be used in the equation of state for fluid density. This value is read only if MT3DRHOFLG = -1.

- **mtrhospec** (*int*) – is the MT3DMS species number corresponding to the adjacent DRHODC and CRHOREF.
- **crhoref** (*float*) – is the reference concentration (C0) for species, MTRHOSPEC. For most simulations, CRHOREF should be specified as zero. If MT3DRHOFLG > 0, CRHOREF is assumed to equal zero (as was done in previous versions of SEAWAT).
- **firstdt** (*float*) – is the length of the first transport timestep used to start the simulation if both of the following two conditions are met: 1. The IMT Process is active, and 2. transport timesteps are calculated as a function of the user-specified Courant number (the MT3DMS input variable, PERCEL, is greater than zero).
- **indense** (*int*) – is a flag. INDENSE is read only if MT3DRHOFLG is equal to zero. If INDENSE < 0, values for the DENSE array will be reused from the previous stress period. If it is the first stress period, values for the DENSE array will be set to DENSEREF. If INDENSE = 0, values for the DENSE array will be set to DENSEREF. If INDENSE >= 1, values for the DENSE array will be read from item 7. If INDENSE = 2, values read for the DENSE array are assumed to represent solute concentration, and will be converted to density values using the equation of state.
- **dense** (*Transient3d*) – A float or array of floats (nlay, nrow, ncol) should be assigned as values to a dictionary related to keys of period number. dense is the fluid density array read for each layer using the MODFLOW-2000 U2DREL array reader. The DENSE array is read only if MT3DRHOFLG is equal to zero. The DENSE array may also be entered in terms of solute concentration, or any other units, if INDENSE is set to 2 and the constants used in the density equation of state are specified appropriately.
- **extension** (*string*) – Filename extension (default is 'vdf')
- **unitnumber** (*int*) – File unit number (default is 37).

## Notes

In swt\_4 mtdnconc became mt3drhoflg. If the latter one is defined in kwargs, it will overwrite mtdnconc. Same goes for denseslp, which has become drhodc.

When loading an existing SEAWAT model that has DENSE specified as concentrations, the load process will convert those concentrations into density values using the equation of state. This is only relevant when mtdnconc (or mt3drhoflg) is set to zero.

## Examples

```
>>> import flopy
>>> m = flopy.seawat.Seawat()
>>> lpf = flopy.seawat.SeawatVdf(m)
```

**classmethod load**(*f, model, nper=None, ext\_unit\_dict=None*)

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type *flopy.seawat.swt.Seawat*) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If nper is None, then nper will be obtained from the model object. (default is None).

- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**Returns** `vdf` – SeawatVdf object.

**Return type** SeawatVdf object

### Examples

```
>>> import flop
>>> mf = flop.modflow.Modflow()
>>> dis = flop.modflow.ModflowDis(mf)
>>> mt = flop.mt3d.Mt3dms()
>>> swt = flop.seawat.Seawat(modflowmodel=mf, mt3dmsmodel=mt)
>>> vdf = flop.seawat.SeawatVdf.load('test.vdf', m)
```

**unitnumber** = 37

**write\_file()**

Write the package file

**Return type** None

### flop.seawat.swtvsc module

```
class SeawatVsc(model, mt3dmuflg=- 1, viscmmin=0.0, viscmmax=0.0, viscref=0.0008904, nsmueos=0,
mutempopt=2, mtmuspec=1, dmudc=1.923e-06, cmuref=0.0, mtmutempspec=1,
amucoeff=None, invisc=- 1, visc=- 1, extension='vsc', unitnumber=None, filenames=None,
**kwargs)
```

Bases: `flop.pakbase.Package`

SEAWAT Viscosity Package Class.

#### Parameters

- **model** (*model object*) – The model object (of type `flop.seawat.swt.Seawat`) to which this package will be added.
- **mt3drhoflg** (*mt3dmuflg (or)*) – is the MT3DMS species number that will be used in the equation to compute fluid viscosity. If `MT3DMUFLG`  $\geq 0$ , fluid density is calculated using the MT3DMS species number that corresponds with `MT3DMUFLG`. If `MT3DMUFLG` = -1, fluid viscosity is calculated using one or more MT3DMS species.
- **viscmmin** (*float*) – is the minimum fluid viscosity. If the resulting viscosity value calculated with the equation is less than `VISCMIN`, the viscosity value is set to `VISCMIN`. If `VISCMIN` = 0, the computed fluid viscosity is not limited by `VISCMIN` (this is the option to use for most simulations). If `VISCMIN` > 0, a computed fluid viscosity less than `VISCMIN` is automatically reset to `VISCMIN`.
- **viscmmax** (*float*) – is the maximum fluid viscosity. If the resulting viscosity value calculated with the equation is greater than `VISCMAX`, the viscosity value is set to `VISCMAX`. If `VISCMAX` = 0, the computed fluid viscosity is not limited by `VISCMAX` (this is the option to use for most simulations). If `VISCMAX` > 0, a computed fluid viscosity larger than `VISCMAX` is automatically reset to `VISCMAX`.

- **visceref** (*float*) – is the fluid viscosity at the reference concentration and reference temperature. For most simulations, VISCREF is specified as the viscosity of freshwater.
- **dmudc** (*float, or list of floats (of size nsmueos) if nsmueos > 1*) – is the slope of the linear equation that relates fluid viscosity to solute concentration.
- **nmueos** (*int*) – is the number of MT3DMS species to be used in the linear equation for fluid viscosity (this number does not include the temperature species if the nonlinear option is being used). This value is read only if MT3DMUFLG = -1. A value of zero indicates that none of the MT3DMS species have a linear effect on fluid viscosity (the nonlinear temperature dependence may still be activated); nothing should be entered for item 3c in this case.
- **mutempopt** (*int*) – is a flag that specifies the option for including the effect of temperature on fluid viscosity. If MUTEMPOPT = 0, the effect of temperature on fluid viscosity is not included or is a simple linear relation that is specified in item 3c. If MUTEMPOPT = 1, fluid viscosity is calculated using equation 18. The size of the AMUCOEFF array in item 3e is 4 (MUNCOEFF = 4). If MUTEMPOPT = 2, fluid viscosity is calculated using equation 19. The size of the AMUCOEFF array in item 3e is 5 (MUNCOEFF = 5). If MUTEMPOPT = 3, fluid viscosity is calculated using equation 20. The size of the AMUCOEFF array in item 3e is 2 (MUNCOEFF = 2). If NSMUEOS and MUTEMPOPT are both set to zero, all fluid viscosities are set to VISCREF.
- **mtmuspec** (*int, or list of ints (of size nsmueos) if nsmueos > 1*) – is the MT3DMS species number corresponding to the adjacent DMUDC and CMUREF.
- **dmudc** – is the slope of the linear equation that relates fluid viscosity to solute concentration.
- **cmuref** (*float, or list of floats (of size nsmueos) if nsmueos > 1*) – is the reference concentration.
- **mtmuspectemp** (*int*) – is the MT3DMS species number that corresponds to temperature. This value must be between 1 and NCOMP and should not be listed in MTMUSPEC of item 3c.
- **amucoeff** (*float*) – is the coefficient array of size MUNCOEFF. AMUCOEFF is A in equations 18, 19, and 20.
- **muncoeff** (*int*) – is the size of the AMUCOEFF array.
- **invisc** (*int*) – is a flag. INVISC is read only if MT3DMUFLG is equal to zero. If INVISC < 0, values for the VISC array will be reused from the previous stress period. If it is the first stress period, values for the VISC array will be set to VISCREF. If INVISC = 0, values for the VISC array will be set to VISCREF. If INVISC >= 1, values for the VISC array will be read from item 5. If INVISC = 2, values read for the VISC array are assumed to represent solute concentration, and will be converted to viscosity values.
- **visc** (*float or array of floats (nlay, nrow, ncol)*) – is the fluid viscosity array read for each layer using the MODFLOW-2000 U2DREL array reader. The VISC array is read only if MT3DMUFLG is equal to zero. The VISC array may also be entered in terms of solute concentration (or any other units) if INVISC is set to 2, and the simple linear expression in item 3 can be used to represent the relation to viscosity.
- **extension** (*string*) – Filename extension (default is 'vsc')
- **unitnumber** (*int*) – File unit number (default is 38).

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.seawat.Seawat()
>>> vsc = flopy.modflow.SeawatVsc(m)
```

**classmethod** `load(f, model, nper=None, ext_unit_dict=None)`

Load an existing package.

### Parameters

- **f** (*filename or file handle*) – File to load.
- **model** (*model object*) – The model object (of type `flopy.seawat.swt.Seawat`) to which this package will be added.
- **nper** (*int*) – The number of stress periods. If `nper` is `None`, then `nper` will be obtained from the model object. (default is `None`).
- **ext\_unit\_dict** (*dictionary, optional*) – If the arrays in the file are specified using EXTERNAL, or older style array control records, then *f* should be a file handle. In this case `ext_unit_dict` is required, which can be constructed using the function `flopy.utils.mfreadnam.parsenamefile`.

**Returns** `vsc` – SeawatVsc object.

**Return type** SeawatVsc object

## Examples

```
>>> import flopy
>>> mf = flopy.modflow.Modflow()
>>> dis = flopy.modflow.ModflowDis(mf)
>>> mt = flopy.mt3d.Mt3dms()
>>> swt = flopy.seawat.Seawat(modflowmodel=mf, mt3dmsmodel=mt)
>>> vdf = flopy.seawat.SeawatVsc.load('test.vsc', m)
```

**unitnumber** = 38

**write\_file()**

Write the package file

**Return type** `None`

## MODPATH 7 Packages

Contents:



## flop.modpath.mp7 module

mp7 module. Contains the Modpath7List and Modpath7 classes.

```
class Modpath7 (modelname='modpath7test', simfile_ext='mpsim', namefile_ext='mpnam', version='modpath7',
                exe_name='mp7.exe', flowmodel=None, headfilename=None, budgetfilename=None,
                model_ws=None, verbose=False)
```

Bases: [flop.mbase.BaseModel](#)

Modpath 7 class.

### Parameters

- **modelname** (*str*, *default "modpath7test"*) – Basename for MODPATH 7 input and output files.
- **simfile\_ext** (*str*, *default "mpsim"*) – Filename extension of the MODPATH 7 simulation file.
- **namefile\_ext** (*str*, *default mpnam"*) – Filename extension of the MODPATH 7 namefile.
- **version** (*str*, *default "modpath7"*) – String that defines the MODPATH version. Valid versions are “modpath7” (default).
- **exe\_name** (*str*, *default "mp7.exe"*) – The name of the executable to use.
- **flowmodel** (*flop.modflow.Modflow or flop.mf6.MFModel object*) – MODFLOW model object.
- **headfilename** (*str*, *optional*) – Filename of the MODFLOW output head file. If headfilename is not provided then it will be set from the flowmodel.
- **budgetfilename** (*str*, *optional*) – Filename of the MODFLOW output cell-by-cell budget file. If budgetfilename is not provided then it will be set from the flowmodel.
- **model\_ws** (*str*, *default "."*) – Model workspace. Directory name to create model data sets. Default is the current working directory.
- **verbose** (*bool*, *default False*) – Print additional information to the screen.

### Examples

```
>>> import flop
>>> m = flop.modflow.Modflow.load('mf2005.nam')
>>> mp = flop.modpath.Modpath7('mf2005_mp', flowmodel=m)
```

```
classmethod create_mp7 (modelname='modpath7test', trackdir='forward', flowmodel=None,
                        exe_name='mp7', model_ws='.', verbose=False, columncelldivisions=2,
                        rowcelldivisions=2, layercelldivisions=2, nodes=None)
```

Create a default MODPATH 7 model using a passed flowmodel with 8 particles in user-specified node locations or every active model cell.

### Parameters

- **modelname** (*str*) – Basename for MODPATH 7 input and output files (default is ‘modpath7test’).
- **trackdir** (*str*) – Keyword that defines the MODPATH particle tracking direction. Available trackdir’s are ‘backward’ and ‘forward’. (default is ‘forward’)

- **flowmodel** (*flopY.modflow.Modflow* or *flopY.mf6.MFModel* object) – MODFLOW model
- **exe\_name** (*str*) – The name of the executable to use (the default is 'mp7').
- **model\_ws** (*str*) – model workspace. Directory name to create model data sets. (default is the current working directory).
- **verbose** (*bool*) – Print additional information to the screen (default is False).
- **columncelldivisions** (*int*) – Number of particles in a cell in the column (x-coordinate) direction (default is 2).
- **rowcelldivisions** (*int*) – Number of particles in a cell in the row (y-coordinate) direction (default is 2).
- **layercelldivisions** (*int*) – Number of particles in a cell in the layer (z-coordinate) direction (default is 2).
- **nodes** (*int, list of ints, tuple of ints, or np.ndarray*) – Nodes (zero-based) with particles. If (default is node 0).

**Returns** mp

**Return type** Modpath7 object

### Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('mf2005.nam')
>>> mp = flopY.modpath.Modpath7.create_mp7(flowmodel=m)
```

**property** hdry

**property** hnoflo

**property** laytyp

**write\_name\_file()**

Write the name file

**Return type** None

**class** Modpath7List(*model, extension='list', unitnumber=None*)

Bases: *flopY.pakbase.Package*

List package class

**write\_file()**

Every Package needs its own write\_file function

## flop.modpath.mp7bas module

mp7bas module. Contains the Modpath7Bas class.

**class Modpath7Bas**(*model*, *porosity*=0.3, *defaultiface*=None, *extension*='mpbas')

Bases: [flop.pakbase.Package](#)

MODPATH 7 Basic Package Class.

### Parameters

- **model** (*model object*) – The model object (of type `flop.modpath.Modpath7`) to which this package will be added.
- **porosity** (*float or array of floats (nlay, nrow, ncol)*) – The porosity array (the default is 0.30).
- **defaultiface** (*dict*) – Dictionary with keys that are the text string used by MODFLOW in the budget output file to label flow rates for a stress package and the values are the cell face (iface) on which to assign flows (the default is None).
- **extension** (*str, optional*) – File extension (default is 'mpbas').

## Examples

```
>>> import flop
>>> m = flop.modflow.Modflow.load('mf2005.nam')
>>> mp = flop.modpath.Modpath7('mf2005_mp', flowmodel=m)
>>> mpbas = flop.modpath.Modpath7Bas(mp)
```

**write\_file**(*check*=False)

Write the package file

**Parameters** **check** (*boolean*) – Check package data for common errors. (default False)

**Return type** None

## flop.modpath.mp7particledata module

**mp7particledata module.** Contains the **ParticleData**, **CellDataType**, **FaceDataType**, and **NodeParticleData** classes.

**class CellDataType**(*drape*=0, *columncelldivisions*=3, *rowcelldivisions*=3, *layercelldivisions*=3)

Bases: object

Cell data type class to create a MODPATH 7 particle location template for input style 2, 3, and 4 in cells (templatesubdivisiontype = 2).

### Parameters

- **drape** (*int*) – Drape indicates how particles are treated when starting locations are specified for cells that are dry. If drape is 0, Particles are placed in the specified cell. If the cell is dry at the time of release, the status of the particle is set to unreleased and removed from the simulation. If drape is 1, particles are placed in the upper most active grid cell directly beneath the specified layer, row, column or node location (default is 0).
- **columncelldivisions** (*int*) – Number of particles in a cell in the column (x-coordinate) direction (default is 3).

- **rowcelldivisions** (*int*) – Number of particles in a cell in the row (y-coordinate) direction (default is 3).
- **layercelldivisions** (*int*) – Number of particles in a cell in the layer (z-coordinate) direction (default is 3).

### Examples

```
>>> import floppy
>>> cd = floppy.modpath.CellDataType()
```

```
write(f=None)
```

**Parameters** *f* (*fileobject*) – Fileobject that is open with write access

```
class FaceDataType(drape=0, verticaldivisions1=3, horizontaldivisions1=3, verticaldivisions2=3,
                  horizontaldivisions2=3, verticaldivisions3=3, horizontaldivisions3=3, verticaldivisions4=3,
                  horizontaldivisions4=3, rowdivisions5=3, columndivisions5=3, rowdivisions6=3,
                  columndivisions6=3)
```

Bases: object

Face data type class to create a MODPATH 7 particle location template for input style 2, 3, and 4 on cell faces (templatesubdivisiontype = 2).

#### Parameters

- **drape** (*int*) – Drape indicates how particles are treated when starting locations are specified for cells that are dry. If drape is 0, Particles are placed in the specified cell. If the cell is dry at the time of release, the status of the particle is set to unreleased and removed from the simulation. If drape is 1, particles are placed in the upper most active grid cell directly beneath the specified layer, row, column or node location (default is 0).
- **verticaldivisions1** (*int*) – The number of vertical subdivisions that define the two-dimensional array of particles on cell face 1 (default is 3).
- **horizontaldivisions1** (*int*) – The number of horizontal subdivisions that define the two-dimensional array of particles on cell face 1 (default is 3).
- **verticaldivisions2** (*int*) – The number of vertical subdivisions that define the two-dimensional array of particles on cell face 2 (default is 3).
- **horizontaldivisions2** (*int*) – The number of horizontal subdivisions that define the two-dimensional array of particles on cell face 2 (default is 3).
- **verticaldivisions3** (*int*) – The number of vertical subdivisions that define the two-dimensional array of particles on cell face 3 (default is 3).
- **horizontaldivisions3** (*int*) – The number of horizontal subdivisions that define the two-dimensional array of particles on cell face 3 (default is 3).
- **verticaldivisions4** (*int*) – The number of vertical subdivisions that define the two-dimensional array of particles on cell face 4 (default is 3).
- **horizontaldivisions4** (*int*) – The number of horizontal subdivisions that define the two-dimensional array of particles on cell face 4 (default is 3).
- **rowdivisions5** (*int*) – The number of row subdivisions that define the two-dimensional array of particles on the bottom cell face (face 5) (default is 3).

- **columndivisions5** (*int*) – The number of column subdivisions that define the two-dimensional array of particles on the bottom cell face (face 5) (default is 3).
- **rowdivisions6** (*int*) – The number of row subdivisions that define the two-dimensional array of particles on the top cell face (face 6) (default is 3).
- **columndivisions6** (*int*) – The number of column subdivisions that define the two-dimensional array of particles on the top cell face (face 6) (default is 3).

## Examples

```
>>> import flopy
>>> fd = flopy.modpath.FaceDataType()
```

**write**(*f=None*)

**Parameters** *f* (*fileobject*) – Fileobject that is open with write access

**class LRCParticleData**(*subdivisiondata=None, lrcregions=None*)

Bases: object

Layer, row, column particle data template class to create MODPATH 7 particle location input style 2 on cell faces (templatesubdivisiontype = 1) and/or in cells (templatesubdivisiontype = 2). Particle locations for this template are specified by layer, row, column regions.

### Parameters

- **subdivisiondata** (*FaceDataType, CellDataType or list of FaceDataType*) – and/or CellDataType types FaceDataType, CellDataType, or a list of FaceDataType and/or CellDataTypes that are used to create one or more particle templates in a particle group. If subdivisiondata is None, a default CellDataType with 27 particles per cell will be created (default is None).
- **lrcregions** (*list of lists tuples or np.ndarrays*) – Layer, row, column (zero-based) regions with particles created using the specified template parameters. A region is defined as a list/tuple of minlayer, minrow, mincolumn, maxlayer, maxrow, maxcolumn values. If subdivisiondata is a list, a list/tuple or array of layer, row, column regions with the same length as subdivision data must be provided. If lrcregions is None, particles will be placed in the first model cell (default is None).

## Examples

```
>>> import flopy
>>> pg = flopy.modpath.LRCParticleData(lrcregions=[0, 0, 0, 3, 10, 10])
```

**write**(*f=None*)

**Parameters** *f* (*fileobject*) – Fileobject that is open with write access

**class NodeParticleData**(*subdivisiondata=None, nodes=None*)

Bases: object

Node particle data template class to create MODPATH 7 particle location input style 3 on cell faces (templatesubdivisiontype = 1) and/or in cells (templatesubdivisiontype = 2). Particle locations for this template are specified by nodes.

### Parameters

- **subdivisiondata** (*FaceDataType, CellDataType or list of FaceDataType*) – and/or CellDataType types FaceDataType, CellDataType, or a list of FaceDataType and/or CellDataTypes that are used to create one or more particle templates in a particle group. If subdivisiondata is None, a default CellDataType with 27 particles per cell will be created (default is None).
- **nodes** (*int, list of ints, tuple of ints, or np.ndarray*) – Nodes (zero-based) with particles created using the specified template parameters. If subdivisiondata is a list, a list of nodes with the same length as subdivision data must be provided. If nodes is None, particles will be placed in the first model cell (default is None).

## Examples

```
>>> import flopy
>>> pg = flopy.modpath.NodeParticleData(nodes=[100, 101])
```

```
write(f=None)
```

**Parameters** *f* (*fileobject*) – Fileobject that is open with write access

**class ParticleData**(*partlocs=None, structured=False, particleids=None, localx=None, locally=None, localz=None, timeoffset=None, drape=None*)

Bases: object

Class to create the most basic particle data type (starting location input style 1). Input style 1 is the most general input style and provides the most flexibility in customizing starting locations.

### Parameters

- **partlocs** (*list/tuple of int, list/tuple of list/tuple, or np.ndarray*) – Particle locations (zero-based) that are either layer, row, column locations or nodes.
- **structured** (*bool*) – Boolean defining if a structured (True) or unstructured particle recarray will be created (default is True).
- **particleids** (*list, tuple, or np.ndarray*) – Particle ids for the defined particle locations. If particleids is None, MODPATH 7 will define the particle ids to each particle location. If particleids is provided a particle id must be provided for each partloc (default is None).
- **localx** (*float, list, tuple, or np.ndarray*) – Local x-location of the particle in the cell. If a single value is provided all particles will have the same localx position. If a list, tuple, or np.ndarray is provided a localx position must be provided for each partloc. If localx is None, a value of 0.5 (center of the cell) will be used (default is None).
- **locally** (*float, list, tuple, or np.ndarray*) – Local y-location of the particle in the cell. If a single value is provided all particles will have the same locally position. If a list, tuple, or np.ndarray is provided a locally position must be provided for each partloc. If locally is None, a value of 0.5 (center of the cell) will be used (default is None).
- **localz** (*float, list, tuple, or np.ndarray*) – Local z-location of the particle in the cell. If a single value is provided all particles will have the same localz position. If a list, tuple, or np.ndarray is provided a localz position must be provided for each partloc. If locally is None, a value of 0.5 (center of the cell) will be used (default is None).
- **timeoffset** (*float, list, tuple, or np.ndarray*) – Timeoffset of the particle relative to the release time. If a single value is provided all particles will have the same

timeoffset. If a list, tuple, or np.ndarray is provided a timeoffset must be provided for each partloc. If timeoffset is None, a value of 0. (equal to the release time) will be used (default is None).

- **drape** (*int, list, tuple, or np.ndarray*) – Drape indicates how particles are treated when starting locations are specified for cells that are dry. If drape is 0, Particles are placed in the specified cell. If the cell is dry at the time of release, the status of the particle is set to unreleased and removed from the simulation. If drape is 1, particles are placed in the upper most active grid cell directly beneath the specified layer, row, column or node location. If a single value is provided all particles will have the same drape value. If a list, tuple, or np.ndarray is provided a drape value must be provided for each partloc. If drape is None, a value of 0 will be used (default is None).

## Examples

```
>>> import floppy
>>> locs = [(0, 0, 0), (1, 0, 0), (2, 0, 0)]
>>> pd = floppy.modpath.ParticleData(locs, structured=True, drape=0,
...                                localx=0.5, localy=0.5, localz=1)
```

```
write(f=None)
```

**Parameters** *f* (*fileobject*) – Fileobject that is open with write access

## flopy.modpath.mp7particlegroup module

**mp7particlegroup module.** Contains the **ParticleGroup**, and **ParticleGroupNodeTemplate** classes.

**class ParticleGroup**(*particlegroupname='PG1', filename=None, releasedata=0.0, particledata=None*)

Bases: `flopy.modpath.mp7particlegroup._Modpath7ParticleGroup`

ParticleGroup class to create MODPATH 7 particle group data for location input style 1. Location input style 1 is the most general type of particle group that requires the user to define the location of all particles and associated data (relative release time, drape, and optionally particle ids). Particledata locations can be specified by layer, row, column (locationstyle=1) or nodes (locationstyle=2) and are created with the ParticleData class.

### Parameters

- **particlegroupname** (*str*) – Name of particle group (default is 'PG1')
- **filename** (*str*) – Name of the external file that will contain the particle data. If filename is '' or None the particle information for the particle group will be written to the MODPATH7 simulation file (default is None).
- **releasedata** (*float, int, list, or tuple*) – If releasedata is a float or an int or a list/tuple with a single float or int, releaseoption is set to 1 and release data is the particle release time (default is 0.0).
- **particledata** (*ParticleData*) – ParticleData instance with particle data. If particledata is None, a ParticleData instance will be created with a node-based particle in the center of the first node in the model (default is None).

## Examples

```
>>> import flopy
>>> p = [(2, 0, 0), (0, 20, 0)]
>>> p = flopy.modpath.ParticleData(p)
>>> pg = flopy.modpath.ParticleGroup(particledata=p)
```

```
write(fp=None, ws='.')
    Write MODPATH 7 particle data items 1 through 5
```

### Parameters

- **fp** (*fileobject*) – Fileobject that is open with write access
- **ws** (*str*) – Workspace for particle data

```
class ParticleGroupLRCTemplate(particlegroupname='PG1', filename=None, releasedata=(0.0),
                                particledata=None)
```

Bases: flopy.modpath.mp7particlegroup.\_ParticleGroupTemplate

Layer, row, column particle template class to create MODPATH 7 particle location input style 2. Particle locations for this template are specified by layer, row, column regions.

### Parameters

- **particlegroupname** (*str*) – Name of particle group
- **filename** (*str*) – Name of the external file that will contain the particle data. If filename is '' or None the particle information for the particle group will be written to the MODPATH7 simulation file.
- **releasedata** (*float, int, list, or tuple*) – If releasedata is a float or an int or a list/tuple with a single float or int, releaseoption is set to 1 and release data is the particle release time.
- **particledata** – LRCParticleData object with input style 2 face and/or node particle data. If particledata is None a default LRCParticleData object is created (default is None).

```
write(fp=None, ws='.')
```

### Parameters

- **fp** (*fileobject*) – Fileobject that is open with write access
- **ws** (*str*) – Workspace for particle data

```
class ParticleGroupNodeTemplate(particlegroupname='PG1', filename=None, releasedata=(0.0),
                                particledata=None)
```

Bases: flopy.modpath.mp7particlegroup.\_ParticleGroupTemplate

Node particle template class to create MODPATH 7 particle location input style 3. Particle locations for this template are specified by nodes.

### Parameters

- **particlegroupname** (*str*) – Name of particle group
- **filename** (*str*) – Name of the external file that will contain the particle data. If filename is '' or None the particle information for the particle group will be written to the MODPATH7 simulation file.



- **releasedata** (*float, int, list, or tuple*) – If releasedata is a float or an int or a list/tuple with a single float or int, releaseoption is set to 1 and release data is the particle release time.
- **particledata** – NodeParticleData object with input style 3 face and/or node particle data. If particledata is None a default NodeParticleData object is created (default is None).

**write**(*fp=None, ws='.'*)

#### Parameters

- **fp** (*fileobject*) – Fileobject that is open with write access
- **ws** (*str*) – Workspace for particle data

### flopy.modpath.mp7sim module

mpsim module. Contains the ModpathSim class. Note that the user can access the ModpathSim class as *flopy.modpath.ModpathSim*.

Additional information for this MODFLOW/MODPATH package can be found at the [Online MODFLOW Guide](#).

```
class Modpath7Sim(model, mpnamefilename=None, listingfilename=None, endpointfilename=None,
                  pathlinefilename=None, timeseriesfilename=None, tracefilename=None,
                  simulationtype='pathline', trackingdirection='forward', weaksinkoption='stop_at',
                  weaksourceoption='stop_at', budgetoutputoption='no', traceparticledata=None,
                  budgetcellnumbers=None, referencetime=None, stoptimeoption='extend', stoptime=None,
                  timepointdata=None, zonedataoption='off', stopzone=None, zones=0,
                  retardationfactoroption='off', retardation=1.0, particlegroups=None, extension='mpsim')
```

Bases: [flopy.pakbase.Package](#)

MODPATH Simulation File Package Class.

- model** [model object] The model object (of type *flopy.modpath.Modpath7*) to which this package will be added.
- mpnamefilename** [str] Filename of the MODPATH 7 name file. If mpnamefilename is not defined it will be generated from the model name (default is None).
- listingfilename** [str] Filename of the MODPATH 7 listing file. If listingfilename is not defined it will be generated from the model name (default is None).
- endpointfilename** [str] Filename of the MODPATH 7 endpoint file. If endpointfilename is not defined it will be generated from the model name (default is None).
- pathlinefilename** [str] Filename of the MODPATH 7 pathline file. If pathlinefilename is not defined it will be generated from the model name (default is None).
- timeseriesfilename** [str] Filename of the MODPATH 7 timeseries file. If timeseriesfilename is not defined it will be generated from the model name (default is None).
- tracefilename** [str] Filename of the MODPATH 7 tracefile file. If tracefilename is not defined it will be generated from the model name (default is None).
- simulationtype** [str] MODPATH 7 simulation type. Valid simulation types are 'endpoint', 'pathline', 'timeseries', or 'combined' (default is 'pathline').
- trackingdirection** [str] MODPATH 7 tracking direction. Valid tracking directions are 'forward' or 'backward' (default os 'forward').

**weaksinkoption** [str] MODPATH 7 weak sink option. Valid weak sink options are ‘pass\_through’ or ‘stop\_at’ (default value is ‘stop\_at’).

**weaksourceoption** [str] MODPATH 7 weak source option. Valid weak source options are ‘pass\_through’ or ‘stop\_at’ (default value is ‘stop\_at’).

**budgetoutputoption** [str] MODPATH 7 budget output option. Valid budget output options are ‘no’ - individual cell water balance errors are not computed and budget record headers are not printed, ‘summary’ - a summary of individual cell water balance errors for each time step is printed in the listing file without record headers, or ‘record\_summary’ - a summary of individual cell water balance errors for each time step is printed in the listing file with record headers (default is ‘summary’).

**traceparticledata** [list or tuple] List or tuple with two ints that define the particle group and particle id (zero-based) of the specified particle that is followed in detail. If traceparticledata is None, trace mode is off (default is None).

**budgetcellnumbers** [int, list of ints, tuple of ints, or np.ndarray] Cell numbers (zero-based) for which detailed water budgets are computed. If budgetcellnumbers is None, detailed water budgets are not calculated (default is None).

**referencetime** [float, list, or tuple] Specified reference time if a float or a list/tuple with a single float value is provided (reference time option 1). Otherwise a list or tuple with a zero-based stress period (int) and time step (int) and a float defining the relative time position in the time step is provided (reference time option 2). If referencetime is None, reference time is set to 0 (default is None).

**stoptimeoption** [str] String indicating how a particle tracking simulation is terminated based on time. If stop time option is ‘total’, particles will be stopped at the end of the final time step if ‘forward’ tracking is simulated or at the beginning of the first time step if backward tracking. If stop time option is ‘extend’, initial or final steady-state time steps will be extended and all particles will be tracked until they reach a termination location. If stop time option is ‘specified’, particles will be tracked until they reach a termination location or the specified stop time is reached (default is ‘extend’).

**stoptime** [float] User-specified value of tracking time at which to stop a particle tracking simulation. Stop time is only used if the stop time option is ‘specified’. If stoptime is None and the stop time option is ‘specified’ particles will be terminated at the end of the last time step if ‘forward’ tracking or the beginning of the first time step if ‘backward’ tracking (default is None).

**timepointdata** [list or tuple] List or tuple with 2 items that is only used if simulationtype is ‘time-series’ or ‘combined’. If the second item is a float then the timepoint data corresponds to time point option 1 and the first entry is the number of time points (timepointcount) and the second entry is the time point interval. If the second item is a list, tuple, or np.ndarray then the timepoint data corresponds to time point option 2 and the number of time points entries (timepointcount) in the second item and the second item is an list, tuple, or array of user-defined time points. If Timepointdata is None, time point option 1 is specified and the total simulation time is split into 100 intervals (default is None).

**zonedataoption** [str] If zonedataoption is ‘off’, zone array data are not read and a zone value of 1 is applied to all cells. If zonedataoption is ‘on’, zone array data are read (default is ‘off’).

**stopzone** [int] A zero-based specified integer zone value that indicates an automatic stopping location for particles and is only used if zonedataoption is ‘on’. A value of -1 indicates no automatic stop zone is used. Stopzone values less than -1 are not allowed. If stopzone is None, stopzone is set to -1 (default is None).

**zones** [float or array of floats (nlay, nrow, ncol)] Array of zero-based positive integer zones that are only used if zonedataoption is ‘on’ (default is 0).

**retardationfactoroption** [str] If retardationfactoroption is 'off', retardation array data are not read and a retardation factor of 1 is applied to all cells. If retardationfactoroption is 'on', retardation factor array data are read (default is 'off').

**retardation** [float or array of floats (nlay, nrow, ncol)] Array of retardation factors that are only used if retardationfactoroption is 'on' (default is 1).

**particlegroups** [ParticleGroup or list of ParticleGroups] ParticleGroup or list of ParticlesGroups that contain data for individual particle groups. If None is specified, a particle in the center of node 0 will be created (default is None).

**extension** [string] Filename extension (default is 'mpsim')

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow.load('mf2005.nam')
>>> mp = flopY.modpath.Modpath7('mf2005_mp', flowmodel=m)
>>> mpsim = flopY.modpath.Modpath7Sim(mp)
```

**write\_file**(*check=False*)

Write the package file

**Parameters** **check** (*boolean*) – Check package data for common errors. (default False)

**Return type** None

**class budgetOpt**(*value*)

Bases: `enum.Enum`

Enumeration of different budget output options

**no** = 0

**record\_summary** = 2

**summary** = 1

**class onoffOpt**(*value*)

Bases: `enum.Enum`

Enumeration of on-off options

**off** = 1

**on** = 2

**class simType**(*value*)

Bases: `enum.Enum`

Enumeration of different simulation types

**combined** = 4

**endpoint** = 1

**pathline** = 2

**timeseries** = 3

**sim\_enum\_error**(*v, s, e*)

Standard enumeration error format error :param v: Enumeration value :type v: str :param s: User-defined value :type s: str :param e: Enumeration class :type e: Enum class

```
class stopOpt(value)
    Bases: enum.Enum

    Enumeration of different stop time options

    extend = 2
    specified = 3
    total = 1

class trackDir(value)
    Bases: enum.Enum

    Enumeration of different tracking directions

    backward = 2
    forward = 1

class weakOpt(value)
    Bases: enum.Enum

    Enumeration of different weak sink and source options

    pass_through = 1
    stop_at = 2
```

## MODPATH 6 Packages

Contents:

### flopY.modpath.mp6 module

```
class Modpath6(modelname='modpathtest', simfile_ext='mpsim', namefile_ext='mpnam', version='modpath',
               exe_name='mp6.exe', modflowmodel=None, dis_file=None, dis_unit=87, head_file=None,
               budget_file=None, model_ws=None, external_path=None, verbose=False, load=True,
               listunit=7)
```

Bases: [\*flopY.mbase.BaseModel\*](#)

Modpath6 class.

#### Parameters

- **modelname** (*str*, default "modpathtest") – Basename for MODPATH 6 input and output files.
- **simfile\_ext** (*str*, default "mpsim") – Filename extension of the MODPATH 6 simulation file.
- **namefile\_ext** (*str*, default mpnam") – Filename extension of the MODPATH 6 namefile.
- **version** (*str*, default "modpath") – String that defines the MODPATH version. Valid versions are “modpath” (default).
- **exe\_name** (*str*, default "mp6.exe") – The name of the executable to use.
- **modflowmodel** (*flopY.modflow.Modflow*) – MODFLOW model object with one of LPF, BCF6, or UPW packages.
- **dis\_file** (*str*) – Required dis file name.

- **dis\_unit** (*int*, *default 87*) – Optional dis file unit number.
- **head\_file** (*str*) – Required filename of the MODFLOW output head file.
- **budget\_file** (*str*) – Required filename of the MODFLOW output cell-by-cell budget file.
- **model\_ws** (*str*, *optional*) – Model workspace. Directory name to create model data sets. Default is the current working directory.
- **external\_path** (*str*, *optional*) – Location for external files.
- **verbose** (*bool*, *default False*) – Print additional information to the screen.
- **load** (*bool*, *default True*) – Load model.
- **listunit** (*int*, *default 7*) – LIST file unit number.

**create\_mpsim**(*simtype='pathline'*, *trackdir='forward'*, *packages='WEL'*, *start\_time=0*, *default\_ifaces=None*, *ParticleColumnCount=4*, *ParticleRowCount=4*, *MinRow=0*, *MinColumn=0*, *MaxRow=None*, *MaxColumn=None*)

Create a MODPATH simulation file using available MODFLOW boundary package data.

#### Parameters

- **simtype** (*str*) –  
**Keyword defining the MODPATH simulation type. Available simtype's** are 'endpoint', 'pathline', and 'timeseries'. (default is 'PATHLINE')
- **trackdir** (*str*) – Keyword that defines the MODPATH particle tracking direction. Available trackdir's are 'backward' and 'forward'. (default is 'forward')
- **packages** (*str or list of strings*) – Keyword defining the modflow packages used to create initial particle locations. Supported packages are 'WEL', 'MNW2' and 'RCH'. (default is 'WEL').
- **start\_time** (*float or tuple*) – Sets the value of MODPATH reference time relative to MODFLOW time. *float* : value of MODFLOW simulation time at which to start the particle tracking simulation.

Sets the value of MODPATH ReferenceTimeOption to 1.

**tuple** [(period, step, time fraction) MODFLOW stress period, time step and fraction] between 0 and 1 at which to start the particle tracking simulation. Sets the value of MODPATH ReferenceTimeOption to 2.

- **default\_ifaces** (*list*) – List of cell faces (1-6; see MODPATH6 manual, fig. 7) on which to start particles. (default is None, meaning ifaces will vary depending on packages argument above)
- **ParticleRowCount** (*int*) – Rows of particles to start on each cell index face (iface).
- **ParticleColumnCount** (*int*) – Columns of particles to start on each cell index face (iface).

**Returns** *mps*

**Return type** ModpathSim object

**getmf**()

**getsim**()

**property mf**

**next\_ext\_unit()**

Function to encapsulate next\_ext\_unit attribute

**property sim**

**write\_name\_file()**

Write the name file

**Return type** None

**class Modpath6List**(*model*, *extension*='list', *listunit*=7)

Bases: [\*flop.py.pakbase.Package\*](#)

List package class

**write\_file()**

Every Package needs its own write\_file function

## flop.modpath.mp6bas module

mpbas module. Contains the ModpathBas class. Note that the user can access the ModpathBas class as *flop.modflow.ModpathBas*.

Additional information for this MODFLOW/MODPATH package can be found at the [Online MODFLOW Guide](#).

**class Modpath6Bas**(*model*, *hnoflo*=- 9999.0, *hdry*=- 8888.0, *def\_face\_ct*=0, *bud\_label*=None, *def\_iface*=None, *laytyp*=0, *ibound*=1, *prsim*=0.3, *prsimCB*=0.3, *extension*='mpbas', *unitnumber*=86)

Bases: [\*flop.py.pakbase.Package\*](#)

MODPATH Basic Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flop.modpath.mp.Modpath*) to which this package will be added.
- **hnoflo** (*float*) – Head value assigned to inactive cells (default is -9999.).
- **hdry** (*float*) – Head value assigned to dry cells (default is -8888.).
- **def\_face\_ct** (*int*) – Number fo default iface codes to read (default is 0).
- **bud\_label** (*str or list of strs*) – MODFLOW budget item to which a default iface is assigned.
- **def\_iface** (*int or list of ints*) – Cell face (iface) on which to assign flows from MODFLOW budget file.
- **laytyp** (*int or list of ints*) – MODFLOW layer type (0 is convertible, 1 is confined).
- **ibound** (*array of ints, optional*) – The ibound array (the default is 1).
- **prsim** (*array of ints, optional*) – The porosity array (the default is 0.30).
- **prsimCB** (*array of ints, optional*) – The porosity array for confining beds (the default is 0.30).
- **extension** (*str, optional*) – File extension (default is 'mpbas').

### heading

Text string written to top of package input file.

**Type** str

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modpath.Modpath6()
>>> mpbas = flopy.modpath.Modpath6Bas(m)
```

### write\_file()

Write the package file

**Return type** None

## flopy.modpath.mp6sim module

mpsim module. Contains the ModpathSim class. Note that the user can access the ModpathSim class as *flopy.modpath.ModpathSim*.

Additional information for this MODFLOW/MODPATH package can be found at the [Online MODFLOW Guide](#).

```
class Modpath6Sim(model, mp_name_file='mp.nam', mp_list_file='mp.list', option_flags=[1, 2, 1, 1, 1, 2, 2, 1, 2,
1, 1, 1], ref_time=0, ref_time_per_stp=[0, 0, 1.0], stop_time=None,
group_name=['group_1'], group_placement=[[1, 1, 1, 0, 1, 1]], release_times=[[1, 1]],
group_region=[[1, 1, 1, 1, 1, 1]], mask_nlay=[1], mask_layer=[1], mask_1lay=[1],
face_ct=[1], ifaces=[[6, 1, 1]], part_ct=[[1, 1, 1]], time_ct=1, release_time_incr=1,
time_pts=[1], particle_cell_cnt=[[2, 2, 2]], cell_bd_ct=1, bud_loc=[[1, 1, 1, 1]],
trace_id=1, stop_zone=1, zone=1, retard_fac=1.0, retard_fcCB=1.0, strt_file=None,
extension='mpsim')
```

Bases: *flopy.pakbase.Package*

MODPATH Simulation File Package Class.

### Parameters

- **model** (*model object*) – The model object (of type *flopy.modpath.mp.Modpath*) to which this package will be added.
- **extension** (*string*) – Filename extension (default is 'mpsim')

### heading

Text string written to top of package input file.

**Type** str

## Notes

## Examples

```
>>> import flopy
>>> m = flopy.modpath.Modpath6()
>>> dis = flopy.modpath.Modpath6Sim(m)
```

**check**(*f=None, verbose=True, level=1, checktype=None*)

Check package data for common errors.

### Parameters

- **f** (*str or file handle*) – String defining file name or file handle for summary file of check method output. If a sting is passed a file handle is created. If f is None, check method does not write results to a summary file. (default is None)
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.

**Return type** None

### Examples

**write\_file()**

Write the package file

**Return type** None

**class StartingLocationsFile**(*model, inputstyle=1, extension='loc', verbose=False*)

Bases: *flop.pakbase.Package*

Class for working with MODPATH Starting Locations file for particles.

#### Parameters

- **model** (*Modpath object*) – The model object (of type *flop.modpath.mp.Modpath*) to which this package will be added.
- **inputstyle** (*1*) – Input style described in MODPATH6 manual (currently only input style 1 is supported)
- **extension** (*string*) – Filename extension (default is 'loc')

**static get\_dtypes()**

Build numpy dtype for the MODPATH 6 starting locations file.

**static get\_empty\_starting\_locations\_data**(*npt=0, default\_xloc=0.5, default\_yloc=0.5, default\_zloc=0.0*)

get an empty recarray for particle starting location info.

**Parameters** **npt** (*int*) – Number of particles. Particles in array will be numbered consecutively from 1 to npt.

**write\_file**(*data=None, float\_format='{: .8f}'*)

Every Package needs its own write\_file function

## 7.1.3 Flopy Utilities

### Model Utilities (including binary file readers)

Contents:



## flop.utils.binaryfile module

Module to read MODFLOW binary output files. The module contains four important classes that can be accessed by the user.

- `HeadFile` (Binary head file. Can also be used for drawdown)
- `HeadUFile` (Binary MODFLOW-USG unstructured head file)
- `UcnFile` (Binary concentration file from MT3DMS)
- `CellBudgetFile` (Binary cell-by-cell flow file)

**class `BinaryHeader`**(*bintype=None, precision='single'*)

Bases: `flop.utils.datafile.Header`

The `binary_header` class is a class to create headers for MODFLOW binary files.

### Parameters

- **`bintype`** (*str*) – is the type of file being opened (head and ucn file currently supported)
- **`precision`** (*str*) – is the precision of the floating point data in the file

**static `create`**(*bintype=None, precision='single', \*\*kwargs*)

Create a binary header

**static `set_dtype`**(*bintype=None, precision='single'*)

Set the dtype

**`set_values`**(*\*\*kwargs*)

Set values using kwargs

**class `BinaryLayerFile`**(*filename, precision, verbose, kwargs*)

Bases: `flop.utils.datafile.LayerFile`

The `BinaryLayerFile` class is the super class from which specific derived classes are formed. This class should not be instantiated directly

**`get_databytes`**(*header*)

**Parameters** *header* (`datafile.Header`) – header object

**Returns** *databytes* – size of the data array, in bytes, following the header

**Return type** `int`

**`get_ts`**(*idx*)

Get a time series from the binary file.

**Parameters** *idx* (*tuple of ints, or a list of a tuple of ints*) – *idx* can be (layer, row, column) or it can be a list in the form [(layer, row, column), (layer, row, column), ...]. The layer, row, and column values must be zero based.

**Returns** *out* – Array has size (ntimes, ncells + 1). The first column in the data array will contain time (totim).

**Return type** `numpy array`

## Notes

The layer, row, and column values must be zero-based, and must be within the following ranges:  $0 \leq k < nlay$ ;  $0 \leq i < nrow$ ;  $0 \leq j < ncol$

## Examples

### exception BudgetIndexError

Bases: Exception

### class CellBudgetFile(filename, precision='auto', verbose=False, \*\*kwargs)

Bases: object

CellBudgetFile Class.

#### Parameters

- **filename** (*string*) – Name of the cell budget file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘single’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flop.utils.binaryfile as bf
>>> cbb = bf.CellBudgetFile('mymodel.cbb')
>>> cbb.list_records()
>>> rec = cbb.get_data(kstpkper=(0,0), text='RIVER LEAKAGE')
```

### close()

Close the file handle

### get\_data(idx=None, kstpkper=None, totim=None, text=None, paknam=None, full3D=False)

Get data from the binary budget file.

#### Parameters

- **idx** (*int or list*) – The zero-based record number. The first record is record 0.
- **kstpkper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). The kstp and kper values are zero based.
- **totim** (*float*) – The simulation time.
- **text** (*str*) – The text identifier for the record. Examples include ‘RIVER LEAKAGE’, ‘STORAGE’, ‘FLOW RIGHT FACE’, etc.
- **full3D** (*boolean*) – If true, then return the record as a three dimensional numpy array, even for those list-style records written as part of a ‘COMPACT BUDGET’ MODFLOW budget file. (Default is False.)

#### Returns

**recordlist** – A list of budget objects. The structure of the returned object depends on the structure of the data in the cbb file.

If full3D is True, then this method will return a numpy masked array of size (nlay, nrow, ncol) for those list-style ‘COMPACT BUDGET’ records written by MODFLOW.

**Return type** list of records

## Notes

## Examples

**get\_indices**(*text=None*)

Get a list of indices for a selected record name

**Parameters** **text** (*str*) – The text identifier for the record. Examples include ‘RIVER LEAKAGE’, ‘STORAGE’, ‘FLOW RIGHT FACE’, etc.

**Returns** **out** – indices of selected record name in budget file.

**Return type** tuple

**get\_kstpker**()

Get a list of unique stress periods and time steps in the file

**Returns** **out** – List of unique kstp, kper combinations in binary file. kstp and kper values are zero-based.

**Return type** list of (kstp, kper) tuples

**get\_nrecords**()

Return the number of records in the file

**Returns** **out** – Number of records in the file.

**Return type** int

**get\_position**(*idx, header=False*)

Get the starting position of the data or header for a specified record number in the binary budget file.

**Parameters**

- **idx** (*int*) – The zero-based record number. The first record is record 0.
- **header** (*bool*) – If True, the position of the start of the header data is returned. If False, the position of the start of the data is returned (default is False).

**Returns** **ipos** – The position of the start of the data in the cell budget file or the start of the header.

**Return type** int64

**get\_record**(*idx, full3D=False*)

Get a single data record from the budget file.

**Parameters**

- **idx** (*int*) – The zero-based record number. The first record is record 0.
- **full3D** (*boolean*) – If true, then return the record as a three dimensional numpy array, even for those list-style records written as part of a ‘COMPACT BUDGET’ MODFLOW budget file. (Default is False.)

**Returns**

**record** – The structure of the returned object depends on the structure of the data in the cbb file. Compact list data are returned as

If full3D is True, then this method will return a numpy masked array of size (nlay, nrow, ncol) for those list-style ‘COMPACT BUDGET’ records written by MODFLOW.

**Return type** a single data record

## Notes

## Examples

**get\_residual**(*totim*, *scaled=False*)

Return an array the size of the model grid containing the flow residual calculated from the budget terms. Residual will not be correct unless all flow terms are written to the budget file.

### Parameters

- **totim** (*float*) – Simulation time for which to calculate the residual. This value must be precise, so it is best to get it from the `get_times` method.
- **scaled** (*bool*) – If True, then divide the residual by the total cell inflow

**Returns** **residual** – The flow residual for the cell of shape (nlay, nrow, ncol)

**Return type** np.ndarray

**get\_times**()

Get a list of unique times in the file

**Returns** **out** – List contains unique simulation times (totim) in binary file.

**Return type** list of floats

**get\_ts**(*idx*, *text=None*, *times=None*)

Get a time series from the binary budget file.

### Parameters

- **idx** (*tuple of ints, or a list of a tuple of ints*) – idx can be (layer, row, column) or it can be a list in the form [(layer, row, column), (layer, row, column), ...]. The layer, row, and column values must be zero based.
- **text** (*str*) – The text identifier for the record. Examples include 'RIVER LEAKAGE', 'STORAGE', 'FLOW RIGHT FACE', etc.
- **times** (*iterable of floats*) – List of times to from which to get time series.

**Returns** **out** – Array has size (ntimes, ncells + 1). The first column in the data array will contain time (totim).

**Return type** numpy array

## Notes

The layer, row, and column values must be zero-based, and must be within the following ranges:  $0 \leq k < nlay$ ;  $0 \leq i < nrow$ ;  $0 \leq j < ncol$

## Examples

**get\_unique\_package\_names**(*decode=False*)

Get a list of unique package names in the file

**Parameters** **decode** (*bool*) – Optional boolean used to decode byte strings (default is False).

**Returns** **names** – List of unique package names in the binary file.

**Return type** list of strings

**get\_unique\_record\_names**(*decode=False*)

Get a list of unique record names in the file

**Parameters** **decode** (*bool*) – Optional boolean used to decode byte strings (default is False).

**Returns** **names** – List of unique text names in the binary file.

**Return type** list of strings

**list\_records**()

Print a list of all of the records in the file

**list\_unique\_packages**()

Print a list of unique package names

**list\_unique\_records**()

Print a list of unique record names

**class HeadFile**(*filename, text='head', precision='auto', verbose=False, \*\*kwargs*)

Bases: [flop.utils.binaryfile.BinaryLayerFile](#)

HeadFile Class.

**Parameters**

- **filename** (*string*) – Name of the concentration file
- **text** (*string*) – Name of the text string in the head file. Default is 'head'
- **precision** (*string*) – 'auto', 'single' or 'double'. Default is 'auto'.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

The HeadFile class provides simple ways to retrieve 2d and 3d head arrays from a MODFLOW binary head file and time series arrays for one or more cells.

The BinaryLayerFile class is built on a record array consisting of headers, which are record arrays of the modflow header information (kstp, kper, pertim, totim, text, nrow, ncol, ilay) and long integers, which are pointers to first bytes of data for the corresponding data array.

## Examples

```
>>> import floppy.utils.binaryfile as bf
>>> hdoobj = bf.HeadFile('model.hds', precision='single')
>>> hdoobj.list_records()
>>> rec = hdoobj.get_data(kstpkper=(1, 50))
```

```
>>> ddnoobj = bf.HeadFile('model.ddn', text='drawdown', precision='single')
>>> ddnoobj.list_records()
>>> rec = ddnoobj.get_data(totim=100.)
```

**class** `HeadUFile`(*filename*, *text*='headu', *precision*='auto', *verbose*=False, *\*\*kwargs*)

Bases: `floppy.utils.binaryfile.BinaryLayerFile`

Unstructured MODFLOW-USG HeadUFile Class.

### Parameters

- **filename** (*string*) – Name of the concentration file
- **text** (*string*) – Name of the text string in the head file. Default is ‘headu’
- **precision** (*string*) – ‘auto’, ‘single’ or ‘double’. Default is ‘auto’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

The HeadUFile class provides simple ways to retrieve a list of head arrays from a MODFLOW-USG binary head file and time series arrays for one or more cells.

The BinaryLayerFile class is built on a record array consisting of headers, which are record arrays of the modflow header information (kstp, kper, pertim, totim, text, nrow, ncol, ilay) and long integers, which are pointers to first bytes of data for the corresponding data array. For unstructured grids, nrow and ncol are the starting and ending node numbers for layer, ilay. This class overrides methods in the parent class so that the proper sized arrays are created.

When the `get_data` method is called for this class, a list of one-dimensional arrays will be returned, where each array is the head array for a layer. If the heads for a layer were not saved, then None will be returned for that layer.

## Examples

```
>>> import floppy.utils.binaryfile as bf
>>> hdoobj = bf.HeadUFile('model.hds')
>>> hdoobj.list_records()
>>> usgheads = hdoobj.get_data(kstpkper=(1, 50))
```

**get\_databytes**(*header*)

**Parameters** **header** (`datafile.Header`) – header object

**Returns** **databytes** – size of the data array, in bytes, following the header

**Return type** `int`

**get\_ts(*idx*)**

Get a time series from the binary HeadUFile

**Parameters** *idx* (*int* or *list of ints*) – *idx* can be nodenumber or it can be a list in the form [nodenumber, nodenumber, ...]. The nodenumber, values must be zero based.

**Returns** *out* – Array has size (ntimes, ncells + 1). The first column in the data array will contain time (totim).

**Return type** numpy array

**class** **UcnFile**(*filename*, *text*='concentration', *precision*='auto', *verbose*=False, *\*\*kwargs*)

Bases: [flop.utils.binaryfile.BinaryLayerFile](#)

UcnFile Class.

**Parameters**

- **filename** (*string*) – Name of the concentration file
- **text** (*string*) – Name of the text string in the ucn file. Default is 'CONCENTRATION'
- **precision** (*string*) – 'auto', 'single' or 'double'. Default is 'auto'.
- **verbose** (*bool*) – Write information to the screen. Default is False.

**Notes**

The UcnFile class provides simple ways to retrieve 2d and 3d concentration arrays from a MT3D binary head file and time series arrays for one or more cells.

The BinaryLayerFile class is built on a record array consisting of headers, which are record arrays of the modflow header information (kstp, kper, pertim, totim, text, nrow, ncol, ilay) and long integers, which are pointers to first bytes of data for the corresponding data array.

**Examples**

```
>>> import flop.utils.binaryfile as bf
>>> ucnobj = bf.UcnFile('MT3D001.UCN', precision='single')
>>> ucnobj.list_records()
>>> rec = ucnobj.get_data(kstp=kper=(1,1))
```

**binaryread**(*file*, *vartype*, *shape*=(1,), *charlen*=16)

Uses numpy to read from binary file. This was found to be faster than the struct approach and is used as the default.

**binaryread\_struct**(*file*, *vartype*, *shape*=(1,), *charlen*=16)

Read text, a scalar value, or an array of values from a binary file.

**file** [file object] is an open file object

**vartype** [type] is the return variable type: str, numpy.int32, numpy.float32, or numpy.float64

**shape** [tuple] is the shape of the returned array (shape(1, ) returns a single value) for example, shape = (nlay, nrow, ncol)

**charlen** [int] is the length of the text string. Note that string arrays cannot be returned, only multi-character strings. Shape has no affect on strings.

**get\_headfile\_precision**(*filename*)

Determine precision of a MODFLOW head file.

**Parameters**

- **filename** (*str*) –
- **precision.** (*Name of binary MODFLOW file to determine*) –

**Returns**

- **result** (*str*)
- *Result will be unknown, single, or double*

**join\_struct\_arrays**(*arrays*)

Simple function that can join two numpy structured arrays.

**flop.utils.check module**

**class check**(*package, f=None, verbose=True, level=1, property\_threshold\_values={}*)

Bases: object

Check package for common errors

**Parameters**

- **package** (*object*) – Instance of Package class.
- **verbose** (*bool*) – Boolean flag used to determine if check method results are written to the screen
- **level** (*int*) – Check method analysis level. If level=0, summary checks are performed. If level=1, full checks are performed.
- **property\_threshold\_values** (*dict*) –

**hk** [tuple] Reasonable minimum/maximum hydraulic conductivity value; values below this will be flagged. Default is (1e-11, 1e5), after Bear, 1972 (see [https://en.wikipedia.org/wiki/Hydraulic\\_conductivity](https://en.wikipedia.org/wiki/Hydraulic_conductivity)) and Schwartz and Zhang (2003, Table 4.4).

**vka** [tuple] Reasonable minimum/maximum hydraulic conductivity value; Default is (1e-11, 1e5), after Bear, 1972 (see [https://en.wikipedia.org/wiki/Hydraulic\\_conductivity](https://en.wikipedia.org/wiki/Hydraulic_conductivity)) and Schwartz and Zhang (2003, Table 4.4).

**vkcb** [tuple] Reasonable minimum/maximum hydraulic conductivity value for quasi-3D confining bed; Default is (1e-11, 1e5), after Bear, 1972 (see [https://en.wikipedia.org/wiki/Hydraulic\\_conductivity](https://en.wikipedia.org/wiki/Hydraulic_conductivity)) and Schwartz and Zhang (2003, Table 4.4).

**sy** [tuple] Reasonable minimum/maximum specific yield values; Default is (0.01,0.5) after Anderson, Woessner and Hunt (2015, Table 5.2).

**sy** [tuple] Reasonable minimum/maximum specific storage values; Default is (3.3e-6, 2e-2) after Anderson, Woessner and Hunt (2015, Table 5.2).



## Notes

Anderson, M.P, Woessner, W.W. and Hunt, R.J., 2015. **Applied Groundwater Modeling: Simulation of Flow and Advective Transport**, Elsevier, 564p.

Bear, J., 1972. **Dynamics of Fluids in Porous Media**. Dover Publications. Schwartz, F.W. and Zhang, H., 2003. **Fundamentals of Groundwater**, Wiley, 583 p.

**append\_passed**(*message*)

Add a check to the passed list if it isn't already in there.

**bc\_stage\_names** = {'DRN': 'elev', 'GHB': 'bhead'}

**get\_active**(*include\_cbd=False*)

Returns a boolean array of active cells for the model.

**Parameters** **include\_cbd** (*boolean*) – If True, active is of same dimension as the thickness array in the DIS module (includes quasi 3-D confining beds). Default False.

**Returns** **active** – True where active.

**Return type** 3-D boolean array

**get\_neighbors**(*a*)

For a structured grid, this returns the 6 neighboring values for each value in a. For an unstructured grid, this returns the *n\_max* neighboring values, where *n\_max* is the maximum number of nodal connections for any node within the model; nodes with less than *n\_max* connections are assigned np.nan for indices above the number of connections for that node.

**Parameters**

- **a** (*3-D Model array in layer, row, column order array, even for an*) –
- **instance** (*unstructured grid; for*) –
- **array** (*a Util3d*) –
- **flop.modflow.ModflowBas.ibound** *.* (*(e.g.)*) –

**Returns** **neighbors** – Array of neighbors, where axis 0 contains the *n* neighboring values for each value in a, and subsequent axes are in layer, row, column order. “*n*” is 6 for a structured grid, and “*n*” is *n\_max* for an unstructured grid, as described above. Nan is returned for values at edges.

**Return type** 4-D array

**isvalid**(*inds*)

Check that indices are valid for model grid

**Parameters** **inds** (*tuple or lists or arrays; or a 1-D array*) – (*k, i, j*) for structured grids; (*node*) for unstructured.

**Returns** **isvalid** – True for each index in inds that is valid for the model grid.

**Return type** 1-D boolean array

**package\_check\_levels** = {'sfr': 1}

**print\_summary**(*cols=None, delimiter=',', float\_format='{:6f}'*)

**property\_threshold\_values** = {'hani': None, 'hk': (1e-11, 100000.0), 'k': (1e-11, 100000.0), 'k22': (1e-11, 100000.0), 'k33': (1e-11, 100000.0), 'ss': (1e-06, 0.01), 'sy': (0.01, 0.5), 'vka': (1e-11, 100000.0), 'vkcb': (1e-11, 100000.0)}

**remove\_passed**(*message*)

Remove a check to the passed list if it failed in any stress period.

**solver\_packages** = {'mf2005': ['DE4', 'SIP', 'GMG', 'PCG', 'PCGN'], 'mf2k': ['DE4', 'SIP', 'SOR', 'GMG', 'PCG', 'PCGN'], 'mfnewt': ['DE4', 'SIP', 'PCG', 'NWT'], 'mfusg': ['SMS']}

**stress\_period\_data\_values**(*stress\_period\_data*, *criteria*, *col=None*, *error\_name=""*, *error\_type='Warning'*)

If *criteria* contains any true values, return the *error\_type*, package name, k,i,j indices, values, and description of error for each row in *stress\_period\_data* where *criteria=True*.

**summarize**()

**thin\_cell\_threshold** = 1.0

**values**(*a*, *criteria*, *error\_name=""*, *error\_type='Warning'*)

If *criteria* contains any true values, return the *error\_type*, package name, indices, array values, and description of error for each True value in *criteria*.

**view\_summary\_array\_fields**(*fields*)

**fields\_view**(*arr*, *fields*)

creates view of array that only contains the fields in *fields*. <http://stackoverflow.com/questions/15182381/how-to-return-a-view-of-several-columns-in-numpy-structured-array>

**class mf6check**(*package*, *f=None*, *verbose=True*, *level=1*, *property\_threshold\_values={}*)

Bases: *flop.utils.check.check*

**get\_active**(*include\_cbd=False*)

Returns a boolean array of active cells for the model.

**Parameters** *include\_cbd* (*boolean*) – Does not apply to MF6 models, always false.

**Returns** *active* – True where active.

**Return type** 3-D boolean array

## flop.utils.cvfdutil module

**class Point**(*x*, *y*)

Bases: *object*

**area\_of\_polygon**(*x*, *y*)

Calculates the signed area of an arbitrary polygon given its vertices <http://stackoverflow.com/a/4682656/190597> (Joe Kington) [http://softsurfer.com/Archive/algorithm\\_0101/algorithm\\_0101.htm#2D%20Polygons](http://softsurfer.com/Archive/algorithm_0101/algorithm_0101.htm#2D%20Polygons)

**centroid\_of\_polygon**(*points*)

<http://stackoverflow.com/a/14115494/190597> (mgamba)

**get\_disv\_gridprops**(*verts*, *iverts*, *xcyc=None*)

Calculate disv grid properties from *verts* and *iverts*

**Parameters**

- **verts** (*ndarray*) – 2d array of x, y vertices
- **iverts** (*list*) – list of size *ncpl*, with a list of vertex numbers for each cell

**Returns** *gridprops* – Dictionary containing entries that can be passed directly into the modflow6 disv package.

**Return type** dict

**gridlist\_to\_disv\_gridprops**(*gridlist*)

Take a list of flopY structured model grids and convert them into a dictionary that can be passed into the modflow6 disv package. Cells from a child grid will be patched in to make a single set of vertices. Cells will be numbered according to consecutive numbering of active cells in the grid list.

**Parameters** **gridlist** (*list*) – List of flopY.discretization.modelgrid. Must be of type structured grids

**Returns** **gridprops** – Dictionary containing entries that can be passed directly into the modflow6 disv package.

**Return type** dict

**gridlist\_to\_verts**(*gridlist*)

Take a list of flopY structured model grids and convert them into vertices. The idomain can be set to remove cells in a parent grid. Cells from a child grid will be patched in to make a single set of vertices. Cells will be numbered according to consecutive numbering of active cells in the grid list.

**Parameters** **gridlist** (*list*) – List of flopY.discretization.modelgrid. Must be of type structured grids

**Returns** **verts, iverts** – vertices and list of cells and which vertices comprise the cells

**Return type** np.ndarray, list

**isBetween**(*a, b, c, epsilon=0.001*)**segment\_face**(*ivert, ivlist1, ivlist2, vertices*)

Check the vertex lists for cell 1 and cell 2. Add a new vertex to cell 1 if necessary.

**Parameters**

- **ivert** (*int*) – vertex number to check
- **ivlist1** (*list*) – list of vertices for cell 1. Add a new vertex to this cell if needed.
- **ivlist2** (*list*) – list of vertices for cell2.
- **vertices** (*ndarray*) – array of x, y vertices

**Returns** **segmented** – Return True if a face in cell 1 was split up by adding a new vertex

**Return type** bool

**shapefile\_to\_cvfd**(*shp, \*\*kwargs*)**shapefile\_to\_xcyc**(*shp*)

Get cell centroid coordinates

**Parameters** **shp** (*string*) – Name of shape file

**Returns** **xcyc** – x, y coordinates of all polygons in shp

**Return type** ndarray

**shared\_face**(*ivlist1, ivlist2*)**to\_cvfd**(*vertdict, nodestart=None, nodestop=None, skip\_hanging\_node\_check=False, verbose=False*)

Convert a vertex dictionary into verts and iverts

**Parameters**

- **vertdict** – vertdict is a dictionary {icell: [(x1, y1), (x2, y2), (x3, y3), ...]}
- **nodestart** (*int*) – starting node number. (default is zero)
- **nodestop** (*int*) – ending node number up to but not including. (default is len(vertdict))
- **skip\_hanging\_node\_check** (*bool*) – skip the hanging node check. this may only be necessary for quad-based grid refinement. (default is False)

- **verbose** (*bool*) – print messages to the screen. (default is False)

**Returns**

- **verts** (*ndarray*) – array of x, y vertices
- **iverts** (*list*) – list containing a list for each cell

**flop.utils.datafile module**

Module to read MODFLOW output files. The module contains shared abstract classes that should not be directly accessed.

**class Header**(*filetype=None, precision='single'*)

Bases: object

The header class is an abstract base class to create headers for MODFLOW files

**get\_dtype()**

Return the dtype

**get\_names()**

Return the dtype names

**get\_values()**

Return the header values

**class LayerFile**(*filename, precision, verbose, kwargs*)

Bases: object

The LayerFile class is the abstract base class from which specific derived classes are formed. LayerFile This class should not be instantiated directly.

**close()**

Close the file handle.

**get\_alldata**(*mflay=None, nodata=- 9999*)

Get all of the data from the file.

**Parameters**

- **mflay** (*integer*) – MODFLOW zero-based layer number to return. If None, then all all layers will be included. (Default is None.)
- **nodata** (*float*) – The nodata value in the data array. All array values that have the nodata value will be assigned np.nan.

**Returns data** – Array has size (ntimes, nlay, nrow, ncol) if mflay is None or it has size (ntimes, nrow, ncol) if mlay is specified.

**Return type** numpy array

## Notes

## Examples

**get\_data**(*kstp**kper*=None, *idx*=None, *totim*=None, *mflay*=None)

Get data from the file for the specified conditions.

### Parameters

- **idx** (*int*) – The zero-based record number. The first record is record 0.
- **kstp****kper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). These are zero-based kstp and kper values.
- **totim** (*float*) – The simulation time.
- **mflay** (*integer*) – MODFLOW zero-based layer number to return. If None, then all layers will be included. (Default is None.)

**Returns data** – Array has size (nlay, nrow, ncol) if mflay is None or it has size (nrow, ncol) if mlay is specified.

**Return type** numpy array

## Notes

if both kstp and totim are None, will return the last entry

## Examples

**get\_kstp**(*kper*)

Get a list of unique stress periods and time steps in the file

**Returns out** – List of unique kstp, kper combinations in binary file. kstp and kper values are presently zero-based.

**Return type** list of (kstp, kper) tuples

**get\_times**()

Get a list of unique times in the file

**Returns out** – List contains unique simulation times (totim) in binary file.

**Return type** list of floats

**list\_records**()

Print a list of all of the records in the file obj.list\_records()

**plot**(*axes*=None, *kstp**kper*=None, *totim*=None, *mflay*=None, *filename\_base*=None, *\*\*kwargs*)

Plot 3-D model output data in a specific location in LayerFile instance

### Parameters

- **axes** (*list of matplotlib.pyplot.axis*) – List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)
- **kstp****kper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). These are zero-based kstp and kper values.
- **totim** (*float*) – The simulation time.

- **mflay** (*int*) – MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **\*\*kwargs** (*dict*) –
  - pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)
  - colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)
  - contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)
  - clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)
  - grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)
  - masked\_values** [list] List of unique values to be excluded from the plot.
  - file\_extension** [str] Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')

**Return type** None

## Notes

## Examples

```
>>> import flop
>>> hdoobj = flop.utils.HeadFile('test.hds')
>>> times = hdoobj.get_times()
>>> hdoobj.plot(totim=times[-1])
```

**to\_shapefile**(*filename*, *kstpkper*=None, *totim*=None, *mflay*=None, *attrib\_name*='lf\_data')

**Export model output data to a shapefile at a specific location** in LayerFile instance.

### Parameters

- **filename** (*str*) – Shapefile name to write
- **kstpkper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). These are zero-based kstp and kper values.
- **totim** (*float*) – The simulation time.
- **mflay** (*integer*) – MODFLOW zero-based layer number to return. If None, then layer 1 will be written
- **attrib\_name** (*str*) – Base name of attribute columns. (default is 'lf\_data')

**Return type** None

## Notes

## Examples

```
>>> import flopy
>>> hdoobj = flopy.utils.HeadFile('test.hds')
>>> times = hdoobj.get_times()
>>> hdoobj.to_shapefile('test_heads_sp6.shp', totim=times[-1])
```

## flopy.utils.datautil module

**class** **ArrayIndexIter**(*array\_shape*, *index\_as\_tuple=False*)  
 Bases: object

**class** **ConstIter**(*value*)  
 Bases: object

**class** **DatumUtil**  
 Bases: object

**static** **is\_basic\_type**(*obj*)

**static** **is\_float**(*str*)

**static** **is\_int**(*str*)

**class** **FileIter**(*file\_path*)  
 Bases: object

**close**()

**class** **MultiList**(*mdlist=None*, *shape=None*, *callback=None*)  
 Bases: object

Class for storing objects in an n-dimensional list which can be iterated through as a single list.

### Parameters

- **mdlist** (*list*) – multi-dimensional list to initialize the multi-list. either mdlist or both shape and callback must be specified
- **shape** (*tuple*) – shape of the multi-list
- **callback** (*method*) – callback method that takes a location in the multi-list (tuple) and returns an object to be stored at that location in the multi-list

**increment\_dimension** : (**dimension**, **callback**)  
 increments the size of one of the two dimensions of the multi-list

**build\_list** : (**callback**)  
 builds a multi-list of shape self.list\_shape, constructing objects for the list using the supplied callback method

**first\_item** : () : **object**  
 gets the first entry in the multi-list

**get\_total\_size** : () : **int**  
 returns the total number of entries in the multi-list

**in\_shape** : (**indexes**) : **boolean**  
 returns whether a tuple of indexes are valid indexes for the shape of the multi-list

**inc\_shape\_idx** : (indexes) : tuple

given a tuple of indexes pointing to an entry in the multi-list, returns a tuple of indexes pointing to the next entry in the multi-list

**first\_index** : () : tuple

returns a tuple of indexes pointing to the first entry in the multi-list

**indexes** : (start\_indexes=None, end\_indexes=None) : iter(tuple)

returns an iterator that iterates from the location in the multi-list defined by start\_indexes to the location in the multi-list defined by end\_indexes

**elements** : () : iter(object)

returns an iterator that iterates over each object stored in the multi-list

**build\_list**(callback)

**elements**()

**first\_index**()

**first\_item**()

**get\_total\_size**()

**in\_shape**(indexes)

**inc\_shape\_idx**(indexes)

**increment\_dimension**(dimension, callback)

**indexes**(start\_indexes=None, end\_indexes=None)

**nth\_index**(n)

**class MultiListIter**(multi\_list, detailed\_info=False, iter\_leaf\_lists=False)

Bases: object

**class NameIter**(name, first\_not\_numbered=True)

Bases: object

**class PathIter**(path, first\_not\_numbered=True)

Bases: object

**class PyListUtil**(path=None, max\_error=0.01)

Bases: object

Class contains miscellaneous methods to work with and compare python lists

**Parameters**

- **path** (string) – file path to read/write to
- **max\_error** (float) – maximum acceptable error when doing a compare of floating point numbers

**is\_iterable** : (obj : unknown) : boolean

determines if obj is iterable

**is\_empty\_list** : (current\_list : list) : boolean

determines if an n-dimensional list is empty

**con\_convert** : (data : string, data\_type : type that has conversion

operation) : boolean

returns true if data can be converted into data\_type



```

max_multi_dim_list_size : (current_list : list) : boolean
    determines the max number of items in a multi-dimensional list 'current_list'

first_item : (current_list : list) : variable
    returns the first item in the list 'current_list'

next_item : (current_list : list) : variable
    returns the next item in the list 'current_list'

array_comp : (first_array : list, second_array : list) : boolean
    compares two lists, returns true if they are identical (with max_error)

spilt_data_line : (line : string) : list
    splits a string apart (using split) and then cleans up the results dealing with various MODFLOW input file
    releated delimiters. returns the delimiter type used.

clean_numeric : (text : string) : string
    returns a cleaned up version of 'text' with only numeric characters

save_array_diff : (first_array : list, second_array : list,

    first_array_name : string, second_array_name : string)

    saves lists 'first_array' and 'second_array' to files first_array_name and second_array_name and then saves
    the difference of the two arrays to 'debug_array_diff.txt'

save_array(filename: string, multi_array: list)
    saves 'multi_array' to the file 'filename'

array_comp(first_array, second_array)

static clean_numeric(text)

consistent_delim = False

delimiter_list = {':', ': 1'}

delimiter_used = None

static first_item(current_list)

static has_one_item(current_list)

static is_empty_list(current_list)

static is_iterable(obj)

line_num = 0

static max_multi_dim_list_size(current_list)

static next_item(current_list, new_list=True, nesting_change=0, end_of_list=True)

static next_list(current_list)

numeric_chars = {'-': 0, '.': 0, '0': 0, '1': 0, '2': 0, '3': 0, '4': 0, '5': 0,
'6': 0, '7': 0, '8': 0, '9': 0}

quote_list = {'"', '"'}

static reset_delimiter_used()

riv_array_comp(first_array, second_array)

save_array(filename, multi_array)

save_array_diff(first_array, second_array, first_array_name, second_array_name)

```

```
static split_data_line(line, external_file=False, delimiter_conf_length=15)
clean_filename(file_name)
clean_name(name)
find_keyword(arr_line, keyword_dict)
max_tuple_abs_size(some_tuple)
```

## flop.utils.flop\_io module

Module for input/output utilities

**flux\_to\_wel**(cbc\_file, text, precision='single', model=None, verbose=False)

Convert flux in a binary cell budget file to a wel instance

**Parameters**

- **cbc\_file**((str) cell budget file name) –
- **text**((str) text string of the desired flux type (e.g. "drains")) –
- **precision**((optional str) precision of the cell budget file) –
- **model** ((optional) BaseModel instance. If passed, a new ModflowWel) – instance will be added to model
- **verbose**(bool flag passed to CellBudgetFile) –

**Return type** flop.modflow.ModflowWel instance

**get\_next\_line**(f)

Get the next line from a file that is not a blank line

**Parameters** **f** (filehandle) – filehandle to a open file

**Returns** **line** – next non-empty line in a open file

**Return type** string

**get\_ts\_sp**(line)

Reader method to get time step and stress period numbers from list files and Modflow other output files

**Parameters** **line** (str) – line containing information about the stress period and time step. The line must contain “STRESS PERIOD <x> TIME STEP <y>”

**Return type** tuple of stress period and time step numbers

**get\_url\_text**(url, error\_msg=None)

Get text from a url.

**line\_parse**(line)

Convert a line of text into to a list of values. This handles the case where a free formatted MODFLOW input file may have commas in it.

**line\_strip**(line)

Remove comments and replace commas from input text for a free formatted modflow input file

**Parameters** **line** (str) – a line of text from a modflow input file

**Returns** **str**

**Return type** line with comments removed and commas replaced

**loadtxt**(file, delimiter=',', dtype=None, skiprows=0, use\_pandas=True, \*\*kwargs)

Use pandas if it is available to load a text file (significantly faster than n.loadtxt or genfromtxt see <http://stackoverflow.com/questions/18259393/numpy-loading-csv-too-slow-compared-to-matlab>)

**Parameters**

- **file** (*file or str*) – File, filename, or generator to read.
- **delimiter** (*str, optional*) – The string used to separate values. By default, this is any whitespace.
- **dtype** (*data-type, optional*) – Data-type of the resulting array
- **skiprows** (*int, optional*) – Skip the first skiprows lines; default: 0.
- **use\_pandas** (*bool*) – If true, the much faster pandas.read\_csv method is used.
- **kwargs** (*dict*) – Keyword arguments passed to numpy.loadtxt or pandas.read\_csv.

**Returns** **ra** – Numpy record array of file contents.

**Return type** np.recarray

**multi\_line\_strip(fobj)**

Get next line that is not blank or is not a comment line from a free formatted modflow input file

**Parameters** **fobj** (*open file object*) – a line of text from an input file

**Returns** **str**

**Return type** line with comments removed and commas replaced

**pop\_item(line, dtype=<class 'str'>)****read\_fixed\_var(line, ncol=1, length=10, ipos=None, free=False)**

Parse a fixed format line using user provided data

**Parameters**

- **line** (*str*) – text string to parse.
- **ncol** (*int*) – number of columns to parse from line. (default is 1)
- **length** (*int*) – length of each column for fixed column widths. (default is 10)
- **ipos** (*list, int, or numpy array*) – user-provided column widths. (default is None)
- **free** (*bool*) – boolean indicating if sting is free format. ncol, length, and ipos are not used if free is True. (default is False)

**Returns** **out** – padded list containing data parsed from the passed text string

**Return type** list

**ulstrd(f, nlist, ra, model, sfac\_columns, ext\_unit\_dict)**

Read a list and allow for open/close, binary, external, sfac, etc.

**Parameters**

- **f** (*file handle*) – file handle for where the list is being read from
- **nlist** (*int*) – size of the list (number of rows) to read
- **ra** (*np.recarray*) – A record array of the correct size that will be filled with the list
- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **sfac\_columns** (*list*) – A list of strings containing the column names to scale by sfac
- **ext\_unit\_dict** (*dictionary, optional*) – If the list in the file is specified using EXTERNAL, then in this case ext\_unit\_dict is required, which can be constructed using the function `flop.utils.mfreadnam.parsenamefile`.

**write\_fixed\_var**(*v*, *length*=10, *ipos*=None, *free*=False, *comment*=None)

**Parameters**

- **v** (*list*, *int*, *float*, *bool*, or *numpy array*) – list, int, float, bool, or numpy array containing the data to be written to a string.
- **length** (*int*) – length of each column for fixed column widths. (default is 10)
- **ipos** (*list*, *int*, or *numpy array*) – user-provided column widths. (default is None)
- **free** (*bool*) – boolean indicating if a free format string should be generated. length and ipos are not used if free is True. (default is False)
- **comment** (*str*) – comment string to add to the end of the string

**Returns** **out** – fixed or free format string generated using user-provided data

**Return type** *str*

## flop.utils.formattedfile module

Module to read MODFLOW formatted output files. The module contains one important classes that can be accessed by the user.

- FormattedHeadFile (Formatted head file. Can also be used for drawdown)

**class FormattedHeadFile**(*filename*, *text*='head', *precision*='single', *verbose*=False, *\*\*kwargs*)

Bases: [flop.utils.formattedfile.FormattedLayerFile](#)

FormattedHeadFile Class.

**Parameters**

- **filename** (*string*) – Name of the formatted head file
- **text** (*string*) – Name of the text string in the formatted head file. Default is 'head'
- **precision** (*string*) – 'single' or 'double'. Default is 'single'.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

The FormattedHeadFile class provides simple ways to retrieve 2d and 3d head arrays from a MODFLOW formatted head file and time series arrays for one or more cells.

The FormattedHeadFile class is built on a record array consisting of headers, which are record arrays of the modflow header information (kstp, kper, pertim, totim, text, nrow, ncol, ilay) and long integers, which are pointers to first bytes of data for the corresponding data array.

FormattedHeadFile can only read formatted head files containing headers. Use the LABEL option in the output control file to generate head files with headers.

## Examples

```
>>> import floppy.utils.formattedfile as ff
>>> hdojb = ff.FormattedHeadFile('model.fhd', precision='single')
>>> hdojb.list_records()
>>> rec = hdojb.get_data(kstpkper=(1, 50))
>>> rec2 = ddnojb.get_data(totim=100.)
```

**class FormattedHeader**(*text\_ident*, *precision*='single')

Bases: *floppy.utils.datafile.Header*

The TextHeader class is a class to read in headers from MODFLOW formatted files.

### Parameters

- **type** (*text\_ident* is the text string in the header that identifies the) –
- **point** (of data (eg. 'head') precision is the precision of the floating) –
- **file** (data in the) –

**read\_header**(*text\_file*)

Read header information from a formatted file

### Parameters

- **of** (*text\_file* is an open file object currently at the beginning) –
- **header** (the) –

### Returns

- **out** (numpy array of header information)
- also stores the header's format string as *self.format\_string*

**class FormattedLayerFile**(*filename*, *precision*, *verbose*, *kwargs*)

Bases: *floppy.utils.datafile.LayerFile*

The FormattedLayerFile class is the super class from which specific derived classes are formed. This class should not be instantiated directly

**close**()

Close the file handle.

**get\_ts**(*idx*)

Get a time series from the formatted file.

**Parameters** *idx* (tuple of ints, or a list of a tuple of ints) – *idx* can be (layer, row, column) or it can be a list in the form [(layer, row, column), (layer, row, column), ...]. The layer, row, and column values must be zero based.

**Returns** *out* – Array has size (ntimes, ncells + 1). The first column in the data array will contain time (totim).

**Return type** numpy array

## Notes

The layer, row, and column values must be zero-based, and must be within the following ranges:  $0 \leq k < nlay$ ;  $0 \leq i < nrow$ ;  $0 \leq j < ncol$

## Examples

`is_float(s)`

`is_int(s)`

## flop.utils.geometry module

Container objects for working with geometric information

**class** `Collection(geometries=())`

Bases: `list`

The collection object is container for a group of flop geometries

This class acts as a base class for `MultiPoint`, `MultiLineString`, and `MultiPolygon` classes. This class can also accept a mix of geometries and act as a stand alone container.

**Parameters** `geometries` (*list*) – list of `flop.util.geometry` objects

**property** `bounds`

Method to calculate the bounding box of the collection

**Return type** tuple (xmin, ymin, xmax, ymax)

**plot**(*ax=None, \*\*kwargs*)

Plotting method for collection

**Parameters**

- **ax** (*matplotlib.axes object*) –
- **kwargs** (*keyword arguments*) – matplotlib keyword arguments

**Return type** matplotlib.axes object

**class** `LineString(coordinates)`

Bases: `flop.utils.geometry.Shape`

**property** `bounds`

**has\_z** = False

**plot**(*ax=None, \*\*kwargs*)

**property** `pyshp_parts`

**shapeType** = 3

**type** = 'LineString'

**property** `x`

**property** `y`

**property** `z`

**class** `MultiLineString(linestrings=())`

Bases: `flop.utils.geometry.Collection`

**Container for housing and describing multilinestring geometries (e.g. to be read or written to shapefiles or other geographic data formats)**

**polygons** [list] list of flopy.utils.geometry.LineString objects

**class MultiPoint**(*points=()*)

Bases: [flopy.utils.geometry.Collection](#)

**Container for housing and describing multipoint geometries (e.g. to be read or written to shapefiles or other geographic data formats)**

**polygons** [list] list of flopy.utils.geometry.Point objects

**class MultiPolygon**(*polygons=()*)

Bases: [flopy.utils.geometry.Collection](#)

**Container for housing and describing multipolygon geometries (e.g. to be read or written to shapefiles or other geographic data formats)**

**polygons** [list] list of flopy.utils.geometry.Polygon objects

**class Point**(*\*coordinates*)

Bases: [flopy.utils.geometry.Shape](#)

**property bounds**

**has\_z** = False

**plot**(*ax=None, \*\*kwargs*)

**property pyshp\_parts**

**shapeType** = 1

**type** = 'Point'

**property x**

**property y**

**property z**

**class Polygon**(*exterior, interiors=None*)

Bases: [flopy.utils.geometry.Shape](#)

**property bounds**

**get\_patch**(*\*\*kwargs*)

**property patch**

**plot**(*ax=None, \*\*kwargs*)

Plot the feature. :param ax: :type ax: matplotlib.pyplot axes instance :param Accepts keyword arguments to descartes.PolygonPatch. Requires the: :param descartes package (pip install descartes).:

**property pyshp\_parts**

**shapeType** = 5

**type** = 'Polygon'

**class Shape**(*shapetype, coordinates=None, exterior=None, interiors=None*)

Bases: object

Parent class for handling geo interfacing, do not instantiate directly

**type** [str] shapetype string

**coordinates** [list or tuple] list of tuple of point or linestring coordinates

**exterior** [list or tuple] 2d list of polygon coordinates

**interiors** [list or tuple] 2d or 3d list of polygon interiors

**static from\_geojson**(*geo\_interface*)

Method to load from geojson

**Parameters** **geo\_interface** (*geojson*, *dict*) – geojson compliant representation of a linestring

**Return type** *Polygon*, *LineString*, or *Point*

**property geojson**

**get\_polygon\_area**(*geom*)

Calculate the area of a closed polygon

**Parameters** **geom** (*geospatial representation of polygon*) – accepted types:

vertices np.array([(x, y),...]) geojson.Polygon shapely.Polygon shapefile.Shape

**Returns** **area** – area of polygon centroid

**Return type** float

**get\_polygon\_centroid**(*geom*)

Calculate the centroid of a closed polygon

**Parameters** **geom** (*geospatial representation of polygon*) – accepted types:

vertices np.array([(x, y),...]) geojson.Polygon shapely.Polygon shapefile.Shape

**Returns** **centroid** – (x, y) of polygon centroid

**Return type** tuple

**is\_clockwise**(\**geom*)

Determine if a ring is defined clockwise

**Parameters** **\*geom** (*geospatial representation of polygon*) – accepted types:

vertices [(x, y),...] geojson.Polygon shapely.Polygon shapefile.Shape x and y vertices: [x1, x2, x3], [y1, y2, y3]

**Returns** **clockwise** – True when the ring is defined clockwise, False otherwise

**Return type** bool

**point\_in\_polygon**(*xc, yc, polygon*)

Use the ray casting algorithm to determine if a point is within a polygon. Enables very fast intersection calculations!

**Parameters**

- **xc** (*np.ndarray*) – 2d array of xpoints
- **yc** (*np.ndarray*) – 2d array of ypoints
- **polygon** (*iterable (list)*) – polygon vertices [(x0, y0),...,(xn, yn)] note: polygon can be open or closed

**Returns** **mask** – True value means point is in polygon!

**Return type** np.array

**project\_point\_onto\_xc\_line**(*line, pts, d0=0, direction='x'*)

Method to project points onto a cross sectional line that is defined by distance. Used for plotting MODPATH results on to a cross section!

**line** [list or np.ndarray] numpy array of [(x0, y0), (x1, y1)] that defines the line to project on to

**pts** [list or np.ndarray] numpy array of [(x, y),] points to be projected

**d0** : distance offset along line of min(x1) **direction** : string

projection direction “x” or “y”



**Returns** np.ndarray of projected [(x, y),] points

**rotate**(x, y, xoff, yoff, angrot\_radians)

Given x and y array-like values calculate the rotation about an arbitrary origin and then return the rotated coordinates.

**transform**(x, y, xoff, yoff, angrot\_radians, length\_multiplier=1.0, inverse=False)

Given x and y array-like values calculate the translation about an arbitrary origin and then return the rotated coordinates.

## flopy.utils.geospatial\_utils module

**class GeoSpatialCollection**(obj, shapetype=None)

Bases: object

The GeoSpatialCollection class allows a user to convert between Collection objects from common geospatial libraries.

### Parameters

- **obj** (*collection object*) – obj can accept the following types  
 str : shapefile name shapefile.Reader object list of [shapefile.Shape, shapefile.Shape,] shapefile.Shapes object flopy.utils.geometry.Collection object list of [flopy.utils.geometry, ...] objects geojson.GeometryCollection object geojson.FeatureCollection object shapely.GeometryCollection object list of [[vertices], ...]  
 • **shapetype** (*list*) – optional list of shapetypes that is required when vertices are supplied to the class as the obj parameter

**property flopy\_geometry**

Property that returns a flopy.util.geometry.Collection object

**Return type** flopy.util.geometry.Collection object

**property geojson**

Property that returns a geojson.GeometryCollection object to the user

**Return type** geojson.GeometryCollection

**property points**

Property returns a multidimensional list of vertices

**Return type** list of vertices

**property shape**

Property that returns a shapefile.Shapes object

**Return type** shapefile.Shapes object

**property shapely**

Property that returns a shapely.geometry.collection.GeometryCollection object to the user

**Return type** shapely.geometry.collection.GeometryCollection object

**property shapetype**

Returns a list of shapetypes to the user

**Return type** list of str

**class GeoSpatialUtil**(obj, shapetype=None)

Bases: object

Geospatial utils are a unifying method to provide conversion between commonly used geospatial input types

**Parameters**

- **obj** (*geospatial object*) –

**obj can accept any of the following objects:** shapefile.Shape object  
flop.utils.geometry objects list of vertices geojson geometry objects  
shapely.geometry objects

- **shapetype** (*str*) – shapetype is required when a list of vertices is supplied for obj

**property flop\_geometry**

Returns a flop geometry object to the user

**Return type** flop.utils.geometry.<Shape>

**property geojson**

Returns a geojson object to the user

**Return type** geojson.<shape>

**property points**

Returns a list of vertices to the user

**Return type** list

**property shape**

Returns a shapefile.Shape object to the user

**Return type** shapefile.shape

**property shapely**

Returns a shapely.geometry object to the user

**Return type** shapely.geometry.<shape>

**property shapetype**

Shapetype string for a geometry

**Return type** str

## flop.utils.gridgen module

```
class Gridgen(dis, model_ws='.', exe_name='gridgen', surface_interpolation='replicate',  
              vertical_pass_through=False, **kwargs)
```

Bases: object

Class to work with the gridgen program to create layered quadtree grids.

**Parameters**

- **dis** (*flop.modflow.ModflowDis*) – Flop discretization object
- **model\_ws** (*str*) – workspace location for creating gridgen files (default is '.')
- **exe\_name** (*str*) – path and name of the gridgen program. (default is gridgen)
- **surface\_interpolation** (*str*) – Default gridgen method for interpolating elevations. Valid options include 'replicate' (default) and 'interpolate'
- **vertical\_pass\_through** (*bool*) – If true, Gridgen's GRID\_TO\_USGDATA command will connect layers where intermediate layers are inactive. (default is False)
- **\*\*kwargs** –

**vertical\_smoothing\_level** [int] maximum level difference between two vertically adjacent cells. Adjust with caution, as adjustments can cause unexpected results to simulated flows

**horizontal\_smoothing\_level** [int] maximum level difference between two horizontally adjacent cells. Adjust with caution, as adjustments can cause unexpected results to simulated flows

## Notes

For the surface elevations, the top of a layer uses the same surface as the bottom of the overlying layer.

**add\_active\_domain**(*feature, layers*)

### Parameters

- **feature** (*str* or *list*) –  
**feature can be:** a string containing the name of a polygon a list of polygons  
 flopy.utils.geometry.Collection object of Polygons shapely.geometry.Collection  
 object of Polygons geojson.GeometryCollection object of Polygons list of  
 shapefile.Shape objects shapefile.Shapes object
- **layers** (*list*) – A list of layers (zero based) for which this active domain applies.

**Return type** None

**add\_refinement\_features**(*features, featuretype, level, layers*)

### Parameters

- **features** (*str, list, or collection object*) –  
**features can be** a string containing the name of a shapefile a list of points, lines,  
 or polygons flopy.utils.geometry.Collection object a list of flopy.utils.geometry  
 objects shapely.geometry.Collection object geojson.GeometryCollection ob-  
 ject a list of shapefile.Shape objects shapefile.Shapes object
- **featuretype** (*str*) – Must be either ‘point’, ‘line’, or ‘polygon’
- **level** (*int*) – The level of refinement for this features
- **layers** (*list*) – A list of layers (zero based) for which this refinement features  
 applies.

**Return type** None

**build**(*verbose=False*)

Build the quadtree grid

**Parameters** **verbose** (*bool*) – If true, print the results of the gridgen command to the terminal (default is False)

**Return type** None

**export**(*verbose=False*)

Export the quadtree grid to shapefiles, usgdata, and vtk

**Parameters** **verbose** (*bool*) – If true, print the results of the gridgen command to the terminal (default is False)

**Return type** None

**get\_angldegx**(*fldr=None*)

Get the angldegx array

**Parameters** **fldr** (*ndarray*) – Flow direction indicator array. If None, then it is read from gridgen output.

**Returns** **angldegx** – A 1D vector indicating the angle (in degrees) between the x axis and an outward normal to the face.

**Return type** ndarray

**get\_area**()

Get the area array

**Returns** **area** – A 1D vector of cell areas of size nodes

**Return type** ndarray

**get\_bot**()

Get the bot array

**Returns** **bot** – A 1D vector of cell bottom elevations of size nodes

**Return type** ndarray

**get\_cellxy**(*ncells*)

**Parameters** **ncells** (*int*) – Number of cells for which to create the list of cell centers

**Returns** **cellxy** – x and y cell centers. Shape is (ncells, 2)

**Return type** ndarray

**get\_center**(*nodenumber*)

Return the cell center x and y coordinates

**Parameters** **nodenumber** –

**Returns** (**x**, **y**)

**Return type** tuple

**get\_cl12**()

Get the cl12 array

**Returns** **cl12** – A 1D vector of the cell connection distances, which are from the center of cell n to its shared face with cell m

**Return type** ndarray

**get\_disu**(*model, nper=1, perlen=1, nstp=1, tsmult=1, steady=True, ituni=4, lenuni=2*)

Create a MODFLOW-USG DISU flopy object.

**Parameters**

- **model** (*Flopy model object*) – The Flopy model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **nper** (*int*) – Number of model stress periods (default is 1).
- **perlen** (*float or array of floats (nper)*) – A single value or array of the stress period lengths (default is 1).
- **nstp** (*int or array of ints (nper)*) – Number of time steps in each stress period (default is 1).

- **tsmult** (*float or array of floats (nper)*) – Time step multiplier (default is 1.0).
- **steady** (*boolean or array of boolean (nper)*) – True or False indicating whether or not stress period is steady state (default is True).
- **itmuni** (*int*) – Time units, default is days (4)
- **lenuni** (*int*) – Length units, default is meters (2)

**Returns** **disu**

**Return type** Flopy ModflowDisU object.

**get\_fahl()**

Get the fahl array

**Returns** **fahl** – A 1D vector of the cell connection information, which is flow area for a vertical connection and horizontal length for a horizontal connection

**Return type** ndarray

**get\_fldr()**

Get the fldr array

**Returns** **fldr** – A 1D vector indicating the direction of the connection 1, 2, and 3 are plus x, y, and z directions. -1, -2, and -3 are negative x, y, and z directions.

**Return type** ndarray

**get\_gridprops\_disu5()**

Get a dictionary of information needed to create a MODFLOW-USG DISU Package. The returned dictionary can be unpacked directly into the ModflowDisU constructor. The ja dictionary entry will be returned as zero-based.

**Returns** **gridprops**

**Return type** dict

**get\_gridprops\_disu6(*repair\_asymmetry=True*)**

Get a dictionary of information needed to create a MODFLOW 6 DISU Package. The returned dictionary can be unpacked directly into the ModflowGwfdisu constructor.

**Parameters** **repair\_asymmetry** (*bool*) – MODFLOW 6 checks for symmetry in the hwva array, and round off errors in the floating point calculations can result in small errors. If this flag is true, then symmetry will be forced by setting the symmetric counterparts to the same value (the first one encountered).

**Returns** **gridprops**

**Return type** dict

**get\_gridprops\_disv()**

Get a dictionary of information needed to create a MODFLOW 6 DISV Package. The returned dictionary can be unpacked directly into the ModflowGwfdisv constructor.

**Returns** **gridprops**

**Return type** dict

**get\_gridprops\_unstructuredgrid()**

Get a dictionary of information needed to create a flopy UnstructuredGrid. The returned dictionary can be unpacked directly into the flopy.discretization.UnstructuredGrid() constructor.

**Returns** **gridprops**

**Return type** dict

**get\_gridprops\_vertexgrid()**

Get a dictionary of information needed to create a flopy VertexGrid. The returned dictionary can be unpacked directly into the flopy.discretization.VertexGrid() constructor.

**Returns** gridprops

**Return type** dict

**get\_hwva**(*ja=None, ihc=None, fahl=None, top=None, bot=None*)

Get the hwva array

**Parameters**

- **ja** (*ndarray*) – Cell connectivity. If None, it will be read from gridgen output.
- **ihc** (*ndarray*) – Connection horizontal indicator array. If None it will be read and calculated from gridgen output.
- **fahl** (*ndarray*) – Flow area, horizontal width array required by MODFLOW-USG. If none then it will be read from the gridgen output. Default is None.
- **top** (*ndarray*) – Cell top elevation. If None, it will be read from gridgen output.
- **bot** (*ndarray*) – Cell bottom elevation. If None, it will be read from gridgen output.

**Returns** **fahl** – A 1D vector of the cell connection information, which is flow area for a vertical connection and horizontal length for a horizontal connection

**Return type** ndarray

**get\_iac()**

Get the iac array

**Returns** **iac** – A 1D vector of the number of connections (plus 1) for each cell

**Return type** ndarray

**get\_ihc**(*nodelay=None, ia=None, fldr=None*)

Get the ihc array

**Parameters** **fldr** (*ndarray*) – Flow direction indicator array. If None, then it is read from gridgen output.

**Returns** **ihc** – A 1D vector indicating the direction of the connection where 0 is vertical, 1 is a regular horizontal connection and 2 is a vertically staggered horizontal connection.

**Return type** ndarray

**get\_ivc**(*fldr=None*)

Get the MODFLOW-USG ivc array

**Parameters** **fldr** (*ndarray*) – Flow direction indicator array. If None, then it is read from gridgen output.

**Returns** **ivc** – A 1D vector indicating the direction of the connection where 1 is vertical and 0 is horizontal.

**Return type** ndarray

**get\_ja**(*nja=None*)

Get the zero-based ja array

**Parameters** **nja** (*int*) – Number of connections. If None, then it is read from gridgen output.

**Returns** **ja** – A 1D vector of the cell connectivity (one-based)

**Return type** ndarray

**get\_nlay()**

Get the number of layers

**Returns** **nlay**

**Return type** int

**get\_nod\_reccarray()**

Load the qtg.nod file and return as a numpy recarray

**Returns** **node\_ra** – Recarray representation of the node file with zero-based indexing

**Return type** ndarray

**get\_nodelay()**

Return the nodelay array, which is an array of size nlay containing the number of nodes in each layer.

**Returns** **nodelay** – Number of nodes in each layer

**Return type** ndarray

**get\_nodes()**

Get the number of nodes

**Returns** **nodes**

**Return type** int

**get\_top()**

Get the top array

**Returns** **top** – A 1D vector of cell top elevations of size nodes

**Return type** ndarray

**get\_vertices(nodenumbr)**

Return a list of 5 vertices for the cell. The first vertex should be the same as the last vertex.

**Parameters** **nodenumbr** –

**Returns** **list of vertices**

**Return type** list

**get\_verts\_iverts(ncells, verbose=False)**

Return a 2d array of x and y vertices and a list of size ncells that has the list of vertices for each cell.

**Parameters**

- **ncells** (*int*) – The number of entries in iverts. This should be ncpl for a layered model and nodes for a disu model.
- **verbose** (*bool*) – Print information as its working

**Returns** **verts, iverts** – **verts** is a 2d array of x and y vertex pairs (nvert, 2) and **iverts** is a list of vertices that comprise each cell

**Return type** tuple

**static gridarray\_to\_flopyusg\_gridarray(nodelay, a)**

**intersect(features, featuretype, layer)**

**Parameters**

- **features** (*str* or *list*) – features can be either a string containing the name of a shapefile or it can be a list of points, lines, or polygons
- **featuretype** (*str*) – Must be either ‘point’, ‘line’, or ‘polygon’
- **layer** (*int*) – Layer (zero based) to intersect with. Zero based.

**Returns** **result** – Recarray of the intersection properties.

**Return type** `np.recarray`

**plot**(*ax=None, layer=0, edgecolor='k', facecolor='none', cmap='Dark2', a=None, masked\_values=None, \*\*kwargs*)

Plot the grid. This method will plot the grid using the shapefile that was created as part of the build method.

Note that the layer option is not working yet.

#### Parameters

- **ax** (*matplotlib.pyplot axis*) – The plot axis. If not provided it, `plt.gca()` will be used. If there is not a current axis then a new one will be created.
- **layer** (*int*) – Layer number to plot
- **cmap** (*string*) – Name of colormap to use for polygon shading (default is ‘Dark2’)
- **edgecolor** (*string*) – Color name. (Default is ‘scaled’ to scale the edge colors.)
- **facecolor** (*string*) – Color name. (Default is ‘scaled’ to scale the face colors.)
- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **kwargs** (*dictionary*) – Keyword arguments that are passed to `PatchCollection.set(**kwargs)`. Some common kwargs would be ‘linewidths’, ‘linestyles’, ‘alpha’, etc.

**Returns** **pc**

**Return type** `matplotlib.collections.PatchCollection`

**set\_surface\_interpolation**(*isurf, type, elev=None, elev\_extent=None*)

#### Parameters

- **isurf** (*int*) – surface number where 0 is top and `nlay + 1` is bottom
- **type** (*str*) – Must be ‘INTERPOLATE’, ‘REPLICATE’ or ‘ASCIIGRID’.
- **elev** (*numpy.ndarray of shape (nr, nc) or str*) – Array that is used as an ascii grid. If `elev` is a string, then it is assumed to be the name of the ascii grid.
- **elev\_extent** (*list-like*) – List of `xmin`, `xmax`, `ymin`, `ymax` extents of the `elev` grid. Must be specified for ASCIIGRID; optional otherwise.

**Return type** `None`

**features\_to\_shapefile**(*features, featuretype, filename*)

Write a shapefile for the features of type `featuretype`.

#### Parameters

- **features** (*list*) – point, line, or polygon features. Method accepts feature can be:



a list of geometries `flop.utils.geometry.Collection` object  
`shapely.geometry.Collection` object `geojson.GeometryCollection` object  
 list of `shapefile.Shape` objects `shapefile.Shapes` object

- **featuretype** (*str*) – Must be ‘point’, ‘line’, ‘linestring’, or ‘polygon’
- **filename** (*string*) – name of the shapefile to write

**Return type** `None`

**get\_ia\_from\_iac**(*iac*)

**get\_isym**(*ia*, *ja*)

**is\_symmetrical**(*isym*, *a*, *atol*=0)

**ndarray\_to\_asciigrid**(*fname*, *a*, *extent*, *nodata*=1e+30)

**readld**(*f*, *a*)

Quick file to array reader for reading gridgen output. Much faster than the `readld` function in `util_array`

**repair\_array\_asymmetry**(*isym*, *a*, *atol*=0)

## flop.utils.gridintersect module

**class** `GridIntersect`(*mfgrid*, *method*=None, *rtree*=True)

Bases: `object`

Class for intersecting shapely shapes (Point, Linestring, Polygon, or their Multi variants) with MODFLOW grids. Contains optimized search routines for structured grids.

## Notes

- The STR-tree query is based on the bounding box of the shape or collection, if the bounding box of the shape covers nearly the entire grid, the query won’t be able to limit the search space much, resulting in slower performance. Therefore, it can sometimes be faster to intersect each individual shape in a collection than it is to intersect with the whole collection at once.
- Building the STR-tree can take a while for large grids. Once built the intersect routines (for individual shapes) should be pretty fast. It is possible to perform intersects without building the STR-tree by setting *rtree*=False.
- The optimized routines for structured grids will often outperform the shapely routines because of the reduced overhead of building and parsing the STR-tree. However, for polygons the STR-tree implementation is often faster than the optimized structured routines, especially for larger grids.

**static** `filter_query_result`(*qresult*, *shp*)

Filter query result to obtain grid cells that intersect with shape. Used to (further) reduce query result to cells that definitely intersect with shape.

### Parameters

- **qresult** (*iterable*) – query result, iterable of polygons
- **shp** (*shapely.geometry*) – shapely geometry that is prepared and used to filter query result

**Returns** filter or generator containing polygons that intersect with shape

**Return type** `qfiltered`

**intersect**(*shp*, *shapetype*=None, *sort\_by\_cellid*=True, *keepzerolengths*=False)

Method to intersect a shape with a model grid.

**Parameters**

- **shp** (*shapely.geometry, geojson object, shapefile.Shape,*) – or flop geometry object
- **shapetype** (*str, optional*) – type of shape (i.e. “point”, “linestring”, “polygon” or their multi-variants), used by GeoSpatialUtil if shp is passed as a list of vertices, default is None
- **sort\_by\_cellid** (*bool*) – sort results by cellid, ensures cell with lowest cellid is returned for boundary cases when using vertex methods, default is True
- **keepzerolengths** (*bool*) – boolean method to keep zero length intersections for linestring intersection, used when shp is of type “linestring”

**Returns** a record array containing information about the intersection

**Return type** `numpy.recarray`

**intersects**(*shp, shapetype=None*)

Return cellIDs for shapes that intersect with shape.

**Parameters**

- **shp** (*shapely.geometry, geojson geometry, shapefile.shape,*) – or flop geometry object shape to intersect with the grid
- **shapetype** (*str, optional*) – type of shape (i.e. “point”, “linestring”, “polygon” or their multi-variants), used by GeoSpatialUtil if shp is passed as a list of vertices, default is None

**Returns** **rec** – a record array containing cell IDs of the gridcells the shape intersects with

**Return type** `numpy.recarray`

**static plot\_linestring**(*rec, ax=None, cmap=None, \*\*kwargs*)

method to plot the linestring intersection results from the resulting `numpy.recarray`.

Note: only works when `recarray` has ‘intersects’ column!

**Parameters**

- **rec** (*numpy.recarray*) – record array containing intersection results (the resulting shapes)
- **ax** (*matplotlib.pyplot.axes, optional*) – axes to plot onto, if not provided, creates a new figure
- **cmap** (*str*) – matplotlib colormap
- **\*\*kwargs** – passed to the plot function

**Returns** **ax** – returns the axes handle

**Return type** `matplotlib.pyplot.axes`

**static plot\_point**(*rec, ax=None, \*\*kwargs*)

method to plot the point intersection results from the resulting `numpy.recarray`.

Note: only works when `recarray` has ‘intersects’ column!

**Parameters**

- **rec** (*numpy.recarray*) – record array containing intersection results
- **ax** (*matplotlib.pyplot.axes, optional*) – axes to plot onto, if not provided, creates a new figure

- **\*\*kwargs** – passed to the scatter function

**Returns** **ax** – returns the axes handle

**Return type** matplotlib.pyplot.axes

**static plot\_polygon**(*rec, ax=None, \*\*kwargs*)

method to plot the polygon intersection results from the resulting numpy.recarray.

Note: only works when recarray has 'intersects' column!

**Parameters**

- **rec** (*numpy.recarray*) – record array containing intersection results (the resulting shapes)
- **ax** (*matplotlib.pyplot.axes, optional*) – axes to plot onto, if not provided, creates a new figure
- **\*\*kwargs** – passed to the plot function

**Returns** **ax** – returns the axes handle

**Return type** matplotlib.pyplot.axes

**query\_grid**(*shp*)

Perform spatial query on grid with shapely geometry. If no spatial query is possible returns all grid cells.

**Parameters** **shp** (*shapely.geometry*) – shapely geometry

**Returns** list or generator containing grid cells in query result

**Return type** list or generator expression

**static sort\_gridshapes**(*shape\_iter*)

Sort query result by node id.

**Parameters** **shape\_iter** (*iterable*) – list or iterable of gridcells

**Returns** sorted list of gridcells

**Return type** list

**class ModflowGridIndices**

Bases: object

Collection of methods that can be used to find cell indices for a structured, but irregularly spaced MODFLOW grid.

**static find\_position\_in\_array**(*arr, x*)

If arr has x positions for the left edge of a cell, then return the cell index containing x.

**Parameters**

- **arr** (*A one dimensional array (such as Xe) that contains*) – coordinates for the left cell edge.
- **x** (*float*) – The x position to find in arr.

**static kij\_from\_nn0**(*n, nlay, nrow, ncol*)

Convert the node number to a zero-based layer, row and column format. Return (k0, i0, j0).

**Parameters**

- **nodenumber** (*int*) – The cell nodenumber, ranging from 0 to number of nodes - 1.
- **nlay** (*int*) – The number of layers.

- **nrow** (*int*) – The number of rows.
- **ncol** (*int*) – The number of columns.

**static kij\_from\_nodenum**(*nodenum*, *nlay*, *nrow*, *ncol*)

Convert the modflow node number to a zero-based layer, row and column format. Return (k0, i0, j0).

**Parameters**

- **nodenum** (*int*) – The cell nodenum, ranging from 1 to number of nodes.
- **nlay** (*int*) – The number of layers.
- **nrow** (*int*) – The number of rows.
- **ncol** (*int*) – The number of columns.

**static nn0\_from\_kij**(*k*, *i*, *j*, *nrow*, *ncol*)

Calculate the zero-based nodenum using the zero-based layer, row, and column values. The first node has a value of 0.

**Parameters**

- **k** (*int*) – The model layer number as a zero-based value.
- **i** (*int*) – The model row number as a zero-based value.
- **j** (*int*) – The model column number as a zero-based value.
- **nrow** (*int*) – The number of model rows.
- **ncol** (*int*) – The number of model columns.

**static nodenum\_from\_kij**(*k*, *i*, *j*, *nrow*, *ncol*)

Calculate the nodenum using the zero-based layer, row, and column values. The first node has a value of 1.

**Parameters**

- **k** (*int*) – The model layer number as a zero-based value.
- **i** (*int*) – The model row number as a zero-based value.
- **j** (*int*) – The model column number as a zero-based value.
- **nrow** (*int*) – The number of model rows.
- **ncol** (*int*) – The number of model columns.

**ignore\_shapely\_warnings\_for\_object\_array()**

**parse\_shapely\_ix\_result**(*collection*, *ix\_result*, *shptyps=None*)

Recursive function for parsing shapely intersection results. Returns a list of shapely shapes matching shptyp.

**Parameters**

- **collection** (*list*) – state variable for storing result, generally an empty list
- **ix\_result** (*shapely.geometry type*) – any shapely intersection result
- **shptyp** (*str, list of str, or None, optional*) – if None (default), return all types of shapes. if str, return shapes of that type, if list of str, return all types in list

**Returns** **collection** – list containing shapely geometries of type shptyp

**Return type** list

**flopy.utils.lgrutil module**

**class Lgr**(*nlayp, nrowp, ncolp, delrp, delcp, topp, botmp, idomainp, ncpp=3, ncpl=1, xllp=0.0, yllp=0.0*)

Bases: object

**get\_delr\_delc**()

**get\_exchange\_data**(*angledegx=False, cdist=False*)

Get the list of parent/child connections

<cellidm1> <cellidm2> <ihc> <cl1> <cl2> <hwva> <angledegx>

**Returns** **exglist** – list of connections between parent and child

**Return type** list

**get\_idomain**()

Return the idomain array for the child model. This will normally be all ones unless the idomain array for the parent model is non-rectangular and irregularly shaped. Then, parts of the child model will have idomain zero cells.

**Returns** **idomain** – idomain array for the child model

**Return type** ndarray

**get\_lower\_left**()

Return the lower left corner of the child grid

**Returns** (**xll**, **yll**) – location of lower left corner of the child grid

**Return type** tuple

**get\_parent\_connections**(*kc, ic, jc*)

Return a list of parent cell indices that are connected to child cell kc, ic, jc.

**get\_parent\_indices**(*kc, ic, jc*)

Method returns the parent cell indices for this child. The returned indices are in zero-based indexing.

**get\_replicated\_parent\_array**(*parent\_array*)

Get a two-dimensional array the size of the child grid that has values replicated from the provided parent array.

**Parameters** **parent\_array** (*ndarray*) – A two-dimensional array that is the size of the parent model rows and columns.

**Returns** **child\_array** – A two-dimensional array that is the size of the child model rows and columns

**Return type** ndarray

**get\_shape**()

Return the shape of the child grid

**Returns** (**nlay**, **nrow**, **ncol**) – shape of the child grid

**Return type** tuple

**get\_top\_botm**()

## flop.utils.mflistfile module

This is a set of classes for reading budget information out of MODFLOW-style listing files. Cumulative and incremental budgets are returned as numpy recarrays, which can then be easily plotted.

**class ListBudget**(*file\_name*, *budgetkey=None*, *timeunit='days'*)

Bases: object

MODFLOW family list file handling

### Parameters

- **file\_name** (*str*) – the list file name
- **budgetkey** (*str*) – the text string identifying the budget table. (default is None)
- **timeunit** (*str*) – the time unit to return in the recarray. (default is 'days')

### Notes

The ListBudget class should not be instantiated directly. Access is through derived classes: MfListBudget (MODFLOW), SwtListBudget (SEAWAT) and SwrListBudget (MODFLOW with the SWR process)

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> incremental, cumulative = mf_list.get_budget()
>>> df_in, df_out = mf_list.get_dataframes(start_datetime="10-21-2015")
```

**get\_budget**(*names=None*)

Get the recarrays with the incremental and cumulative water budget items in the list file.

**Parameters** **names** (*str or list of strings*) – Selection of column names to return. If names is not None then totim, time\_step, stress\_period, and selection(s) will be returned. (default is None).

**Returns** **out** – Numpy recarrays with the water budget items in list file. The recarray also includes totim, time\_step, and stress\_period. A separate recarray is returned for the incremental and cumulative water budget entries.

**Return type** recarrays

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> budget = mf_list.get_budget()
```

**get\_cumulative**(*names=None*)

Get a recarray with the cumulative water budget items in the list file.

**Parameters** **names** (*str or list of strings*) – Selection of column names to return. If names is not None then totim, time\_step, stress\_period, and selection(s) will be returned. (default is None).

**Returns** **out** – Numpy recarray with the water budget items in list file. The recarray also includes totim, time\_step, and stress\_period.

**Return type** recarray

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> cumulative = mf_list.get_cumulative()
```

**get\_data**(*kstpkper=None, idx=None, totim=None, incremental=False*)

Get water budget data from the list file for the specified conditions.

#### Parameters

- **idx** (*int*) – The zero-based record number. The first record is record 0. (default is None).
- **kstpkper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). These are zero-based kstp and kper values. (default is None).
- **totim** (*float*) – The simulation time. (default is None).
- **incremental** (*bool*) – Boolean flag used to determine if incremental or cumulative water budget data for the specified conditions will be returned. If incremental=True, incremental water budget data will be returned. If incremental=False, cumulative water budget data will be returned. (default is False).

**Returns data** – Array has size (number of budget items, 3). Recarray names are 'index', 'value', 'name'.

**Return type** numpy recarray

### Notes

if both kstpkper and totim are None, will return the last entry

### Examples

```
>>> import matplotlib.pyplot as plt
>>> import flopy
>>> mf_list = flopy.utils.MfListBudget("my_model.list")
>>> data = mf_list.get_data(kstpkper=(0,0))
>>> plt.bar(data['index'], data['value'])
>>> plt.xticks(data['index'], data['name'], rotation=45, size=6)
>>> plt.show()
```

**get\_dataframes**(*start\_datetime='1-1-1970', diff=False*)

Get pandas dataframes with the incremental and cumulative water budget items in the list file.

**Parameters start\_datetime** (*str*) – If start\_datetime is passed as None, the rows are indexed on totim. Otherwise, a DatetimeIndex is set. (default is 1-1-1970).

**Returns out** – Pandas dataframes with the incremental and cumulative water budget items in list file. A separate pandas dataframe is returned for the incremental and cumulative water budget entries.

**Return type** pandas dataframes

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> incrementaldf, cumulativdf = mf_list.get_dataframes()
```

#### **get\_incremental** (*names=None*)

Get a recarray with the incremental water budget items in the list file.

**Parameters** **names** (*str or list of strings*) – Selection of column names to return. If names is not None then totim, time\_step, stress\_period, and selection(s) will be returned. (default is None).

**Returns out** – Numpy recarray with the water budget items in list file. The recarray also includes totim, time\_step, and stress\_period.

**Return type** recarray

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> incremental = mf_list.get_incremental()
```

#### **get\_kstpkper** ()

Get a list of unique stress periods and time steps in the list file water budgets.

**Returns out** – List of unique kstp, kper combinations in list file. kstp and kper values are zero-based.

**Return type** list of (kstp, kper) tuples

### Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> kstpkper = mf_list.get_kstpkper()
```

#### **get\_model\_runtime** (*units='seconds'*)

Get the elapsed runtime of the model from the list file.

**Parameters** **units** (*str*) – Units in which to return the runtime. Acceptable values are 'seconds', 'minutes', 'hours' (default is 'seconds')

**Returns out** – Floating point value with the runtime in requested units. Returns NaN if runtime not found in list file

**Return type** float



## Examples

```
>>> mf_list = MfListBudget("my_model.list")
>>> budget = mf_list.get_model_runtime(units='hours')
```

### get\_record\_names()

Get a list of water budget record names in the file.

**Returns out** – List of unique text names in the binary file.

**Return type** list of strings

## Examples

```
>>> mf_list = MfListBudget('my_model.list')
>>> names = mf_list.get_record_names()
```

### get\_reduced\_pumping()

Get numpy recarray of reduced pumping data from a list file. Reduced pumping data most have been written to the list file during the model run. Works with MfListBudget and MfusgListBudget.

**Returns** A numpy recarray with the reduced pumping data from the list file.

**Return type** numpy recarray

## Example

```
>>> objLST = MfListBudget("my_model.lst")
>>> raryReducedPpg = objLST.get_reduced_pumping()
>>> dfReducedPpg = pd.DataFrame.from_records(raryReducedPpg)
```

### get\_times()

Get a list of unique water budget times in the list file.

**Returns out** – List contains unique water budget simulation times (totim) in list file.

**Return type** list of floats

## Examples

```
>>> mf_list = MfListBudget('my_model.list')
>>> times = mf_list.get_times()
```

### isvalid()

Get a boolean indicating if budget data are available in the file.

**Returns out** – Boolean indicating if budget data are available in the file.

**Return type** boolean

## Examples

```
>>> mf_list = MfListBudget('my_model.list')
>>> valid = mf_list.isvalid()
```

**set\_budget\_key()**

**class Mf6ListBudget**(*file\_name, budgetkey=None, timeunit='days'*)  
Bases: *flop.utils.mflistfile.ListBudget*

**set\_budget\_key()**

**class MfListBudget**(*file\_name, budgetkey=None, timeunit='days'*)  
Bases: *flop.utils.mflistfile.ListBudget*

**set\_budget\_key()**

**class MfusgListBudget**(*file\_name, budgetkey=None, timeunit='days'*)  
Bases: *flop.utils.mflistfile.ListBudget*

**set\_budget\_key()**

**class SwrListBudget**(*file\_name, budgetkey=None, timeunit='days'*)  
Bases: *flop.utils.mflistfile.ListBudget*

**set\_budget\_key()**

**class SwtListBudget**(*file\_name, budgetkey=None, timeunit='days'*)  
Bases: *flop.utils.mflistfile.ListBudget*

**set\_budget\_key()**

## flop.utils.mfreadnam module

mfreadnam module. Contains the NamData class. Note that the user can access the NamData class as *flop.modflow.NamData*.

Additional information about the MODFLOW name file can be found at the [Online MODFLOW Guide](#).

**class NamData**(*pkgtype, name, handle, packages*)  
Bases: object

MODFLOW Namefile Class.

### Parameters

- **pkgtype** (*string*) – String identifying the type of MODFLOW package. See the *mf-nam\_packages* dictionary keys in the model object for a list of supported packages. This dictionary is also passed in as *packages*.
- **name** (*string*) – Filename of the package file identified in the name file
- **handle** (*file handle*) – File handle referring to the file identified by *name*
- **packages** (*dictionary*) – Dictionary of package objects as defined in the *mf-nam\_packages* attribute of *flop.modflow.mf.Modflow*.

### filehandle

File handle to the package file. Read from *handle*.

**Type** file handle

### filename

Filename of the package file identified in the name file. Read from *name*.

**Type** string

**filetype**

String identifying the type of MODFLOW package. Read from *pkgtype*.

**Type** string

**package**

Package type. Only assigned if *pkgtype* is found in the keys of *packages*

**Type** string

**Notes**

**Examples**

**attrs\_from\_namfile\_header**(*namefile*)

**getfiletypeunit**(*nf*, *filetype*)

Method to return unit number of a package from a NamData instance

**Parameters**

- **nf** (*NamData instance*) –
- **filetype** (*string, name of package seeking information for*) –

**Returns** *cunit*

**Return type** int, unit number corresponding to the package type

**parsenamefile**(*namfilename*, *packages*, *verbose=True*)

Returns dict from the nam file with NamData keyed by unit number

**Parameters**

- **namefilename** (*str*) – Name of the MODFLOW namefile to parse.
- **packages** (*dict*) – Dictionary of package objects as defined in the *mfnam\_packages* attribute of *flopY.modflow.mf.Modflow*.
- **verbose** (*bool*) – Print messages to screen. Default is True.

**Returns** For each file listed in the name file, a *flopY.utils.mfreadnam.NamData* instance is stored in the returned dict keyed by unit number.

**Return type** dict

**Raises**

- **FileNotFoundError** – If *namfilename* does not exist in the directory.
- **ValueError** – For lines that cannot be parsed.

## flop.utils.modpathfile module

Module to read MODPATH output files. The module contains two important classes that can be accessed by the user.

- EndpointFile (ascii endpoint file)
- PathlineFile (ascii pathline file)

**class** `EndpointFile(filename, verbose=False)`

Bases: object

EndpointFile Class.

### Parameters

- **filename** (*string*) – Name of the endpoint file
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Examples

```
>>> import flop
>>> endobj = flop.utils.EndpointFile('model.mpend')
>>> e1 = endobj.get_data(partid=1)
```

### get\_alldata()

Get endpoint data from the endpoint file for all endpoints.

**Returns** **ra** – A numpy recarray with the endpoint particle data

**Return type** numpy record array

## Notes

## Examples

```
>>> import flop
>>> endobj = flop.utils.EndpointFile('model.mpend')
>>> e = endobj.get_alldata()
```

### get\_data(partid=0)

Get endpoint data from the endpoint file for a single particle.

**Parameters** **partid** (*int*) – The zero-based particle id. The first record is record 0. (default is 0)

**Returns** **ra** – A numpy recarray with the endpoint particle data for endpoint partid.

**Return type** numpy record array

## Notes

## Examples

```
>>> import flopy
>>> endobj = flopy.utils.EndpointFile('model.mpend')
>>> e1 = endobj.get_data(partid=1)
```

**get\_destination\_endpoint\_data**(*dest\_cells*, *source=False*)

Get endpoint data that terminate in a set of destination cells.

### Parameters

- **dest\_cells** (*list or array of tuples*) – (k, i, j) of each destination cell for MODPATH versions less than MODPATH 7 or node number of each destination cell. (zero based)
- **source** (*bool*) – Boolean to specify if dest\_cells applies to source or destination cells (default is False).

**Returns** **epdest** – Slice of endpoint data array (e.g. EndpointFile.get\_alldata) containing only endpoint data with final locations in (k,i,j) or (node) dest\_cells.

**Return type** np.recarray

## Examples

```
>>> import flopy
>>> e = flopy.utils.EndpointFile('modpath.endpoint')
>>> e0 = e.get_destination_endpoint_data([(0, 0, 0),
...                                     (1, 0, 0)])
```

**get\_maxid**()

Get the maximum endpoint particle id in the file endpoint file

**Returns** **out** – Maximum endpoint particle id.

**Return type** int

**get\_maxtime**()

Get the maximum time in the endpoint file

**Returns** **out** – Maximum endpoint time.

**Return type** float

**get\_maxtraveltime**()

Get the maximum travel time in the endpoint file

**Returns** **out** – Maximum endpoint travel time.

**Return type** float

**kijnames** = ['k0', 'i0', 'j0', 'node0', 'k', 'i', 'j', 'node', 'particleid', 'particlegroup', 'particleidloc', 'zone0', 'zone']

**write\_shapefile**(*endpoint\_data=None*, *shpname='endpoints.shp'*, *direction='ending'*, *mg=None*, *epsg=None*, *\*\*kwargs*)

Write particle starting / ending locations to shapefile.

**endpoint\_data** [np.recarray] Record array of same form as that returned by EndpointFile.get\_alldata. (if none, EndpointFile.get\_alldata() is exported).

**shpname** [str] File path for shapefile

**direction** [str] String defining if starting or ending particle locations should be considered. (default is 'ending')

**mg** [flop.discretization.grid instance] Used to scale and rotate Global x,y,z values in MODPATH Endpoint file.

**epsg** [int] EPSG code for writing projection (.prj) file. If this is not supplied, the proj4 string or epsg code associated with mg will be used.

kwargs : keyword arguments to flop.export.shapefile\_utils.reccarray2shp

**class PathlineFile**(filename, verbose=False)

Bases: flop.utils.modpathfile.\_ModpathSeries

PathlineFile Class.

#### Parameters

- **filename** (*string*) – Name of the pathline file
- **verbose** (*bool*) – Write information to the screen. Default is False.

### Examples

```
>>> import flop
>>> pthobj = flop.utils.PathlineFile('model.mppth')
>>> p1 = pthobj.get_data(partid=1)
```

**get\_alldata**(totim=None, ge=True)

get pathline data from the pathline file for all pathlines and all times.

#### Parameters

- **totim** (*float*) – The simulation time. All pathline points for particle partid that are greater than or equal to (ge=True) or less than or equal to (ge=False) totim will be returned. Default is None
- **ge** (*bool*) – Boolean that determines if pathline times greater than or equal to or less than or equal to totim is used to create a subset of pathlines. Default is True.

**Returns** **plist** – A list of numpy recarrays with the x, y, z, time, k, and particleid for all pathlines.

**Return type** a list of numpy record array

### Examples

```
>>> import flop.utils.modpathfile as mpf
>>> pthobj = flop.utils.PathlineFile('model.mppth')
>>> p = pthobj.get_alldata()
```

**get\_data**(partid=0, totim=None, ge=True)

get pathline data from the pathline file for a single pathline.

#### Parameters

- **partid** (*int*) – The zero-based particle id. The first record is record 0.
- **totim** (*float*) – The simulation time. All pathline points for particle partid that are greater than or equal to (*ge=True*) or less than or equal to (*ge=False*) totim will be returned. Default is None
- **ge** (*bool*) – Boolean that determines if pathline times greater than or equal to or less than or equal to totim is used to create a subset of pathlines. Default is True.

**Returns** **ra** – A numpy recarray with the x, y, z, time, k, and particleid for pathline partid.

**Return type** numpy record array

## Notes

## Examples

```
>>> import flopY.utils.modpathfile as mpf
>>> pthobj = flopY.utils.PathlineFile('model.mppth')
>>> p1 = pthobj.get_data(partid=1)
```

**get\_destination\_pathline\_data**(*dest\_cells, to\_reccarray=False*)

Get pathline data that pass through a set of destination cells.

### Parameters

- **dest\_cells** (*list or array of tuples*) – (k, i, j) of each destination cell for MODPATH versions less than MODPATH 7 or node number of each destination cell. (zero based)
- **to\_reccarray** (*bool*) – Boolean that controls returned pthldest. If to\_reccarray is True, a single recarray with all of the pathlines that intersect dest\_cells are returned. If to\_reccarray is False, a list of recarrays (the same form as returned by get\_alldata method) that intersect dest\_cells are returned (default is False).

**Returns** **pthldest** – Slice of pathline data array (e.g. PathlineFile.\_data) containing only pathlines that pass through (k,i,j) or (node) dest\_cells.

**Return type** np.recarray

## Examples

```
>>> import flopY
>>> p = flopY.utils.PathlineFile('modpath.pathline')
>>> p0 = p.get_destination_pathline_data([(0, 0, 0),
...                                     (1, 0, 0)])
```

**get\_maxid**()

Get the maximum pathline number in the file pathline file

**Returns** **out** – Maximum pathline number.

**Return type** int

**get\_maxtime**()

Get the maximum time in pathline file

**Returns** **out** – Maximum pathline time.

**Return type** float

```
kijnames = ['k', 'i', 'j', 'node', 'particleid', 'particlegroup',  
'linesegmentindex', 'particleidloc', 'sequencenumber']
```

```
write_shapefile(pathline_data=None, one_per_particle=True, direction='ending',  
                shpname='pathlines.shp', mg=None, epsg=None, **kwargs)
```

Write pathlines to a shapefile

**pathline\_data** [np.recarray] Record array of same form as that returned by PathlineFile.get\_alldata(). (if none, PathlineFile.get\_alldata() is exported).

**one\_per\_particle** [boolean (default True)] True writes a single LineString with a single set of attribute data for each particle. False writes a record/geometry for each pathline segment (each row in the PathLine file). This option can be used to visualize attribute information (time, model layer, etc.) across a pathline in a GIS.

**direction** [str] String defining if starting or ending particle locations should be included in shapefile attribute information. Only used if one\_per\_particle=False. (default is 'ending')

**shpname** [str] File path for shapefile

**mg** [flop.discretization.grid instance] Used to scale and rotate Global x,y,z values in MODPATH Pathline file.

**epsg** [int] EPSG code for writing projection (.prj) file. If this is not supplied, the proj4 string or epsg code associated with mg will be used.

kwargs : keyword arguments to flop.export.shapefile\_utils.reccarray2shp

```
class TimeseriesFile(filename, verbose=False)
```

Bases: flop.utils.modpathfile.\_ModpathSeries

TimeseriesFile Class.

#### Parameters

- **filename** (*string*) – Name of the timeseries file
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Examples

```
>>> import flop  
>>> tsobj = flop.utils.TimeseriesFile('model.timeseries')  
>>> ts1 = tsobj.get_data(partid=1)
```

```
get_alldata(totim=None, ge=True)
```

get timeseries data from the timeseries file for all timeseries and all times.

#### Parameters

- **totim** (*float*) – The simulation time. All timeseries points for timeseries partid that are greater than or equal to (ge=True) or less than or equal to (ge=False) totim will be returned. Default is None
- **ge** (*bool*) – Boolean that determines if timeseries times greater than or equal to or less than or equal to totim is used to create a subset of timeseries. Default is True.

**Returns** **tlist** – A list of numpy recarrays with the x, y, z, time, k, and particleid for all timeseries.

**Return type** a list of numpy record array



## Examples

```
>>> import flopy
>>> tsobj = flopy.utils.TimeseriesFile('model.timeseries')
>>> ts = tsobj.get_alldata()
```

**get\_data**(*partid=0, totim=None, ge=True*)

get timeseries data from the timeseries file for a single timeseries particleid.

### Parameters

- **partid** (*int*) – The zero-based particle id. The first record is record 0.
- **totim** (*float*) – The simulation time. All timeseries points for particle partid that are greater than or equal to (*ge=True*) or less than or equal to (*ge=False*) totim will be returned. Default is None
- **ge** (*bool*) – Boolean that determines if timeseries times greater than or equal to or less than or equal to totim is used to create a subset of timeseries. Default is True.

**Returns** *ra* – A numpy recarray with the x, y, z, time, k, and particleid for timeseries partid.

**Return type** numpy record array

## Notes

## Examples

```
>>> import flopy
>>> tsobj = flopy.utils.TimeseriesFile('model.timeseries')
>>> ts1 = tsobj.get_data(partid=1)
```

**get\_destination\_timeseries\_data**(*dest\_cells*)

Get timeseries data that pass through a set of destination cells.

**Parameters** *dest\_cells* (*list or array of tuples*) – (k, i, j) of each destination cell for MODPATH versions less than MODPATH 7 or node number of each destination cell. (zero based)

**Returns** *tsdest* – Slice of timeseries data array (e.g. *TmeseriesFile.\_data*) containing only timeseries that pass through (k,i,j) or (node) *dest\_cells*.

**Return type** np.recarray

## Examples

```
>>> import flopy
>>> ts = flopy.utils.TimeseriesFile('modpath.timeseries')
>>> tss = ts.get_destination_timeseries_data([(0, 0, 0),
...                                         (1, 0, 0)])
```

**get\_maxid**()

Get the maximum timeseries number in the file timeseries file

**Returns** *out* – Maximum pathline number.

**Return type** int

**get\_maxtime()**

Get the maximum time in timeseries file

**Returns out** – Maximum pathline time.

**Return type** float

**kijnames** = ['k', 'i', 'j', 'node', 'particleid', 'particlegroup', 'particleidloc', 'timestep', 'timestepindex', 'timepointindex']

**write\_shapefile**(*timeseries\_data=None, one\_per\_particle=True, direction='ending', shpname='pathlines.shp', mg=None, epsg=None, \*\*kwargs*)

Write pathlines to a shapefile

**timeseries\_data** [np.recarray] Record array of same form as that returned by Timeseries.get\_alldata(). (if none, Timeseries.get\_alldata() is exported).

**one\_per\_particle** [boolean (default True)] True writes a single LineString with a single set of attribute data for each particle. False writes a record/geometry for each pathline segment (each row in the Timeseries file). This option can be used to visualize attribute information (time, model layer, etc.) across a pathline in a GIS.

**direction** [str] String defining if starting or ending particle locations should be included in shapefile attribute information. Only used if one\_per\_particle=False. (default is 'ending')

**shpname** [str] File path for shapefile

**mg** [flop.discretization.grid instance] Used to scale and rotate Global x,y,z values in MODPATH Timeseries file.

**epsg** [int] EPSG code for writing projection (.prj) file. If this is not supplied, the proj4 string or epsg code associated with mg will be used.

**kwargs** : keyword arguments to flop.export.shapefile\_utils.reccarray2shp

## flop.utils.mtlistfile module

This is a class for reading the mass budget from a (multi-component) mt3d(usgs) run. Also includes support for SFT budget.

**class MtListBudget**(*file\_name*)

Bases: object

MT3D mass budget reader

**Parameters** **file\_name** (*str*) – the list file name

## Examples

```
>>> mt_list = MtListBudget("my_mt3d.list")
>>> incremental, cumulative = mt_list.get_budget()
>>> gw_df, sw_df = mt_list.parse(start_datetime="10-21-2015")
```

**parse**(*forgive=True, diff=True, start\_datetime=None, time\_unit='d'*)

Main entry point for parsing the list file.

**Parameters**

- **forgive** (*bool*) – flag to raise exceptions when fail-to-read occurs. Default is True

- **diff** (*bool*) – flag to return dataframes with ‘in minus out’ columns. Default is True
- **start\_datetime** (*str*) – str that can be parsed by pandas.to\_datetime. Example: ‘1-1-1970’. Default is None.
- **time\_unit** (*str*) – str to pass to pandas.to\_timedelta. Default is ‘d’ (days)

**Returns** **df\_gw,df\_sw** – a dataframe for the groundwater mass and (optionally) surface-water mass budget. If the SFT process is not used, df\_sw is None.

**Return type** pandas.DataFrame

## flop.utils.observationfile module

**class** **CsvFile**(*csvfile, delimiter=','*)

Bases: object

Class for reading csv based output files

### Parameters

- **csvfile** (*str*) – csv file name
- **delimiter** (*str*) – optional delimiter for the csv or formatted text file, defaults to “,”

**property** **nobs**

Method to get the number of observations

**Return type** int

**property** **obsnames**

Method to get the observation names

**Return type** list

**static** **read\_csv**(*fobj, dtype, delimiter=','*)

### Parameters

- **fobj** (*file object*) – open text file object to read
- **dtype** (*np.dtype*) –
- **delimiter** (*str*) – optional delimiter for the csv or formatted text file, defaults to “,”

**Return type** np.recarray

**class** **HydmodObs**(*filename, verbose=False, hydlbl\_len=20*)

Bases: [flop.utils.observationfile.ObsFiles](#)

HydmodObs Class - used to read binary MODFLOW HYDMOD package output

### Parameters

- **filename** (*str*) – Name of the hydmod output file
- **verbose** (*boolean*) – If true, print additional information to the screen during the extraction. (default is False)
- **hydlbl\_len** (*int*) – Length of hydmod labels. (default is 20)

**Return type** None

**class** `Mf6Obs`(*filename*, *verbose*=False, *isBinary*='auto')

Bases: `flopY.utils.observationfile.ObsFiles`

Mf6Obs Class - used to read ascii and binary MODFLOW6 observation output

#### Parameters

- **filename** (*str*) – Name of the hydmod output file
- **verbose** (*boolean*) – If true, print additional information to the screen during the extraction. (default is False)
- **isBinary** (*str*, *bool*) – default is “auto”, code will attempt to automatically check if file is binary. User can change this to True or False if the auto check fails to work

**Return type** None

**class** `ObsFiles`

Bases: `flopY.utils.utils_def.FlopYBinaryData`

**get\_data**(*idx*=None, *obsname*=None, *totim*=None)

Get data from the observation file.

#### Parameters

- **idx** (*int*) – The zero-based record number. The first record is record 0. If idx is None and totim are None, data for all simulation times are returned. (default is None)
- **obsname** (*string*) – The name of the observation to return. If obsname is None, all observation data are returned. (default is None)
- **totim** (*float*) – The simulation time to return. If idx is None and totim are None, data for all simulation times are returned. (default is None)

**Returns** **data** – Array has size (ntimes, nitens). totim is always returned. nitens is 2 if idx or obsname is not None or nobs+1.

**Return type** numpy record array

#### Notes

If both idx and obsname are None, will return all of the observation data.

#### Examples

```
>>> hyd = HydmodObs("my_model.hyd")
>>> ts = hyd.get_data()
```

**get\_dataframe**(*start\_datetime*='1-1-1970', *idx*=None, *obsname*=None, *totim*=None, *timeunit*='D')

Get pandas dataframe with the incremental and cumulative water budget items in the hydmod file.

#### Parameters

- **start\_datetime** (*str*) – If start\_datetime is passed as None, the rows are indexed on totim. Otherwise, a DatetimeIndex is set. (default is 1-1-1970).
- **idx** (*int*) – The zero-based record number. The first record is record 0. If idx is None and totim are None, a dataframe with all simulation times is returned. (default is None)

- **obsname** (*string*) – The name of the observation to return. If obsname is None, all observation data are returned. (default is None)
- **totim** (*float*) – The simulation time to return. If idx is None and totim are None, a dataframe with all simulation times is returned. (default is None)
- **timeunit** (*string*) – time unit of the simulation time. Valid values are ‘S’econds, ‘M’inutes, ‘H’ours, ‘D’ays, ‘Y’ears. (default is ‘D’).

**Returns out** – Pandas dataframe of selected data.

**Return type** pandas dataframe

## Notes

If both idx and obsname are None, will return all of the observation data as a dataframe.

## Examples

```
>>> hyd = HydmodObs("my_model.hyd")
>>> df = hyd.get_dataframes()
```

### get\_nobs()

Get the number of observations in the file

**Returns out** – A tupe with the number of records and number of flow items in the file. The number of flow items is non-zero only if swrtype=‘flow’.

**Return type** tuple of int

### get\_ntimes()

Get the number of times in the file

**Returns out** – The number of simulation times (totim) in binary file.

**Return type** int

### get\_obsnames()

Get a list of observation names in the file

**Returns out** – List of observation names in the binary file. totim is not included in the list of observation names.

**Return type** list of strings

### get\_times()

Get a list of unique times in the file

**Returns out** – List contains unique simulation times (totim) in binary file.

**Return type** list of floats

**class SwrObs**(*filename*, *precision*=‘double’, *verbose*=False)

Bases: [flop.utils.observationfile.ObsFiles](#)

Read binary SWR observations output from MODFLOW SWR Process observation files

#### Parameters

- **filename** (*string*) – Name of the cell budget file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.

- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flopY
>>> so = flopY.utils.SwrObs('mymodel.swr.obs')
```

**get\_reduced\_pumping**(*f*, *structured=True*)

Method to read reduced pumping from a list file or an external reduced pumping observation file

### Parameters

- **f** (*str*) – file name
- **structured** (*bool*) – boolean flag to indicate if model is Structured or USG model. Defaults to True (structured grid).

**Returns** *np.recarray*

**Return type** recarray of reduced pumping records.

**get\_selection**(*data*, *names*)

### Parameters

- **data** (*numpy recarray*) – recarray of data to make a selection from
- **names** (*string or list of strings*) – column names to return

**Returns** *out* – recarray with selection

**Return type** numpy recarray

## flopY.utils.optionblock module

**class OptionBlock**(*options\_line*, *package*, *block=True*)

Bases: object

Parent class to for option blocks within Modflow-nwt models. This class contains base information and routines that can be shared throughout all option block classes.

### Parameters

- **options\_line** (*str*) – single line based options string
- **package** (*flopY.pakbase.Package instance*) – valid packages include ModflowWel, ModflowSfr2, ModflowUzf1
- **block** (*bool*) – flag to write as single line or block type

**dtype** = 'dtype'

**classmethod load\_options**(*options*, *package*)

Loader for the options class. Reads in an options block and uses context from option util dictionaries to check the validity of the data

### Parameters

- **options** (*str or file*) – string path to a file or file object

- **package** (*flop.package type*) – valid packages include flop.modflow.ModflowWel, flop.modflow.ModflowSfr2

**Return type** OptionBlock object

**n\_nested** = 'nvars'

**nested** = 'nested'

**optional** = 'optional'

**simple\_flag** = {'dtype': <class 'numpy.bool\_'>, 'nested': False, 'optional': False}

**simple\_float** = {'dtype': <class 'float'>, 'nested': False, 'optional': False}

**simple\_int** = {'dtype': <class 'int'>, 'nested': False, 'optional': False}

**simple\_str** = {'dtype': <class 'str'>, 'nested': False, 'optional': False}

**simple\_tabfile** = {'dtype': <class 'numpy.bool\_'>, 'nested': True, 'nvars': 2, 'vars': {'maxval': {'dtype': <class 'int'>, 'nested': False, 'optional': False}, 'numtab': {'dtype': <class 'int'>, 'nested': False, 'optional': False}}}

**property single\_line\_options**

Method to get the single line representation of the Options Block

**Returns** t

**Return type** (str) single line representation of Options

**update\_from\_package**(*pak*)

Updater method to check the package and update OptionBlock attribute values based on package values.

**Parameters** **pak** (*flop.package*) – valid packages include ModflowWel, ModflowSfr2, and ModflowUzf1 instances

**vars** = 'vars'

**write\_options**(*f*)

Method to write the options block or options line to an open file object.

**Parameters**

**f** [file, str] open file object, or path to file

**class OptionUtil**

Bases: object

**static isfloat**(*s*)

Simple method to check that a string is a valid floating point variable

**Parameters** **s** (*str*) –

**Return type** bool

**static isint**(*s*)

Simple data check method to check that a string is a valid integer

**Parameters** **s** (*str*) –

**Return type** bool

**static isvalid**(*dtype, val*)

Check to see if a dtype is valid before setting as an attribute

**Parameters**

- **dtype** (*type*) – int, float, str, bool, etc...
- **val** (*string*) –

**Return type** bool

### flop.utils.parse\_version module

#### exception InvalidVersion

Bases: ValueError

An invalid version was found, users should refer to PEP 440.

#### class LegacyVersion(*version: str*)

Bases: flop.utils.parse\_version.\_BaseVersion

**property** base\_version: str

**property** dev: None

**property** epoch: int

**property** is\_devrelease: bool

**property** is\_postrelease: bool

**property** is\_prerelease: bool

**property** local: None

**property** post: None

**property** pre: None

**property** public: str

**property** release: None

#### class Version(*version: str*)

Bases: flop.utils.parse\_version.\_BaseVersion

**property** base\_version: str

**property** dev: int | None

**property** epoch: int

**property** is\_devrelease: bool

**property** is\_postrelease: bool

**property** is\_prerelease: bool

**property** local: str | None

**property** major: int

**property** micro: int

**property** minor: int

**property** post: int | None

**property** pre: tuple[str, int] | None

**property** public: str

**property** release: tuple[int, ...]



**parse**(*version: str*) → *LegacyVersion* | *Version*

Parse the given version string and return either a *Version* object or a *LegacyVersion* object depending on if the given version is a valid PEP 440 version or a legacy version.

## flop.utils.postprocessing module

**get\_extended\_budget**(*cbcfile*, *precision='single'*, *idx=None*, *kstpker=None*, *totim=None*,  
*boundary\_ifaces=None*, *hdsfile=None*, *model=None*)

Get the flow rate across cell faces including potential stresses applied along boundaries at a given time. Only implemented for “classical” MODFLOW versions where the budget is recorded as FLOW RIGHT FACE, FLOW FRONT FACE and FLOW LOWER FACE arrays.

### Parameters

- **cbcfile** (*str*) – Cell by cell file produced by Modflow.
- **precision** (*str*) – Binary file precision, default is ‘single’.
- **idx** (*int* or *list*) – The zero-based record number.
- **kstpker** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). The kstp and kper values are zero based.
- **totim** (*float*) – The simulation time.
- **boundary\_ifaces** (*dictionary {str: int or list}*) – A dictionary defining how to treat stress flows at boundary cells. The keys are budget terms corresponding to stress packages (same term as in the overall volumetric budget printed in the listing file). The values are either a single iface number to be applied to all cells for the stress package, or a list of lists describing individual boundary cells in the same way as in the package input plus the iface number appended. The iface number indicates the face to which the stress flow is assigned, following the MODPATH convention (see MODPATH user guide). Example: `boundary_ifaces = { 'RECHARGE': 6, 'RIVER LEAKAGE': 6, 'CONSTANT HEAD': [[lay, row, col, iface], ...], 'WELLS': [[lay, row, col, flux, iface], ...], 'HEAD DEP BOUNDS': [[lay, row, col, head, cond, iface], ...]}`. Note: stresses that are not informed in `boundary_ifaces` are implicitly treated as internally-distributed sinks/sources.
- **hdsfile** (*str*) – Head file produced by MODFLOW (only required if `boundary_ifaces` is used).
- **model** (*flop.modflow.Modflow object*) – Modflow model instance (only required if `boundary_ifaces` is used).

**Returns** (**Qx\_ext**, **Qy\_ext**, **Qz\_ext**) – Flow rates across cell faces. `Qx_ext` is a ndarray of size (nlay, nrow, ncol + 1). `Qy_ext` is a ndarray of size (nlay, nrow + 1, ncol). The sign is such that the y axis is considered to increase in the north direction. `Qz_ext` is a ndarray of size (nlay + 1, nrow, ncol). The sign is such that the z axis is considered to increase in the upward direction.

**Return type** tuple

**get\_gradients**(*heads*, *m*, *nodata*, *per\_idx=None*)

Calculates the hydraulic gradients from the heads array for each stress period.

### Parameters

- **heads** (3 or 4-D *np.ndarray*) – Heads array.
- **m** (*flop.modflow.Modflow object*) – Must have a `flop.modflow.ModflowDis` object attached.
- **nodata** (*real*) – HDRY value indicating dry cells.

- **per\_idx** (*int or sequence of ints*) – stress periods to return. If None, returns all stress periods (default).

**Returns** **grad** – Array of hydraulic gradients

**Return type** 3 or 4-D np.ndarray

**get\_specific\_discharge**(*vectors, model, head=None, position='centers'*)

Get the discharge vector at cell centers at a given time. For “classical” MODFLOW versions, we calculate it from the flow rate across cell faces. For MODFLOW 6, we directly take it from MODFLOW output (this requires setting the option “save\_specific\_discharge” in the NPF package).

**Parameters**

- **vectors** (*tuple, np.recarray*) – either a tuple of (flow right face, flow front face, flow lower face) numpy arrays from a MODFLOW-2005 compatible Cell Budget File or a specific discharge recarray from a MODFLOW 6 Cell Budget File
- **model** (*object*) – flopY model object
- **head** (*np.ndarray*) – numpy array of head values for a specific model position : str  
Position at which the specific discharge will be calculated. Possible values are “centers” (default), “faces” and “vertices”.

**Returns** (**qx, qy, qz**) – Discharge vector. qx, qy, qz are ndarrays of size (nlay, nrow, ncol) for a structured grid or size (nlay, ncol) for an unstructured grid. The sign of qy is such that the y axis is considered to increase in the north direction. The sign of qz is such that the z axis is considered to increase in the upward direction. Note: if a head array is provided, inactive and dry cells are set to NaN.

**Return type** tuple

**get\_transmissivities**(*heads, m, r=None, c=None, x=None, y=None, sctop=None, scbot=None, nodata=- 999*)

Computes transmissivity in each model layer at specified locations and open intervals. A saturated thickness is determined for each row, column or x, y location supplied, based on the open interval (sctop, scbot), if supplied, otherwise the layer tops and bottoms and the water table are used.

**Parameters**

- **heads** (*2D array OR 3D array*) – numpy array of shape nlay by n locations (2D) OR complete heads array of the model for one time (3D)
- **m** (*flopY.modflow.Modflow object*) – Must have dis and lpf or upw packages.
- **r** (*1D array-like of ints, of length n locations*) – row indices (optional; alternately specify x, y)
- **c** (*1D array-like of ints, of length n locations*) – column indices (optional; alternately specify x, y)
- **x** (*1D array-like of floats, of length n locations*) – x locations in real world coordinates (optional)
- **y** (*1D array-like of floats, of length n locations*) – y locations in real world coordinates (optional)
- **sctop** (*1D array-like of floats, of length n locations*) – open interval tops (optional; default is model top)
- **scbot** (*1D array-like of floats, of length n locations*) – open interval bottoms (optional; default is model bottom)
- **nodata** (*numeric*) – optional; locations where heads=nodata will be assigned T=0

**Returns** **T** – Transmissivities in each layer at each location

**Return type** 2D array of same shape as heads (nlay x n locations)

**get\_water\_table**(heads, nodata, per\_idx=None)

Get a 2D array representing the water table elevation for each stress period in heads array.

**Parameters**

- **heads** (3 or 4-D *np.ndarray*) – Heads array.
- **nodata** (*real*) – HDRY value indicating dry cells.
- **per\_idx** (*int or sequence of ints*) – stress periods to return. If None, returns all stress periods (default is None).

**Returns** **wt** – for each stress period.

**Return type** 2 or 3-D *np.ndarray* of water table elevations

## flop.utils.rasters module

**class Raster**(array, bands, crs, transform, nodataval, driver='GTiff', rio\_ds=None)

Bases: object

The Raster object is used for cropping, sampling raster values, and re-sampling raster values to grids, and provides methods to plot rasters and histograms of raster digital numbers for visualization and analysis purposes.

**Parameters**

- **array** (*np.ndarray*) – a three dimensional array of raster values with dimensions defined by (raster band, nrow, ncol)
- **bands** (*tuple*) – a tuple of raster bands
- **crs** (*int, string, rasterio.crs.CRS object*) – either a epsg code, a proj4 string, or a CRS object
- **transform** (*affine.Affine object*) – affine object, which is used to define geometry
- **nodataval** (*float*) – raster no data value
- **rio\_ds** (*DatasetReader object*) – rasterIO dataset Reader object

## Notes

## Examples

```
>>> from flop.utils import Raster
>>>
>>> rio = Raster.load("myraster.tif")
```

```
FLOAT32 = (<class 'float'>, <class 'numpy.float32'>, <class 'numpy.float64'>)
```

```
FLOAT64 = (<class 'numpy.float64'>,)

```

```
INT16 = (<class 'numpy.int16'>, <class 'numpy.uint16'>)
```

```
INT32 = (<class 'int'>, <class 'numpy.int32'>, <class 'numpy.uint32'>, <class
'numpy.uint64'>, <class 'numpy.uint32'>, <class 'numpy.uint32'>)
```

```
INT64 = (<class 'numpy.int64'>, <class 'numpy.uint64'>)
```

```
INT8 = (<class 'numpy.int8'>, <class 'numpy.uint8'>)
```

**property bands**

Returns a tuple of raster bands

**property bounds**

Returns a tuple of xmin, xmax, ymin, ymax boundaries

**crop**(*polygon*, *invert=False*)

Method to crop a new raster object from the current raster object

**Parameters**

- **polygon** (*list*, *geojson*, *shapely.geometry*, *shapefile.Shape*) – crop method accepts any of these geometries:

a list of (x, y) points, ex. [(x1, y1), ...] geojson Polygon object shapely Polygon object shapefile Polygon shape flop Polygon shape

- **invert** (*bool*) – Default value is False. If invert is True then the area inside the shapes will be masked out

**get\_array**(*band*, *masked=True*)

Method to get a numpy array corresponding to the provided raster band. Nodata vals are set to np.NaN

**Parameters**

- **band** (*int*) – band number from the raster
- **masked** (*bool*) – determines if nodatavals will be returned as np.nan to the user

**Return type** np.ndarray

**histogram**(*ax=None*, *\*\*kwargs*)

Method to plot a histogram of digital numbers

**Parameters**

- **ax** (*matplotlib.pyplot.axes*) – optional matplotlib axes for plotting
- **\*\*kwargs** – matplotlib keyword arguments see matplotlib documentation for valid arguments for histogram

**Returns** *ax*

**Return type** matplotlib.pyplot.axes

**static load**(*raster*)

Static method to load a raster file into the raster object

**Parameters** **raster** (*str*) –

**Return type** Raster object

**property nodatavals**

Returns a Tuple of values used to define no data

**plot**(*ax=None*, *contour=False*, *\*\*kwargs*)

Method to plot raster layers or contours.

**Parameters**

- **ax** (*matplotlib.pyplot.axes*) – optional matplotlib axes for plotting
- **contour** (*bool*) – flag to indicate creation of contour plot
- **\*\*kwargs** – matplotlib keyword arguments see matplotlib documentation for valid arguments for plot and contour.

**Returns** ax**Return type** matplotlib.pyplot.axes

**resample\_to\_grid**(*modelgrid*, *band*, *method*='nearest', *multithread*=False, *thread\_pool*=2, *extrapolate\_edges*=False)

Method to resample the raster data to a user supplied grid of x, y coordinates.

x, y coordinate arrays should correspond to grid vertices

**Parameters**

- **modelgrid** (*flop*.Grid object) – model grid to sample data from
- **band** (*int*) – raster band to re-sample
- **method** (*str*) – scipy interpolation methods  
     linear for bi-linear interpolation  
     nearest for nearest neighbor  
     cubic for bi-cubic interpolation  
     mean for mean sampling  
     median for median sampling  
     min for minimum sampling  
     max for maximum sampling
- **multithread** (*bool*) – boolean flag indicating if multithreading should be used with the mean and median sampling methods
- **thread\_pool** (*int*) – number of threads to use for mean and median sampling
- **extrapolate\_edges** (*bool*) – boolean flag indicating if areas without data should be filled using the nearest interpolation method. This option has no effect when using the nearest interpolation method.

**Return type** np.array

**sample\_point**(\**point*, *band*=1)

Method to get nearest raster value at a user provided point

**Parameters**

- **\*point** (*point geometry representation*) – accepted data types: x, y values  
     : ex. sample\_point(1, 3, band=1) tuple of x, y: ex sample\_point((1, 3), band=1)  
     shapely.geometry.Point geojson.Point flop.geometry.Point
- **band** (*int*) – raster band to re-sample

**Returns** value**Return type** float

**sample\_polygon**(*polygon*, *band*, *invert*=False, *\*\*kwargs*)

Method to get an unordered list of raster values that are located within a arbitrary polygon

**Parameters**

- **polygon** (*list*, *geojson*, *shapely.geometry*, *shapefile.Shape*) – sample\_polygon method accepts any of these geometries:  
     a list of (x, y) points, ex. [(x1, y1), ...] geojson Polygon object shapely Polygon object shapefile Polygon shape flop Polygon shape

- **band** (*int*) – raster band to re-sample
- **invert** (*bool*) – Default value is False. If invert is True then the area inside the shapes will be masked out

**Return type** np.ndarray of unordered raster values

**write**(*name*)

Method to write raster data to a .tif file

**Parameters** **name** (*str*) – output raster .tif file name

**property** **xcenters**

Returns a np.ndarray of raster x cell centers

**property** **ycenters**

Returns a np.ndarray of raster y cell centers

## flopy.utils.reccarray\_utils module

**create\_empty\_reccarray**(*length, dtype, default\_value=0*)

Create a empty reccarray with a defined default value for floats.

**Parameters**

- **length** (*int*) – Shape of the empty reccarray.
- **dtype** (*np.dtype*) – dtype of the empty reccarray.
- **default\_value** (*float*) – default value to use for floats in reccarray.

**Returns** **r** – Recarray of type dtype with shape length.

**Return type** np.reccarray

## Examples

```
>>> import numpy as np
>>> import flopy
>>> dtype = np.dtype([('x', np.float32), ('y', np.float32)])
>>> ra = flopy.utils.create_empty_reccarray(10, dtype)
```

**ra\_slice**(*ra, cols*)

Create a slice of a reccarray

**Parameters**

- **ra** (*np.reccarray*) – reccarray to extract a limited number of columns from.
- **cols** (*list of str*) – List of key names to extract from ra.

**Returns** **ra\_slice** – Slice of ra

**Return type** np.reccarray

## Examples

```
>>> import flopy
>>> raslice = flopy.utils.ra_slice(ra, ['x', 'y'])
```

### recarray(array, dtype)

Convert a list of lists or tuples to a recarray.

#### Parameters

- **array** (*list of lists*) – list of lists containing data to convert to a recarray. The number of entries in each list in the list must be the same.
- **dtype** (*np.dtype*) – dtype of the array data

**Returns** **r** – Recarray of type dtype with shape equal to the length of array.

**Return type** np.recarray

## Examples

```
>>> import numpy as np
>>> import flopy
>>> dtype = np.dtype([('x', np.float32), ('y', np.float32)])
>>> arr = [(1., 2.), (10., 20.), (100., 200.)]
>>> ra = flopy.utils.recarray(arr, dtype)
```

## flopy.utils.reference module

Module spatial referencing for flopy model objects

**class** **TemporalReference**(*itmuni=4, start\_datetime=None*)

Bases: object

For now, just a container to hold start time and time units files outside of DIS package.

**defaults** = {'itmuni': 4, 'start\_datetime': '01-01-1970'}

**itmuni\_text** = {0: 'undefined', 1: 'seconds', 2: 'minutes', 3: 'hours', 4: 'days', 5: 'years'}

**itmuni\_values** = {'days': 4, 'hours': 3, 'minutes': 2, 'seconds': 1, 'undefined': 0, 'years': 5}

**property** **model\_time\_units**

## flopy.utils.sfroutputfile module

**class** **SfrFile**(*filename, geometries=None, verbose=False*)

Bases: object

Read SFR package results from text file (ISTCB2 > 0)

#### Parameters

- **filename** (*str*) – Name of the sfr output file
- **geometries** (*any*) – Ignored

- **verbose** (*any*) – Ignored

## Notes

Indexing starts at one for: layer, row, column, segment, reach. Indexing starts at zero for: i, j, k, and kstpker.

## Examples

```
>>> import flop
>>> sfq = flop.utils.SfrFile('mymodel.sfq')
```

**property df**

**dtypes** = {'column': <class 'int'>, 'layer': <class 'int'>, 'reach': <class 'int'>, 'row': <class 'int'>, 'segment': <class 'int'>}

**get\_dataframe()**

Read the whole text file into a pandas dataframe.

**Returns df** – SFR output as a pandas dataframe

**Return type** pandas dataframe

**static get\_nstrm(df)**

Get the number of SFR cells from the results dataframe.

**Returns nrch** – Number of SFR cells

**Return type** int

**get\_results(segment, reach)**

Get results for a single reach or sequence of segments and reaches.

**Parameters**

- **segment** (*int or sequence of ints*) – Segment number for each location.
- **reach** (*int or sequence of ints*) – Reach number for each location

**Returns results** – Dataframe of same format as SfrFile.df, but subset to input locations.

**Return type** dataframe

**get\_times()**

Parse the stress period/timestep headers.

**Returns kstpker** – list of kstp, kper tuples

**Return type** tuple



## **flopy.utils.swroutputfile module**

**class** `SwrBudget`(*filename*, *precision*='double', *verbose*=False)

Bases: `flopy.utils.swroutputfile.SwrFile`

Read binary SWR budget output from MODFLOW SWR Process binary output files

### **Parameters**

- **filename** (*string*) – Name of the swr budget output file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

### **Notes**

### **Examples**

```
>>> import flopy
>>> stageobj = flopy.utils.SwrStage('mymodel.swr.bud')
```

**class** `SwrExchange`(*filename*, *precision*='double', *verbose*=False)

Bases: `flopy.utils.swroutputfile.SwrFile`

Read binary SWR surface-water groundwater exchange output from MODFLOW SWR Process binary output files

### **Parameters**

- **filename** (*string*) – Name of the swr surface-water groundwater exchange output file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

### **Notes**

### **Examples**

```
>>> import flopy
>>> stageobj = flopy.utils.SwrStage('mymodel.swr.qaq')
```

**class** `SwrFile`(*filename*, *swrtype*='stage', *precision*='double', *verbose*=False)

Bases: `flopy.utils.utils_def.FlopyBinaryData`

Read binary SWR output from MODFLOW SWR Process binary output files The SwrFile class is the super class from which specific derived classes are formed. This class should not be instantiated directly

### **Parameters**

- **filename** (*string*) – Name of the swr output file
- **swrtype** (*str*) – swr data type. Valid data types are ‘stage’, ‘budget’, ‘flow’, ‘exchange’, or ‘structure’. (default is ‘stage’)
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flop
>>> so = flop.utils.SwrFile('mymodel.swr.stage.bin')
```

### get\_connectivity()

Get connectivity data from the file.

**Returns** **data** – Array has size (nrecord, 3). None is returned if swrtype is not ‘flow’

**Return type** numpy array

## Notes

## Examples

### get\_data(idx=None, kswrkstpkiper=None, totim=None)

Get data from the file for the specified conditions.

#### Parameters

- **idx** (*int*) – The zero-based record number. The first record is record 0. (default is None)
- **kswrkstpkiper** (*tuple of ints*) – A tuple containing the swr time step, time step, and stress period (kswr, kstp, kper). These are zero-based kswr, kstp, and kper values. (default is None)
- **totim** (*float*) – The simulation time. (default is None)

**Returns** **data** – Array has size (nitems).

**Return type** numpy record array

## Notes

if both kswrkstpkiper and totim are None, will return the last entry

## Examples

### get\_kswrkstpkiper()

Get a list of unique stress periods, time steps, and swr time steps in the file

**Returns** **out** – List of unique kswr, kstp, kper combinations in binary file. kswr, kstp, and kper values are zero-based.

**Return type** list of (kswr, kstp, kper) tuples

### get\_nrecords()

Get the number of records in the file

**Returns** **out** – A tupe with the number of records and number of flow items in the file. The number of flow items is non-zero only if swrtype=‘flow’.

**Return type** tuple of int

**get\_ntimes()**

Get the number of times in the file

**Returns out** – The number of simulation times (totim) in binary file.

**Return type** int

**get\_record\_names()**

Get a list of unique record names in the file

**Returns out** – List of unique text names in the binary file.

**Return type** list of strings

**get\_times()**

Get a list of unique times in the file

**Returns out** – List contains unique simulation times (totim) in binary file.

**Return type** list of floats

**get\_ts(irec=0, iconn=0, klay=0, istr=0)**

Get a time series from a swr binary file.

**Parameters**

- **irec** (*int*) – is the zero-based reach (stage, qm, qaq) or reach group number (budget) to retrieve. (default is 0)
- **iconn** (*int*) – is the zero-based connection number for reach (irch) to retrieve qm data. iconn is only used if qm data is being read. (default is 0)
- **klay** (*int*) – is the zero-based layer number for reach (irch) to retrieve qaq data . klay is only used if qaq data is being read. (default is 0)
- **klay** – is the zero-based structure number for reach (irch) to retrieve structure data . isrt is only used if structure data is being read. (default is 0)

**Returns out** – Array has size (ntimes, nitens). The first column in the data array will contain time (totim). nitens is 2 for stage data, 15 for budget data, 3 for qm data, and 11 for qaq data.

**Return type** numpy recarray

**Notes**

The irec, iconn, and klay values must be zero-based.

**Examples**

```
class SwrFlow(filename, precision='double', verbose=False)
```

Bases: [flopY.utils.swroutputfile.SwrFile](#)

Read binary SWR flow output from MODFLOW SWR Process binary output files

**Parameters**

- **filename** (*string*) – Name of the swr flow output file
- **precision** (*string*) – ‘single’ or ‘double’. Default is ‘double’.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flopy
>>> stageobj = flopy.utils.SwrStage('mymodel.swr.flow')
```

**class SwrStage**(filename, precision='double', verbose=False)

Bases: *flopy.utils.swroutputfile.SwrFile*

Read binary SWR stage output from MODFLOW SWR Process binary output files

### Parameters

- **filename** (*string*) – Name of the swr stage output file
- **precision** (*string*) – 'single' or 'double'. Default is 'double'.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flopy
>>> stageobj = flopy.utils.SwrStage('mymodel.swr.stg')
```

**class SwrStructure**(filename, precision='double', verbose=False)

Bases: *flopy.utils.swroutputfile.SwrFile*

Read binary SWR structure output from MODFLOW SWR Process binary output files

### Parameters

- **filename** (*string*) – Name of the swr structure output file
- **precision** (*string*) – 'single' or 'double'. Default is 'double'.
- **verbose** (*bool*) – Write information to the screen. Default is False.

## Notes

## Examples

```
>>> import flopy
>>> stageobj = flopy.utils.SwrStage('mymodel.swr.str')
```

**flop.utils.triangle module**

**class Triangle**(*model\_ws='.', exe\_name='triangle', maximum\_area=None, angle=20.0, nodes=None, additional\_args=None*)

Bases: object

Class to work with the triangle program to unstructured triangular grids. Information on the triangle program can be found at <https://www.cs.cmu.edu/~quake/triangle.html>

**Parameters**

- **model\_ws** (*str*) – workspace location for creating triangle files (default is '.')
- **exe\_name** (*str*) – path and name of the triangle program. (default is triangle, which means that the triangle program must be in your path)
- **maximum\_area** (*float*) – the maximum area for any triangle. The default value is None, which means that the user must specify maximum areas for each region.
- **angle** (*float*) – Triangle will continue to add vertices until no angle is less than this specified value. (default is 20 degrees)
- **nodes** (*ndarray*) – Two dimensional array of shape (npoints, 2) with x and y positions of fixed node locations to include in the resulting triangular mesh. (default is None)
- **additional\_args** (*list*) – list of additional command line switches to pass to triangle

**Return type** None

**add\_hole**(*hole*)

Add a point that will turn enclosing polygon into a hole

**Parameters** **hole** (*tuple*) – (x, y)

**Return type** None

**add\_polygon**(*polygon*)

Add a polygon

**Parameters** **polygon** (*list, geojson, shapely.geometry, shapefile.Shape*) – add polygon method accepts any of these geometries:

a list of (x, y) points geojson Polygon object shapely Polygon object shapefile Polygon shape flop.utils.geometry.Polygon object

**Return type** None

**add\_region**(*point, attribute=0, maximum\_area=None*)

Add a point that will become a region with a maximum area, if specified.

**Parameters**

- **point** (*tuple*) – (x, y)
- **attribute** (*integer or float*) – integer value assigned to output elements
- **maximum\_area** (*float*) – maximum area of elements in region

**Return type** None

**build**(*verbose=False*)

Build the triangular mesh

**Parameters** **verbose** (*bool*) – If true, print the results of the triangle command to the terminal (default is False)

**Return type** None

**clean()**

Remove the input and output files created by this class and by the Triangle program

**Return type** None

**get\_attribute\_array()**

Return an array containing the attribute value for each cell. These are the attribute values that are passed into the `add_region()` method.

**Returns** `attribute_array`

**Return type** ndarray

**get\_boundary\_marker\_array()**

Get an integer array that has boundary markers

**Returns** `iedge` – integer array of size `ncpl` containing a boundary ids. The array contains zeros for cells that do not touch a boundary. The boundary ids are the segment numbers for each segment in each polygon that is added with the `add_polygon` method.

**Return type** ndarray

**get\_cell2d()**

Get a list of the information needed for the MODFLOW DISV Package.

**Returns** `cell2d` – innermost list contains cell number, x, y, number of vertices, and then the vertex numbers comprising the cell.

**Return type** list (of lists)

**get\_cell\_edge\_length(*n*, *ibm*)**

Get the length of the edge for cell *n* that corresponds to boundary marker *ibm*

**Parameters**

- ***n*** (*int*) – cell number.  $0 \leq n < \text{self.ncpl}$
- ***ibm*** (*integer*) – boundary marker number

**Returns** `length` – Length of the edge along that boundary marker. Will return None if cell *n* does not touch boundary marker.

**Return type** float

**get\_edge\_cells(*ibm*)**

Get a list of cell numbers that correspond to the specified boundary marker.

**Parameters** ***ibm*** (*integer*) – boundary marker value

**Returns** `cell_list` – list of zero-based cell numbers

**Return type** list

**get\_vertices()**

Get a list of vertices in the form needed for the MODFLOW DISV Package.

**Returns** `vertices` – innermost list contains vertex number, x, and y

**Return type** list (of lists)

**get\_xcyc()**

Get a 2-dimensional array of x and y cell center coordinates.

**Returns** `xcyc` – column 0 contains the x coordinates and column 1 contains the y coordinates

**Return type** ndarray

**label\_cells**(*ax=None, onebased=True, \*\*kwargs*)

Label the cells with their cell numbers

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axis to add the plot to. (default is plt.gca())
- **onebased** (*bool*) – Make the labels one-based if True so that they correspond to what would be written to MODFLOW.
- **kwargs** (*dictionary*) – dictionary of arguments to pass to ax.text()

**Return type** None

**label\_vertices**(*ax=None, onebased=True, \*\*kwargs*)

Label the mesh vertices with their vertex numbers

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axis to add the plot to. (default is plt.gca())
- **onebased** (*bool*) – Make the labels one-based if True so that they correspond to what would be written to MODFLOW.
- **kwargs** (*dictionary*) – dictionary of arguments to pass to ax.text()

**Return type** None

**plot**(*ax=None, layer=0, edgecolor='k', facecolor='none', cmap='Dark2', a=None, masked\_values=None, \*\*kwargs*)

Plot the grid. This method will plot the grid using the shapefile that was created as part of the build method.

Note that the layer option is not working yet.

**Parameters**

- **ax** (*matplotlib.pyplot axis*) – The plot axis. If not provided it, plt.gca() will be used. If there is not a current axis then a new one will be created.
- **layer** (*int*) – Layer number to plot
- **cmap** (*string*) – Name of colormap to use for polygon shading (default is 'Dark2')
- **edgecolor** (*string*) – Color name. (Default is 'scaled' to scale the edge colors.)
- **facecolor** (*string*) – Color name. (Default is 'scaled' to scale the face colors.)
- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **kwargs** (*dictionary*) – Keyword arguments that are passed to PatchCollection.set(\*\*kwargs). Some common kwargs would be 'linewidths', 'linestyles', 'alpha', etc.

**Return type** None

**plot\_boundary**(*ibm, ax=None, \*\*kwargs*)

Plot a line and vertices for the specified boundary marker

**Parameters**

- **ibm** (*integer*) – plot the boundary for this boundary marker
- **ax** (*matplotlib.pyplot.Axes*) – axis to add the plot to. (default is plt.gca())
- **kwargs** (*dictionary*) – dictionary of arguments to pass to ax.plot()

**Return type** None

**plot\_centroids**(*ax=None, \*\*kwargs*)  
Plot the cell centroids

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axis to add the plot to. (default is plt.gca())
- **kwargs** (*dictionary*) – dictionary of arguments to pass to ax.plot()

**Return type** None

**plot\_vertices**(*ax=None, \*\*kwargs*)  
Plot the mesh vertices

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axis to add the plot to. (default is plt.gca())
- **kwargs** (*dictionary*) – dictionary of arguments to pass to ax.plot()

**Return type** None

## flop.utils.util\_array module

**util\_array module.** Contains the **util\_2d**, **util\_3d** and **transient\_2d** classes. These classes encapsulate modflow-style array inputs away from the individual packages. The end-user should not need to instantiate these classes directly.

**class ArrayFormat**(*u2d, python=None, fortran=None, array\_free\_format=None*)

Bases: object

ArrayFormat class for handling various output format types for both MODFLOW and flop

**Parameters**

- **u2d** (*Util2d instance*) –
- **python** (*str (optional)*) – python-style output format descriptor e.g. {0:15.6e}
- **fortran** (*str (optional)*) – fortran style output format descriptor e.g. (2E15.6)

**fortran**

fortran format output descriptor (e.g. (100G15.6)

**Type** str

**py**

python format output descriptor (e.g. "{0:15.6E}")

**Type** str

**numpy**

numpy format output descriptor (e.g. "%15.6e")

**Type** str

**npl**

number if items per line of output

**Type** int

**width**

the width of the formatted numeric output

**Type** int



**decimal**

the number of decimal digits in the numeric output

**Type** int

**format**

the output format type e.g. I, G, E, etc

**Type** str

**free**

free format flag

**Type** bool

**binary**

binary format flag

**Type** bool

**get\_default\_numpy\_fmt** : (dtype : [np.int32, np.float32])

a static method to get a default numpy dtype - used for loading

**decode\_fortran\_descriptor** : (fd : str)

a static method to decode fortran descriptors into npl, format, width, decimal.

**Notes****Examples**

property **array\_free\_format**

property **binary**

property **decimal**

static **decode\_fortran\_descriptor**(fd)

Decode fortran descriptor

**Parameters** fd (str) –

**Returns** npl, fmt, width, decimal

**Return type** int, str, int, int

classmethod **float**()

property **format**

property **fortran**

property **free**

static **get\_default\_numpy\_fmt**(dtype)

classmethod **integer**()

property **npl**

property **numpy**

property **py**

property **width**

```
class Transient2d(model, shape, dtype, value, name, fmtin=None, cnstnt=1.0, iprn=- 1, ext_filename=None,  
                  locat=None, bin=False, array_free_format=None)
```

Bases: flopY.database.DataInterface

Transient2d class for handling time-dependent 2-D model arrays. just a thin wrapper around Util2d

#### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **shape** (*length 2 tuple*) – shape of the 2-D transient arrays, typically (nrow,ncol)
- **dtype** (*[np.int32, np.float32, bool]*) – the type of the data
- **value** (*variable*) – the data to be assigned to the 2-D arrays. Typically a dict of {kper:value}, where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time.
- **name** (*string*) – name of the property, used for writing comments to input files and for forming external files names (if needed)
- **fmtin** (*string*) – modflow fmtin variable (optional). (the default is None)
- **cnstnt** (*string*) – modflow cnstnt variable (optional) (the default is 1.0)
- **iprn** (*int*) – modflow iprn variable (optional) (the default is -1)
- **locat** (*int*) – modflow locat variable (optional) (the default is None). If the model instance does not support free format and the external flag is not set and the value is a simple scalar, then locat must be explicitly passed as it is the unit number  
to read the array from
- **ext\_filename** (*string*) – the external filename to write the array representation to (optional) (the default is None) . If type(value) is a string and is an accessible filename, the ext\_filename is reset to value.
- **bin** (*bool*) – flag to control writing external arrays as binary (optional) (the default is False)

**transient\_2ds**

the transient sequence of Util2d objects

**Type** dict{kper:Util2d}

**get\_kper\_entry : (itmp,string)**

get the itmp value and the Util2d file entry of the value in transient\_2ds in bin kper. if kper < min(Transient2d.keys()), return (1,zero\_entry<Util2d>). If kper > < min(Transient2d.keys()), but is not found in Transient2d.keys(), return (-1,"")

#### Notes

#### Examples

**property array**

**build\_transient\_sequence()**

parse self.\_\_value into a dict{kper:Util2d}

**property data\_type**

**property dtype**

**export**(*f*, *\*\*kwargs*)

**classmethod from\_4d**(*model*, *pak\_name*, *m4ds*)

construct a Transient2d instance from a dict(name: (masked) 4d numpy.ndarray :param model: :type model: flopy.mbase derived type :param pak\_name: :type pak\_name: str package name (e.g. RCH) :param m4ds: each ndarray must have shape (nper,1,nrow,ncol).

if an entire (nrow,ncol) slice is np.NaN, then that kper is skipped.

**Return type** Transient2d instance

**get\_kper\_entry**(*kper*)

Get the file entry info for a given kper returns (itmp,file entry string from Util2d)

**get\_zero\_2d**(*kper*)

**static masked4d\_array\_to\_kper\_dict**(*m4d*)

**property model**

**property name**

**plot**(*filename\_base=None*, *file\_extension=None*, *kper=0*, *fignum=None*, *\*\*kwargs*)

Plot transient 2-D model input data

#### Parameters

- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')
- **kper** (*int or str*) – model stress period. if 'all' is provided, all stress periods will be plotted
- **fignum** (*list or int*) – Figure numbers for plot title
- **\*\*kwargs** (*dict*) –

**axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)

**pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)

**colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)

**inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)

**contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**kper** [str] MODFLOW zero-based stress period number to return. If kper='all' then data for all stress period will be extracted. (default is zero).

**Returns out** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

## Notes

## Examples

```
>>> import flop
>>> ml = flop.modflow.Modflow.load('test.nam')
>>> ml.rch.rch.plot()
```

### property plottable

**class Transient3d**(*model, shape, dtype, value, name, fmtin=None, cnstnt=1.0, iprn=- 1, ext\_filename=None, locat=None, bin=False, array\_free\_format=None*)

Bases: flop.database.DataInterface

Transient3d class for handling time-dependent 3-D model arrays. just a thin wrapper around Util3d

### Parameters

- **model** (*model object*) – The model object (of type `flop.modflow.mf.Modflow`) to which this package will be added.
- **shape** (*length 3 tuple*) – shape of the 3-D transient arrays, typically (nlay,nrow,ncol)
- **dtype** (*[np.int32, np.float32, bool]*) – the type of the data
- **value** (*variable*) – the data to be assigned to the 3-D arrays. Typically a dict of {kper:value}, where kper is the zero-based stress period to assign a value to. Value should be cast-able to Util2d instance can be a scalar, list, or ndarray is the array value is constant in time.
- **name** (*string*) – name of the property, used for writing comments to input files and for forming external files names (if needed)
- **fmtin** (*string*) – modflow fmtin variable (optional). (the default is None)
- **cnstnt** (*string*) – modflow cnstnt variable (optional) (the default is 1.0)
- **iprn** (*int*) – modflow iprn variable (optional) (the default is -1)
- **locat** (*int*) – modflow locat variable (optional) (the default is None). If the model instance does not support free format and the external flag is not set and the value is a simple scalar, then locat must be explicitly passed as it is the unit number  
to read the array from
- **ext\_filename** (*string*) – the external filename to write the array representation to (optional) (the default is None) . If type(value) is a string and is an accessible filename, the ext\_filename is reset to value.
- **bin** (*bool*) – flag to control writing external arrays as binary (optional) (the default is False)

### transient\_3ds

the transient sequence of Util3d objects

Type dict{kper:Util3d}

**get\_kper\_entry** : (itmp,string)

get the itmp value and the Util2d file entry of the value in transient\_2ds in bin kper. if kper < min(Transient2d.keys()), return (1,zero\_entry<Util2d>). If kper > < min(Transient2d.keys()), but is not found in Transient2d.keys(), return (-1,"")

## Notes

## Examples

property array

**build\_transient\_sequence**()

parse self.\_\_value into a dict{kper:Util3d}

property data\_type

property dtype

**get\_kper\_entry**(kper)

get the file entry info for a given kper returns (itmp,file entry string from Util3d)

**get\_zero\_3d**(kper)

property model

property name

property plottable

**class Util2d**(model, shape, dtype, value, name, fmtin=None, cnstnt=1.0, iprn=- 1, ext\_filename=None, locat=None, bin=False, how=None, array\_free\_format=None)

Bases: flopy.database.DataInterface

Util2d class for handling 1- or 2-D model arrays

### Parameters

- **model** (*model object*) – The model object (of type *flopy.modflow.mf.Modflow*) to which this package will be added.
- **shape** (*tuple*) – Shape of the 1- or 2-D array
- **dtype** (*[np.int32, np.float32, bool]*) – the type of the data
- **value** (*variable*) – the data to be assigned to the 1- or 2-D array. can be a scalar, list, ndarray, or filename
- **name** (*string*) – name of the property (optional). (the default is None)
- **fmtin** (*string*) – modflow fmtin variable (optional). (the default is None)
- **cnstnt** (*string*) – modflow cnstnt variable (optional) (the default is 1.0)
- **iprn** (*int*) – modflow iprn variable (optional) (the default is -1)
- **locat** (*int*) – modflow locat variable (optional) (the default is None). If the model instance does not support free format and the external flag is not set and the value is a simple scalar, then locat must be explicitly passed as it is the unit number to read the array from)

- **ext\_filename** (*string*) – the external filename to write the array representation to (optional) (the default is None) . If type(value) is a string and is an accessible filename, the ext\_filename is reset to value.
- **bin** (*bool*) – flag to control writing external arrays as binary (optional) (the default is False)

**array**

the array representation of the 2-D object

**Type** np.ndarray

**how**

the str flag to control how the array is written to the model input files e.g. “constant”, “internal”, “external”, “open/close”

**Type** str

**format**

controls the ASCII representation of the numeric array

**Type** ArrayFormat object

**get\_file\_entry : string**

get the model input file string including the control record

## Notes

If value is a valid filename and model.external\_path is None, then a copy of the file is made and placed in model.model\_ws directory.

If value is a valid filename and model.external\_path is not None, then a copy of the file is made a placed in the external\_path directory.

If value is a scalar, it is always written as a constant, regardless of the model.external\_path setting.

If value is an array and model.external\_path is not None, then the array is written out in the external\_path directory. The name of the file that holds the array is created from the name attribute. If the model supports “free format”, then the array is accessed via the “open/close” approach. Otherwise, a unit number and filename is added to the name file.

If value is an array and model.external\_path is None, then the array is written internally to the model input file.

## Examples

**all()****property array**

Get the COPY of array representation of value attribute with the effects of the control record multiplier applied.

**Returns array** – Copy of the array with the multiplier applied.

**Return type** numpy.ndarray

---

**Note:** .array is a COPY of the array representation as seen by the model - with the effects of the control record multiplier applied.

---

**static array2string**(*shape, data, fortran\_format='(FREE)', python\_format=None*)  
 return a string representation of a (possibly wrapped format) array from a file (self.\_\_value) and casts to the proper type (self.\_dtype) made static to support the load functionality this routine now supports fixed format arrays where the numbers may touch.

**property cnsntnt\_str**

**property data\_type**

**property dtype**

**export**(*f, \*\*kwargs*)

**property filename**

**property format**

**get\_constant\_cr**(*value*)

**get\_external\_cr**()

**get\_file\_entry**(*how=None*)

**get\_internal\_cr**()

**get\_openclose\_cr**()

**get\_value**()

**property how**

**classmethod load**(*f\_handle, model, shape, dtype, name, ext\_unit\_dict=None, array\_free\_format=None, array\_format='modflow'*)  
 functionality to load Util2d instance from an existing model input file. external and internal record types must be fully loaded if you are using fixed format record types, make sure ext\_unit\_dict has been initialized from the NAM file

**static load\_bin**(*shape, file\_in, dtype, bintype=None*)  
 Load unformatted file to a 2-D array

#### Parameters

- **shape** (*tuple of int*) – One or two array dimensions
- **file\_in** (*file or str*) – Filename or file handle
- **dtype** (*np.int32 or np.float32*) – Data type of unformatted file and Numpy array; use np.int32 for Fortran's INTEGER, and np.float32 for Fortran's REAL data types.
- **bintype** (*str*) – Normally 'Head'

#### Notes

This method is similar to MODFLOW's U2DREL and U2DINT subroutines, but only for unformatted files.

**Return type** 2-D array

**static load\_block**(*shape, file\_in, dtype*)  
 Load block format from a MT3D file to a 2-D array

#### Parameters

- **shape** (*tuple of int*) – Array dimensions (nrow, ncol)

- **file\_in** (*file* or *str*) – Filename or file handle
- **dtype** (*np.int32* or *np.float32*) –

**Return type** 2-D array

**static load\_txt** (*shape, file\_in, dtype, fmtin*)

Load formatted file to a 1-D or 2-D array

**Parameters**

- **shape** (*tuple of int*) – One or two array dimensions
- **file\_in** (*file* or *str*) – Filename or file handle
- **dtype** (*np.int32* or *np.float32*) –
- **fmtin** (*str*) – Fortran array format descriptor, '(FREE)' or e.g. '(10G11.4)'

## Notes

This method is similar to MODFLOW's U1DREL, U1DINT, U2DREL and U2DINT subroutines, but only for formatted files.

**Return type** 1-D or 2-D array

**property model**

**property model\_file\_path**

where the model expects the file to be

**Returns** **file\_path** (*str*)

**Return type** path relative to the name file

**property name**

**static parse\_control\_record** (*line, current\_unit=None, dtype=<class 'numpy.float32'>, ext\_unit\_dict=None, array\_format=None*)

parses a control record when reading an existing file rectifies fixed to free format *current\_unit* (optional) indicates the unit number of the file being parsed

**parse\_value** (*value*)

parses and casts the raw value into an acceptable format for \_\_value lot of defense here, so we can make assumptions later

**plot** (*title=None, filename\_base=None, file\_extension=None, fignum=None, \*\*kwargs*)

Plot 2-D model input data

**Parameters**

- **title** (*str*) – Plot title. If a plot title is not provide one will be created based on data name (*self.\_name*). (default is None)
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if *file\_name\_base* is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for *savefig()*. Only used if *filename\_base* is not None. (default is 'png')
- **\*\*kwargs** (*dict*) –



**axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)

**pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)

**colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)

**inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)

**contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**Returns** **out** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

## Notes

## Examples

```
>>> import flop
>>> ml = flop.modflow.Modflow.load('test.nam')
>>> ml.dis.top.plot()
```

**property** **plottable**

**property** **python\_file\_path**

where python is going to write the file :returns: **file\_path** (str) :rtype: path relative to python: includes model\_ws

**set\_fmtin**(fmtin)

**property** **string**

get the string representation of value attribute

---

**Note:** the string representation DOES NOT include the effects of the control record multiplier - this method is used primarily for writing model input files

---

**sum**()

**unique**()

**property** **vtype**

**static** **write\_bin**(shape, file\_out, data, bintype=None, header\_data=None)

**static** **write\_txt**(shape, file\_out, data, fortran\_format='(FREE)', python\_format=None)

```
class Util3d(model, shape, dtype, value, name, fmtin=None, cnstnt=1.0, iprn=- 1, locat=None,
             ext_unit_dict=None, array_free_format=None)
```

Bases: `flopY.database.DataInterface`

Util3d class for handling 3-D model arrays. just a thin wrapper around Util2d

#### Parameters

- **model** (*model object*) – The model object (of type `flopY.modflow.mf.Modflow`) to which this package will be added.
- **shape** (*length 3 tuple*) – shape of the 3-D array, typically (nlay,nrow,ncol)
- **dtype** (*[np.int32, np.float32, bool]*) – the type of the data
- **value** (*variable*) – the data to be assigned to the 3-D array. can be a scalar, list, or ndarray
- **name** (*string*) – name of the property, used for writing comments to input files
- **fmtin** (*string*) – modflow fmtin variable (optional). (the default is None)
- **cnstnt** (*string*) – modflow cnstnt variable (optional) (the default is 1.0)
- **iprn** (*int*) – modflow iprn variable (optional) (the default is -1)
- **locat** (*int*) – modflow locat variable (optional) (the default is None). If the model instance does not support free format and the external flag is not set and the value is a simple scalar, then locat must be explicitly passed as it is the unit number to read the array from
- **ext\_filename** (*string*) – the external filename to write the array representation to (optional) (the default is None) . If type(value) is a string and is an accessible filename, the ext\_filename is reset to value.
- **bin** (*bool*) – flag to control writing external arrays as binary (optional) (the default is False)

#### array

the array representation of the 3-D object

**Type** np.ndarray

#### get\_file\_entry : string

get the model input file string including the control record for the entire 3-D property

#### Notes

#### Examples

##### property array

Return a numpy array of the 3D shape. If an unstructured model, then return an array of size nodes.

##### build\_2d\_instances()

##### property data\_type

##### property dtype

##### export(f, \*\*kwargs)

##### get\_file\_entry()

##### get\_value()

**classmethod** `load(f_handle, model, shape, dtype, name, ext_unit_dict=None, array_format=None)`

**property** `model`

**property** `name`

**plot**(*filename\_base=None, file\_extension=None, mflay=None, fignum=None, \*\*kwargs*)

Plot 3-D model input data

#### Parameters

- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if `file_name_base` is not `None`. (default is `None`)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for `savefig()`. Only used if `filename_base` is not `None`. (default is `'png'`)
- **mflay** (*int*) – MODFLOW zero-based layer number to return. If `None`, then all layers will be included. (default is `None`)
- **\*\*kwargs** (*dict*) –
  - axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If `axes=None` axes will be generated. (default is `None`)
  - pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is `True`)
  - colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if `pcolor=True`. (default is `False`)
  - inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is `True`)
  - contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is `False`)
  - clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if `contour=True`. (default is `False`)
  - grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is `False`)
  - masked\_values** [list] List of unique values to be excluded from the plot.

**Returns** `out` – Empty list is returned if `filename_base` is not `None`. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

#### Notes

#### Examples

```
>>> import flop
>>> m1 = flop.modflow.Modflow.load('test.nam')
>>> m1.lpf.hk.plot()
```

**property** `plottable`

**new\_u2d**(*old\_util2d, value*)

**read1d**(*f, a*)

Fill the 1d array, a, with the correct number of values. Required in case lpf 1d arrays (chani, layvka, etc) extend over more than one line

## flopy.utils.util\_list module

**util\_list module.** Contains the **mflist** class. This classes encapsulates modflow-style list inputs away from the individual packages. The end-user should not need to instantiate this class directly.

some more info

**class MfList**(*package, data=None, dtype=None, model=None, list\_free\_format=None, binary=False*)

Bases: `flopy.database.DataInterface`, `flopy.database.DataListInterface`

a generic object for handling transient boundary condition lists

### Parameters

- **package** (*package object*) – The package object (of type `flopy.pakbase.Package`) to which this MfList will be added.
- **data** (*varies*) – the data of the transient list (optional). (the default is None)

**mxact**

the max number of active bc for any stress period

**Type** int

**add\_record(kper, index, value) : None**

add a record to stress period kper at index location

**write\_transient(f) : None**

write the transient sequence to the model input file f

**check\_kij() : None**

checks for boundaries outside of model domain - issues warnings only

## Notes

## Examples

**add\_record(kper, index, values)**

**append(other)**

append the recarrays from one MfList to another :param other: that corresponds with self :type other: variable: an item that can be cast in to an MfList

**Returns** dict of {kper

**Return type** recarray}

**property** array

**attribute\_by\_kper**(*attr, function=<function mean>, idx\_val=None*)

**property** binary

**check\_kij()**

**property** data

**property** data\_type

**property df****drop**(*fields*)

drop fields from an MfList

**Parameters** *fields* (*list or set of field names to drop*) –

**Returns** **dropped**

**Return type** MfList without the dropped fields

**property dtype****export**(*f*, *\*\*kwargs*)**property fmt\_string**

Returns a C-style fmt string for numpy savetxt that corresponds to the dtype

**classmethod from\_4d**(*model*, *pak\_name*, *m4ds*)

construct an MfList instance from a dict of (attribute\_name,masked 4D ndarray :param model: :type model: mbase derived type :param pak\_name: :type pak\_name: str package name (e.g GHB) :param m4ds: :type m4ds: {attribute name:4d masked numpy.ndarray}

**Return type** MfList instance

**get\_dataframe**(*squeeze=False*)

Cast recarrays for stress periods into single dataframe containing all stress periods.

**Parameters** **squeeze** (*bool*) – Reduce number of rows in dataframe to only include stress periods where a variable changes.

**Returns** **df** – Dataframe of shape nrow = nper x ncells, ncol = nvar. If the squeeze option is chosen, nper is the number of stress periods where at least one cells is different, otherwise it is equal to the number of keys in MfList.data.

**Return type** dataframe

**Notes**

Requires pandas.

**get\_empty**(*ncell=0*)**get\_filename**(*kper*)**get\_filenames**()**get\_indices**()

a helper function for plotting - get all unique indices

**get\_itmp**(*kper*)**static masked4D\_arrays\_to\_stress\_period\_data**(*dtype*, *m4ds*)

convert a dictionary of 4-dim masked arrays to a stress\_period\_data style dict of recarray

**Parameters**

- **dtype** (*numpy dtype*) –
- **m4ds** (*dict {name:masked numpy 4-dim ndarray}*) –

**Returns** **dict {kper**

**Return type** recarray}

`property masked_4D_arrays`

`masked_4D_arrays_itr()`

`property mg`

`property model`

`property mxact`

`property name`

`property package`

`plot(key=None, names=None, kper=0, filename_base=None, file_extension=None, mflay=None, **kwargs)`  
Plot stress period boundary condition (MfList) data for a specified stress period

#### Parameters

- **key** (*str*) – MfList dictionary key. (default is None)
- **names** (*list*) – List of names for figure titles. (default is None)
- **kper** (*int*) – MODFLOW zero-based stress period number to return. (default is zero)
- **filename\_base** (*str*) – Base file name that will be used to automatically generate file names for output image files. Plots will be exported as image files if file\_name\_base is not None. (default is None)
- **file\_extension** (*str*) – Valid matplotlib.pyplot file extension for savefig(). Only used if filename\_base is not None. (default is 'png')
- **mflay** (*int*) – MODFLOW zero-based layer number to return. If None, then all layers will be included. (default is None)
- **\*\*kwargs** (*dict*) –

**axes** [list of matplotlib.pyplot.axis] List of matplotlib.pyplot.axis that will be used to plot data for each layer. If axes=None axes will be generated. (default is None)

**pcolor** [bool] Boolean used to determine if matplotlib.pyplot.pcolormesh plot will be plotted. (default is True)

**colorbar** [bool] Boolean used to determine if a color bar will be added to the matplotlib.pyplot.pcolormesh. Only used if pcolor=True. (default is False)

**inactive** [bool] Boolean used to determine if a black overlay in inactive cells in a layer will be displayed. (default is True)

**contour** [bool] Boolean used to determine if matplotlib.pyplot.contour plot will be plotted. (default is False)

**clabel** [bool] Boolean used to determine if matplotlib.pyplot.clabel will be plotted. Only used if contour=True. (default is False)

**grid** [bool] Boolean used to determine if the model grid will be plotted on the figure. (default is False)

**masked\_values** [list] List of unique values to be excluded from the plot.

**Returns** **out** – Empty list is returned if filename\_base is not None. Otherwise a list of matplotlib.pyplot.axis is returned.

**Return type** list

## Notes

## Examples

```
>>> import flopY
>>> ml = flopY.modflow.Modflow.load('test.nam')
>>> ml.wel.stress_period_data.plot(ml.wel, kper=1)
```

### property `plottable`

**to\_array**(*kper=0, mask=False*)

Convert stress period boundary condition (MfList) data for a specified stress period to a 3-D numpy array

#### Parameters

- **kper** (*int*) – MODFLOW zero-based stress period number to return. (default is zero)
- **mask** (*boolean*) – return array with np.NaN instead of zero

**Returns** **out** – Dictionary of 3-D numpy arrays containing the stress period data for a selected stress period. The dictionary keys are the MfList dtype names for the stress period data ('cond', 'flux', 'bhead', etc.).

**Return type** dict of numpy.ndarrays

## Notes

## Examples

```
>>> import flopY
>>> ml = flopY.modflow.Modflow.load('test.nam')
>>> v = ml.wel.stress_period_data.to_array(kper=1)
```

**to\_shapefile**(*filename, kper=None*)

Export stress period boundary condition (MfList) data for a specified stress period

#### Parameters

- **filename** (*str*) – Shapefile name to write
- **kper** (*int*) – MODFLOW zero-based stress period number to return. (default is None)

**Return type** None

## Notes

## Examples

```
>>> import flopY
>>> ml = flopY.modflow.Modflow.load('test.nam')
>>> ml.wel.to_shapefile('test_hk.shp', kper=1)
```

### property `vtype`

**write\_transient**(*f, single\_per=None, forceInternal=False*)

**flop.utils.utils\_def module**

Generic classes and utility functions

**class FlopyBinaryData**

Bases: object

The FlopyBinaryData class is a class to that defines the data types for integer, floating point, and character data in MODFLOW binary files. The FlopyBinaryData class is the super class from which the specific derived classes are formed. This class should not be instantiated directly.

**read\_integer()**

**read\_real()**

**read\_record(count, dtype=None)**

**read\_text(nchar=20)**

**set\_float(precision)**

**get\_open\_file\_object(fname\_or\_fobj, read\_write='rw')**

Returns an open file object for either a file name or open file object.

**get\_pak\_vals\_shape(model, vals)**

Function to define shape of package input data for Util2d.

**Parameters**

- **model** (*flop model object*) –
- **vals** (*Package input values (dict of arrays or scalars, or ndarray, or) – single scalar*).

**Returns** **shape** – shape of input data for Util2d

**Return type** tuple

**get\_unitnumber\_from\_ext\_unit\_dict(model, pak\_class, ext\_unit\_dict=None, ipakcb=0)**

For a given modflow package, defines input file unit number, plus package input and (optionally) output (budget) save file names.

**Parameters**

- **model** (*model object*) – model for which the unit number is sought.
- **pak\_class** (*modflow package class for which the unit number is sought.*) –
- **ext\_unit\_dict** (*external unit dictionary, optional.*) – If not provided, unitnumber and filenames will be returned as None.
- **ipakcb** (*int, optional*) – Modflow package unit number on which budget is saved. Default is 0, in which case the returned output file is None.

**Returns**

- **unitnumber** (*int*) – file unit number for the given modflow package (or None)
- **filenames** (*list*) – list of [package input file name, budget file name],

**get\_util2d\_shape\_for\_layer(model, layer=0)**

Define nrow and ncol for array (Util2d) shape of a given layer in structured and/or unstructured models.

**Parameters**

- **model** (*model object*) – model for which Util2d shape is sought.
- **layer** (*int*) – layer (base 0) for which Util2d shape is sought.



**Returns** (nrow,ncol) – util2d shape for the given layer

**Return type** tuple of ints

**totim\_to\_datetime**(*totim*, *start*='1-1-1970', *timeunit*='D')

**Parameters**

- **totim** (*list or numpy array*) –
- **start** (*str*) – Starting date for simulation. (default is 1-1-1970).
- **timeunit** (*string*) – time unit of the simulation time. Valid values are ‘S’econds, ‘M’inutes, ‘H’ours, ‘D’ays, ‘Y’ears. (default is ‘D’).

**Returns** **out** – datetime object calculated from start and totim values

**Return type** list

**type\_from\_iterable**(*\_iter*, *index*=0, *\_type*=<class 'int'>, *default\_val*=0)

Returns value of specified type from iterable.

**Parameters**

- **\_iter** (*iterable*) –
- **index** (*int*) – Iterable index to try to convert
- **\_type** (*Python type*) –
- **default\_val** (*default value (0)*) –

**Returns** **val**

**Return type** value of type *\_type*, or *default\_val*

## flopy.utils.utl\_import module

**get\_version**(*module: module*) → str

**import\_optional\_dependency**(*name: str*, *error\_message: str* = "", *errors: str* = 'raise', *min\_version: str* | *None* = *None*)

Import an optional dependency.

By default, if a dependency is missing an ImportError with a nice message will be raised. If a dependency is present, but too old, we raise.

**Parameters**

- **name** (*str*) – The module name.
- **error\_message** (*str*) – Additional text to include in the ImportError message.
- **errors** (*str* {'raise', 'warn', 'ignore'}) – What to do when a dependency is not found or its version is too old.
  - raise : Raise an ImportError
  - warn : Only applicable when a module’s version is to old. Warns that the version is too old and returns None
  - ignore: If the module is not installed, return None, otherwise, return the module, even if the version is too old. It’s expected that users validate the version locally when using errors="ignore" (see. io/html.py)
  - silent: Same as “ignore” except warning message is not written to the screen.

- **min\_version** (*str*, *default None*) – Specify a minimum version that is different from the global FloPy minimum version required.

**Returns** **maybe\_module** – The imported module, when found and the version is correct. None is returned when the package is not found and *errors* is False, or when the package’s version is too old and *errors* is 'warn'.

**Return type** Optional[ModuleType]

## flopY.utils.voronoi module

**class** **VoronoiGrid**(*tri*, *\*\*kwargs*)

Bases: object

FloPy VoronoiGrid helper class for creating a voronoi model grid from an array of input points that define cell centers. The class handles boundary cells by closing polygons along the edge, something that cannot be done directly with the `scipy.spatial.Voronoi` class.

### Parameters

- **input** (*flopY.utils.Triangle*) – Constructed and built flopY Triangle object.
- **kwargs** (*dict*) – List of additional keyword arguments that will be passed through to `scipy.spatial.Voronoi`. For circular shaped model grids, the `qhull_options='Qz'` option has been found to work well.

## Notes

When using VoronoiGrid, the construction order used for the Triangle grid matters. The first `add_polygon()` call must be to add the model domain. Then `add_polygon()` must be used to add any holes. Lastly, `add_polygon()` can be used to add regions. This VoronoiGrid class uses this order to find model edges that require further work for defining and closing edge model cells.

**get\_disu5\_gridprops()**

**get\_disu6\_gridprops()**

**get\_disv\_gridprops()**

Get a dictionary of arguments that can be passed in to the `flopY.mf6.ModflowGwfdiscv` class.

**Returns** **disv\_gridprops** – Dictionary of arguments than can be unpacked into the `flopY.mf6.ModflowGwfdiscv` constructor

**Return type** dict

**get\_gridprops\_unstructuredgrid()**

Get a dictionary of information needed to create a flopY UnstructuredGrid. The returned dictionary can be unpacked directly into the `flopY.discretization.UnstructuredGrid()` constructor.

**Returns** **gridprops**

**Return type** dict

**get\_gridprops\_vertexgrid()**

Get a dictionary of information needed to create a flopY VertexGrid. The returned dictionary can be unpacked directly into the `flopY.discretization.VertexGrid()` constructor.

**Returns** **gridprops**

**Return type** dict

**get\_patch\_collection**(*ax=None, \*\*kwargs*)

Get a matplotlib patch collection representation of the voronoi grid

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axes to plot the patch collection
- **kwargs** (*dict*) – Additional keyword arguments to pass to the `flopy.plot.plot_cvfd` function that returns a patch collection from `verts` and `iverts`

**Returns** **pc** – patch collection of model

**Return type** `matplotlib.collections.PatchCollection`

**plot**(*ax=None, plot\_title=True, \*\*kwargs*)

Plot the voronoi model grid

**Parameters**

- **ax** (*matplotlib.pyplot.Axes*) – axes to plot the voronoi grid
- **plot\_title** (*bool*) – Add the number of cells and number of vertices as a plot title
- **kwargs** (*dict*) – Additional keyword arguments to pass to `self.get_patch_collection`

**Returns** **ax** – axes that contains the voronoi model grid

**Return type** `matplotlib.pyplot.Axes`

**get\_sorted\_vertices**(*icell\_vertices, vertices*)

**get\_valid\_faces**(*vor*)

**point\_in\_cell**(*point, vertices*)

**sort\_vertices**(*vlist*)

**tri2vor**(*tri, \*\*kwargs*)

This is the workhorse for the `VoronoiGrid` class for creating a voronoi grid from a constructed and built flopy Triangle grid.

**Parameters**

- **tri** (*flopy.utils.Triangle*) –
- **voronoi** (*Flopy triangle object is used to construct the complementary*) –
- **diagram.** –

**Returns** **verts, iverts**

**Return type** `ndarray`, list of lists

**flopY.utils.zonbud module****class ZBNetOutput**(*zones, time, arrays, zone\_array, flux=True*)

Bases: object

Class that holds zonebudget netcdf output and allows export utilities to recognize the output data type.

**Parameters**

- **zones** (*np.ndarray*) – array of zone numbers
- **time** (*np.ndarray*) – array of totim
- **arrays** (*dict*) – dictionary of budget term arrays. axis 0 is totim, axis 1 is zones
- **flux** (*bool*) – boolean flag to indicate if budget data is a flux “L<sup>3</sup>/T” (True, default) or if the data have been processed to volumetric values “L<sup>3</sup>” (False)

**class ZoneBudget**(*cbc\_file, z, kstp, kper=None, totim=None, aliases=None, verbose=False, \*\*kwargs*)

Bases: object

ZoneBudget class

**Parameters**

- **cbc\_file** (*str or CellBudgetFile object*) – The file name or CellBudgetFile object for which budgets will be computed.
- **z** (*ndarray*) – The array containing to zones to be used.
- **kstp, kper** (*tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). The kstp and kper values are zero based.
- **totim** (*float*) – The simulation time.
- **aliases** (*dict*) – A dictionary with key, value pairs of zones and aliases. Replaces the corresponding record and field names with the aliases provided. When using this option in conjunction with a list of zones, the zone(s) passed may either be all strings (aliases), all integers, or mixed.

**Return type** None**Examples**

```
>>> from flopY.utils.zonbud import ZoneBudget
>>> zon = ZoneBudget.read_zone_file('zone_input_file')
>>> zb = ZoneBudget('zonebudtest.cbc', zon, kstp, kper=(0, 0))
>>> zb.to_csv('zonebudtest.csv')
>>> zb_mgd = zb * 7.48052 / 1000000
```

**copy()**

Return a deepcopy of the object.

**export**(*f, ml, \*\*kwargs*)

Method to export a netcdf file, or add zonebudget output to an open netcdf file instance

**Parameters**

- **f** (*str or flopY.export.netcdf.NetCdf object*) –
- **ml** (*flopY.modflow.Modflow or flopY.mf6.ModflowGwf object*) –
- **\*\*kwargs** – logger : flopY.export.netcdf.Logger instance masked\_vals : list

list of values to mask

**Return type** flopy.export.netcdf.NetCdf object

**get\_budget**(*names=None, zones=None, net=False, pivot=False*)

Get a list of zonebudget record arrays.

**Parameters**

- **names** (*list of strings*) – A list of strings containing the names of the records desired.
- **zones** (*list of ints or strings*) – A list of integer zone numbers or zone names desired.
- **net** (*boolean*) – If True, returns net IN-OUT for each record.
- **pivot** (*boolean*) – If True, returns data in a more user friendly format

**Returns** **budget\_list** – A list of the zonebudget record arrays.

**Return type** list of record arrays

**Examples**

```
>>> names = ['FROM_CONSTANT_HEAD', 'RIVER_LEAKAGE_OUT']
>>> zones = ['ZONE_1', 'ZONE_2']
>>> zb = ZoneBudget('zonebudtest.cbc', zon, kstpkper=(0, 0))
>>> bud = zb.get_budget(names=names, zones=zones)
```

**get\_dataframes**(*start\_datetime=None, timeunit='D', index\_key='totim', names=None, zones=None, net=False, pivot=False*)

Get pandas dataframes.

**Parameters**

- **start\_datetime** (*str*) – Datetime string indicating the time at which the simulation starts.
- **timeunit** (*str*) – String that indicates the time units used in the model.
- **index\_key** (*str*) – Indicates the fields to be used (in addition to “record”) in the resulting DataFrame multi-index.
- **names** (*list of strings*) – A list of strings containing the names of the records desired.
- **zones** (*list of ints or strings*) – A list of integer zone numbers or zone names desired.
- **net** (*boolean*) – If True, returns net IN-OUT for each record.
- **pivot** (*bool*) – If True, returns dataframe in a more user friendly format

**Returns** **df** – Pandas DataFrame with the budget information.

**Return type** Pandas DataFrame

## Examples

```
>>> from flopY.utils.zonbud import ZoneBudget
>>> zon = ZoneBudget.read_zone_file('zone_input_file')
>>> zb = ZoneBudget('zonebudtest.cbc', zon, kstpkper=(0, 0))
>>> df = zb.get_dataframes()
```

### `get_model_shape()`

Get model shape

#### Returns

- **nlay** (*int*) – Number of layers
- **nrow** (*int*) – Number of rows
- **ncol** (*int*) – Number of columns

### `get_record_names(stripped=False)`

Get a list of water budget record names in the file.

**Returns out** – List of unique text names in the binary file.

**Return type** list of strings

## Examples

```
>>> zb = ZoneBudget('zonebudtest.cbc', zon, kstpkper=(0, 0))
>>> recnames = zb.get_record_names()
```

### `get_volumetric_budget(modeltime, recarray=None, extrapolate_kper=False)`

Method to generate a volumetric budget table based on flux information

#### Parameters

- **modeltime** (*flopY.discretization.ModelTime object*) – ModelTime object for calculating volumes
- **recarray** (*np.recarray*) – optional, user can pass in a numpy recarray to calculate volumetric budget. recarray must be pivoted before passing to `get_volumetric_budget`
- **extrapolate\_kper** (*bool*) – flag to determine if we fill in data gaps with other timestep information from the same stress period. if True, we assume that flux is constant throughout a stress period and the pandas dataframe returned contains a volumetric budget per stress period

if False, calculates volumes from available flux data

**Return type** `pd.DataFrame`

### `classmethod read_output(fname, net=False, dataframe=False, **kwargs)`

Method to read a zonebudget output file into a recarray or pandas dataframe

#### Parameters

- **fname** (*str*) – zonebudget output file name
- **net** (*bool*) – boolean flag for net budget
- **dataframe** (*bool*) – boolean flag to return a pandas dataframe



**Parameters** **name** (*str*) – new model name

**change\_model\_ws**(*model\_ws*)

Method to change the model ws for writing a zonebudget model.

**Parameters** **model\_ws** (*str*) – new model directory

**export**(*f*, *ml*, *\*\*kwargs*)

Method to export a netcdf file, or add zonebudget output to an open netcdf file instance

**Parameters**

- **f** (*str* or *flop.export.netcdf.NetCdf* object) –
- **ml** (*flop.modflow.Modflow* or *flop.mf6.ModflowGwf* object) –
- **\*\*kwargs** – logger : *flop.export.netcdf.Logger* instance masked\_vals : list  
list of values to mask

**Return type** *flop.export.netcdf.NetCdf* object

**get\_budget**(*f=None*, *names=None*, *zones=None*, *net=False*, *pivot=False*)

Method to read and get zonebudget output

**Parameters**

- **f** (*str*) – zonebudget output file name
- **names** (*list of strings*) – A list of strings containing the names of the records desired.
- **zones** (*list of ints or strings*) – A list of integer zone numbers or zone names desired.
- **net** (*boolean*) – If True, returns net IN-OUT for each record.
- **pivot** (*bool*) – Method to pivot recordarray into a more user friendly method for working with data

**Return type** *np.recarray*

**get\_dataframes**(*start\_datetime=None*, *timeunit='D'*, *index\_key='totim'*, *names=None*, *zones=None*, *net=False*, *pivot=False*)

Get pandas dataframes.

**Parameters**

- **start\_datetime** (*str*) – Datetime string indicating the time at which the simulation starts.
- **timeunit** (*str*) – String that indicates the time units used in the model.
- **index\_key** (*str*) – Indicates the fields to be used (in addition to “record”) in the resulting DataFrame multi-index.
- **names** (*list of strings*) – A list of strings containing the names of the records desired.
- **zones** (*list of ints or strings*) – A list of integer zone numbers or zone names desired.
- **net** (*boolean*) – If True, returns net IN-OUT for each record.
- **pivot** (*bool*) – If True, returns data in a more user friendly fashion

**Returns** **df** – Pandas DataFrame with the budget information.



**Return type** Pandas DataFrame

### Examples

```
>>> from floppy.utils.zonbud import ZoneBudget6
>>> zb6 = ZoneBudget6.load("my_nam_file", model_ws="my_model_ws")
>>> zb6.run_model()
>>> df = zb6.get_dataframes()
```

**get\_volumetric\_budget**(*modeltime*, *recarray=None*, *extrapolate\_kper=False*)

Method to generate a volumetric budget table based on flux information

#### Parameters

- **modeltime** (*floppy.discretization.ModelTime* object) – ModelTime object for calculating volumes
- **recarray** (*np.recarray*) – optional, user can pass in a numpy recarray to calculate volumetric budget. recarray must be pivoted before passing to `get_volumetric_budget`
- **extrapolate\_kper** (*bool*) – flag to determine if we fill in data gaps with other timestep information from the same stress period. if True, we assume that flux is constant throughout a stress period and the pandas dataframe returned contains a volumetric budget per stress period

if False, calculates volumes from available flux data

**Return type** `pd.DataFrame`

**static load**(*nam\_file*, *model\_ws='.'*)

Method to load a zonebudget model from namefile

#### Parameters

- **nam\_file** (*str*) – zonebudget name file
- **model\_ws** (*str*) – model workspace path

**Return type** ZoneBudget6 object

**run\_model**(*exe\_name=None*, *nam\_file=None*, *silent=False*)

Method to run a zonebudget model

#### Parameters

- **exe\_name** (*str*) – optional zonebudget executable name
- **nam\_file** (*str*) – optional zonebudget name file name
- **silent** (*bool*) – optional flag to silence output

**Return type** tuple

**write\_input**(*line\_length=20*)

Method to write a ZoneBudget 6 model to file

**Parameters** **line\_length** (*int*) – length of line for izeone array

**class ZoneFile6**(*model*, *izeone*, *extension='.zon'*, *aliases=None*)

Bases: object

Class to build, read, write and edit MODFLOW 6 zonebudget zone files

**Parameters**

- **model** (*ZoneBudget6 object*) – model object
- **izone** (*np.array*) – numpy array of zone numbers
- **extension** (*str*) – zone file extension name, defaults to “.zon”
- **aliases** (*dict*) – optional dictionary of zone aliases. ex. {1 : “nw\_model”}

**static load**(*f, model*)

Method to load a Zone file for zonebudget 6.

**f** [str] zone file name**model** [ZoneBudget6 object] zonebudget 6 model object**Return type** ZoneFile6 object**property ncells**

Method to get number of model cells

**write\_input**(*f=None, line\_length=20*)

Method to write the zonebudget 6 file

**Parameters**

- **f** (*str*) – zone file name
- **line\_length** (*int*) – maximum length of line to write in izone array

**dataframe\_to\_netcdf\_fmt**(*df, zone\_array, flux=True*)

Method to transform a volumetric zonebudget dataframe into array format for netcdf.

time is on axis 0 zone is on axis 1

**Parameters**

- **df** (*pd.DataFrame*) –
- **zone\_array** (*np.ndarray*) – zonebudget zones array
- **flux** (*bool*) – boolean flag to indicate if budget data is a flux “L^3/T” (True, default) or if the data have been processed to volumetric values “L^3” (False)

**Return type** ZBNetOutput object**sort\_tuple**(*tup, n=2*)

Sort a tuple by the first n values

**tup: tuple** input tuple**n** [int] values to sort tuple by (default is 2)**Returns tup** – tuple sorted by the first n values**Return type** tuple**sum\_flux\_tuples**(*fromzones, tozones, fluxes*)

## Plotting Utilities

Contents:

### flop.plot.crosssection module

**class PlotCrossSection**(*model=None, modelgrid=None, ax=None, line=None, extent=None, geographic\_coords=False*)

Bases: object

Class to create a cross sectional plot of a model.

#### Parameters

- **ax** (*matplotlib.pyplot axis*) – The plot axis. If not provided it, plt.gca() will be used.
- **model** (*flop.modflow object*) – flop model object. (Default is None)
- **modelgrid** (*flop.discretization.Grid object*) – can be a StructuredGrid, VertexGrid, or UnstructuredGrid object
- **line** (*dict*) – Dictionary with either “row”, “column”, or “line” key. If key is “row” or “column” key value should be the zero-based row or column index for cross-section. If key is “line” value should be an array of (x, y) tuples with vertices of cross-section. Vertices should be in map coordinates consistent with xul, yul, and rotation.
- **extent** (*tuple of floats*) – (xmin, xmax, ymin, ymax) will be used to specify axes limits. If None then these will be calculated based on grid, coordinates, and rotation.
- **geographic\_coords** (*bool*) – boolean flag to allow the user to plot cross section lines in geographic coordinates. If False (default), cross section is plotted as the distance along the cross section line.

**contour\_array**(*a, masked\_values=None, head=None, \*\*kwargs*)

Contour a two-dimensional array.

#### Parameters

- **a** (*numpy.ndarray*) – Three-dimensional array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **head** (*numpy.ndarray*) – Three-dimensional array to set top of patches to the minimum of the top of a layer or the head value. Used to create patches that conform to water-level elevations.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.pyplot.contour

**Returns** *contour\_set*

**Return type** matplotlib.pyplot.contour

**get\_extent**()

Get the extent of the rotated and offset grid

**Returns** *tuple*

**Return type** (xmin, xmax, ymin, ymax)

**get\_grid\_line\_collection**(*\*\*kwargs*)

Get a PatchCollection of the grid

**Parameters** **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.collections.LineCollection

**Returns** PatchCollection

**Return type** matplotlib.collections.LineCollection

**get\_grid\_patch\_collection**(*plotarray, projpts=None, fill\_between=False, \*\*kwargs*)

Get a PatchCollection of plotarray in unmasked cells

**Parameters**

- **plotarray** (*numpy.ndarray*) – One-dimensional array to attach to the Patch Collection.
- **projpts** (*dict*) – dictionary defined by node number which contains model patch vertices.
- **fill\_between** (*bool*) – flag to create polygons that mimic the matplotlib fill between method. Only used by the plot\_fill\_between method.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.collections.PatchCollection

**Returns** patches

**Return type** matplotlib.collections.PatchCollection

**plot\_array**(*a, masked\_values=None, head=None, \*\*kwargs*)

Plot a three-dimensional array as a patch collection.

**Parameters**

- **a** (*numpy.ndarray*) – Three-dimensional array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **head** (*numpy.ndarray*) – Three-dimensional array to set top of patches to the minimum of the top of a layer or the head value. Used to create patches that conform to water-level elevations.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.collections.PatchCollection

**Returns** patches

**Return type** matplotlib.collections.PatchCollection

**plot\_bc**(*name=None, package=None, kper=0, color=None, head=None, \*\*kwargs*)

Plot boundary conditions locations for a specific boundary type from a flopy model

**Parameters**

- **name** (*string*) – Package name string ('WEL', 'GHB', etc.). (Default is None)
- **package** (*flopy.modflow.Modflow package class instance*) – flopy package class instance. (Default is None)
- **kper** (*int*) – Stress period to plot
- **color** (*string*) – matplotlib color string. (Default is None)
- **head** (*numpy.ndarray*) – Three-dimensional array (structured grid) or Two-dimensional array (vertex grid) to set top of patches to the minimum of the top of a layer or the head value. Used to create patches that conform to water-level elevations.

- **\*\*kwargs** (*dictionary*) – keyword arguments passed to `matplotlib.collections.PatchCollection`

**Returns patches**

**Return type** `matplotlib.collections.PatchCollection`

**plot\_endpoint**(*ep*, *direction*='ending', *selection*=None, *selection\_direction*=None, *method*='cell', *head*=None, **\*\*kwargs**)

**plot\_fill\_between**(*a*, *colors*=('blue', 'red'), *masked\_values*=None, *head*=None, **\*\*kwargs**)  
Plot a three-dimensional array as lines.

**Parameters**

- **a** (*numpy.ndarray*) – Three-dimensional array to plot.
- **colors** (*list*) – matplotlib fill colors, two required
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **head** (*numpy.ndarray*) – Three-dimensional array to set top of patches to the minimum of the top of a layer or the head value. Used to create patches that conform to water-level elevations.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to `matplotlib.pyplot.plot`

**Returns plot**

**Return type** list containing `matplotlib.fillbetween` objects

**plot\_grid**(**\*\*kwargs**)  
Plot the grid lines.

**Parameters** **kwargs** (*ax*, *colors*. *The remaining kwargs are passed into the*)  
– the `LineCollection` constructor.

**Returns lc**

**Return type** `matplotlib.collections.LineCollection`

**plot\_ibound**(*ibound*=None, *color\_noflow*='black', *color\_ch*='blue', *color\_vpt*='red', *head*=None, **\*\*kwargs**)  
Make a plot of ibound. If not specified, then pull ibound from the `self.model`

**Parameters**

- **ibound** (*numpy.ndarray*) – ibound array to plot. (Default is ibound in 'BAS6' package.)
- **color\_noflow** (*string*) – (Default is 'black')
- **color\_ch** (*string*) – Color for constant heads (Default is 'blue').
- **head** (*numpy.ndarray*) – Three-dimensional array to set top of patches to the minimum of the top of a layer or the head value. Used to create patches that conform to water-level elevations.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to `matplotlib.collections.PatchCollection`

**Returns patches**

**Return type** `matplotlib.collections.PatchCollection`

**plot\_inactive**(*ibound*=None, *color\_noflow*='black', **\*\*kwargs**)  
Make a plot of inactive cells. If not specified, then pull ibound from the `self.ml`

**Parameters**

- **ibound** (*numpy.ndarray*) – ibound array to plot. (Default is ibound in ‘BAS6’ package.)
- **color\_noflow** (*string*) – (Default is ‘black’)

**Returns quadmesh**

**Return type** matplotlib.collections.QuadMesh

**plot\_pathline**(*pl, travel\_time=None, method='cell', head=None, \*\*kwargs*)

Plot the MODPATH pathlines

**Parameters**

- **pl** (*list of rec arrays or a single rec array*) – rec array or list of rec arrays is data returned from modpathfile PathlineFile get\_data() or get\_alldata() methods. Data in rec array is ‘x’, ‘y’, ‘z’, ‘time’, ‘k’, and ‘particleid’.
- **travel\_time** (*float or str*) – travel\_time is a travel time selection for the displayed pathlines. If a float is passed then pathlines with times less than or equal to the passed time are plotted. If a string is passed a variety logical constraints can be added in front of a time value to select pathlines for a select period of time. Valid logical constraints are <=, <, >=, and >. For example, to select all pathlines less than 10000 days travel\_time=’< 10000’ would be passed to plot\_pathline. (default is None)

- **method** (*str*) –

“cell” shows only pathlines that intersect with a cell

”all” projects all pathlines onto the cross section regardless of whether they intersect with a given cell

- **head** (*np.ndarray*) – optional adjustment to only show pathlines that are <= to the top of the water table given a user supplied head array
- **kwargs** (*layer, ax, colors. The remaining kwargs are passed*) – into the LineCollection constructor.

**Returns lc**

**Return type** matplotlib.collections.LineCollection

**plot\_surface**(*a, masked\_values=None, \*\*kwargs*)

Plot a two- or three-dimensional array as line(s).

**Parameters**

- **a** (*numpy.ndarray*) – Two- or three-dimensional array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.pyplot.plot

**Returns plot**

**Return type** list containing matplotlib.plot objects

**plot\_timeseries**(*ts, travel\_time=None, method='cell', head=None, \*\*kwargs*)

Plot the MODPATH timeseries.

**Parameters**

- **ts** (*list of rec arrays or a single rec array*) – rec array or list of rec arrays is data returned from modpathfile TimeseriesFile get\_data() or get\_alldata() methods. Data in rec array is 'x', 'y', 'z', 'time', 'k', and 'particleid'.
- **travel\_time** (*float or str*) – travel\_time is a travel time selection for the displayed pathlines. If a float is passed then pathlines with times less than or equal to the passed time are plotted. If a string is passed a variety logical constraints can be added in front of a time value to select pathlines for a select period of time. Valid logical constraints are <=, <, >=, and >. For example, to select all pathlines less than 10000 days travel\_time='< 10000' would be passed to plot\_pathline. (default is None)
- **kwargs** (*layer, ax, colors. The remaining kwargs are passed*) – into the LineCollection constructor. If layer='all', pathlines are output for all layers

**Returns** **lo**

**Return type** list of Line2D objects

**plot\_vector**(vx, vy, vz, head=None, kstep=1, hstep=1, normalize=False, masked\_values=None, \*\*kwargs)  
Plot a vector.

**Parameters**

- **vx** (*np.ndarray*) – x component of the vector to be plotted (non-rotated) array shape must be (nlay, nrow, ncol) for a structured grid array shape must be (nlay, ncpl) for a unstructured grid
- **vy** (*np.ndarray*) – y component of the vector to be plotted (non-rotated) array shape must be (nlay, nrow, ncol) for a structured grid array shape must be (nlay, ncpl) for a unstructured grid
- **vz** (*np.ndarray*) – y component of the vector to be plotted (non-rotated) array shape must be (nlay, nrow, ncol) for a structured grid array shape must be (nlay, ncpl) for a unstructured grid
- **head** (*numpy.ndarray*) – MODFLOW's head array. If not provided, then the quivers will be plotted in the cell center.
- **kstep** (*int*) – layer frequency to plot (default is 1)
- **hstep** (*int*) – horizontal frequency to plot (default is 1)
- **normalize** (*bool*) – boolean flag used to determine if vectors should be normalized using the vector magnitude in each cell (default is False)
- **masked\_values** (*iterable of floats*) – values to mask
- **kwargs** (*matplotlib.pyplot keyword arguments for the*) – plt.quiver method

**Returns** **quiver** – result of the quiver function

**Return type** matplotlib.pyplot.quiver

**property polygons**

Method to return cached matplotlib polygons for a cross section

**Returns** **dict**

**Return type** [matplotlib.patches.Polygon]

**set\_zcentergrid**(*vs*, *kstep*=1)

Get an array of z elevations at the center of a cell that is based on minimum of cell top elevation (self.elev) or passed *vs* `numpy.ndarray`

**Parameters**

- **vs** (`numpy.ndarray`) – Three-dimensional array to plot.
- **kstep** (`int`) – plotting layer interval

**Returns** `zcentergrid`**Return type** `numpy.ndarray`**set\_zpts**(*vs*)

Get an array of projected vertices corrected with corrected elevations based on minimum of cell elevation (self.elev) or passed *vs* `numpy.ndarray`

**Parameters** **vs** (`numpy.ndarray`) – Two-dimensional array to plot.**Returns** `zpts`**Return type** `dict`

## flop.plot.map module

**class** **PlotMapView**(*model*=None, *modelgrid*=None, *ax*=None, *layer*=0, *extent*=None)

Bases: `object`

Class to create a map of the model. Delegates plotting functionality based on model grid type.

**Parameters**

- **modelgrid** (`flop.discretization.Grid`) – The `modelgrid` class can be `StructuredGrid`, `VertexGrid`, or `UnstructuredGrid` (Default is None)
- **ax** (`matplotlib.pyplot.axis`) – The plot axis. If not provided it, `plt.gca()` will be used. If there is not a current axis then a new one will be created.
- **model** (`flop.modflow object`) – `flop` model object. (Default is None)
- **layer** (`int`) – Layer to plot. Default is 0. Must be between 0 and `nlay - 1`.
- **extent** (`tuple of floats`) – (`xmin`, `xmax`, `ymin`, `ymax`) will be used to specify axes limits. If None then these will be calculated based on grid, coordinates, and rotation.

## Notes

**contour\_array**(*a*, *masked\_values*=None, *\*\*kwargs*)

Contour an array. If the array is three-dimensional, then the method will contour the layer tied to this class (self.layer).

**Parameters**

- **a** (`numpy.ndarray`) – Array to plot.
- **masked\_values** (`iterable of floats, ints`) – Values to mask.
- **\*\*kwargs** (`dictionary`) – keyword arguments passed to `matplotlib.pyplot.pcolormesh`

**Returns** `contour_set`**Return type** `matplotlib.pyplot.contour`



**contour\_array\_cvfd**(*vertc, a, masked\_values=None, \*\*kwargs*)

Contour a cvfd array. If the array is three-dimensional, then the method will contour the layer tied to this class (*self.layer*). The vertices must be in the same coordinates as the rotated and offset grid.

**Parameters**

- **vertc** (*np.ndarray*) – Array with of size (nc, 2) with centroid location of cvfd
- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.pyplot.pcolormesh

**Returns contour\_set**

**Return type** matplotlib.pyplot.contour

**property extent**

**plot\_array**(*a, masked\_values=None, \*\*kwargs*)

Plot an array. If the array is three-dimensional, then the method will plot the layer tied to this class (*self.layer*).

**Parameters**

- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.pyplot.pcolormesh

**Returns quadmesh** – matplotlib.collections.PatchCollection

**Return type** matplotlib.collections.QuadMesh or

**plot\_bc**(*name=None, package=None, kper=0, color=None, plotAll=False, \*\*kwargs*)

Plot boundary conditions locations for a specific boundary type from a flop model

**Parameters**

- **name** (*string*) – Package name string ('WEL', 'GHB', etc.). (Default is None)
- **package** (*flop.modflow.Modflow package class instance*) – flop package class instance. (Default is None)
- **kper** (*int*) – Stress period to plot
- **color** (*string*) – matplotlib color string. (Default is None)
- **plotAll** (*bool*) – Boolean used to specify that boundary condition locations for all layers will be plotted on the current ModelMap layer. (Default is False)
- **\*\*kwargs** (*dictionary*) – keyword arguments passed to matplotlib.collections.PatchCollection

**Returns quadmesh**

**Return type** matplotlib.collections.QuadMesh

**plot\_cvfd**(*verts, iverts, \*\*kwargs*)

Plot a cvfd grid. The vertices must be in the same coordinates as the rotated and offset grid.

**Parameters**

- **verts** (*ndarray*) – 2d array of x and y points.

- **iverts** (*list of lists*) – should be of len(ncells) with a list of vertex number for each cell
- **kwargs** (*dictionary*) – Keyword arguments passed to plotutil.plot\_cvfd()

**plot\_endpoint**(*ep, direction='ending', selection=None, selection\_direction=None, \*\*kwargs*)  
Plot the MODPATH endpoints.

**Parameters**

- **ep** (*rec array*) – A numpy recarray with the endpoint particle data from the MODPATH 6 endpoint file
- **direction** (*str*) – String defining if starting or ending particle locations should be considered. (default is 'ending')
- **selection** (*tuple*) – tuple that defines the zero-base layer, row, column location (l, r, c) to use to make a selection of particle endpoints. The selection could be a well location to determine capture zone for the well. If selection is None, all particle endpoints for the user-specified direction will be plotted. (default is None)
- **selection\_direction** (*str*) – String defining is a selection should be made on starting or ending particle locations. If selection is not None and selection\_direction is None, the selection direction will be set to the opposite of direction. (default is None)
- **kwargs** (*ax, c, s or size, colorbar, colorbar\_label, shrink. The*) – remaining kwargs are passed into the matplotlib scatter method. If colorbar is True a colorbar will be added to the plot. If colorbar\_label is passed in and colorbar is True then colorbar\_label will be passed to the colorbar set\_label() method. If shrink is passed in and colorbar is True then the colorbar size will be set using shrink.

**Returns sp**

**Return type** matplotlib.pyplot.scatter

**plot\_grid**(*\*\*kwargs*)  
Plot the grid lines.

**Parameters** **kwargs** (*ax, colors. The remaining kwargs are passed into the*)  
– the LineCollection constructor.

**Returns lc**

**Return type** matplotlib.collections.LineCollection

**plot\_ibound**(*ibound=None, color\_noflow='black', color\_ch='blue', color\_vpt='red', \*\*kwargs*)  
Make a plot of ibound. If not specified, then pull ibound from the self.ml

**Parameters**

- **ibound** (*numpy.ndarray*) – ibound array to plot. (Default is ibound in the modelgrid)
- **color\_noflow** (*string*) – (Default is 'black')
- **color\_ch** (*string*) – Color for constant heads (Default is 'blue'.)
- **color\_vpt** (*string*) – Color for vertical pass through cells (Default is 'red')

**Returns quadmesh**

**Return type** matplotlib.collections.QuadMesh

**plot\_inactive**(*ibound=None, color\_noflow='black', \*\*kwargs*)

Make a plot of inactive cells. If not specified, then pull ibound from the self.ml

**Parameters**

- **ibound** (*numpy.ndarray*) – ibound array to plot. (Default is ibound in ‘BAS6’ package.)
- **color\_noflow** (*string*) – (Default is ‘black’)

**Returns** quadmesh

**Return type** matplotlib.collections.QuadMesh

**plot\_pathline**(*pl, travel\_time=None, \*\*kwargs*)

Plot the MODPATH pathlines.

**Parameters**

- **pl** (*list of rec arrays or a single rec array*) – rec array or list of rec arrays is data returned from modpathfile PathlineFile get\_data() or get\_alldata() methods. Data in rec array is ‘x’, ‘y’, ‘z’, ‘time’, ‘k’, and ‘particleid’.
- **travel\_time** (*float or str*) – travel\_time is a travel time selection for the displayed pathlines. If a float is passed then pathlines with times less than or equal to the passed time are plotted. If a string is passed a variety logical constraints can be added in front of a time value to select pathlines for a select period of time. Valid logical constraints are <=, <, >=, and >. For example, to select all pathlines less than 10000 days travel\_time='< 10000' would be passed to plot\_pathline. (default is None)
- **kwargs** (*layer, ax, colors. The remaining kwargs are passed*) – into the LineCollection constructor. If layer='all', pathlines are output for all layers

**Returns** lc

**Return type** matplotlib.collections.LineCollection

**plot\_shapefile**(*shp, \*\*kwargs*)

Plot a shapefile. The shapefile must be in the same coordinates as the rotated and offset grid.

**Parameters**

- **shp** (*string or pyshp shapefile object*) – Name of the shapefile to plot
- **kwargs** (*dictionary*) – Keyword arguments passed to plotutil.plot\_shapefile()

**plot\_shapes**(*obj, \*\*kwargs*)

Plot shapes is a method that facilitates plotting a collection of geospatial objects

**Parameters**

- **obj** (*collection object*) – obj can accept the following types  
 str : shapefile name shapefile.Reader object list of [shapefile.Shape, shapefile.Shape,] shapefile.Shapes object flopy.utils.geometry.Collection object list of [flopy.utils.geometry, ...] objects geojson.GeometryCollection object geojson.FeatureCollection object shapely.GeometryCollection object list of [[vertices], ...]
- **kwargs** (*dictionary*) – keyword arguments passed to plotutil.plot\_shapefile()

**Return type** matplotlib.Collection object

**plot\_timeseries**(*ts*, *travel\_time=None*, *\*\*kwargs*)

Plot the MODPATH timeseries.

**Parameters**

- **ts** (*list of rec arrays or a single rec array*) – rec array or list of rec arrays is data returned from modpathfile TimeseriesFile get\_data() or get\_alldata() methods. Data in rec array is 'x', 'y', 'z', 'time', 'k', and 'particleid'.
- **travel\_time** (*float or str*) – travel\_time is a travel time selection for the displayed pathlines. If a float is passed then pathlines with times less than or equal to the passed time are plotted. If a string is passed a variety logical constraints can be added in front of a time value to select pathlines for a select period of time. Valid logical constraints are <=, <, >=, and >. For example, to select all pathlines less than 10000 days travel\_time='< 10000' would be passed to plot\_pathline. (default is None)
- **kwargs** (*layer, ax, colors. The remaining kwargs are passed*) – into the LineCollection constructor. If layer='all', pathlines are output for all layers

**Returns** *lo*

**Return type** list of Line2D objects

**plot\_vector**(*vx*, *vy*, *istep=1*, *jstep=1*, *normalize=False*, *masked\_values=None*, *\*\*kwargs*)

Plot a vector.

**Parameters**

- **vx** (*np.ndarray*) – x component of the vector to be plotted (non-rotated) array shape must be (nlay, nrow, ncol) for a structured grid array shape must be (nlay, ncpl) for an unstructured grid
- **vy** (*np.ndarray*) – y component of the vector to be plotted (non-rotated) array shape must be (nlay, nrow, ncol) for a structured grid array shape must be (nlay, ncpl) for an unstructured grid
- **istep** (*int*) – row frequency to plot (default is 1)
- **jstep** (*int*) – column frequency to plot (default is 1)
- **normalize** (*bool*) – boolean flag used to determine if vectors should be normalized using the vector magnitude in each cell (default is False)
- **masked\_values** (*iterable of floats*) – values to mask
- **kwargs** (*matplotlib.pyplot keyword arguments for the*) – plt.quiver method

**Returns** *quiver* – result of the quiver function

**Return type** matplotlib.pyplot.quiver

**flop.plot.plotutil module**

Module containing helper functions for plotting model data using ModelMap and ModelCrossSection. Functions for plotting shapefiles are also included.

**class PlotUtilities**

Bases: object

Class which groups a collection of plotting utilities which Flopy and Flopy6 can use to generate map based plots

**static centered\_specific\_discharge(Qx, Qy, Qz, delr, delc, sat\_thk)**

DEPRECATED. Use postprocessing.get\_specific\_discharge() instead.

Using the MODFLOW discharge, calculate the cell centered specific discharge by dividing by the flow width and then averaging to the cell center.

**Parameters**

- **Qx** (*numpy.ndarray*) – MODFLOW ‘flow right face’
- **Qy** (*numpy.ndarray*) – MODFLOW ‘flow front face’. The sign on this array will be flipped by this function so that the y axis is positive to north.
- **Qz** (*numpy.ndarray*) – MODFLOW ‘flow lower face’. The sign on this array will be flipped by this function so that the z axis is positive in the upward direction.
- **delr** (*numpy.ndarray*) – MODFLOW delr array
- **delc** (*numpy.ndarray*) – MODFLOW delc array
- **sat\_thk** (*numpy.ndarray*) – Saturated thickness for each cell

**Returns** (qx, qy, qz) – Specific discharge arrays that have been interpolated to cell centers.

**Return type** tuple of *numpy.ndarrays*

**static saturated\_thickness(head, top, botm, laytyp, mask\_values=None)**

Calculate the saturated thickness.

**Parameters**

- **head** (*numpy.ndarray*) – head array
- **top** (*numpy.ndarray*) – top array of shape (nrow, ncol)
- **botm** (*numpy.ndarray*) – botm array of shape (nlay, nrow, ncol)
- **laytyp** (*numpy.ndarray*) – confined (0) or convertible (1) of shape (nlay)
- **mask\_values** (*list of floats*) – If head is one of these values, then set sat to top - bot

**Returns** **sat\_thk** – Saturated thickness of shape (nlay, nrow, ncol).

**Return type** *numpy.ndarray*

**class SwiConcentration(model=None, botm=None, istrat=1, nu=None)**

Bases: object

The binary\_header class is a class to create headers for MODFLOW binary files

**calc\_conc(zeta, layer=None)**

Calculate concentrations for a given time step using passed zeta.

**Parameters**

- **zeta** (*dictionary of numpy arrays*) – Dictionary of zeta results. zeta keys are zero-based zeta surfaces.
- **layer** (*int*) – Concentration will be calculated for the specified layer. If layer is None, then the concentration will be calculated for all layers. (default is None).

**Returns** **conc** – Calculated concentration.

**Return type** numpy array

### Examples

```
>>> import flopy
>>> m = flopy.modflow.Modflow.load('test')
>>> c = flopy.plot.SwiConcentration(model=m)
>>> conc = c.calc_conc(z, layer=0)
```

### class UnstructuredPlotUtilities

Bases: object

Collection of unstructured grid and vertex grid compatible plotting helper functions

**static** **arctan2**(*verts, reverse=False*)

Reads 2 dimensional set of verts and orders them using the arctan 2 method

**Parameters** **verts** (*np.array of floats*) – Nx2 array of verts

**Returns** **verts** – Nx2 array of verts

**Return type** np.array of float

**static** **irregular\_shape\_patch**(*xverts, yverts*)

Patch for vertex cross section plotting when we have an irregular shape type throughout the model grid or multiple shape types.

**Parameters**

- **xverts** (*list*) – xvertices
- **yverts** (*list*) – yvertices

**Return type** xverts, yverts as np.ndarray

**static** **line\_intersect\_grid**(*ptsin, xgrid, ygrid*)

Uses cross product method to find which cells intersect with the line and then uses the parameterized line equation to calculate intersection x, y vertex points. Should be quite fast for large model grids!

**Parameters**

- **pts** (*list*) – list of tuple line vertex pairs (ex. [(1, 0), (10, 0)])
- **xgrid** (*np.array*) – model grid x vertices
- **ygrid** (*np.array*) – model grid y vertices

**Returns** **vdict**

**Return type** dict of cell vertices

**advanced\_package\_bc\_helper**(*pkg, modelgrid, kper*)

Helper function for plotting boundary conditions from “advanced” packages

**Parameters**

- **pkg** (*flopy Package objects*) –

- **modelgrid** (*flop.discretization.Grid object*) –

**cvfd\_to\_patch\_collection**(*verts, iverts*)

Create a patch collection from control volume vertices and incidence list

**Parameters**

- **verts** (*ndarray*) – 2d array of x and y points.
- **iverts** (*list of lists*) – should be of len(ncells) with a list of vertex numbers for each cell

**filter\_modpath\_by\_travel\_time**(*recarray, travel\_time*)

**Parameters**

- **recarray** –
- **travel\_time** –

**Returns**

**intersect\_modpath\_with\_crosssection**(*recarrays, projpts, xvertices, yvertices, projection, ncpl, method='cell', starting=False*)

Method to intersect modpath output with a cross-section

**Parameters**

- **recarrays** (*list*) – list of numpy recarrays
- **projpts** (*dict*) – dict of crosssectional cell vertices
- **xvertices** (*np.array*) – array of modelgrid xvertices
- **yvertices** (*np.array*) – array of modelgrid yvertices
- **projection** (*str*) – projection direction (x or y)
- **ncpl** (*int*) – number of cells per layer (cross sectional version)
- **method** (*str*) – intersection method ('cell' or 'all')
- **starting** (*bool*) – modpath starting location flag

**Returns dict**

**Return type** dictionary of intersecting recarrays

**parse\_modpath\_selection\_options**(*ep, direction, selection, selection\_direction*)

**Returns**

**plot\_cvfd**(*verts, iverts, ax=None, layer=0, cmap='Dark2', edgecolor='scaled', facecolor='scaled', a=None, masked\_values=None, \*\*kwargs*)

Generic function for plotting a control volume finite difference grid of information.

**Parameters**

- **verts** (*ndarray*) – 2d array of x and y points.
- **iverts** (*list of lists*) – should be of len(ncells) with a list of vertex number for each cell
- **ax** (*matplotlib.pyplot axis*) – matplotlib.pyplot axis instance. Default is None
- **layer** (*int*) – layer to extract. Used in combination to the optional ncpl parameter. Default is 0
- **cmap** (*string*) – Name of colormap to use for polygon shading (default is 'Dark2')
- **edgecolor** (*string*) – Color name. (Default is 'scaled' to scale the edge colors.)

- **facecolor** (*string*) – Color name. (Default is ‘scaled’ to scale the face colors.)
- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **kwargs** (*dictionary*) – Keyword arguments that are passed to `PatchCollection.set(**kwargs)`. Some common kwargs would be ‘linewidths’, ‘linestyles’, ‘alpha’, etc.

**Returns** `pc`

**Return type** `matplotlib.collections.PatchCollection`

### Examples

```
plot_shapefile(shp, ax=None, radius=500.0, cmap='Dark2', edgecolor='scaled', facecolor='scaled', a=None,
               masked_values=None, idx=None, **kwargs)
```

Generic function for plotting a shapefile.

#### Parameters

- **shp** (*string*) – Name of the shapefile to plot.
- **ax** (*matplotlib.pyplot.axes object*) –
- **radius** (*float*) – Radius of circle for points. (Default is 500.)
- **cmap** (*string*) – Name of colormap to use for polygon shading (default is ‘Dark2’)
- **edgecolor** (*string*) – Color name. (Default is ‘scaled’ to scale the edge colors.)
- **facecolor** (*string*) – Color name. (Default is ‘scaled’ to scale the face colors.)
- **a** (*numpy.ndarray*) – Array to plot.
- **masked\_values** (*iterable of floats, ints*) – Values to mask.
- **idx** (*iterable int*) – A list or array that contains shape numbers to include in the patch collection. Return all shapes if not specified.
- **kwargs** (*dictionary*) – Keyword arguments that are passed to `PatchCollection.set(**kwargs)`. Some common kwargs would be ‘linewidths’, ‘linestyles’, ‘alpha’, etc.

**Returns** `pc`

**Return type** `matplotlib.collections.PatchCollection`

### Examples

```
reproject_modpath_to_crosssection(idict, projpts, xypts, projection, modelgrid, ncpl, geographic_coords,
                                  starting=False)
```

Method to reproject modpath points onto cross sectional line

#### Parameters

- **idict** (*dict*) – dictionary of intersecting points
- **projpts** (*dict*) – dictionary of cross sectional cells
- **xypts** (*dict*) – dictionary of cross sectional line
- **projection** (*str*) – projection direction (x or y)
- **modelgrid** (*Grid object*) – flop modelgrid object



- **ncpl** (*int*) – number of cells per layer (cross sectional version)
- **geographic\_coords** (*bool*) – flag for plotting in geographic coordinates
- **starting** (*bool*) – flag for modpath position

**Return type** dictionary of projected modpath lines or points

#### **shapefile\_extents**(*shp*)

Determine the extents of a shapefile

**Parameters** **shp** (*string*) – Name of the shapefile to convert to a PatchCollection.

**Returns** **extents** – tuple with xmin, xmax, ymin, ymax from shapefile.

**Return type** tuple

#### Examples

```
>>> import flopy
>>> fshp = 'myshapefile'
>>> extent = flopy.plot.plotutil.shapefile_extents(fshp)
```

#### **shapefile\_get\_vertices**(*shp*)

Get vertices for the features in a shapefile

**Parameters** **shp** (*string*) – Name of the shapefile to extract shapefile feature vertices.

**Returns** **vertices** – Vertices is a list with vertices for each feature in the shapefile. Individual feature vertices are x, y tuples and contained in a list. A list with a single x, y tuple is returned for point shapefiles. A list with multiple x, y tuples is returned for polyline and polygon shapefiles.

**Return type** list

#### Examples

```
>>> import flopy
>>> fshp = 'myshapefile'
>>> lines = flopy.plot.plotutil.shapefile_get_vertices(fshp)
```

#### **shapefile\_to\_patch\_collection**(*shp, radius=500.0, idx=None*)

Create a patch collection from the shapes in a shapefile

**Parameters**

- **shp** (*string*) – Name of the shapefile to convert to a PatchCollection.
- **radius** (*float*) – Radius of circle for points in the shapefile. (Default is 500.)
- **idx** (*iterable int*) – A list or array that contains shape numbers to include in the patch collection. Return all shapes if not specified.

**Returns** **pc** – Patch collection of shapes in the shapefile

**Return type** matplotlib.collections.PatchCollection

**flop.plot.styles module****class styles**

Bases: object

Styles class for custom matplotlib styling

The class contains both custom styles and plotting methods for custom formatting using a specific matplotlib style

Additional styles can be easily added to the mplstyle folder and accessed using the `plt.style.context()` method.

**classmethod** `USGSMap()`

**classmethod** `USGSPlot()`

**classmethod** `add_annotation(ax=None, text='', xy=None, xytext=None, bold=True, italic=True, fontsize=9, ha='left', va='bottom', **kwargs)`

Add an annotation to a axis object

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **text** (*str*) – text string
- **xy** (*tuple*) – tuple with the location of the annotation (default is None)
- **xytext** (*tuple*) – tuple with the location of the text
- **bold** (*bool*) – boolean indicating if bold font (default is True)
- **italic** (*bool*) – boolean indicating if italic font (default is True)
- **fontsize** (*int*) – font size (default is 9 points)
- **ha** (*str*) – matplotlib horizontal alignment keyword (default is left)
- **va** (*str*) – matplotlib vertical alignment keyword (default is bottom)
- **kwargs** (*dict*) – dictionary with valid matplotlib annotation object keywords

**Returns** `ann_obj` – matplotlib annotation object

**Return type** object

**classmethod** `add_text(ax=None, text='', x=0.0, y=0.0, transform=True, bold=True, italic=True, fontsize=9, ha='left', va='bottom', **kwargs)`

Add USGS-style text to a axis object

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **text** (*str*) – text string
- **x** (*float*) – x-location of text string (default is 0.)
- **y** (*float*) – y-location of text string (default is 0.)
- **transform** (*bool*) – boolean that determines if a transformed (True) or data (False) coordinate system is used to define the (x, y) location of the text string (default is True)
- **bold** (*bool*) – boolean indicating if bold font (default is True)
- **italic** (*bool*) – boolean indicating if italic font (default is True)

- **fontsize** (*int*) – font size (default is 9 points)
- **ha** (*str*) – matplotlib horizontal alignment keyword (default is left)
- **va** (*str*) – matplotlib vertical alignment keyword (default is bottom)
- **kwargs** (*dict*) – dictionary with valid matplotlib text object keywords

**Returns** **text\_obj** – matplotlib text object

**Return type** object

**classmethod** **graph\_legend**(*ax=None, handles=None, labels=None, \*\*kwargs*)

Add a USGS-style legend to a matplotlib axis object

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **handles** (*list*) – list of legend handles
- **labels** (*list*) – list of labels for legend handles
- **kwargs** (*kwargs*) – matplotlib legend kwargs

**Returns** **leg** – matplotlib legend object

**Return type** object

**classmethod** **graph\_legend\_title**(*leg, title=None*)

Set the legend title for a matplotlib legend object

**Parameters**

- **leg** (*legend object*) – matplotlib legend object
- **title** (*str*) – title for legend

**Returns** **leg** – matplotlib legend object

**Return type** object

**classmethod** **heading**(*ax=None, letter=None, heading=None, x=0.0, y=1.01, idx=None, fontsize=9*)

Add a USGS-style heading to a matplotlib axis object

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **letter** (*str*) – string that defines the subplot (A, B, C, etc.)
- **heading** (*str*) – text string
- **x** (*float*) – location of the heading in the x-direction in normalized plot dimensions ranging from 0 to 1 (default is 0.00)
- **y** (*float*) – location of the heading in the y-direction in normalized plot dimensions ranging from 0 to 1 (default is 1.01)
- **idx** (*int*) – index for programatically generating the heading letter when letter is None and idx is not None. idx = 0 will generate A (default is None)

**Returns** **text** – matplotlib text object

**Return type** object

**classmethod** **remove\_edge\_ticks**(*ax=None*)

Remove unnecessary ticks on the edges of the plot

**Parameters** **ax** (*axis object*) – matplotlib axis object (default is None)

**Returns** **ax** – matplotlib axis object

**Return type** axis object

**classmethod** **set\_font\_type**(*family, fontname*)

Method to set the matplotlib font type for the current style

Note: this method only works when adding text using the styles methods.

**Parameters**

- **family** (*str*) – matplotlib.rcParams font.family
- **font** (*str*) – matplotlib.rcParams font.fontname

**Return type** None

**classmethod** **xlabel**(*ax=None, label="", bold=False, italic=False, \*\*kwargs*)

Method to set the xlabel using the styled fontdict

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **label** (*str*) – axis label for the chart
- **bold** (*bool*) – flag to switch to boldface text
- **italic** (*bool*) – flag to use italic text
- **kwargs** (*dict*) – keyword arguments for the matplotlib set\_xlabel method

**Return type** None

**classmethod** **ylabel**(*ax=None, label="", bold=False, italic=False, \*\*kwargs*)

Method to set the ylabel using the styled fontdict

**Parameters**

- **ax** (*axis object*) – matplotlib axis object (default is None)
- **label** (*str*) – axis label for the chart
- **bold** (*bool*) – flag to switch to boldface text
- **italic** (*bool*) – flag to use italic text
- **kwargs** (*dict*) – keyword arguments for the matplotlib set\_xlabel method

**Return type** None

## Export Utilities

Contents:

## flopY.export.longnames module

Human readable long names for netCDF variables.

## flopY.export.metadata module

**class** `acdd(sciencebase_id, model)`

Bases: `object`

Translate ScienceBase global metadata attributes to CF and ACDD global attributes.

### Parameters

- **sciencebase\_id** (*str*) – Unique identifier for ScienceBase record (e.g. 582da7efe4b04d580bd37be8)
- **model** (*flopY model object*) – Model object

## References

<https://www.sciencebase.gov/catalog/> <http://cfconventions.org/cf-conventions/v1.6.0/cf-conventions.html#description-of-file-contents> [http://wiki.esipfed.org/index.php/Attribute\\_Convention\\_for\\_Data\\_Discovery](http://wiki.esipfed.org/index.php/Attribute_Convention_for_Data_Discovery)

**property** `bounds`

**property** `creator`

**property** `creator_url`

**property** `geospatial_bounds`

Describes the data's 2D or 3D geospatial extent in OGC's Well-Known Text (WKT) Geometry format

**property** `geospatial_bounds_vertical_crs`

The vertical coordinate reference system (CRS) for the Z axis of the point coordinates in the `geospatial_bounds` attribute.

**get\_sciencebase\_metadata**(*id*)

Gets metadata json text for given ID from sciencebase.gov; loads into python dictionary. Fetches the reference text using the url: <https://www.sciencebase.gov/catalog/item/<ID>?format=json>

**Parameters** **ID** (*str*) – ScienceBase ID string; e.g. 582da7efe4b04d580bd37be8 for Dane County Model

**Returns** **metadata** – Dictionary of metadata

**Return type** `dict`

**get\_sciencebase\_xml\_metadata**()

Gets xml from sciencebase.gov, using XML url obtained from json using `get_sciencebase_metadata()`.

**Parameters** **ID** (*str*) – ScienceBase ID string; e.g. 582da7efe4b04d580bd37be8 for Dane County Model

**Returns** **metadata** – Dictionary of metadata

**Return type** `dict`

**property** `references`

**property** `time_coverage`

**property vertical\_datum**

Try to parse the vertical datum from the xml info

**property xmlfile****property xmlroot**

ElementTree root element object for xml metadata

**flop.export.netcdf module****class Logger**(*filename, echo=False*)

Bases: object

Basic class for logging events during the linear analysis calculations if filename is passed, then an file handle is opened

**Parameters** **filename** (*bool or string*) – if string, it is the log file to write. If a bool, then log is written to the screen. **echo** (*bool*): a flag to force screen output

**items**

tracks when something is started. If a log entry is not in items, then it is treated as a new entry with the string being the key and the datetime as the value. If a log entry is in items, then the end time and delta time are written and the item is popped from the keys

**Type** dict

**log**(*phrase*)

log something that happened

**Parameters** **phrase** (*str*) – the thing that happened

**warn**(*message*)

Write a warning to the log file

**Parameters** **message** (*str*) – the warning text

**class NetCdf**(*output\_filename, model, time\_values=None, z\_positive='up', verbose=None, prj=None, logger=None, forgive=False, \*\*kwargs*)

Bases: object

Support for writing a netCDF4 compliant file from a flop model

**Parameters**

- **output\_filename** (*str*) – Name of the .nc file to write
- **model** (*flop model instance*) –
- **time\_values** (*the entries for the time dimension*) – if not None, the constructor will initialize the file. If None, the perlen array of ModflowDis will be used
- **z\_positive** (*str ('up' or 'down')*) – Positive direction of vertical coordinates written to NetCDF file. (default 'down')
- **verbose** (*if True, stdout is verbose. If str, then a log file*) – is written to the verbose file
- **forgive** (*what to do if a duplicate variable name is being created. If*) – True, then the newly requested var is skipped. If False, then an exception is raised.
- **\*\*kwargs** (*keyword arguments*) –

**modelgrid** [*flop.discretization.Grid instance*] user supplied model grid which will be used in lieu of the model object modelgrid for netcdf production

## Notes

This class relies heavily on the grid and modeltime objects, including these attributes: `lenuni`, `itmuni`, `start_datetime`, and `proj4`. Make sure these attributes have meaningful values.

**add\_global\_attributes**(*attr\_dict*)

add global attribute to an initialized file

**Parameters** *attr\_dict* (*dict*(*attribute name*, *attribute value*)) –

**Return type** `None`

**Raises**

- **Exception of `self.nc` is `None` (`initialize_file()` –**
- **has not been called) –**

**add\_sciencebase\_metadata**(*id*, *check=True*)

Add metadata from ScienceBase using the `flopy.export.metadata.acdd` class.

**Returns metadata**

**Return type** `flopy.export.metadata.acdd` object

**append**(*other*, *suffix='\_1'*)

**copy**(*output\_filename*)

**create\_group\_variable**(*group*, *name*, *attributes*, *precision\_str*, *dimensions=('time',)*)

Create a new group variable in the netcdf object

**Parameters**

- **name** (*str*) – the name of the variable
- **attributes** (*dict*) – attributes to add to the new variable
- **precision\_str** (*str*) – netcdf-compliant string. e.g. `f4`
- **dimensions** (*tuple*) – which dimensions the variable applies to default : (`"time"`, `"layer"`, `"x"`, `"y"`)
- **group** (*str*) – which netcdf group the variable goes in default : `None` which creates the variable in root

**Return type** `nc` variable

**Raises**

- **AssertionError if `precision_str` not right –**
- **AssertionError if variable name already in netcdf object –**
- **AssertionError if one of more dimensions do not exist –**

**create\_variable**(*name*, *attributes*, *precision\_str='f4'*, *dimensions=('time', 'layer')*, *group=None*)

Create a new variable in the netcdf object

**Parameters**

- **name** (*str*) – the name of the variable
- **attributes** (*dict*) – attributes to add to the new variable
- **precision\_str** (*str*) – netcdf-compliant string. e.g. `f4`

- **dimensions** (*tuple*) – which dimensions the variable applies to default : (“time”, “layer”, “x”, “y”)
- **group** (*str*) – which netcdf group the variable goes in default : None which creates the variable in root

**Return type** nc variable

**Raises**

- **AssertionError** if **precision\_str** not right –
- **AssertionError** if **variable name** already in netcdf object –
- **AssertionError** if one of more dimensions do not exist –

**difference**(*other*, *minuend*='self', *mask\_zero\_diff*=True, *onlydiff*=True)

make a new NetCDF instance that is the difference with another netcdf file

**Parameters**

- **other** (*either an str filename of a netcdf file or*) – a netCDF4 instance
- **minuend** (*(optional) the order of the difference operation.*) – Default is self (e.g. self - other). Can be “self” or “other”
- **mask\_zero\_diff** (*bool flag to mask differences that are zero. If*) – True, positions in the difference array that are zero will be set to self.fillvalue
- **only\_diff** (*bool flag to only add non-zero diffs to output file*) –

**Return type** net NetCDF instance

## Notes

assumes the current NetCDF instance has been populated. The variable names and dimensions between the two files must match exactly. The name of the new .nc file is <self.output\_filename>.diff.nc. The masks from both self and other are carried through to the new instance

**classmethod empty\_like**(*other*, *output\_filename*=None, *verbose*=None, *logger*=None)

**get\_longnames\_from\_docstrings**(*outfile*='longnames.py')

This is experimental.

Scrape Flopy module docstrings and return docstrings for parameters included in the list of variables added to NetCdf object. Create a dictionary of longnames keyed by the NetCdf variable names; make each longname from the first sentence of the docstring for that parameter.

One major limitation is that variables from mflists often aren’t described in the docstrings.

**initialize\_file**(*time\_values*=None)

initialize the netcdf instance, including global attributes, dimensions, and grid information

**Parameters** **time\_values** (*list of times to use as time dimension*) – entries. If none, then use the times in self.model.dis.perlen and self.start\_datetime

**initialize\_geometry**()

initialize the geometric information needed for the netcdf file

**initialize\_group**(*group*='timeseries', *dimensions*=('time'), *attributes*=None, *dimension\_data*=None)

Method to initialize a new group within a netcdf file. This group can have independent dimensions from the global dimensions



**name** [str] name of the netcdf group

**dimensions** [tuple] data dimension names for group

**dimension\_shape** [tuple] tuple of data dimension lengths

**attributes** [dict] nested dictionary of {dimension : {attributes}} for each netcdf group dimension

**dimension\_data** [dict] dictionary of {dimension : [data]} for each netcdf group dimension

**static normalize\_name(name)**

**write()**  
write the nc object to disk

**classmethod zeros\_like(other, output\_filename=None, verbose=None, logger=None)**

### flopY.export.shapefile\_utils module

Module for exporting and importing flopY model attributes

**class CRS**(prj=None, esri\_wkt=None, epsg=None)

Bases: object

Container to parse and store coordinate reference system parameters, and translate between different formats.

#### property crs

Dict mapping crs attributes to proj4 parameters

**static get\_spatialreference**(epsg, text='esriwkt')

Gets text for given epsg code and text format from spatialreference.org Fetches the reference text using the url:

<https://spatialreference.org/ref/epsg/<epsg code>/<text>>

See: <https://www.epsg-registry.org/>

#### Parameters

- **epsg** (int) – epsg code for coordinate system
- **text** (str) – string added to url

#### Returns url

**Return type** str

**static getprj**(epsg, addlocalreference=True, text='esriwkt')

Gets projection file (.prj) text for given epsg code from spatialreference.org See: <https://www.epsg-registry.org/>

#### Parameters

- **epsg** (int) – epsg code for coordinate system
- **addlocalreference** (boolean) – adds the projection file text associated with epsg to a local database, epsgref.json, located in the user's data directory.

**Returns prj** – text for a projection (\*.prj) file.

**Return type** str

**static getproj4**(epsg)

Gets projection file (.prj) text for given epsg code from spatialreference.org. See: <https://www.epsg-registry.org/>

**Parameters** `epsg` (*int*) – epsg code for coordinate system

**Returns** `prj` – text for a projection (*\**.prj) file.

**Return type** `str`

**property** `grid_mapping_attris`

Map parameters for CF Grid Mappings <http://http://cfconventions.org/cf-conventions/cf-conventions.html>, Appendix F: Grid Mappings

**parse\_wkt()**

**property** `proj4`

Not implemented yet

**class** `EpsgReference`

Bases: `object`

Sets up a local database of text representations of coordinate reference systems, keyed by EPSG code.

The database is `epsgref.json`, located in the user's data directory. If optional 'appdirs' package is available, this is in the platform-dependent user directory, otherwise in the user's 'HOME/.flopy' directory.

**add**(*epsg*, *prj*)

add an epsg code to `epsgref.json`

**get**(*epsg*)

returns `prj` from a epsg code, otherwise `None` if not found

**remove**(*epsg*)

removes an epsg entry from `epsgref.json`

**reset**(*verbose=True*)

**static** `show()`

**to\_dict()**

returns dict with EPSG code integer key, and WKT CRS text

**enforce\_10ch\_limit**(*names*)

Enforce 10 character limit for fieldnames. Add suffix for duplicate names starting at 0.

**Parameters** `names` (*list of strings*) –

**Returns** `names`

**Return type** list of unique strings of len <= 10.

**get\_pyshp\_field\_dtypes**(*code*)

Returns a numpy dtype for a pyshp field type.

**get\_pyshp\_field\_info**(*dtype*)

Get pyshp dtype information for a given numpy dtype.

**model\_attributes\_to\_shapefile**(*filename*, *ml*, *package\_names=None*, *array\_dict=None*, *\*\*kwargs*)

Wrapper function for writing a shapefile of model data. If `package_names` is not `None`, then search through the requested packages looking for arrays that can be added to the shapefile as attributes

**Parameters**

- **filename** (*string*) – name of the shapefile to write
- **ml** (*flopy.mbase*) – model instance
- **package\_names** (*list of package names (e.g. ["dis", "lpf"])*) – Packages to export data arrays to shapefile. (default is `None`)

- **array\_dict** (*dict of {name:2D array} pairs*) – Additional 2D arrays to add as attributes to the shapefile. (default is None)
- **\*\*kwargs** (*keyword arguments*) –
  - modelgrid** [`fp.modflow.Grid` object] if `modelgrid` is supplied, user supplied `modelgrid` is used in lieu of the `modelgrid` attached to the `modflow` model object
  - epsg** [`int`] `epsg` projection information
  - prj** [`str`] user supplied `prj` file

**Return type** None

## Examples

```
>>> import flopY
>>> m = flopY.modflow.Modflow()
>>> flopY.utils.model_attributes_to_shapefile('model.shp', m)
```

**recarray2shp**(*recarray, geoms, shpname='recarray.shp', mg=None, epsg=None, prj=None, \*\*kwargs*)

Write a numpy record array to a shapefile, using a corresponding list of geometries. Method supports list of flopY geometry objects, flopY Collection object, shapely Collection object, and geojson Geometry Collection objects

### Parameters

- **recarray** (*np.recarray*) – Numpy record array with attribute information that will go in the shapefile
  - **geoms** (*list of flopY.utils.geometry, shapely geometry collection,*) – **flopY geometry collection, shapefile.Shapes**, list of `shapefile.Shape` objects, or `geojson` geometry collection
- The number of geometries in `geoms` must equal the number of records in `recarray`.
- **shpname** (*str*) – Path for the output shapefile
  - **epsg** (*int*) – EPSG code. See <https://www.epsg-registry.org/> or [spatialreference.org](https://spatialreference.org/)
  - **prj** (*str*) – Existing projection file to be used with new shapefile.

## Notes

Uses `pysp`. `epsg` code requires an internet connection the first time to get the projection file text from [spatialreference.org](https://spatialreference.org/), but then stashes the text in the file `epsgref.json` (located in the user's data directory) for subsequent use. See `flopY.reference` for more details.

**shape\_attr\_name**(*name, length=6, keep\_layer=False*)

Function for to format an array name to a maximum of 10 characters to conform with ESRI shapefile maximum attribute name length

### Parameters

- **name** (*string*) – data array name
- **length** (*int*) – maximum length of string to return. Value passed to function is overridden and set to 10 if `keep_layer=True`. (default is 6)
- **keep\_layer** (*bool*) – Boolean that determines if layer number in name should be retained. (default is False)

**Return type** String

## Examples

```
>>> import flopY
>>> name = flopY.utils.shape_attr_name('averylongstring')
>>> name
>>> 'averyl'
```

### **shp2recarray**(*shpname*)

Read a shapefile into a numpy recarray.

**Parameters** **shpname** (*str*) – ESRI Shapefile.

**Returns** **recarray**

**Return type** `np.recarray`

### **write\_grid\_shapefile**(*filename, mg, array\_dict, nan\_val=nan, epsg=None, prj=None*)

Method to write a shapefile of gridded input data

**Parameters**

- **filename** (*str*) – shapefile file name path
- **mg** (*flopY.discretization.Grid object*) – flopY model grid
- **array\_dict** (*dict*) – dictionary of model input arrays
- **nan\_val** (*float*) – value to fill nans
- **epsg** (*str, int*) – epsg code
- **prj** (*str*) – projection file name path

**Return type** `None`

### **write\_gridlines\_shapefile**(*filename, mg*)

Write a polyline shapefile of the grid lines - a lightweight alternative to polygons.

**Parameters**

- **filename** (*string*) – name of the shapefile to write
- **mg** (*model grid*) –

**Return type** `None`

### **write\_prj**(*shpname, mg=None, epsg=None, prj=None, wkt\_string=None*)

## flopY.export.unitsformat module

unit format strings for netCDF variables.

## flopY.export.utils module

### **array2d\_export**(*f, u2d, fmt=None, \*\*kwargs*)

export helper for Util2d instances

**Parameters**

- **f** (*str*) – filename or existing export instance type (NetCdf only for now)
- **u2d** (*Util2d instance*) –
- **fmt** (*str*) – output format flag. ‘vtk’ will export to vtk

- **\*\*kwargs** (*keyword arguments*) – min\_valid : minimum valid value max\_valid : maximum valid value modelgrid : flopy.discretization.Grid

model grid instance which will supercede the flopy.model.modelgrid

if fmt is set to 'vtk', parameters of vtk.export\_array

**array3d\_export**(*f, u3d, fmt=None, \*\*kwargs*)

export helper for Transient2d instances

#### Parameters

- **f** (*str*) – filename or existing export instance type (NetCdf only for now)
- **u3d** (*Util3d instance*) –
- **fmt** (*str*) – output format flag. 'vtk' will export to vtk
- **\*\*kwargs** (*keyword arguments*) – min\_valid : minimum valid value max\_valid : maximum valid value modelgrid : flopy.discretization.Grid

model grid instance which will supercede the flopy.model.modelgrid

if fmt is set to 'vtk', parameters of vtk.export\_array

**contour\_array**(*modelgrid, ax, a, \*\*kwargs*)

Create a QuadMesh plot of the specified array using pcolormesh

#### Parameters

- **modelgrid** (*flopy.discretization.Grid object*) – modelgrid object
- **ax** (*matplotlib.axes.Axes*) – ax to add the contours
- **a** (*np.ndarray*) – array to contour

**Returns** *contour\_set*

**Return type** ContourSet

**ensemble\_helper**(*inputs\_filename, outputs\_filename, models, add\_reals=True, \*\*kwargs*)

Helper to export an ensemble of model instances. Assumes all models have same dis and reference information, only difference is properties and boundary conditions. Assumes model.nam.split('\_')[-1] is the realization suffix to use in the netcdf variable names

**export\_array**(*modelgrid, filename, a, nodata=-9999, fieldname='value', \*\*kwargs*)

Write a numpy array to Arc Ascii grid or shapefile with the model reference.

#### Parameters

- **modelgrid** (*flopy.discretization.StructuredGrid object*) – model grid
- **filename** (*str*) – Path of output file. Export format is determined by file extension. 'asc' Arc Ascii grid 'tif' GeoTIFF (requires rasterio package) 'shp' Shapefile
- **a** (*2D numpy.ndarray*) – Array to export
- **nodata** (*scalar*) – Value to assign to np.nan entries (default -9999)
- **fieldname** (*str*) – Attribute field name for array values (shapefile export only). (default 'values')
- **kwargs** – keyword arguments to np.savetxt (ascii) rasterio.open (GeoTIFF) or flopy.export.shapefile\_utils.write\_grid\_shapefile2

## Notes

Rotated grids will be either be unrotated prior to export, using `scipy.ndimage.rotate` (Arc Ascii format) or rotation will be included in their transform property (GeoTiff format). In either case the pixels will be displayed in the (unrotated) projected geographic coordinate system, so the pixels will no longer align exactly with the model grid (as displayed from a shapefile, for example). A key difference between Arc Ascii and GeoTiff (besides disk usage) is that the unrotated Arc Ascii will have a different grid size, whereas the GeoTiff will have the same number of rows and pixels as the original.

**export\_array\_contours**(*modelgrid, filename, a, fieldname='level', interval=None, levels=None, maxlevels=1000, epsg=None, prj=None, \*\*kwargs*)

Contour an array using matplotlib; write shapefile of contours.

### Parameters

- **modelgrid** (*flop.discretization.Grid object*) – model grid object
- **filename** (*str*) – Path of output file with ‘.shp’ extention.
- **a** (*2D numpy array*) – Array to contour
- **fieldname** (*str*) – gis field name
- **interval** (*float*) – interval to calculate levels from
- **levels** (*list*) – list of contour levels
- **maxlevels** (*int*) – maximum number of contour levels
- **epsg** (*int*) – EPSG code. See <https://www.epsg-registry.org/> or [spatialreference.org](https://spatialreference.org)
- **prj** (*str*) – Existing projection file to be used with new shapefile.
- **\*\*kwargs** (*keyword arguments to flop.export.shapefile\_utils.reccarray2shp*) –

**export\_contourf**(*filename, contours, fieldname='level', epsg=None, prj=None, \*\*kwargs*)

Write matplotlib filled contours to shapefile.

### Parameters

- **filename** (*str*) – name of output shapefile (e.g. myshp.shp)
- **contours** (*matplotlib.contour.QuadContourSet or list of them*) – (object returned by `matplotlib.pyplot.contourf`)
- **fieldname** (*str*) – Name of shapefile attribute field to contain the contour level. The fieldname column in the attribute table will contain the lower end of the range represented by the polygon. Default is ‘level’.
- **epsg** (*int*) – EPSG code. See <https://www.epsg-registry.org/> or [spatialreference.org](https://spatialreference.org)
- **prj** (*str*) – Existing projection file to be used with new shapefile.
- **\*\*kwargs** (*keyword arguments to flop.export.shapefile\_utils.reccarray2shp*) –

**Return type** None

## Examples

```
>>> import flopy
>>> import matplotlib.pyplot as plt
>>> from flopy.export.utils import export_contourf
>>> a = np.random.random((10, 10))
>>> cs = plt.contourf(a)
>>> export_contourf('myfilledcontours.shp', cs)
```

**export\_contours**(*modelgrid*, *filename*, *contours*, *fieldname*='level', *epsg*=None, *prj*=None, *\*\*kwargs*)  
Convert matplotlib contour plot object to shapefile.

### Parameters

- **modelgrid** (*flopy.discretization.Grid*) – flopy modelgrid instance
- **filename** (*str*) – path of output shapefile
- **contours** (*matplotlib.contour.QuadContourSet* or *list of them*) – (object returned by `matplotlib.pyplot.contour`)
- **fieldname** (*str*) – gis attribute table field name
- **epsg** (*int*) – EPSG code. See <https://www.epsg-registry.org/> or [spatialreference.org](http://spatialreference.org)
- **prj** (*str*) – Existing projection file to be used with new shapefile.
- **\*\*kwargs** (*key-word arguments to flopy.export.shapefile\_utils.reccarray2shp*) –

### Returns df

**Return type** dataframe of shapefile contents

**generic\_array\_export**(*f*, *array*, *var\_name*='generic\_array', *dimensions*=('time', 'layer', 'y', 'x'), *precision\_str*='f4', *units*='unitless', *\*\*kwargs*)

Method to export a generic array to NetCdf

### Parameters

- **f** (*str*) – filename or existing export instance type (NetCdf only for now)
- **array** (*np.ndarray*) –
- **var\_name** (*str*) – variable name
- **dimensions** (*tuple*) – netcdf dimensions
- **precision\_str** (*str*) – binary precision string, default “f4”
- **units** (*string*) – units of array data
- **\*\*kwargs** (*keyword arguments*) –
- **model** [*flopy.modflow.mbase*] flopy model object

**mflist\_export**(*f*, *mfl*, *\*\*kwargs*)

export helper for MfList instances

### Parameters

- **f** (*str*) – filename or existing export instance type (NetCdf only for now)
- **mfl** (*MfList instance*) –
- **\*\*kwargs** (*keyword arguments*) –

**modelgrid** [flop.discretization.Grid] model grid instance which will supercede the flop.model.modelgrid

**model\_export**(*f*, *ml*, *fmt=None*, *\*\*kwargs*)

Method to export a model to a shapefile or netcdf file

**Parameters**

- **f** (*str*) – file name (“nc” for netcdf or “.shp” for shapefile) or dictionary of ....
- **ml** (*flop.modflow.mbase.ModelInterface object*) – flop model object
- **fmt** (*str*) – output format flag. ‘vtk’ will export to vtk
- **\*\*kwargs** (*keyword arguments*) –  
**modelgrid**: **flop.discretization.Grid** user supplied modelgrid object which will supercede the built in modelgrid object  
**epsg** [int] epsg projection code  
**prj** [str] prj file name  
if fmt is set to ‘vtk’, parameters of vtk.export\_model

**output\_helper**(*f*, *ml*, *oudic*, *\*\*kwargs*)

Export model outputs using the model spatial reference info.

**Parameters**

- **f** (*str*) – filename for output - must have .shp or .nc extension
- **ml** (*flop.mbase.ModelInterface derived type*) –
- **oudic** (*dict*) – output\_filename, flop datafile/cellbudgetfile instance
- **\*\*kwargs** (*keyword arguments*) –  
**modelgrid** [flop.discretization.Grid] user supplied model grid instance that will be used for export in lieu of the models model grid instance  
**mflay** [int] zero based model layer which can be used in shapefile exporting  
**kper** [int] zero based stress period which can be used for shapefile exporting

**Return type** None

casts down double precision to single precision for netCDF files

**package\_export**(*f*, *pak*, *fmt=None*, *\*\*kwargs*)

Method to export a package to shapefile or netcdf

**Parameters**

- **f** (*str*) – output file name (ends in .shp for shapefile or .nc for netcdf)
- **pak** (*flop.pakbase.Package object*) – package to export
- **fmt** (*str*) – output format flag. ‘vtk’ will export to vtk
- **kwargs** (*\*\**) –  
**modelgrid**: **flop.discretization.Grid** user supplied modelgrid object which will supercede the built in modelgrid object  
**epsg** [int] epsg projection code  
**prj** [str] prj file name  
if fmt is set to ‘vtk’, parameters of vtk.export\_package



**Return type** NetCdf object or None

## Parameters

- ## flopy.export.vtk module

```
class Pvd
```

## Simple class to build a Paraview Data File (PVD)

### Method to add a Dataset record to the pvd file

- **file** (*str*) – vtu file name
- **timevalue** (*float*) – time step value in model time

### Method to write a pvd file from the PVD object

**f** [str] PVD file name

Bases: object

Class that builds VTK objects and exports models to VTK files

**model** [flopy.ModelInterface object] any flopy model object, example flopy.modflow.Modflow() object

**modelgrid** [flopy.discretization.Grid object] any flopy modelgrid object, example. VertexGrid

**vertical\_exaggeration** [float] floating point value to scale vertical exaggeration of the vtk points default is 1.

**binary** [bool] flag that indicates if Vtk will write a binary or text file. Binary is preferred as paraview has a bug (8/4/2021) where it cannot represent NaN values from ASCII (non xml) files. In this case no-data values are set to 1e+30.

**xml** [bool] flag to write xml based VTK files

**pvd** [bool] boolean flag to write a paraview pvd file for transient data. This file maps vtk files to a model time.

**shared\_points** [bool] boolean flag to share points in grid polyhedron construction. Default is False, as paraview has a bug (8/4/2021) where some polyhedrons will not properly close when using shared points. If shared\_points is True file size will be slightly smaller.

**smooth** [bool] boolean flag to interpolate vertex elevations based on shared cell elevations. Default is False.

**point\_scalars** [bool] boolean flag to write interpolated data at each point based “shared vertices”.

**add\_array**(*array, name, masked\_values=None, dtype=None*)

Method to set an array to the vtk grid

**Parameters**

- **array** (*np.ndarray, list*) – list of array values to set to the vtk\_array
- **name** (*str*) – array name for vtk
- **masked\_values** (*list, None*) – list of values to set equal to nan
- **dtype** (*vtk datatype object*) – method to supply and force a vtk datatype

**add\_cell\_budget**(*cbc, text=None, kstpkper=None, masked\_values=None*)

Method to add cell budget data to vtk

**Parameters**

- **cbc** (*flop.utils.CellBudget object*) – flop binary CellBudget object
- **text** (*str or None*) – The text identifier for the record. Examples include ‘RIVER LEAKAGE’, ‘STORAGE’, ‘FLOW RIGHT FACE’, etc. If text=None all compatible records are exported
- **kstpkper** (*tuple, list of tuples, None*) – tuple or list of tuples of kstpkper, if kstpkper=None all records are selected
- **masked\_values** (*list, None*) – list of values to set equal to nan

**add\_heads**(*hds, kstpkper=None, masked\_values=None*)

Method to add head data to a vtk file

**Parameters**

- **hds** (*flop.utils.LayerFile object*) – Binary or Formatted HeadFile type object
- **kstpkper** (*tuple, list of tuples, None*) – tuple or list of tuples of kstpkper, if kstpkper=None all records are selected
- **masked\_values** (*list, None*) – list of values to set equal to nan

**add\_model**(*model, selpaklist=None, masked\_values=None*)

Method to add all array and transient list data from a modflow model to a timeseries of vtk files

**Parameters**

- **model** (*fp.modflow.ModelInterface*) – any flop model object
- **selpaklist** (*list, None*) – optional parameter where the user can supply a list of packages to export.
- **masked\_values** (*list, None*) – list of values to set equal to nan

**add\_package**(*pkg, masked\_values=None*)

Method to set all arrays within a package to VTK arrays

**Parameters**

- **pkg** (*flop.pakbase.Package object*) – flop package object, example ModflowWel
- **masked\_values** (*list, None*) – list of values to set equal to nan

**add\_pathline\_points**(*pathlines, timeseries=False*)

Method to add Modpath output from a pathline or timeseries file to the grid. Colors will be representative of totim.

**pathlines** [np.reccarray or list] pathlines accepts a numpy reccarray of a particle pathline or a list of numpy reccarrays associated with pathlines

**timeseries** [bool] method to plot data as a series of vtk timeseries files for animation or as a single static vtk file. Default is false

**add\_transient\_array**(*d*, *name=None*, *masked\_values=None*)

Method to add transient array data to the vtk object

#### Parameters

- **d** (*dict*) – dictionary of array2d, array3d data or numpy array data
- **name** (*str*, *None*) – parameter name, required when user provides a dictionary of numpy arrays
- **masked\_values** (*list*, *None*) – list of values to set equal to nan

**add\_transient\_list**(*mflist*, *masked\_values=None*)

Method to add transient list data to a vtk object

#### Parameters

- **mflist** (*flop.utils.MfList* object) –
- **masked\_values** (*list*, *None*) – list of values to set equal to nan

**add\_transient\_vector**(*d*, *name*, *masked\_values=None*)

Method to add transient vector data to vtk

**d** [dict] dictionary of vectors

**name** [str] name of vector to be displayed in vtk

**masked\_values** [list, None] list of values to set equal to nan

**add\_vector**(*vector*, *name*, *masked\_values=None*)

Method to add vector data to vtk

#### Parameters

- **vector** (*array*) – array of dimension (3, nnodes)
- **name** (*str*) – name of the vector to be displayed in vtk
- **masked\_values** (*list*, *None*) – list of values to set equal to nan

**write**(*f*, *kper=None*)

Method to write a vtk file from the VTK object

#### Parameters

- **f** (*str*) – vtk file name
- **kpers** (*int*, *list*, *tuple*) – stress period or list of stress periods to write to vtk. This parameter only applies to transient package data.

**export\_array**(*model*, *array*, *output\_folder*, *name*, *nanval=-1e+20*, *array2d=False*, *smooth=False*, *point\_scalars=False*, *vtk\_grid\_type='auto'*, *true2d=False*, *binary=True*)

DEPRECATED method to export array to vtk

#### Parameters

- **model** (*flop model instance*) – the flop model instance
- **array** (*flop array*) – flop 2d or 3d array
- **output\_folder** (*str*) – output folder to write the data

- **name** (*str*) – name of array
- **nanval** (*scalar*) – no data value, default value is -1e20
- **array2d** (*bool*) – true if the array is 2d and represents the first layer, default is False
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific `vtk_grid_type` or 'auto' (default). Possible specific values are 'ImageData', 'RectilinearGrid', and 'UnstructuredGrid'. If 'auto', the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an 'ImageData'.
  - A rectilinear (in all three directions), non-regular grid will be saved as a 'RectilinearGrid'.
  - Other grids will be saved as 'UnstructuredGrid'.
- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False

**export\_cbc**(*model*, *cbcfile*, *otfolder*, *precision*='single', *verbose*=False, *nanval*=- 1e+20, *kstp**kper*=None, *text*=None, *smooth*=False, *point\_scalars*=False, *vtk\_grid\_type*='auto', *true2d*=False, *binary*=True)

DEPRECATED method

Exports cell by cell file to vtk

#### Parameters

- **model** (*flop model instance*) – the flop model instance
- **cbcfile** (*str*) – the cell by cell file
- **otfolder** (*str*) – output folder to write the data
- **precision** (*str*) – Precision of data in the cell by cell file: 'single' or 'double'. Default is 'single'.
- **verbose** (*bool*) – If True, write information to the screen. Default is False.
- **nanval** (*scalar*) – no data value
- **kstp****kper** (*tuple of ints or list of tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). The kstp and kper values are zero based.
- **text** (*str or list of str*) – The text identifier for the record. Examples include 'RIVER LEAKAGE', 'STORAGE', 'FLOW RIGHT FACE', etc.
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific `vtk_grid_type` or 'auto' (default). Possible specific values are 'ImageData', 'RectilinearGrid', and 'UnstructuredGrid'. If 'auto', the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an 'ImageData'.
  - A rectilinear (in all three directions), non-regular grid will be saved as a 'RectilinearGrid'.

– Other grids will be saved as ‘UnstructuredGrid’.

- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False

**export\_heads**(*model*, *hdsfile*, *otfolder*, *text*='head', *precision*='auto', *verbose*=False, *nanval*=- 1e+20, *kstpkper*=None, *smooth*=False, *point\_scalars*=False, *vtk\_grid\_type*='auto', *true2d*=False, *binary*=True)

DEPRECATED method

Exports binary head file to vtk

#### Parameters

- **model** (*MFModel*) – the flopY model instance
- **hdsfile** (*str*, *HeadFile* object) – binary head file path or object
- **otfolder** (*str*) – output folder to write the data
- **text** (*string*) – Name of the text string in the head file. Default is ‘head’.
- **precision** (*str*) – Precision of data in the head file: ‘auto’, ‘single’ or ‘double’. Default is ‘auto’.
- **verbose** (*bool*) – If True, write information to the screen. Default is False.
- **nanval** (*scalar*) – no data value, default value is -1e20
- **kstpkper** (*tuple of ints or list of tuple of ints*) – A tuple containing the time step and stress period (kstp, kper). The kstp and kper values are zero based.
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific *vtk\_grid\_type* or ‘auto’ (default). Possible specific values are ‘ImageData’, ‘RectilinearGrid’, and ‘UnstructuredGrid’. If ‘auto’, the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an ‘ImageData’.
  - A rectilinear (in all three directions), non-regular grid will be saved as a ‘RectilinearGrid’.
  - Other grids will be saved as ‘UnstructuredGrid’.
- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False

**export\_model**(*model*, *otfolder*, *package\_names*=None, *nanval*=- 1e+20, *smooth*=False, *point\_scalars*=False, *vtk\_grid\_type*='auto', *true2d*=False, *binary*=True, *kpers*=None)

DEPRECATED method to export model to vtk

#### Parameters

- **model** (*flopY model instance*) – flopY model
- **otfolder** (*str*) – output folder
- **package\_names** (*list*) – list of package names to be exported
- **nanval** (*scalar*) – no data value, default value is -1e20

- **array2d** (*bool*) – True if array is 2d, default is False
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific `vtk_grid_type` or ‘auto’ (default). Possible specific values are ‘ImageData’, ‘RectilinearGrid’, and ‘UnstructuredGrid’. If ‘auto’, the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an ‘ImageData’.
  - A rectilinear (in all three directions), non-regular grid will be saved as a ‘RectilinearGrid’.
  - Other grids will be saved as ‘UnstructuredGrid’.
- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False
- **kpers** (*iterable of int*) – Stress periods to export. If None (default), all stress periods will be exported.

**export\_package**(*pak\_model*, *pak\_name*, *otfolder*, *vtkobj=None*, *nanval=-1e+20*, *smooth=False*, *point\_scalars=False*, *vtk\_grid\_type='auto'*, *true2d=False*, *binary=True*, *kpers=None*)

DEPRECATED method to export package to vtk

#### Parameters

- **pak\_model** (*flop model instance*) – the model of the package
- **pak\_name** (*str*) – the name of the package
- **otfolder** (*str*) – output folder to write the data
- **vtkobj** (*VTK instance*) – a vtk object (allows `export_package` to be called from `export_model`)
- **nanval** (*scalar*) – no data value, default value is -1e20
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific `vtk_grid_type` or ‘auto’ (default). Possible specific values are ‘ImageData’, ‘RectilinearGrid’, and ‘UnstructuredGrid’. If ‘auto’, the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an ‘ImageData’.
  - A rectilinear (in all three directions), non-regular grid will be saved as a ‘RectilinearGrid’.
  - Other grids will be saved as ‘UnstructuredGrid’.
- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False
- **kpers** (*iterable of int*) – Stress periods to export. If None (default), all stress periods will be exported.

**export\_transient**(*model*, *array*, *output\_folder*, *name*, *nanval*=- 1e+20, *array2d*=False, *smooth*=False, *point\_scalars*=False, *vtk\_grid\_type*='auto', *true2d*=False, *binary*=True, *kpers*=None)

DEPRECATED method to export transient arrays and lists to vtk

#### Parameters

- **model** (*MFModel*) – the flopY model instance
- **array** (*Transient instance*) – flopY transient array
- **output\_folder** (*str*) – output folder to write the data
- **name** (*str*) – name of array
- **nanval** (*scalar*) – no data value, default value is -1e20
- **array2d** (*bool*) – True if array is 2d, default is False
- **smooth** (*bool*) – if True, will create smooth layer elevations, default is False
- **point\_scalars** (*bool*) – if True, will also output array values at cell vertices, default is False; note this automatically sets smooth to True
- **vtk\_grid\_type** (*str*) – Specific *vtk\_grid\_type* or ‘auto’ (default). Possible specific values are ‘ImageData’, ‘RectilinearGrid’, and ‘UnstructuredGrid’. If ‘auto’, the grid type is automatically determined. Namely:
  - A regular grid (in all three directions) will be saved as an ‘ImageData’.
  - A rectilinear (in all three directions), non-regular grid will be saved as a ‘RectilinearGrid’.
  - Other grids will be saved as ‘UnstructuredGrid’.
- **true2d** (*bool*) – If True, the model is expected to be 2d (1 layer, 1 row or 1 column) and the data will be exported as true 2d data, default is False.
- **binary** (*bool*) – if True the output file will be binary, default is False
- **kpers** (*iterable of int*) – Stress periods to export. If None (default), all stress periods will be exported.

## PEST Utilities

Contents:

### flopY.pest.params module

**class Params**(*mfpkg*, *partype*, *parname*, *startvalue*, *lbound*, *ubound*, *span*, *transform*='log')

Bases: object

Class to define parameters that will be estimated using PEST.

#### Parameters

- **mfpkg** (*str*) – The Modflow package type to associated with this parameter. ‘LPF’ is one package that is working now.
- **partype** (*str*) – The parameter type, such as ‘hk’. This must be a valid attribute in the mfpkg.
- **parname** (*str*) – The parameter name, such as ‘HK\_1’.
- **startvalue** (*float*) – The starting value for the parameter.

- **lbound** (*float*) – The lower bound for the parameter.
- **ubound** (*float*) – The upper bound for the parameter.
- **span** (*dict*) – The span over which the parameter applies. The span depends on the type of array that the parameter applies to. For 3d arrays, span should have either ‘idx’ or ‘layers’ keys. span[‘layers’] should be a list of layer to for which parname will be applied as a multiplier. idx is a tuple, which contains the indices to which this parameter applies. For example, if the parameter applies to a part of a 3D MODFLOW array, then idx can be a tuple of layer, row, and column indices (e.g. (karray, iarray, jarray). This idx variable could also be a 3D bool array. It is ultimately used to assign parameter to the array using `arr[idx] = parname`. For transient 2d arrays, span must include a ‘kpers’ key such that span[‘kpers’] is a list of stress period to which parname will be applied as a multiplier.
- **transform** (*Parameter transformation type.*) –

**zonearray2params**(*mfppackage, partype, parzones, lbound, ubound, parvals, transform, zonearray*)

Helper function to create a list of flop parameters from a zone array and list of parameter zone numbers.

The parameter name is set equal to the parameter type and the parameter zone value, separated by an underscore.

## flop.pest.templatewriter module

**class** **TemplateWriter**(*model, plist*)

Bases: object

Class for writing PEST template files.

### Parameters

- **model** (*flop.modflow object*) – flop model object.
- **plist** (*list*) – list of parameter objects of type flop.pest.params.Params.

**write\_template**()

Write the template files for all model files that have arrays that have been parameterized.

## flop.pest.tplarray module

**class** **Transient2dTpl**(*transient2d*)

Bases: object

**add\_parameter**(*p*)

Store the parameters in a list for later substitution

**get\_kper\_entry**(*kper*)

**class** **Util2dTpl**(*chararray, name, multiplier, indexed\_param*)

Bases: object

Class to define a two-dimensional template array for use with parameter estimation.

### Parameters

- **chararray** (*A Numpy ndarray of dtype 'str'.*) –
- **name** (*The parameter type. This will be written to the control record*) – as a comment.
- **indexed\_param** (*bool*) – A flag to indicated whether or not the array contains parameter names within the array itself.



**get\_file\_entry()**

Convert the array into a string.

**Returns** `file_entry`

**Return type** `str`

**class** `Util3dTpl(u3d)`

Bases: `object`

Class to define a three-dimensional template array for use with parameter estimation.

**Parameters** `u3d (Util3d object)` –

**add\_parameter(p)**

Fill the chararray with the parameter name.

**Parameters** `p (flopY.pest.params.Params)` – Parameter. Must have `.idx` and `.name` attributes

**get\_template\_array(pakarray)**

Convert the package array into the appropriate template array

## Discretization Utilities

Contents:

### flopY.discretization.grid module

**class** `CachedData(data)`

Bases: `object`

**property** `data`

**property** `data_nocopy`

**update\_data(data)**

**class** `Grid(grid_type=None, top=None, botm=None, idomain=None, lenuni=None, epsg=None, proj4=None, prj=None, xoff=0.0, yoff=0.0, angrot=0.0)`

Bases: `object`

Base class for a structured or unstructured model grid

**Parameters**

- **grid\_type** (*enumeration*) – type of model grid ('structured', 'vertex', 'unstructured')
- **top** (*ndarray(float)*) – top elevations of cells in topmost layer
- **botm** (*ndarray(float)*) – bottom elevations of all cells
- **idomain** (*ndarray(int)*) – ibound/idomain value for each cell
- **lenuni** (*ndarray(int)*) – model length units
- **espg** (*str, int*) – optional espg projection code
- **proj4** (*str*) – optional proj4 projection string code
- **prj** (*str*) – optional projection file name path
- **xoff** (*float*) – x coordinate of the origin point (lower left corner of model grid) in the spatial reference coordinate system

- **yoff** (*float*) – y coordinate of the origin point (lower left corner of model grid) in the spatial reference coordinate system
- **angrot** (*float*) – rotation angle of model grid, as it is rotated around the origin point

**grid\_type**

type of model grid ('structured', 'vertex', 'unstructured')

**Type** enumeration

**top**

top elevations of cells in topmost layer

**Type** ndarray(float)

**botm**

bottom elevations of all cells

**Type** ndarray(float)

**idomain**

ibound/idomain value for each cell

**Type** ndarray(int)

**proj4**

spatial reference locates the grid in a coordinate system

**Type** proj4 SpatialReference

**epsg**

spatial reference locates the grid in a coordinate system

**Type** epsg SpatialReference

**lenuni**

modflow lenuni parameter

**Type** int

**xoffset**

x coordinate of the origin point in the spatial reference coordinate system

**Type** float

**yoffset**

y coordinate of the origin point in the spatial reference coordinate system

**Type** float

**angrot**

rotation angle of model grid, as it is rotated around the origin point

**Type** float

**angrot\_radians**

rotation angle of model grid, in radians

**Type** float

**xgrid**

returns numpy meshgrid of x edges in reference frame defined by point\_type

**Type** ndarray

**ygrid**

returns numpy meshgrid of y edges in reference frame defined by point\_type

**Type** ndarray

### **zgrid**

returns numpy meshgrid of z edges in reference frame defined by point\_type

**Type** ndarray

### **xcenters**

returns x coordinate of cell centers

**Type** ndarray

### **ycenters**

returns y coordinate of cell centers

**Type** ndarray

### **zcenters**

returns z coordinate of cell centers

**Type** ndarray

### **xyzgrid**

returns the location of grid edges of all model cells. if the model grid contains spatial reference information, the grid edges are in the coordinate system provided by the spatial reference information. returns a list of three ndarrays for the x, y, and z coordinates

**Type** [ndarray, ndarray, ndarray]

### **xyzcellcenters**

returns the cell centers of all model cells in the model grid. if the model grid contains spatial reference information, the cell centers are in the coordinate system provided by the spatial reference information. otherwise the cell centers are based on a 0,0 location for the upper left corner of the model grid. returns a list of three ndarrays for the x, y, and z coordinates

**Type** [ndarray, ndarray, ndarray]

### **get\_coords(x, y)**

transform point or array of points x, y from model coordinates to spatial coordinates

### **grid\_lines : (point\_type=PointType.spatialxyz) : list**

returns the model grid lines in a list. each line is returned as a list containing two tuples in the format [(x1,y1), (x2,y2)] where x1,y1 and x2,y2 are the endpoints of the line.

### **xyvertices : (point\_type) : ndarray**

1D array of x and y coordinates of cell vertices for whole grid (single layer) in C-style (row-major) order (same as np.ravel())

### **intersect(x, y, local)**

returns the row and column of the grid that the x, y point is in

## **Notes**

## **Examples**

property angrot

property angrot\_radians

attrs\_from\_namfile\_header(*namefile*)

property botm

**cross\_section\_adjust\_indicies**(*k, cbcnt*)

Method to get adjusted indicies by layer and confining bed for PlotCrossSection plotting

**Parameters**

- **k** (*int*) – zero based layer number
- **cbcnt** (*int*) – confining bed counter

**Returns**

- **tuple** ((*int, int, int*) (*adjusted layer, nodeskip layer, node*)
- *adjustment value based on number of confining beds and the layer*)

**cross\_section\_lay\_ncpl\_ncb**(*ncb*)

Get PlotCrossSection compatible layers, ncpl, and ncb variables

**Parameters** **ncb** (*int*) – number of confining beds

**Returns** **tuple**

**Return type** (*int, int, int*) layers, ncpl, ncb

**cross\_section\_nodeskip**(*nlay, xypts*)

Get a nodeskip list for PlotCrossSection. This is a correction for UnstructuredGridPlotting

**Parameters**

- **nlay** (*int*) – nlay is nlay + ncb
- **xypts** (*dict*) – dictionary of node number and xyvertices of a cross-section

**Returns** **list**

**Return type** n-dimensional list of nodes to not plot for each layer

**cross\_section\_set\_contour\_arrays**(*plotarray, xcenters, head, elev, projpts*)

Method to set countour array centers for rare instances where matplotlib contouring is preferred over trimesh plotting

**Parameters**

- **plotarray** (*np.ndarray*) – array of data for contouring
- **xcenters** (*np.ndarray*) – xcenters array
- **zcenters** (*np.ndarray*) – zcenters array
- **head** (*np.ndarray*) – head array to adjust cell centers location
- **elev** (*np.ndarray*) – cell elevation array
- **projpts** (*dict*) – dictionary of projected cross sectional vertices

**Returns**

- **tuple** ((*np.ndarray, np.ndarray, np.ndarray, bool*)
- *plotarray, xcenter array, ycenter array, and a boolean flag*
- *for contouring*

**property** **cross\_section\_vertices**

**property** **epsg**

**property** **extent**

**classmethod** **from\_binary\_grid\_file**(*file\_path, verbose=False*)

**get\_coords**(*x*, *y*)

Given *x* and *y* array-like values, apply rotation, scale and offset, to convert them from model coordinates to real-world coordinates.

**get\_local\_coords**(*x*, *y*)

Given *x* and *y* array-like values, apply rotation, scale and offset, to convert them from real-world coordinates to model coordinates.

**get\_number\_plottable\_layers**(*a*)

**get\_plottable\_layer\_array**(*plotarray*, *layer*)

**get\_plottable\_layer\_shape**(*layer=None*)

Determine the shape that is required in order to plot a 2d array for this grid. For a regular MODFLOW grid, this is (*nrow*, *ncol*). For a vertex grid, this is (*ncpl*,) and for an unstructured grid this is (*ncpl*[*layer*],).

**Parameters** *layer* (*int*) – Has no effect unless grid changes by layer

**Returns** *shape* – required shape of array to plot for a layer

**Return type** tuple

**get\_xcellcenters\_for\_layer**(*layer*)

**get\_xvertices\_for\_layer**(*layer*)

**get\_ycellcenters\_for\_layer**(*layer*)

**get\_yvertices\_for\_layer**(*layer*)

**property** *grid\_lines*

**property** *grid\_type*

**property** *idomain*

**intersect**(*x*, *y*, *local=False*, *forgive=False*)

**property** *is\_complete*

**property** *is\_valid*

**property** *iverts*

**property** *laycbd*

**property** *lenuni*

**load\_coord\_info**(*namefile=None*, *reffile='usgs.model.reference'*)

Attempts to load spatial reference information from the following files (in order): 1) *usgs.model.reference*  
2) NAM file (header comment) 3) defaults

**property** *map\_polygons*

**property** *ncpl*

**property** *nnodes*

**property** *nvert*

**property** *prj*

**property** *proj4*

**read\_usgs\_model\_reference\_file**(*reffile='usgs.model.reference'*)

read spatial reference info from the *usgs.model.reference* file <https://water.usgs.gov/ogw/policy/gw-model/modelers-setup.html>

**remove\_confining\_beds**(*array*)

Method to remove confining bed layers from an array

**Parameters** **array** (*np.ndarray*) – array to remove quasi3d confining bed data from. Shape of axis 0 should be (self.lay + ncb) to remove beds

**Return type** *np.ndarray*

**saturated\_thick**(*array, mask=None*)

Get the saturated thickness for a structured, vertex, or unstructured grid. If the optional array is passed then thickness is returned relative to array values (saturated thickness). Returned values ranges from zero to cell thickness if optional array is passed.

**Parameters**

- **array** (*ndarray*) – array of elevations that will be used to adjust the cell thickness
- **mask** (*float, list, tuple, ndarray*) – array values to replace with a nan value.

**Returns** **thick**

**Return type** calculated saturated thickness

**set\_coord\_info**(*xoff=None, yoff=None, angrot=None, epsg=None, proj4=None, merge\_coord\_info=True*)

**property** **shape**

**property** **thick**

Get the cell thickness for a structured, vertex, or unstructured grid.

**Returns** **thick**

**Return type** calculated thickness

**property** **top**

**property** **top\_botm**

**property** **units**

**property** **verts**

**write\_shapefile**(*filename='grid.shp', epsg=None, prj=None*)

Write a shapefile of the grid with just the row and column attributes.

**property** **xcellcenters**

**property** **xoffset**

**property** **xvertices**

**property** **xyzcellcenters**

**property** **xyzextent**

**property** **xyzvertices**

**property** **ycellcenters**

**property** **yoffset**

**property** **yvertices**

**property** **zcellcenters**

**property** **zvertices**

**flopY.discretization.modeltime module**

**class** **ModelTime**(*period\_data=None, time\_units='days', start\_datetime=None, steady\_state=None*)

Bases: object

Class for MODFLOW simulation time

**Parameters**

- **stress\_periods** (*pandas dataframe*) – headings are: perlen, nstp, tsmult
- **temporal\_reference** ([TemporalReference](#)) – contains start time and time units information

property **nper**

property **nstp**

property **perlen**

property **start\_datetime**

property **steady\_state**

property **time\_units**

property **totim**

property **tslen**

property **tsmult**

**flopY.discretization.structuredgrid module**

**class** **StructuredGrid**(*delc=None, delr=None, top=None, botm=None, idomain=None, lenuni=None, epsg=None, proj4=None, prj=None, xoff=0.0, yoff=0.0, angrot=0.0, nlay=None, nrow=None, ncol=None, laycbd=None*)

Bases: [flopY.discretization.grid.Grid](#)

class for a structured model grid

**Parameters**

- **delc** – delc array
- **delr** – delr array
- **Properties** –
- ----- –
- **nlay** – returns the number of model layers
- **nrow** – returns the number of model rows
- **ncol** – returns the number of model columns
- **delc** – returns the delc array
- **delr** – returns the delr array
- **xyedges** – returns x-location points for the edges of the model grid and y-location points for the edges of the model grid

**get\_cell\_vertices**(*i, j*)

returns vertices for a single cell at row, column i, j.

**array\_at\_faces**(*a*, *direction*, *withnan*=*True*)

Computes values at the center of cell faces using linear interpolation.

**Parameters**

- **a** (*ndarray*) – Values at cell centers, shape (nlay, row, ncol).
- **direction** (*str*, possible values are 'x', 'y' and 'z') – Direction in which values will be interpolated at cell faces.
- **withnan** (*bool*) – If True (default), the result value will be set to NaN where the cell face sits between inactive cells. If False, not.

**Returns** **afaces** – Array values interpolated at cell vertices, shape as input extended by 1 along the specified direction.

**Return type** ndarray

**array\_at\_verts**(*a*)

Interpolate array values at cell vertices.

**Parameters** **a** (*ndarray*) – Array values. Allowed shapes are: (nlay, nrow, ncol), (nlay, nrow, ncol+1), (nlay, nrow+1, ncol) and (nlay+1, nrow, ncol). \* When the shape is (nlay, nrow, ncol), input values are considered at cell centers, and output values are computed by trilinear interpolation. \* When the shape is extended in one direction, input values are considered at the center of cell faces in this direction, and output values are computed by bilinear interpolation in planes defined by these cell faces.

**Returns** **averts** – Array values interpolated at cell vertices, shape (nlay+1, nrow+1, ncol+1).

**Return type** ndarray

**Notes**

- Output values are smooth (continuous) even if top elevations or

bottom elevations are not constant across layers (i.e., in this case, vertices of neighboring cells are implicitly merged). \* NaN values are assigned in accordance with inactive cells defined by idomain.

**array\_at\_verts\_basic**(*a*)

Computes values at cell vertices using neighbor averaging.

**Parameters** **a** (*ndarray*) – Array values at cell centers.

**Returns** **averts** – Array values at cell vertices, shape (a.shape[0]+1, a.shape[1]+1, a.shape[2]+1). NaN values are assigned in accordance with inactive cells defined by idomain.

**Return type** ndarray

**property cross\_section\_vertices**

Get a set of xvertices and yvertices ordered by node for plotting cross sections

**Returns** **xverts**, **yverts**

**Return type** (np.ndarray, np.ndarray)

**property delc**

**property delr**

**property delz**

**property extent**



**classmethod** `from_binary_grid_file(file_path, verbose=False)`

Instantiate a StructuredGrid model grid from a MODFLOW 6 binary grid (\*.grb) file.

**Parameters**

- **file\_path** (*str*) – file path for the MODFLOW 6 binary grid file
- **verbose** (*bool*) – Write information to standard output. Default is False.

**Returns** `return`

**Return type** *StructuredGrid*

**classmethod** `from_gridspec(gridspec_file, lenuni=0)`

**get\_cell\_vertices**(\*args, \*\*kwargs)

**Method to get a set of cell vertices for a single cell** used in the Shapefile export utilities and plotting code

**Parameters**

- **node** – (int) node number
- **i** – (int) cell row number
- **j** – (int) cell column number

Returns ——— list of x,y cell vertices

**get\_lrc**(nodes)

Get layer, row, column from a list of zero based MODFLOW node numbers.

**Returns** **v** – and column (j) for each node in the input list

**Return type** list of tuples containing the layer (k), row (i),

**get\_node**(lrc\_list)

Get node number from a list of zero based MODFLOW layer, row, column tuples.

**Returns** **v** – and column (j) tuple in the input list

**Return type** list of MODFLOW nodes for each layer (k), row (i),

**get\_number\_plottable\_layers**(a)

Calculate and return the number of 2d plottable arrays that can be obtained from the array passed (a)

**Parameters** **a** (*ndarray*) – array to check for plottable layers

**Returns** **nplottable** – number of plottable layers

**Return type** `int`

**get\_plottable\_layer\_array**(a, layer)

**property** `grid_lines`

Get the grid lines as a list

**intersect**(x, y, z=None, local=False, forgive=False)

Get the row and column of a point with coordinates x and y

When the point is on the edge of two cells, the cell with the lowest row or column is returned.

**Parameters**

- **x** (*float*) – The x-coordinate of the requested point

- **y** (*float*) – The y-coordinate of the requested point
- **z** (*float*) – Optional z-coordinate of the requested point (will return layer, row, column) if supplied
- **local** (*bool (optional)*) – If True, x and y are in local coordinates (defaults to False)
- **forgive** (*bool (optional)*) – Forgive x,y arguments that fall outside the model grid and return NaNs instead (defaults to False - will throw exception)

#### Returns

- **row** (*int*) – The row number
- **col** (*int*) – The column number

**property is\_complete**

**property is\_rectilinear**

Test whether the grid is rectilinear (it is always so in the x and y directions, but not necessarily in the z direction).

**property is\_regular**

Test if the grid spacing is regular and equal in x, y and z directions.

**property is\_regular\_x**

Test whether the grid spacing is regular in the x direction.

**property is\_regular\_xy**

Test if the grid spacing is regular and equal in x and y directions.

**property is\_regular\_xz**

Test if the grid spacing is regular and equal in x and z directions.

**property is\_regular\_y**

Test whether the grid spacing is regular in the y direction.

**property is\_regular\_yz**

Test if the grid spacing is regular and equal in y and z directions.

**property is\_regular\_z**

Test if the grid spacing is regular in z direction.

**property is\_valid**

**property iverts**

**property map\_polygons**

Get a list of matplotlib Polygon patches for plotting

**Return type** list of Polygon objects

**property ncol**

**property ncpl**

**property nlay**

**property nnodes**

**property nrow**

**property nvert**

**plot(\*\*kwargs)**

Plot the grid lines.

**Parameters** *kwargs* (*ax*, *colors*. The remaining *kwargs* are passed into the) – the LineCollection constructor.

**Returns** *lc*

**Return type** matplotlib.collections.LineCollection

**property** *shape*

**property** *top\_botm*

**property** *top\_botm\_withnan*

Same as *top\_botm* array but with NaN where *idomain*==0 both above and below a cell.

**property** *verts*

**property** *xycenters*

Return a list of two numpy one-dimensional float arrays for center x and y coordinates in model space - not offset or rotated.

**property** *xyedges*

one with the cell edge x coordinate (size = *ncol*+1) and the other with the cell edge y coordinate (size = *nrow*+1) in model space - not offset or rotated.

**Type** Return a list of two 1D numpy arrays

**property** *xyzcellcenters*

two two-dimensional arrays for center x and y coordinates, and one three-dimensional array for center z coordinates. Coordinates are given in real-world coordinates.

**Type** Return a list of three numpy float arrays

**property** *xyzvertices*

Method to get all grid vertices in a layer

**Returns** [] 2D array

**property** *zedges*

Return zedges for (column, row)==(0, 0).

**property** *zverts\_smooth*

Get a unique z of cell vertices using bilinear interpolation of top and bottom elevation layers.

**Returns** *zverts* – z of cell vertices. NaN values are assigned in accordance with inactive cells defined by *idomain*.

**Return type** ndarray, shape (*nlay*+1, *nrow*+1, *ncol*+1)

**array\_at\_faces\_1d**(*a*, *delta*)

Interpolate array at cell faces of a 1d grid using linear interpolation.

**Parameters**

- *a* (1d ndarray) – Values at cell centers.
- *delta* (1d ndarray) – Grid steps.

**Returns** *afaces* – Array values interpolated at cell faces, shape as input extended by 1.

**Return type** 1d ndarray

**array\_at\_verts\_basic2d**(*a*)

Computes values at cell vertices on 2d array using neighbor averaging.

**Parameters** *a* (ndarray) – Array values at cell centers, could be a slice in any orientation.

**Returns** *averts* – Array values at cell vertices, shape (*a.shape*[0]+1, *a.shape*[1]+1).

**Return type** ndarray

### flopY.discretization.unstructuredgrid module

```
class UnstructuredGrid(vertices=None, iverts=None, xcenters=None, ycenters=None, top=None, botm=None,
                        idomain=None, lenuni=None, ncpl=None, epsg=None, proj4=None, prj=None,
                        xoff=0.0, yoff=0.0, angrot=0.0)
```

Bases: *flopY.discretization.grid.Grid*

Class for an unstructured model grid

#### Parameters

- **vertices** (*list*) – list of vertices that make up the grid. Each vertex consists of three entries [iv, xv, yv] which are the vertex number, which should be zero-based, and the x and y vertex coordinates.
- **iverts** (*list*) – list of vertex numbers that comprise each cell. This list must be of size nodes, if the grid\_varies\_by\_nodes argument is true, or it must be of size ncpl[0] if the same 2d spatial grid is used for each layer.
- **xcenters** (*list or ndarray*) – list of x center coordinates for all cells in the grid if the grid varies by layer or for all cells in a layer if the same grid is used for all layers
- **ycenters** (*list or ndarray*) – list of y center coordinates for all cells in the grid if the grid varies by layer or for all cells in a layer if the same grid is used for all layers
- **ncpl** (*ndarray*) – one dimensional array of size nlay with the number of cells in each layer. This can also be passed in as a tuple or list as long as it can be set using ncpl = np.array(ncpl, dtype=int). The sum of ncpl must be equal to the number of cells in the grid. ncpl is optional and if it is not passed in, then it is set using ncpl = np.array([len(iverts)], dtype=int), which means that all cells in the grid are contained in a single plottable layer. If the model grid defined in verts and iverts applies for all model layers, then the length of iverts can be equal to ncpl[0] and there is no need to repeat all of the vertex information for cells in layers beneath the top layer.
- **top** (*list or ndarray*) – top elevations for all cells in the grid.
- **botm** (*list or ndarray*) – bottom elevations for all cells in the grid.
- **Properties** –
- -----
- **vertices** – returns list of vertices that make up the grid
- **cell2d** – returns list of cells and their vertices

**get\_cell\_vertices**(*cellid*)

returns vertices for a single cell at cellid.

## Notes

This class handles spatial representation of unstructured grids. It is based on the concept of being able to support multiple model layers that may have a different number of cells in each layer. The array `ncpl` is of size `nlay` and its sum must equal `nodes`. If the length of `iverts` is equal to `ncpl[0]` and the number of cells per layer is the same for each layer, then it is assumed that the grid does not vary by layer. In this case, the `xcenters` and `ycenters` arrays must also be of size `ncpl[0]`. This makes it possible to efficiently store spatial grid information for multiple layers.

If the spatial grid is different for each model layer, then the `grid_varies_by_layer` flag will automatically be set to `false`, and `iverts` must be of size `nodes`. The arrays for `xcenters` and `ycenters` must also be of size `nodes`.

### `cross_section_adjust_indicies(k, cbcnt)`

Method to get adjusted indicies by layer and confining bed for `PlotCrossSection` plotting

#### Parameters

- `k (int)` – zero based model layer
- `cbcnt (int)` – confining bed counter

#### Returns

- `tuple ((int, int, int) (adjusted layer, nodeskip layer, node)`
- *adjustment value based on number of confining beds and the layer)*

### `cross_section_lay_ncpl_ncb(ncb)`

Get `PlotCrossSection` compatible layers, `ncpl`, and `ncb` variables

**Parameters** `ncb (int)` – number of confining beds

**Returns** `tuple`

**Return type** `(int, int, int)` layers, `ncpl`, `ncb`

### `cross_section_nodeskip(nlay, xypts)`

Get a nodeskip list for `PlotCrossSection`. This is a correction for `UnstructuredGridPlotting`

#### Parameters

- `nlay (int)` – `nlay` is `nlay + ncb`
- `xypts (dict)` – dictionary of node number and xyvertices of a cross-section

#### Returns

**Return type** `n-dimensional` list of nodes to not plot for each layer

### `cross_section_set_contour_arrays(plotarray, xcenters, head, elev, projpts)`

Method to set contour array centers for rare instances where `matplotlib` contouring is preferred over `trimesh` plotting

#### Parameters

- `plotarray (np.ndarray)` – array of data for contouring
- `xcenters (np.ndarray)` – `xcenters` array
- `head (np.ndarray)` – `head` array to adjust cell centers location
- `elev (np.ndarray)` – cell elevation array
- `projpts (dict)` – dictionary of projected cross sectional vertices

#### Returns

- **tuple** ((*np.ndarray*, *np.ndarray*, *np.ndarray*, *bool*))
- *plotarray*, *xcenter* array, *ycenter* array, and a *boolean flag*
- *for contouring*

**property cross\_section\_vertices**

Method to get vertices for cross-sectional plotting

**Return type** *xvertices*, *yvertices*

**property extent****classmethod from\_argus\_export**(*fname*, *nlay=1*)

Create a new UnstructuredGrid from an Argus One Trimesh file

**Parameters**

- **fname** (*string*) – File name
- **nlay** (*int*) – Number of layers to create

**Return type** *flopY.discretization.unstructuredgrid.UnstructuredGrid*

**classmethod from\_binary\_grid\_file**(*file\_path*, *verbose=False*)

Instantiate a UnstructuredGrid model grid from a MODFLOW 6 binary grid (\*.grb) file.

**Parameters**

- **file\_path** (*str*) – file path for the MODFLOW 6 binary grid file
- **verbose** (*bool*) – Write information to standard output. Default is False.

**Returns** *return*

**Return type** *UnstructuredGrid*

**get\_cell\_vertices**(*cellid*)

Method to get a set of cell vertices for a single cell used in the Shapefile export utilities

**Parameters** *cellid* – (int) cellid number

**Returns** —— list of x,y cell vertices

**get\_layer\_node\_range**(*layer*)**get\_number\_plottable\_layers**(*a*)

Calculate and return the number of 2d plottable arrays that can be obtained from the array passed (*a*)

**Parameters** *a* (*ndarray*) – array to check for plottable layers

**Returns** *nplottable* – number of plottable layers

**Return type** *int*

**get\_plottable\_layer\_array**(*a*, *layer*)**get\_plottable\_layer\_shape**(*layer=None*)

Determine the shape that is required in order to plot in 2d for this grid.

**Parameters** *layer* (*int*) – Has no effect unless grid changes by layer

**Returns** *shape* – required shape of array to plot for a layer

**Return type** *tuple*

**get\_xcellcenters\_for\_layer**(*layer*)

**get\_xvertices\_for\_layer**(*layer*)

**get\_ycellcenters\_for\_layer**(*layer*)

**get\_yvertices\_for\_layer**(*layer*)

**property grid\_lines**

Creates a series of grid line vertices for drawing a model grid line collection. If the grid varies by layer, then return a dictionary with keys equal to layers and values equal to grid lines. Otherwise, just return the grid lines

**Returns** grid lines or dictionary of lines by layer

**Return type** dict

**property grid\_varies\_by\_layer**

**property ia**

**intersect**(*x, y, z=None, local=False, forgive=False*)

Get the CELL2D number of a point with coordinates x and y

When the point is on the edge of two cells, the cell with the lowest CELL2D number is returned.

**Parameters**

- **x** (*float*) – The x-coordinate of the requested point
- **y** (*float*) – The y-coordinate of the requested point
- **z** (*float, None*) – optional, z-coordiante of the requested point
- **local** (*bool (optional)*) – If True, x and y are in local coordinates (defaults to False)
- **forgive** (*bool (optional)*) – Forgive x,y arguments that fall outside the model grid and return NaNs instead (defaults to False - will throw exception)

**Returns** **icell2d** – The CELL2D number

**Return type** int

**property is\_complete**

**property is\_valid**

**property iverts**

**property ja**

**property map\_polygons**

Property to get Matplotlib polygon objects for the modelgrid

**Return type** list or dict of matplotlib.collections.Polygon

**property ncpl**

**static ncpl\_from\_ihc**(*ihc, iac*)

Use the ihc and iac arrays to calculate the number of cells per layer array (ncpl) assuming that the plottable layer number is stored in the diagonal position of the ihc array.

**Parameters**

- **ihc** (*ndarray*) – horizontal indicator array. If the plottable layer number is stored in the diagonal position, then this will be used to create the returned ncpl array. plottable layer numbers must increase monotonically and be consecutive with node number

- **iac** (*ndarray*) – array of size nodes that has the number of connections for a cell, plus one for the cell itself

**Returns** **ncpl** – number of cells per plottable layer

**Return type** *ndarray*

**property** **nlay**

**property** **nnodes**

**property** **nvert**

**plot**(*\*\*kwargs*)

Plot the grid lines.

**Parameters** **kwargs** (*ax, colors*. The remaining *kwargs* are passed into the) – the LineCollection constructor.

**Returns** **lc**

**Return type** *matplotlib.collections.LineCollection*

**set\_ncpl**(*ncpl*)

**property** **shape**

**property** **top\_botm**

**property** **verts**

**property** **xyzcellcenters**

Method to get cell centers and set to grid

**property** **xyzvertices**

Method to get model grid vertices

**Returns** list of dimension *ncpl* by *nvertices*

## **flop.discretization.vertexgrid module**

**class** **VertexGrid**(*vertices=None, cell2d=None, top=None, botm=None, idomain=None, lenuni=None, epsg=None, proj4=None, prj=None, xoff=0.0, yoff=0.0, angrot=0.0, nlay=None, ncpl=None, cell1d=None*)

Bases: *flop.discretization.grid.Grid*

class for a vertex model grid

**Parameters**

- **vertices** – list of vertices that make up the grid
- **cell2d** – list of cells and their vertices
- **Properties** –
- ----- –
- **vertices** – returns list of vertices that make up the grid
- **cell2d** – returns list of cells and their vertices

**get\_cell\_vertices**(*cellid*)

returns vertices for a single cell at *cellid*.

**property** **cell1d**



**property cell2d**

**property extent**

**classmethod from\_binary\_grid\_file**(*file\_path*, *verbose=False*)

Instantiate a VertexGrid model grid from a MODFLOW 6 binary grid (\*.grb) file.

**Parameters**

- **file\_path** (*str*) – file path for the MODFLOW 6 binary grid file
- **verbose** (*bool*) – Write information to standard output. Default is False.

**Returns** **return**

**Return type** *VertexGrid*

**get\_cell\_vertices**(*cellid*)

**Method to get a set of cell vertices for a single cell** used in the Shapefile export utilities

**Parameters** **cellid** – (int) cellid number

**Returns** ——— list of x,y cell vertices

**get\_number\_plottable\_layers**(*a*)

Calculate and return the number of 2d plottable arrays that can be obtained from the array passed (*a*)

**Parameters** **a** (*ndarray*) – array to check for plottable layers

**Returns** **nplottable** – number of plottable layers

**Return type** **int**

**get\_plottable\_layer\_array**(*a*, *layer*)

**get\_xcellcenters\_for\_layer**(*layer*)

**get\_xvertices\_for\_layer**(*layer*)

**get\_ycellcenters\_for\_layer**(*layer*)

**get\_yvertices\_for\_layer**(*layer*)

**property grid\_lines**

Creates a series of grid line vertices for drawing a model grid line collection

**Returns** grid line vertices

**Return type** **list**

**intersect**(*x*, *y*, *z=None*, *local=False*, *forgive=False*)

Get the CELL2D number of a point with coordinates *x* and *y*

When the point is on the edge of two cells, the cell with the lowest CELL2D number is returned.

**Parameters**

- **x** (*float*) – The x-coordinate of the requested point
- **y** (*float*) – The y-coordinate of the requested point
- **z** (*float*, *None*) – optional, z-coordiante of the requested point will return (lay, icell2d)
- **local** (*bool* (*optional*)) – If True, *x* and *y* are in local coordinates (defaults to False)

- **forgive** (*bool (optional)*) – Forgive x,y arguments that fall outside the model grid and return NaNs instead (defaults to False - will throw exception)

**Returns** **icell2d** – The CELL2D number

**Return type** **int**

**property** **is\_complete**

**property** **is\_valid**

**property** **iverts**

**property** **map\_polygons**

Get a list of matplotlib Polygon patches for plotting

**Return type** list of Polygon objects

**property** **ncpl**

**property** **nlay**

**property** **nnodes**

**property** **nvert**

**plot**(*\*\*kwargs*)

Plot the grid lines.

**Parameters** **kwargs** (*ax, colors. The remaining kwargs are passed into the*)  
– the LineCollection constructor.

**Returns** **lc**

**Return type** matplotlib.collections.LineCollection

**property** **shape**

**property** **top\_botm**

**property** **verts**

**property** **xyzcellcenters**

Method to get cell centers and set to grid

**property** **xyzvertices**

Method to get all grid vertices in a layer, arranged per cell

**Returns** list of size sum(nvertices per cell)

## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`



## PYTHON MODULE INDEX

### f

- `flopy.discretization.grid`, 701
- `flopy.discretization.modeltime`, 707
- `flopy.discretization.structuredgrid`, 707
- `flopy.discretization.unstructuredgrid`, 712
- `flopy.discretization.vertexgrid`, 716
- `flopy.export.longnames`, 681
- `flopy.export.metadata`, 681
- `flopy.export.netcdf`, 682
- `flopy.export.shapefile_utils`, 685
- `flopy.export.unitsformat`, 688
- `flopy.export.utils`, 688
- `flopy.export.vtk`, 693
- `flopy.mbase`, 374
- `flopy.mf6.data.mfdataarray`, 355
- `flopy.mf6.data.mfdatalist`, 361
- `flopy.mf6.data.mfdatascalar`, 368
- `flopy.mf6.mbase`, 109
- `flopy.mf6.mfmodel`, 116
- `flopy.mf6.mfpackage`, 122
- `flopy.mf6.modflow.mfgnc`, 137
- `flopy.mf6.modflow.mfgwf`, 153
- `flopy.mf6.modflow.mfgwfapi`, 156
- `flopy.mf6.modflow.mfgwfbuy`, 158
- `flopy.mf6.modflow.mfgwfchd`, 160
- `flopy.mf6.modflow.mfgwfcsb`, 163
- `flopy.mf6.modflow.mfgwfdis`, 170
- `flopy.mf6.modflow.mfgwfdisu`, 172
- `flopy.mf6.modflow.mfgwfdisv`, 177
- `flopy.mf6.modflow.mfgwfdrn`, 180
- `flopy.mf6.modflow.mfgwfevt`, 183
- `flopy.mf6.modflow.mfgwfevta`, 187
- `flopy.mf6.modflow.mfgwfgfb`, 190
- `flopy.mf6.modflow.mfgwfgnc`, 193
- `flopy.mf6.modflow.mfgwfgwf`, 195
- `flopy.mf6.modflow.mfgwfgwt`, 200
- `flopy.mf6.modflow.mfgwfhfb`, 200
- `flopy.mf6.modflow.mfgwfgic`, 202
- `flopy.mf6.modflow.mfgwflak`, 202
- `flopy.mf6.modflow.mfgwfmaw`, 212
- `flopy.mf6.modflow.mfgwfmvr`, 221
- `flopy.mf6.modflow.mfgwfnam`, 224
- `flopy.mf6.modflow.mfgwfnpf`, 225
- `flopy.mf6.modflow.mfgwfoc`, 231
- `flopy.mf6.modflow.mfgwfrch`, 234
- `flopy.mf6.modflow.mfgwfrcha`, 237
- `flopy.mf6.modflow.mfgwfriv`, 239
- `flopy.mf6.modflow.mfgwfsfr`, 243
- `flopy.mf6.modflow.mfgwfsto`, 252
- `flopy.mf6.modflow.mfgwfufz`, 254
- `flopy.mf6.modflow.mfgwfwel`, 261
- `flopy.mf6.modflow.mfgwt`, 155
- `flopy.mf6.modflow.mfgwtadv`, 265
- `flopy.mf6.modflow.mfgwtapi`, 265
- `flopy.mf6.modflow.mfgwtcnc`, 267
- `flopy.mf6.modflow.mfgwtdis`, 270
- `flopy.mf6.modflow.mfgwtdisu`, 272
- `flopy.mf6.modflow.mfgwtdisv`, 277
- `flopy.mf6.modflow.mfgwt dsp`, 280
- `flopy.mf6.modflow.mfgwtfmi`, 282
- `flopy.mf6.modflow.mfgwtgwt`, 283
- `flopy.mf6.modflow.mfgwtic`, 287
- `flopy.mf6.modflow.mfgwtist`, 287
- `flopy.mf6.modflow.mfgwtlkt`, 291
- `flopy.mf6.modflow.mfgwtmst`, 296
- `flopy.mf6.modflow.mfgwtmvt`, 298
- `flopy.mf6.modflow.mfgwtmw`, 299
- `flopy.mf6.modflow.mfgwt nam`, 304
- `flopy.mf6.modflow.mfgwtoc`, 305
- `flopy.mf6.modflow.mfgwtsft`, 309
- `flopy.mf6.modflow.mfgwtsrc`, 314
- `flopy.mf6.modflow.mfgwtssm`, 316
- `flopy.mf6.modflow.mfgwtuzt`, 318
- `flopy.mf6.modflow.mfims`, 139
- `flopy.mf6.modflow.mfmvr`, 147
- `flopy.mf6.modflow.mfnam`, 150
- `flopy.mf6.modflow.mfsimulation`, 128
- `flopy.mf6.modflow.mftdis`, 152
- `flopy.mf6.modflow.mfutlats`, 324
- `flopy.mf6.modflow.mfutllaktab`, 326
- `flopy.mf6.modflow.mfutlobs`, 327
- `flopy.mf6.modflow.mfutlsfrtab`, 329
- `flopy.mf6.modflow.mfutlspc`, 331
- `flopy.mf6.modflow.mfutlspca`, 333

`flop.py.mf6.modflow.mfutltas`, 334  
`flop.py.mf6.modflow.mfutlts`, 336  
`flop.py.mf6.modflow.mfutltvk`, 338  
`flop.py.mf6.modflow.mfutltvs`, 341  
`flop.py.mf6.utils.binaryfile_utils`, 343  
`flop.py.mf6.utils.binarygrid_util`, 344  
`flop.py.mf6.utils.createpackages`, 372  
`flop.py.mf6.utils.generate_classes`, 373  
`flop.py.mf6.utils.lakpak_utils`, 354  
`flop.py.mf6.utils.mfobservation`, 347  
`flop.py.mf6.utils.output_util`, 348  
`flop.py.mf6.utils.postprocessing`, 349  
`flop.py.mf6.utils.reference`, 350  
`flop.py.modflow.mf`, 383  
`flop.py.modflow.mfaddoutsidefile`, 385  
`flop.py.modflow.mfag`, 386  
`flop.py.modflow.mfbas`, 387  
`flop.py.modflow.mfbcf`, 389  
`flop.py.modflow.mfbct`, 391  
`flop.py.modflow.mfchd`, 392  
`flop.py.modflow.mfde4`, 394  
`flop.py.modflow.mfdis`, 396  
`flop.py.modflow.mfdrn`, 401  
`flop.py.modflow.mfdrt`, 403  
`flop.py.modflow.mfevt`, 405  
`flop.py.modflow.mffhb`, 407  
`flop.py.modflow.mfflwob`, 409  
`flop.py.modflow.mfgage`, 411  
`flop.py.modflow.mfghb`, 413  
`flop.py.modflow.mfgmg`, 415  
`flop.py.modflow.mfhfb`, 418  
`flop.py.modflow.mfhob`, 420  
`flop.py.modflow.mfhyd`, 423  
`flop.py.modflow.mflak`, 424  
`flop.py.modflow.mflmt`, 429  
`flop.py.modflow.mflpf`, 430  
`flop.py.modflow.mfmlt`, 433  
`flop.py.modflow.mfmnw1`, 435  
`flop.py.modflow.mfmnw2`, 436  
`flop.py.modflow.mfmnwi`, 446  
`flop.py.modflow.mfnwt`, 448  
`flop.py.modflow.mfoc`, 451  
`flop.py.modflow.mfpar`, 456  
`flop.py.modflow.mfparbc`, 458  
`flop.py.modflow.mfpbc`, 459  
`flop.py.modflow.mfpbcg`, 460  
`flop.py.modflow.mfpbcgn`, 461  
`flop.py.modflow.mfpks`, 464  
`flop.py.modflow.mfpval`, 466  
`flop.py.modflow.mfrch`, 467  
`flop.py.modflow.mfriv`, 470  
`flop.py.modflow.mfsfr2`, 473  
`flop.py.modflow.mfsip`, 481  
`flop.py.modflow.mfsor`, 482  
`flop.py.modflow.mfstr`, 484  
`flop.py.modflow.mfsub`, 488  
`flop.py.modflow.mfswi2`, 492  
`flop.py.modflow.mfswr1`, 495  
`flop.py.modflow.mfswt`, 496  
`flop.py.modflow.mfupw`, 500  
`flop.py.modflow.mfuzf1`, 502  
`flop.py.modflow.mfwel`, 508  
`flop.py.modflow.mfzon`, 510  
`flop.py.modpath.mp6`, 560  
`flop.py.modpath.mp6bas`, 562  
`flop.py.modpath.mp6sim`, 563  
`flop.py.modpath.mp7`, 549  
`flop.py.modpath.mp7bas`, 551  
`flop.py.modpath.mp7particledata`, 551  
`flop.py.modpath.mp7particlegroup`, 555  
`flop.py.modpath.mp7sim`, 557  
`flop.py.mt3d.mt`, 511  
`flop.py.mt3d.mtadv`, 514  
`flop.py.mt3d.mtbtn`, 517  
`flop.py.mt3d.mtcts`, 520  
`flop.py.mt3d.mtdsp`, 522  
`flop.py.mt3d.mtgcg`, 524  
`flop.py.mt3d.mtlkt`, 526  
`flop.py.mt3d.mtphc`, 528  
`flop.py.mt3d.mtrct`, 528  
`flop.py.mt3d.mtsft`, 532  
`flop.py.mt3d.mtssm`, 536  
`flop.py.mt3d.mttob`, 538  
`flop.py.mt3d.mtuzt`, 539  
`flop.py.pakbase`, 381  
`flop.py.pest.params`, 699  
`flop.py.pest.templatewriter`, 700  
`flop.py.pest.tplarray`, 700  
`flop.py.plot.crosssection`, 663  
`flop.py.plot.map`, 668  
`flop.py.plot.plotutil`, 673  
`flop.py.plot.styles`, 678  
`flop.py.seawat.swt`, 541  
`flop.py.seawat.swtvdf`, 543  
`flop.py.seawat.swtvsc`, 546  
`flop.py.utils.binaryfile`, 565  
`flop.py.utils.check`, 572  
`flop.py.utils.cvfdutil`, 574  
`flop.py.utils.datafile`, 576  
`flop.py.utils.datautil`, 579  
`flop.py.utils.flop_io`, 582  
`flop.py.utils.formattedfile`, 584  
`flop.py.utils.geometry`, 586  
`flop.py.utils.geospatial_utils`, 589  
`flop.py.utils.gridgen`, 590  
`flop.py.utils.gridintersect`, 597  
`flop.py.utils.lgrutil`, 601  
`flop.py.utils.mflistfile`, 602

`flopY.utils.mfreadnam`, 606  
`flopY.utils.modpathfile`, 608  
`flopY.utils.mtlistfile`, 614  
`flopY.utils.observationfile`, 615  
`flopY.utils.optionblock`, 618  
`flopY.utils.parse_version`, 620  
`flopY.utils.postprocessing`, 621  
`flopY.utils.rasters`, 623  
`flopY.utils.reccarray_utils`, 626  
`flopY.utils.reference`, 627  
`flopY.utils.sfroutputfile`, 627  
`flopY.utils.swroutputfile`, 629  
`flopY.utils.triangle`, 633  
`flopY.utils.util_array`, 636  
`flopY.utils.util_list`, 648  
`flopY.utils.utils_def`, 652  
`flopY.utils.utl_import`, 653  
`flopY.utils.voronoi`, 654  
`flopY.utils.zonbud`, 656





## A

- acdd (*class in flopy.export.metadata*), 681
- add() (*EpsgReference method*), 686
- add\_active\_domain() (*Gridgen method*), 591
- add\_annotation() (*styles class method*), 678
- add\_array() (*Vtk method*), 694
- add\_cell\_budget() (*Vtk method*), 694
- add\_data\_item() (*MFBBlockHeader method*), 124
- add\_dataset() (*MFBBlock method*), 123
- add\_existing\_package() (*BaseModel method*), 374
- add\_ext\_file() (*MFFileMgmt method*), 110
- add\_external() (*BaseModel method*), 374
- add\_file() (*FileData method*), 379
- add\_global\_attributes() (*NetCdf method*), 683
- add\_heads() (*Vtk method*), 694
- add\_hole() (*Triangle method*), 633
- add\_model() (*Vtk method*), 694
- add\_one() (*MFSScalar method*), 368
- add\_one() (*MFSScalarTransient method*), 370
- add\_output() (*BaseModel method*), 374
- add\_output\_file() (*BaseModel method*), 375
- add\_package() (*BaseModel method*), 375
- add\_package() (*Vtk method*), 694
- add\_package() (*ZoneBudget6 method*), 659
- add\_parameter() (*Transient2dTpl method*), 700
- add\_parameter() (*Util3dTpl method*), 701
- add\_pathline\_points() (*Vtk method*), 694
- add\_polygon() (*Triangle method*), 633
- add\_pop\_key\_list() (*BaseModel method*), 375
- add\_record() (*MfList method*), 648
- add\_record() (*ModflowChd method*), 393
- add\_record() (*ModflowDrn method*), 402
- add\_record() (*ModflowDrt method*), 404
- add\_record() (*ModflowGhb method*), 414
- add\_record() (*ModflowRiv method*), 471
- add\_record() (*ModflowWel method*), 509
- add\_refinement\_features() (*Gridgen method*), 591
- add\_region() (*Triangle method*), 633
- add\_sciencebase\_metadata() (*NetCdf method*), 683
- add\_text() (*styles class method*), 678
- add\_timevalue() (*Pvd method*), 693
- add\_to\_dtype() (*Package static method*), 381
- add\_transient\_array() (*Vtk method*), 695
- add\_transient\_key() (*MFSScalarTransient method*), 370
- add\_transient\_key() (*MFTransientArray method*), 358
- add\_transient\_key() (*MFTransientList method*), 365
- add\_transient\_list() (*Vtk method*), 695
- add\_transient\_vector() (*Vtk method*), 695
- add\_var() (*in module flopy.mf6.utils.createpackages*), 372
- add\_vector() (*Vtk method*), 695
- advanced\_package\_bc\_helper() (*in module flopy.plot.plotutil*), 674
- afrcsv\_filerecord (*ModflowGwfwel attribute*), 263
- alh (*ModflowGwtdsp attribute*), 281
- all() (*Util2d method*), 642
- alv (*ModflowGwtdsp attribute*), 281
- angldegx (*ModflowGwfdisu attribute*), 175
- angldegx (*ModflowGwtdisu attribute*), 275
- angle1 (*ModflowGwfnpf attribute*), 229
- angle2 (*ModflowGwfnpf attribute*), 229
- angle3 (*ModflowGwfnpf attribute*), 229
- angrot (*Grid attribute*), 702
- angrot (*Grid property*), 703
- angrot (*MfGrdFile property*), 344
- angrot\_radians (*Grid attribute*), 702
- angrot\_radians (*Grid property*), 703
- append() (*MfList method*), 648
- append() (*NetCdf method*), 683
- append\_data() (*MFList method*), 361
- append\_list\_as\_record() (*MFList method*), 361
- append\_list\_as\_record() (*MFTransientList method*), 365
- append\_package() (*UtlatsPackages method*), 325, 326
- append\_package() (*UtlaktabPackages method*), 327
- append\_package() (*UtlsftrtabPackages method*), 330
- append\_package() (*UtlspcaPackages method*), 334
- append\_package() (*UtlspcPackages method*), 332
- append\_package() (*UtltsasPackages method*), 336
- append\_package() (*UtltsPackages method*), 338
- append\_package() (*UtltvkPackages method*), 340
- append\_package() (*Utltvspackages method*), 342

`append_passed()` (*check method*), 573  
`arctan2()` (*UnstructuredPlotUtilities static method*), 674  
`area` (*ModflowGwfdisu attribute*), 175  
`area` (*ModflowGwtdisu attribute*), 275  
`area_of_polygon()` (*in module flopy.utils.cvfutil*), 574  
`array` (*MfList property*), 648  
`array` (*Transient2d property*), 638  
`array` (*Transient3d property*), 641  
`array` (*Util2d attribute*), 642  
`array` (*Util2d property*), 642  
`array` (*Util3d attribute*), 646  
`array` (*Util3d property*), 646  
`array2d_export()` (*in module flopy.export.utils*), 688  
`array2string()` (*Util2d static method*), 642  
`array3d_export()` (*in module flopy.export.utils*), 689  
`array_at_faces()` (*StructuredGrid method*), 707  
`array_at_faces_1d()` (*in module flopy.discretization.structuredgrid*), 711  
`array_at_verts()` (*StructuredGrid method*), 708  
`array_at_verts_basic()` (*StructuredGrid method*), 708  
`array_at_verts_basic2d()` (*in module flopy.discretization.structuredgrid*), 711  
`array_comp()` (*PyListUtil method*), 581  
`array_free_format` (*ArrayFormat property*), 637  
`ArrayFormat` (*class in flopy.utils.util\_array*), 636  
`ArrayIndexIter` (*class in flopy.utils.datautil*), 579  
`assign_layers()` (*ModflowSfr2 method*), 476  
`ath1` (*ModflowGwtdsp attribute*), 281  
`ath2` (*ModflowGwtdsp attribute*), 281  
`ats_filerecord` (*ModflowTdis attribute*), 152  
`attrs_from_namfile_header()` (*Grid method*), 703  
`attrs_from_namfile_header()` (*in module flopy.utils.mfreadnam*), 607  
`attribute_by_kper()` (*MfList method*), 648  
`attribute_dict` (*StructuredSpatialReference property*), 351  
`atv` (*ModflowGwtdsp attribute*), 281  
`aux` (*ModflowGwfevt attribute*), 188  
`aux` (*ModflowGwfrcha attribute*), 238  
`auxiliary` (*ModflowGwfchd attribute*), 161  
`auxiliary` (*ModflowGwfdrn attribute*), 182  
`auxiliary` (*ModflowGwfevt attribute*), 185  
`auxiliary` (*ModflowGwfevt attribute*), 188  
`auxiliary` (*ModflowGwfgbh attribute*), 192  
`auxiliary` (*ModflowGwfgwf attribute*), 198  
`auxiliary` (*ModflowGwflak attribute*), 210  
`auxiliary` (*ModflowGwfmaw attribute*), 219  
`auxiliary` (*ModflowGwfrch attribute*), 235  
`auxiliary` (*ModflowGwfrcha attribute*), 238  
`auxiliary` (*ModflowGwfriv attribute*), 241  
`auxiliary` (*ModflowGwfsfr attribute*), 250

`auxiliary` (*ModflowGwfuzf attribute*), 259  
`auxiliary` (*ModflowGwfwel attribute*), 263  
`auxiliary` (*ModflowGwtcnc attribute*), 269  
`auxiliary` (*ModflowGwtgwt attribute*), 285  
`auxiliary` (*ModflowGwtlkt attribute*), 294  
`auxiliary` (*ModflowGwtmwt attribute*), 302  
`auxiliary` (*ModflowGwtsft attribute*), 312  
`auxiliary` (*ModflowGwtsrc attribute*), 316  
`auxiliary` (*ModflowGwtuzt attribute*), 322

## B

`backup_existing_dfn()` (*in module flopy.mf6.utils.generate\_classes*), 373  
`backward` (*trackDir attribute*), 560  
`bands` (*Raster property*), 623  
`base_version` (*LegacyVersion property*), 620  
`base_version` (*Version property*), 620  
`BaseModel` (*class in flopy.mbase*), 374  
`bc_stage_names` (*check attribute*), 573  
`binary` (*ArrayFormat attribute*), 637  
`binary` (*ArrayFormat property*), 637  
`binary` (*MfList property*), 648  
`BinaryHeader` (*class in flopy.utils.binaryfile*), 565  
`BinaryLayerFile` (*class in flopy.utils.binaryfile*), 565  
`binaryread()` (*in module flopy.utils.binaryfile*), 571  
`binaryread_struct()` (*in module flopy.utils.binaryfile*), 571  
`block_headers` (*MFBBlock attribute*), 122  
`blocks` (*MFPackage attribute*), 125  
`bot` (*MfGrdFile property*), 344  
`bot` (*ModflowGwfdisu attribute*), 175  
`bot` (*ModflowGwtdisu attribute*), 275  
`botm` (*Grid attribute*), 702  
`botm` (*Grid property*), 703  
`botm` (*ModflowGwfdis attribute*), 171  
`botm` (*ModflowGwfdisv attribute*), 179  
`botm` (*ModflowGwtdis attribute*), 271  
`botm` (*ModflowGwtdisv attribute*), 279  
`bounds` (*acdd property*), 681  
`bounds` (*Collection property*), 586  
`bounds` (*LineString property*), 586  
`bounds` (*Point property*), 587  
`bounds` (*Polygon property*), 587  
`bounds` (*Raster property*), 624  
`budget_filerecord` (*ModflowGwflak attribute*), 210  
`budget_filerecord` (*ModflowGwfmaw attribute*), 219  
`budget_filerecord` (*ModflowGwfmvr attribute*), 223  
`budget_filerecord` (*ModflowGwfoc attribute*), 232  
`budget_filerecord` (*ModflowGwfsfr attribute*), 250  
`budget_filerecord` (*ModflowGwfuzf attribute*), 259  
`budget_filerecord` (*ModflowGwtist attribute*), 289  
`budget_filerecord` (*ModflowGwtlkt attribute*), 294  
`budget_filerecord` (*ModflowGwtmvt attribute*), 298  
`budget_filerecord` (*ModflowGwtmwt attribute*), 302

budget\_filerecord (*ModflowGwtoc attribute*), 307  
 budget\_filerecord (*ModflowGwtsft attribute*), 312  
 budget\_filerecord (*ModflowGwtuzt attribute*), 322  
 budget\_filerecord (*ModflowMvr attribute*), 149  
 budgetcsv\_filerecord (*ModflowGwflak attribute*), 210  
 budgetcsv\_filerecord (*ModflowGwfmaw attribute*), 219  
 budgetcsv\_filerecord (*ModflowGwfmvr attribute*), 223  
 budgetcsv\_filerecord (*ModflowGwfoc attribute*), 232  
 budgetcsv\_filerecord (*ModflowGwfsfr attribute*), 250  
 budgetcsv\_filerecord (*ModflowGwfuzf attribute*), 259  
 budgetcsv\_filerecord (*ModflowGwtist attribute*), 289  
 budgetcsv\_filerecord (*ModflowGwtlkt attribute*), 294  
 budgetcsv\_filerecord (*ModflowGwtmvt attribute*), 298  
 budgetcsv\_filerecord (*ModflowGwtmwt attribute*), 302  
 budgetcsv\_filerecord (*ModflowGwtoc attribute*), 307  
 budgetcsv\_filerecord (*ModflowGwtsft attribute*), 312  
 budgetcsv\_filerecord (*ModflowGwtuzt attribute*), 322  
 budgetcsv\_filerecord (*ModflowMvr attribute*), 149  
 BudgetIndexError, 566  
 budgetOpt (*class in flopy.modpath.mp7sim*), 559  
 build() (*Gridgen method*), 591  
 build() (*Triangle method*), 633  
 build\_2d\_instances() (*Util3d method*), 646  
 build\_child\_package() (*MFPackage method*), 125  
 build\_child\_packages\_container() (*MFPackage method*), 125  
 build\_dfn\_string() (*in module flopy.mf6.utils.createpackages*), 372  
 build\_doc\_string() (*in module flopy.mf6.utils.createpackages*), 372  
 build\_header\_variables() (*MFBBlockHeader method*), 124  
 build\_init\_string() (*in module flopy.mf6.utils.createpackages*), 372  
 build\_list() (*MultiList method*), 580  
 build\_mfdata() (*MFPackage method*), 125  
 build\_model\_init\_vars() (*in module flopy.mf6.utils.createpackages*), 372  
 build\_model\_load() (*in module flopy.mf6.utils.createpackages*), 372  
 build\_transient\_sequence() (*Transient2d method*), 638  
 build\_transient\_sequence() (*Transient3d method*), 641  
 bulk\_density (*ModflowGwtist attribute*), 289

bulk\_density (*ModflowGwtmst attribute*), 297  
 by\_node\_variables (*Mnw attribute*), 441

## C

CachedData (*class in flopy.discretization.grid*), 701  
 calc\_conc() (*SwiConcentration method*), 673  
 cell1d (*VertexGrid property*), 716  
 cell2d (*MfGrdFile property*), 344  
 cell2d (*ModflowGwfdisu attribute*), 175  
 cell2d (*ModflowGwfdisv attribute*), 179  
 cell2d (*ModflowGwtdisu attribute*), 275  
 cell2d (*ModflowGwtdisv attribute*), 279  
 cell2d (*VertexGrid property*), 716  
 CellBudgetFile (*class in flopy.utils.binaryfile*), 566  
 cellcenters (*MfGrdFile property*), 344  
 CellDataType (*class in flopy.modpath.mp7particledata*), 551  
 centered\_specific\_discharge() (*PlotUtilities static method*), 673  
 centroid\_of\_polygon() (*in module flopy.utils.cvfutil*), 574  
 cg\_ske\_cr (*ModflowGwfcsb attribute*), 168  
 cg\_theta (*ModflowGwfcsb attribute*), 168  
 change\_model\_name() (*ZoneBudget6 method*), 659  
 change\_model\_ws() (*BaseModel method*), 375  
 change\_model\_ws() (*Seawat method*), 542  
 change\_model\_ws() (*ZoneBudget6 method*), 660  
 check (*class in flopy.modflow.mfsfr2*), 479  
 check (*class in flopy.utils.check*), 572  
 check() (*BaseModel method*), 375  
 check() (*MFMModel method*), 117  
 check() (*MFPackage method*), 126  
 check() (*MFSimulation method*), 129  
 check() (*Mnw method*), 441  
 check() (*ModelInterface method*), 379  
 check() (*ModflowBas method*), 388  
 check() (*ModflowDis method*), 397  
 check() (*ModflowMnw2 method*), 444  
 check() (*ModflowMnwi method*), 447  
 check() (*ModflowOc method*), 453  
 check() (*ModflowRch method*), 468  
 check() (*ModflowRiv method*), 471  
 check() (*ModflowSfr2 method*), 477  
 check() (*Modpath6Sim method*), 563  
 check() (*PackageInterface method*), 382  
 check\_kij() (*MfList method*), 648  
 checklayerthickness() (*ModflowDis method*), 398  
 cim (*ModflowGwtist attribute*), 289  
 cim\_filerecord (*ModflowGwtist attribute*), 289  
 cimprintrecord (*ModflowGwtist attribute*), 289  
 cl12 (*ModflowGwfdisu attribute*), 175  
 cl12 (*ModflowGwtdisu attribute*), 275  
 clean() (*Triangle method*), 633

`clean_class_string()` (in module `flopY.mf6.utils.createpackages`), 373  
`clean_filename()` (in module `flopY.utils.datautil`), 582  
`clean_name()` (in module `flopY.utils.datautil`), 582  
`clean_numeric()` (`PyListUtil` static method), 581  
`close()` (`CellBudgetFile` method), 566  
`close()` (`FileIter` method), 579  
`close()` (`FormattedLayerFile` method), 585  
`close()` (`LayerFile` method), 576  
`cnstnt_str` (`Util2d` property), 643  
`Collection` (class in `flopY.utils.geometry`), 586  
`combined` (`simType` attribute), 559  
`comment` (`MFBBlockHeader` attribute), 124  
`compaction_coarse_filerecord` (`ModflowGwfcs` sub attribute), 168  
`compaction_elastic_filerecord` (`ModflowGwfcs` sub attribute), 168  
`compaction_filerecord` (`ModflowGwfcs` sub attribute), 168  
`compaction_inelastic_filerecord` (`ModflowGwfcs` sub attribute), 168  
`compaction_interbed_filerecord` (`ModflowGwfcs` sub attribute), 168  
`concentration` (`ModflowUtlspca` attribute), 333  
`concentration_filerecord` (`ModflowGwtlkt` attribute), 294  
`concentration_filerecord` (`ModflowGwtmwt` attribute), 302  
`concentration_filerecord` (`ModflowGwtoc` attribute), 307  
`concentration_filerecord` (`ModflowGwtsft` attribute), 312  
`concentration_filerecord` (`ModflowGwtuzt` attribute), 322  
`concentrationprintrecord` (`ModflowGwtoc` attribute), 307  
`connect_to_dict()` (`MFBBlockHeader` method), 124  
`connectiondata` (`ModflowGwflak` attribute), 210  
`connectiondata` (`ModflowGwfma` attribute), 219  
`connectiondata` (`ModflowGwfsfr` attribute), 250  
`consistent_delim` (`PyListUtil` attribute), 581  
`const` (`ModflowSfr2` property), 477  
`ConstIter` (class in `flopY.utils.datautil`), 579  
`continuous` (`ModflowUtlobs` attribute), 328  
`contour_array()` (in module `flopY.export.utils`), 689  
`contour_array()` (`PlotCrossSection` method), 663  
`contour_array()` (`PlotMapView` method), 668  
`contour_array_cvfd()` (`PlotMapView` method), 668  
`copy()` (`NetCdf` method), 683  
`copy()` (`ZoneBudget` method), 656  
`copy_all` (`ExtFileAction` attribute), 109  
`copy_files()` (`MFFileMgmt` method), 110  
`copy_none` (`ExtFileAction` attribute), 109  
`copy_relative_paths` (`ExtFileAction` attribute), 109  
`create()` (`BinaryHeader` static method), 565  
`create_basic_init()` (in module `flopY.mf6.utils.createpackages`), 373  
`create_empty_recarray()` (in module `flopY.utils.recarray_utils`), 626  
`create_group_variable()` (`NetCdf` method), 683  
`create_init_var()` (in module `flopY.mf6.utils.createpackages`), 373  
`create_mp7()` (`Modpath7` class method), 549  
`create_mpsim()` (`Modpath6` method), 561  
`create_package_dimensions()` (`MFPackage` method), 126  
`create_package_init_var()` (in module `flopY.mf6.utils.createpackages`), 373  
`create_packages()` (in module `flopY.mf6.utils.createpackages`), 373  
`create_property()` (in module `flopY.mf6.utils.createpackages`), 373  
`create_variable()` (`NetCdf` method), 683  
`creator` (`acdd` property), 681  
`creator_url` (`acdd` property), 681  
`crop()` (`Raster` method), 624  
`cross_section_adjust_indicies()` (`Grid` method), 703  
`cross_section_adjust_indicies()` (`UnstructuredGrid` method), 713  
`cross_section_lay_ncpl_ncb()` (`Grid` method), 704  
`cross_section_lay_ncpl_ncb()` (`UnstructuredGrid` method), 713  
`cross_section_nodeskip()` (`Grid` method), 704  
`cross_section_nodeskip()` (`UnstructuredGrid` method), 713  
`cross_section_set_contour_arrays()` (`Grid` method), 704  
`cross_section_set_contour_arrays()` (`UnstructuredGrid` method), 713  
`cross_section_vertices` (`Grid` property), 704  
`cross_section_vertices` (`StructuredGrid` property), 708  
`cross_section_vertices` (`UnstructuredGrid` property), 714  
`crossections` (`ModflowGwfsfr` attribute), 250  
`CRS` (class in `flopY.export.shapefile_utils`), 685  
`crs` (`CRS` property), 685  
`csv_inner_output_filerecord` (`ModflowIms` attribute), 145  
`csv_names` (`MF6Output` property), 348  
`csv_outer_output_filerecord` (`ModflowIms` attribute), 145  
`csv_output_filerecord` (`ModflowIms` attribute), 145  
`CsvFile` (class in `flopY.utils.observationfile`), 615  
`cvfd_to_patch_collection()` (in module `flopY.plot.plotutil`), 675



## D

- `data` (*CachedData* property), 701
- `data` (*MfArray* property), 355
- `data` (*MfList* property), 648
- `data` (*MfScalar* property), 368
- `data` (*MfTransientList* property), 365
- `data_factory()` (*MfBlock* method), 123
- `data_items` (*MfBlockHeader* attribute), 124
- `data_list` (*MfPackage* property), 126
- `data_list` (*Package* property), 381
- `data_list` (*PackageInterface* property), 383
- `data_nocopy` (*CachedData* property), 701
- `data_type` (*MfArray* property), 355
- `data_type` (*MfList* property), 361
- `data_type` (*MfList* property), 648
- `data_type` (*MfScalar* property), 369
- `data_type` (*MfSimulation* property), 370
- `data_type` (*MfTransientArray* property), 358
- `data_type` (*MfTransientList* property), 366
- `data_type` (*Transient2d* property), 638
- `data_type` (*Transient3d* property), 641
- `data_type` (*Util2d* property), 643
- `data_type` (*Util3d* property), 646
- `dataframe_to_netcdf_fmt()` (in module *flop.utils.zonbud*), 662
- `dataset_5` (*ModflowSfr2* property), 477
- `datasets` (*MfBlock* attribute), 123
- `datasets_keyword` (*MfBlock* attribute), 123
- `DatumUtil` (class in *flop.utils.datautil*), 579
- `deactivate_ibound_above()` (*ModflowSfr2* method), 477
- `decay` (*ModflowGwtist* attribute), 289
- `decay` (*ModflowGwtmst* attribute), 297
- `decay_sorbed` (*ModflowGwtist* attribute), 289
- `decay_sorbed` (*ModflowGwtmst* attribute), 297
- `decimal` (*ArrayFormat* attribute), 636
- `decimal` (*ArrayFormat* property), 637
- `decode_fortran_descriptor()` (*ArrayFormat* static method), 637
- `default_value` (*ModflowSfr2* attribute), 477
- `defaults` (*TemporalReference* attribute), 627
- `delc` (*MfGrdFile* property), 344
- `delc` (*ModflowGwfdis* attribute), 171
- `delc` (*ModflowGwtid* attribute), 271
- `delc` (*StructuredGrid* property), 708
- `delete_files()` (in module *flop.mf6.utils.generate\_classes*), 373
- `delete_mf6_classes()` (in module *flop.mf6.utils.generate\_classes*), 373
- `delete_output_files()` (*MfSimulation* method), 129
- `delimiter_list` (*PyListUtil* attribute), 581
- `delimiter_used` (*PyListUtil* attribute), 581
- `delr` (*MfGrdFile* property), 345
- `delr` (*ModflowGwfdis* attribute), 171
- `delr` (*ModflowGwtid* attribute), 271
- `delr` (*StructuredGrid* property), 708
- `delz` (*StructuredGrid* property), 708
- `density_filerecord` (*ModflowGwfbuy* attribute), 159
- `depth` (*ModflowGwfevt* attribute), 188
- `dev` (*LegacyVersion* property), 620
- `dev` (*Version* property), 620
- `df` (*MfList* property), 649
- `df` (*ModflowSfr2* property), 477
- `df` (*SfrFile* property), 628
- `dfn` (*ModflowGnc* attribute), 138
- `dfn` (*ModflowGwfapi* attribute), 157
- `dfn` (*ModflowGwfbuy* attribute), 159
- `dfn` (*ModflowGwfchd* attribute), 161
- `dfn` (*ModflowGwfcsb* attribute), 168
- `dfn` (*ModflowGwfdis* attribute), 171
- `dfn` (*ModflowGwfdisu* attribute), 175
- `dfn` (*ModflowGwfdisv* attribute), 179
- `dfn` (*ModflowGwfdrn* attribute), 182
- `dfn` (*ModflowGwfevt* attribute), 185
- `dfn` (*ModflowGwfevt* attribute), 188
- `dfn` (*ModflowGwfgbh* attribute), 192
- `dfn` (*ModflowGwfgnc* attribute), 194
- `dfn` (*ModflowGwfgwf* attribute), 198
- `dfn` (*ModflowGwfgwt* attribute), 200
- `dfn` (*ModflowGwfhfb* attribute), 201
- `dfn` (*ModflowGwfgic* attribute), 202
- `dfn` (*ModflowGwflak* attribute), 210
- `dfn` (*ModflowGwfmaw* attribute), 219
- `dfn` (*ModflowGwfmvr* attribute), 223
- `dfn` (*ModflowGwfnam* attribute), 225
- `dfn` (*ModflowGwfnpf* attribute), 229
- `dfn` (*ModflowGwfoc* attribute), 232
- `dfn` (*ModflowGwfrch* attribute), 235
- `dfn` (*ModflowGwfrcha* attribute), 238
- `dfn` (*ModflowGwfriv* attribute), 241
- `dfn` (*ModflowGwfsfr* attribute), 250
- `dfn` (*ModflowGwfsto* attribute), 253
- `dfn` (*ModflowGwfufz* attribute), 259
- `dfn` (*ModflowGwfwel* attribute), 263
- `dfn` (*ModflowGwtadv* attribute), 265
- `dfn` (*ModflowGwtapi* attribute), 266
- `dfn` (*ModflowGwtcnc* attribute), 269
- `dfn` (*ModflowGwtid* attribute), 271
- `dfn` (*ModflowGwtidisu* attribute), 275
- `dfn` (*ModflowGwtidiv* attribute), 279
- `dfn` (*ModflowGwtidsp* attribute), 281
- `dfn` (*ModflowGwtfmi* attribute), 282
- `dfn` (*ModflowGwtgwt* attribute), 285
- `dfn` (*ModflowGwtic* attribute), 287
- `dfn` (*ModflowGwtist* attribute), 289
- `dfn` (*ModflowGwtlkt* attribute), 294
- `dfn` (*ModflowGwtmst* attribute), 297
- `dfn` (*ModflowGwtmvt* attribute), 298

`dfn` (*ModflowGwtmwt* attribute), 302  
`dfn` (*ModflowGwtnam* attribute), 305  
`dfn` (*ModflowGwtoc* attribute), 307  
`dfn` (*ModflowGwtsft* attribute), 312  
`dfn` (*ModflowGwtsrc* attribute), 316  
`dfn` (*ModflowGwtssm* attribute), 318  
`dfn` (*ModflowGwtuzt* attribute), 322  
`dfn` (*ModflowIms* attribute), 145  
`dfn` (*ModflowMvr* attribute), 149  
`dfn` (*ModflowNam* attribute), 151  
`dfn` (*ModflowTdis* attribute), 152  
`dfn` (*ModflowUtilats* attribute), 325  
`dfn` (*ModflowUtlaktab* attribute), 327  
`dfn` (*ModflowUtlobs* attribute), 328  
`dfn` (*ModflowUtlstfrtab* attribute), 330  
`dfn` (*ModflowUtlspc* attribute), 332  
`dfn` (*ModflowUtlspca* attribute), 333  
`dfn` (*ModflowUtlts* attribute), 335  
`dfn` (*ModflowUtlts* attribute), 337  
`dfn` (*ModflowUtltkv* attribute), 339  
`dfn` (*ModflowUtltsv* attribute), 342  
`dfn_file_name` (*ModflowGnc* attribute), 139  
`dfn_file_name` (*ModflowGwfapi* attribute), 157  
`dfn_file_name` (*ModflowGwfbuy* attribute), 159  
`dfn_file_name` (*ModflowGwfchd* attribute), 162  
`dfn_file_name` (*ModflowGwfcsb* attribute), 170  
`dfn_file_name` (*ModflowGwfdis* attribute), 172  
`dfn_file_name` (*ModflowGwfdisu* attribute), 176  
`dfn_file_name` (*ModflowGwfdisv* attribute), 179  
`dfn_file_name` (*ModflowGwfdrn* attribute), 182  
`dfn_file_name` (*ModflowGwfevt* attribute), 186  
`dfn_file_name` (*ModflowGwfevta* attribute), 189  
`dfn_file_name` (*ModflowGwfgbh* attribute), 192  
`dfn_file_name` (*ModflowGwfgnc* attribute), 194  
`dfn_file_name` (*ModflowGwfgwf* attribute), 199  
`dfn_file_name` (*ModflowGwfgwt* attribute), 200  
`dfn_file_name` (*ModflowGwfhfb* attribute), 201  
`dfn_file_name` (*ModflowGwfic* attribute), 202  
`dfn_file_name` (*ModflowGwflak* attribute), 212  
`dfn_file_name` (*ModflowGwfmaw* attribute), 221  
`dfn_file_name` (*ModflowGwfmvr* attribute), 223  
`dfn_file_name` (*ModflowGwfnam* attribute), 225  
`dfn_file_name` (*ModflowGwfnpf* attribute), 230  
`dfn_file_name` (*ModflowGwfoc* attribute), 233  
`dfn_file_name` (*ModflowGwfrch* attribute), 236  
`dfn_file_name` (*ModflowGwfrcha* attribute), 239  
`dfn_file_name` (*ModflowGwfriv* attribute), 242  
`dfn_file_name` (*ModflowGwfsfr* attribute), 252  
`dfn_file_name` (*ModflowGwfsto* attribute), 253  
`dfn_file_name` (*ModflowGwfufz* attribute), 261  
`dfn_file_name` (*ModflowGwfwel* attribute), 264  
`dfn_file_name` (*ModflowGwtadv* attribute), 265  
`dfn_file_name` (*ModflowGwtapi* attribute), 267  
`dfn_file_name` (*ModflowGwtcnc* attribute), 269

`dfn_file_name` (*ModflowGwtdis* attribute), 271  
`dfn_file_name` (*ModflowGwtdisu* attribute), 276  
`dfn_file_name` (*ModflowGwtdisv* attribute), 279  
`dfn_file_name` (*ModflowGwt dsp* attribute), 281  
`dfn_file_name` (*ModflowGwtfmi* attribute), 282  
`dfn_file_name` (*ModflowGwtgwt* attribute), 286  
`dfn_file_name` (*ModflowGwtic* attribute), 287  
`dfn_file_name` (*ModflowGwtist* attribute), 290  
`dfn_file_name` (*ModflowGwtlkt* attribute), 296  
`dfn_file_name` (*ModflowGwtmst* attribute), 297  
`dfn_file_name` (*ModflowGwtmvt* attribute), 299  
`dfn_file_name` (*ModflowGwtmwt* attribute), 304  
`dfn_file_name` (*ModflowGwtnam* attribute), 305  
`dfn_file_name` (*ModflowGwtoc* attribute), 308  
`dfn_file_name` (*ModflowGwtsft* attribute), 314  
`dfn_file_name` (*ModflowGwtsrc* attribute), 316  
`dfn_file_name` (*ModflowGwtssm* attribute), 318  
`dfn_file_name` (*ModflowGwtuzt* attribute), 324  
`dfn_file_name` (*ModflowIms* attribute), 147  
`dfn_file_name` (*ModflowMvr* attribute), 149  
`dfn_file_name` (*ModflowNam* attribute), 151  
`dfn_file_name` (*ModflowTdis* attribute), 153  
`dfn_file_name` (*ModflowUtilats* attribute), 325  
`dfn_file_name` (*ModflowUtlaktab* attribute), 327  
`dfn_file_name` (*ModflowUtlobs* attribute), 329  
`dfn_file_name` (*ModflowUtlstfrtab* attribute), 330  
`dfn_file_name` (*ModflowUtlspc* attribute), 332  
`dfn_file_name` (*ModflowUtlspca* attribute), 334  
`dfn_file_name` (*ModflowUtlts* attribute), 335  
`dfn_file_name` (*ModflowUtlts* attribute), 337  
`dfn_file_name` (*ModflowUtltkv* attribute), 340  
`dfn_file_name` (*ModflowUtltsv* attribute), 342  
`diffc` (*ModflowGwt dsp* attribute), 281  
`difference()` (*NetCDF* method), 684  
`dimensions` (*MFPackage* attribute), 125  
`distcoef` (*ModflowGwtist* attribute), 290  
`distcoef` (*ModflowGwtmst* attribute), 297  
`diversions` (*ModflowGwfsfr* attribute), 252  
`download_dfn()` (in module  
    *flop.mf6.utils.generate\_classes*), 373  
`drop()` (*MfList* method), 649  
`dtype` (*MfArray* property), 355  
`dtype` (*MfList* property), 361  
`dtype` (*MfList* property), 649  
`dtype` (*MfScalar* property), 369  
`dtype` (*MfTransientList* property), 366  
`dtype` (*OptionBlock* attribute), 618  
`dtype` (*Transient2d* property), 638  
`dtype` (*Transient3d* property), 641  
`dtype` (*Util2d* property), 643  
`dtype` (*Util3d* property), 646  
`dtypes` (*SfrFile* attribute), 628

## E

[elements\(\)](#) (*MultiList* method), 580  
[elevations\(\)](#) (*check* method), 480  
[empty\\_like\(\)](#) (*NetCDF* class method), 684  
[enabled](#) (*MFB*Block attribute), 123  
[endpoint](#) (*simType* attribute), 559  
[EndpointFile](#) (class in *flopY*.utils.modpathfile), 608  
[enforce\\_10ch\\_limit\(\)](#) (in module *flopY*.export.shapefile\_utils), 686  
[ensemble\\_helper\(\)](#) (in module *flopY*.export.utils), 689  
[epoch](#) (*LegacyVersion* property), 620  
[epoch](#) (*Version* property), 620  
[epsg](#) (*Grid* attribute), 702  
[epsg](#) (*Grid* property), 704  
[EpsgReference](#) (class in *flopY*.export.shapefile\_utils), 686  
[exchange\\_files](#) (*MFSimulation* property), 129  
[exchangedata](#) (*ModflowGwfgwf* attribute), 199  
[exchangedata](#) (*ModflowGwtgwt* attribute), 286  
[exchanges](#) (*ModflowNam* attribute), 151  
[exe\\_name](#) (*MFModel* attribute), 117  
[exename](#) (*BaseModel* property), 376  
[exename](#) (*MFModel* property), 117  
[exename](#) (*ModelInterface* property), 379  
[export\(\)](#) (*BaseModel* method), 376  
[export\(\)](#) (*Gridgen* method), 591  
[export\(\)](#) (*MfList* method), 649  
[export\(\)](#) (*MFModel* method), 117  
[export\(\)](#) (*MFPackage* method), 126  
[export\(\)](#) (*ModelInterface* method), 379  
[export\(\)](#) (*ModflowMnw2* method), 444  
[export\(\)](#) (*ModflowSfr2* method), 477  
[export\(\)](#) (*Package* method), 381  
[export\(\)](#) (*PackageInterface* method), 383  
[export\(\)](#) (*Transient2d* method), 638  
[export\(\)](#) (*Util2d* method), 643  
[export\(\)](#) (*Util3d* method), 646  
[export\(\)](#) (*ZoneBudget* method), 656  
[export\(\)](#) (*ZoneBudget6* method), 660  
[export\\_array\(\)](#) (in module *flopY*.export.utils), 689  
[export\\_array\(\)](#) (in module *flopY*.export.vtk), 695  
[export\\_array\\_contours\(\)](#) (in module *flopY*.export.utils), 690  
[export\\_cbc\(\)](#) (in module *flopY*.export.vtk), 696  
[export\\_contourf\(\)](#) (in module *flopY*.export.utils), 690  
[export\\_contours\(\)](#) (in module *flopY*.export.utils), 691  
[export\\_heads\(\)](#) (in module *flopY*.export.vtk), 697  
[export\\_linkages\(\)](#) (*ModflowSfr2* method), 478  
[export\\_model\(\)](#) (in module *flopY*.export.vtk), 697  
[export\\_outlets\(\)](#) (*ModflowSfr2* method), 478  
[export\\_package\(\)](#) (in module *flopY*.export.vtk), 698  
[export\\_transient\(\)](#) (in module *flopY*.export.vtk), 698  
[export\\_transient\\_variable\(\)](#) (*ModflowSfr2* method), 478

[extend](#) (*stopOpt* attribute), 560  
[extent](#) (*Grid* property), 704  
[extent](#) (*PlotMapView* property), 669  
[extent](#) (*StructuredGrid* property), 708  
[extent](#) (*UnstructuredGrid* property), 714  
[extent](#) (*VertexGrid* property), 717  
[external\\_formatting](#) (*MFSimulationData* attribute), 135  
[ExtFileAction](#) (class in *flopY*.mf6.mfbase), 109

## F

[FaceDataType](#) (class in module *flopY*.modpath.mp7particledata), 552  
[features\\_to\\_shapefile\(\)](#) (in module *flopY*.utils.gridgen), 596  
[fields\\_view\(\)](#) (in module *flopY*.utils.check), 574  
[FileData](#) (class in *flopY*.mbase), 379  
[FileDataEntry](#) (class in *flopY*.mbase), 379  
[filehandle](#) (*NamData* attribute), 606  
[fileinput](#) (*ModflowGwtssm* attribute), 318  
[FileIter](#) (class in *flopY*.utils.datautil), 579  
[filename](#) (*MFPackage* property), 126  
[filename](#) (*NamData* attribute), 606  
[filename](#) (*Util2d* property), 643  
[filetype](#) (*NamData* attribute), 607  
[filter\\_modpath\\_by\\_travel\\_time\(\)](#) (in module *flopY*.plot.plotutil), 675  
[filter\\_query\\_result\(\)](#) (*GridIntersect* static method), 597  
[find\\_in\\_path\(\)](#) (*SimulationDict* method), 136  
[find\\_keyword\(\)](#) (in module *flopY*.utils.datautil), 582  
[find\\_path\(\)](#) (in module *flopY*.modflow.mfsfr2), 480  
[find\\_position\\_in\\_array\(\)](#) (*ModflowGridIndices* static method), 599  
[first\\_index\(\)](#) (*MultiList* method), 580  
[first\\_item\(\)](#) (*MultiList* method), 580  
[first\\_item\(\)](#) (*PyListUtil* static method), 581  
[float\(\)](#) (*ArrayFormat* class method), 637  
[FLOAT32](#) (*Raster* attribute), 623  
[FLOAT64](#) (*Raster* attribute), 623  
[float\\_characters](#) (*MFSimulationData* attribute), 135  
[float\\_precision](#) (*MFSimulationData* attribute), 135  
[flopY.discretization.grid](#) module, 701  
[flopY.discretization.modeltime](#) module, 707  
[flopY.discretization.structuredgrid](#) module, 707  
[flopY.discretization.unstructuredgrid](#) module, 712  
[flopY.discretization.vertexgrid](#) module, 716  
[flopY.export.longnames](#) module, 681

flop.export.metadata  
  module, 681

flop.export.netcdf  
  module, 682

flop.export.shapefile\_utils  
  module, 685

flop.export.unitsformat  
  module, 688

flop.export.utils  
  module, 688

flop.export.vtk  
  module, 693

flop.mbase  
  module, 374

flop.mf6.data.mfdataarray  
  module, 355

flop.mf6.data.mfdatalist  
  module, 361

flop.mf6.data.mfdatascalar  
  module, 368

flop.mf6.mbase  
  module, 109

flop.mf6.mfmodel  
  module, 116

flop.mf6.mfpackage  
  module, 122

flop.mf6.modflow.mfgnc  
  module, 137

flop.mf6.modflow.mfgwf  
  module, 153

flop.mf6.modflow.mfgwfapi  
  module, 156

flop.mf6.modflow.mfgwfbuy  
  module, 158

flop.mf6.modflow.mfgwfchd  
  module, 160

flop.mf6.modflow.mfgwfcsb  
  module, 163

flop.mf6.modflow.mfgwfdis  
  module, 170

flop.mf6.modflow.mfgwfdisu  
  module, 172

flop.mf6.modflow.mfgwfdisv  
  module, 177

flop.mf6.modflow.mfgwfdrn  
  module, 180

flop.mf6.modflow.mfgwfevt  
  module, 183

flop.mf6.modflow.mfgwfevta  
  module, 187

flop.mf6.modflow.mfgwfgbh  
  module, 190

flop.mf6.modflow.mfgwfgnc  
  module, 193

flop.mf6.modflow.mfgwfgwf  
  module, 195

flop.mf6.modflow.mfgwfgwt  
  module, 200

flop.mf6.modflow.mfgwfhfb  
  module, 200

flop.mf6.modflow.mfgwfic  
  module, 202

flop.mf6.modflow.mfgwflak  
  module, 202

flop.mf6.modflow.mfgwfmau  
  module, 212

flop.mf6.modflow.mfgwfmvr  
  module, 221

flop.mf6.modflow.mfgwfnau  
  module, 224

flop.mf6.modflow.mfgwfnpf  
  module, 225

flop.mf6.modflow.mfgwfoc  
  module, 231

flop.mf6.modflow.mfgwfrch  
  module, 234

flop.mf6.modflow.mfgwfrcha  
  module, 237

flop.mf6.modflow.mfgwfriv  
  module, 239

flop.mf6.modflow.mfgwfsfr  
  module, 243

flop.mf6.modflow.mfgwfsto  
  module, 252

flop.mf6.modflow.mfgwfufz  
  module, 254

flop.mf6.modflow.mfgwfwel  
  module, 261

flop.mf6.modflow.mfgwt  
  module, 155

flop.mf6.modflow.mfgwtadv  
  module, 265

flop.mf6.modflow.mfgwtapi  
  module, 265

flop.mf6.modflow.mfgwtcnc  
  module, 267

flop.mf6.modflow.mfgwtdis  
  module, 270

flop.mf6.modflow.mfgwtdisu  
  module, 272

flop.mf6.modflow.mfgwtdisv  
  module, 277

flop.mf6.modflow.mfgwt dsp  
  module, 280

flop.mf6.modflow.mfgwt fmi  
  module, 282

flop.mf6.modflow.mfgwt gwt  
  module, 283



flopy.mf6.modflow.mfgwtic  
     module, 287  
 flopy.mf6.modflow.mfgwtist  
     module, 287  
 flopy.mf6.modflow.mfgwtlkt  
     module, 291  
 flopy.mf6.modflow.mfgwtmst  
     module, 296  
 flopy.mf6.modflow.mfgwtmvt  
     module, 298  
 flopy.mf6.modflow.mfgwtmwt  
     module, 299  
 flopy.mf6.modflow.mfgwtnam  
     module, 304  
 flopy.mf6.modflow.mfgwtoc  
     module, 305  
 flopy.mf6.modflow.mfgwtsft  
     module, 309  
 flopy.mf6.modflow.mfgwtsrc  
     module, 314  
 flopy.mf6.modflow.mfgwtssm  
     module, 316  
 flopy.mf6.modflow.mfgwtuzt  
     module, 318  
 flopy.mf6.modflow.mfims  
     module, 139  
 flopy.mf6.modflow.mfmvr  
     module, 147  
 flopy.mf6.modflow.mfnam  
     module, 150  
 flopy.mf6.modflow.mfsimulation  
     module, 128  
 flopy.mf6.modflow.mftdis  
     module, 152  
 flopy.mf6.modflow.mfutlats  
     module, 324  
 flopy.mf6.modflow.mfutllaktab  
     module, 326  
 flopy.mf6.modflow.mfutlobs  
     module, 327  
 flopy.mf6.modflow.mfutlsfrtab  
     module, 329  
 flopy.mf6.modflow.mfutlspc  
     module, 331  
 flopy.mf6.modflow.mfutlspca  
     module, 333  
 flopy.mf6.modflow.mfutltas  
     module, 334  
 flopy.mf6.modflow.mfutlts  
     module, 336  
 flopy.mf6.modflow.mfutltvk  
     module, 338  
 flopy.mf6.modflow.mfutltvs  
     module, 341  
 flopy.mf6.utils.binaryfile\_utils  
     module, 343  
 flopy.mf6.utils.binarygrid\_util  
     module, 344  
 flopy.mf6.utils.createpackages  
     module, 372  
 flopy.mf6.utils.generate\_classes  
     module, 373  
 flopy.mf6.utils.lakpak\_utils  
     module, 354  
 flopy.mf6.utils.mfobservation  
     module, 347  
 flopy.mf6.utils.output\_util  
     module, 348  
 flopy.mf6.utils.postprocessing  
     module, 349  
 flopy.mf6.utils.reference  
     module, 350  
 flopy.modflow.mf  
     module, 383  
 flopy.modflow.mfaddoutsidefile  
     module, 385  
 flopy.modflow.mfag  
     module, 386  
 flopy.modflow.mfbas  
     module, 387  
 flopy.modflow.mfbcf  
     module, 389  
 flopy.modflow.mfbct  
     module, 391  
 flopy.modflow.mfchd  
     module, 392  
 flopy.modflow.mfde4  
     module, 394  
 flopy.modflow.mfdis  
     module, 396  
 flopy.modflow.mfdrn  
     module, 401  
 flopy.modflow.mfdrt  
     module, 403  
 flopy.modflow.mfevt  
     module, 405  
 flopy.modflow.mffhb  
     module, 407  
 flopy.modflow.mfflwob  
     module, 409  
 flopy.modflow.mfgage  
     module, 411  
 flopy.modflow.mfghb  
     module, 413  
 flopy.modflow.mfgmg  
     module, 415  
 flopy.modflow.mfhfb  
     module, 418

flopy.modflow.mfhob module, 420	flopy.modflow.mfswt module, 496
flopy.modflow.mfhyd module, 423	flopy.modflow.mfupw module, 500
flopy.modflow.mflak module, 424	flopy.modflow.mfuzf1 module, 502
flopy.modflow.mflmt module, 429	flopy.modflow.mfwel module, 508
flopy.modflow.mflpf module, 430	flopy.modflow.mfzon module, 510
flopy.modflow.mfmlt module, 433	flopy.modpath.mp6 module, 560
flopy.modflow.mfmnw1 module, 435	flopy.modpath.mp6bas module, 562
flopy.modflow.mfmnw2 module, 436	flopy.modpath.mp6sim module, 563
flopy.modflow.mfmnwi module, 446	flopy.modpath.mp7 module, 549
flopy.modflow.mfnwt module, 448	flopy.modpath.mp7bas module, 551
flopy.modflow.mfoc module, 451	flopy.modpath.mp7particledata module, 551
flopy.modflow.mfpar module, 456	flopy.modpath.mp7particlegroup module, 555
flopy.modflow.mfparbc module, 458	flopy.modpath.mp7sim module, 557
flopy.modflow.mfpbc module, 459	flopy.mt3d.mt module, 511
flopy.modflow.mfpccg module, 460	flopy.mt3d.mtadv module, 514
flopy.modflow.mfpccgn module, 461	flopy.mt3d.mtbtn module, 517
flopy.modflow.mfpks module, 464	flopy.mt3d.mtcts module, 520
flopy.modflow.mfpval module, 466	flopy.mt3d.mtdsp module, 522
flopy.modflow.mfrch module, 467	flopy.mt3d.mtgccg module, 524
flopy.modflow.mfriv module, 470	flopy.mt3d.mtlkt module, 526
flopy.modflow.mfsfr2 module, 473	flopy.mt3d.mtphc module, 528
flopy.modflow.mfsip module, 481	flopy.mt3d.mtrct module, 528
flopy.modflow.mfsor module, 482	flopy.mt3d.mtsft module, 532
flopy.modflow.mfstr module, 484	flopy.mt3d.mtssm module, 536
flopy.modflow.mfsub module, 488	flopy.mt3d.mttob module, 538
flopy.modflow.mfswi2 module, 492	flopy.mt3d.mtuzt module, 539
flopy.modflow.mfswr1 module, 495	flopy.pakbase module, 381

---

flop.pest.params  
  module, 699  
flop.pest.templatewriter  
  module, 700  
flop.pest.tplarray  
  module, 700  
flop.plot.crossection  
  module, 663  
flop.plot.map  
  module, 668  
flop.plot.plotutil  
  module, 673  
flop.plot.styles  
  module, 678  
flop.seawat.swt  
  module, 541  
flop.seawat.swtvdf  
  module, 543  
flop.seawat.swtvsc  
  module, 546  
flop.utils.binaryfile  
  module, 565  
flop.utils.check  
  module, 572  
flop.utils.cvfdutil  
  module, 574  
flop.utils.datafile  
  module, 576  
flop.utils.datautil  
  module, 579  
flop.utils.flop\_io  
  module, 582  
flop.utils.formattedfile  
  module, 584  
flop.utils.geometry  
  module, 586  
flop.utils.geospatial\_utils  
  module, 589  
flop.utils.gridgen  
  module, 590  
flop.utils.gridintersect  
  module, 597  
flop.utils.lgrutil  
  module, 601  
flop.utils.mflistfile  
  module, 602  
flop.utils.mfreadnam  
  module, 606  
flop.utils.modpathfile  
  module, 608  
flop.utils.mtlistfile  
  module, 614  
flop.utils.observationfile  
  module, 615  
flop.utils.optionblock  
  module, 618  
flop.utils.parse\_version  
  module, 620  
flop.utils.postprocessing  
  module, 621  
flop.utils.rasters  
  module, 623  
flop.utils.reccarray\_utils  
  module, 626  
flop.utils.reference  
  module, 627  
flop.utils.sfroutputfile  
  module, 627  
flop.utils.swroutputfile  
  module, 629  
flop.utils.triangle  
  module, 633  
flop.utils.util\_array  
  module, 636  
flop.utils.util\_list  
  module, 648  
flop.utils.utils\_def  
  module, 652  
flop.utils.utl\_import  
  module, 653  
flop.utils.voronoi  
  module, 654  
flop.utils.zonbud  
  module, 656  
flop\_geometry (*GeoSpatialCollection* property), 589  
flop\_geometry (*GeoSpatialUtil* property), 590  
FlopBinaryData (*class in flop.utils.utils\_def*), 652  
FlopException, 109  
flux\_to\_wel() (*in module flop.utils.flop\_io*), 582  
fmt\_string (*MfList* property), 649  
for\_nans() (*check method*), 480  
format (*ArrayFormat* attribute), 637  
format (*ArrayFormat* property), 637  
format (*Util2d* attribute), 642  
format (*Util2d* property), 643  
format\_var\_list() (*in module flop.mf6.utils.createpackages*), 373  
FormattedHeader (*class in flop.utils.formattedfile*), 585  
FormattedHeadFile (*class in flop.utils.formattedfile*), 584  
FormattedLayerFile (*class in flop.utils.formattedfile*), 585  
fortran (*ArrayFormat* attribute), 636  
fortran (*ArrayFormat* property), 637  
forward (*trackDir* attribute), 560  
free (*ArrayFormat* attribute), 637  
free (*ArrayFormat* property), 637  
from\_4d() (*MfList* class method), 649

[from\\_4d\(\)](#) (*Transient2d class method*), 639  
[from\\_argus\\_export\(\)](#) (*UnstructuredGrid class method*), 714  
[from\\_binary\\_grid\\_file\(\)](#) (*Grid class method*), 704  
[from\\_binary\\_grid\\_file\(\)](#) (*StructuredGrid class method*), 709  
[from\\_binary\\_grid\\_file\(\)](#) (*UnstructuredGrid class method*), 714  
[from\\_binary\\_grid\\_file\(\)](#) (*VertexGrid class method*), 717  
[from\\_geojson\(\)](#) (*Shape static method*), 588  
[from\\_gridspec\(\)](#) (*StructuredGrid class method*), 709  
[from\\_gridspec\(\)](#) (*StructuredSpatialReference class method*), 351  
[from\\_namfile\\_header\(\)](#) (*StructuredSpatialReference class method*), 351  
[from\\_namfile\\_header\(\)](#) (*VertexSpatialReference class method*), 353  
[from\\_package\(\)](#) (*Mt3dSsm method*), 537  
[ftype\(\)](#) (*ModflowFlwob method*), 411

## G

[generate\\_classes\(\)](#) (in *flop.mf6.utils.generate\_classes*), 373  
[generator\\_type\(\)](#) (in *flop.mf6.utils.createpackages*), 373  
[generic\\_array\\_export\(\)](#) (in *flop.export.utils*), 691  
[geojson](#) (*GeoSpatialCollection property*), 589  
[geojson](#) (*GeoSpatialUtil property*), 590  
[geojson](#) (*Shape property*), 588  
[geospatial\\_bounds](#) (*acdd property*), 681  
[geospatial\\_bounds\\_vertical\\_crs](#) (*acdd property*), 681  
[GeoSpatialCollection](#) (class in *flop.utils.geospatial\_utils*), 589  
[GeoSpatialUtil](#) (class in *flop.utils.geospatial\_utils*), 589  
[get\(\)](#) (*EpsgReference method*), 686  
[get\(\)](#) (*ModflowParBc method*), 458  
[get\\_active\(\)](#) (*check method*), 573  
[get\\_active\(\)](#) (*mf6check method*), 574  
[get\\_alldata\(\)](#) (*EndpointFile method*), 608  
[get\\_alldata\(\)](#) (*LayerFile method*), 576  
[get\\_alldata\(\)](#) (*PathlineFile method*), 610  
[get\\_alldata\(\)](#) (*TimeseriesFile method*), 612  
[get\\_allnode\\_data\(\)](#) (*ModflowMnw2 method*), 444  
[get\\_angldegx\(\)](#) (*Gridgen method*), 591  
[get\\_area\(\)](#) (*Gridgen method*), 592  
[get\\_array\(\)](#) (*Raster method*), 624  
[get\\_attribute\\_array\(\)](#) (*Triangle method*), 634  
[get\\_bot\(\)](#) (*Gridgen method*), 592  
[get\\_boundary\\_marker\\_array\(\)](#) (*Triangle method*), 634

[get\\_budget\(\)](#) (*ListBudget method*), 602  
[get\\_budget\(\)](#) (*ZoneBudget method*), 657  
[get\\_budget\(\)](#) (*ZoneBudget6 method*), 660  
[get\\_budgetunit\(\)](#) (*ModflowOc method*), 453  
[get\\_cell2d\(\)](#) (*Triangle method*), 634  
[get\\_cell\\_edge\\_length\(\)](#) (*Triangle method*), 634  
[get\\_cell\\_vertices\(\)](#) (*StructuredGrid method*), 707, 709  
[get\\_cell\\_vertices\(\)](#) (*UnstructuredGrid method*), 712, 714  
[get\\_cell\\_vertices\(\)](#) (*VertexGrid method*), 716, 717  
[get\\_cell\\_volumes\(\)](#) (*ModflowDis method*), 398  
[get\\_cellxy\(\)](#) (*Gridgen method*), 592  
[get\\_center\(\)](#) (*Gridgen method*), 592  
[get\\_cl12\(\)](#) (*Gridgen method*), 592  
[get\\_comment\(\)](#) (*MFBBlockHeader method*), 124  
[get\\_connectivity\(\)](#) (*SwrFile method*), 630  
[get\\_constant\\_cr\(\)](#) (*Util2d method*), 643  
[get\\_coords\(\)](#) (*Grid method*), 703, 704  
[get\\_cumulative\(\)](#) (*ListBudget method*), 602  
[get\\_data\(\)](#) (*CellBudgetFile method*), 566  
[get\\_data\(\)](#) (*EndpointFile method*), 608  
[get\\_data\(\)](#) (*LayerFile method*), 577  
[get\\_data\(\)](#) (*ListBudget method*), 603  
[get\\_data\(\)](#) (*MfArray method*), 355  
[get\\_data\(\)](#) (*MFList method*), 361  
[get\\_data\(\)](#) (*MFMultipleList method*), 365  
[get\\_data\(\)](#) (*MFSscalar method*), 369  
[get\\_data\(\)](#) (*MFSscalarTransient method*), 370  
[get\\_data\(\)](#) (*MFTransientArray method*), 358  
[get\\_data\(\)](#) (*MFTransientList method*), 366  
[get\\_data\(\)](#) (*Observations method*), 347  
[get\\_data\(\)](#) (*ObsFiles method*), 616  
[get\\_data\(\)](#) (*PathlineFile method*), 610  
[get\\_data\(\)](#) (*SwrFile method*), 630  
[get\\_data\(\)](#) (*TimeseriesFile method*), 613  
[get\\_databytes\(\)](#) (*BinaryLayerFile method*), 565  
[get\\_databytes\(\)](#) (*HeadUFile method*), 570  
[get\\_dataframe\(\)](#) (*MfList method*), 649  
[get\\_dataframe\(\)](#) (*Observations method*), 348  
[get\\_dataframe\(\)](#) (*ObsFiles method*), 616  
[get\\_dataframe\(\)](#) (*SfrFile method*), 628  
[get\\_dataframes\(\)](#) (*ListBudget method*), 603  
[get\\_dataframes\(\)](#) (*ZoneBudget method*), 657  
[get\\_dataframes\(\)](#) (*ZoneBudget6 method*), 660  
[get\\_default\\_CTS\\_dtype\(\)](#) (*Mt3dCts static method*), 522  
[get\\_default\\_dtype\(\)](#) (*ModflowAg static method*), 386  
[get\\_default\\_dtype\(\)](#) (*ModflowChd static method*), 393  
[get\\_default\\_dtype\(\)](#) (*ModflowDrn static method*), 402  
[get\\_default\\_dtype\(\)](#) (*ModflowDrt static method*), 404

[get\\_default\\_dtype\(\)](#) (*ModflowFhb static method*), 408  
[get\\_default\\_dtype\(\)](#) (*ModflowGage static method*), 412  
[get\\_default\\_dtype\(\)](#) (*ModflowGhb static method*), 414  
[get\\_default\\_dtype\(\)](#) (*ModflowHfb static method*), 419  
[get\\_default\\_dtype\(\)](#) (*ModflowHyd static method*), 424  
[get\\_default\\_dtype\(\)](#) (*ModflowMnw1 static method*), 436  
[get\\_default\\_dtype\(\)](#) (*ModflowRiv static method*), 472  
[get\\_default\\_dtype\(\)](#) (*ModflowStr static method*), 487  
[get\\_default\\_dtype\(\)](#) (*ModflowWel static method*), 509  
[get\\_default\\_dtype\(\)](#) (*Mt3dLkt static method*), 527  
[get\\_default\\_dtype\(\)](#) (*Mt3dSft static method*), 534  
[get\\_default\\_dtype\(\)](#) (*Mt3dSsm static method*), 537  
[get\\_default\\_node\\_dtype\(\)](#) (*ModflowMnw2 static method*), 444  
[get\\_default\\_numpy\\_fmt\(\)](#) (*ArrayFormat static method*), 637  
[get\\_default\\_reach\\_dtype\(\)](#) (*ModflowSfr2 static method*), 478  
[get\\_default\\_segment\\_dtype\(\)](#) (*ModflowSfr2 static method*), 478  
[get\\_default\\_spd\\_dtype\(\)](#) (*Mnw static method*), 441  
[get\\_default\\_spd\\_dtype\(\)](#) (*ModflowMnw2 static method*), 445  
[get\\_delr\\_delc\(\)](#) (*Lgr method*), 601  
[get\\_destination\\_endpoint\\_data\(\)](#) (*EndpointFile method*), 609  
[get\\_destination\\_pathline\\_data\(\)](#) (*PathlineFile method*), 611  
[get\\_destination\\_timeseries\\_data\(\)](#) (*Timeseries-File method*), 613  
[get\\_disu\(\)](#) (*Gridgen method*), 592  
[get\\_disu5\\_gridprops\(\)](#) (*VoronoiGrid method*), 654  
[get\\_disu6\\_gridprops\(\)](#) (*VoronoiGrid method*), 654  
[get\\_disv\\_gridprops\(\)](#) (*in module flopy.utils.cvfdutil*), 574  
[get\\_disv\\_gridprops\(\)](#) (*VoronoiGrid method*), 654  
[get\\_dtype\(\)](#) (*Header method*), 576  
[get\\_dtypes\(\)](#) (*StartingLocationsFile static method*), 564  
[get\\_edge\\_cells\(\)](#) (*Triangle method*), 634  
[get\\_empty\(\)](#) (*MfList method*), 649  
[get\\_empty\(\)](#) (*ModflowAg static method*), 386  
[get\\_empty\(\)](#) (*ModflowChd static method*), 393  
[get\\_empty\(\)](#) (*ModflowDrn static method*), 402  
[get\\_empty\(\)](#) (*ModflowDrt static method*), 404  
[get\\_empty\(\)](#) (*ModflowFhb static method*), 408  
[get\\_empty\(\)](#) (*ModflowGage static method*), 412  
[get\\_empty\(\)](#) (*ModflowGhb static method*), 414  
[get\\_empty\(\)](#) (*ModflowHfb static method*), 419  
[get\\_empty\(\)](#) (*ModflowHyd static method*), 424  
[get\\_empty\(\)](#) (*ModflowRiv static method*), 472  
[get\\_empty\(\)](#) (*ModflowStr static method*), 487  
[get\\_empty\(\)](#) (*ModflowWel static method*), 509  
[get\\_empty\\_node\\_data\(\)](#) (*ModflowMnw2 static method*), 445  
[get\\_empty\\_reach\\_data\(\)](#) (*ModflowSfr2 static method*), 478  
[get\\_empty\\_segment\\_data\(\)](#) (*ModflowSfr2 static method*), 478  
[get\\_empty\\_starting\\_locations\\_data\(\)](#) (*StartingLocationsFile static method*), 564  
[get\\_empty\\_stress\\_period\\_data\(\)](#) (*Mnw static method*), 441  
[get\\_empty\\_stress\\_period\\_data\(\)](#) (*ModflowMnw1 static method*), 436  
[get\\_empty\\_stress\\_period\\_data\(\)](#) (*ModflowMnw2 static method*), 445  
[get\\_exchange\\_data\(\)](#) (*Lgr method*), 601  
[get\\_exchange\\_file\(\)](#) (*MFSimulation method*), 129  
[get\\_ext\\_dict\\_attr\(\)](#) (*BaseModel method*), 376  
[get\\_extended\\_budget\(\)](#) (*in module flopy.utils.postprocessing*), 621  
[get\\_extent\(\)](#) (*PlotCrossSection method*), 663  
[get\\_extent\(\)](#) (*StructuredSpatialReference method*), 351  
[get\\_extent\(\)](#) (*VertexSpatialReference method*), 353  
[get\\_external\\_cr\(\)](#) (*Util2d method*), 643  
[get\\_fahl\(\)](#) (*Gridgen method*), 593  
[get\\_file\\_entry\(\)](#) (*MfArray method*), 355  
[get\\_file\\_entry\(\)](#) (*MfList method*), 362  
[get\\_file\\_entry\(\)](#) (*MfScalar method*), 369  
[get\\_file\\_entry\(\)](#) (*MfScalarTransient method*), 370  
[get\\_file\\_entry\(\)](#) (*MfTransientArray method*), 359  
[get\\_file\\_entry\(\)](#) (*MfTransientList method*), 366  
[get\\_file\\_entry\(\)](#) (*Util2d method*), 643  
[get\\_file\\_entry\(\)](#) (*Util2dTpl method*), 701  
[get\\_file\\_entry\(\)](#) (*Util3d method*), 646  
[get\\_file\\_path\(\)](#) (*MFPackage method*), 126  
[get\\_filename\(\)](#) (*MfList method*), 649  
[get\\_filenames\(\)](#) (*MfList method*), 649  
[get\\_final\\_totim\(\)](#) (*ModflowDis method*), 398  
[get\\_fldr\(\)](#) (*Gridgen method*), 593  
[get\\_gnc\\_file\(\)](#) (*MFSimulation method*), 130  
[get\\_gradients\(\)](#) (*in module flopy.utils.postprocessing*), 621  
[get\\_grid\\_line\\_collection\(\)](#) (*PlotCrossSection method*), 663  
[get\\_grid\\_lines\(\)](#) (*StructuredSpatialReference method*), 351



get\_grid\_patch\_collection() (*PlotCrossSection method*), 664  
 get\_grid\_type() (*MFSimulation method*), 117  
 get\_gridprops\_disu5() (*Gridgen method*), 593  
 get\_gridprops\_disu6() (*Gridgen method*), 593  
 get\_gridprops\_disv() (*Gridgen method*), 593  
 get\_gridprops\_unstructuredgrid() (*Gridgen method*), 593  
 get\_gridprops\_unstructuredgrid() (*VoronoiGrid method*), 654  
 get\_gridprops\_vertexgrid() (*Gridgen method*), 594  
 get\_gridprops\_vertexgrid() (*VoronoiGrid method*), 654  
 get\_headfile\_precision() (in module *floppy.utils.binaryfile*), 571  
 get\_hvva() (*Gridgen method*), 594  
 get\_ia\_from\_iac() (in module *floppy.utils.gridgen*), 597  
 get\_iac() (*Gridgen method*), 594  
 get\_idomain() (*Lgr method*), 601  
 get\_ifrefm() (*Modflow method*), 384  
 get\_ifrefm() (*Seawat method*), 542  
 get\_ihc() (*Gridgen method*), 594  
 get\_ims\_package() (*MFSimulation method*), 118  
 get\_ims\_package() (*MFSimulation method*), 130  
 get\_incremental() (*ListBudget method*), 604  
 get\_indices() (*CellBudgetFile method*), 567  
 get\_indices() (*MfList method*), 649  
 get\_internal\_cr() (*Util2d method*), 643  
 get\_isym() (in module *floppy.utils.gridgen*), 597  
 get\_item2\_names() (*Mnw static method*), 441  
 get\_itmp() (*MfList method*), 649  
 get\_ivc() (*Gridgen method*), 594  
 get\_ja() (*Gridgen method*), 594  
 get\_kper\_entry() (*Transient2d method*), 639  
 get\_kper\_entry() (*Transient2dTpl method*), 700  
 get\_kper\_entry() (*Transient3d method*), 641  
 get\_kstp\_kper\_toffset() (*ModflowDis method*), 398  
 get\_kstpkper() (*CellBudgetFile method*), 567  
 get\_kstpkper() (*LayerFile method*), 577  
 get\_kstpkper() (*ListBudget method*), 604  
 get\_kswrkstp\_kper() (*SwrFile method*), 630  
 get\_lak\_connections() (in module *floppy.mf6.utils.lakpak\_utils*), 354  
 get\_layer() (in module *floppy.modflow.mfdis*), 400  
 get\_layer() (*ModflowDis method*), 398  
 get\_layer\_node\_range() (*UnstructuredGrid method*), 714  
 get\_local\_coords() (*Grid method*), 705  
 get\_longnames\_from\_docstrings() (*NetCdf method*), 684  
 get\_lower\_left() (*Lgr method*), 601  
 get\_lrc() (*ModflowDis method*), 398  
 get\_lrc() (*StructuredGrid method*), 709  
 get\_maxid() (*EndpointFile method*), 609  
 get\_maxid() (*PathlineFile method*), 611  
 get\_maxid() (*TimeseriesFile method*), 613  
 get\_maxtime() (*EndpointFile method*), 609  
 get\_maxtime() (*PathlineFile method*), 611  
 get\_maxtime() (*TimeseriesFile method*), 613  
 get\_maxtraveltime() (*EndpointFile method*), 609  
 get\_model() (*MFSimulation method*), 130  
 get\_model\_path() (*MFFileMgmt method*), 110  
 get\_model\_runtime() (*ListBudget method*), 604  
 get\_model\_shape() (*ZoneBudget method*), 658  
 get\_module\_val() (*PackageContainer static method*), 111  
 get\_mvr\_file() (*MFSimulation method*), 130  
 get\_mvt\_file() (*MFSimulation method*), 130  
 get\_name\_file\_entries() (*BaseModel method*), 376  
 get\_names() (*Header method*), 576  
 get\_neighbors() (*check method*), 573  
 get\_next\_line() (in module *floppy.utils.floppy\_io*), 582  
 get\_nlay() (*Gridgen method*), 595  
 get\_nnodes() (*Mnw static method*), 441  
 get\_nobs() (*Observations method*), 348  
 get\_nobs() (*ObsFiles method*), 617  
 get\_nod\_rearray() (*Gridgen method*), 595  
 get\_node() (*ModflowDis method*), 399  
 get\_node() (*StructuredGrid method*), 709  
 get\_node\_coordinates() (*ModflowDis method*), 399  
 get\_nodelay() (*Gridgen method*), 595  
 get\_nodes() (*Gridgen method*), 595  
 get\_nrecords() (*CellBudgetFile method*), 567  
 get\_nrecords() (*Observations method*), 348  
 get\_nrecords() (*SwrFile method*), 630  
 get\_nrow\_ncol\_nlay\_nper() (*Modflow method*), 384  
 get\_nrow\_ncol\_nlay\_nper() (*Mt3dms method*), 512  
 get\_nrow\_ncol\_nlay\_nper() (*Seawat method*), 542  
 get\_nstrm() (*SfrFile static method*), 628  
 get\_ntimes() (*Observations method*), 348  
 get\_ntimes() (*ObsFiles method*), 617  
 get\_ntimes() (*SwrFile method*), 630  
 get\_number\_plottable\_layers() (*Grid method*), 705  
 get\_number\_plottable\_layers() (*StructuredGrid method*), 709  
 get\_number\_plottable\_layers() (*UnstructuredGrid method*), 714  
 get\_number\_plottable\_layers() (*VertexGrid method*), 717  
 get\_obs\_data() (*Observations method*), 348  
 get\_obsnames() (*ObsFiles method*), 617  
 get\_ocoutput\_units() (*ModflowOc static method*), 454  
 get\_open\_file\_object() (in module *floppy.utils.utils\_def*), 652  
 get\_openclose\_cr() (*Util2d method*), 643  
 get\_outlets() (*ModflowSfr2 method*), 478

- get\_output() (*BaseModel* method), 376  
 get\_output\_attribute() (*BaseModel* method), 376  
 get\_package() (*BaseModel* method), 376  
 get\_package() (*PackageContainer* method), 111  
 get\_package\_list() (*ModelInterface* method), 379  
 get\_pak\_vals\_shape() (in module *flopY.utils.utils\_def*), 652  
 get\_parent\_connections() (*Lgr* method), 601  
 get\_parent\_indices() (*Lgr* method), 601  
 get\_patch() (*Polygon* method), 587  
 get\_patch\_collection() (*VoronoiGrid* method), 654  
 get\_plottable\_layer\_array() (*Grid* method), 705  
 get\_plottable\_layer\_array() (*StructuredGrid* method), 709  
 get\_plottable\_layer\_array() (*UnstructuredGrid* method), 714  
 get\_plottable\_layer\_array() (*VertexGrid* method), 717  
 get\_plottable\_layer\_shape() (*Grid* method), 705  
 get\_plottable\_layer\_shape() (*UnstructuredGrid* method), 714  
 get\_polygon\_area() (in module *flopY.utils.geometry*), 588  
 get\_polygon\_centroid() (in module *flopY.utils.geometry*), 588  
 get\_position() (*CellBudgetFile* method), 567  
 get\_pyshp\_field\_dtypes() (in module *flopY.export.shapefile\_utils*), 686  
 get\_pyshp\_field\_info() (in module *flopY.export.shapefile\_utils*), 686  
 get\_rc\_from\_node\_coordinates() (*ModflowDis* method), 399  
 get\_record() (*CellBudgetFile* method), 567  
 get\_record\_names() (*ListBudget* method), 605  
 get\_record\_names() (*SwrFile* method), 631  
 get\_record\_names() (*ZoneBudget* method), 658  
 get\_reduced\_pumping() (in module *flopY.utils.observationfile*), 618  
 get\_reduced\_pumping() (*ListBudget* method), 605  
 get\_replicated\_parent\_array() (*Lgr* method), 601  
 get\_residual() (*CellBudgetFile* method), 568  
 get\_residuals() (in module *flopY.mf6.utils.postprocessing*), 349  
 get\_results() (*SfrFile* method), 628  
 get\_sciencebase\_metadata() (*acdd* method), 681  
 get\_sciencebase\_xml\_metadata() (*acdd* method), 681  
 get\_selection() (in module *flopY.utils.observationfile*), 618  
 get\_shape() (*Lgr* method), 601  
 get\_sim\_path() (*MFFileMgmt* method), 110  
 get\_slopes() (*ModflowSfr2* method), 478  
 get\_sorted\_vertices() (in module *flopY.utils.voronoi*), 655  
 get\_spatialreference() (*CRS* static method), 685  
 get\_specific\_discharge() (in module *flopY.utils.postprocessing*), 622  
 get\_steadystate\_list() (*MFModel* method), 118  
 get\_structured\_faceflows() (in module *flopY.mf6.utils.postprocessing*), 349  
 get\_template\_array() (in module *flopY.pest.tplarray*), 701  
 get\_times() (*CellBudgetFile* method), 568  
 get\_times() (*LayerFile* method), 577  
 get\_times() (*ListBudget* method), 605  
 get\_times() (*Observations* method), 348  
 get\_times() (*ObsFiles* method), 617  
 get\_times() (*SfrFile* method), 628  
 get\_times() (*SwrFile* method), 631  
 get\_top() (*Gridgen* method), 595  
 get\_top\_botm() (*Lgr* method), 601  
 get\_total\_size() (*MultiList* method), 580  
 get\_totim() (*ModflowDis* method), 399  
 get\_totim\_from\_kper\_toffset() (*ModflowDis* method), 399  
 get\_transient\_key() (*MFBBlockHeader* method), 124  
 get\_transmissivities() (in module *flopY.utils.postprocessing*), 622  
 get\_ts() (*BinaryLayerFile* method), 565  
 get\_ts() (*CellBudgetFile* method), 568  
 get\_ts() (*FormattedLayerFile* method), 585  
 get\_ts() (*HeadUFile* method), 570  
 get\_ts() (*SwrFile* method), 631  
 get\_ts\_sp() (in module *flopY.utils.flopY\_io*), 582  
 get\_unique\_package\_names() (*CellBudgetFile* method), 569  
 get\_unique\_record\_names() (*CellBudgetFile* method), 569  
 get\_unitnumber\_from\_ext\_unit\_dict() (in module *flopY.utils.utils\_def*), 652  
 get\_updated\_path() (*MFFileMgmt* method), 110  
 get\_upsegs() (*ModflowSfr2* method), 478  
 get\_url\_text() (in module *flopY.utils.flopY\_io*), 582  
 get\_util2d\_shape\_for\_layer() (in module *flopY.utils.utils\_def*), 652  
 get\_valid\_faces() (in module *flopY.utils.voronoi*), 655  
 get\_value() (*Util2d* method), 643  
 get\_value() (*Util3d* method), 646  
 get\_values() (*Header* method), 576  
 get\_variable\_by\_stress\_period() (*ModflowSfr2* method), 479  
 get\_version() (in module *flopY.utils.utl\_import*), 653  
 get\_vertices() (*Gridgen* method), 595  
 get\_vertices() (*StructuredSpatialReference* method), 351  
 get\_vertices() (*Triangle* method), 634  
 get\_verts\_iverts() (*Gridgen* method), 595  
 get\_volumetric\_budget() (*ZoneBudget* method), 658

- get\_volumetric\_budget() (*ZoneBudget6 method*), 661  
 get\_water\_table() (in module *flop.util.postprocessing*), 623  
 get\_xcellcenters\_for\_layer() (*Grid method*), 705  
 get\_xcellcenters\_for\_layer() (*UnstructuredGrid method*), 714  
 get\_xcellcenters\_for\_layer() (*VertexGrid method*), 717  
 get\_xcenter\_array() (*StructuredSpatialReference method*), 351  
 get\_xcyc() (*Triangle method*), 634  
 get\_xedge\_array() (*StructuredSpatialReference method*), 351  
 get\_xvertices\_for\_layer() (*Grid method*), 705  
 get\_xvertices\_for\_layer() (*UnstructuredGrid method*), 714  
 get\_xvertices\_for\_layer() (*VertexGrid method*), 717  
 get\_ycellcenters\_for\_layer() (*Grid method*), 705  
 get\_ycellcenters\_for\_layer() (*UnstructuredGrid method*), 715  
 get\_ycellcenters\_for\_layer() (*VertexGrid method*), 717  
 get\_ycenter\_array() (*StructuredSpatialReference method*), 351  
 get\_yedge\_array() (*StructuredSpatialReference method*), 351  
 get\_yvertices\_for\_layer() (*Grid method*), 705  
 get\_yvertices\_for\_layer() (*UnstructuredGrid method*), 715  
 get\_yvertices\_for\_layer() (*VertexGrid method*), 717  
 get\_zero\_2d() (*Transient2d method*), 639  
 get\_zero\_3d() (*Transient3d method*), 641  
 getbotm() (*ModflowDis method*), 400  
 getfiletypeunit() (in module *flop.util.mfreadnam*), 607  
 getkeys() (*MFObservationRequester static method*), 347  
 getkeys() (*MFOutputRequester static method*), 343  
 getmf() (*Modpath6 method*), 561  
 getprj() (*CRS static method*), 685  
 getproj4() (*CRS static method*), 685  
 getsim() (*Modpath6 method*), 561  
 gettop() (*ModflowDis method*), 400  
 gnc\_filerecord (*ModflowGwfgwf attribute*), 199  
 gncdata (*ModflowGnc attribute*), 139  
 gncdata (*ModflowGwfgnc attribute*), 194  
 graph (*ModflowSfr2 property*), 479  
 graph\_legend() (*styles class method*), 679  
 graph\_legend\_title() (*styles class method*), 679  
 Grid (*class in flop.discretization.grid*), 701  
 grid\_lines (*Grid property*), 705  
 grid\_lines (*StructuredGrid property*), 709  
 grid\_lines (*UnstructuredGrid property*), 715  
 grid\_lines (*VertexGrid property*), 717  
 grid\_mapping\_attri (CRS property), 686  
 grid\_type (*Grid attribute*), 702  
 grid\_type (*Grid property*), 705  
 grid\_type (*MfGrdFile property*), 345  
 grid\_varies\_by\_layer (*UnstructuredGrid property*), 715  
 gridarray\_to\_flopyusg\_gridarray() (*Gridgen static method*), 595  
 Gridgen (*class in flop.util.gridgen*), 590  
 GridIntersect (*class in flop.util.gridintersect*), 597  
 gridlist\_to\_disv\_gridprops() (in module *flop.util.cvfutil*), 574  
 gridlist\_to\_verts() (in module *flop.util.cvfutil*), 575
- ## H
- has\_data() (*MFArrary method*), 355  
 has\_data() (*MFList method*), 362  
 has\_data() (*MFSscalar method*), 369  
 has\_data() (*MFSscalarTransient method*), 371  
 has\_data() (*MFTransientArray method*), 359  
 has\_data() (*MFTransientList method*), 366  
 has\_one\_item() (*PyListUtil static method*), 581  
 has\_package() (*BaseModel method*), 376  
 has\_stress\_period\_data (*PackageInterface property*), 383  
 has\_z (*LineString attribute*), 586  
 has\_z (*Point attribute*), 587  
 hdry (*BaseModel property*), 376  
 hdry (*MFModel property*), 118  
 hdry (*ModelInterface property*), 379  
 hdry (*Modpath7 property*), 550  
 head\_filerecord (*ModflowGwfmaw attribute*), 221  
 head\_filerecord (*ModflowGwfoc attribute*), 233  
 Header (*class in flop.util.datafile*), 576  
 header\_exists() (*MFBLOCK method*), 123  
 HeadFile (*class in flop.util.binaryfile*), 569  
 heading (*ModflowBas attribute*), 388  
 heading (*ModflowDis attribute*), 397  
 heading (*Modpath6Bas attribute*), 562  
 heading (*Modpath6Sim attribute*), 563  
 heading() (*styles class method*), 679  
 HeadObservation (*class in flop.modflow.mfhob*), 420  
 headprintrecord (*ModflowGwfoc attribute*), 233  
 HeadUFile (*class in flop.util.binaryfile*), 570  
 histogram() (*Raster method*), 624  
 hnoflo (*BaseModel property*), 376  
 hnoflo (*MFModel property*), 118  
 hnoflo (*ModelInterface property*), 379  
 hnoflo (*Modpath7 property*), 550  
 how (*Util2d attribute*), 642



how (*Util2d* property), 643  
 hwva (*ModflowGwfdisu* attribute), 176  
 hwva (*ModflowGwtdisu* attribute), 276  
 HydmodObs (*class in flop.py.utils.observationfile*), 615

## I

ia (*MfGrdFile* property), 345  
 ia (*UnstructuredGrid* property), 715  
 iac (*ModflowGwfdisu* attribute), 176  
 iac (*ModflowGwtdisu* attribute), 276  
 iavert (*MfGrdFile* property), 345  
 icelltype (*ModflowGwfnpf* attribute), 230  
 iconvert (*ModflowGwfsto* attribute), 253  
 idomain (*Grid* attribute), 702  
 idomain (*Grid* property), 705  
 idomain (*MfGrdFile* property), 345  
 idomain (*ModflowGwfdisu* attribute), 172  
 idomain (*ModflowGwfdisu* attribute), 176  
 idomain (*ModflowGwfdisu* attribute), 179  
 idomain (*ModflowGwtdisu* attribute), 271  
 idomain (*ModflowGwtdisu* attribute), 276  
 idomain (*ModflowGwtdisu* attribute), 279  
 ievt (*ModflowGwfevta* attribute), 189  
 ifrefm (*ModflowBas* attribute), 388  
 ifrefm (*ModflowBas* property), 389  
 ignore\_shapely\_warnings\_for\_object\_array() (*in module flop.py.utils.gridintersect*), 600  
 ihc (*ModflowGwfdisu* attribute), 176  
 ihc (*ModflowGwtdisu* attribute), 276  
 import\_optional\_dependency() (*in module flop.py.utils.utl\_import*), 653  
 in\_shape() (*MultiList* method), 580  
 inc\_shape\_idx() (*MultiList* method), 580  
 increment\_dimension() (*MultiList* method), 580  
 indent\_string (*MFSimulationData* attribute), 134  
 indexes() (*MultiList* method), 580  
 initialize() (*UtlatsPackages* method), 325, 326  
 initialize() (*UtlaktabPackages* method), 327  
 initialize() (*UtlobsPackages* method), 329  
 initialize() (*UtlstftabPackages* method), 330, 331  
 initialize() (*UtlspcaPackages* method), 334  
 initialize() (*UtlspcPackages* method), 332  
 initialize() (*UtlstasPackages* method), 336  
 initialize() (*UtltsPackages* method), 338  
 initialize() (*UtltkPackages* method), 340  
 initialize() (*UtltsPackages* method), 342  
 initialize\_file() (*NetCdf* method), 684  
 initialize\_geometry() (*NetCdf* method), 684  
 initialize\_group() (*NetCdf* method), 684  
 input\_keys() (*SimulationDict* method), 136  
 inspect\_cells() (*MFSimulationData* method), 118  
 inspect\_cells() (*MFPackage* method), 126  
 INT16 (*Raster* attribute), 623  
 INT32 (*Raster* attribute), 623

INT64 (*Raster* attribute), 623  
 INT8 (*Raster* attribute), 623  
 integer() (*ArrayFormat* class method), 637  
 internal\_formatting (*MFSimulationData* attribute), 134  
 interpolate() (*StructuredSpatialReference* method), 351  
 interpolation\_methodrecord (*ModflowUtlts* attribute), 335  
 interpolation\_methodrecord (*ModflowUtlts* attribute), 337  
 interpolation\_methodrecord\_single (*ModflowUtlts* attribute), 337  
 intersect() (*Grid* method), 703, 705  
 intersect() (*Gridgen* method), 595  
 intersect() (*GridIntersect* method), 597  
 intersect() (*StructuredGrid* method), 709  
 intersect() (*UnstructuredGrid* method), 715  
 intersect() (*VertexGrid* method), 717  
 intersect\_modpath\_with\_crosssection() (*in module flop.py.plot.plotutil*), 675  
 intersects() (*GridIntersect* method), 598  
 InvalidVersion, 620  
 irch (*ModflowGwfrcha* attribute), 239  
 irregular\_shape\_patch() (*UnstructuredPlotUtilities* static method), 674  
 is\_allowed() (*MFBBlock* method), 123  
 is\_basic\_type() (*DatumUtil* static method), 579  
 is\_clockwise() (*in module flop.py.utils.geometry*), 588  
 is\_complete (*Grid* property), 705  
 is\_complete (*StructuredGrid* property), 710  
 is\_complete (*UnstructuredGrid* property), 715  
 is\_complete (*VertexGrid* property), 718  
 is\_devrelease (*LegacyVersion* property), 620  
 is\_devrelease (*Version* property), 620  
 is\_empty() (*MFBBlock* method), 123  
 is\_empty\_list() (*PyListUtil* static method), 581  
 is\_float() (*DatumUtil* static method), 579  
 is\_float() (*in module flop.py.utils.formattedfile*), 586  
 is\_int() (*DatumUtil* static method), 579  
 is\_int() (*in module flop.py.utils.formattedfile*), 586  
 is\_iterable() (*PyListUtil* static method), 581  
 is\_postrelease (*LegacyVersion* property), 620  
 is\_postrelease (*Version* property), 620  
 is\_prerelease (*LegacyVersion* property), 620  
 is\_prerelease (*Version* property), 620  
 is\_rectilinear (*StructuredGrid* property), 710  
 is\_regular (*StructuredGrid* property), 710  
 is\_regular\_x (*StructuredGrid* property), 710  
 is\_regular\_xy (*StructuredGrid* property), 710  
 is\_regular\_xz (*StructuredGrid* property), 710  
 is\_regular\_y (*StructuredGrid* property), 710  
 is\_regular\_yz (*StructuredGrid* property), 710  
 is\_regular\_z (*StructuredGrid* property), 710

`is_same_header()` (*MFBlockHeader* method), 124  
`is_symmetrical()` (in module *flopy.utils.gridgen*), 597  
`is_valid` (*Grid* property), 705  
`is_valid` (*StructuredGrid* property), 710  
`is_valid` (*UnstructuredGrid* property), 715  
`is_valid` (*VertexGrid* property), 718  
`is_valid()` (*MFBlock* method), 123  
`is_valid()` (*MFModel* method), 118  
`is_valid()` (*MFPackage* method), 126  
`is_valid()` (*MFSimulation* method), 130  
`isabs()` (*MFFilePath* method), 111  
`isBetween()` (in module *flopy.utils.cvfutil*), 575  
`isfloat()` (*OptionUtil* static method), 619  
`isint()` (*OptionUtil* static method), 619  
`isvalid()` (check method), 573  
`isvalid()` (*ListBudget* method), 605  
`isvalid()` (*OptionUtil* static method), 619  
`items` (*Logger* attribute), 682  
`ItmpError`, 436  
`itmuni_text` (*TemporalReference* attribute), 627  
`itmuni_values` (*TemporalReference* attribute), 627  
`itype_dict()` (*Mt3dSsm* static method), 537  
`iverts` (*Grid* property), 705  
`iverts` (*MfGrdFile* property), 345  
`iverts` (*StructuredGrid* property), 710  
`iverts` (*UnstructuredGrid* property), 715  
`iverts` (*VertexGrid* property), 718

## J

`ja` (*MfGrdFile* property), 345  
`ja` (*ModflowGwfdisu* attribute), 176  
`ja` (*ModflowGwtDisu* attribute), 276  
`ja` (*UnstructuredGrid* property), 715  
`javert` (*MfGrdFile* property), 345  
`join_struct_arrays()` (in module *flopy.utils.binaryfile*), 572

## K

`k` (*ModflowGwfnpf* attribute), 230  
`k22` (*ModflowGwfnpf* attribute), 230  
`k33` (*ModflowGwfnpf* attribute), 230  
`keys()` (*SimulationDict* method), 136  
`kij_from_nn0()` (*ModflowGridIndices* static method), 599  
`kij_from_nodenummer()` (*ModflowGridIndices* static method), 600  
`kijnames` (*EndpointFile* attribute), 609  
`kijnames` (*PathlineFile* attribute), 612  
`kijnames` (*TimeseriesFile* attribute), 614

## L

`label_cells()` (*Triangle* method), 634  
`label_vertices()` (*Triangle* method), 635  
`lakeperioddata` (*ModflowGwtlkt* attribute), 296

`laycbd` (*BaseModel* property), 377  
`laycbd` (*Grid* property), 705  
`laycbd` (*MFModel* property), 119  
`laycbd` (*ModelInterface* property), 379  
`LayerFile` (class in *flopy.utils.datafile*), 576  
`laytyp` (*BaseModel* property), 377  
`laytyp` (*MFModel* property), 119  
`laytyp` (*ModelInterface* property), 380  
`laytyp` (*Modpath7* property), 550  
`LegacyVersion` (class in *flopy.utils.parse\_version*), 620  
`len_const` (*ModflowSfr2* attribute), 479  
`lenuni` (*Grid* attribute), 702  
`lenuni` (*Grid* property), 705  
`level1_arraylist()` (*Package* method), 381  
`Lgr` (class in *flopy.utils.lgrutil*), 601  
`line_intersect_grid()` (*UnstructuredPlotUtilities* static method), 674  
`line_num` (*PyListUtil* attribute), 581  
`line_parse()` (in module *flopy.utils.flopy\_io*), 582  
`line_strip()` (in module *flopy.utils.flopy\_io*), 582  
`LineString` (class in *flopy.utils.geometry*), 586  
`list_files()` (in module *flopy.mf6.utils.generate\_classes*), 373  
`list_records()` (*CellBudgetFile* method), 569  
`list_records()` (*LayerFile* method), 577  
`list_records()` (*Observations* method), 348  
`list_unique_packages()` (*CellBudgetFile* method), 569  
`list_unique_records()` (*CellBudgetFile* method), 569  
`ListBudget` (class in *flopy.utils.mflistfile*), 602  
`load()` (*MFArrary* method), 356  
`load()` (*MFBlock* method), 123  
`load()` (*MFList* method), 362  
`load()` (*MFPackage* method), 127  
`load()` (*MFScalar* method), 369  
`load()` (*MFScalarTransient* method), 371  
`load()` (*MFSimulation* class method), 130  
`load()` (*MFTransientArray* method), 359  
`load()` (*MFTransientList* method), 366  
`load()` (*Modflow* class method), 384  
`load()` (*ModflowAg* class method), 387  
`load()` (*ModflowBas* class method), 389  
`load()` (*ModflowBcf* class method), 391  
`load()` (*ModflowChd* class method), 393  
`load()` (*ModflowDe4* class method), 395  
`load()` (*ModflowDis* class method), 400  
`load()` (*ModflowDrn* class method), 402  
`load()` (*ModflowDrt* class method), 404  
`load()` (*ModflowEvt* class method), 406  
`load()` (*ModflowFhb* class method), 408  
`load()` (*ModflowFlwob* class method), 411  
`load()` (*ModflowGage* class method), 412  
`load()` (*ModflowGhb* class method), 414  
`load()` (*ModflowGmg* class method), 417

[load\(\)](#) (*ModflowGwf class method*), 154  
[load\(\)](#) (*ModflowGwt class method*), 156  
[load\(\)](#) (*ModflowHfb class method*), 419  
[load\(\)](#) (*ModflowHob class method*), 422  
[load\(\)](#) (*ModflowHyd class method*), 424  
[load\(\)](#) (*ModflowLak class method*), 428  
[load\(\)](#) (*ModflowLmt class method*), 430  
[load\(\)](#) (*ModflowLpf class method*), 433  
[load\(\)](#) (*ModflowMlt class method*), 434  
[load\(\)](#) (*ModflowMnw1 class method*), 436  
[load\(\)](#) (*ModflowMnw2 class method*), 445  
[load\(\)](#) (*ModflowMnwi class method*), 447  
[load\(\)](#) (*ModflowNwt class method*), 450  
[load\(\)](#) (*ModflowOc class method*), 454  
[load\(\)](#) (*ModflowPar static method*), 456  
[load\(\)](#) (*ModflowParBc class method*), 458  
[load\(\)](#) (*ModflowPcg class method*), 461  
[load\(\)](#) (*ModflowPcgn class method*), 464  
[load\(\)](#) (*ModflowPks class method*), 465  
[load\(\)](#) (*ModflowPval class method*), 467  
[load\(\)](#) (*ModflowRch class method*), 469  
[load\(\)](#) (*ModflowRiv class method*), 472  
[load\(\)](#) (*ModflowSfr2 class method*), 479  
[load\(\)](#) (*ModflowSip class method*), 482  
[load\(\)](#) (*ModflowSor class method*), 483  
[load\(\)](#) (*ModflowStr class method*), 487  
[load\(\)](#) (*ModflowSub class method*), 491  
[load\(\)](#) (*ModflowSwi2 class method*), 494  
[load\(\)](#) (*ModflowSwr1 class method*), 495  
[load\(\)](#) (*ModflowSwt class method*), 499  
[load\(\)](#) (*ModflowUpw class method*), 502  
[load\(\)](#) (*ModflowUzf1 class method*), 507  
[load\(\)](#) (*ModflowWel class method*), 509  
[load\(\)](#) (*ModflowZon class method*), 510  
[load\(\)](#) (*Mt3dAdv class method*), 516  
[load\(\)](#) (*Mt3dBt1 class method*), 519  
[load\(\)](#) (*Mt3dCts class method*), 522  
[load\(\)](#) (*Mt3dDsp class method*), 524  
[load\(\)](#) (*Mt3dGcg class method*), 525  
[load\(\)](#) (*Mt3dLkt class method*), 527  
[load\(\)](#) (*Mt3dms class method*), 512  
[load\(\)](#) (*Mt3dRct class method*), 531  
[load\(\)](#) (*Mt3dSft class method*), 534  
[load\(\)](#) (*Mt3dSsm class method*), 537  
[load\(\)](#) (*Mt3dUzt class method*), 540  
[load\(\)](#) (*Package static method*), 381  
[load\(\)](#) (*Raster static method*), 624  
[load\(\)](#) (*Seawat class method*), 542  
[load\(\)](#) (*SeawatVdf class method*), 545  
[load\(\)](#) (*SeawatVsc class method*), 548  
[load\(\)](#) (*Util2d class method*), 643  
[load\(\)](#) (*Util3d class method*), 646  
[load\(\)](#) (*ZoneBudget6 static method*), 661  
[load\(\)](#) (*ZoneFile6 static method*), 662

[load\\_base\(\)](#) (*MFModel class method*), 119  
[load\\_bin\(\)](#) (*Util2d static method*), 643  
[load\\_block\(\)](#) (*Util2d static method*), 643  
[load\\_coord\\_info\(\)](#) (*Grid method*), 705  
[load\\_mas\(\)](#) (*Mt3dms static method*), 513  
[load\\_obs\(\)](#) (*Mt3dms static method*), 513  
[load\\_options\(\)](#) (*OptionBlock class method*), 618  
[load\\_package\(\)](#) (*MFModel method*), 119  
[load\\_package\(\)](#) (*MFSimulation method*), 131  
[load\\_results\(\)](#) (*BaseModel method*), 377  
[load\\_results\(\)](#) (*Modflow method*), 385  
[load\\_results\(\)](#) (*Mt3dms method*), 513  
[load\\_txt\(\)](#) (*Util2d static method*), 644  
[loadarray\(\)](#) (*ModflowParBc static method*), 459  
[loadtxt\(\)](#) (*in module flopy.utils.flopy\_io*), 582  
[local](#) (*LegacyVersion property*), 620  
[local](#) (*Version property*), 620  
[log\(\)](#) (*Logger method*), 682  
[Logger](#) (*class in flopy.export.netcdf*), 682  
[LRCParticleData](#) (*class in flopy.modpath.mp7particledata*), 553

## M

[major](#) (*Version property*), 620  
[make\\_layered\(\)](#) (*MFArrary method*), 356  
[make\\_mnw\\_objects\(\)](#) (*ModflowMnw2 method*), 446  
[make\\_node\\_data\(\)](#) (*Mnw method*), 442  
[make\\_node\\_data\(\)](#) (*ModflowMnw2 method*), 446  
[make\\_stress\\_period\\_data\(\)](#) (*ModflowMnw2 method*), 446  
[map\\_polygons](#) (*Grid property*), 705  
[map\\_polygons](#) (*StructuredGrid property*), 710  
[map\\_polygons](#) (*UnstructuredGrid property*), 715  
[map\\_polygons](#) (*VertexGrid property*), 718  
[masked4d\\_array\\_to\\_kper\\_dict\(\)](#) (*Transient2d static method*), 639  
[masked4D\\_arrays\\_to\\_stress\\_period\\_data\(\)](#) (*MfList static method*), 649  
[masked\\_4D\\_arrays](#) (*MfList property*), 650  
[masked\\_4D\\_arrays](#) (*MFTransientList property*), 366  
[masked\\_4D\\_arrays\\_itr\(\)](#) (*MfList method*), 650  
[masked\\_4D\\_arrays\\_itr\(\)](#) (*MFTransientList method*), 366  
[match\\_array\\_cells\(\)](#) (*MFModel method*), 120  
[max\\_columns\\_of\\_data](#) (*MFSimulationData attribute*), 135  
[max\\_columns\\_of\\_data](#) (*MFSimulationData property*), 135  
[max\\_multi\\_dim\\_list\\_size\(\)](#) (*PyListUtil static method*), 581  
[max\\_tuple\\_abs\\_size\(\)](#) (*in module flopy.utils.datautil*), 582  
[mcomp](#) (*Mt3dms property*), 513  
[mcomp](#) (*Seawat property*), 542



- methods() (*MF6Output* method), 348  
 mf (*Modpath6* property), 561  
 mf6check (*class* in *flopy.utils.check*), 574  
 Mf6ListBudget (*class* in *flopy.utils.mf6listfile*), 606  
 Mf6Obs (*class* in *flopy.utils.observationfile*), 615  
 MF6Output (*class* in *flopy.mf6.utils.output\_util*), 348  
 mfaddoutsidefile (*class* in *flopy.modflow.mfaddoutsidefile*), 385  
 MFArray (*class* in *flopy.mf6.data.mfdataarray*), 355  
 MFBlock (*class* in *flopy.mf6.mfpackage*), 122  
 MFBlockHeader (*class* in *flopy.mf6.mfpackage*), 124  
 MFChildPackages (*class* in *flopy.mf6.mfpackage*), 125  
 mfddata (*MFSimulationData* attribute), 135  
 MFDDataException, 109  
 MFFileMgmt (*class* in *flopy.mf6.mfbase*), 110  
 MFFilePath (*class* in *flopy.mf6.mfbase*), 111  
 MfGrdFile (*class* in *flopy.mf6.utils.binarygrid\_util*), 344  
 MFInvalidTransientBlockHeaderException, 111  
 MFList (*class* in *flopy.mf6.data.mfdatalist*), 361  
 MfList (*class* in *flopy.utils.util\_list*), 648  
 mflist\_export() (*in module* *flopy.export.utils*), 691  
 MfListBudget (*class* in *flopy.utils.mf6listfile*), 606  
 MFModel (*class* in *flopy.mf6.mfmodel*), 116  
 MFMultipleList (*class* in *flopy.mf6.data.mfdatalist*), 364  
 MFObservation (*class* in *flopy.mf6.utils.mfobservation*), 347  
 MFObservationRequester (*class* in *flopy.mf6.utils.mfobservation*), 347  
 MFOutput (*class* in *flopy.mf6.utils.binaryfile\_utils*), 343  
 MFOutputRequester (*class* in *flopy.mf6.utils.binaryfile\_utils*), 343  
 MFPackage (*class* in *flopy.mf6.mfpackage*), 125  
 mfpath (*MFSimulationData* attribute), 135  
 MFScalar (*class* in *flopy.mf6.data.mfdatascalar*), 368  
 MFScalarTransient (*class* in *flopy.mf6.data.mfdatascalar*), 370  
 MFSimulation (*class* in *flopy.mf6.modflow.mfsimulation*), 128  
 MFSimulationData (*class* in *flopy.mf6.modflow.mfsimulation*), 134  
 MFTransientArray (*class* in *flopy.mf6.data.mfdataarray*), 358  
 MFTransientList (*class* in *flopy.mf6.data.mfdatalist*), 365  
 MfusgListBudget (*class* in *flopy.utils.mf6listfile*), 606  
 mg (*MfList* property), 650  
 micro (*Version* property), 620  
 minor (*Version* property), 620  
 Mnw (*class* in *flopy.modflow.mfmnw2*), 436  
 model (*MfList* property), 650  
 model (*PackageContainerType* attribute), 116  
 model (*Transient2d* property), 639  
 model (*Transient3d* property), 641  
 model (*Util2d* property), 644  
 model (*Util3d* property), 647  
 model\_attributes\_to\_shapefile() (*in module* *flopy.export.shapefile\_utils*), 686  
 model\_dict (*MFSimulation* property), 131  
 model\_dimensions (*MFSimulationData* attribute), 135  
 model\_export() (*in module* *flopy.export.utils*), 692  
 model\_factory() (*PackageContainer* static method), 111  
 model\_file\_path (*Util2d* property), 644  
 model\_level (*PackageLevel* attribute), 372  
 model\_names (*MFSimulation* property), 132  
 model\_relative\_path (*MFFileMgmt* attribute), 110  
 model\_time\_units (*TemporalReference* property), 627  
 model\_type (*ModflowGwf* attribute), 154  
 model\_type (*ModflowGwt* attribute), 156  
 model\_ws (*BaseModel* property), 377  
 model\_ws (*MFModel* property), 120  
 model\_ws (*ModelInterface* property), 380  
 modeldiscrit (*MFModel* property), 120  
 modelgrid (*BaseModel* property), 377  
 modelgrid (*MfGrdFile* property), 345  
 modelgrid (*MFModel* property), 120  
 modelgrid (*ModelInterface* property), 380  
 modelgrid (*Modflow* property), 385  
 modelgrid (*Mt3dms* property), 513  
 modelgrid (*Seawat* property), 542  
 ModelInterface (*class* in *flopy.mbase*), 379  
 models (*ModflowNam* attribute), 151  
 models\_by\_type (*PackageContainer* attribute), 112  
 modeltime (*BaseModel* property), 377  
 ModelTime (*class* in *flopy.discretization.modeltime*), 707  
 modeltime (*MFModel* property), 120  
 modeltime (*Modflow* property), 385  
 modeltime (*Mt3dms* property), 513  
 modeltime (*Seawat* property), 542  
 Modflow (*class* in *flopy.modflow.mf*), 383  
 modflow\_models (*PackageContainer* attribute), 112  
 modflow\_packages (*PackageContainer* attribute), 112  
 ModflowAg (*class* in *flopy.modflow.mfag*), 386  
 ModflowBas (*class* in *flopy.modflow.mfbas*), 387  
 ModflowBcf (*class* in *flopy.modflow.mfbcf*), 389  
 ModflowBct (*class* in *flopy.modflow.mfbct*), 391  
 ModflowChd (*class* in *flopy.modflow.mfchd*), 392  
 ModflowDe4 (*class* in *flopy.modflow.mfde4*), 394  
 ModflowDis (*class* in *flopy.modflow.mfdis*), 396  
 ModflowDrn (*class* in *flopy.modflow.mfdrn*), 401  
 ModflowDrt (*class* in *flopy.modflow.mfdrt*), 403  
 ModflowEvt (*class* in *flopy.modflow.mfevt*), 405  
 ModflowFhb (*class* in *flopy.modflow.mffhb*), 407  
 ModflowFlwob (*class* in *flopy.modflow.mfflwob*), 409  
 ModflowGage (*class* in *flopy.modflow.mfgage*), 411  
 ModflowGhb (*class* in *flopy.modflow.mfghb*), 413  
 ModflowGlobal (*class* in *flopy.modflow.mf*), 385

- ModflowGmg (class in *flopy.modflow.mfgmg*), 415  
 ModflowGnc (class in *flopy.mf6.modflow.mfgnc*), 137  
 ModflowGridIndices (class in *flopy.utils.gridintersect*), 599  
 ModflowGwf (class in *flopy.mf6.modflow.mfgwf*), 153  
 ModflowGwfapi (class in *flopy.mf6.modflow.mfgwfapi*), 156  
 ModflowGwfbuy (class in *flopy.mf6.modflow.mfgwfbuy*), 158  
 ModflowGwfchd (class in *flopy.mf6.modflow.mfgwfchd*), 160  
 ModflowGwfcsb (class in *flopy.mf6.modflow.mfgwfcsb*), 163  
 ModflowGwfdis (class in *flopy.mf6.modflow.mfgwfdis*), 170  
 ModflowGwfdisu (class in *flopy.mf6.modflow.mfgwfdisu*), 172  
 ModflowGwfdisv (class in *flopy.mf6.modflow.mfgwfdisv*), 177  
 ModflowGwfdrn (class in *flopy.mf6.modflow.mfgwfdrn*), 180  
 ModflowGwfevt (class in *flopy.mf6.modflow.mfgwfevt*), 183  
 ModflowGwfevta (class in *flopy.mf6.modflow.mfgwfevta*), 187  
 ModflowGwfgbh (class in *flopy.mf6.modflow.mfgwfgbh*), 190  
 ModflowGwfgnc (class in *flopy.mf6.modflow.mfgwfgnc*), 193  
 ModflowGwfgwf (class in *flopy.mf6.modflow.mfgwfgwf*), 195  
 ModflowGwfgwt (class in *flopy.mf6.modflow.mfgwfgwt*), 200  
 ModflowGwfhfb (class in *flopy.mf6.modflow.mfgwfhfb*), 200  
 ModflowGwfic (class in *flopy.mf6.modflow.mfgwfic*), 202  
 ModflowGwflak (class in *flopy.mf6.modflow.mfgwflak*), 202  
 ModflowGwfmaw (class in *flopy.mf6.modflow.mfgwfmaw*), 212  
 ModflowGwfmvr (class in *flopy.mf6.modflow.mfgwfmvr*), 221  
 ModflowGwfnam (class in *flopy.mf6.modflow.mfgwfnam*), 224  
 ModflowGwfnpf (class in *flopy.mf6.modflow.mfgwfnpf*), 225  
 ModflowGwfoc (class in *flopy.mf6.modflow.mfgwfoc*), 231  
 ModflowGwfrch (class in *flopy.mf6.modflow.mfgwfrch*), 234  
 ModflowGwfrcha (class in *flopy.mf6.modflow.mfgwfrcha*), 237  
 ModflowGwfriv (class in *flopy.mf6.modflow.mfgwfriv*), 239  
 ModflowGwfsfr (class in *flopy.mf6.modflow.mfgwfsfr*), 243  
 ModflowGwfsto (class in *flopy.mf6.modflow.mfgwfsto*), 252  
 ModflowGwfufz (class in *flopy.mf6.modflow.mfgwfufz*), 254  
 ModflowGwfwel (class in *flopy.mf6.modflow.mfgwfwel*), 261  
 ModflowGwt (class in *flopy.mf6.modflow.mfgwt*), 155  
 ModflowGwtadv (class in *flopy.mf6.modflow.mfgwtadv*), 265  
 ModflowGwtapi (class in *flopy.mf6.modflow.mfgwtapi*), 265  
 ModflowGwtcnc (class in *flopy.mf6.modflow.mfgwtcnc*), 267  
 ModflowGwtdis (class in *flopy.mf6.modflow.mfgwtdis*), 270  
 ModflowGwtdisu (class in *flopy.mf6.modflow.mfgwtdisu*), 272  
 ModflowGwtdisv (class in *flopy.mf6.modflow.mfgwtdisv*), 277  
 ModflowGwt dsp (class in *flopy.mf6.modflow.mfgwt dsp*), 280  
 ModflowGwtfmi (class in *flopy.mf6.modflow.mfgwtfmi*), 282  
 ModflowGwtgwt (class in *flopy.mf6.modflow.mfgwtgwt*), 283  
 ModflowGwtic (class in *flopy.mf6.modflow.mfgwtic*), 287  
 ModflowGwtist (class in *flopy.mf6.modflow.mfgwtist*), 287  
 ModflowGwtlkt (class in *flopy.mf6.modflow.mfgwtlkt*), 291  
 ModflowGwtmst (class in *flopy.mf6.modflow.mfgwtmst*), 296  
 ModflowGwtmvt (class in *flopy.mf6.modflow.mfgwtmvt*), 298  
 ModflowGwtmwt (class in *flopy.mf6.modflow.mfgwtmwt*), 299  
 ModflowGwt nam (class in *flopy.mf6.modflow.mfgwt nam*), 304  
 ModflowGwtoc (class in *flopy.mf6.modflow.mfgwtoc*), 305  
 ModflowGwtsft (class in *flopy.mf6.modflow.mfgwtsft*), 309  
 ModflowGwtsrc (class in *flopy.mf6.modflow.mfgwtsrc*), 314  
 ModflowGwtssm (class in *flopy.mf6.modflow.mfgwtssm*), 316  
 ModflowGwtuizt (class in *flopy.mf6.modflow.mfgwtuizt*), 318  
 ModflowHfb (class in *flopy.modflow.mfhfb*), 418  
 ModflowHob (class in *flopy.modflow.mfhob*), 421  
 ModflowHyd (class in *flopy.modflow.mfhyd*), 423  
 ModflowIms (class in *flopy.mf6.modflow.mfims*), 139

- ModflowLak (class in *flopy.modflow.mflak*), 424  
ModflowList (class in *flopy.modflow.mf*), 385  
ModflowLmt (class in *flopy.modflow.mflmt*), 429  
ModflowLpf (class in *flopy.modflow.mflpf*), 430  
ModflowMlt (class in *flopy.modflow.mfmlt*), 433  
ModflowMnw1 (class in *flopy.modflow.mfmnw1*), 435  
ModflowMnw2 (class in *flopy.modflow.mfmnw2*), 442  
ModflowMnwi (class in *flopy.modflow.mfmnwi*), 446  
ModflowMvr (class in *flopy.mf6.modflow.mfmvr*), 147  
ModflowNam (class in *flopy.mf6.modflow.mfnam*), 150  
ModflowNwt (class in *flopy.modflow.mfnwt*), 448  
ModflowOc (class in *flopy.modflow.mfoc*), 451  
ModflowPar (class in *flopy.modflow.mfpar*), 456  
ModflowParBc (class in *flopy.modflow.mfparbc*), 458  
ModflowPbc (class in *flopy.modflow.mfpbc*), 459  
ModflowPcg (class in *flopy.modflow.mfpccg*), 460  
ModflowPcgn (class in *flopy.modflow.mfpccgn*), 461  
ModflowPks (class in *flopy.modflow.mfpks*), 464  
ModflowPval (class in *flopy.modflow.mfpval*), 466  
ModflowRch (class in *flopy.modflow.mfrch*), 467  
ModflowRiv (class in *flopy.modflow.mfriv*), 470  
ModflowSfr2 (class in *flopy.modflow.mfsfr2*), 473  
ModflowSip (class in *flopy.modflow.mfsip*), 481  
ModflowSor (class in *flopy.modflow.mfsor*), 482  
ModflowStr (class in *flopy.modflow.mfstr*), 484  
ModflowSub (class in *flopy.modflow.mfsub*), 488  
ModflowSwi2 (class in *flopy.modflow.mfswi2*), 492  
ModflowSwr1 (class in *flopy.modflow.mfswr1*), 495  
ModflowSwt (class in *flopy.modflow.mfswt*), 496  
ModflowTdis (class in *flopy.mf6.modflow.mftdis*), 152  
ModflowUpw (class in *flopy.modflow.mfupw*), 500  
ModflowUtlats (class in *flopy.mf6.modflow.mfutlats*), 324  
ModflowUtlaktab (class in *flopy.mf6.modflow.mfutlaktab*), 326  
ModflowUtlobs (class in *flopy.mf6.modflow.mfutlobs*), 327  
ModflowUtlstrtab (class in *flopy.mf6.modflow.mfutlstrtab*), 329  
ModflowUtlspc (class in *flopy.mf6.modflow.mfutlspc*), 331  
ModflowUtlspca (class in *flopy.mf6.modflow.mfutlspca*), 333  
ModflowUtltas (class in *flopy.mf6.modflow.mfutltas*), 334  
ModflowUtlts (class in *flopy.mf6.modflow.mfutlts*), 336  
ModflowUtltvk (class in *flopy.mf6.modflow.mfutltvk*), 338  
ModflowUtltvts (class in *flopy.mf6.modflow.mfutltvts*), 341  
ModflowUzf1 (class in *flopy.modflow.mfuzf1*), 502  
ModflowWel (class in *flopy.modflow.mfwel*), 508  
ModflowZon (class in *flopy.modflow.mfzon*), 510  
Modpath6 (class in *flopy.modpath.mp6*), 560  
Modpath6Bas (class in *flopy.modpath.mp6bas*), 562  
Modpath6List (class in *flopy.modpath.mp6*), 562  
Modpath6Sim (class in *flopy.modpath.mp6sim*), 563  
Modpath7 (class in *flopy.modpath.mp7*), 549  
Modpath7Bas (class in *flopy.modpath.mp7bas*), 551  
Modpath7List (class in *flopy.modpath.mp7*), 550  
Modpath7Sim (class in *flopy.modpath.mp7sim*), 557  
module  
    flopy.discretization.grid, 701  
    flopy.discretization.modeltime, 707  
    flopy.discretization.structuredgrid, 707  
    flopy.discretization.unstructuredgrid, 712  
    flopy.discretization.vertexgrid, 716  
    flopy.export.longnames, 681  
    flopy.export.metadata, 681  
    flopy.export.netcdf, 682  
    flopy.export.shapefile\_utils, 685  
    flopy.export.unitsformat, 688  
    flopy.export.utils, 688  
    flopy.export.vtk, 693  
    flopy.mbase, 374  
    flopy.mf6.data.mfdataarray, 355  
    flopy.mf6.data.mfdatalist, 361  
    flopy.mf6.data.mfdatascalar, 368  
    flopy.mf6.mbase, 109  
    flopy.mf6.mfmodel, 116  
    flopy.mf6.mfpackage, 122  
    flopy.mf6.modflow.mfgnc, 137  
    flopy.mf6.modflow.mfgwf, 153  
    flopy.mf6.modflow.mfgwfapi, 156  
    flopy.mf6.modflow.mfgwfbuy, 158  
    flopy.mf6.modflow.mfgwfhcd, 160  
    flopy.mf6.modflow.mfgwfcsub, 163  
    flopy.mf6.modflow.mfgwfdis, 170  
    flopy.mf6.modflow.mfgwfdisu, 172  
    flopy.mf6.modflow.mfgwfdisv, 177  
    flopy.mf6.modflow.mfgwfdrn, 180  
    flopy.mf6.modflow.mfgwfevt, 183  
    flopy.mf6.modflow.mfgwfevta, 187  
    flopy.mf6.modflow.mfgwfggb, 190  
    flopy.mf6.modflow.mfgwfgnc, 193  
    flopy.mf6.modflow.mfgwfgwf, 195  
    flopy.mf6.modflow.mfgwfgwt, 200  
    flopy.mf6.modflow.mfgwfhfb, 200  
    flopy.mf6.modflow.mfgwfic, 202  
    flopy.mf6.modflow.mfgwflak, 202  
    flopy.mf6.modflow.mfgwfmaw, 212  
    flopy.mf6.modflow.mfgwfmvr, 221  
    flopy.mf6.modflow.mfgwfnam, 224  
    flopy.mf6.modflow.mfgwfnpf, 225  
    flopy.mf6.modflow.mfgwfoc, 231  
    flopy.mf6.modflow.mfgwfrch, 234  
    flopy.mf6.modflow.mfgwfrcha, 237

flopy.mf6.modflow.mfgwfriv, 239  
 flopy.mf6.modflow.mfgwfsfr, 243  
 flopy.mf6.modflow.mfgwfsto, 252  
 flopy.mf6.modflow.mfgwfufz, 254  
 flopy.mf6.modflow.mfgwfwel, 261  
 flopy.mf6.modflow.mfgwt, 155  
 flopy.mf6.modflow.mfgwtadv, 265  
 flopy.mf6.modflow.mfgwtapi, 265  
 flopy.mf6.modflow.mfgwtcnc, 267  
 flopy.mf6.modflow.mfgwtdis, 270  
 flopy.mf6.modflow.mfgwtdisu, 272  
 flopy.mf6.modflow.mfgwtdisv, 277  
 flopy.mf6.modflow.mfgwt dsp, 280  
 flopy.mf6.modflow.mfgwtfmi, 282  
 flopy.mf6.modflow.mfgwtgwt, 283  
 flopy.mf6.modflow.mfgwtic, 287  
 flopy.mf6.modflow.mfgwtist, 287  
 flopy.mf6.modflow.mfgwtlkt, 291  
 flopy.mf6.modflow.mfgwtmst, 296  
 flopy.mf6.modflow.mfgwtmvt, 298  
 flopy.mf6.modflow.mfgwtmw, 299  
 flopy.mf6.modflow.mfgwtmnam, 304  
 flopy.mf6.modflow.mfgwtoc, 305  
 flopy.mf6.modflow.mfgwtsft, 309  
 flopy.mf6.modflow.mfgwtsrc, 314  
 flopy.mf6.modflow.mfgwtssm, 316  
 flopy.mf6.modflow.mfgwtuzt, 318  
 flopy.mf6.modflow.mfims, 139  
 flopy.mf6.modflow.mfmvr, 147  
 flopy.mf6.modflow.mfnam, 150  
 flopy.mf6.modflow.mfsimulation, 128  
 flopy.mf6.modflow.mftdis, 152  
 flopy.mf6.modflow.mfutlats, 324  
 flopy.mf6.modflow.mfutllaktab, 326  
 flopy.mf6.modflow.mfutlobs, 327  
 flopy.mf6.modflow.mfutlsfrtab, 329  
 flopy.mf6.modflow.mfutlspc, 331  
 flopy.mf6.modflow.mfutlspca, 333  
 flopy.mf6.modflow.mfutltas, 334  
 flopy.mf6.modflow.mfutlts, 336  
 flopy.mf6.modflow.mfutltvk, 338  
 flopy.mf6.modflow.mfutltvs, 341  
 flopy.mf6.utils.binaryfile\_utils, 343  
 flopy.mf6.utils.binarygrid\_util, 344  
 flopy.mf6.utils.createpackages, 372  
 flopy.mf6.utils.generate\_classes, 373  
 flopy.mf6.utils.lakpak\_utils, 354  
 flopy.mf6.utils.mfobservation, 347  
 flopy.mf6.utils.output\_util, 348  
 flopy.mf6.utils.postprocessing, 349  
 flopy.mf6.utils.reference, 350  
 flopy.modflow.mf, 383  
 flopy.modflow.mfaddoutsidefile, 385  
 flopy.modflow.mfag, 386  
 flopy.modflow.mfbas, 387  
 flopy.modflow.mfbcf, 389  
 flopy.modflow.mfbct, 391  
 flopy.modflow.mfchd, 392  
 flopy.modflow.mfde4, 394  
 flopy.modflow.mfdis, 396  
 flopy.modflow.mfdrn, 401  
 flopy.modflow.mfdrt, 403  
 flopy.modflow.mfevt, 405  
 flopy.modflow.mffhb, 407  
 flopy.modflow.mfflwob, 409  
 flopy.modflow.mfgage, 411  
 flopy.modflow.mfghb, 413  
 flopy.modflow.mfgmg, 415  
 flopy.modflow.mfhfb, 418  
 flopy.modflow.mfhob, 420  
 flopy.modflow.mfhyd, 423  
 flopy.modflow.mflak, 424  
 flopy.modflow.mflmt, 429  
 flopy.modflow.mflpf, 430  
 flopy.modflow.mfm1t, 433  
 flopy.modflow.mfmnw1, 435  
 flopy.modflow.mfmnw2, 436  
 flopy.modflow.mfmnwi, 446  
 flopy.modflow.mfnwt, 448  
 flopy.modflow.mfoc, 451  
 flopy.modflow.mfpar, 456  
 flopy.modflow.mfparbc, 458  
 flopy.modflow.mfpbc, 459  
 flopy.modflow.mfpcg, 460  
 flopy.modflow.mfpcgn, 461  
 flopy.modflow.mfpks, 464  
 flopy.modflow.mfpval, 466  
 flopy.modflow.mfrch, 467  
 flopy.modflow.mfriv, 470  
 flopy.modflow.mfsfr2, 473  
 flopy.modflow.mfsip, 481  
 flopy.modflow.mfsor, 482  
 flopy.modflow.mfstr, 484  
 flopy.modflow.mfsub, 488  
 flopy.modflow.mfswi2, 492  
 flopy.modflow.mfswr1, 495  
 flopy.modflow.mfswt, 496  
 flopy.modflow.mfupw, 500  
 flopy.modflow.mfufz1, 502  
 flopy.modflow.mfwel, 508  
 flopy.modflow.mfzon, 510  
 flopy.modpath.mp6, 560  
 flopy.modpath.mp6bas, 562  
 flopy.modpath.mp6sim, 563  
 flopy.modpath.mp7, 549  
 flopy.modpath.mp7bas, 551  
 flopy.modpath.mp7particledata, 551  
 flopy.modpath.mp7particlegroup, 555



flop.modpath.mp7sim, 557  
flop.mt3d.mt, 511  
flop.mt3d.mtadv, 514  
flop.mt3d.mtbtn, 517  
flop.mt3d.mtcts, 520  
flop.mt3d.mtdsp, 522  
flop.mt3d.mtgcg, 524  
flop.mt3d.mtlkt, 526  
flop.mt3d.mtphc, 528  
flop.mt3d.mtrct, 528  
flop.mt3d.mtsft, 532  
flop.mt3d.mtssm, 536  
flop.mt3d.mttob, 538  
flop.mt3d.mtuzt, 539  
flop.pakbase, 381  
flop.pest.params, 699  
flop.pest.templatewriter, 700  
flop.pest.tplarray, 700  
flop.plot.crossection, 663  
flop.plot.map, 668  
flop.plot.plotutil, 673  
flop.plot.styles, 678  
flop.seawat.swt, 541  
flop.seawat.swtvdf, 543  
flop.seawat.swtvsc, 546  
flop.utils.binaryfile, 565  
flop.utils.check, 572  
flop.utils.cvfdutil, 574  
flop.utils.datafile, 576  
flop.utils.datautil, 579  
flop.utils.flop\_io, 582  
flop.utils.formattedfile, 584  
flop.utils.geometry, 586  
flop.utils.geospatial\_utils, 589  
flop.utils.gridgen, 590  
flop.utils.gridintersect, 597  
flop.utils.lgrutil, 601  
flop.utils.mflistfile, 602  
flop.utils.mfreadnam, 606  
flop.utils.modpathfile, 608  
flop.utils.mtlistfile, 614  
flop.utils.observationfile, 615  
flop.utils.optionblock, 618  
flop.utils.parse\_version, 620  
flop.utils.postprocessing, 621  
flop.utils.rasters, 623  
flop.utils.reccarray\_utils, 626  
flop.utils.reference, 627  
flop.utils.sfrouputfile, 627  
flop.utils.swrouputfile, 629  
flop.utils.triangle, 633  
flop.utils.util\_array, 636  
flop.utils.util\_list, 648  
flop.utils.utils\_def, 652  
flop.utils.utl\_import, 653  
flop.utils.voronoi, 654  
flop.utils.zonbud, 656  
Mt3dAdv (class in flop.mt3d.mtadv), 514  
Mt3dBtn (class in flop.mt3d.mtbtn), 517  
Mt3dCts (class in flop.mt3d.mtcts), 520  
Mt3dDsp (class in flop.mt3d.mtdsp), 522  
Mt3dGcg (class in flop.mt3d.mtgcg), 524  
Mt3dList (class in flop.mt3d.mt), 511  
Mt3dLkt (class in flop.mt3d.mtlkt), 526  
Mt3dms (class in flop.mt3d.mt), 511  
Mt3dPhc (class in flop.mt3d.mtphc), 528  
Mt3dRct (class in flop.mt3d.mtrct), 528  
Mt3dSft (class in flop.mt3d.mtsft), 532  
Mt3dSsm (class in flop.mt3d.mtssm), 536  
Mt3dTob (class in flop.mt3d.mttob), 538  
Mt3dUzt (class in flop.mt3d.mtuzt), 539  
MtListBudget (class in flop.utils.mtlistfile), 614  
mult\_function() (ModflowMlt static method), 434  
multi\_line\_strip() (in module flop.utils.flop\_io), 583  
MultiLineString (class in flop.utils.geometry), 586  
MultiList (class in flop.utils.datautil), 579  
MultiListIter (class in flop.utils.datautil), 580  
MultiPoint (class in flop.utils.geometry), 587  
MultiPolygon (class in flop.utils.geometry), 587  
mvr\_filerecord (ModflowGwfgwf attribute), 200  
mvt\_filerecord (ModflowGwtgwt attribute), 286  
mwtperioddata (ModflowGwtmwt attribute), 304  
mxact (MfList attribute), 648  
mxact (MfList property), 650  
mxactc (ModflowChd attribute), 393  
mxactr (ModflowRiv attribute), 471  
mxactw (ModflowWel attribute), 509

## N

n\_nested (OptionBlock attribute), 619  
NamData (class in flop.utils.mfreadnam), 606  
name (BaseModel property), 377  
name (MFBlockHeader attribute), 124  
name (MfList property), 650  
name (MFModel attribute), 116  
name (MFPackage property), 127  
name (Package property), 381  
name (PackageInterface property), 383  
name (Transient2d property), 639  
name (Transient3d property), 641  
name (Util2d property), 644  
name (Util3d property), 647  
name\_file (MFSimulation attribute), 129  
namefile (BaseModel property), 377  
namefile (MFModel property), 120  
namefile (ModelInterface property), 380  
NameIter (class in flop.utils.datautil), 580



- ncells (*MfGrdFile* property), 345
  - ncells (*ZoneFile6* property), 662
  - ncol (*MfGrdFile* property), 346
  - ncol (*Modflow* property), 385
  - ncol (*Mt3dms* property), 513
  - ncol (*Seawat* property), 542
  - ncol (*StructuredGrid* property), 710
  - ncol (*StructuredSpatialReference* property), 352
  - ncomp (*Mt3dms* property), 513
  - ncomp (*Seawat* property), 542
  - ncpl (*Grid* property), 705
  - ncpl (*MfGrdFile* property), 346
  - ncpl (*Modflow* property), 385
  - ncpl (*StructuredGrid* property), 710
  - ncpl (*UnstructuredGrid* property), 715
  - ncpl (*VertexGrid* property), 718
  - ncpl (*VertexSpatialReference* property), 353
  - ncpl\_from\_ihc() (*UnstructuredGrid* static method), 715
  - ndarray\_to\_asciigrid() (in module *flopY.utils.gridgen*), 597
  - nested (*OptionBlock* attribute), 619
  - NetCdf (class in *flopY.export.netcdf*), 682
  - new\_simulation() (*MFArrary* method), 356
  - new\_simulation() (*MFList* method), 362
  - new\_u2d() (in module *flopY.utils.util\_array*), 647
  - next\_ext\_unit() (*BaseModel* method), 377
  - next\_ext\_unit() (*Modpath6* method), 562
  - next\_item() (*PyListUtil* static method), 581
  - next\_list() (*PyListUtil* static method), 581
  - next\_unit() (*BaseModel* method), 377
  - nja (*MfGrdFile* property), 346
  - nlay (*MfGrdFile* property), 346
  - nlay (*Modflow* property), 385
  - nlay (*Mt3dms* property), 513
  - nlay (*Seawat* property), 543
  - nlay (*StructuredGrid* property), 710
  - nlay (*UnstructuredGrid* property), 716
  - nlay (*VertexGrid* property), 718
  - nn0\_from\_kij() (*ModflowGridIndices* static method), 600
  - nnodes (*Grid* property), 705
  - nnodes (*StructuredGrid* property), 710
  - nnodes (*UnstructuredGrid* property), 716
  - nnodes (*VertexGrid* property), 718
  - no (*budgetOpt* attribute), 559
  - no\_ptcrecord (*ModflowIms* attribute), 147
  - nobs (*CsvFile* property), 615
  - nodatavals (*Raster* property), 624
  - nodenumber\_from\_kij() (*ModflowGridIndices* static method), 600
  - NodeParticleData (class in *flopY.modpath.mp7particledata*), 553
  - nodes (*MfGrdFile* property), 346
  - normal (*VerbosityLevel* attribute), 116
  - normalize\_name() (*NetCdf* static method), 685
  - nper (*MFModel* property), 120
  - nper (*ModelTime* property), 707
  - nper (*Modflow* property), 385
  - nper (*ModflowSfr2* property), 479
  - nper (*Mt3dms* property), 513
  - nper (*Seawat* property), 543
  - npl (*ArrayFormat* attribute), 636
  - npl (*ArrayFormat* property), 637
  - nrow (*MfGrdFile* property), 346
  - nrow (*Modflow* property), 385
  - nrow (*Mt3dms* property), 513
  - nrow (*Seawat* property), 543
  - nrow (*StructuredGrid* property), 710
  - nrow (*StructuredSpatialReference* property), 352
  - nrow\_ncol\_nlay\_nper (*Modflow* property), 385
  - nrow\_ncol\_nlay\_nper (*Mt3dms* property), 513
  - nrow\_ncol\_nlay\_nper (*Seawat* property), 543
  - nsfrpar (*ModflowSfr2* attribute), 479
  - nss (*ModflowSfr2* property), 479
  - nstp (*ModelTime* property), 707
  - nstrm (*ModflowSfr2* property), 479
  - nth\_index() (*MultiList* method), 580
  - numbering() (*check* method), 480
  - numeric\_chars (*PyListUtil* attribute), 581
  - numpy (*ArrayFormat* attribute), 636
  - numpy (*ArrayFormat* property), 637
  - nuzgag (*ModflowUzf1* attribute), 507
  - nuzgag (*ModflowUzf1* property), 507
  - nvert (*Grid* property), 705
  - nvert (*StructuredGrid* property), 710
  - nvert (*UnstructuredGrid* property), 716
  - nvert (*VertexGrid* property), 718
- ## O
- obs\_filerecord (*ModflowGwfapi* attribute), 157
  - obs\_filerecord (*ModflowGwfchd* attribute), 162
  - obs\_filerecord (*ModflowGwfcsb* attribute), 170
  - obs\_filerecord (*ModflowGwfdn* attribute), 182
  - obs\_filerecord (*ModflowGwfevt* attribute), 186
  - obs\_filerecord (*ModflowGwfevta* attribute), 189
  - obs\_filerecord (*ModflowGwfgfb* attribute), 192
  - obs\_filerecord (*ModflowGwfgwf* attribute), 200
  - obs\_filerecord (*ModflowGwflak* attribute), 212
  - obs\_filerecord (*ModflowGwfmaw* attribute), 221
  - obs\_filerecord (*ModflowGwfrch* attribute), 236
  - obs\_filerecord (*ModflowGwfrcha* attribute), 239
  - obs\_filerecord (*ModflowGwfriv* attribute), 242
  - obs\_filerecord (*ModflowGwfsfr* attribute), 252
  - obs\_filerecord (*ModflowGwfufz* attribute), 261
  - obs\_filerecord (*ModflowGwfwel* attribute), 264
  - obs\_filerecord (*ModflowGwtapi* attribute), 267
  - obs\_filerecord (*ModflowGwtenc* attribute), 269

obs\_filerecord (*ModflowGwtgwt attribute*), 286  
obs\_filerecord (*ModflowGwtlkt attribute*), 296  
obs\_filerecord (*ModflowGwtmwt attribute*), 304  
obs\_filerecord (*ModflowGwtsft attribute*), 314  
obs\_filerecord (*ModflowGwtsrc attribute*), 316  
obs\_filerecord (*ModflowGwtuzt attribute*), 324  
obs\_names (*MF6Output property*), 348  
observation\_keys() (*SimulationDict method*), 136  
Observations (*class in flopy.mf6.utils.mfobservation*), 347  
ObsFiles (*class in flopy.utils.observationfile*), 616  
obsnames (*CsvFile property*), 615  
off (*onoffOpt attribute*), 559  
on (*onoffOpt attribute*), 559  
onoffOpt (*class in flopy.modpath.mp7sim*), 559  
open\_close\_formatting (*MFSimulationData attribute*), 135  
optional (*OptionBlock attribute*), 619  
OptionBlock (*class in flopy.utils.optionblock*), 618  
options (*ModflowBas attribute*), 388  
OptionUtil (*class in flopy.utils.optionblock*), 619  
outlets (*ModflowGwflak attribute*), 212  
outlets (*ModflowSfr2 attribute*), 476  
output (*MFModel property*), 120  
output (*MFPackage property*), 127  
output\_helper() (*in module flopy.export.utils*), 692  
output\_keys() (*SimulationDict method*), 136  
outsegs (*ModflowSfr2 attribute*), 476  
overlapping\_conductance() (*check method*), 480

## P

Package (*class in flopy.pakbase*), 381  
package (*MFList property*), 362  
package (*MfList property*), 650  
package (*NamData attribute*), 607  
package (*PackageContainerType attribute*), 116  
package\_abbr (*ModflowGnc attribute*), 139  
package\_abbr (*ModflowGwfapi attribute*), 157  
package\_abbr (*ModflowGwfbuy attribute*), 159  
package\_abbr (*ModflowGwfchd attribute*), 162  
package\_abbr (*ModflowGwfcsb attribute*), 170  
package\_abbr (*ModflowGwfdis attribute*), 172  
package\_abbr (*ModflowGwfdisu attribute*), 176  
package\_abbr (*ModflowGwfdisv attribute*), 179  
package\_abbr (*ModflowGwfdrn attribute*), 182  
package\_abbr (*ModflowGwfeyt attribute*), 186  
package\_abbr (*ModflowGwfeyta attribute*), 189  
package\_abbr (*ModflowGwfgfb attribute*), 192  
package\_abbr (*ModflowGwfgnc attribute*), 194  
package\_abbr (*ModflowGwfgwf attribute*), 200  
package\_abbr (*ModflowGwfgwt attribute*), 200  
package\_abbr (*ModflowGwfhfb attribute*), 202  
package\_abbr (*ModflowGwfic attribute*), 202  
package\_abbr (*ModflowGwflak attribute*), 212

package\_abbr (*ModflowGwfmaw attribute*), 221  
package\_abbr (*ModflowGwfmvr attribute*), 223  
package\_abbr (*ModflowGwfnam attribute*), 225  
package\_abbr (*ModflowGwfnpf attribute*), 230  
package\_abbr (*ModflowGwfoc attribute*), 233  
package\_abbr (*ModflowGwfrch attribute*), 236  
package\_abbr (*ModflowGwfrcha attribute*), 239  
package\_abbr (*ModflowGwfriv attribute*), 242  
package\_abbr (*ModflowGwfsfr attribute*), 252  
package\_abbr (*ModflowGwfsto attribute*), 254  
package\_abbr (*ModflowGwfufz attribute*), 261  
package\_abbr (*ModflowGwfwel attribute*), 264  
package\_abbr (*ModflowGwtadv attribute*), 265  
package\_abbr (*ModflowGwtapi attribute*), 267  
package\_abbr (*ModflowGwtcnc attribute*), 269  
package\_abbr (*ModflowGwtdis attribute*), 271  
package\_abbr (*ModflowGwtdisu attribute*), 276  
package\_abbr (*ModflowGwtdisv attribute*), 279  
package\_abbr (*ModflowGwt dsp attribute*), 281  
package\_abbr (*ModflowGwtfmi attribute*), 282  
package\_abbr (*ModflowGwtgwt attribute*), 286  
package\_abbr (*ModflowGwtic attribute*), 287  
package\_abbr (*ModflowGwtist attribute*), 290  
package\_abbr (*ModflowGwtlkt attribute*), 296  
package\_abbr (*ModflowGwtmst attribute*), 298  
package\_abbr (*ModflowGwtmvt attribute*), 299  
package\_abbr (*ModflowGwtmwt attribute*), 304  
package\_abbr (*ModflowGwt nam attribute*), 305  
package\_abbr (*ModflowGwtoc attribute*), 308  
package\_abbr (*ModflowGwtsft attribute*), 314  
package\_abbr (*ModflowGwtsrc attribute*), 316  
package\_abbr (*ModflowGwtssm attribute*), 318  
package\_abbr (*ModflowGwtuzt attribute*), 324  
package\_abbr (*ModflowIm s attribute*), 147  
package\_abbr (*ModflowMvr attribute*), 149  
package\_abbr (*ModflowNam attribute*), 151  
package\_abbr (*ModflowTdis attribute*), 153  
package\_abbr (*ModflowUtlats attribute*), 325  
package\_abbr (*ModflowUtlaktab attribute*), 327  
package\_abbr (*ModflowUtl obs attribute*), 329  
package\_abbr (*ModflowUtl sfrtab attribute*), 330  
package\_abbr (*ModflowUtl spc attribute*), 332  
package\_abbr (*ModflowUtl spca attribute*), 334  
package\_abbr (*ModflowUtl tas attribute*), 335  
package\_abbr (*ModflowUtl ts attribute*), 337  
package\_abbr (*ModflowUtl tvk attribute*), 340  
package\_abbr (*ModflowUtl tvs attribute*), 342  
package\_abbr (*UtlatsPackages attribute*), 326  
package\_abbr (*UtlaktabPackages attribute*), 327  
package\_abbr (*Utl obsPackages attribute*), 329  
package\_abbr (*Utl sfrtabPackages attribute*), 331  
package\_abbr (*Utl spcaPackages attribute*), 334  
package\_abbr (*Utl spcPackages attribute*), 332  
package\_abbr (*Utl tasPackages attribute*), 336

- `package_abbr` (*UtilsPackages* attribute), 338
- `package_abbr` (*UiltvkPackages* attribute), 340
- `package_abbr` (*UiltvsPackages* attribute), 343
- `package_check_levels` (*check* attribute), 573
- `package_convergence_filerecord` (*ModflowGwfc-sub* attribute), 170
- `package_convergence_filerecord` (*ModflowGwflak* attribute), 212
- `package_convergence_filerecord` (*ModflowGwfsfr* attribute), 252
- `package_convergence_filerecord` (*ModflowGwfufz* attribute), 261
- `package_dict` (*PackageContainer* property), 114
- `package_export()` (in module *flop.export.utils*), 692
- `package_factory()` (*PackageContainer* static method), 114
- `package_key_dict` (*PackageContainer* attribute), 111
- `package_list()` (*PackageContainer* static method), 114
- `package_name_dict` (*PackageContainer* attribute), 111
- `package_names` (*PackageContainer* property), 114
- `package_type` (*MFPackage* property), 127
- `package_type` (*Package* property), 381
- `package_type` (*PackageInterface* property), 383
- `package_type_dict` (*PackageContainer* attribute), 111
- PackageContainer* (class in *flop.mf6.mfbase*), 111
- PackageContainerType* (class in *flop.mf6.mfbase*), 116
- `packagedata` (*ModflowGwfbuy* attribute), 159
- `packagedata` (*ModflowGwfcsub* attribute), 170
- `packagedata` (*ModflowGwflak* attribute), 212
- `packagedata` (*ModflowGwfmaw* attribute), 221
- `packagedata` (*ModflowGwfsfr* attribute), 252
- `packagedata` (*ModflowGwfufz* attribute), 261
- `packagedata` (*ModflowGwtfmi* attribute), 283
- `packagedata` (*ModflowGwtlkt* attribute), 296
- `packagedata` (*ModflowGwtmw* attribute), 304
- `packagedata` (*ModflowGwtsft* attribute), 314
- `packagedata` (*ModflowGwtuzt* attribute), 324
- PackageInterface* (class in *flop.pakbase*), 382
- PackageLevel* (class in *flop.mf6.utils.createpackages*), 372
- `packagelist` (*BaseModel* property), 377
- `packagelist` (*MFModel* property), 120
- `packagelist` (*ModelInterface* property), 380
- PackageLoadException*, 380
- `packages` (*MFModel* attribute), 117
- `packages` (*ModflowGwfmvr* attribute), 224
- `packages` (*ModflowGwfnam* attribute), 225
- `packages` (*ModflowGwtmam* attribute), 305
- `packages` (*ModflowMvr* attribute), 149
- `packages_by_abbr` (*PackageContainer* attribute), 114
- `parameter_bcfill()` (*ModflowParBc* static method), 459
- `parameter_fill()` (*ModflowPar* static method), 456
- Params* (class in *flop.pest.params*), 699
- `parent` (*MFPackage* property), 127
- `parent` (*Package* property), 381
- `parent` (*PackageInterface* property), 383
- `parse()` (in module *flop.utils.parse\_version*), 620
- `parse()` (*MtListBudget* method), 614
- `parse_control_record()` (*Util2d* static method), 644
- `parse_modpath_selection_options()` (in module *flop.plot.plotutil*), 675
- `parse_shapely_ix_result()` (in module *flop.utils.gridintersect*), 600
- `parse_value()` (*Util2d* method), 644
- `parse_wkt()` (*CRS* method), 686
- `parsenamefile()` (in module *flop.utils.mfreadnam*), 607
- ParticleData* (class in *flop.modpath.mp7particledata*), 554
- ParticleGroup* (class in *flop.modpath.mp7particlegroup*), 555
- ParticleGroupLRCTemplate* (class in *flop.modpath.mp7particlegroup*), 556
- ParticleGroupNodeTemplate* (class in *flop.modpath.mp7particlegroup*), 556
- `pass_through` (*weakOpt* attribute), 560
- `patch` (*Polygon* property), 587
- `path` (*MFBBlock* attribute), 122
- `path` (*MFPackage* attribute), 125
- PathIter* (class in *flop.utils.datautil*), 580
- `pathline` (*simType* attribute), 559
- PathlineFile* (class in *flop.utils.modpathfile*), 610
- `paths` (*ModflowSfr2* property), 479
- `perioddata` (*ModflowGwflak* attribute), 212
- `perioddata` (*ModflowGwfmaw* attribute), 221
- `perioddata` (*ModflowGwfmvr* attribute), 224
- `perioddata` (*ModflowGwfsfr* attribute), 252
- `perioddata` (*ModflowGwfufz* attribute), 261
- `perioddata` (*ModflowMvr* attribute), 149
- `perioddata` (*ModflowTdis* attribute), 153
- `perioddata` (*ModflowUtlats* attribute), 325
- `perioddata` (*ModflowUtlspc* attribute), 332
- `perioddata` (*ModflowUtltk* attribute), 340
- `perioddata` (*ModflowUtlts* attribute), 342
- `perlen` (*ModelTime* property), 707
- `plot()` (*BaseModel* method), 377
- `plot()` (*Collection* method), 586
- `plot()` (*Gridgen* method), 596
- `plot()` (*LayerFile* method), 577
- `plot()` (*LineString* method), 586
- `plot()` (*MFArrary* method), 356
- `plot()` (*MFList* method), 362
- `plot()` (*MfList* method), 650
- `plot()` (*MFModel* method), 120
- `plot()` (*MFPackage* method), 127
- `plot()` (*MFScalar* method), 369



`plot()` (*MfScalarTransient* method), 371  
`plot()` (*MfSimulation* method), 132  
`plot()` (*MfTransientArray* method), 359  
`plot()` (*MfTransientList* method), 366  
`plot()` (*Package* method), 381  
`plot()` (*Point* method), 587  
`plot()` (*Polygon* method), 587  
`plot()` (*Raster* method), 624  
`plot()` (*StructuredGrid* method), 710  
`plot()` (*Transient2d* method), 639  
`plot()` (*Triangle* method), 635  
`plot()` (*UnstructuredGrid* method), 716  
`plot()` (*Util2d* method), 644  
`plot()` (*Util3d* method), 647  
`plot()` (*VertexGrid* method), 718  
`plot()` (*VoronoiGrid* method), 655  
`plot_array()` (*PlotCrossSection* method), 664  
`plot_array()` (*PlotMapView* method), 669  
`plot_bc()` (*PlotCrossSection* method), 664  
`plot_bc()` (*PlotMapView* method), 669  
`plot_boundary()` (*Triangle* method), 635  
`plot_centroids()` (*Triangle* method), 636  
`plot_cvfd()` (in module *flopy.plot.plotutil*), 675  
`plot_cvfd()` (*PlotMapView* method), 669  
`plot_endpoint()` (*PlotCrossSection* method), 665  
`plot_endpoint()` (*PlotMapView* method), 670  
`plot_fill_between()` (*PlotCrossSection* method), 665  
`plot_grid()` (*PlotCrossSection* method), 665  
`plot_grid()` (*PlotMapView* method), 670  
`plot_ibound()` (*PlotCrossSection* method), 665  
`plot_ibound()` (*PlotMapView* method), 670  
`plot_inactive()` (*PlotCrossSection* method), 665  
`plot_inactive()` (*PlotMapView* method), 670  
`plot_linestring()` (*GridIntersect* static method), 598  
`plot_path()` (*ModflowSfr2* method), 479  
`plot_pathline()` (*PlotCrossSection* method), 666  
`plot_pathline()` (*PlotMapView* method), 671  
`plot_point()` (*GridIntersect* static method), 598  
`plot_polygon()` (*GridIntersect* static method), 599  
`plot_shapefile()` (in module *flopy.plot.plotutil*), 676  
`plot_shapefile()` (*PlotMapView* method), 671  
`plot_shapes()` (*PlotMapView* method), 671  
`plot_surface()` (*PlotCrossSection* method), 666  
`plot_timeseries()` (*PlotCrossSection* method), 666  
`plot_timeseries()` (*PlotMapView* method), 671  
`plot_vector()` (*PlotCrossSection* method), 667  
`plot_vector()` (*PlotMapView* method), 672  
`plot_vertices()` (*Triangle* method), 636  
*PlotCrossSection* (class in *flopy.plot.crosssection*), 663  
*PlotMapView* (class in *flopy.plot.map*), 668  
`plottable` (*MfArray* property), 357  
`plottable` (*MfList* property), 363  
`plottable` (*MfList* property), 651  
`plottable` (*MfPackage* property), 127  
`plottable` (*MfScalar* property), 370  
`plottable` (*MfScalarTransient* property), 372  
`plottable` (*ModflowAg* property), 387  
`plottable` (*Package* property), 382  
`plottable` (*PackageInterface* property), 383  
`plottable` (*Transient2d* property), 640  
`plottable` (*Transient3d* property), 641  
`plottable` (*Util2d* property), 645  
`plottable` (*Util3d* property), 647  
*PlotUtilities* (class in *flopy.plot.plotutil*), 673  
*Point* (class in *flopy.utils.cvfdutil*), 574  
*Point* (class in *flopy.utils.geometry*), 587  
`point_in_cell()` (in module *flopy.utils.voronoi*), 655  
`point_in_polygon()` (in module *flopy.utils.geometry*), 588  
`points` (*GeoSpatialCollection* property), 589  
`points` (*GeoSpatialUtil* property), 590  
*Polygon* (class in *flopy.utils.geometry*), 587  
`polygons` (*PlotCrossSection* property), 667  
`pop_item()` (in module *flopy.utils.flopy\_io*), 583  
`porosity` (*ModflowGwtmst* attribute), 298  
`post` (*LegacyVersion* property), 620  
`post` (*Version* property), 620  
`pre` (*LegacyVersion* property), 620  
`pre` (*Version* property), 620  
`print_summary()` (*check* method), 573  
`printrecord` (*ModflowGwfoc* attribute), 233  
`printrecord` (*ModflowGwtoc* attribute), 308  
`prj` (*Grid* property), 705  
`proj4` (*CRS* property), 686  
`proj4` (*Grid* attribute), 702  
`proj4` (*Grid* property), 705  
`project_point_onto_xc_line()` (in module *flopy.utils.geometry*), 588  
`property_threshold_values` (*check* attribute), 573  
`public` (*LegacyVersion* property), 620  
`public` (*Version* property), 620  
*Pvd* (class in *flopy.export.vtk*), 693  
`py` (*ArrayFormat* attribute), 636  
`py` (*ArrayFormat* property), 637  
*PyListUtil* (class in *flopy.utils.datautil*), 580  
`pyshp_parts` (*LineString* property), 586  
`pyshp_parts` (*Point* property), 587  
`pyshp_parts` (*Polygon* property), 587  
`python_file_path` (*Util2d* property), 645

## Q

`query_grid()` (*GridIntersect* method), 599  
`quiet` (*VerbosityLevel* attribute), 116  
`quote_list` (*PyListUtil* attribute), 581  
`quoted_filename` (*MfPackage* property), 127

## R

[ra\\_slice\(\)](#) (in module `flop.utils.reccarray_utils`), 626  
[Raster](#) (class in `flop.utils.rasters`), 623  
[rate](#) (*ModflowGwfevt* attribute), 189  
[rcloserecord](#) (*ModflowIms* attribute), 147  
[reachperioddata](#) (*ModflowGwtsft* attribute), 314  
[readld\(\)](#) (in module `flop.utils.gridgen`), 597  
[readld\(\)](#) (in module `flop.utils.util_array`), 648  
[read\\_csv\(\)](#) (*CsvFile* static method), 615  
[read\\_fixed\\_var\(\)](#) (in module `flop.utils.flop_io`), 583  
[read\\_header\(\)](#) (*FormattedHeader* method), 585  
[read\\_integer\(\)](#) (*FlopBinaryData* method), 652  
[read\\_output\(\)](#) (*ZoneBudget* class method), 658  
[read\\_real\(\)](#) (*FlopBinaryData* method), 652  
[read\\_record\(\)](#) (*FlopBinaryData* method), 652  
[read\\_text\(\)](#) (*FlopBinaryData* method), 652  
[read\\_usgs\\_model\\_reference\\_file\(\)](#) (*Grid* method), 705  
[read\\_zone\\_file\(\)](#) (*ZoneBudget* class method), 659  
[ReadAsArraysException](#), 116  
[reccarray\(\)](#) (in module `flop.utils.reccarray_utils`), 627  
[reccarray2shp\(\)](#) (in module `flop.export.shapefile_utils`), 687  
[recharge](#) (*ModflowGwfrcha* attribute), 239  
[record\\_summary](#) (*budgetOpt* attribute), 559  
[references](#) (*acdd* property), 681  
[register\\_exchange\\_file\(\)](#) (*MFSimulation* method), 132  
[register\\_ims\\_package\(\)](#) (*MFSimulation* method), 132  
[register\\_model\(\)](#) (*MFSimulation* method), 132  
[register\\_package\(\)](#) (*MFModel* method), 121  
[register\\_package\(\)](#) (*MFSimulation* method), 133  
[register\\_package\(\)](#) (*PackageContainer* method), 116  
[release](#) (*LegacyVersion* property), 620  
[release](#) (*Version* property), 620  
[remove\(\)](#) (*EpsgReference* method), 686  
[remove\(\)](#) (*MFPackage* method), 127  
[remove\\_confining\\_beds\(\)](#) (*Grid* method), 705  
[remove\\_edge\\_ticks\(\)](#) (*styles* class method), 679  
[remove\\_exchange\\_file\(\)](#) (*MFSimulation* method), 133  
[remove\\_external\(\)](#) (*BaseModel* method), 378  
[remove\\_model\(\)](#) (*MFSimulation* method), 133  
[remove\\_output\(\)](#) (*BaseModel* method), 378  
[remove\\_package\(\)](#) (*BaseModel* method), 378  
[remove\\_package\(\)](#) (*MFModel* method), 121  
[remove\\_package\(\)](#) (*MFSimulation* method), 133  
[remove\\_passed\(\)](#) (*check* method), 573  
[remove\\_transient\\_key\(\)](#) (*MFTransientArray* method), 360  
[remove\\_transient\\_key\(\)](#) (*MFTransientList* method), 367  
[rename\\_all\\_packages\(\)](#) (*MFModel* method), 121

[rename\\_all\\_packages\(\)](#) (*MFSimulation* method), 133  
[rename\\_model\\_namefile\(\)](#) (*MFSimulation* method), 133  
[renumber\\_segments\(\)](#) (*ModflowSfr2* method), 479  
[repair\\_array\\_asymmetry\(\)](#) (in module `flop.utils.gridgen`), 597  
[repair\\_outsegs\(\)](#) (*ModflowSfr2* method), 479  
[replace\\_dfn\\_files\(\)](#) (in module `flop.mf6.utils.generate_classes`), 373  
[reproject\\_modpath\\_to\\_crosssection\(\)](#) (in module `flop.plot.plotutil`), 676  
[resample\\_to\\_grid\(\)](#) (*Raster* method), 625  
[reset\(\)](#) (*EpsgReference* method), 686  
[reset\(\)](#) (*StructuredSpatialReference* method), 352  
[reset\\_budgetunit\(\)](#) (*ModflowOc* method), 455  
[reset\\_delimiter\\_used\(\)](#) (*PyListUtil* static method), 581  
[reset\\_reaches\(\)](#) (*ModflowSfr2* method), 479  
[resolve\\_path\(\)](#) (*MFFileMgmt* method), 110  
[rewet\\_record](#) (*ModflowGwfnpf* attribute), 230  
[riv\\_array\\_comp\(\)](#) (*PyListUtil* method), 581  
[rotate\(\)](#) (in module `flop.utils.geometry`), 589  
[rotate\(\)](#) (*StructuredSpatialReference* static method), 352  
[rotate\(\)](#) (*VertexSpatialReference* static method), 353  
[routing\(\)](#) (*check* method), 480  
[run\\_all\(\)](#) (*check* method), 480  
[run\\_model\(\)](#) (*BaseModel* method), 378  
[run\\_model\(\)](#) (in module `flop.mbase`), 380  
[run\\_model\(\)](#) (*ZoneBudget6* method), 661  
[run\\_simulation\(\)](#) (*MFSimulation* method), 133

## S

[sample\\_point\(\)](#) (*Raster* method), 625  
[sample\\_polygon\(\)](#) (*Raster* method), 625  
[saturated\\_thick\(\)](#) (*Grid* method), 706  
[saturated\\_thickness\(\)](#) (*PlotUtilities* static method), 673  
[save\\_array\(\)](#) (*PyListUtil* method), 581  
[save\\_array\\_diff\(\)](#) (*PyListUtil* method), 581  
[saverecord](#) (*ModflowGwfoc* attribute), 234  
[saverecord](#) (*ModflowGwtoc* attribute), 308  
[sci\\_note\\_lower\\_thres](#) (*MFSimulationData* attribute), 135  
[sci\\_note\\_upper\\_thres](#) (*MFSimulationData* attribute), 135  
[search\\_data\(\)](#) (*MFList* method), 363  
[Seawat](#) (class in `flop.seawat.swt`), 541  
[SeawatList](#) (class in `flop.seawat.swt`), 543  
[SeawatVdf](#) (class in `flop.seawat.swtvdf`), 543  
[SeawatVsc](#) (class in `flop.seawat.swtvsc`), 546  
[segment\\_face\(\)](#) (in module `flop.utils.cvfdutil`), 575  
[segment\\_list](#) (*ModflowAg* property), 387  
[set\\_all\\_data\\_external\(\)](#) (*MFBBlock* method), 123

- `set_all_data_external()` (*MFModel method*), 121
- `set_all_data_external()` (*MFPackage method*), 127
- `set_all_data_external()` (*MFSimulation method*), 134
- `set_all_data_internal()` (*MFBBlock method*), 123
- `set_all_data_internal()` (*MFModel method*), 121
- `set_all_data_internal()` (*MFPackage method*), 127
- `set_all_data_internal()` (*MFSimulation method*), 134
- `set_budget_key()` (*ListBudget method*), 606
- `set_budget_key()` (*Mf6ListBudget method*), 606
- `set_budget_key()` (*MfListBudget method*), 606
- `set_budget_key()` (*MfusgListBudget method*), 606
- `set_budget_key()` (*SwrListBudget method*), 606
- `set_budget_key()` (*SwtListBudget method*), 606
- `set_coord_info()` (*Grid method*), 706
- `set_data()` (*MFArrary method*), 357
- `set_data()` (*MFList method*), 363
- `set_data()` (*MFSscalar method*), 370
- `set_data()` (*MFSscalarTransient method*), 372
- `set_data()` (*MFTransientArray method*), 360
- `set_data()` (*MFTransientList method*), 367
- `set_dtype()` (*BinaryHeader static method*), 565
- `set_float()` (*FlopyBinaryData method*), 652
- `set_fmtin()` (*Util2d method*), 645
- `set_font_type()` (*styles class method*), 680
- `set_ifrefm()` (*Modflow method*), 385
- `set_last_accessed_model_path()` (*MFFileMgmt method*), 110
- `set_last_accessed_path()` (*MFFileMgmt method*), 110
- `set_layered_data()` (*MFArrary method*), 357
- `set_model_relative_path()` (*MFBBlock method*), 123
- `set_model_relative_path()` (*MFModel method*), 121
- `set_model_relative_path()` (*MFPackage method*), 128
- `set_model_units()` (*BaseModel method*), 378
- `set_model_units()` (*Modflow method*), 385
- `set_mult()` (*ModflowPar method*), 457
- `set_ncpl()` (*UnstructuredGrid method*), 716
- `set_output_attribute()` (*BaseModel method*), 378
- `set_outreaches()` (*ModflowSfr2 method*), 479
- `set_pval()` (*ModflowPar method*), 457
- `set_sci_note_lower_thres()` (*MFSimulationData method*), 135
- `set_sci_note_upper_thres()` (*MFSimulationData method*), 136
- `set_sim_path()` (*MFFileMgmt method*), 110
- `set_sim_path()` (*MFSimulation method*), 134
- `set_spatialreference()` (*StructuredSpatialReference method*), 352
- `set_spatialreference()` (*VertexSpatialReference method*), 353
- `set_surface_interpolation()` (*Gridgen method*), 596
- `set_values()` (*BinaryHeader method*), 565
- `set_version()` (*BaseModel method*), 379
- `set_zcentergrid()` (*PlotCrossSection method*), 667
- `set_zone()` (*ModflowPar method*), 457
- `set_zpts()` (*PlotCrossSection method*), 668
- `setmodflowvars()` (*Mt3dBtn method*), 520
- `sfacrecord` (*ModflowUtlts attribute*), 335
- `sfacrecord` (*ModflowUtlts attribute*), 337
- `sfacrecord_single` (*ModflowUtlts attribute*), 337
- `SfrFile` (*class in flopy.utils.sfroutputfile*), 627
- `sgm` (*ModflowGwfcs sub attribute*), 170
- `sgs` (*ModflowGwfcs sub attribute*), 170
- `Shape` (*class in flopy.utils.geometry*), 587
- `shape` (*GeoSpatialCollection property*), 589
- `shape` (*GeoSpatialUtil property*), 590
- `shape` (*Grid property*), 706
- `shape` (*MfGrdFile property*), 346
- `shape` (*StructuredGrid property*), 711
- `shape` (*UnstructuredGrid property*), 716
- `shape` (*VertexGrid property*), 718
- `shape_attr_name()` (*in module flopy.export.shapefile\_utils*), 687
- `shapefile_extents()` (*in module flopy.plot.plotutil*), 677
- `shapefile_get_vertices()` (*in module flopy.plot.plotutil*), 677
- `shapefile_to_cvfd()` (*in module flopy.utils.cvfdutil*), 575
- `shapefile_to_patch_collection()` (*in module flopy.plot.plotutil*), 677
- `shapefile_to_xcyc()` (*in module flopy.utils.cvfdutil*), 575
- `shapely` (*GeoSpatialCollection property*), 589
- `shapely` (*GeoSpatialUtil property*), 590
- `shapetype` (*GeoSpatialCollection property*), 589
- `shapetype` (*GeoSpatialUtil property*), 590
- `shapeType` (*LineString attribute*), 586
- `shapeType` (*Point attribute*), 587
- `shapeType` (*Polygon attribute*), 587
- `shared_face()` (*in module flopy.utils.cvfdutil*), 575
- `show()` (*EpsgReference static method*), 686
- `shp2recarray()` (*in module flopy.export.shapefile\_utils*), 688
- `sim` (*Modpath6 property*), 562
- `sim_enum_error()` (*in module flopy.modpath.mp7sim*), 559
- `sim_level` (*PackageLevel attribute*), 372
- `sim_name` (*MFSimulation attribute*), 129
- `sim_package_list` (*MFSimulation property*), 134
- `simple_flag` (*OptionBlock attribute*), 619
- `simple_float` (*OptionBlock attribute*), 619
- `simple_int` (*OptionBlock attribute*), 619



- simple\_str (*OptionBlock* attribute), 619  
 simple\_tabfile (*OptionBlock* attribute), 619  
 simType (class in *flopy.modpath.mp7sim*), 559  
 simulation (*PackageContainerType* attribute), 116  
 SimulationDict (class in *flopy.mf6.modflow.mfsimulation*), 136  
 single\_line\_options (*OptionBlock* property), 619  
 skipcomments() (in module *flopy.modflow.mfmmw1*), 436  
 slope() (check method), 480  
 solutiongroup (*ModflowNam* attribute), 151  
 solver\_packages (check attribute), 574  
 solver\_tols (*MfModel* property), 122  
 solver\_tols (*ModelInterface* property), 380  
 solver\_tols (*Modflow* property), 385  
 solver\_tols (*Mt3dms* property), 513  
 sort\_gridshapes() (*GridIntersect* static method), 599  
 sort\_node\_data() (*Mnw* static method), 442  
 sort\_tuple() (in module *flopy.utils.zonbud*), 662  
 sort\_vertices() (in module *flopy.utils.voronoi*), 655  
 sources (*ModflowGwtssm* attribute), 318  
 sp2 (*ModflowGwtmst* attribute), 298  
 SpatialReference (class in *flopy.mf6.utils.reference*), 350  
 specified (*stopOpt* attribute), 560  
 split\_data\_line() (*PyListUtil* static method), 581  
 sr (*Mt3dms* property), 513  
 ss (*ModflowGwfsto* attribute), 254  
 SsmPackage (class in *flopy.mt3d.mtssm*), 538  
 stage\_filerecord (*ModflowGwflak* attribute), 212  
 stage\_filerecord (*ModflowGwfsfr* attribute), 252  
 start\_datetime (*ModelTime* property), 707  
 StartingLocationsFile (class in *flopy.modpath.mp6sim*), 564  
 steady\_state (*ModelTime* property), 707  
 stop\_at (*weakOpt* attribute), 560  
 stopOpt (class in *flopy.modpath.mp7sim*), 559  
 store\_as\_external\_file() (*MfArray* method), 357  
 store\_as\_external\_file() (*MfList* method), 364  
 store\_as\_external\_file() (*MfTransientArray* method), 360  
 store\_as\_external\_file() (*MfTransientList* method), 368  
 store\_internal() (*MfArray* method), 358  
 store\_internal() (*MfList* method), 364  
 store\_internal() (*MfTransientArray* method), 361  
 store\_internal() (*MfTransientList* method), 368  
 straincg\_filerecord (*ModflowGwfcsb* attribute), 170  
 strainib\_filerecord (*ModflowGwfcsb* attribute), 170  
 stress\_period\_data (*ModflowGwfchd* attribute), 162  
 stress\_period\_data (*ModflowGwfcsb* attribute), 170  
 stress\_period\_data (*ModflowGwfdm* attribute), 182  
 stress\_period\_data (*ModflowGwfevt* attribute), 186  
 stress\_period\_data (*ModflowGwfgfb* attribute), 192  
 stress\_period\_data (*ModflowGwfhfb* attribute), 202  
 stress\_period\_data (*ModflowGwfrch* attribute), 236  
 stress\_period\_data (*ModflowGwfriv* attribute), 242  
 stress\_period\_data (*ModflowGwfwel* attribute), 264  
 stress\_period\_data (*ModflowGwtcnc* attribute), 269  
 stress\_period\_data (*ModflowGwtsrc* attribute), 316  
 stress\_period\_data\_values() (check method), 574  
 string (*Util2d* property), 645  
 string\_to\_file\_path() (*MfFileMgmt* static method), 111  
 strip\_model\_relative\_path() (*MfFileMgmt* method), 111  
 strt (*ModflowGwfic* attribute), 202  
 strt (*ModflowGwtic* attribute), 287  
 StructException, 116  
 structure (*MfBlock* attribute), 122  
 structure (*MfPackage* attribute), 125  
 StructuredGrid (class in *flopy.discretization.structuredgrid*), 707  
 StructuredSpatialReference (class in *flopy.mf6.utils.reference*), 350  
 styles (class in *flopy.plot.styles*), 678  
 sum() (*Util2d* method), 645  
 sum\_flux\_tuples() (in module *flopy.utils.zonbud*), 662  
 summarize() (check method), 574  
 summary (*budgetOpt* attribute), 559  
 supports\_layered() (*MfArray* method), 358  
 surface (*ModflowGwfevt* attribute), 189  
 SwiConcentration (class in *flopy.plot.plotutil*), 673  
 SwrBudget (class in *flopy.utils.swroutputfile*), 629  
 SwrExchange (class in *flopy.utils.swroutputfile*), 629  
 SwrFile (class in *flopy.utils.swroutputfile*), 629  
 SwrFlow (class in *flopy.utils.swroutputfile*), 631  
 SwrListBudget (class in *flopy.utils.mflistfile*), 606  
 SwrObs (class in *flopy.utils.observationfile*), 617  
 SwrStage (class in *flopy.utils.swroutputfile*), 632  
 SwrStructure (class in *flopy.utils.swroutputfile*), 632  
 SwtListBudget (class in *flopy.utils.mflistfile*), 606  
 sy (*ModflowGwfsto* attribute), 254
- ## T
- table (*ModflowUtlaktab* attribute), 327  
 table (*ModflowUtlstftab* attribute), 330  
 tables (*ModflowGwflak* attribute), 212  
 tas\_array (*ModflowUtlas* attribute), 335  
 tas\_filerecord (*ModflowGwfevt* attribute), 189  
 tas\_filerecord (*ModflowGwfrcha* attribute), 239  
 tas\_filerecord (*ModflowUtlspca* attribute), 334  
 TemplateWriter (class in *flopy.pest.templatewriter*), 700  
 TemporalReference (class in *flopy.utils.reference*), 627  
 thetaim (*ModflowGwtist* attribute), 290

- thick (*Grid* property), 706
  - thin\_cell\_threshold (*check* attribute), 574
  - time\_const (*ModflowSfr2* attribute), 479
  - time\_coverage (*acdd* property), 681
  - time\_series\_namerecord (*ModflowUtlts* attribute), 335
  - time\_series\_namerecord (*ModflowUtlts* attribute), 337
  - time\_units (*ModelTime* property), 707
  - timeseries (*ModflowUtlts* attribute), 337
  - timeseries (*simType* attribute), 559
  - TimeseriesFile (*class* in *flop.py.utils.modpathfile*), 612
  - to\_array() (*MFList* method), 364
  - to\_array() (*MfList* method), 651
  - to\_array() (*MFTransientList* method), 368
  - to\_csv() (*ZoneBudget* method), 659
  - to\_cvfd() (*in* module *flop.py.utils.cvfdutil*), 575
  - to\_dict() (*EpsgReference* method), 686
  - to\_shapefile() (*BaseModel* method), 379
  - to\_shapefile() (*LayerFile* method), 578
  - to\_shapefile() (*MfList* method), 651
  - to\_shapefile() (*Package* method), 382
  - top (*Grid* attribute), 702
  - top (*Grid* property), 706
  - top (*MfGrdFile* property), 346
  - top (*ModflowGwfdis* attribute), 172
  - top (*ModflowGwfdisu* attribute), 176
  - top (*ModflowGwfdisv* attribute), 179
  - top (*ModflowGwtdis* attribute), 271
  - top (*ModflowGwtdisu* attribute), 276
  - top (*ModflowGwtdisv* attribute), 279
  - top\_botm (*Grid* property), 706
  - top\_botm (*StructuredGrid* property), 711
  - top\_botm (*UnstructuredGrid* property), 716
  - top\_botm (*VertexGrid* property), 718
  - top\_botm\_withnan (*StructuredGrid* property), 711
  - total (*stopOpt* attribute), 560
  - totim (*ModelTime* property), 707
  - totim\_to\_datetime() (*in* module *flop.py.utils.utils\_def*), 653
  - trackDir (*class* in *flop.py.modpath.mp7sim*), 560
  - transform() (*in* module *flop.py.utils.geometry*), 589
  - Transient2d (*class* in *flop.py.utils.util\_array*), 637
  - transient2d\_export() (*in* module *flop.py.export.utils*), 693
  - Transient2dTpl (*class* in *flop.py.pest.tplarray*), 700
  - Transient3d (*class* in *flop.py.utils.util\_array*), 640
  - transient\_2ds (*Transient2d* attribute), 638
  - transient\_3ds (*Transient3d* attribute), 640
  - tri2vor() (*in* module *flop.py.utils.voronoi*), 655
  - Triangle (*class* in *flop.py.utils.triangle*), 633
  - try\_float() (*in* module *flop.py.mf6.utils.mfobservation*), 348
  - ts\_filerecord (*ModflowGwfchd* attribute), 162
  - ts\_filerecord (*ModflowGwfcsb* attribute), 170
  - ts\_filerecord (*ModflowGwfdrn* attribute), 183
  - ts\_filerecord (*ModflowGwfevt* attribute), 186
  - ts\_filerecord (*ModflowGwfgbh* attribute), 192
  - ts\_filerecord (*ModflowGwflak* attribute), 212
  - ts\_filerecord (*ModflowGwfmaw* attribute), 221
  - ts\_filerecord (*ModflowGwfrch* attribute), 236
  - ts\_filerecord (*ModflowGwfriv* attribute), 242
  - ts\_filerecord (*ModflowGwfsfr* attribute), 252
  - ts\_filerecord (*ModflowGwfufz* attribute), 261
  - ts\_filerecord (*ModflowGwfwel* attribute), 264
  - ts\_filerecord (*ModflowGwtcnc* attribute), 269
  - ts\_filerecord (*ModflowGwtlkt* attribute), 296
  - ts\_filerecord (*ModflowGwtmwt* attribute), 304
  - ts\_filerecord (*ModflowGwtsft* attribute), 314
  - ts\_filerecord (*ModflowGwtsrc* attribute), 316
  - ts\_filerecord (*ModflowGwtuzt* attribute), 324
  - ts\_filerecord (*ModflowUtlspc* attribute), 332
  - ts\_filerecord (*ModflowUtltkv* attribute), 340
  - ts\_filerecord (*ModflowUtltsv* attribute), 342
  - tslen (*ModelTime* property), 707
  - tsmult (*ModelTime* property), 707
  - tvk\_filerecord (*ModflowGwfnpf* attribute), 231
  - tvsv\_filerecord (*ModflowGwfsto* attribute), 254
  - type (*LineString* attribute), 586
  - type (*Point* attribute), 587
  - type (*Polygon* attribute), 587
  - type\_from\_iterable() (*in* module *flop.py.utils.utils\_def*), 653
- ## U
- UcnFile (*class* in *flop.py.utils.binaryfile*), 571
  - ulstrd() (*in* module *flop.py.utils.flop\_io*), 583
  - unique() (*Util2d* method), 645
  - unique\_file\_name() (*MFFileMgmt* static method), 111
  - unitnumber (*Mt3dGcg* attribute), 526
  - unitnumber (*Mt3dPhc* attribute), 528
  - unitnumber (*SeawatVdf* attribute), 546
  - unitnumber (*SeawatVsc* attribute), 548
  - units (*Grid* property), 706
  - UnstructuredGrid (*class* in *flop.py.discretization.unstructuredgrid*), 712
  - UnstructuredPlotUtilities (*class* in *flop.py.plot.plotutil*), 674
  - update\_data() (*CachedData* method), 701
  - update\_from\_package() (*OptionBlock* method), 619
  - update\_modelgrid() (*ModelInterface* method), 380
  - update\_package\_filename() (*MFModel* method), 122
  - update\_package\_filename() (*MFSimulation* method), 134
  - update\_record() (*MFList* method), 364
  - update\_record() (*MFTransientList* method), 368



USGSMap() (*styles class method*), 678  
 USGSPlot() (*styles class method*), 678  
 Util2d (*class in flopy.utils.util\_array*), 641  
 Util2dTpl (*class in flopy.pest.tplarray*), 700  
 Util3d (*class in flopy.utils.util\_array*), 645  
 Util3dTpl (*class in flopy.pest.tplarray*), 701  
 UtlatsPackages (*class in flopy.mf6.modflow.mfutlats*), 325  
 UtlaktabPackages (*class in flopy.mf6.modflow.mfutlaktab*), 327  
 UtllobsPackages (*class in flopy.mf6.modflow.mfutllobs*), 329  
 UtlsfrtabPackages (*class in flopy.mf6.modflow.mfutlsfrtab*), 330  
 UtlspcaPackages (*class in flopy.mf6.modflow.mfutlspca*), 334  
 UtlspcPackages (*class in flopy.mf6.modflow.mfutlspc*), 332  
 UtltsPackages (*class in flopy.mf6.modflow.mfutlts*), 335  
 UtltsPackages (*class in flopy.mf6.modflow.mfutlts*), 338  
 UtltvkPackages (*class in flopy.mf6.modflow.mfutltvk*), 340  
 Utltvspackages (*class in flopy.mf6.modflow.mfutltvs*), 342  
 uzgag (*ModflowUzf1 property*), 507  
 uztperioddata (*ModflowGwtuzt attribute*), 324

## V

values() (*check method*), 574  
 variable\_strings (*MFBBlockHeader attribute*), 124  
 vars (*OptionBlock attribute*), 619  
 verbose (*BaseModel property*), 379  
 verbose (*MFMModel property*), 122  
 verbose (*ModelInterface property*), 380  
 verbose (*VerbosityLevel attribute*), 116  
 VerbosityLevel (*class in flopy.mf6.mfbase*), 116  
 version (*BaseModel property*), 379  
 Version (*class in flopy.utils.parse\_version*), 620  
 version (*MFMModel property*), 122  
 version (*ModelInterface property*), 380  
 VertexGrid (*class in flopy.discretization.vertexgrid*), 716  
 VertexSpatialReference (*class in flopy.mf6.utils.reference*), 352  
 vertical\_datum (*acdd property*), 681  
 vertices (*ModflowGwfdisu attribute*), 176  
 vertices (*ModflowGwfdisv attribute*), 179  
 vertices (*ModflowGwtdisu attribute*), 276  
 vertices (*ModflowGwtdisv attribute*), 279  
 verts (*Grid property*), 706  
 verts (*MfGrdFile property*), 346  
 verts (*StructuredGrid property*), 711  
 verts (*UnstructuredGrid property*), 716

verts (*VertexGrid property*), 718  
 view\_summary\_array\_fields() (*check method*), 574  
 VoronoiGrid (*class in flopy.utils.voronoi*), 654  
 Vtk (*class in flopy.export.vtk*), 693  
 vtype (*MfList property*), 651  
 vtype (*Util2d property*), 645

## W

warn() (*Logger method*), 682  
 wc\_filerecord (*ModflowGwfufz attribute*), 261  
 weakOpt (*class in flopy.modpath.mp7sim*), 560  
 webdoc() (*Package method*), 382  
 wetdry (*ModflowGwfnpf attribute*), 231  
 width (*ArrayFormat attribute*), 636  
 width (*ArrayFormat property*), 637  
 wrap\_multidim\_arrays (*MFSimulationData attribute*), 135  
 write() (*CellDataType method*), 552  
 write() (*FaceDataType method*), 553  
 write() (*LRCParticleData method*), 553  
 write() (*MFBBlock method*), 124  
 write() (*MFMModel method*), 122  
 write() (*MFPackage method*), 128  
 write() (*NetCdf method*), 685  
 write() (*NodeParticleData method*), 554  
 write() (*ParticleData method*), 555  
 write() (*ParticleGroup method*), 556  
 write() (*ParticleGroupLRCTemplate method*), 556  
 write() (*ParticleGroupNodeTemplate method*), 557  
 write() (*Pvd method*), 693  
 write() (*Raster method*), 626  
 write() (*Vtk method*), 695  
 write\_bin() (*Util2d static method*), 645  
 write\_file() (*mfaddoutsidefile method*), 385  
 write\_file() (*ModflowAg method*), 387  
 write\_file() (*ModflowBas method*), 389  
 write\_file() (*ModflowBcf method*), 391  
 write\_file() (*ModflowBct method*), 391  
 write\_file() (*ModflowChd method*), 394  
 write\_file() (*ModflowDe4 method*), 396  
 write\_file() (*ModflowDis method*), 400  
 write\_file() (*ModflowDrn method*), 403  
 write\_file() (*ModflowDrt method*), 405  
 write\_file() (*ModflowEvt method*), 406  
 write\_file() (*ModflowFhb method*), 409  
 write\_file() (*ModflowFlwob method*), 411  
 write\_file() (*ModflowGage method*), 413  
 write\_file() (*ModflowGhb method*), 415  
 write\_file() (*ModflowGlobal method*), 385  
 write\_file() (*ModflowGmg method*), 418  
 write\_file() (*ModflowHfb method*), 420  
 write\_file() (*ModflowHob method*), 422  
 write\_file() (*ModflowHyd method*), 424  
 write\_file() (*ModflowLak method*), 429

[write\\_file\(\)](#) (*ModflowList method*), 385  
[write\\_file\(\)](#) (*ModflowLmt method*), 430  
[write\\_file\(\)](#) (*ModflowLpf method*), 433  
[write\\_file\(\)](#) (*ModflowMlt method*), 434  
[write\\_file\(\)](#) (*ModflowMnw1 method*), 436  
[write\\_file\(\)](#) (*ModflowMnw2 method*), 446  
[write\\_file\(\)](#) (*ModflowMnwi method*), 447  
[write\\_file\(\)](#) (*ModflowNwt method*), 451  
[write\\_file\(\)](#) (*ModflowOc method*), 455  
[write\\_file\(\)](#) (*ModflowPbc method*), 459  
[write\\_file\(\)](#) (*ModflowPcg method*), 461  
[write\\_file\(\)](#) (*ModflowPcgn method*), 464  
[write\\_file\(\)](#) (*ModflowPks method*), 466  
[write\\_file\(\)](#) (*ModflowPval method*), 467  
[write\\_file\(\)](#) (*ModflowRch method*), 470  
[write\\_file\(\)](#) (*ModflowRiv method*), 472  
[write\\_file\(\)](#) (*ModflowSfr2 method*), 479  
[write\\_file\(\)](#) (*ModflowSip method*), 482  
[write\\_file\(\)](#) (*ModflowSor method*), 484  
[write\\_file\(\)](#) (*ModflowStr method*), 488  
[write\\_file\(\)](#) (*ModflowSub method*), 491  
[write\\_file\(\)](#) (*ModflowSwi2 method*), 494  
[write\\_file\(\)](#) (*ModflowSwr1 method*), 496  
[write\\_file\(\)](#) (*ModflowSwt method*), 500  
[write\\_file\(\)](#) (*ModflowUpw method*), 502  
[write\\_file\(\)](#) (*ModflowUzf1 method*), 507  
[write\\_file\(\)](#) (*ModflowWel method*), 510  
[write\\_file\(\)](#) (*ModflowZon method*), 511  
[write\\_file\(\)](#) (*Modpath6Bas method*), 563  
[write\\_file\(\)](#) (*Modpath6List method*), 562  
[write\\_file\(\)](#) (*Modpath6Sim method*), 564  
[write\\_file\(\)](#) (*Modpath7Bas method*), 551  
[write\\_file\(\)](#) (*Modpath7List method*), 550  
[write\\_file\(\)](#) (*Modpath7Sim method*), 559  
[write\\_file\(\)](#) (*Mt3dAdv method*), 516  
[write\\_file\(\)](#) (*Mt3dBtm method*), 520  
[write\\_file\(\)](#) (*Mt3dDsp method*), 524  
[write\\_file\(\)](#) (*Mt3dGcg method*), 526  
[write\\_file\(\)](#) (*Mt3dList method*), 511  
[write\\_file\(\)](#) (*Mt3dLkt method*), 528  
[write\\_file\(\)](#) (*Mt3dPhc method*), 528  
[write\\_file\(\)](#) (*Mt3dRct method*), 531  
[write\\_file\(\)](#) (*Mt3dSft method*), 535  
[write\\_file\(\)](#) (*Mt3dSsm method*), 538  
[write\\_file\(\)](#) (*Mt3dTob method*), 538  
[write\\_file\(\)](#) (*Mt3dUzt method*), 541  
[write\\_file\(\)](#) (*Package method*), 382  
[write\\_file\(\)](#) (*SeawatList method*), 543  
[write\\_file\(\)](#) (*SeawatVdf method*), 546  
[write\\_file\(\)](#) (*SeawatVsc method*), 548  
[write\\_file\(\)](#) (*StartingLocationsFile method*), 564  
[write\\_fixed\\_var\(\)](#) (in module *flop.utils.flop\_io*), 583  
[write\\_footer\(\)](#) (*MFBBlockHeader method*), 124

[write\\_grid\\_shapefile\(\)](#) (in module *flop.export.shapefile\_utils*), 688  
[write\\_gridlines\\_shapefile\(\)](#) (in module *flop.export.shapefile\_utils*), 688  
[write\\_gridSpec\(\)](#) (*StructuredSpatialReference method*), 352  
[write\\_header\(\)](#) (*MFBBlockHeader method*), 124  
[write\\_headers](#) (*MFSimulationData attribute*), 135  
[write\\_input\(\)](#) (*BaseModel method*), 379  
[write\\_input\(\)](#) (*ZoneBudget6 method*), 661  
[write\\_input\(\)](#) (*ZoneFile6 method*), 662  
[write\\_name\\_file\(\)](#) (*BaseModel method*), 379  
[write\\_name\\_file\(\)](#) (*Modflow method*), 385  
[write\\_name\\_file\(\)](#) (*Modpath6 method*), 562  
[write\\_name\\_file\(\)](#) (*Modpath7 method*), 550  
[write\\_name\\_file\(\)](#) (*Mt3dms method*), 514  
[write\\_name\\_file\(\)](#) (*Seawat method*), 543  
[write\\_options\(\)](#) (*OptionBlock method*), 619  
[write\\_prj\(\)](#) (in module *flop.export.shapefile\_utils*), 688  
[write\\_shapefile\(\)](#) (*EndpointFile method*), 609  
[write\\_shapefile\(\)](#) (*Grid method*), 706  
[write\\_shapefile\(\)](#) (*PathlineFile method*), 612  
[write\\_shapefile\(\)](#) (*TimeseriesFile method*), 614  
[write\\_simulation\(\)](#) (*MFSimulation method*), 134  
[write\\_template\(\)](#) (*TemplateWriter method*), 700  
[write\\_transient\(\)](#) (*MfList method*), 651  
[write\\_txt\(\)](#) (*Util2d static method*), 645  
[write\\_zone\\_file\(\)](#) (*ZoneBudget class method*), 659

## X

[x](#) (*LineString property*), 586  
[x](#) (*Point property*), 587  
[xarr](#) (*VertexSpatialReference property*), 354  
[xccllcenters](#) (*Grid property*), 706  
[xcenter](#) (*StructuredSpatialReference attribute*), 351  
[xcenter](#) (*StructuredSpatialReference property*), 352  
[xcenter](#) (*VertexSpatialReference attribute*), 353  
[xcenter\\_array](#) (*VertexSpatialReference property*), 354  
[xcentergrid](#) (*StructuredSpatialReference attribute*), 351  
[xcentergrid](#) (*StructuredSpatialReference property*), 352  
[xcentergrid](#) (*VertexSpatialReference attribute*), 353  
[xcnters](#) (*Grid attribute*), 703  
[xcnters](#) (*Raster property*), 626  
[xdict](#) (*VertexSpatialReference property*), 354  
[xedge](#) (*StructuredSpatialReference attribute*), 350  
[xedge](#) (*StructuredSpatialReference property*), 352  
[xedge](#) (*VertexSpatialReference attribute*), 353  
[xgrid](#) (*Grid attribute*), 702  
[xgrid](#) (*StructuredSpatialReference attribute*), 350  
[xgrid](#) (*StructuredSpatialReference property*), 352  
[xgrid](#) (*VertexSpatialReference attribute*), 353

xlabel() (*styles class method*), 680  
 xmlfile (*acdd property*), 682  
 xmlroot (*acdd property*), 682  
 xoffset (*Grid attribute*), 702  
 xoffset (*Grid property*), 706  
 xorigin (*MfGrdFile property*), 347  
 xvertices (*Grid property*), 706  
 xycenters (*StructuredGrid property*), 711  
 xydict (*VertexSpatialReference property*), 354  
 xyedges (*StructuredGrid property*), 711  
 xyzcellcenters (*Grid attribute*), 703  
 xyzcellcenters (*Grid property*), 706  
 xyzcellcenters (*StructuredGrid property*), 711  
 xyzcellcenters (*UnstructuredGrid property*), 716  
 xyzcellcenters (*VertexGrid property*), 718  
 xyzextent (*Grid property*), 706  
 xyzgrid (*Grid attribute*), 703  
 xyzvertices (*Grid property*), 706  
 xyzvertices (*StructuredGrid property*), 711  
 xyzvertices (*UnstructuredGrid property*), 716  
 xyzvertices (*VertexGrid property*), 718  
 z (*Point property*), 587  
 ZBNetOutput (*class in flopY.utils.zonbud*), 656  
 zcellcenters (*Grid property*), 706  
 zcentroids (*ModflowDis property*), 400  
 zdisplacement\_filerecord (*ModflowGwfcs sub attribute*), 170  
 zedges (*StructuredGrid property*), 711  
 zeros\_like() (*NetCdf class method*), 685  
 zetaim (*ModflowGwtist attribute*), 290  
 zgrid (*Grid attribute*), 703  
 zonearray2params() (*in module flopY.pest.params*), 700  
 ZoneBudget (*class in flopY.utils.zonbud*), 656  
 ZoneBudget6 (*class in flopY.utils.zonbud*), 659  
 ZoneFile6 (*class in flopY.utils.zonbud*), 661  
 zvertices (*Grid property*), 706  
 zverts\_smooth (*StructuredGrid property*), 711

## Y

y (*LineString property*), 586  
 y (*Point property*), 587  
 yarr (*VertexSpatialReference property*), 354  
 ycellcenters (*Grid property*), 706  
 ycenter (*StructuredSpatialReference attribute*), 351  
 ycenter (*StructuredSpatialReference property*), 352  
 ycenter (*VertexSpatialReference attribute*), 353  
 ycenter\_array (*VertexSpatialReference property*), 354  
 ycentergrid (*StructuredSpatialReference attribute*), 351  
 ycentergrid (*StructuredSpatialReference property*), 352  
 ycentergrid (*VertexSpatialReference attribute*), 353  
 ycenters (*Grid attribute*), 703  
 ycenters (*Raster property*), 626  
 ydict (*VertexSpatialReference property*), 354  
 yedge (*StructuredSpatialReference attribute*), 350  
 yedge (*StructuredSpatialReference property*), 352  
 yedge (*VertexSpatialReference attribute*), 353  
 ygrid (*Grid attribute*), 702  
 ygrid (*StructuredSpatialReference attribute*), 351  
 ygrid (*StructuredSpatialReference property*), 352  
 ygrid (*VertexSpatialReference attribute*), 353  
 ylabel() (*styles class method*), 680  
 yoffset (*Grid attribute*), 702  
 yoffset (*Grid property*), 706  
 yorigin (*MfGrdFile property*), 347  
 yvertices (*Grid property*), 706

## Z

z (*LineString property*), 586